

FCC RF Test Report

APPLICANT : VERTU Corporation Limited
EQUIPMENT : GSM Quad-band / UMTS Quad-band /CDMA
Single-band/WIFI/BT mobile phone
BRAND NAME : VERTU
MODEL NAME : SIGNATURE S
TYPE : VM-06
FCC ID : P7QVM-06
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DSS) Spread Spectrum Transmitter

The product was received on Jun. 03, 2016 and testing was completed on Sep. 23, 2016. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.



Reviewed by: Joseph Lin / Supervisor



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test	5
1.4 Product Specification of Equipment Under Test	6
1.5 Modification of EUT	6
1.6 Testing Location	6
1.7 Applicable Standards	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1 Descriptions of Test Mode	8
2.2 Test Mode	9
2.3 Connection Diagram of Test System	10
2.4 Support Unit used in test configuration and system	11
2.5 EUT Operation Test Setup	11
2.6 Measurement Results Explanation Example	12
3 TEST RESULT	13
3.1 Number of Channel Measurement	13
3.2 Hopping Channel Separation Measurement	15
3.3 Dwell Time Measurement	22
3.4 20dB and 99% Bandwidth Measurement	25
3.5 Peak Output Power Measurement	38
3.6 Conducted Band Edges Measurement	40
3.7 Conducted Spurious Emission Measurement	47
3.8 Radiated Band Edges and Spurious Emission Measurement	57
3.9 AC Conducted Emission Measurement	65
3.10 Antenna Requirements	69
4 LIST OF MEASURING EQUIPMENT	70
5 UNCERTAINTY OF EVALUATION	71
APPENDIX A. RADIATED TEST RESULTS	
APPENDIX B. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR660304A	Rev. 01	Initial issue of report	Dec. 01, 2016

SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(1)	RSS-247 5.1(4)	Number of Channels	$\geq 15\text{Chs}$	Pass	-
3.2	15.247(a)(1)	RSS-247 5.1(2)	Hopping Channel Separation	$\geq 2/3$ of 20dB BW	Pass	-
3.3	15.247(a)(1)	RSS-247 5.1(4)	Dwell Time of Each Channel	$\leq 0.4\text{sec}$ in 31.6sec period	Pass	-
3.4	15.247(a)(1)	RSS-247 5.1(1)	20dB Bandwidth	NA	Pass	-
3.4	-	RSS-Gen 6.6	99% Bandwidth	-	Pass	-
3.5	15.247(b)(1)	RSS-247 5.4(2)	Peak Output Power	$\leq 125\text{ mW}$	Pass	-
3.6	15.247(d)	RSS-247 5.5	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
3.7	15.247(d)	RSS-247 5.5	Conducted Spurious Emission	$\leq 20\text{dBc}$	Pass	-
3.8	15.247(d)	RSS-247 5.5	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 5.44 dB at 46.200 MHz for Quasi-peak
3.9	15.207	RSS-Gen 8.8	AC Conducted Emission	15.207(a)	Pass	Under limit 21.70 dB at 0.150 MHz
3.10	15.203 & 15.247(b)	N/A	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

VERTU Corporation Limited

Beacon Hill Road, Church Crookham, Hampshire GU52 8DY, United Kingdom.

1.2 Manufacturer

VERTU Corporation Limited

Beacon Hill Road, Church Crookham, Hampshire GU52 8DY, United Kingdom.

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	GSM Quad-band / UMTS Quad-band /CDMA Single-band/WIFI/BT mobile phone
Brand Name	VERTU
Model Name	SIGNATURE S
Type	VM-06
FCC ID	P7QVM-06
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/DC-HSDPA/HSPA+ (16QAM uplink is not supported)/ CDMA/EV-DO WLAN 2.4GHz 802.11b/g/n HT20 Bluetooth v3.0 + EDR/Bluetooth v4.1 LE
IMEI Code	Conducted: 004402550074607 Radiation: Sample 1:004402550074623 Sample 2:004402550074714 Conduction: 004402550074722
HW Version	LOT0
SW Version	5.1.1_0.500.0.100
EUT Stage	Identical Prototype

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are two types of EUT sample 1 and sample 2, the differences between two samples are only for Gain and shape of 2.4GHz Antenna and the material of shell parts, sample 1 with cortical shell and sample 2 with ceramic shell. After pre-scan two types of EUT, we only chose the sample 1 to perform all tests and sample 2 only verified the worse of Sample 1..

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	79
Carrier Frequency of Each Channel	2402+n*1 MHz; n=0~78
Maximum Output Power to Antenna	Bluetooth BR(1Mbps) : 11.14 dBm (0.0130 W) Bluetooth EDR (2Mbps) : 11.96 dBm (0.0157 W) Bluetooth EDR (3Mbps) : 12.39 dBm (0.0173 W)
99% Occupied Bandwidth	Bluetooth BR(1Mbps) : 0.892MHz Bluetooth EDR (2Mbps) : 1.168MHz Bluetooth EDR (3Mbps) : 1.156MHz
Antenna Type / Gain	Sample 1: PIFA Antenna with gain -3.9 dBi Sample 2: PIFA Antenna with gain -6.0 dBi
Type of Modulation	Bluetooth BR (1Mbps) : GFSK Bluetooth EDR (2Mbps) : $\pi/4$ -DQPSK Bluetooth EDR (3Mbps) : 8-DPSK

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No.	
	TH02-HY	CO05-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-3273456 FAX: +886-3-3284978	
Test Site No.	Sporton Site No.	FCC/IC Registration No.
	03CH12-HY	380227/4086H-3

Note: The test site complies with ANSI C63.4 2014 requirement.



1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Descriptions of Test Mode

Preliminary tests were performed in different data rates and recorded the RF output power in the following table:

Channel	Frequency	Bluetooth RF Output Power		
		Data Rate / Modulation		
		GFSK	$\pi/4$ -DQPSK	8-DPSK
		1Mbps	2Mbps	3Mbps
Ch00	2402MHz	11.14 dBm	11.96 dBm	12.39 dBm
Ch39	2441MHz	11.10 dBm	11.85 dBm	12.38 dBm
Ch78	2480MHz	10.98 dBm	11.77 dBm	12.26 dBm

Remark:

1. All the test data for each data rate were verified, but only the worst case was reported.
 2. The data rate was set in 3Mbps for all the test items due to the highest RF output power.
- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). Pre-scanned tests, X, Y, Z in three orthogonal panels, and different data rates were conducted to determine the final configuration (Z plane as worst plane for Sample 1, and Y plane as worst plane for Sample 2) from all possible combinations, and the worst mode of radiated spurious emissions is Bluetooth 3Mbps mode, and recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.


2.2 Test Mode

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases			
Test Item	Data Rate / Modulation		
	Bluetooth BR 1Mbps GFSK	Bluetooth EDR 2Mbps π /4-DQPSK	Bluetooth EDR 3Mbps 8-DPSK
Conducted Test Cases	Mode 1: CH00_2402 MHz	Mode 4: CH00_2402 MHz	Mode 7: CH00_2402 MHz
	Mode 2: CH39_2441 MHz	Mode 5: CH39_2441 MHz	Mode 8: CH39_2441 MHz
	Mode 3: CH78_2480 MHz	Mode 6: CH78_2480 MHz	Mode 9: CH78_2480 MHz
Radiated Test Cases	Bluetooth EDR 3Mbps 8-DPSK		
	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz		
AC Conducted Emission	Mode 1 :GSM850 Idle + Bluetooth Link + WLAN Link + USB Cable (Charging from Adapter)		
Remark:			
1. For radiated test cases, the worst mode data rate 3Mbps was reported only, because this data rate has the highest RF output power at preliminary tests, and the conducted spurious emissions and conducted band edge measurement for each data rate are no worse than 3Mbps, and no other significantly frequencies found in conducted spurious emission.			
2. For radiated test cases, the tests were performance with Adapter , and USB Cable .			
3. For radiated test cases, Sample 1 was for full test and Sample 2 only verified the worst case of Sample 1.			

2.3 Connection Diagram of Test System

<Bluetooth Tx Mode>



<AC Conducted Emission Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritus	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	Bluetooth Base Station	R&S	CBT32	N/A	N/A	Unshielded, 1.8 m
3.	Bluetooth Speaker	VERTU	SP-1V	P7Q-SP1V	N/A	N/A
4.	WLAN AP	D-Link	DIR-628	KA2DIR628A2	N/A	Unshielded, 1.8 m
5.	Notebook	DELL	Latitude E6320	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m

2.5 EUT Operation Test Setup

For Bluetooth test items, an engineering test program was provided and enabled to make EUT contact with Bluetooth base station for continuous transmitting and receiving signals.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.



2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 3.8 dB and 20dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 3.8 + 20 = 23.8(\text{dB})\end{aligned}$$

3 Test Result

3.1 Number of Channel Measurement

3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation;
RBW = 300kHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.

3.1.4 Test Setup




3.1.5 Test Result of Number of Hopping Frequency


Test Mode :	3Mbps	Temperature :	21~25°C
Test Engineer :	AC Chang	Relative Humidity :	50~54%
Number of Hopping (Channel)	Adaptive Frequency Hopping (Channel)	Limits (Channel)	Pass/Fail
79	20	> 15	Pass



Number of Hopping Channel Plot on Channel 00 - 78



Date: 20.SEP.2016 11:05:51



Date: 20.SEP.2016 11:06:42

3.2 Hopping Channel Separation Measurement

3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.2.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels;
RBW = 300kHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.


3.2.4 Test Setup



**3.2.5 Test Result of Hopping Channel Separation**

Test Mode :	1Mbps	Temperature :	21~25°C
Test Engineer :	AC Chang	Relative Humidity :	50~54%


Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.008	0.6627	Pass
39	2441	1.008	0.6213	Pass
78	2480	1.014	0.6213	Pass

Channel Separation Plot on Channel 00 - 01

Date: 20.SEP.2016 10:36:07




Channel Separation Plot on Channel 39 - 40



Date: 20.SEP.2016 10:39:03

Channel Separation Plot on Channel 77 - 78




Date: 20.SEP.2016 10:41:43



Test Mode :	2Mbps	Temperature :	21~25°C
Test Engineer :	AC Chang	Relative Humidity :	50~54%


Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.002	0.8373	Pass
39	2441	1.002	0.8400	Pass
78	2480	1.002	0.8400	Pass

Channel Separation Plot on Channel 00 - 01

Date: 20.SEP.2016 10:45:15




Channel Separation Plot on Channel 39 - 40



Date: 20.SEP.2016 10:49:11

Channel Separation Plot on Channel 77 - 78




Date: 20.SEP.2016 10:51:52



Test Mode :	3Mbps	Temperature :	21~25°C
Test Engineer :	AC Chang	Relative Humidity :	50~54%


Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.002	0.8213	Pass
39	2441	1.002	0.8213	Pass
78	2480	1.008	0.8187	Pass

Channel Separation Plot on Channel 00 - 01

Date: 20.SEP.2016 10:55:41




Channel Separation Plot on Channel 39 - 40



Date: 20.SEP.2016 10:58:47

Channel Separation Plot on Channel 77 - 78



Date: 20.SEP.2016 11:01:33

3.3 Dwell Time Measurement

3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.4.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW $\geq$ RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Dwell Time

Test Mode :	3DH5	Temperature :	21~25℃
Test Engineer :	AC Chang	Relative Humidity :	50~54%


Mode	Hopping Channel Number	Hops Over Occupancy Time(hops)	Package Transfer Time (msec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
Normal	79	106.67	2.90	0.31	0.4	Pass
AFH	20	53.33	2.90	0.15	0.4	Pass

Remark:

- In normal mode, hopping rate is 1600 hops/s with 6 slots in 79 hopping channels.
With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4 x 79) (s),
Hops Over Occupancy Time comes to (1600 / 6 / 79) x (0.4 x 79) = 106.67 hops.
- In AFH mode, hopping rate is 800 hops/s with 6 slots in 20 hopping channels.
With channel hopping rate (800 / 6 / 20) in Occupancy Time Limit (0.4 x 20) (s),
Hops Over Occupancy Time comes to (800 / 6 / 20) x (0.4 x 20) = 53.33 hops.
- Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time



Package Transfer Time Plot



Date: 7.SEP.2016 00:52:19

3.4 20dB and 99% Bandwidth Measurement

3.4.1 Limit of 20dB and 99% Bandwidth

Reporting only


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 6.9.2 and 6.9.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.
Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel;
RBW $\geq$ 1% of the 20 dB bandwidth; VBW $\geq$ RBW; Sweep = auto; Detector function = peak;
Trace = max hold.
5. Use the following spectrum analyzer settings for 99 % Bandwidth measurement.
Span = approximately 1.5 to 5 times the 99% bandwidth, centered on a hopping channel;
RBW $\geq$ 1% of the 99% bandwidth; VBW $\geq$ RBW; Sweep = auto; Detector function = peak;
Trace = max hold.
6. Measure and record the results in the test report.


3.4.4 Test Setup



**3.4.5 Test Result of 20dB Bandwidth**


Test Mode :	1Mbps	Temperature :	21~25°C
Test Engineer :	AC Chang	Relative Humidity :	50~54%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	0.944
39	2441	0.932
78	2480	0.932

20 dB Bandwidth Plot on Channel 00


Date: 20.SEP.2016 11:31:44

20 dB Bandwidth Plot on Channel 39



Date: 20.SEP.2016 11:32:51

20 dB Bandwidth Plot on Channel 78




Date: 20.SEP.2016 11:33:55

Test Mode :	2Mbps	Temperature :	21~25℃
Test Engineer :	AC Chang	Relative Humidity :	50~54%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.256
39	2441	1.260
78	2480	1.260


20 dB Bandwidth Plot on Channel 00



Date: 20.SEP.2016 11:41:40




20 dB Bandwidth Plot on Channel 39



Date: 20.SEP.2016 11:40:22

20 dB Bandwidth Plot on Channel 78




Date: 20.SEP.2016 11:35:28

Test Mode :	3Mbps	Temperature :	21~25℃
Test Engineer :	AC Chang	Relative Humidity :	50~54%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.232
39	2441	1.232
78	2480	1.228


20 dB Bandwidth Plot on Channel 00



Date: 20.SEP.2016 11:42:37




20 dB Bandwidth Plot on Channel 39



Date: 20.SEP.2016 11:43:32

20 dB Bandwidth Plot on Channel 78




Date: 20.SEP.2016 11:44:37

**3.4.6 Test Result of 99% Occupied Bandwidth**

Test Mode :	1Mbps	Temperature :	21~25°C
Test Engineer :	AC Chang	Relative Humidity :	50~54%


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
00	2402	0.892
39	2441	0.884
78	2480	0.876

99% Occupied Bandwidth Plot on Channel 00

Date: 20.SEP.2016 10:36:51




99% Occupied Bandwidth Plot on Channel 39



Date: 20.SEP.2016 10:39:41

99% Occupied Bandwidth Plot on Channel 78




Date: 20.SEP.2016 10:42:22



Test Mode :	2Mbps	Temperature :	21~25°C
Test Engineer :	AC Chang	Relative Humidity :	50~54%


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
00	2402	1.168
39	2441	1.164
78	2480	1.168

99% Occupied Bandwidth Plot on Channel 00

Date: 20.SEP.2016 10:45:58




99% Occupied Bandwidth Plot on Channel 39



Date: 20.SEP.2016 10:49:48

99% Occupied Bandwidth Plot on Channel 78




Date: 20.SEP.2016 10:52:54



Test Mode :	3Mbps	Temperature :	21~25°C
Test Engineer :	AC Chang	Relative Humidity :	50~54%


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
00	2402	1.156
39	2441	1.148
78	2480	1.148

99% Occupied Bandwidth Plot on Channel 00

Date: 20.SEP.2016 10:56:16




99% Occupied Bandwidth Plot on Channel 39



Date: 20.SEP.2016 10:59:24

99% Occupied Bandwidth Plot on Channel 78



Date: 20.SEP.2016 11:02:09

Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.5 Peak Output Power Measurement

3.5.1 Limit of Peak Output Power

Section 15.247 (b) The maximum peak conducted output power of the intentional radiator shall not exceed the following: (1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts. The power limit for 1Mbps, 2Mbps, 3Mbps and AFH modes are 0.125 watts.


3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.5.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. Measure and record the results in the test report.

3.5.4 Test Setup





3.5.5 Test Result of Peak Output Power

Test Mode :	1Mbps	Temperature :	21~25°C
Test Engineer :	AC Chang	Relative Humidity :	50~54%

Channel	Frequency (MHz)	RF Power (dBm)		
		GFSK	Max. Limits (dBm)	Pass/Fail
		1 Mbps		
00	2402	11.14	20.97	Pass
39	2441	11.10	20.97	Pass
78	2480	10.98	20.97	Pass

Test Mode :	2Mbps	Temperature :	21~25°C
Test Engineer :	AC Chang	Relative Humidity :	50~54%

Channel	Frequency (MHz)	RF Power (dBm)		
		$\pi/4$ -DQPSK	Max. Limits (dBm)	Pass/Fail
		2 Mbps		
00	2402	11.96	20.97	Pass
39	2441	11.85	20.97	Pass
78	2480	11.77	20.97	Pass

Test Mode :	3Mbps	Temperature :	21~25°C
Test Engineer :	AC Chang	Relative Humidity :	50~54%

Channel	Frequency (MHz)	RF Power (dBm)		
		8-DPSK	Max. Limits (dBm)	Pass/Fail
		3 Mbps		
00	2402	12.39	20.97	Pass
39	2441	12.38	20.97	Pass
78	2480	12.26	20.97	Pass

3.6 Conducted Band Edges Measurement

3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.6.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100kHz, VBW = 300kHz. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2. and 3.
5. Measure and record the results in the test report.


3.6.4 Test Setup



3.6.5 Test Result of Conducted Band Edges


Test Mode :	1Mbps	Temperature :	21~25℃
Test Channel :	00 and 78	Relative Humidity :	50~54%
		Test Engineer :	AC Chang

Low Band Edge Plot on Channel 00



Date: 20.SEP.2016 11:25:42


High Band Edge Plot on Channel 78



Date: 20.SEP.2016 11:26:07


Test Mode :	2Mbps	Temperature :	21~25℃
Test Channel :	00 and 78	Relative Humidity :	50~54%
		Test Engineer :	AC Chang

Low Band Edge Plot on Channel 00



Date: 20.SEP.2016 11:26:44


High Band Edge Plot on Channel 78



Date: 20.SEP.2016 11:27:07


Test Mode :	3Mbps	Temperature :	21~25℃
Test Channel :	00 and 78	Relative Humidity :	50~54%
		Test Engineer :	AC Chang

Low Band Edge Plot on Channel 00



Date: 20.SEP.2016 11:27:38


High Band Edge Plot on Channel 78




Date: 20.SEP.2016 11:28:10

**3.6.6 Test Result of Conducted Hopping Mode Band Edges**

Test Mode :	1Mbps	Temperature :	21~25℃
Test Engineer :	AC Chang	Relative Humidity :	50~54%

1Mbps Hopping Mode Low Band Edge Plot


Date: 20.SEP.2016 11:07:47

1Mbps Hopping Mode High Band Edge Plot

Date: 20.SEP.2016 11:08:31


Test Mode :	2Mbps	Temperature :	21~25℃
Test Engineer :	AC Chang	Relative Humidity :	50~54%

2Mbps Hopping Mode Low Band Edge Plot



Date: 20.SEP.2016 11:10:07


2Mbps Hopping Mode High Band Edge Plot




Date: 20.SEP.2016 11:10:54



Test Mode :	3Mbps	Temperature :	21~25°C
Test Engineer :	AC Chang	Relative Humidity :	50~54%

3Mbps Hopping Mode Low Band Edge Plot

Date: 20.SEP.2016 11:12:14

3Mbps Hopping Mode High Band Edge Plot

Date: 20.SEP.2016 11:21:06

3.7 Conducted Spurious Emission Measurement

3.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.8.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


3.7.4 Test Setup



3.7.5 Test Result of Conducted Spurious Emission


Test Mode :	1Mbps	Temperature :	21~25°C
Test Channel :	00	Relative Humidity :	50~54%
		Test Engineer :	AC Chang

1Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 20.SEP.2016 10:37:26


1Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz




Date: 20.SEP.2016 10:37:48



Test Mode :	1Mbps	Temperature :	21~25°C
Test Channel :	39	Relative Humidity :	50~54%
		Test Engineer :	AC Chang

1Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz


Date: 20.SEP.2016 10:40:07

1Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz


Date: 20.SEP.2016 10:40:28



Test Mode :	1Mbps	Temperature :	21~25°C
Test Channel :	78	Relative Humidity :	50~54%
		Test Engineer :	AC Chang

1Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz


Date: 20.SEP.2016 10:42:48

1Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz


Date: 20.SEP.2016 10:43:10



Test Mode :	2Mbps	Temperature :	21~25°C
Test Channel :	00	Relative Humidity :	50~54%
		Test Engineer :	AC Chang

2Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz


Date: 20.SEP.2016 10:46:23

2Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz


Date: 20.SEP.2016 10:46:44



Test Mode :	2Mbps	Temperature :	21~25°C
Test Channel :	39	Relative Humidity :	50~54%
		Test Engineer :	AC Chang

2Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz


Date: 20.SEP.2016 10:50:13

2Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz


Date: 20.SEP.2016 10:50:35



Test Mode :	2Mbps	Temperature :	21~25°C
Test Channel :	78	Relative Humidity :	50~54%
		Test Engineer :	AC Chang

2Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz


Date: 20.SEP.2016 10:53:20

2Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz


Date: 20.SEP.2016 10:53:41



Test Mode :	3Mbps	Temperature :	21~25°C
Test Channel :	00	Relative Humidity :	50~54%
		Test Engineer :	AC Chang

3Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz


Date: 20.SEP.2016 10:56:42

3Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz


Date: 20.SEP.2016 10:57:04



Test Mode :	3Mbps	Temperature :	21~25°C
Test Channel :	39	Relative Humidity :	50~54%
		Test Engineer :	AC Chang

3Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz


Date: 20.SEP.2016 10:59:54

3Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz


Date: 20.SEP.2016 11:00:15



Test Mode :	3Mbps	Temperature :	21~25°C
Test Channel :	78	Relative Humidity :	50~54%
		Test Engineer :	AC Chang

3Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz

Date: 20.SEP.2016 11:02:52

3Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz

Date: 20.SEP.2016 11:03:14

3.8 Radiated Band Edges and Spurious Emission Measurement

3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.8.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.




3.8.3 Test Procedures

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz, RBW=1MHz for $f > 1$ GHz ; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
 - (3) For average measurement: use duty cycle correction factor method per 15.35(c).
Duty cycle = On time/100 milliseconds
On time = $N_1 * L_1 + N_2 * L_2 + \dots + N_{n-1} * L_{n-1} + N_n * L_n$
Where N_1 is number of type 1 pulses, L_1 is length of type 1 pulses, etc.
Average Emission Level = Peak Emission Level + $20 * \log(\text{Duty cycle})$
6. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level


Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (-24.78dB for sample 1 and -24.73dB for sample 2) derived from $20\log(\text{dwell time}/100\text{ms})$. This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.

3.8.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz




3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

3.8.6 Duty cycle correction factor for average measurement


Simple 1

3DH5 on time (One Pulse) Plot on Channel 39



Date: 22.SEP.2016 03:18:20

3DH5 on time (Count Pulses) Plot on Channel 39



Date: 22.SEP.2016 03:19:01

Note:

1. Worst case Duty cycle = on time/100 milliseconds = $2 * 2.88 / 100 = 5.76 \%$
2. Worst case Duty cycle correction factor = $20 * \log(\text{Duty cycle}) = -24.78 \text{ dB}$
3. 3DH5 has the highest duty cycle worst case and is reported.

**Duty Cycle Correction Factor Consideration for AFH mode:**

Bluetooth normal hopping rate is 1600Hz and reduced to 800Hz in AFH mode; due to the reduced number of hopping frequencies, with the same packet configuration the dwell time in each channel frequency within 100msec period is longer in AFH mode than normal mode.

In AFH mode, the minimum hopping frequencies are 20, to get the longest dwell time DH5 packet is observed; the period to have DH5 packet completing one hopping sequence is

$$2.88 \text{ ms} \times 20 \text{ channels} = 57.6 \text{ ms}$$


There cannot be 2 complete hopping sequences within 100ms period, considering the random hopping behavior, maximum 2 hops can be possibly observed within the period. $[100\text{ms} / 57.6\text{ms}] = 2 \text{ hops}$

Thus, the maximum possible ON time:


$$2.88 \text{ ms} \times 2 = 5.76 \text{ ms}$$

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time,

$$20 \times \log(5.76 \text{ ms}/100\text{ms}) = -24.78 \text{ dB}$$

Simple 2
3DH5 on time (One Pulse) Plot on Channel 39


Date: 23.SEP.2016 07:44:29

3DH5 on time (Count Pulses) Plot on Channel 39


Date: 23.SEP.2016 07:45:38

Note:

4. Worst case Duty cycle = on time/100 milliseconds = $2 * 2.90 / 100 = 5.80 \%$
5. Worst case Duty cycle correction factor = $20 * \log(\text{Duty cycle}) = -24.73 \text{ dB}$
6. 3DH5 has the highest duty cycle worst case and is reported.

Duty Cycle Correction Factor Consideration for AFH mode:

Bluetooth normal hopping rate is 1600Hz and reduced to 800Hz in AFH mode; due to the reduced number of hopping frequencies, with the same packet configuration the dwell time in each channel frequency within 100msec period is longer in AFH mode than normal mode.

In AFH mode, the minimum hopping frequencies are 20, to get the longest dwell time DH5 packet is observed; the period to have DH5 packet completing one hopping sequence is

$$2.90 \text{ ms} \times 20 \text{ channels} = 58.0 \text{ ms}$$

There cannot be 2 complete hopping sequences within 100ms period, considering the random hopping behavior, maximum 2 hops can be possibly observed within the period. $[100\text{ms} / 57.6\text{ms}] = 2 \text{ hops}$

Thus, the maximum possible ON time:

$$2.90 \text{ ms} \times 2 = 5.80 \text{ ms}$$

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time,

$$20 \times \log(5.80 \text{ ms}/100\text{ms}) = -24.73 \text{ dB}$$

3.8.7 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix A.

3.8.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix A.

3.9 AC Conducted Emission Measurement

3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.9.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.9.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


3.9.4 Test Setup



**3.9.5 Test Result of AC Conducted Emission**

Test Mode :	Mode 1	Temperature :	24~25°C
Test Engineer :	Kai-Chun Chu	Relative Humidity :	49~50%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + USB Cable (Charging from Adapter)		

ENV216 Auto Test FCC Power Bar - L

**Final Result : Quasi-Peak**

Frequency (MHz)	Quasi-Peak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	40.2	Off	L1	19.6	25.8	66.0
0.190000	28.4	Off	L1	19.6	35.6	64.0
0.270000	22.2	Off	L1	19.6	38.9	61.1
0.478000	25.8	Off	L1	19.6	30.6	56.4
1.142000	26.9	Off	L1	19.7	29.1	56.0
2.758000	21.4	Off	L1	19.5	34.6	56.0
18.150000	38.1	Off	L1	20.6	21.9	60.0


Final Result : Average

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	22.3	Off	L1	19.6	33.7	56.0
0.190000	19.3	Off	L1	19.6	34.7	54.0
0.270000	17.4	Off	L1	19.6	33.7	51.1
0.478000	20.7	Off	L1	19.6	25.7	46.4
1.142000	17.6	Off	L1	19.7	28.4	46.0
2.758000	14.7	Off	L1	19.5	31.3	46.0
18.150000	22.9	Off	L1	20.6	27.1	50.0



Test Mode :	Mode 1	Temperature :	24~25°C
Test Engineer :	Kai-Chun Chu	Relative Humidity :	49~50%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + USB Cable (Charging from Adapter)		

ENV216 Auto Test FCC Power Bar - N

**Final Result : Quasi-Peak**

Frequency (MHz)	Quasi-Peak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	44.3	Off	N	19.6	21.7	66.0
0.198000	31.4	Off	N	19.6	32.3	63.7
0.534000	28.3	Off	N	19.6	27.7	56.0
1.126000	21.6	Off	N	19.6	34.4	56.0
1.782000	20.4	Off	N	19.7	35.6	56.0
19.158000	28.2	Off	N	20.7	31.8	60.0

Final Result : Average

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	23.0	Off	N	19.6	33.0	56.0
0.198000	18.5	Off	N	19.6	35.2	53.7
0.534000	22.6	Off	N	19.6	23.4	46.0
1.126000	16.7	Off	N	19.6	29.3	46.0
1.782000	16.2	Off	N	19.7	29.8	46.0
19.158000	17.0	Off	N	20.7	33.0	50.0



3.10 Antenna Requirements

3.10.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.10.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.10.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Agilent	E4416A	GB41292344	300MHz~40GHz	Jan. 08, 2016	Sep. 07, 2016~ Sep. 20, 2016	Jan. 07, 2017	Conducted (TH02-HY)
Power Sensor	Agilent	E9327A	US40441548	300MHz~40GHz	Jan. 07, 2016	Sep. 07, 2016~ Sep. 20, 2016	Jan. 06, 2017	Conducted (TH02-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz~40GHz	Jun. 17, 2016	Sep. 07, 2016~ Sep. 20, 2016	Jun. 16, 2017	Conducted (TH02-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Sep. 14, 2016	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESCI 7	100724	9kHz~7GHz	Aug. 30, 2016	Sep. 14, 2016	Aug. 29, 2017	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Apr. 19, 2016	Sep. 14, 2016	Apr. 18, 2017	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Dec. 02, 2015	Sep. 14, 2016	Dec. 01, 2016	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Jan. 06, 2016	Sep. 14, 2016	Jan. 05, 2017	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Jan. 08, 2016	Sep. 14, 2016	Jan. 07, 2017	Conduction (CO05-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Sep. 02, 2015	Sep. 13, 2016~ Sep. 23, 2016	Sep. 01, 2017	Radiation (03CH12-HY)
Loop Cable	Rohde & Schwarz	N/A	N/A	9KHz~30MHz	Dec. 03, 2015	Sep. 13, 2016~ Sep. 23, 2016	Dec. 02, 2016	Radiation (03CH12-HY)
Amplifier	SONOMA	310N	187311	9kHz~1GHz	Nov. 16, 2015	Sep. 13, 2016~ Sep. 23, 2016	Nov. 15, 2016	Radiation (03CH12-HY)
Bilog Antenna	TESEQ	CBL 6111D	37059	30MHz~1GHz	Dec. 29, 2015	Sep. 13, 2016~ Sep. 23, 2016	Dec. 28, 2016	Radiation (03CH12-HY)
EMI Test Receiver	Rohde & Schwarz	ESU26	100390	20Hz~26.5GHz	Dec. 21, 2015	Sep. 13, 2016~ Sep. 23, 2016	Dec. 20, 2016	Radiation (03CH12-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1328	1GHz ~ 18GHz	Nov. 02, 2015	Sep. 13, 2016~ Sep. 23, 2016	Nov. 01, 2016	Radiation (03CH12-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1815698	1GHz~18GHz	Dec. 14, 2015	Sep. 13, 2016~ Sep. 23, 2016	Dec. 13, 2016	Radiation (03CH12-HY)
Preamplifier	Keysight	83017A	MY53270148	1GHz~26.5GHz	Jan. 30, 2016	Sep. 13, 2016~ Sep. 23, 2016	Jan. 29, 2017	Radiation (03CH12-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	Sep. 13, 2016~ Sep. 23, 2016	N/A	Radiation (03CH12-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1m~4m	N/A	Sep. 13, 2016~ Sep. 23, 2016	N/A	Radiation (03CH12-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	Sep. 13, 2016~ Sep. 23, 2016	N/A	Radiation (03CH12-HY)
Preamplifier	MITEQ	JS44-180040 00-33-8P	1840917	18GHz ~ 40GHz	Jun. 14, 2016	Sep. 13, 2016~ Sep. 23, 2016	Jun. 13, 2017	Radiation (03CH12-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170584	18GHz- 40GHz	Nov. 02, 2015	Sep. 13, 2016~ Sep. 23, 2016	Nov. 01, 2016	Radiation (03CH12-HY)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.3 dB
--	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.1 dB
--	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.2 dB
--	--------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.7 dB
--	--------



Appendix A. Radiated Spurious Emission

Sample 1

2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

BT	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BT CH00 2402MHz		2362.185	50.76	-23.24	74	47.92	26.97	7.37	31.5	100	306	P	H
		2362.185	25.98	-28.02	54	-	-	-	-	-	-	A	H
		2402	97.37	-	-	94.36	27.05	7.45	31.49	100	306	P	H
		2402	72.59	-	-	-	-	-	-	-	-	A	H
		2366.385	51.26	-22.74	74	48.41	26.97	7.37	31.49	100	356	P	V
		2366.385	26.48	-27.52	54	-	-	-	-	-	-	A	V
		2402	100.27	-	-	97.26	27.05	7.45	31.49	100	356	P	V
		2402	75.49	-	-	-	-	-	-	-	-	A	V
BT CH 39 2441MHz		2376.92	51.39	-22.61	74	48.5	27.01	7.37	31.49	100	299	P	H
		2376.92	26.61	-27.39	54	-	-	-	-	-	-	A	H
		2441	95.27	-	-	92.07	27.18	7.49	31.47	100	299	P	H
		2441	70.49	-	-	-	-	-	-	-	-	A	H
		2495.24	50.56	-23.44	74	47.19	27.3	7.53	31.46	100	299	P	H
		2495.24	25.78	-28.22	54	-	-	-	-	-	-	A	H
		2321.2	51.22	-22.78	74	48.54	26.89	7.3	31.51	100	357	P	V
		2321.2	26.44	-27.56	54	-	-	-	-	-	-	A	V
		2441	98.07	-	-	94.87	27.18	7.49	31.47	100	357	P	V
		2441	73.29	-	-	-	-	-	-	-	-	A	V
		2493.56	50.56	-23.44	74	47.19	27.3	7.53	31.46	100	357	P	V
		2493.56	25.78	-28.22	54	-	-	-	-	-	-	A	V



BT CH 78 2480MHz		2480	94.42	-	-	91.1	27.26	7.53	31.47	100	301	P	H
		2480	69.64	-	-	-	-	-	-	-	-	A	H
		2495.56	51.14	-22.86	74	47.77	27.3	7.53	31.46	100	301	P	H
		2495.56	26.36	-27.64	54	-	-	-	-	-	-	A	H
		2480	97.22	-	-	93.9	27.26	7.53	31.47	100	357	P	V
		2480	72.44	-	-	-	-	-	-	-	-	A	V
		2492.24	50.86	-23.14	74	47.49	27.3	7.53	31.46	100	357	P	V
		2492.24	26.08	-27.92	54	-	-	-	-	-	-	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BT (Harmonic @ 3m)

BT	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BT CH 00 2402MHz		4806	36.59	-37.41	74	52.92	31.23	10.59	58.15	100	0	P	H
		4806	11.81	-42.19	54	-	-	-	-	-	-	A	H
		4806	36.33	-37.67	74	52.66	31.23	10.59	58.15	100	0	P	V
		4806	11.55	-42.45	54	-	-	-	-	-	-	A	V
BT CH 39 2441MHz		4884	37.7	-36.3	74	53.58	31.33	10.89	58.1	100	0	P	H
		4884	12.92	-41.08	54	-	-	-	-	-	-	A	H
		7323	43.16	-30.84	74	51.96	36.12	14.18	59.1	100	0	P	H
		7323	18.38	-35.62	54	-	-	-	-	-	-	A	H
		4884	37.85	-36.15	74	53.73	31.33	10.89	58.1	100	0	P	V
		4884	13.07	-40.93	54	-	-	-	-	-	-	A	V
		7323	41.95	-32.05	74	50.75	36.12	14.18	59.1	100	0	P	V
		7323	17.17	-36.83	54	-	-	-	-	-	-	A	V
BT CH 78 2480MHz		4962	37.35	-36.65	74	52.74	31.45	11.19	58.03	100	0	P	H
		4962	12.57	-41.43	54	-	-	-	-	-	-	A	H
		7440	42.78	-31.22	74	51.17	36.46	14.32	59.17	100	0	P	H
		7440	18	-36	54	-	-	-	-	-	-	A	H
		4962	36.97	-37.03	74	52.36	31.45	11.19	58.03	100	0	P	V
		4962	12.19	-41.81	54	-	-	-	-	-	-	A	V
		7440	43.74	-30.26	74	52.13	36.46	14.32	59.17	100	0	P	V
		7440	18.96	-35.04	54	-	-	-	-	-	-	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

2.4GHz BT (LF)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BT LF		54.84	24.36	-15.64	40	42.69	13.35	0.78	32.46	-	-	P	H
		66.72	26.44	-13.56	40	45.68	12.15	1.06	32.45	300	107	P	H
		119.91	27.92	-15.58	43.5	41.32	17.6	1.43	32.43	-	-	P	H
		159.87	26.56	-16.94	43.5	40.23	17	1.75	32.42	-	-	P	H
		688.5	26.64	-19.36	46	28.92	26.31	3.82	32.41	-	-	P	H
		835.5	32.17	-13.83	46	31.51	28.36	4.28	31.98	-	-	P	H
		46.2	34.56	-5.44	40	49.61	16.63	0.78	32.46	100	358	QP	V
		66.72	36.59	-3.41	40	55.83	12.15	1.06	32.45	-	-	P	V
		92.37	28.26	-15.24	43.5	44.59	15.04	1.06	32.43	-	-	P	V
		160.14	30.05	-13.45	43.5	43.72	17	1.75	32.42	-	-	P	V
		559.7	26.16	-19.84	46	30.59	24.67	3.3	32.4	-	-	P	V
		949.6	33.83	-12.17	46	29.91	30.3	4.75	31.13	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Sample 2

2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BT CH 39 2441MHz		2312.94	45.97	-28.03	74	43.35	26.84	7.3	31.52	223	23	P	H
		2312.94	21.24	-32.76	54	-	-	-	-	-	-	A	H
		2441	99.09	-	-	95.89	27.18	7.49	31.47	223	23	P	H
		2441	74.36	-	-	-	-	-	-	-	-	A	H
		2488.38	46.24	-27.76	74	42.88	27.3	7.53	31.47	223	23	P	H
		2488.38	21.51	-32.49	54	-	-	-	-	-	-	A	H
		2380	45.43	-28.57	74	42.54	27.01	7.37	31.49	358	83	P	V
		2380	20.7	-33.3	54	-	-	-	-	-	-	A	V
		2441	93.4	-	-	90.2	27.18	7.49	31.47	358	83	P	V
		2441	68.67	-	-	-	-	-	-	-	-	A	V
		2493.98	46.09	-27.91	74	42.72	27.3	7.53	31.46	358	83	P	V
		2493.98	21.36	-32.64	54	-	-	-	-	-	-	A	V



2.4GHz 2400~2483.5MHz

BT (Harmonic @ 3m)

BT	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BT CH 39 2441MHz		4884	37.81	-36.19	74	53.69	31.33	10.89	58.1	100	0	P	H
		4884	13.08	-40.92	54	-	-	-	-	-	-	A	H
		7320	41.73	-32.27	74	50.53	36.12	14.18	59.1	100	0	P	H
		7320	17	-37	54	-	-	-	-	-	-	A	H
		4884	36.96	-37.04	74	52.84	31.33	10.89	58.1	100	0	P	V
		4884	12.23	-41.77	54	-	-	-	-	-	-	A	V
		7320	42.68	-31.32	74	51.48	36.12	14.18	59.1	100	0	P	V
		7320	17.95	-36.05	54	-	-	-	-	-	-	A	V
Remark	3. No other spurious found. 4. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

2.4GHz BT (LF)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BT LF		48.9	29.71	-10.29	40	45.62	15.77	0.78	32.46	317	58	P	H
		66.72	27.09	-12.91	40	46.33	12.15	1.06	32.45	-	-	P	H
		94.26	31.12	-12.38	43.5	47.21	15.28	1.06	32.43	-	-	P	H
		139.62	30.77	-12.73	43.5	43.96	17.8	1.43	32.42	-	-	P	H
		860	31.68	-14.32	46	30.56	28.66	4.28	31.82	-	-	P	H
		932.8	31.71	-14.29	46	28.56	29.83	4.6	31.28	-	-	P	H
		47.01	33.62	-6.38	40	49.1	16.2	0.78	32.46	100	312	QP	V
		66.72	31.91	-8.09	40	51.15	12.15	1.06	32.45	-	-	P	V
		92.64	28.62	-14.88	43.5	44.83	15.16	1.06	32.43	-	-	P	V
		159.87	31.65	-11.85	43.5	45.32	17	1.75	32.42	-	-	P	V
		512.8	25.65	-20.35	46	30.73	24.13	3.19	32.4	-	-	P	V
		962.2	31.7	-22.3	54	27.82	30.15	4.75	31.02	-	-	P	V
Remark	3. No other spurious found.												
	4. All results are PASS against limit line.												

**Note symbol**

	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.