


Test Report

| | |
|---------------------|--|
| FCC ID | P8KPxFB |
| Client | Interflex |
| Item tested | IF P600 |
| Standards | Class B FCC/CISPR AC line conducted emissions |
| Test Dates | June 4, 2003 |
| Results | As detailed within this report |
| Prepared by |  _____ Evan Gould – Test Engineer |
| Authorized by |  _____ Michael Buchholz – EMC Manager |
| Issue Date | 4/1/04 |
| Conditions of Issue | <p>This Test Report is issued subject to the conditions stated in the 'Terms and Conditions' section on page 7 of this report.</p> |

Curtis-Straus LLC is accredited by the American Association for Laboratory Accreditation for the specific scope of accreditation under Certificate Number 1627-01. This report may contain data which is not covered by the A2LA accreditation.

page 1 of 11

Introduction

On June 4, 2003 the IF P600 was tested for Class B FCC/CISPR AC line conducted emissions in the range 150kHz – 30MHz. The FCC ID P8KPxFB covers two models: P600 and P603. Both models have the same transmitter.

Setup Photo

IF P600



Measurements

| AC Mains Conducted Emissions | | | | | | | | | Curtis-Straus LLC | |
|---|---------------------|--------------------------------------|---------------------|--|-----------------------------|--------------------------|-----------------|---------------------------|-------------------|----------------------------------|
| Date: 04-Jun-03 Engineer: Evan Gould | | Company: Interflex EUT Desc: P600 | | Table No: 1 Work Order: D0428 Test Site: EMI 2 | | | | | | |
| Notes: LISN(s): Orange | | | | | | | | | | |
| Range: 0.15-30Mhz | | | Other Equipment: | | | Spectrum Analyzer: Blue | | | | |
| Frequency (MHz) | Q.P. Readings | | Ave. Readings | | Impedance Factor (dB) | FCC/CISPR B | | FCC/CISPR B | | Overall Result (Pass/Fail) |
| | QP1 (dB μ V) | QP2 (dB μ V) | AV1 (dB μ V) | AV2 (dB μ V) | | qp Limit (dB μ V) | qp Margin dB | AVE Limit (dB μ V) | AVE Margin dB | |
| 9.14 | 13.1 | 14.0 | | 20.0 | 60.0 | -26.0 | 50.0 | -16.0 | Pass | |
| 9.39 | 12.9 | 13.7 | | 20.0 | 60.0 | -26.3 | 50.0 | -16.3 | Pass | |
| 16.50 | 13.3 | 13.6 | | 20.0 | 60.0 | -26.4 | 50.0 | -16.4 | Pass | |
| 17.00 | 12.1 | 13.2 | | 20.0 | 60.0 | -26.8 | 50.0 | -16.8 | Pass | |
| 26.00 | 11.5 | 10.3 | | 20.0 | 60.0 | -28.5 | 50.0 | -18.5 | Pass | |
| 26.50 | 11.8 | 12.5 | | 20.0 | 60.0 | -27.5 | 50.0 | -17.5 | Pass | |

Table Result: Pass by -16.00 dB **Worst Freq:** 9.14 MHz

Test Procedure

Line Conducted Emissions Overview

REV 25-OCT-02

Digital and microprocessor based devices use radio frequency (RF) digital techniques for timing purposes and in applications such as switching power supplies. An unintentional consequence of this for AC powered devices is that a certain amount of the RF energy is impressed upon the AC power mains in the form of a conducted noise voltage. These conducted emissions have the potential to interfere with constructive uses of the RF spectrum such as AM radio and may also interfere with other devices attached to the same AC mains circuit. In order to reduce the likelihood that a device will interfere it is required that the conducted RF signals from the device are below an allowable level.

Testing is performed according to test methods from ANSI C63.4:1992 and CISPR 22:1998.

Line conducted emissions are measured from the device over the frequency range of 0.15 to 30 MHz. The EUT is powered from a Line Impedance Stabilization Network (LISN). The purpose of the LISN is to provide a calibrated impedance across which to measure the conducted emissions. The RF noise voltage produced by the EUT across the LISN is measured and compared to the limit. In order for the LISN to perform properly it is attached to a ground plane at least 2 meters by 2 meters in size. For tabletop equipment the measurement is performed with the equipment 40 cm from a vertical conducting surface bonded to a ground plane under the product. The ground plane extends 0.5 meters beyond the product and is 2.5mx3.7m in size. The vertical surface is 2.5mx2.5m.

As with radiated emissions, the “human factor” is accounted for by the use of a “quasi-peak” detector in the receiver or spectrum analyzer that measures the signal from the LISN. For certain tests (such as EN55022), both an average and a quasi-peak limit are specified. Emissions from a device must be below both limits when measured with the appropriate detector. If the emission level is below the average limit when measured with the quasi-peak detector, the EUT is presumed to pass both limits.

The possible operating modes of the EUT are explored to determine the configuration that maximizes emissions. Software is investigated as well as different methods of displaying data if available. Data is recorded in the worst case operating mode.

As of September 9, 2002, the FCC has harmonized it's conducted emission limits with CISPR. The following table displays the limits applicable to both FCC and CISPR.

| Line Conducted Emissions Limits: Class A (dB μ V) | | |
|---|------------|----------|
| Frequency (MHz) | Quasi-Peak | Average |
| 0.15 - 0.5 | 79 | 66 |
| 0.5 - 30 | 73 | 60 |
| Line Conducted Emissions Limits: Class B (dB μ V) | | |
| Frequency (MHz) | Quasi-Peak | Average |
| 0.15 - 0.5 | 66 - 56* | 56 - 46* |
| 0.5 - 5 | 56 | 46 |
| 5 - 30 | 60 | 50 |

Note 1: The lower limit applies at the transition frequencies
*Note 2: The limit decreases linearly with the logarithm of the frequency

Although the FCC is now accepting the limits shown above, it should be noted that the former FCC limits may be used until July 11, 2005 for any equipment authorized prior to July 12, 2004.

At least the six highest emissions with respect to the limit are recorded. If less than six emissions are visible above the noise floor of the instrumentation, then the noise floor at six representative frequencies is recorded. The test report will document if noise floor readings are reported.

Standard Uncertainty per NIST Technical Note 1297 1994 for this test is estimated to be 2dB.

All testing is performed within the framework of a laboratory quality system modeled on ISO/IEC 17025 *General requirements for the competence of calibration and testing laboratories* and is subject to our terms and conditions. This test method is covered by our A2LA accreditation.

Test Report for Interflex

Test Equipment Used

REV. 3/9/04

| SPECTRUM ANALYZER | RANGE | MN | MFR | SN | ASSET | CALIBRATION DUE |
|---------------------------------|-------------|------------------|---------|------------|-----------------|-----------------|
| BLUE | 9kHz-1.8GHz | 8591E | HP | 3223A00227 | 00070 | 04-SEP-2003 |
| LISN | RANGE | MN | MFR | SN | ASSET | CALIBRATION DUE |
| ORANGE | 10kHz-30MHz | 8012-50-R-24-BNC | SOLAR | 903707 | 00754 | 24-OCT-2003 |
| LINE CONDUCTED TEST SITE | | FCC CODE | IC CODE | VCCI CODE | CALIBRATION DUE | |
| EMI 2 | | 93448 | N/A | C-480 | 01-MAY-2006 | |

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.

Test Report for Interflex

Terms and Conditions

Paragraph 1. SERVICES. LABORATORY will:

- 1.1 Use the degree of care and skill ordinarily exercised by and consistent with the standards of the profession.
- 1.2 Perform all technical services in substantial accordance with the generally accepted laboratory principles and practices.
- 1.3 Retain all pertinent records relating to the services performed for a period of three (3) years following submission of the report describing such services, during which period the records will be made available to CLIENT upon reasonable request.

Paragraph 2. CLIENT'S RESPONSIBILITIES. CLIENT or his authorized representative will:

- 2.1 Provide LABORATORY with all plans, schematics, specifications, addenda, change orders, drawings and other information for the proper performance of technical services.
- 2.2 Designate a person to act as CLIENT's representative with respect to LABORATORY's services to be performed on behalf of the CLIENT; such person or firm to have complete authority to transmit instructions, receive information and data, interpret and define CLIENT's policies and decisions with respect to the LABORATORY's work on behalf of the CLIENT and to order, at CLIENT's expense, such technical services as may be required.
- 2.3 Designate a person who is authorized to receive copies of LABORATORY's reports.
- 2.4 Undertake the following:
 - (a) Secure and deliver to LABORATORY, without cost to LABORATORY, preliminary representative samples of the equipment proposed to require technical services, together with any relevant data.
 - (b) Furnish such labor and equipment needed by LABORATORY to handle samples at the LABORATORY and to facilitate the specified technical services.

Paragraph 3. GENERAL CONDITIONS:

- 3.1 LABORATORY, by the performance of services covered hereunder, does not in any way assume any of those duties or responsibilities customarily vested in the CLIENT, its employees, or any other party, agency or authority.
- 3.2 LABORATORY shall not be responsible for acts of omissions of any other party or parties involved in the design, manufacture or maintenance of the equipment or the failure of any employee, contractor or subcontractor to undertake any aspect of equipment's design, manufacture or maintenance.
- 3.3 LABORATORY is not authorized to revoke, alter, release, enlarge or release any requirement of the equipment's design, manufacture or maintenance unless specifically authorized by CLIENT or his authorized representative.
- 3.4 THE ONLY WARRANTY MADE BY LABORATORY IN CONNECTION WITH ITS SERVICE PERFORMED HEREUNDER IS THAT IT WILL USE THAT DEGREE OF CARE AND SKILL AS SET FORTH IN PARAGRAPH 1 ABOVE. NO OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE OR INTENDED FOR SERVICES PROVIDED HEREUNDER.
- 3.5 Where the LABORATORY indicates that additional testing is advisable to obtain more valid or useful data, and where such testing has not been authorized, CLIENT agrees to view such test reports as inconclusive and preliminary.
- 3.6 The LABORATORY will supply technical service and prepare a report based solely on the sample submitted to the LABORATORY by the CLIENT. The CLIENT understands that application of the data to other devices is highly speculative and should be applied with extreme caution.
- 3.7 The LABORATORY agrees to exercise ordinary care in receiving, preserving and shipping (F.O.B. Littleton, MA) any sample to be tested, but assumes no responsibility for damages, either direct or consequential, which arise from loss, damage or destruction of the samples due to the act of examination, modification or testing, or technical services or circumstances beyond LABORATORY's control.
- 3.8 The LABORATORY will hold samples for thirty (30) days after tests are completed, or until the CLIENT's outstanding debts to the LABORATORY are satisfied, whichever is later.
- 3.9 The CLIENT recognizes that generally accepted error variances apply and agrees to consider such error variances in its use of test data.
- 3.10 It is agreed between LABORATORY and CLIENT that no distribution of any tests, reports or analysis other than that described below shall be made to any third party without the prior written consent of both parties unless such distribution is mandated by operation of law. It is agreed that tests, reports, or analysis results may be disclosed to third party auditors of the laboratory at the laboratory facility in the course of accreditation maintenance audits. No reference to reports or technical services of the LABORATORY shall be made in any advertising or promotional literature without the express written permission of the LABORATORY.
- 3.11 The CLIENT acknowledges that all employees of LABORATORY operate under employment contracts with the LABORATORY and CLIENT agrees not to solicit employment of such employees or to solicit information related to other clients from said employees.
- 3.12 In recognition of the relative risks and benefits of the project to both CLIENT and LABORATORY, the risks have been allocated such that the CLIENT agrees, to the fullest extent permitted by law, to limit the liability of the LABORATORY to the CLIENT for any and all claims, losses, costs, damages of any nature whatsoever or claims expenses from any cause or causes, including attorneys' fees and costs and expert witness fees and costs, so that the total aggregate liability of the LABORATORY to the CLIENT shall not exceed \$100,000, or the LABORATORY'S total fee for services rendered on this project, whichever is greater. It is intended that this limitation apply to any and all liability or cause of action however alleged or arising, unless otherwise prohibited by law.

Paragraph 4. INSURANCE:

- 4.1 LABORATORY shall secure and maintain throughout the full period of the services provided to the CLIENT adequate insurance to protect it from claims under applicable Workmen's Compensation Acts and also shall maintain one million dollars of general liability coverage to cover claims for bodily injury, death or property damage as may arise from the performance of its services.
- 4.2 The CLIENT hereby warrants that it has sufficient insurance to protect its employees adequately under applicable Workmen's Compensation Acts and for bodily injury, death, or property damage.
- 4.3 No insurance of whatever kind or type, which may be carried by either party is to be considered as in any way limiting any other party's responsibility for damages resulting from their operations or for furnishing work and materials.

Paragraph 5. PAYMENT:

- 5.1 CLIENT shall pay to LABORATORY such fees for services as previously agreed, orally or in writing, within 30 days of presentation of a bill for such services performed. In the event CLIENT ordered, orally or in writing, services but such services were not assigned a rate for billing, such services shall be billed at the LABORATORY's reasonable and customary rate.
- 5.2 CLIENT shall be responsible for all shipping, customs and other expenses related to services provided by LABORATORY to the CLIENT, and shall fully insure any test sample or other equipment provided to LABORATORY by the CLIENT.
- 5.3 Amounts overdue from CLIENT to LABORATORY shall be charged interest at a rate of 1½% per month.

Test Report for Interflex

Paragraph 6. ISO/IEC GUIDE 17025 ADDITIONS:

- 6.1 CLIENT agrees that this test report will not be reproduced except in full, without written approval from the LABORATORY.
- 6.2 CLIENT agrees that this test report shall not be used to claim product endorsement by A2LA or ANSI or any agency of the U.S. Government.
- 6.3 CLIENT agrees that test results presented herein relate only to the sample tested by the LABORATORY.

Test Report for Interflex

A2LA Accreditation

| <p><u>SCOPE OF ACCREDITATION TO ISO/IEC 17025-1999</u></p> <p>CURTIS-STRAU¹ 527 Great Road Littleton, MA 01460 Barry Quinlan Phone: 978-486-8880</p> <p>ELECTRICAL</p> <p>Valid until: July 31, 2005</p> <p>Certificate Number: 1627-01</p> <p>In recognition of the successful completion of the A2LA evaluation process, accreditation is granted to this laboratory to perform the following Electromagnetic Compatibility (EMC), Telecommunications, and Product Safety tests:</p> <p>Electromagnetic Compatibility (EMC)</p> <p>Radiated emissions testing (electric and magnetic fields); Conducted emissions testing (voltage and current); Electrostatic Discharge testing; Electrical Fast Transient testing; Radiated Immunity testing; Conducted Immunity testing; Lightning Immunity testing; Voltage Dips, Interrupts and Voltage Variations testing; Magnetic Immunity testing; RF Power measurements; Frequency Stability measurements; Longitudinal Induction measurements; Harmonic emissions testing; Light flicker testing; Low frequency disturbance voltage testing; Disturbance Power measurements</p> <p>EMC Standards</p> <table border="0"> <thead> <tr> <th><u>Title</u></th> </tr> </thead> <tbody> <tr> <td>Emissions</td> <td>Limits and methods of measurement of radio disturbance characteristics of information technology equipment</td> </tr> <tr> <td>CISPR 22 1997 with amendments 1 and 2</td> <td>Limits and methods of measurement of radio interference characteristics of information technology equipment</td> </tr> <tr> <td>CNS13438 1994</td> <td>Limits and methods of measurement of radio disturbance characteristics of information technology equipment</td> </tr> <tr> <td>EN55022:1994 and 1998</td> <td>Limits and methods of measurement of radio disturbance characteristics of information technology equipment</td> </tr> <tr> <td>SABS CISPR 22:1997</td> <td>Information technology equipment – Radio disturbance characteristics – Limits and methods of measurement</td> </tr> <tr> <td>Canada ICES-003 1997 AS/NZS 3548 1995</td> <td>Digital apparatus</td> </tr> <tr> <td>CISPR 11 1990, 1997, 1999</td> <td>Australian/New Zealand Standard Limits and methods of measurement of radio disturbance characteristics of information technology equipment</td> </tr> <tr> <td></td> <td>Limits and methods of measurement of electromagnetic disturbance characteristics of industrial, scientific and medical (ISM) radio-frequency equipment</td> </tr> </tbody> </table> <p>¹ Note: This accreditation covers testing performed at the laboratory listed above and the satellite facility located at 168 Ayer Rd, Littleton, MA 01460</p> | | <u>Title</u> | Emissions | Limits and methods of measurement of radio disturbance characteristics of information technology equipment | CISPR 22 1997 with amendments 1 and 2 | Limits and methods of measurement of radio interference characteristics of information technology equipment | CNS13438 1994 | Limits and methods of measurement of radio disturbance characteristics of information technology equipment | EN55022:1994 and 1998 | Limits and methods of measurement of radio disturbance characteristics of information technology equipment | SABS CISPR 22:1997 | Information technology equipment – Radio disturbance characteristics – Limits and methods of measurement | Canada ICES-003 1997 AS/NZS 3548 1995 | Digital apparatus | CISPR 11 1990, 1997, 1999 | Australian/New Zealand Standard Limits and methods of measurement of radio disturbance characteristics of information technology equipment | | Limits and methods of measurement of electromagnetic disturbance characteristics of industrial, scientific and medical (ISM) radio-frequency equipment | <p>EN 55011 1991, 1998</p> <p>SABS CISPR 11:1997</p> <p>–</p> <p>Canada ICES-001 1998 CNS13803 AS/NZS 2064: 1997 disturbance</p> <p>CSA C108.8 – M1983</p> <p>CISPR 13:1996, 1998, 2001</p> <p>EN 55013: 1990, 2001 equipment:</p> <p>EN 55013 Amend 12 1994</p> <p>SABS CISPR 13: 1996</p> <p>CNS 13439 of AS/NZS 1053: 1999</p> <p>CISPR 14 1993 (<i>except discontinuous disturbances</i>) for apparatus.</p> <p>EN 55014 1993, 1997 <i>discontinuous disturbances</i>) for</p> <p>AS/NZS 1044: 1995 <i>discontinuous disturbances</i>) for</p> <p>Immunity</p> <p>CNS13783-1 SABS CISPR 14-1 1993</p> <p>SABS CISPR 14-2 1997 + A1:2001</p> <p>Household Electrical Appliances</p> <p>Electromagnetic compatibility – Requirements for household appliances, electric tools and similar apparatus Part 1: Emission – Product family standard</p> <p>Electromagnetic compatibility – Requirements for household appliances, electric tools and similar apparatus Part 2: Immunity – Product family standard</p> <p>(A2LA Cert. No. 1627-01) 10/31/03</p> <p>Page 1 of 11</p> <p>EN 61000-6-1: 1997, 2001</p> <p>industrial</p> <p>EN 61000-6-2: 1998, 2001</p> <p>EN 50091-2 1996</p> <p>EMC</p> <p>EN 55024 1998</p> <p>Limits</p> <p>EN 55103-1 1997</p> <p>audio, for</p> <p>EN 55103-2 1997</p> <p>audio, (<i>excluding Annex A3</i>) use.</p> <p>EN 61326 1998</p> <p>–</p> <p>EN 61547 1996</p> <p>EN 50130-4 1996</p> <p>family</p> <p>and</p> <p>EN 55104 1995</p> <p>household</p> <p>EN 50083-2 1995</p> <p>2:</p> <p>EN 60601-1-2: 1993, 2002</p> <p>safety</p> <p>IEC 1800-3 1995</p> <p>product</p> <p>EN 60555 Part 2 1987</p> <p>and</p> <p>EN 60555 Part 3 1987</p> <p>and</p> <p>EN 61000-3-2: 1995, 2000</p> <p>Limits AS/NZS 61000.3.2 1998</p> <p>EN 61000-3-3 1995</p> <p>AS/NZS 61000.3.3 1999</p> <p>ETS 300 386-1 1994</p> <p>Part 1:</p> <p>(A2LA Cert. No. 1627-01) 10/31/03</p> <p>Page 2 of 11</p> <p>Electromagnetic Compatibility (EMC)- Part 6: Generic standards-Section 1: Immunity for residential, commercial and light-environments</p> <p>Electromagnetic Compatibility (EMC)- Part 6: Generic standards-Specification for Uninterruptible Power Systems (UPS). Part 2: requirements</p> <p>Information technology equipment – Immunity Characteristics – and methods of measurement.</p> <p>Electromagnetic Compatibility – Product family standard for video, audio-visual and entertainment lighting control apparatus professional use. Part 1: Emission</p> <p>Electromagnetic Compatibility – Product family standard for video, audio-visual and entertainment lighting control professional Part 2: Immunity</p> <p>Electrical equipment for measurement, control and laboratory use</p> <p>EMC requirements</p> <p>Equipment for general lighting purposes – EMC immunity</p> <p>Alarm Systems. Part 4: Electromagnetic compatibility. Product standard: Immunity requirements for components of fire, intruder social alarm systems.</p> <p>Electromagnetic compatibility immunity – requirements for appliances, tools and similar apparatus. Product family standard. Cabled distribution systems for television and sound signals. Part</p> <p>Electromagnetic compatibility for equipment.</p> <p>Medical electrical equipment Part 1: general requirements for Section 2: Collateral standard: Electromagnetic compatibility – Adjustable speed electrical power drive systems. Part 3: EMC standard including specific test methods.</p> <p>Disturbances in supply systems caused by household appliances similar electrical equipment. Part 2: Harmonics</p> <p>Disturbances in supply systems caused by household appliances similar electrical equipment. Part 3: Voltage fluctuations.</p> <p>Electromagnetic compatibility (EMC). Part 3: Limits Section 2: for harmonic current emissions</p> <p>Electromagnetic compatibility (EMC). Part 3: Limits Section 2: Limitation of voltage fluctuations and flicker in low-voltage supply systems.</p> <p>Equipment Engineering (EE); Public telecommunication network equipment electro-magnetic compatibility (EMC) requirements</p> <p>Product family overview, compliance criteria and test levels</p> <p>(A2LA Cert. No. 1627-01) 10/31/03</p> <p>Page 4</p> | |
|---|--|--|-----------|--|---------------------------------------|---|---------------|--|-----------------------|--|--------------------|--|--|-------------------|---------------------------|--|--|--|---|--|
| <u>Title</u> | | | | | | | | | | | | | | | | | | | | |
| Emissions | Limits and methods of measurement of radio disturbance characteristics of information technology equipment | | | | | | | | | | | | | | | | | | | |
| CISPR 22 1997 with amendments 1 and 2 | Limits and methods of measurement of radio interference characteristics of information technology equipment | | | | | | | | | | | | | | | | | | | |
| CNS13438 1994 | Limits and methods of measurement of radio disturbance characteristics of information technology equipment | | | | | | | | | | | | | | | | | | | |
| EN55022:1994 and 1998 | Limits and methods of measurement of radio disturbance characteristics of information technology equipment | | | | | | | | | | | | | | | | | | | |
| SABS CISPR 22:1997 | Information technology equipment – Radio disturbance characteristics – Limits and methods of measurement | | | | | | | | | | | | | | | | | | | |
| Canada ICES-003 1997 AS/NZS 3548 1995 | Digital apparatus | | | | | | | | | | | | | | | | | | | |
| CISPR 11 1990, 1997, 1999 | Australian/New Zealand Standard Limits and methods of measurement of radio disturbance characteristics of information technology equipment | | | | | | | | | | | | | | | | | | | |
| | Limits and methods of measurement of electromagnetic disturbance characteristics of industrial, scientific and medical (ISM) radio-frequency equipment | | | | | | | | | | | | | | | | | | | |
| <p>European Union Basic EMC Standards</p> <p>EN 61000-4-2: 1995, 1999, 2001</p> <p>EN 61000-4-3:1997, 1998, 2002</p> <p>AS/NZS 61000.4.3 1999</p> <p>EN 61000-4-4 1995</p> <p>EN 61000-4-5 1995</p> <p>AS/NZS 61000.4.5 1999</p> <p>EN 61000-4-6 1996</p> <p>AS/NZS 61000.4.6 1999</p> <p>EN 61000-4-8 1994</p> <p>EN 61000-4-11 1994</p> <p>ENV 61000-2-2 1993</p> <p>EU Product Family Standards</p> <p>EN 50081-1 1992</p> <p>EN 50081-2 1993</p> <p>EN 50082-1 1992, 1998</p> <p>EN 50082-2 1995</p> <p>(A2LA Cert. No. 1627-01) 10/31/03</p> | <p>Immunity requirements for household appliances, tools and similar apparatus.</p> <p>Limits and methods of measurement of immunity characteristics of sound and television broadcast receivers and associated equipment.</p> <p>Electromagnetic immunity of broadcast receivers and Associated equipment.</p> <p>Information technology equipment – Immunity characteristics – Limits and methods of measurement</p> <p>Information technology equipment – Immunity characteristics – Limits and methods of measurement</p> <p>Approval and test specification – Medical electrical Equipment – General requirements for safety – Collateral Standard: Electromagnetic compatibility – Requirements and tests.</p> <p>Electromagnetic compatibility (EMC). Part 4: Testing and measurement techniques. Section 2: Electrostatic discharge immunity test – Basic EMC Publication</p> <p>Electromagnetic compatibility (EMC). Part 4: Testing and measurement techniques. Section 3: Radiated, radio-frequency, electromagnetic field immunity test</p> <p>Electromagnetic compatibility (EMC). Part 4: Testing and measurement techniques. Section 4: Electrical fast transient/burst immunity test – Basic EMC publication (EMC) Part 4: Testing and measurement techniques. Section 5: Surge immunity test.</p> <p>Electromagnetic compatibility (EMC). Part 4: Testing and measurement techniques. Section 6: Immunity to conducted disturbances, induce by radio-frequency fields.</p> <p>Electromagnetic compatibility (EMC). Part 4: Testing and measurement techniques. Section 8: Power frequency magnetic field immunity test.</p> <p>(EMC) Part 4: Testing and measurement techniques. Section 11: Voltage dips, short interruptions and voltage Variations immunity tests.</p> <p>Electromagnetic compatibility (EMC). Part 2: Environment, Section 2: Compatibility levels for low-frequency conducted disturbances and signaling in public low-voltage power supply systems (IEC 1000-2-2:1990)</p> <p>Electromagnetic capability – Generic emission standard. Part 1: Residential, commercial and light industry. (I.S.)</p> <p>Electromagnetic compatibility – Generic emission standard. Part 2: Industrial environment</p> <p>Electromagnetic compatibility – Generic emission standard. Part 1: Residential, commercial and light industry</p> <p>Electromagnetic compatibility – Generic immunity Standard. Part 2: Industrial environment</p> <p>Page 3 of 11</p> | <p>Electromagnetic Compatibility (EMC)- Part 6: Generic standards-Section 1: Immunity for residential, commercial and light-environments</p> <p>Electromagnetic Compatibility (EMC)- Part 6: Generic standards-Specification for Uninterruptible Power Systems (UPS). Part 2: requirements</p> <p>Information technology equipment – Immunity Characteristics – and methods of measurement.</p> <p>Electromagnetic Compatibility – Product family standard for video, audio-visual and entertainment lighting control apparatus professional use. Part 1: Emission</p> <p>Electromagnetic Compatibility – Product family standard for video, audio-visual and entertainment lighting control professional Part 2: Immunity</p> <p>Electrical equipment for measurement, control and laboratory use</p> <p>EMC requirements</p> <p>Equipment for general lighting purposes – EMC immunity</p> <p>Alarm Systems. Part 4: Electromagnetic compatibility. Product standard: Immunity requirements for components of fire, intruder social alarm systems.</p> <p>Electromagnetic compatibility immunity – requirements for appliances, tools and similar apparatus. Product family standard. Cabled distribution systems for television and sound signals. Part</p> <p>Electromagnetic compatibility for equipment.</p> <p>Medical electrical equipment Part 1: general requirements for Section 2: Collateral standard: Electromagnetic compatibility – Adjustable speed electrical power drive systems. Part 3: EMC standard including specific test methods.</p> <p>Disturbances in supply systems caused by household appliances similar electrical equipment. Part 2: Harmonics</p> <p>Disturbances in supply systems caused by household appliances similar electrical equipment. Part 3: Voltage fluctuations.</p> <p>Electromagnetic compatibility (EMC). Part 3: Limits Section 2: for harmonic current emissions</p> <p>Electromagnetic compatibility (EMC). Part 3: Limits Section 2: Limitation of voltage fluctuations and flicker in low-voltage supply systems.</p> <p>Equipment Engineering (EE); Public telecommunication network equipment electro-magnetic compatibility (EMC) requirements</p> <p>Product family overview, compliance criteria and test levels</p> <p>(A2LA Cert. No. 1627-01) 10/31/03</p> <p>Page 4</p> | | | | | | | | | | | | | | | | | | |



Test Report for Interflex

| | | |
|--|---|--|
| <p>ETS EN 300 386-2 1997, 1998, ETS EN 300 386 2000 v1.2.1, 2001 v1.3.1</p> <p>ETS 300 132-1 1996</p> <p>ETS 300 132-2 1996</p> <p>ETR 283 1997</p> <p>EU radio standards (ETS) EN 300 385 v1.2.1: 1998, 1999</p> <p>EN 300 330 v1.2.1: 1998, 1999</p> <p>ETS 300 328 1996</p> <p>ETS EN 300 440 v1.2.1 1999</p> <p>EN 301 893:2002 v1.2.1</p> <p>ETS 300 836-1:1998</p> <p>EN301 489-17:2002</p> | <p>Electromagnetic compatibility and Radio spectrum matters (ERM); Telecommunication network equipment; Electromagnetic compatibility (EMC) requirements; Part 2: Product family standard.</p> <p>Equipment Engineering (EE); Power supply interface at the input to telecommunications equipment; Part 1: Operated by alternating current (ac) derived from direct current (dc) sources</p> <p>Equipment Engineering (EE); Power supply interface at the input to telecommunications equipment; Part 2: Operated by direct current (dc)</p> <p>Equipment Engineering (EE); Transient voltages at Interface A on telecommunications direct current (DC) power distributions.</p> <p>Electromagnetic compatibility and Radio spectrum matters (ERM); Electromagnetic Compatibility (EMC) standard for fixed radio links and ancillary equipment (ETS)</p> <p>Electromagnetic compatibility and Radio spectrum matters (ERM); Short range devices (SRD); Technical characteristics and test methods for radio equipment in the range 9 kHz to 25 MHz and inductive loop systems in the frequency range 9 kHz to 30 MHz</p> <p>Radio Equipment and Systems (RES); Wideband transmission systems; Technical characteristics and test conditions for data transmission equipment operating in the 2.4 GHz ISM band and using spread spectrum modulation techniques</p> <p>Electromagnetic compatibility and Radio spectrum matters (ERM); Short range devices; Technical characteristics and test methods for radio equipment to be used in the 1 GHz to 40 GHz frequency range</p> <p>Broadband Radio Access Networks (BRAN); 5 GHz (draft) high performance RLAN; Harmonized EN covering Essential requirements of article 3.2 of the R&TTE Directive</p> <p>Broadband Radio Access Networks (BRAN); High Performance Radio Local Area Network (HIPERLAN) Type 1; Conformance testing specification; Part 1: Radio Type approval and Radio Frequency (RF) conformance test specification</p> <p>Electromagnetic compatibility and Radio spectrum Matters v1.2.1 (ERM); Electromagnetic Compatibility (EMC) standard for radio equipment and services; Part 17: Specific conditions for 2.4 GHz wideband transmission systems and 5 GHz high performance RLAN equipment</p> | <p>EN 300 328-2:2001 v1.2.1 in the 2.4 GHz ISM band and using spread spectrum modulation techniques; Part 2: Harmonized EN covering requirements under article 3.2 of the R&TTE Directive</p> <p>Electromagnetic compatibility and Radio spectrum Matters (ERM); Electromagnetic Compatibility (EMC) standard for radio equipment and services; Part 1: Common technical requirements</p> <p>EN 60669-2-1:2002 Switches for household and similar fixed electrical installations -- Part 2-1: Particular requirements -- Electronic switches</p> <p>Canada Radio Standards Canadian GL-36 1995</p> <p>Canadian RSS-119 1999, 2000 Issue 6 27.41 to 960.0 MHz</p> <p>Canadian RSS-134 1996 & 2000, Issue 1 Rev 1</p> <p>Canadian RSS-210 2000 Issue 3</p> <p>RFS29 1998</p> <p>FCC Standards</p> <p>47 CFR FCC low power transmitters operating on frequencies below 1 GHz, emergency alert systems, unintentional radiators and ISM devices. Scope A1</p> <p>47 CFR FCC low power transmitters operating on frequencies above 1 GHz, with the exception of spread spectrum devices. Scope A2</p> <p>47 CFR FCC Unlicensed Personal Scope A3 Communications System (PCS) devices</p> <p>47 CFR FCC Unlicensed National Scope A4 Information Infrastructure devices and low power transmitters using spread spectrum techniques.</p> <p>47 CFR FCC Personal mobile Scope B1 Radio Services in the following FCC Rule Parts 22, 24, 25, 27.</p> <p>47 CFR FCC General Mobile Radio Scope Services in the following FCC Rule Parts 22, 74, 90, 95, 97.</p> <p>47 CFR FCC Maritime and Aviation Scope RadioServices in 47 CFR Parts 80 and 87</p> <p>47 CFR FCC Microwave Radio Services B4 Scope in 47 CFR Parts 21, 74 and 101.</p> |
| <p>(A2LA Cert. No. 1627-01) 10/31/03</p> | <p>Page 5 of 11</p> <p>(A2LA Cert. No. 1627-01) 10/31/03</p> <p>Page 6 of 11</p> | |

| | | |
|---|--|--|
| <p>FCC/OST MP-5 1986</p> <p>GR-1089-CORE: 1997, 1999 issue 2/ 2002 Issue 3</p> <p>ANSI EMC Standards ANSI C63.4: 1992, 1999, 2001</p> <p>ANSI C63.5 1988</p> <p>IEEE EMC Standards IEEE C62.41: 1980, 1991</p> <p>Swedish EMC Standards BAKOM 3336.3 1995</p> <p>South African EMC standards other than CISPR equivalents SABS 1718-1: 1996</p> <p>Japanese VCCI Standards VCCI V-3/99.05 1999 VCCI V-4/99.05 1999</p> <p>Telecommunications Telecommunications Registration; General test methods; Lightning surge; Drop testing; Balance testing; Signal power (metallic and longitudinal); Frequency measurements; Pulse templates; Leakage testing; Impedance testing; Hearing Aid Compatibility testing (<i>excluding volume control</i>); Protocol analysis and Jitter testing.</p> <p>Telecom Standards</p> <p>FCC 47 CFR Part 68 Telephone</p> <p>CS-03 Issue 8 1996 through amendment 5</p> <p>TIA/EIA TSB31-B 1998</p> | <p>FCC (Federal Communications Commission) methods Of measurement of radio noise emissions from industrial, scientific and medical equipment.</p> <p>Bellcore electromagnetic compatibility and electrical safety – Generic criteria for network telecommunications equipment.</p> <p>American National Standard for methods of measurement of radio-noise emissions for low-voltage electrical and electronic equipment in the range of 9 kHz to 40GHz</p> <p>American National Standard for electromagnetic compatibility – radiated emissions measurements in electromagnetic interference (EMI) control – calibration of antennas.</p> <p>IEEE recommended practice on surge voltages in low-voltage AC power circuits</p> <p>Electromagnetic compatibility and electrical safety (EMC & S) for wired terminal equipment. Harmonization document information over the OFCOM requirements.</p> <p>South African Bureau of Standards: Specification for Gaming equipment. Part 1: Casino equipment.</p> <p>Technical Requirements Instruction for Test Conditions for Requirement under Test</p> <p>Connection of terminal equipment to the telephone Terminal Equipment network. Analog and Digital Equipment. TCB Scope C1.</p> <p>Specification for terminal equipment, terminal systems, Network protection devices, connection arrangements and hearing aids compatibility.</p> <p>Bulletin Part 68 Rationale and Measurement Guidelines (Feb 1998)</p> | <p>TIA/EIA-IS-968</p> <p>TIA/EIA-IS-883</p> <p>TIA-968-A</p> <p>T1.TRQ 6-2001</p> <p>Canada VDSL January 2003</p> <p>AS/ACIF S002-2001 AS/ACIF S016-2001</p> <p>AS/ACIF S031-2001 AS/ACIF S038-2001 AS/ACIF S043-2001</p> <p>ITU-T G.703 HKTA 2028</p> <p>HKTA 2029</p> <p>TBR 1 : 1995</p> <p>TBR 2 : 1997</p> <p>Recommendation X.25 interfaces at data signaling rates up to 1 920 kbit/s utilizing interfaces derived from CCITT Recommendations</p> |
| <p>(A2LA Cert. No. 1627-01) 10/31/03</p> | <p>Page 7 of 11</p> | <p>(A2LA Cert. No. 1627-01) 10/31/03</p> <p>Page 8 of 11</p> |



Test Report for Interflex

| | |
|---|---|
| <p>TBR 3 : 1995 + Amdt : 1997</p> <p>TBR 4 : 1995 + Amdt : 1997</p> <p>TBR 012 : 1993 + Amdt : 1996</p> <p>TBR 013 : 1996</p> <p>TBR 21 : 1998</p> <p>TBR 24 : 1997</p> <p><i>Australia</i></p> <p>TS 002 : 1997</p> <p>TS 016 : 1997</p> <p>TS 031 : 1997</p> <p>TS 038 : 1997</p> <p>AS/ACIF S043.2:2001</p> <p>Product Safety</p> <p>General test methods; Input tests; Electric strength tests; Impulse tests; Permanency of marking tests; Accessibility tests; Energy Hazard measurements; Capacitor discharge tests; Humidity conditioning; Earthing tests; Limited power source measurements; Stability tests; Steel ball tests; Lithium Battery Reverse Current measurements; Leakage current tests; Transformer abnormal tests; Telecom leakage tests; Over voltage/power cross tests (excluding x-ray tests).</p> <p>Product Safety Standards</p> <p><i>Specific Product Safety Standards</i></p> <p>IEC 950 1991</p> <p>UL 1950 1998</p> <p>CSA C22.2 No.950-95</p> <p>UL 60950 2000</p> <p>(A2LA Cert. No. 1627-01) 10/31/03</p> | <p>Integrated Services Digital Network (ISDN); Attachment requirements for terminal equipment to connect to an ISDN using ISDN basic access</p> <p>Integrated Services Digital Network (ISDN); Attachment requirements for terminal equipment to connect to an ISDN using ISDN primary rate access</p> <p>Business Telecommunications (BT); Open Network Provision (ONP) technical requirements; 2 048 kbit/s digital unstructured leased line (D2048U) Attachment requirements for terminal equipment</p> <p>Business Telecommunications (BTC); 2 048 kbit/s digital structured leased lines (D2048S); Attachment requirements for terminal equipment interface</p> <p>Terminal Equipment (TE); Attachment requirements for pan-European approval for connection to the analogue Public Switched Telephone Networks (PSTNs) of TE (excluding TE supporting the voice telephony service) in which network addressing, if provided, is by means of Dual Tone Multi Frequency (DTMF) signaling</p> <p>Business Telecommunications (BTC); 34 Mbit/s digital Unstructured and structured leased lines (D34U and D34S); Attachment requirements for terminal equipment interface</p> <p>Analogue Interworking and Non interference Requirements for Customer Equipment Connected to the Public Switched Telephone Network</p> <p>General Requirements for Customer Equipment Connected to Hierarchical Digital Interfaces</p> <p>Requirements for ISDN Basic Access Interface Requirements for ISDN Primary Rate Access Interface Requirements for Customer Equipment for connection to a metallic loop interface of a Telecommunications Network – Part 2 Broadband</p> <p>Title</p> <p>Safety of information technology equipment including Includes Amendments 1, 2, 3, and 4 electrical business equipment.</p> <p>Safety of information technology equipment, including electrical business equipment.</p> <p>Safety of Information Technology Equipment (UL 1950)</p> <p>Safety of information technology equipment</p> <p>IEC 60950 2000</p> <p>EN 60950 1997, 1998, 2000</p> <p>IEC 60950-1 2001</p> <p>UL 60950-1 2003</p> <p>CSA C22.2 No. 60950-00</p> <p>CSA C22.2 No. 60950-1 03</p> <p>AS/NZS 3260 1993</p> <p>AS/NZS 3260 Supp 1 1996</p> <p>ACA TS 001 1997</p> <p>UL 1459 1995</p> <p>IEC 1010-1 1990</p> <p>61010-1 1993</p> <p>EN 61010-1 1993, 2001</p> <p>61010-1 2001</p> <p>UL 61010B-1 2003</p> <p>UL 3101-1 1993</p> <p>CAN/CSA 1010-1 1999 (<i>Including AM 2</i>)</p> <p>UL 3111-1 1996</p> <p>UL 3121-1 1995</p> <p>IEC 60601-1 1995</p> <p>EN 60601-1 1995 (<i>Including AM 2</i>)</p> <p>UL 2601-1 1997</p> <p>IEC 60065 1998, 2000</p> <p>ANSI/UL 6500: 1998</p> <p>CAN/CSA 60065-00</p> <p>AS/NZS 3250 1995</p> <p>AS/NZS 60065 2000</p> <p>Canadian C22.2 No. 1-94 (1-98)</p> <p>1994, 1998</p> <p>EN 60065 1994</p> <p>IEC 60825 1990</p> <p>and user's guide</p> <p>EN 60825-1 1994</p> <p>IEC 60825-1 2001</p> <p>IEC 60825-2 2000-5</p> <p>IEC 60825-4 1997-11</p> <p>IEC 60335-1 1995</p> <p>(<i>Including AM 2 – 1997 & AM 12 – 1997</i>)</p> <p>EN 60335-1 2001</p> <p>UL 60335-1 1998</p> <p>CAN/CSA E335-1 1994</p> <p>IEC 60335-1 1995</p> <p>Safety of electrical equipment. Part 1: General requirements for electrical equipment for measurement, control and laboratory use - Part 1: General requirements</p> <p>Safety of information technology equipment</p> <p>Approval and test specification – Safety of information technology equipment including electrical business Equipment.</p> <p>Approval and test specification – Safety of information technology equipment including electrical business equipment – Alphabetical reference index to IEC 950 (Supplement to AS/NZS 3260:1993)</p> <p>Australian Communications Authority – Safety requirements for customer</p> <p>Telephone Equipment</p> <p>Safety requirements for electrical equipment for measurement, control IEC and laboratory use, Part 1: General requirements.</p> <p>Safety requirements for electrical equipment for measurement, control IEC and laboratory use, Part 1: General requirements.</p> <p>Electrical equipment for laboratory use Part 1: General requirements.</p> <p>Electrical measuring and test equipment. Part 1: General requirements.</p> <p>Medical electrical equipment. Part 1: General requirements for safety.</p> <p>Medical electrical equipment</p> <p>Medical electrical equipment. Part 1: General Requirements for safety.</p> <p>Audio, video and similar electronic apparatus – Safety requirements</p> <p>Audio/video and musical instrument apparatus for Household, commercial and similar general use</p> <p>Australian/New Zealand Standard – Approval and test Specification – Mains operated electronic and related Equipment for household and similar general use</p> <p>Audio, video and similar electronic equipment. Consumer and commercial products</p> <p>Safety requirements for main operated electronic and related apparatus for household and similar general use.</p> <p>Radation safety of laser products, equipment Classification, requirements</p> <p>Safety of laser products Part 1: equipment Classification, requirements and user's guide.</p> <p>Safety of laser products – Part 2: Safety of optical communication systems</p> <p>Safety of laser products – Part 4: Laser guards</p> <p>Safety of household and similar electrical appliances</p> <p>(<i>Including AM 2 – 1997 & AM 12 – 1997</i>)</p> <p>Part 1: General requirements</p> <p>(A2LA Cert. No. 1627-01) 10/31/03</p> <p>Page 9 of 11</p> <p>(A2LA Cert. No. 1627-01) 10/31/03</p> <p>Page 10 of 11</p> |
| <p>UL 61010A-1 : 2002</p> <p>EN 61010-1 : 2001</p> <p>AS/NZS 60950 : 2000</p> <p>Environmental²</p> <p>Environmental Standards</p> <p>GR-63-CORE</p> <p>ETS 300 019</p> <p>(vibration up to 1000Hz)</p> <p>(A2LA Cert. No. 1627-01) 10/31/03</p> | <p>Electrical equipment for laboratory use; part 1: General requirements</p> <p>Safety requirements for electrical equipment for measurement, control, and laboratory use - Part 1: General requirements</p> <p>Safety information technology equipment</p> <p>Title</p> <p>NEBS Requirements: Physical Protection</p> <p>Environmental conditions and environmental tests For telecommunications equipment</p> <p>(A2LA Cert. No. 1627-01) 10/31/03</p> <p>Page 11 of 11</p> |

² Environmental testing is performed at the satellite facility located at 168 Ayer Rd, Littleton, MA 01460

