

2400MHz Omnidirectional Antenna

Specifications:

- **2400-2500MHz**
- **Gain: 7.4dBi**
- **Length: 19 inches**
- **Weight: 4.7 oz**
- **-3dB Beam-width: 20 degrees**
- **Cross Polar Rejection: 15dB +**
- **Max Power: 50 watts**
- **Max wind survival: 150MPH +**
- **Wind Load: 7.1 sq in**
- **Connector: Integral N-male**
- **Radome: Black UV stabilized fiberglass**
- **Mast mounting hardware optional**
- **Mobile lip mount optional**

Vertical radiation pattern

Elevation pattern at:


2400MHz

2425MHz

2450MHz

2475MHz

2500MHz



NCG Company

**1275 N. Grove St.
Anaheim, CA 92806-2114**

Phone: 800.962.2611

Fax: 714.630.7024

Email: micks@natcommgroup.com

FEATURES:

- **802.11b and 802.11g compatible**
- **Compact gain antenna for point-to-multipoint applications.**
- **Male N-connector for easy installation**
- **BASE or MOBILE use**
- **Heavy duty fiberglass for durability**
- **Weather proof for indoor or outdoor use**
- **MB-100: Mast mount**
- **GR-5N: Mobile lip mount**
- **5D4N: 5/8 inch hole mount**

