

5 FCC §2.1091, §15.407(f) & ISED RSS-102 - RF Exposure

5.1 Applicable Standards

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB 447 498 Section (7.2), "simultaneous transmission of MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on calculated or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum *test separation distance* required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	* (100)	30
1.34-30	824/f	2.19/f	* (180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

Where: f = frequency in MHz

* = Plane-wave equivalent power density

Before equipment certification is granted, the procedure of IC RSS-102 must be followed concerning the exposure of humans to RF field.

According to ISED RSS-102 Issue 5:

Table 4: RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment)				
Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Reference Period (minutes)
0.003-10 ²¹	83	90	-	Instantaneous*
0.1-10	-	0.73/ f	-	6 ^{**}
1.1-10	87/ $f^{0.5}$	-	-	6 ^{**}
10-20	27.46	0.0728	2	6
20-48	58.07/ $f^{0.25}$	0.1540/ $f^{0.25}$	8.944/ $f^{0.5}$	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 $f^{0.3417}$	0.008335 $f^{0.3417}$	0.02619 $f^{0.6834}$	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ $f^{1.2}$
150000-300000	0.158 $f^{0.5}$	4.21 $\times 10^{-4}$ $f^{0.5}$	6.67 $\times 10^{-5}$ f	616000/ $f^{1.2}$

Note: f is frequency in MHz.
* Based on nerve stimulation (NS).
** Based on specific absorption rate (SAR).

5.2 MPE Prediction

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Note: According to MIMOFCC KDB 662911 D02 MIMO with Cross Polarized Antenna v01, Where an FCC rule specifies limits in radiated terms such as EIRP or ERP, the limits apply to the maximum emission that would be observed by a linearly polarized measurement antenna. Therefore, the highest output power from single antenna power was selected to calculate in this section.

5.3 MPE Results

Worst Case: 802.11n40, 2437 MHz

<u>Maximum output power at antenna input terminal (dBm):</u>	<u>25.56</u>
<u>Maximum output power at antenna input terminal (mW):</u>	<u>359.75</u>
<u>Prediction distance (cm):</u>	<u>25</u>
<u>Prediction frequency (MHz):</u>	<u>2437</u>
<u>Maximum Directional Antenna Gain, typical (dBi):</u>	<u>10.4</u>
<u>Maximum Antenna Gain (numeric):</u>	<u>10.96</u>
<u>Power density of prediction frequency at 25.0 cm (mW/cm²):</u>	<u>0.502</u>
<u>FCC MPE limit for uncontrolled exposure at prediction frequency (mW/cm²):</u>	<u>1.0</u>

The device is compliant with the requirement FCC MPE limit for uncontrolled exposure. The maximum power density at the distance of 25cm is 0.502 mW/cm². Limit is 1.0 mW/cm².

5.4 RF exposure evaluation for IC

Worst Case: 802.11n40, 2437 MHz

<u>Maximum output power at antenna input terminal (dBm):</u>	<u>25.56</u>
<u>Maximum output power at antenna input terminal (W):</u>	<u>0.35975</u>
<u>Prediction distance (m):</u>	<u>0.25</u>
<u>Prediction frequency (MHz):</u>	<u>2437</u>
<u>Maximum Directional Antenna Gain, typical (dBi):</u>	<u>10.4</u>
<u>Maximum Antenna Gain (numeric):</u>	<u>10.96</u>
<u>Power density of prediction frequency at 0.25m (W/m²):</u>	<u>5.02</u>
<u>IC MPE limit for uncontrolled exposure at prediction frequency (W/m²):</u>	<u>5.66</u>

The device is compliant with the requirement IC MPE limit for uncontrolled exposure. The maximum power density at the distance of 0.25m is 5.02W/m². Limit is 5.66 W/m².

Note: Maximum Antenna Gain used is based on Combined Antenna Gain calculation for MIMO transmitting usage (i.e. Combined Antenna Gain(dBi) = Single Antenna Gain(dBi) + 10*log(Number of Antennas)). In this case the Combined Antenna Gain is 10.4 dBi = 7.4 dBi +10*log(2).