



# Maximum Permissible Exposure Evaluation

FCC ID: PADWF157

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b).

## EUT Specification

Product Name:	Bike Computer
Trade Mark:	WAHOO FITNESS
Model/Type Reference:	WF157
Listed Model(s):	/
Model Differences:	/
Frequency Band (Operating)	BT: 2402MHz ~ 2480MHz WLAN: 2412MHz ~ 2462MHz U-NII-1: 5180MHz ~ 5240MHz U-NII-2A: 5260MHz ~ 5320MHz U-NII-2C: 5500MHz ~ 5700MHz U-NII-3: 5745MHz ~ 5825MHz ANT+: 2457MHz
Device Category	<input type="checkbox"/> Portable (<5mm separation) <input type="checkbox"/> Mobile (>20cm separation) <input checked="" type="checkbox"/> Fixed (>20cm separation) <input type="checkbox"/> Others _____
Exposure Classification	<input type="checkbox"/> Occupational/Controlled exposure (S=5mW/cm <sup>2</sup> ) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm <sup>2</sup> )
Antenna Diversity	<input type="checkbox"/> Single antenna <input checked="" type="checkbox"/> Multiple antennas <input type="checkbox"/> TX diversity <input type="checkbox"/> RX diversity <input type="checkbox"/> TX/RX diversity
Antenna Gain (Max)	ANT+: 2.4dBi BT: 2.72dBi 2.4G WIFI: 1.83dBi 5G WIFI: 2.5dBi
Evaluation Applied	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation

---

CTC Laboratories, Inc.

Room 101 Building B, No. 7, Lanqing 1st Road, Luhu Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China  
Tel.: (86)755-27521059    Fax: (86)755-27521011    [Http://www.sz-ctc.org.cn](http://www.sz-ctc.org.cn)

TRF No: CTC-TR-066\_A1

For anti-fake verification, please visit the official website of China Inspection And Testing Society : [www.cnca.gov.cn](http://www.cnca.gov.cn)

**Limits for Maximum Permissible Exposure (MPE)**

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minutes)
(A) Limits for Occupational/Controlled Exposure				
300-1500	--	--	F/300	<6
1500-100000	--	--	5	<6
(B) Limits for General Population/Uncontrolled Exposure				
300-1500	--	--	F/1500	<30
1500-100000	--	--	1	<30

**Calculation Method**

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where:

$P_d$  = Power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

$G$  = gain of antenna in linear scale

$\pi = 3.1416$

$R$  = distance between observation point and center of the radiator in cm

$P_d$  limit of MPE is 1mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

$$eirp = pt \times gt = (E \times d)^2 / 30$$

where:

$pt$  = transmitter output power in watts,

$gt$  = numeric gain of the transmitting antenna (unitless),

$E$  = electric field strength in V/m, ---  $10^{(dB_{uV}/m)/20} / 10^6$

$d$  = measurement distance in meters (m), --- 3m

$$\text{So } pt = (E \times d)^2 / (30 \times gt)$$

ANT+ 2457MHz Field strength = 74.38 dBuV/m @3m

Ant gain = 2.4dBi, Ant numeric gain = 1.74

$$\text{So } pt = \{[10^{(74.38/20)}/10^6 \times 3]^2 / (30 \times 1.74)\} \times 1000 \text{ mW} = 0.0047 \text{ mW} = -23.28 \text{ dBm}$$

**Measurement Result**

Mode	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Tune Up Tolerance (dB)	Max. Tune Up Power (dBm)	Power Density at 20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
BLE	2402	2.72	-2.79	±1	-2.00	0.0002	1
WLAN 802.11b	2437	1.83	20.31	±1	21.00	0.0382	1
U-NII-3 802.11a	5825	2.5	17.63	±1	18.50	0.0250	1

The BT and WIFI can transmit simultaneously.

BT Power density at 20cm (mW/cm <sup>2</sup> )	WLAN Power density at 20cm (mW/cm <sup>2</sup> )	Total Power density at 20cm (mW/cm <sup>2</sup> )	Power density Limit (mW/cm <sup>2</sup> )
0.0002	0.0382	0.0384	1

**Note:**

1. Calculate in the worst-case mode.
2. Max. Tune Up Power is declared by manufacturer, and used to calculate.
3. For a more detailed features description, please refer to the RF Test Report.

\*\*\*\*\*THE END\*\*\*\*\*

---

CTC Laboratories, Inc.

Room 101 Building B, No. 7, Lanqing 1st Road, Luhu Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China  
Tel.: (86)755-27521059    Fax: (86)755-27521011    [Http://www.sz-ctc.org.cn](http://www.sz-ctc.org.cn)

TRF No: CTC-TR-066\_A1

For anti-fake verification, please visit the official website of China Inspection And Testing Society : [www.cnca.gov.cn](http://www.cnca.gov.cn)