

## CERTIFICATE OF COMPLIANCE SAR EVALUATION

**Test Lab:**

**CELLTECH RESEARCH INC.**  
 Testing and Engineering Lab  
 1955 Moss Court  
 Kelowna, B.C.  
 Canada V1Y 9L3  
 Phone: 250 - 860-3130  
 Fax: 250 - 860-3110  
 Toll Free: 1-877-545-6287  
 e-mail: [celltech@globuswireless.com](mailto:celltech@globuswireless.com)  
 web site: [www.globuswireless.com](http://www.globuswireless.com)

**Applicant Name:**


**DASSAULT Automatismes & Telecommunications**  
 9, rue Elsa TRIOLET - Z.I. des Gatines - BP 13  
 78 373 PLAISIR Cedex  
 FRANCE  
 Attn: Mr. Olivier POITRENAUD  
 R & D Engineer  
 Tel.: (33) 1 30 81 26 95  
 Fax: (33) 1 30 81 23 45

<b>Trade Name:</b>	<b>ARTEMA US MOBILE</b>
<b>Model No.:</b>	<b>P4432-909</b>
<b>Equipment Type:</b>	<b>E.F.T./P.O.S. Terminal with CDPD Modem Card</b>
<b>Equipment Classification:</b>	<b>Licensed Non-Broadcast Station Transmitter (TNB)</b>
<b>Tx Frequency Range:</b>	<b>824-849 MHz</b>
<b>Rx Frequency Range:</b>	<b>869-894 MHz</b>
<b>Max. RF Output Power:</b>	<b>0.6 Watts (ERP)</b>
<b>FCC Rule Part(s):</b>	<b>2.1093; ET Docket 96.326</b>

This wireless mobile and/or portable device has been shown to be compliant for localized specific absorption rate (SAR) for uncontrolled environment/general exposure limits specified in ANSI/IEEE Std. C95.1-1992 and had been tested in accordance with the measurement procedures specified in ANSI/IEEE Std. C95.3-1999. (See test report).

I attest to the accuracy of data. All measurements were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Celltech Research Inc. certifies that no party to this application has been denied FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 853(a).



**Shawn McMillen**  
**General Manager**  
**Celltech Research Inc.**



## **TABLE OF CONTENTS**

1.0	<b>INTRODUCTION</b> .....	1
2.0	<b>DESCRIPTION OF EUT</b> .....	1
3.0	<b>SAR MEASUREMENT SYSTEM</b> .....	2
4.0	<b>MEASUREMENT SUMMARY</b> .....	3
5.0	<b>SAR LIMITS</b> .....	3
6.0	<b>DETAILS OF SAR EVALUATION</b> .....	4
7.0	<b>EVALUATION PROCEDURES</b> .....	5
8.0	<b>SYSTEM VALIDATION</b> .....	5
9.0	<b>SIMULATED EQUIVALENT TISSUES</b> .....	6
10.0	<b>TISSUE PARAMETERS</b> .....	6
11.0	<b>SYSTEM SPECIFICATIONS</b> .....	7
12.0	<b>TEST EQUIPMENT LIST</b> .....	8
13.0	<b>MEASUREMENT UNCERTAINTIES</b> .....	9
14.0	<b>REFERENCES</b> .....	10
	<b>APPENDIX A - SAR MEASUREMENT DATA</b> .....	11
	<b>APPENDIX B - DIPOLE VALIDATION</b> .....	12
	<b>APPENDIX C - PROBE CALIBRATION</b> .....	13
	<b>APPENDIX D - TEST SETUP PHOTOGRAPHS</b> .....	14

## 1.0 INTRODUCTION

This measurement report shows compliance of the DASSAULT *Artema US Mobile* Model: P4432-909 Portable E.F.T./P.O.S. Terminal with internal CDPD Modem Card with FCC Part 2.1093, ET Docket 96-326 Rules for mobile and portable devices. The test procedures, as described in American National Standards Institute C95.1 - 1992 (1), FCC OET Bulletin 65-1997 were employed. A description of the product and operating configuration, detailed summary of the test results, methodology and procedures used in the evaluation, equipment used, and the various provisions of the rules are included within this test report.

## 2.0 DESCRIPTION of Equipment Under Test (EUT)

<b>EUT Type</b>	Portable E.F.T./P.O.S. Terminal with internal CDPD Modem Card	<b>Equipment Class</b>	Licensed Non-Broadcast Station Transmitter (TNB)
<b>Trade Name</b>	ARTEMA US MOBILE	<b>Model No.</b>	P4432-909
<b>Tx Frequency Range (MHz)</b>	824-849	<b>S/N No.</b>	Pre-production
<b>Rx Frequency Range (MHz)</b>	869-894	<b>Max. RF Output Power</b>	0.6 Watts
<b>Power Supply</b>	Ni-Cad Battery Pack	<b>Signal Modulation(s)</b>	GMSK FM



Fig. 1. Front of EUT



Fig. 2. Rear of EUT



Fig. 3. Antenna Side



Fig. 4. CDPD Modem

### 3.0 SAR MEASUREMENT SYSTEM

Celltech Research SAR measurement facility utilizes the Dosimetric Assessment System (DASY™) manufactured by Schmid & Partner Engineering AG (SPEAG™) of Zurich, Switzerland. The DASY system is comprised of the robot controller, computer, near-field probe, probe alignment sensor, and the generic twin phantom containing brain or muscle equivalent material (see Figure 6). The robot is a six-axis industrial robot performing precise movements to position the probe to the location (points) of maximum electromagnetic field (EMF). A cell controller system contains the power supply, robot controller, teach pendant (Joystick), and remote control, is used to drive the robot motors. The Staubli robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronics (DAE) circuit performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC plug-in card. The DAE3 utilizes a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the PC-card is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe-mounting device includes two different sensor systems for frontal and sidewise probe contacts. They are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer.



Figure 5. DASY3 SAR Measurement System

**4.0 MEASUREMENT SUMMARY**

The measurement results were obtained with the EUT tested in the conditions described in this report. Detailed measurement data and plots showing the maximum SAR location of the EUT are reported in Appendix A.

**Body SAR Measurement Results**

Freq. (MHz)	Chan.	Mode Tested	Max. ERP (W)	EUT Position	Phantom Section	Separation Distance (cm)	SAR (w/kg)
824.04	991	Unmod.	0.6	Front side	Flat	none	<b>0.324</b>
824.04	991	Unmod.	0.6	Back side	Flat	none	<b>1.48</b>
824.04	991	Unmod.	0.6	Antenna side	Flat	0.5	<b>0.872</b>
836.49	383	Unmod.	0.6	Front side	Flat	none	<b>0.233</b>
836.49	383	Unmod.	0.6	Back side	Flat	none	<b>0.995</b>
836.49	383	Unmod.	0.6	Antenna side	Flat	0.5	<b>0.785</b>
848.97	799	Unmod.	0.6	Front side	Flat	none	<b>0.195</b>
848.97	799	Unmod.	0.6	Back side	Flat	none	<b>0.829</b>
848.97	799	Unmod.	0.6	Antenna side	Flat	0.5	<b>0.515</b>
<b>Mixture Type: Muscle</b> <b>Dielectric Constant: 56.1</b> <b>Conductivity: 0.95</b>				<b>ANSI / IEEE C95.1 1992 - SAFETY LIMIT</b> <b>Spatial Peak Uncontrolled Exposure/General Population</b> <b>Body SAR: 1.6 W/kg (averaged over 1 gram)</b>			

Notes:

1. All modes of operation were investigated and the worst-case SAR levels are reported.
2. The SAR values found were below the maximum limit of 1.6 w/kg.
3. The worst-case body SAR value found was 1.48 w/kg.
4. The antenna is integral to the EUT.

**Hand SAR Measurement Results**

<b>Freq. (MHz)</b>	<b>Chan.</b>	<b>Mode Tested</b>	<b>Max. ERP (W)</b>	<b>EUT Position</b>	<b>Phantom Section</b>	<b>Separation Distance (cm)</b>	<b>SAR (w/kg)</b>
824.04	991	Unmod.	0.6	Antenna side	Flat	none	<b>0.955</b>
836.49	383	Unmod.	0.6	Antenna side	Flat	none	<b>0.804</b>
848.97	799	Unmod.	0.6	Antenna side	Flat	none	<b>0.538</b>
<b>Mixture Type: Muscle Dielectric Constant: 56.1 Conductivity: 0.95</b>				<b>ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Hand SAR: 4.0 W/kg (averaged over 10 grams)</b>			

## Notes:

1. All modes of operation were investigated and the worst-case SAR levels are reported.
2. The SAR values found were below the maximum limit of 4.0 w/kg.
3. The worst-case hand SAR value found was 0.955 w/kg.
4. The antenna is integral to the EUT.

***5.0 SAR SAFETY LIMITS***

<b>EXPOSURE LIMITS</b> (General populations/Uncontrolled Exposure Environment)	<b>SAR (W/Kg)</b>
Spatial Average (averaged over the whole body)	0.08
Spatial Peak (averaged over any 1g of tissue)	1.60
Spatial Peak (hands/wrists/feet/ankles averaged over 10g)	4.00

Notes:

1. The FCC SAR safety limits specified in the table above apply to devices operated in the General Population / Uncontrolled Exposure environment.
2. Uncontrolled environments are defined as locations where there is exposure of individuals who have no knowledge or control of their exposure.

## 6.0 DETAILS OF SAR EVALUATION

The DASSAULT *Artema US Mobile* Model: P4432-909 Portable E.F.T./P.O.S. Terminal with internal CDPD Modem Card was found to be compliant for localized specific absorption rate (SAR) based on the following test provisions and conditions:

- 1) The face of the EUT was tested in a body-worn configuration. For the test setup the face of the device was placed parallel to and touching the outer surface of the phantom.
- 2) The bottom side of the EUT was tested in a body-worn configuration. For the test setup the under side of the device was placed parallel to and touching the outer surface of the phantom.
- 3) The antenna side of the EUT was tested in a body-worn configuration. For the test setup the antenna side of the device was placed parallel to the outer surface of the phantom with a 0.5cm separation distance.
- 4) The antenna side of the EUT was tested in a hand-held configuration. For the test setup the antenna side of the device was placed parallel to and touching the outer surface of the phantom.
- 5) SAR measurements were evaluated at maximum power and the unit was operated for an appropriate period prior to the evaluation in order to minimize drift.
- 6) The device was keyed to operate continuously in the transmit mode for the duration of the test.
- 7) The location of the maximum spatial SAR distribution (Hot Spot) was determined relative to the device and its antenna.
- 8) The EUT was tested with a fully charged battery.



Fig. 6. Body SAR - Top Side



Fig. 7. Body SAR – Bottom Side



Fig. 8. Body SAR - Antenna Side (0.5cm)



Fig. 9. Hand SAR – Antenna Side

## 7.0 EVALUATION PROCEDURES

The Specific Absorption Rate (SAR) evaluation was performed in the following manner:

- a. (i) The evaluation was performed in an applicable area of the phantom depending on the type of device being tested. For devices worn about the ear during normal operation, both the left and right ear positions were evaluated at the center frequency of the band at maximum power. The side, which produced the greatest SAR, determined which side of the phantom would be used for the entire evaluation. The positioning of the head worn device relative to the phantom was dictated by FCC OET bulletin 65 Supp., C.  
(ii) For body-worn devices or devices which can be operated within 20cm of the body, the planar section of the phantom was used. The type of device being evaluated dictated the distance of the EUT to the outer surface of the planar phantom.
- b. The SAR was determined by a pre-defined procedure within the DASY3 software. Upon completion of a reference and optical surface check, the exposed region of the phantom was scanned near the inner surface with a grid spacing of 20mm x 20mm.
- c. A 5x5x7 matrix was performed around the greatest spatial SAR distribution found during the area scan of the applicable exposed region. SAR values were then calculated using a 3-D spline interpolation algorithm and averaged over spatial volumes of 1 and 10 grams.
- d. If the EUT had any appreciable drift over the course of the evaluation, then the EUT was re-evaluated. Any unusual anomalies over the course of the test also warranted a re-evaluation.

## 8.0 SYSTEM VALIDATION

Prior to the assessment, the system was verified in the planar region of the phantom. For devices operating below 1GHz, an 835MHz dipole or 900MHz was used, depending on the operating frequency of the EUT. For devices operating above 1GHz, an 1800MHz dipole was used. A forward power of 250mW was applied to the dipole and system was verified to a tolerance of  $\pm 5\%$ . Following the validation, the fluid remained or was changed depending on the particular part of the body being evaluated. The applicable verification(s) is/are as follows (see Appendix B for validation test plot):

Dipole Validation Kit	Target SAR 1g (w/kg)	Measured SAR 1g (w/kg)
D835V2	2.06	2.03

## 9.0 SIMULATED TISSUES

The brain and muscle mixtures consist of a viscous gel using hydroxethylcellulose (HEC) gelling agent and saline solution. Preservation with a bactericide is added and visual inspection is made to ensure air bubbles are not trapped during the mixing process. The mixture is calibrated to obtain proper dielectric constant (permittivity) and conductivity of the tissue.

INGREDIENT	FREQUENCY (835MHz Muscle)
Water	52.4%
Sugar	45.0%
Salt	1.4%
HEC	1.0%
Bactericide	0.2%

## 10.0 TISSUE PARAMETERS

The dielectric parameters of the fluids were verified prior to the SAR evaluation using an 85070C Dielectric Probe Kit and an 8753E Network Analyzer. The dielectric parameters of the fluid are as follows:

Frequency (Muscle)	Dielectric Constant $\epsilon_r$	Conductivity $\sigma$ (mho/m)	$\rho$ (Kg/m <sup>3</sup> )
800-850 MHz	56.1 $\pm$ 5%	0.95 $\pm$ 10%	1000

## ***11.0 ROBOT SYSTEM SPECIFICATIONS***

### **Specifications**

**POSITIONER:** Stäubli Unimation Corp. Robot Model: RX60L  
**Repeatability:** 0.02 mm  
**No. of axis:** 6

### **Data Acquisition Electronic (DAE) System**

#### **Cell Controller**

**Processor:** Pentium III  
**Clock Speed:** 450 MHz  
**Operating System:** Windows NT  
**Data Card:** DASY3 PC-Board

#### **Data Converter**

**Features:** Signal Amplifier, multiplexer, A/D converter, and control logic  
**Software:** DASY3 software  
**Connecting Lines:** Optical downlink for data and status info.  
Optical uplink for commands and clock

### **PC Interface Card**

**Function:** 24 bit (64 MHz) DSP for real time processing  
Link to DAE3  
16 bit A/D converter for surface detection system  
serial link to robot  
direct emergency stop output for robot

### **E-Field Probe**

**Model:** ET3DV6  
**Serial No.:** 1387  
**Construction:** Triangular core fiber optic detection system  
**Frequency:** 10 MHz to 6 GHz  
**Linearity:**  $\pm 0.2$  dB (30 MHz to 3 GHz)

### **Phantom**

**Phantom:** Generic Twin  
**Shell Material:** Fiberglass  
**Thickness:**  $2.0 \pm 0.1$  mm

**12.0 TEST EQUIPMENT LIST**

<b>SAR MEASUREMENT SYSTEM</b>		
<b><u>EQUIPMENT</u></b>	<b><u>S/N #</u></b>	<b><u>CALIBRATION DATE</u></b>
<b>DASY3 System</b> -Robot -ET3DV6 E-Field Probe -DAE -835MHz Validation Dipole -900MHz Validation Dipole -1800MHz Validation Dipole -Generic Twin Phantom V3.0	599396-01 1387 383 411 054 247 N/A	N/A Sept 1999 Sept 1999 Aug 1999 Aug 1999 Aug 1999 N/A
<b>85070C Dielectric Probe Kit</b>	N/A	N/A
<b>Gigatronics 8652A Power Meter</b> -Power Sensor 80701A -Power Sensor 80701A	1835272 1833535 1833542	Oct 1999 Oct 1999 Oct 1999
<b>E4408B Spectrum Analyzer</b>	US39240170	Nov 1999
<b>8594E Spectrum Analyzer</b>	3543A02721	Mar 2000
<b>8753E Network Analyzer</b>	US38433013	Nov 1999
<b>8648D Signal Generator</b>	3847A00611	N/A
<b>5S1G4 Amplifier Research Power Amplifier</b>	26235	N/A

**13.0 MEASUREMENT UNCERTAINTIES**

Uncertainty Description	Error	Distribution	Weight	Standard Deviation	Offset
<b>Probe Uncertainty</b>					
Axial isotropy	±0.2 dB	U-Shaped	0.5	±2.4 %	
Spherical isotropy	±0.4 dB	U-Shaped	0.5	±4.8 %	
Isotropy from gradient	±0.5 dB	U-Shaped	0	±	
Spatial resolution	±0.5 %	Normal	1	±0.5 %	
Linearity error	±0.2 dB	Rectangle	1	±2.7 %	
Calibration error	±3.3 %	Normal	1	±3.3 %	
<b>SAR Evaluation Uncertainty</b>					
Data acquisition error	±1 %	Rectangle	1	±0.6 %	
ELF and RF disturbances	±0.25 %	Normal	1	±0.25 %	
Conductivity assessment	±10 %	Rectangle	1	±5.8 %	
<b>Spatial Peak SAR Evaluation Uncertainty</b>					
Extrapolated boundary effect	±3 %	Normal	1	±3 %	±5 %
Probe positioning error	±0.1 mm	Normal	1	±1 %	
Integrated and cube orientation	±3 %	Normal	1	±3 %	
Cube Shape inaccuracies	±2 %	Rectangle	1	±1.2 %	
Device positioning	±6 %	Normal	1	±6 %	
<b>Combined Uncertainties</b>				±11.7 %	±5 %

Measurement uncertainties in SAR measurements are difficult to quantify due to several variables including biological, physiological, and environmental. However, the estimated measurement uncertainties in SAR are less than 15-25 %.

According to ANSI/IEEE C95.3, the overall uncertainties are difficult to assess and will vary with the type of meter and usage situation. However, accuracy's of ± 1 to 3 dB can be expected in practice, with greater uncertainties in near-field situations and at higher frequencies (shorter wavelengths), or areas where large reflecting objects are present. Under optimum measurement conditions, SAR measurement uncertainties of at least ± 2dB can be expected.

According to CENELEC, typical worst-case uncertainty of field measurements is ± 5 dB. For well-defined modulation characteristics the uncertainty can be reduced to ± 3 dB.

## 14.0 REFERENCES

- (1) ANSI, *ANSI/IEEE C95.1: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3kHz to 300 Ghz*, The Institute of Electrical and Electronics Engineers, Inc., New York, NY 10017, 1992;
- (2) Federal Communications Commission, “Evaluating Compliance with FCC Guidelines for Human Exposure to Radio frequency Electromagnetic Fields”, OET Bulletin 65, FCC, Washington, D.C. 20554, 1997;
- (3) Thomas Schmid, Oliver Egger, and Neils Kuster, “Automated E-field scanning system for dosimetric assessments”, *IEEE Transaction on Microwave Theory and Techniques*, Vol. 44, pp. 105 – 113, January, 1996.
- (4) Niels Kuster, Ralph Kastle, and Thomas Schmid, “Dosimetric evaluation of mobile communications equipment with known precision”, *IEICE Transactions of Communications*, vol. E80-B, no. 5, pp. 645 – 652, May 1997.


***APPENDIX "A" - SAR MEASUREMENT DATA***

# DASSAULT AUTOMATISMES & TELECOMMUNICATIONS

Generic Twin Phantom; Flat Section; Position: (270°,270°);  
Probe: ET3DV6 - SN1387; ConvF(6.43,6.43,6.43); Crest factor: 1.0;  
Muscle 835 MHz:  $\sigma = 0.95 \text{ mho/m}$   $\epsilon_r = 56.1$   $\rho = 1.00 \text{ g/cm}^3$   
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0  
Cube 5x5x7  
**SAR (1g): 0.324 mW/g, SAR (10g): 0.237 mW/g**

**Body SAR**  
**Face Of Unit - 0.0mm Separation**


ARTEMA US MOBILE  
Model No: P4432-909  
Unmodulated Carrier  
Max Power  
Channel 991 [824.04MHz]  
Date Tested: Oct. 24, 2000



# DASSAULT AUTOMATISMES & TELECOMMUNICATIONS

Generic Twin Phantom; Flat Section; Position: (270°,270°);  
Probe: ET3DV6 - SN1387; ConvF(6.43,6.43,6.43); Crest factor: 1.0;  
Muscle 835 MHz:  $\sigma = 0.95 \text{ mho/m}$   $\epsilon_r = 56.1$   $\rho = 1.00 \text{ g/cm}^3$   
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0  
Cube 5x5x7  
**SAR (1g): 1.48 mW/g, SAR (10g): 1.03 mW/g**

**Body SAR**  
**Back Side Of Unit - Separation Distance 0.0mm**  
ARTEMA US MOBILE  
Model No: P4432-909  
Unmodulated Carrier  
Max Power  
Channel 991 [824.04MHz]  
Date Tested: Oct. 24, 2000



# DASSAULT AUTOMATISMES & TELECOMMUNICATIONS

Generic Twin Phantom; Flat Section; Position: (270°,270°);  
Probe: ET3DV6 - SN1387; ConvF(6.43,6.43,6.43); Crest factor: 1.0;  
Muscle 835 MHz:  $\sigma = 0.95 \text{ mho/m}$   $\epsilon_r = 56.1$   $\rho = 1.00 \text{ g/cm}^3$   
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0  
Cube 5x5x7  
**SAR (1g): 0.872 mW/g, SAR (10g): 0.515 mW/g**

## Body SAR

### Antenna Side Of Unit - Separation Distance 5.0mm

ARTEMA US MOBILE


Model No: P4432-909

Unmodulated Carrier

Max Power

Channel 991 [824.04MHz]

Date Tested: Oct. 24, 2000




# DASSAULT AUTOMATISMES & TELECOMMUNICATIONS

Generic Twin Phantom; Flat Section; Position: (270°,270°);  
Probe: ET3DV6 - SN1387; ConvF(6.43,6.43,6.43); Crest factor: 1.0;  
Muscle 835 MHz:  $\sigma = 0.95 \text{ mho/m}$   $\epsilon_r = 56.1$   $\rho = 1.00 \text{ g/cm}^3$   
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0  
Cube 5x5x7  
**SAR (10g): 0.955 mW/g**

## Hand SAR

### Antenna Side Of Unit - Separation Distance 0.0mm


ARTEMA US MOBILE  
Model No: P4432-909  
Unmodulated Carrier  
Max Power  
Channel 991 [824.04MHz]  
Date Tested: Oct. 24, 2000



## DASSAULT AUTOMATISMES & TELECOMMUNICATIONS

Generic Twin Phantom; Flat Section; Position: (270°,270°);  
Probe: ET3DV6 - SN1387; ConvF(6.43,6.43,6.43); Crest factor: 1.0;  
Muscle 835 MHz:  $\sigma = 0.95 \text{ mho/m}$   $\epsilon_r = 56.1$   $\rho = 1.00 \text{ g/cm}^3$   
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0  
Cube 5x5x7  
**SAR (1g): 0.233 mW/g**, SAR (10g): 0.170 mW/g \* Max outside

**Body SAR**  
**Face Of Unit - 0.0mm Separation**  
ARTEMA US MOBILE  
Model No: P4432-909  
Unmodulated Carrier  
Max Power  
Channel 383 [836.49MHz]  
Date Tested: Oct. 24, 2000



# DASSAULT AUTOMATISMES & TELECOMMUNICATIONS

Generic Twin Phantom; Flat Section; Position: (270°,270°);  
Probe: ET3DV6 - SN1387; ConvF(6.43,6.43,6.43); Crest factor: 1.0;  
Muscle 835 MHz:  $\sigma = 0.95 \text{ mho/m}$   $\epsilon_r = 56.1$   $\rho = 1.00 \text{ g/cm}^3$   
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0  
Cube 5x5x7  
**SAR (1g): 0.995 mW/g, SAR (10g): 0.700 mW/g \* Max outside**

## Body SAR Back Side Of Unit - Separation Distance 0.0mm

ARTEMA US MOBILE


Model No: P4432-909

Unmodulated Carrier

Max Power

Channel 383 [836.49MHz]

Date Tested: Oct. 24, 2000



# DASSAULT AUTOMATISMES & TELECOMMUNICATIONS

Generic Twin Phantom; Flat Section; Position: (270°,270°);  
Probe: ET3DV6 - SN1387; ConvF(6.43,6.43,6.43); Crest factor: 1.0;  
Muscle 835 MHz:  $\sigma = 0.95 \text{ mho/m}$   $\epsilon_r = 56.1$   $\rho = 1.00 \text{ g/cm}^3$   
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0  
Cube 5x5x7  
**SAR (1g): 0.785 mW/g, SAR (10g): 0.466 mW/g**

## Body SAR

### Antenna Side Of Unit - Separation Distance 5.0mm

ARTEMA US MOBILE


Model No: P4432-909

Unmodulated Carrier

Max Power

Channel 383 [836.49MHz]

Date Tested: Oct. 24, 2000



# DASSAULT AUTOMATISMES & TELECOMMUNICATIONS

Generic Twin Phantom; Flat Section; Position: (270°,270°);  
Probe: ET3DV6 - SN1387; ConvF(6.43,6.43,6.43); Crest factor: 1.0;  
Muscle 835 MHz:  $\sigma = 0.95 \text{ mho/m}$   $\epsilon_r = 56.1$   $\rho = 1.00 \text{ g/cm}^3$   
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0  
Cube 5x5x7  
**SAR (10g): 0.804 mW/g**

## Hand SAR

### Antenna Side Of Unit - Separation Distance 0.0mm

ARTEMA US MOBILE


Model No: P4432-909

Unmodulated Carrier

Max Power

Channel 383 [836.49MHz]


Date Tested: Oct. 24, 2000



# DASSAULT AUTOMATISMES & TELECOMMUNICATIONS

Generic Twin Phantom; Flat Section; Position: (270°,270°);  
Probe: ET3DV6 - SN1387; ConvF(6.43,6.43,6.43); Crest factor: 1.0;  
Muscle 835 MHz:  $\sigma = 0.95 \text{ mho/m}$   $\epsilon_r = 56.1$   $\rho = 1.00 \text{ g/cm}^3$   
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0  
Cube 5x5x7  
**SAR (1g): 0.195 mW/g, SAR (10g): 0.142 mW/g**


**Body SAR**  
**Face Of Unit - 0.0mm Separation**  
ARTEMA US MOBILE  
Model No: P4432-909  
Unmodulated Carrier  
Max Power  
Channel 799 [848.97MHz]  
Date Tested: Oct. 24, 2000



# DASSAULT AUTOMATISMES & TELECOMMUNICATIONS

Generic Twin Phantom; Flat Section; Position: (270°,270°);  
Probe: ET3DV6 - SN1387; ConvF(6.43,6.43,6.43); Crest factor: 1.0;  
Muscle 835 MHz:  $\sigma = 0.95 \text{ mho/m}$   $\epsilon_r = 56.1$   $\rho = 1.00 \text{ g/cm}^3$   
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0  
Cube 5x5x7  
**SAR (1g): 0.829 mW/g, SAR (10g): 0.584 mW/g**

**Body SAR**  
**Back Side Of Unit - Separation Distance 0.0mm**  
ARTEMA US MOBILE  
Model No: P4432-909  
Unmodulated Carrier  
Max Power  
Channel 799 [848.97MHz]  
Date Tested: Oct. 24, 2000



# DASSAULT AUTOMATISMES & TELECOMMUNICATIONS

Generic Twin Phantom; Flat Section; Position: (270°,270°);  
Probe: ET3DV6 - SN1387; ConvF(6.43,6.43,6.43); Crest factor: 1.0;  
Muscle 835 MHz:  $\sigma = 0.95 \text{ mho/m}$   $\epsilon_r = 56.1$   $\rho = 1.00 \text{ g/cm}^3$   
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0  
Cube 5x5x7  
**SAR (1g): 0.515 mW/g, SAR (10g): 0.305 mW/g**

## Body SAR

### Antenna Side Of Unit - Separation Distance 5.0mm

ARTEMA US MOBILE


Model No: P4432-909

Unmodulated Carrier

Max Power

Channel 799 [848.97MHz]

Date Tested: Oct. 24, 2000



# DASSAULT AUTOMATISMES & TELECOMMUNICATIONS

Generic Twin Phantom; Flat Section; Position: (270°,270°);  
Probe: ET3DV6 - SN1387; ConvF(6.43,6.43,6.43); Crest factor: 1.0;  
Muscle 835 MHz:  $\sigma = 0.95 \text{ mho/m}$   $\epsilon_r = 56.1$   $\rho = 1.00 \text{ g/cm}^3$   
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0  
Cube 5x5x7  
**SAR (10g): 0.538 mW/g**

## Hand SAR

### Antenna Side Of Unit - Separation Distance 0.0mm

ARTEMA US MOBILE


Model No: P4432-909

Unmodulated Carrier

Max Power

Channel 799 [848.97MHz]

Date Tested: Oct. 24, 2000




***APPENDIX "B" – DIPOLE VALIDATION***

## Dipole 835 MHz

Generic Twin Phantom; Flat Section; Position: (90°,90°);  
Probe: ET3DV6 - SN1387; ConvF(6.43,6.43,6.43); Crest factor: 1.0;  
Brain 835 MHz:  $\sigma = 0.80 \text{ mho/m}$   $\epsilon_f = 44.2$   $\rho = 1.00 \text{ g/cm}^3$   
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0  
Cube 5x5x7  
SAR (1g): 2.03 mW/g, SAR (10g): 1.34 mW/g

Validation Date: Oct. 24, 2000



## Validation Dipole D835V2 SN:411, $d = 15\text{mm}$

Frequency: 835 MHz; Antenna Input Power: 250 [mW]


Generic Twin Phantom; Flat Section; Grid Spacing:  $Dx = 20.0$ ,  $Dy = 20.0$ ,  $Dz = 10.0$

Probe: ET3DV5 - SN1342/DAE3; ConvF(5.75,5.75,5.75); Brain 835 MHz:  $\sigma = 0.80 \text{ mho/m}$   $\epsilon_r = 44.2$   $\rho = 1.00 \text{ g/cm}^3$

Cubes (2): Peak: 3.07 mW/g  $\pm 0.05$  dB, SAR (1g): 2.06 mW/g  $\pm 0.05$  dB, SAR (10g): 1.38 mW/g  $\pm 0.05$  dB, (Worst-case extrapolation)

Penetration depth: 13.6 (12.7, 14.8) [mm]

Powerdrift: -0.00 dB



***APPENDIX "C" – PROBE CALIBRATION***

**Schmid & Partner  
Engineering AG**

---

Staffelstrasse 8, 8045 Zurich, Switzerland, Telefon +41 1 280 08 60, Fax +41 1 280 08 64

---

**Probe ET3DV6**

**SN:1387**

Manufactured: September 21, 1999  
Last calibration: September 22, 1999

Calibrated for System DASY3

**DASY3 - Parameters of Probe: ET3DV6 SN:1387****Sensitivity in Free Space**

NormX	<b>1.55</b> $\mu\text{V}/(\text{V}/\text{m})^2$
NormY	<b>1.65</b> $\mu\text{V}/(\text{V}/\text{m})^2$
NormZ	<b>1.64</b> $\mu\text{V}/(\text{V}/\text{m})^2$

**Diode Compression**

DCP X	<b>98</b> mV
DCP Y	<b>98</b> mV
DCP Z	<b>98</b> mV

**Sensitivity in Tissue Simulating Liquid**

**Brain**      **450 MHz**       $e_r = 48 \pm 5\%$        $s = 0.50 \pm 10\% \text{ mho/m}$

ConvF X	<b>6.76</b> extrapolated	Boundary effect:
ConvF Y	<b>6.76</b> extrapolated	Alpha <b>0.30</b>
ConvF Z	<b>6.76</b> extrapolated	Depth <b>2.52</b>

**Brain**      **900 MHz**       $e_r = 42.5 \pm 5\%$        $s = 0.86 \pm 10\% \text{ mho/m}$

ConvF X	<b>6.34</b> $\pm 7\%$ (k=2)	Boundary effect:
ConvF Y	<b>6.34</b> $\pm 7\%$ (k=2)	Alpha <b>0.47</b>
ConvF Z	<b>6.34</b> $\pm 7\%$ (k=2)	Depth <b>2.25</b>

**Brain**      **1500 MHz**       $e_r = 41 \pm 5\%$        $s = 1.32 \pm 10\% \text{ mho/m}$

ConvF X	<b>5.78</b> interpolated	Boundary effect:
ConvF Y	<b>5.78</b> interpolated	Alpha <b>0.69</b>
ConvF Z	<b>5.78</b> interpolated	Depth <b>1.88</b>


**Brain**      **1800 MHz**       $e_r = 41 \pm 5\%$        $s = 1.69 \pm 10\% \text{ mho/m}$

ConvF X	<b>5.50</b> $\pm 7\%$ (k=2)	Boundary effect:
ConvF Y	<b>5.50</b> $\pm 7\%$ (k=2)	Alpha <b>0.81</b>
ConvF Z	<b>5.50</b> $\pm 7\%$ (k=2)	Depth <b>1.70</b>


**Sensor Offset**

Probe Tip to Sensor Center	<b>2.7</b>	mm
Optical Surface Detection	<b>1.6 <math>\pm</math> 0.2</b>	mm


## Receiving Pattern (f), $q = 0^\circ$



## ET3DV6 SN:1387




### Isotropy Error (f), q = 0°





## Frequency Response of E-Field


( TEM-Cell:ifi110, Waveguide R22, R26 )



**Dynamic Range f(SAR<sub>brain</sub>)**  
 ( TEM-Cell:ifi110 )




## Conversion Factor Assessment



## Receiving Pattern (f)

( in brain tissue,  $z = 5 \text{ mm}$  )



CELLTECH RESEARCH INC.

1955 Moss Court, Kelowna,  
B.C. CANADA V1Y 9L3

Test Report S/N: 101700-33DAS

Date(s) of Tests: October 24, 2000

---

***APPENDIX "D" – TEST SETUP PHOTOGRAPHS***

CELLTECH RESEARCH INC.  
1955 Moss Court, Kelowna  
B.C. CANADA V1Y 9L3

Test Report S/N: 101700-33DAS  
Date(s) of Tests: October 24, 2000

**BODY SAR TEST SETUP**  
**Top Side of EUT**  
**(EUT touching phantom surface)**



CELLTECH RESEARCH INC.  
1955 Moss Court, Kelowna  
B.C. CANADA V1Y 9L3

Test Report S/N: 101700-33DAS  
Date(s) of Tests: October 24, 2000

**BODY SAR TEST SETUP**  
**Bottom Side of EUT**  
**(EUT touching phantom surface)**



CELLTECH RESEARCH INC.  
1955 Moss Court, Kelowna  
B.C. CANADA V1Y 9L3

Test Report S/N: 101700-33DAS  
Date(s) of Tests: October 24, 2000

**BODY SAR TEST SETUP**  
**Antenna Side of EUT**  
**(0.5cm separation distance)**



CELLTECH RESEARCH INC.  
1955 Moss Court, Kelowna  
B.C. CANADA V1Y 9L3

Test Report S/N: 101700-33DAS  
Date(s) of Tests: October 24, 2000

**HAND SAR TEST SETUP**  
**Antenna Side of EUT**  
**(EUT touching phantom surface)**

