

## ATTACHMENT

### \* Standalone SAR test exclusion considerations

- Min. transmitting frequency = 2442 MHz
- Min. test separation distance = 5 mm
- Max. Power with tune-up tolerance = 5.18 dBm = 3.30 mW  
(Measured power 4.68 dBm ± 0.5 dB)

Step 1)

SAR Test exclusion thresholds for 100 MHz to 6 GHz at test separation distance  $\leq$  50 mm = **Used**

$[(\text{max.power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}]$

$$= [3.30 / 5] * [\sqrt{2.442}] = 1.031 \leq 3, \text{ for 1g SAR}$$

**Thus, SAR for this device is not required.**

Step 2)

SAR Test exclusion thresholds for 100 MHz to 1500 MHz at test separation distance  $>$  50 mm = **N/A**

$[\text{Threshold at 50 mm in step 1} + (\text{test separation distance} - 50 \text{ mm}) * (\sqrt{f(\text{MHz})} / 150)] \text{ mW}$

Step 3)

SAR Test exclusion thresholds for 1500 MHz to 6 GHz at test separation distance  $>$  50 mm = **N/A**

$[\text{Threshold at 50 mm in step 1} + (\text{test separation distance} - 50 \text{ mm}) * 10] \text{ mW}$