



A D T

RF EXPOSURE REPORT

REPORT NO.: SA991207C23

MODEL NO.: LM-WM860A

FCC ID: PD5-LMWM860A

ACCORDING: FCC Guidelines for Human Exposure
IEEE C95.1

APPLICANT: Delta Networks, Inc.

ADDRESS: 252, Shang Ying Road, Kuei San Taoyuan Shien
333, Taiwan, R.O.C.

ISSUED BY: Bureau Veritas Consumer Products Services
(H.K.) Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou
Hsiang, Taipei Hsien 244, Taiwan, R.O.C.



A D T

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
Original release	NA	Dec. 20, 2010



A D T

1. RF EXPOSURE LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

2. MPE CALCULATION FORMULA

$$Pd = (Pout \cdot G) / (4 \cdot \pi \cdot r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

3. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.



A D T

4. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

MODULATION MODE	FREQUENCY BAND (MHz)	MAX CONDUCTED POWER (dBm)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
802.11b	2412-2462	22.5	3.01	20	0.071	1
802.11g	2412-2462	28.7	3.01	20	0.295	1
802.11n (20MHz)	2412-2462	28.7	0	20	0.147	1
802.11n (40MHz)	2422-2452	27.9	0	20	0.123	1

NOTE:

(802.11 b/g): Directional gain =0dBi + 10log(2)=3.01dBi