

MPE Calculations

Systems operating under the provision of 47 CFR 1.1307(b)(1) shall be operated in a manor that ensures that the public is not exposed to radio frequency energy levels in excess of the FCC guidelines.

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user or nearby persons and can therefore be considered a mobile transmitter per 47 CFR 2.1091(b). The MPE calculation for this exposure is shown below.

Using the Antennas with highest output power: Shanghai Universe Communication Electron Co., Ltd Antennas

The peak radiated output power (EIRP) is calculated as follows:

Antenna	Frequency (GHz)	Power input to the antenna (P) (dBm)	Power gain of the antenna (G) (dBi)	EIRP (P+G) (dBm)	EIRP Log ^{-1(dBm/10)} (mW)
WiFi (Chain A)	2.4	22.97	3.24	26.21	417.83
WiFi (Chain A)	5	23.99	4.97	28.96	787.05
WiFi (Chain B)	2.4	22.84	3.24	26.08	405.51
WiFi (Chain B)	5	23.95	4.97	28.92	779.83
WiFi (Chain C)	2.4	23.24	3.24	26.48	444.63
WiFi (Chain C)	5	24.94	4.97	29.91	979.49
WiMax (Chain A)	2.5	23.25	3.47	26.72	469.89

$$\text{EIRP} = P + G$$

Where

P = Power input to the antenna (mW).

G = Power gain of the antenna (dBi)

The numeric gain (G) of the antenna with a gain specified in dB is determined by:

Antenna	Frequency (GHz)	Antenna Gain (G) (dBi)	Numeric Antenna Gain Log ^{-1(dBm/10)} (dB)
WiFi (Chain A)	2.4	3.24	2.11
WiFi (Chain A)	5	4.97	3.14
WiFi (Chain B)	2.4	3.24	2.11
WiFi (Chain B)	5	4.97	3.14
WiFi (Chain C)	2.4	3.24	2.11
WiFi (Chain C)	5	4.97	3.14
WiMax (Chain A)	2.5	3.47	2.22

$$G = \text{Log}^{-1}(\text{dB antenna gain}/10)$$

Power density at the specific separation:

Antenna	Frequency (GHz)	Power input to the antenna (P) (mW)	Numeric Power Gain of the Antenna (G) (dB)	Maximum Power Spectral Density $S=PG/(4R^2\pi)$ (mW/cm ²)	Maximum Power Spectral Density Limit (mW/cm ²)
WiFi (Chain A)	2.4	198.15	2.11	0.083	1.00
WiFi (Chain A)	5	250.61	3.14	0.157	1.00
WiFi (Chain B)	2.4	192.31	2.11	0.081	1.00
WiFi (Chain B)	5	248.31	3.14	0.155	1.00
WiFi (Chain C)	2.4	210.86	2.11	0.088	1.00
WiFi (Chain C)	5	311.89	3.14	0.195	1.00
WiMax (Chain A)	2.5	211.35	2.22	0.093	1.00

$$S = PG/(4R^2\pi)$$

Where

S = Maximum power density (mW/cm²)

P = Power input to the antenna (mW).

G = Numeric power gain of the antenna

R = Distance to the center of the radiation of the antenna (20cm = limit for MPE)

The maximum permissible exposure (MPE) for the general population is 1mW/cm².

The power density at 20cm does not exceed the 1mW/cm² limit. Therefore, the exposure condition is compliant with FCC rules.

Aggregate Maximum Power Spectral Density:

Antenna	Frequency (GHz)	Maximum Power Spectral Density Chain A (dBi)	Maximum Power Spectral Density Chain B (dBi)	Maximum Power Spectral Density Chain C (dBi)	Maximum Power Spectral Density Aggregate Chain A, B, & C (dBi)	Maximum Power Spectral Density Limit (mW/cm ²)
WiFi	2.4	0.083	0.081	0.088	0.084	1.00
WiFi	5	0.157	0.155	0.195	0.169	1.00

Note: WiMax only transmits from chain A so no aggregate measurements are required.