



June 12, 2013

Federal Communications Commission
7435 Oakland Mills Road
Columbia, Maryland 21046
USA

Subject: FCC ID: PD97260H (original issue granted 04/04/2013)
Model 7260HMW Wireless Network Card

Gentlemen:

Please be advised that the Model 7260HMW Wireless LAN mini-PCIe card is manufactured for the global market but when marketed in the U.S. under FCC ID PD97260H the non-volatile memory (NVM) will be programmed at the factory to only actively scan and operate on these specific channels during normal WLAN operation. During Wi-Fi Direct mode the device may act as a group owner (GO) to establish a peer-to-peer (P2P) network including conditions when no master device is present on these specific channels.

Worldwide sku:

Channels 1-11, 2412-2462MHz 802.11b mode
Channels 1-11, 2412-2462MHz 802.11g mode
Channels 1-11, 2412-2462MHz 802.11n mode (20MHz channel)
Channels 3-9, 2422-2452MHz 802.11n mode (40MHz channel)

MoW2 sku :

Channels 1-11, 2412-2462MHz 802.11b mode
Channels 1-11, 2412-2462MHz 802.11g mode
Channels 1-11, 2412-2462MHz 802.11n mode (20MHz channel)
Channels 3-9, 2422-2452MHz 802.11n mode (40MHz channel)
Channels 149-161, 5745-5805 802.11a mode *
Channels 149-161, 5745-5805MHz 802.11n mode (20 MHz channel) *
Channels 149-161, 5745-5805MHz 802.11ac mode (20 MHz channel) *
Channels 151-159, 5755-5795 802.11n mode (40MHz channel) *
Channels 151-159, 5755-5795 802.11ac mode (40MHz channel) *
Channel 155, 5775MHz 802.11ac mode (80MHz channel) *

* When operating in Wi-Fi Direct mode on these non-DFS channels, it may operate as a P2P client device or GO to establish a P2P network if, and only if, a master device is present and network communication is maintained between a master device and the GO.

Intel Mobile Communications
100 Center Point Circle
Columbia, South Carolina 29210
USA



The following dynamic frequency selection (DFS) channels will be programmed at the factory to passively scan and will only listen for a master device and cannot send a probe request to initiate communication on these DFS channels. Accordingly passive scanning provides protection for TDWR operations and preventing transmission in the 5600MHz – 5650MHz frequency band. Client software and drivers will never enable the device to act as a master or GO for operation in DFS frequency bands and therefore ad-hoc mode is always disabled on these passive scan DFS channels.

Worldwide/MoW2 sku :

Channels 52-64, 5260-5320MHz 802.11a mode
Channels 52-64, 5260-5320MHz 802.11n mode (20 MHz channel)
Channels 52-64, 5260-5320MHz 802.11ac mode (20 MHz channel)
Channels 54-62, 5270-5310MHz 802.11n mode (40MHz channel)
Channels 54-62, 5270-5310MHz 802.11ac mode (40MHz channel)
Channel 58, 5290MHz 802.11ac mode (80MHz channel)
Channels 100-140, 5500-5700MHz 802.11a mode
Channels 100-140, 5500-5700MHz 802.11n mode (20 MHz channel)
Channels 100-144, 5500-5720MHz 802.11ac mode (20 MHz channel)
Channels 102-134, 5510-5670MHz 802.11n mode (40MHz channel)
Channels 102-142, 5510-5710MHz 802.11ac mode (40MHz channel)
Channels 106 & 138, 5540 & 5690MHz 802.11ac mode (80MHz channel)

This device meets the requirements of FCC Part 15.202 and accordingly the following non-DFS channels will be programmed at the factory to passively scan and will only listen for a master device and cannot send a probe request to initiate communication during normal WLAN operation. When operating in Wi-Fi Direct mode these non-DFS channels may operate as a P2P client device or GO to establish a P2P network if, and only if, a master device is present and network communication is maintained between a master device and the GO.

Worldwide sku:

Channels 12 & 13, 2467 & 2472MHz 802.11b mode
Channels 12 & 13, 2467 & 2472MHz 802.11g mode
Channels 12 & 13, 2467 & 2472MHz 802.11n mode (20MHz channel)
Channels 10 & 11, 2457 & 2462MHz 802.11n mode (40MHz channel)
Channels 36-48, 5180-5240MHz 802.11a mode
Channels 36-48, 5180-5240MHz 802.11n mode (20 MHz channel)
Channels 36-48, 5180-5240MHz 802.11ac mode (20 MHz channel)
Channels 38-46, 5190-5230MHz 802.11n mode (40MHz channel)
Channels 38-46, 5190-5230MHz 802.11ac mode (40MHz channel)
Channel 42, 5210MHz 802.11ac mode (80MHz channel)
Channels 149-165, 5745-5825 802.11a mode
Channels 149-165, 5745-5825MHz 802.11n mode (20 MHz channel)
Channels 149-165, 5745-5825MHz 802.11ac mode (20 MHz channel)



Channels 151-159, 5755-5795 802.11n mode (40MHz channel)
Channels 151-159, 5755-5795MHz 802.11ac mode (40MHz channel)
Channel 155, 5775MHz 802.11ac mode (80MHz channel)

MoW2 sku :

Channels 12 & 13, 2467 & 2472MHz 802.11b mode
Channels 12 & 13, 2467 & 2472MHz 802.11g mode
Channels 12 & 13, 2467 & 2472MHz 802.11n mode (20MHz channel)
Channels 10 & 11, 2457 & 2462MHz 802.11n mode (40MHz channel)
Channels 36-48, 5180-5240MHz 802.11a mode
Channels 36-48, 5180-5240MHz 802.11n mode (20 MHz channel)
Channels 36-48, 5180-5240MHz 802.11ac mode (20 MHz channel)
Channels 38-46, 5190-5230MHz 802.11n mode (40MHz channel)
Channels 38-46, 5190-5230MHz 802.11ac mode (40MHz channel)
Channel 42, 5210MHz 802.11ac mode (80MHz channel)
Channel 165, 5825MHz 802.11a mode
Channel 165, 5825MHz 802.11n mode (20 MHz channel)
Channel 165, 5825MHz 802.11ac mode (20 MHz channel)

This information when programmed into the NVM will not be accessible and can not be changed by the end user. The transmitter is approved as a non-software defined radio and OEMs and third party system integrators do not have the ability through software to allow configuration controls that would permit the device to operate outside the grant conditions per FCC KDB 594280.

Sincerely,

Steven C. Hackett
Product Regulations Engineer
Wireless Platforms R&D
TEL: 803-216-2344
CELL: 803-315-6704
steven.c.hackett@intel.com