

**FCC LISTED, REGISTRATION
NUMBER: 905266**

**IC LISTED REGISTRATION NUMBER
IC 4621A-1**

AT4 wireless, S.A.

Parque Tecnológico de Andalucía,
c/ Severo Ochoa nº 2

29590 Campanillas/ Málaga/ España

Tel. 952 61 91 00 - Fax 952 61 91 13

MÁLAGA, C.I.F. A29 507 456

Registro Mercantil de Málaga, Tomo 1169,

Libro 82, Folio 133, Hoja MA3729

TEST REPORT (MODIFICATION 1)

REFERENCE STANDARD:

USA FCC Part 15.247, 15.209

CANADA RSS-210, RSS-Gen

Radio Frequency Devices. Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz, and 5725 - 5850 MHz.

Licence-Exempt Radio Apparatus (All Frequency Bands): Category I Equipment.

General Requirements and Information for the Certification of Radio Apparatus.

MIE : 38067RRF.001A1

Approved by
(name / position & signature) : A. Llamas / RF Lab. Manager

Elaboration date : 2013-03-15

Identification of item tested : 7260HMW

Brand name : INTEL

Model and/or type reference : 7260HMW

Serial number : TA#: G83347-004

WF MAC: 001500B666C9

BD MAC: 001500B666CD

Other identification of the product : Commercial name: 7260HMW

HW version: QS

SW version: Intel Pro Set V16

For OEM factory installation:

FCC ID: PD97260H

IC: 1000M-7260H

For user installation:

FCC ID: PD97260HU

IC: 1000M-7260H

Features : No provided data

Description : 802.11a/b/g/n/ac wireless LAN + BT PCIe half-mini card

Applicant : INTEL CORPORTATION

Address : 100 Center Point Circle, Suite 200, Columbia, South Carolina 29210 USA

CIF/NIF/Passport : No provided data

Contact person: Steven Hackett

Telephone / Fax : Tel: 803-216-2344/ FAX: 803-216-2176

e-mail: : steven.c.hackett@intel.com

Test samples supplier	Same as applicant
Manufacturer	Same as applicant

Test method requested	See Standard																																																																																																																
Standard	USA FCC Part 15.247 10-01-10 Edition: Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz, and 5725 - 5850 MHz.																																																																																																																
	USA FCC Part 15.209 10-01-10 Edition: Radiated emission limits; general requirements.																																																																																																																
	CANADA RSS-210 Issue 8 (December 2010).																																																																																																																
	CANADA RSS-Gen Issue 3 (December 2010).																																																																																																																
	FCC part 15.247 and Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum System DA 00-705 Released March 30, 2000.																																																																																																																
	ANSI C63.10-2009: American National Standard for Testing Unlicensed Wireless Devices.																																																																																																																
Test procedure	PERF010																																																																																																																
Non-standardized test method	N/A																																																																																																																
Used instrumentation	<u>Conducted Measurements</u> <table border="0"> <thead> <tr> <th></th> <th></th> <th></th> <th></th> <th></th> <th>Last Cal. date</th> <th>Cal. due date</th> </tr> </thead> <tbody> <tr> <td>1.</td> <td>Spectrum analyser</td> <td>Agilent</td> <td>PSA</td> <td>E4440A</td> <td>2012/02</td> <td>2014/02</td> </tr> </tbody> </table> <u>Radiated Measurements</u> <table border="0"> <thead> <tr> <th></th> <th></th> <th></th> <th></th> <th></th> <th>Last Cal. date</th> <th>Cal. due date</th> </tr> </thead> <tbody> <tr> <td>1.</td> <td>Semianechoic Absorber Lined Chamber</td> <td></td> <td></td> <td>IR 11. BS</td> <td>N.A.</td> <td>N.A.</td> </tr> <tr> <td>2.</td> <td>Control Chamber</td> <td></td> <td></td> <td>IR 12.BC</td> <td>N.A.</td> <td>N.A.</td> </tr> <tr> <td>3.</td> <td>Hybrid Bilog antenna</td> <td>Sunol Sciences Corporation</td> <td></td> <td>JB6</td> <td>2011/05</td> <td>2014/05</td> </tr> <tr> <td>4.</td> <td>Antenna mast</td> <td></td> <td></td> <td>EM 1072 NMT</td> <td>N.A.</td> <td>N.A.</td> </tr> <tr> <td>5.</td> <td>Rotating table</td> <td></td> <td></td> <td>EM 1084-4. ON</td> <td>N.A.</td> <td>N.A.</td> </tr> <tr> <td>6.</td> <td>Double-ridge Guide Horn antenna</td> <td></td> <td></td> <td>1-18 GHz HP 11966E</td> <td>2011/05</td> <td>2014/05</td> </tr> <tr> <td>7.</td> <td>Double-ridge Guide Horn antenna</td> <td></td> <td></td> <td>18-40 GHz Agilent 119665J</td> <td>2011/09</td> <td>2014/09</td> </tr> <tr> <td>8.</td> <td>EMI Test Receiver</td> <td>R&S</td> <td></td> <td>ESIB26</td> <td>2011/11</td> <td>2013/11</td> </tr> <tr> <td>9.</td> <td>RF pre-amplifier</td> <td>Miteq</td> <td></td> <td>JS4-12002600-30-5A.</td> <td>2012/07</td> <td>2014/07</td> </tr> <tr> <td>10.</td> <td>Multi Device Controller</td> <td>EMCO</td> <td></td> <td>2090</td> <td>N.A.</td> <td>N.A.</td> </tr> <tr> <td>11.</td> <td>Spectrum Analyzer</td> <td>Agilent</td> <td></td> <td>E4440A</td> <td>2012/02</td> <td>2014/02</td> </tr> <tr> <td>12.</td> <td>RF pre-amplifier</td> <td>Miteq</td> <td></td> <td>AFS5-04001300-15-10P-6.</td> <td>2012/07</td> <td>2014/07</td> </tr> <tr> <td>13.</td> <td>RF pre-amplifier</td> <td>Schaffner</td> <td></td> <td>CPA 9231A.</td> <td>2011/06</td> <td>2013/06</td> </tr> </tbody> </table>						Last Cal. date	Cal. due date	1.	Spectrum analyser	Agilent	PSA	E4440A	2012/02	2014/02						Last Cal. date	Cal. due date	1.	Semianechoic Absorber Lined Chamber			IR 11. BS	N.A.	N.A.	2.	Control Chamber			IR 12.BC	N.A.	N.A.	3.	Hybrid Bilog antenna	Sunol Sciences Corporation		JB6	2011/05	2014/05	4.	Antenna mast			EM 1072 NMT	N.A.	N.A.	5.	Rotating table			EM 1084-4. ON	N.A.	N.A.	6.	Double-ridge Guide Horn antenna			1-18 GHz HP 11966E	2011/05	2014/05	7.	Double-ridge Guide Horn antenna			18-40 GHz Agilent 119665J	2011/09	2014/09	8.	EMI Test Receiver	R&S		ESIB26	2011/11	2013/11	9.	RF pre-amplifier	Miteq		JS4-12002600-30-5A.	2012/07	2014/07	10.	Multi Device Controller	EMCO		2090	N.A.	N.A.	11.	Spectrum Analyzer	Agilent		E4440A	2012/02	2014/02	12.	RF pre-amplifier	Miteq		AFS5-04001300-15-10P-6.	2012/07	2014/07	13.	RF pre-amplifier	Schaffner		CPA 9231A.	2011/06	2013/06
					Last Cal. date	Cal. due date																																																																																																											
1.	Spectrum analyser	Agilent	PSA	E4440A	2012/02	2014/02																																																																																																											
					Last Cal. date	Cal. due date																																																																																																											
1.	Semianechoic Absorber Lined Chamber			IR 11. BS	N.A.	N.A.																																																																																																											
2.	Control Chamber			IR 12.BC	N.A.	N.A.																																																																																																											
3.	Hybrid Bilog antenna	Sunol Sciences Corporation		JB6	2011/05	2014/05																																																																																																											
4.	Antenna mast			EM 1072 NMT	N.A.	N.A.																																																																																																											
5.	Rotating table			EM 1084-4. ON	N.A.	N.A.																																																																																																											
6.	Double-ridge Guide Horn antenna			1-18 GHz HP 11966E	2011/05	2014/05																																																																																																											
7.	Double-ridge Guide Horn antenna			18-40 GHz Agilent 119665J	2011/09	2014/09																																																																																																											
8.	EMI Test Receiver	R&S		ESIB26	2011/11	2013/11																																																																																																											
9.	RF pre-amplifier	Miteq		JS4-12002600-30-5A.	2012/07	2014/07																																																																																																											
10.	Multi Device Controller	EMCO		2090	N.A.	N.A.																																																																																																											
11.	Spectrum Analyzer	Agilent		E4440A	2012/02	2014/02																																																																																																											
12.	RF pre-amplifier	Miteq		AFS5-04001300-15-10P-6.	2012/07	2014/07																																																																																																											
13.	RF pre-amplifier	Schaffner		CPA 9231A.	2011/06	2013/06																																																																																																											
Report template No.	FDT11_14																																																																																																																
IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of AT4 wireless, S.A.																																																																																																																	

INDEX

Competences and guarantees	5
General conditions	5
Uncertainty	5
Usage of samples.....	6
Usage of samples.....	7
Testing period	7
Environmental conditions	8
Modifications to the reference test report	9
Summary	9
Remarks and comments	9
Testing verdicts	9
APPENDIX A: Test result	10

Competences and guarantees

AT4 wireless is a laboratory with a measurement facility in compliance with the requirements of Section 2.948 of the FCC rules and has been added to the list of facilities whose measurements data will be accepted in conjunction with applications for Certification under Parts 15 or 18 of the Commission's Rules. Registration Number: 905266.

AT4 wireless is a laboratory with a measurement site in compliance with the requirements of RSS 212, Issue 1 (Provisional) and has been added to the list of filed sites of the Canadian Certification and Engineering Bureau. Reference File Number: IC 4621A-1.

In order to assure the traceability to other national and international laboratories, AT4 wireless has a calibration and maintenance programme for its measurement equipment.

AT4 wireless guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at AT4 wireless at the time of performance of the test.

AT4 wireless is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

General conditions

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of AT4 wireless.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of AT4 wireless and the Accreditation Bodies.

Uncertainty

Uncertainty (factor $k=2$) was calculated according to the AT4 wireless internal document:

PODT000: Procedimiento para el cálculo de incertidumbres de medida.

Usage of samples

Samples undergoing test have been selected by: **the client**.

Sample S/01 is composed of the following elements:

<u>Control N°</u>	<u>Description</u>	<u>Model</u>	<u>Serial N°</u>	<u>Date of reception</u>
38067/33	802.11a/b/g/n/ac wireless LAN + BT PCIe half-mini card	7260HMW	TA#: G83347-004 WFMAC:001500B666C9 BDMAC:001500B666CD	08/01/2013

Auxiliary elements used with the sample S/01:

<u>Control N°</u>	<u>Description</u>	<u>Manufacture</u>	<u>Model</u>	<u>Serial N°</u>	<u>Date of reception</u>
38067/28	Laptop PC	DELL	Latitude E5420	CTFQQL1	08/01/2013
38067/29	Cable of the AC/DC Adapter	DELL	---	---	08/01/2013
38067/30	AC/DC Adapter	DELL	LA90PM111	---	08/01/2013
38067/34	Reference Antenna	Universe	WIMAX/WLAN	---	08/01/2013
38067/35	Reference Antenna	Universe	WIMAX/WLAN	---	08/01/2013
38067/36	M2/NGFF extender cable	---	---	---	08/01/2013
38067/37	HMC/NGFF Testing board	INTEL	PCB00390	3902412-252	11/01/2013
38067/38	Adapter of the AC/DC Board Testing	SINPRO	SPU60-102	07990464 1249	11/01/2013
1302	Board 35mmx35mm	---	---	---	---
---	USB cable	---	---	---	---

Usage of samples

Sample S/02 is composed of the following elements:

<u>Control N°</u>	<u>Description</u>	<u>Model</u>	<u>Serial N°</u>	<u>Date of reception</u>
38067/33	802.11a/b/g/n/ac wireless LAN + BT PCIe half-mini card	7260HWMW	TA#: G83347-004 WFMAC:001500B666C9 BDMAC:001500B666CD	08/01/2013

Auxiliary elements used with the sample S/02:

<u>Control N°</u>	<u>Description</u>	<u>Manufacture</u>	<u>Model</u>	<u>Serial N°</u>	<u>Date of reception</u>
38067/28	Laptop PC	DELL	Latitude E5420	CTFQQL1	08/01/2013
38067/29	Cable of the AC/DC Adapter	DELL	---	---	08/01/2013
38067/30	AC/DC Adapter	DELL	LA90PM111	---	08/01/2013
38067/36	M2/NGFF extender cable	---	---	---	08/01/2013
38067/37	HMC/NGFF Testing board	INTEL	PCB00390	3902412-252	11/01/2013
38067/38	Adapter of the AC/DC Board Testing	SINPRO	SPU60-102	07990464 1249	11/01/2013
---	USB cable	---	---	---	---

1. Sample S/01 has undergone following test(s).
All radiated tests indicated in appendix A.
2. Sample S/02 has undergone following test(s).
All conducted tests indicated in appendix A.

Testing period

The performed test started on 2013-01-09 and finished on 2013-01-14.

The tests have been performed at AT4 wireless.

Environmental conditions

In the control chamber, the following limits were not exceeded during the test:

Temperature	Min. = 22.8 °C Max. = 23.1 °C
Relative humidity	Min. = 46.8 % Max. = 47.3 %
Shielding effectiveness	> 100 dB
Electric insulation	> 10 kΩ
Reference resistance to earth	< 0,5 Ω

In the semianechoic chamber (21 meters x 11 meters x 8 meters), the following limits were not exceeded during the test.

Temperature	Min. = 19.8 °C Max. = 20.1 °C
Relative humidity	Min. = 50 % Max. = 52 %
Air pressure	Min. = 1019 mbar Max. = 1019 mbar
Shielding effectiveness	> 100 dB
Electric insulation	> 10 kΩ
Reference resistance to earth	< 0,5 Ω
Normal site attenuation (NSA)	< ±4 dB at 10 m distance between item under test and receiver antenna, (30 MHz to 1000 MHz)
Field homogeneity	More than 75% of illuminated surface is between 0 and 6 dB (26 MHz to 1000 MHz).

In the chamber for conducted measurements the following limits were not exceeded during the test:

Temperature	Min. = 24.6 °C Max. = 25.3 °C
Relative humidity	Min. = 40.2 % Max. = 41.3 %
Air pressure	Min. = 1020 mbar Max. = 1020 mbar
Shielding effectiveness	> 100 dB
Electric insulation	> 10 kΩ
Reference resistance to earth	< 0,5 Ω

Modifications to the reference test report

It was introduced the following modifications in respect to the test report number 38067RRF.001 related with the same samples, in the next clauses and sub-clauses:

CLAUSES / SUB-CLAUSES	MODIFICATION	JUSTIFICATION
Appendix A. TEST CONDITIONS	Deletion of wrong reference to standard ANSI C63.4-2009	Typo in report

Summary

Considering the results of the performed test according to standard USA FCC Parts 15.247 and 15.209 / Canada RSS-210, the item under test is **IN COMPLIANCE** with the requested specifications specified in the standard.

NOTE: The results presented in this Test Report apply only to the particular item under test established in page 1 of this document, as presented for test on the date(s) shown in section, "USAGE OF SAMPLES, TESTING PERIOD AND ENVIRONMENTAL CONDITIONS".

Remarks and comments

1.- No comments.

Testing verdicts

Not applicable: NA

Pass.....: P

Fail: F

Not measured.....: NM

FCC PART 15 / RSS-210 PARAGRAPH	VERDICT			
	NA	P	F	NM
FCC 15.247 Subclause (a) (1). 20 dB Bandwidth and Carrier frequency separation / RSS-210 Clause A8.1 (b)		P		
FCC 15.247 Subclause (a) (1) (iii). Number of hopping channels / RSS-210 Clause A8.1 (d)		P		
FCC 15.247 Subclause (a) (1) (iii). Time of occupancy (Dwell Time) / RSS-210 Clause A8.1 (d)		P		
FCC 15.247 Subclause (b). Maximum peak output power (radiated) and antenna gain / RSS-210, Clause A8.4 (2)		P		
FCC 15.247 Subclause (c). Band-edge of radiated emissions (Transmitter) / RSS-210 Clauses 2.2 & A8.5		P		
FCC 15.247 Subclause (c). Emission limitations conducted (Transmitter) / RSS-210 Clauses 2.2 & A8.5		P		
FCC 15.247 Subclause (c). Emission limitations radiated (Transmitter) / RSS-210 Clauses 2.2 & A8.5		P		

APPENDIX A: Test result

INDEX

TEST CONDITIONS	12
FCC Section 15.247 Subclause (a) (1) / RSS-210 Clause A8.1 (b). 20 dB Bandwidth and Carrier frequency separation	13
FCC Section 15.247 Subclause (a) (1) (iii) / RSS-210 Clause A8.1 (d). Number of hopping channels.....	20
FCC Section 15.247 Subclause (a) (1) (iii) / RSS-210 Clause A8.1 (d). Time of occupancy (Dwell Time).....	26
FCC Section 15.247 Subclause (b) / RSS-210 Clause A8.4 (2). Maximum peak output power and antenna gain.....	35
FCC Section 15.247 Subclause (d) / RSS-210 Clauses 2.2 & A8.5. Band-edge compliance of conducted emissions (Transmitter).....	41
FCC Section 15.247 Subclause (d) / RSS-210 Clauses 2.2 & A8.5. Band-edge compliance of radiated emissions (Transmitter).....	48
FCC Section 15.247 Subclause (d) / RSS-210 Clause A8.5. Emission limitations conducted (Transmitter)	58
FCC Section 15.247 Subclause (d) / RSS-210 Clauses 2.2. & A8.5. Emission limitations radiated (Transmitter)	64

TEST CONDITIONS

Power supply (V):

$$V_{\text{nominal}} = 3.3 \text{ Vdc}$$

Type of power supply = DC voltage from HMC/NGFF Testing board.

Type of antenna = External attachable PIFA antenna.

Declared Gain for antenna (maximum) = 3 dBi

TEST FREQUENCIES:

Lowest channel: 2402 MHz

Middle channel: 2441 MHz

Highest channel: 2480 MHz

For Bluetooth Basic and EDR operational modes the transmission is at CHAIN B RF output.

For radio testing purposes the card was installed in a test fixture. The test fixture is connected to a laptop computer and dc power supplied. The laptop computer was used to configure the EUT to continuously transmit at a specified output power with different modes and modulation schemes.

CONDUCTED MEASUREMENTS

The equipment under test was set up in a shielded room and it is connected to the spectrum analyzer using a low loss RF cable. The reading in the spectrum analyser is corrected taking into account the cable loss.

RADIATED MEASUREMENTS

All radiated tests were performed in a semi-anechoic chamber. The measurement antenna is situated at a distance of 3 m for the frequency range 30 MHz-1000 MHz (30 MHz-1000 MHz Bilog antenna) and at a distance of 1m for the frequency range 1 GHz-25 GHz (1 GHz-18 GHz Double ridge horn antenna and 18 GHz-40 GHz horn antenna).

For radiated emissions in the range 1 GHz-25 GHz that is performed at a distance closer than the specified distance, an inverse proportionality factor of 20 dB per decade is used to normalize the measured data for determining compliance.

The equipment under test was set up on a non-conductive (wooden) platform one meter above the ground plane and the situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

FCC Section 15.247 Subclause (a) (1) / RSS-210 Clause A8.1 (b). 20 dB Bandwidth and Carrier frequency separation

SPECIFICATION

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

RESULTS

(See next plots)

Modulation: GFSK

	Lowest frequency 2402 MHz	Middle frequency 2441 MHz	Highest frequency 2480 MHz
20 dB Spectrum bandwidth (kHz)	944.571	939.336	944.133
Measurement uncertainty (kHz)	±11		

Modulation: $\Pi/4$ -DQPSK (2Mbps)

	Lowest frequency 2402 MHz	Middle frequency 2441 MHz	Highest frequency 2480 MHz
20 dB Spectrum bandwidth (kHz)	1431	1434	1430
Measurement uncertainty (kHz)	±11		


Modulation: 8-DPSK (3Mbps)

	Lowest frequency 2402 MHz	Middle frequency 2441 MHz	Highest frequency 2480 MHz
20 dB Spectrum bandwidth (kHz)	1449	1444	1443
Measurement uncertainty (kHz)	±11		

Modulation: GFSK


20 dB BANDWIDTH.

Lowest Channel: 2402 MHz.




20 dB BANDWIDTH

Middle Channel: 2441 MHz.




20 dB BANDWIDTH

Highest Channel: 2480 MHz.



Carrier frequency separation




The hopping channel carrier frequencies are separated by a minimum of the 20 dB bandwidth of the hopping channel.

Verdict: PASS

Modulation: $\Pi/4$ -DQPSK


20 dB BANDWIDTH.

Lowest Channel: 2402 MHz.




20 dB BANDWIDTH

Middle Channel: 2441 MHz.




20 dB BANDWIDTH

Highest Channel: 2480 MHz.



Carrier frequency separation




The hopping channel carrier frequencies are separated by a minimum of the two-thirds of the 20 dB bandwidth of the hopping channel

Verdict: PASS

Modulation: 8-DPSK


20 dB BANDWIDTH

Lowest Channel: 2402 MHz.




20 dB BANDWIDTH

Middle Channel: 2441 MHz.




20 dB BANDWIDTH

Highest Channel: 2480 MHz.



Carrier frequency separation



The hopping channel carrier frequencies are separated by a minimum of the two-thirds of the 20 dB bandwidth of the hopping channel.

Verdict: PASS

FCC Section 15.247 Subclause (a) (1) (iii) / RSS-210 Clause A8.1 (d). Number of hopping channels


SPECIFICATION

Frequency hopping system in the 2400-2483.5 MHz band shall use at least 15 channels.


RESULTS

The number of hopping channels is 79 for all three modes (see next plots).

Modulation: GFSK



Number of hopping frequencies: 39




Number of hopping frequencies: 40


Total number of hopping frequencies: 79

Verdict: PASS

Modulation: $\Pi/4$ -DQPSK



Number of hopping frequencies: 39




Number of hopping frequencies: 40


Total number of hopping frequencies: 79

Verdict: PASS

Modulation: 8-DPSK



Number of hopping frequencies: 39



Number of hopping frequencies: 40

Total number of hopping frequencies: 79

Verdict: PASS

FCC Section 15.247 Subclause (a) (1) (iii) / RSS-210 Clause A8.1 (d). Time of occupancy (Dwell Time)

SPECIFICATION

The average time of occupancy on any channel shall not be greater than 0.4 seconds (400 ms) within a period of 0.4 seconds multiplied by the number of hopping channels employed = $0.4 \times 79 = 31.6$ seconds.

RESULTS


Modulation: GFSK

1. TIME OF OCCUPANCY (DWELL TIME) FOR PACKET TYPE DH1.

The system makes worst case 1600 hops per second or 1 time slot has a length of $625\mu s$ with 79 channels. A DH1 Packet need 1 time slot for transmitting and 1 time slot for receiving. Then the system makes worst case $1600/2 = 800$ hops per second with 79 channels. So you have each channel $800/79 = 10.13$ times per second and so for a period of $0.4 \times 79 = 31.6$ seconds you have $10.13 \times 31.6 = 320.11$ times of appearance.

Each Tx-time per appearance is $378.4\mu s$ (see next plot).

So we have $320.11 \times 378.4\mu s = 121.13$ ms per 31.6 seconds.




Verdict: PASS

2. TIME OF OCCUPANCY (DWEELL TIME) FOR PACKET TYPE DH3.

A DH3 Packet needs 3 time slots for transmitting and 1 time slot for receiving. Then the system makes worst case $1600/4 = 400$ hops per second with 79 channels. So you have each channel $400/79 = 5.1$ times per second and so for a period of $0.4 \times 79 = 31.6$ seconds you have $5.1 \times 31.6 = 161.16$ times of appearance.

Each Tx-time per appearance is 1.635 ms (see next plot).

So we have $161.16 \times 1.635 \text{ ms} = 263.50 \text{ ms}$ per 31.6 seconds.




Verdict: PASS

3. TIME OF OCCUPANCY (DWEELL TIME) FOR PACKET TYPE DH5.

A DH5 Packet needs 5 time slots for transmitting and 1 time slot for receiving. Then the system makes worst case $1600/6 = 266.67$ hops per second with 79 channels. So you have each channel $266.67/79 = 3.37$ times per second and so for a period of $0.4 \times 79 = 31.6$ seconds you have $3.37 \times 31.6 = 106.49$ times of appearance.

Each Tx-time per appearance is 2.887 ms (see next plot).

So we have $106.49 \times 2.887 \text{ ms} = 307.44 \text{ ms}$ per 31.6 seconds.



Verdict: PASS


Modulation: $\Pi/4$ -DQPSK

1. TIME OF OCCUPANCY (DWELL TIME) FOR PACKET TYPE DH1.

The system makes worst case 1600 hops per second or 1 time slot has a length of $625\mu\text{s}$ with 79 channels. A DH1 Packet need 1 time slot for transmitting and 1 time slot for receiving. Then the system makes worst case $1600/2 = 800$ hops per second with 79 channels. So you have each channel $800/79 = 10.13$ times per second and so for a period of $0.4 \times 79 = 31.6$ seconds you have $10.13 \times 31.6 = 320.11$ times of appearance.

Each Tx-time per appearance is $389.1\mu\text{s}$ (see next plot).

So we have $320.11 \times 389.1\mu\text{s} = 124.55\text{ ms}$ per 31.6 seconds.




Verdict: PASS

2. TIME OF OCCUPANCY (DWELL TIME) FOR PACKET TYPE DH3.

A DH3 Packet needs 3 time slots for transmitting and 1 time slot for receiving. Then the system makes worst case $1600/4 = 400$ hops per second with 79 channels. So you have each channel $400/79 = 5.1$ times per second and so for a period of $0.4 \times 79 = 31.6$ seconds you have $5.1 \times 31.6 = 161.16$ times of appearance.

Each Tx-time per appearance is 1.643 ms (see next plot).

So we have $161.16 \times 1.643 \text{ ms} = 264.78 \text{ ms}$ per 31.6 seconds.




Verdict: PASS

3. TIME OF OCCUPANCY (DWEELL TIME) FOR PACKET TYPE DH5.

A DH5 Packet needs 5 time slots for transmitting and 1 time slot for receiving. Then the system makes worst case $1600/6 = 266.67$ hops per second with 79 channels. So you have each channel $266.67/79 = 3.37$ times per second and so for a period of $0.4 \times 79 = 31.6$ seconds you have $3.37 \times 31.6 = 106.49$ times of appearance.

Each Tx-time per appearance is 2.891 ms (see next plot).

So we have $106.49 \times 2.891 \text{ ms} = 307.86 \text{ ms}$ per 31.6 seconds.




Verdict: PASS

2. TIME OF OCCUPANCY (DWELL TIME) FOR PACKET TYPE DH3.

A DH3 Packet needs 3 time slots for transmitting and 1 time slot for receiving. Then the system makes worst case $1600/4 = 400$ hops per second with 79 channels. So you have each channel $400/79 = 5.1$ times per second and so for a period of $0.4 \times 79 = 31.6$ seconds you have $5.1 \times 31.6 = 161.16$ times of appearance.

Each Tx-time per appearance is 1.639 ms (see next plot).

So we have $161.16 \times 1.639 \text{ ms} = 268.14 \text{ ms}$ per 31.6 seconds.




Verdict: PASS

3. TIME OF OCCUPANCY (DWEELL TIME) FOR PACKET TYPE DH5.

A DH5 Packet needs 5 time slots for transmitting and 1 time slot for receiving. Then the system makes worst case $1600/6 = 266.67$ hops per second with 79 channels. So you have each channel $266.67/79 = 3.37$ times per second and so for a period of $0.4 \times 79 = 31.6$ seconds you have $3.37 \times 31.6 = 106.49$ times of appearance.

Each Tx-time per appearance is 2.895 ms (see next plot).

So we have $106.49 \times 2.895 \text{ ms} = 308.29 \text{ ms}$ per 31.6 seconds.



Verdict: PASS

FCC Section 15.247 Subclause (b) / RSS-210 Clause A8.4 (2). Maximum peak output power and antenna gain

SPECIFICATION

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 hopping channels: 1 watt (30 dBm).

RESULTS

MAXIMUM OUTPUT POWER. See next plots.

Declared maximum antenna gain: 3 dBi.

The EIRP power (dBm) is calculated by adding the declared maximum antenna gain to the measured conducted power.

Modulation: GFSK

	Lowest frequency 2402 MHz	Middle frequency 2441 MHz	Highest frequency 2480 MHz
Maximum peak power (dBm)	2.94	3.77	4.66
Maximum EIRP power (dBm)	5.94	6.77	7.66
Measurement uncertainty (dB)	±1.5		

Modulation: $\pi/4$ -DQPSK (2Mbps)

	Lowest frequency 2402 MHz	Middle frequency 2441 MHz	Highest frequency 2480 MHz
Maximum peak power (dBm)	3.02	3.74	4.69
Maximum EIRP power (dBm)	6.02	6.74	7.69
Measurement uncertainty (dB)	±1.5		

Modulation: 8-DPSK (3Mbps)

	Lowest frequency 2402 MHz	Middle frequency 2441 MHz	Highest frequency 2480 MHz
Maximum peak power (dBm)	3.27	4.09	4.87
Maximum EIRP power (dBm)	6.27	7.09	7.87
Measurement uncertainty (dB)	±1.5		


The maximum directional gain of the antenna is less than 6 dBi and therefore the maximum output power is not required to be reduced from the stated values.

Verdict: PASS

PEAK OUTPUT POWER (CONDUCTED).


Modulation: GFSK

Lowest Channel: 2402 MHz.



Modulation: GFSK


Middle Channel: 2441 MHz.



PEAK OUTPUT POWER (CONDUCTED).


Modulation: GFSK

Highest Channel: 2480 MHz.



Modulation: $\pi/4$ -DQPSK


Lowest Channel: 2402 MHz



PEAK OUTPUT POWER (CONDUCTED)


Modulation: $\Pi/4$ -DQPSK

Middle Channel: 2441 MHz.



Modulation: $\Pi/4$ -DQPSK


Highest Channel: 2480 MHz.



PEAK OUTPUT POWER (CONDUCTED).


Modulation: 8-DPSK

Lowest Channel: 2402 MHz




Modulation: 8-DPSK

Middle Channel: 2441 MHz.



PEAK OUTPUT POWER (CONDUCTED).

Modulation: 8-DPSK Highest Channel: 2480 MHz.



FCC Section 15.247 Subclause (d) / RSS-210 Clauses 2.2 & A8.5. Band-edge compliance of conducted emissions (Transmitter)


SPECIFICATION

Emissions outside the frequency band in which the intentional radiator is operating shall be at least 20dB below the highest level of the desired power.

RESULTS:


Modulation: GFSK

1. LOW FREQUENCY SECTION 2402 MHz (HOPPING OFF). See next plot.




Verdict: PASS

2. HIGH FREQUENCY SECTION 2480 MHz (HOPPING OFF). See next plot.




Verdict: PASS

3. LOW FREQUENCY SECTION (HOPPING ON). See next plot.



Verdict: PASS


4. HIGH FREQUENCY SECTION (HOPPING ON). See next plot.



Verdict: PASS


Modulation: $\Pi/4$ -DQPSK

1. LOW FREQUENCY SECTION 2402 MHz (HOPPING OFF). See next plot.




Verdict: PASS

2. HIGH FREQUENCY SECTION 2480 MHz (HOPPING OFF). See next plot.




Verdict: PASS

3. LOW FREQUENCY SECTION (HOPPING ON). See next plot.



Verdict: PASS


4. HIGH FREQUENCY SECTION (HOPPING ON). See next plot.



Verdict: PASS


Modulation: 8-DPSK

1. LOW FREQUENCY SECTION 2402 MHz (HOPPING OFF). See next plot.




Verdict: PASS

2. HIGH FREQUENCY SECTION 2480 MHz (HOPPING OFF). See next plot.




Verdict: PASS

3. LOW FREQUENCY SECTION (HOPPING ON). See next plot.



Verdict: PASS

4. HIGH FREQUENCY SECTION (HOPPING ON). See next plot.



Verdict: PASS

FCC Section 15.247 Subclause (d) / RSS-210 Clauses 2.2 & A8.5. Band-edge compliance of radiated emissions (Transmitter)

SPECIFICATION:

Emissions outside the frequency band in which the intentional radiator is operating shall be at least 20 dB below the highest level of the desired power. Attenuation below the general field strength limits specified in RSS-Gen is not required.

RESULTS:


Band-edge compliance of radiated emissions

Maximum peak and average field strength of fundamental emission at 3 m distance

HIGHEST CHANNEL (2480 MHz):


Modulation: GFSK

Maximum field strength at 3 m. Peak value.



Note: The correction factor is already included in the spectrum analyzer as a transducer factor so that the marker shows directly the field strength level.


Maximum field strength at 3 m. Average value.




Note: The correction factor is already included in the spectrum analyzer as a transducer factor so that the marker shows directly the field strength level.

BAND-EDGE COMPLIANCE. RADIATED. Marker-Delta Method.

Single carrier



Hopping mode



Note: No correction is applied for this relative measurement.

Band edge compliance of radiated emissions


Fundamental max. average value 3 m	Delta value	Calculated value 3 m	Limit
85.80 dB μ V/m	47.41 dB (single carrier) 45.05 dB (hopping mode)	38.39 dB μ V/m (single carrier) 40.75 dB μ V/m (hopping mode)	54 dB μ V/m

Fundamental max. Peak value 3 m	Delta value	Calculated value 3 m	Limit
96.87 dB μ V/m	47.41 dB (single carrier) 45.05 dB (hopping mode)	49.46 dB μ V/m (single carrier) 51.82 dB μ V/m (hopping mode)	74 dB μ V/m


Verdict: PASS

Modulation: $\Pi/4$ -DQPSK

Maximum field strength at 3 m. Peak value.




Maximum field strength at 3 m. Average value.




Note: The correction factor is already included in the spectrum analyzer as a transducer factor so that the marker shows directly the field strength level.

BAND-EDGE COMPLIANCE. RADIATED. Marker-Delta Method.

Single carrier



Hopping mode



Note: No correction is applied for this relative measurement.

Band edge compliance of radiated emissions


Fundamental max. average value 3 m	Delta value	Calculated value 3 m	Limit
83.41 dB μ V/m	45.47 dB (single carrier) 43.51 dB (hopping mode)	37.94 dB μ V/m (single carrier) 39.90 dB μ V/m (hopping mode)	54 dB μ V/m

Fundamental max. Peak value 3 m	Delta value	Calculated value 3 m	Limit
95.90 dB μ V/m	45.47 dB (single carrier) 43.51 dB (hopping mode)	50.43 dB μ V/m (single carrier) 52.39 dB μ V/m (hopping mode)	74 dB μ V/m


Verdict: PASS

Modulation: 8-DPSK

Maximum field strength at 3 m. Peak value.




Maximum field strength at 3 m. Average value.




Note: The correction factor is already included in the spectrum analyzer as a transducer factor so that the marker shows directly the field strength level.

BAND-EDGE COMPLIANCE. RADIATED. Marker-Delta Method.

Single carrier



Hopping mode



Note: No correction is applied for this relative measurement.

Band edge compliance of radiated emissions

Fundamental max. average value 3 m	Delta value	Calculated value 3 m	Limit
83.36 dB μ V/m	44.94 dB (single carrier) 44.99 dB (hopping mode)	38.42 dB μ V/m (single carrier) 38.37 dB μ V/m (hopping mode)	54 dB μ V/m

Fundamental max. Peak value 3 m	Delta value	Calculated value 3 m	Limit
96.16 dB μ V/m	44.94 dB (single carrier) 44.99 dB (hopping mode)	51.22 dB μ V/m (single carrier) 51.17 dB μ V/m (hopping mode)	74 dB μ V/m

Verdict: PASS

FCC Section 15.247 Subclause (d) / RSS-210 Clause A8.5. Emission limitations conducted (Transmitter)


SPECIFICATION

In any 100 kHz bandwidths outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

RESULTS:

Modulation: GFSK


1. LOWEST CHANNEL (2402 MHz): 30 MHz-25 GHz (see next plot).



Note: The peak above the limit is the carrier frequency.

Verdict: PASS


2. MIDDLE CHANNEL (2441 MHz): 30 MHz-25 GHz (see next plot).



Note: The peak above the limit is the carrier frequency.

Verdict: PASS

3. HIGH CHANNEL (2480 MHz): 30 MHz-25 GHz (see next plot).




Note: The peak above the limit is the carrier frequency.

Verdict: PASS

Modulation: $\Pi/4$ -DQPSK


1. LOWEST CHANNEL (2402 MHz): 30 MHz-25 GHz (see next plot).



Note: The peak above the limits is the carrier frequency.

Verdict: PASS


2. MIDDLE CHANNEL (2441 MHz): 30 MHz-25 GHz (see next plot).



Note: The peaks above the limits are the carrier frequencies.

Verdict: PASS

3. HIGH CHANNEL (2480 MHz): 30 MHz-25 GHz (see next plot).




Note: The peak above the limit is the carrier frequency.

Verdict: PASS

Modulation: 8-DPSK


1. LOWEST CHANNEL (2402 MHz): 30 MHz-25 GHz (see next plot).



Note: The peak above the limits is the carrier frequency.

Verdict: PASS


2. MIDDLE CHANNEL (2441 MHz): 30 MHz-25 GHz (see next plot).



Note: The peaks above the limit are the carrier frequencies.

Verdict: PASS

3. HIGH CHANNEL (2480 MHz): 30 MHz-25 GHz (see next plot).



Note: The peak above the limit is the carrier frequency.

Verdict: PASS

FCC Section 15.247 Subclause (d) / RSS-210 Clauses 2.2. & A8.5. Emission limitations radiated (Transmitter)

SPECIFICATION

Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)):

Frequency Range (MHz)	Field strength ($\mu\text{V/m}$)	Field strength ($\text{dB}\mu\text{V/m}$)	Measurement distance (m)
0.009-0.490	$2400/F(\text{kHz})$	-	300
0.490-1.705	$24000/F(\text{kHz})$	-	300
1.705 - 30.0	30	-	30
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
960 - 25000	500	54	3

The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

For average radiated emission measurements above 1000 MHz, there is also a limit corresponding to 20 dB above the indicated values in the table is specified when measuring with peak detector function.

RESULTS:

The situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

All tests were performed in a semi-anechoic chamber at a distance of 3 m for the frequency range 30 MHz-1000 MHz and at distance of 1m for the frequency range 1 GHz-25 GHz.

The field strength is calculated by adding correction factor to the measured level from the spectrum analyzer. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

The equipment transmits continuously in the selected channel so it is not necessary a duty cycle correction factor.

Frequency range 30 MHz-1000 MHz.

Note: The spurious emissions below 1 GHz do not depend on either the operating channel or the modulation mode selected in the EUT.

Spurious levels operating (radiated) closest to limit.

Spurious frequency (MHz)	Polarization	Detector	Emission Level (dBμV/m)	Measurement Uncertainty (dB)
32.719438	V	Quasi-peak	24.89	±3.8

All other peaks are more than 20 dB below the limit.

Frequency range 1 GHz-25 GHz

Modulation: GFSK

1. CHANNEL: LOWEST (2402 MHz).

Spurious frequency (MHz)	Polarization	Detector	Emission Level (dBμV/m)	Measurement Uncertainty (dB)
2441.77	H	Peak	52.51	± 4.0
	H	Average	46.83	± 4.0
2461.74	H	Peak	50.93	± 4.0
	H	Average	45.97	± 4.0
2482.13	H	Peak	53.31	± 4.0
	H	Average	48.27	± 4.0

2. CHANNEL: MIDDLE (2441 MHz).

Spurious frequency (MHz)	Polarization	Detector	Emission Level (dBμV/m)	Measurement Uncertainty (dB)
2481.06	H	Peak	53.16	± 4.0
	H	Average	48.89	± 4.0
2521.01	H	Peak	53.06	± 4.0
	H	Average	48.94	± 4.0
2541.05	H	Peak	52.26	± 4.0
	H	Average	46.77	± 4.0
2560.83	H	Peak	53.26	± 4.0
	H	Average	49.14	± 4.0

3. CHANNEL: HIGHEST (2480 MHz).

Spurious frequency (MHz)	Polarization	Detector	Emission Level (dBμV/m)	Measurement Uncertainty (dB)
2520.30	H	Peak	53.24	± 4.0
	H	Average	48.30	± 4.0
2559.82	H	Peak	52.75	± 4.0
	H	Average	48.32	± 4.0
2580.00	H	Peak	52.20	± 4.0
	H	Average	47.29	± 4.0
2600.06	H	Peak	52.86	± 4.0
	H	Average	47.90	± 4.0

Verdict: PASS

Modulation: $\Pi/4$ -DQPSK

1. CHANNEL: LOWEST (2402 MHz).

Spurious frequency (MHz)	Polarization	Detector	Emission Level (dB μ V/m)	Measurement Uncertainty (dB)
2442.09	H	Peak	51.85	± 4.0
	H	Average	44.23	± 4.0
2482.17	H	Peak	52.36	± 4.0
	H	Average	46.1	± 4.0
2501.88	H	Peak	51.59	± 4.0
	H	Average	44.47	± 4.0
2522.25	H	Peak	52.31	± 4.0
	H	Average	46.12	± 4.0
3088.45	V	Peak	40.39	± 4.0
	V	Average	34.61	± 4.0

2. CHANNEL: MIDDLE (2441 MHz).

Spurious frequency (MHz)	Polarization	Detector	Emission Level (dB μ V/m)	Measurement Uncertainty (dB)
2479.63	H	Peak	52.44	± 4.0
	H	Average	46.65	± 4.0
2500.19	H	Peak	51.81	± 4.0
	H	Average	44.84	± 4.0
2519.84	H	Peak	52.53	± 4.0
	H	Average	46.28	± 4.0
2559.79	H	Peak	51.88	± 4.0
	H	Average	45.68	± 4.0
3137.18	V	Peak	43.45	± 4.0
	V	Average	37.56	± 4.0
4879.97	V	Peak	41.38	± 4.0
	V	Average	35.31	± 4.0

3. CHANNEL: HIGHEST (2480 MHz).

Spurious frequency (MHz)	Polarization	Detector	Emission Level (dB μ V/m)	Measurement Uncertainty (dB)
2519.91	H	Peak	52.42	± 4.0
	H	Average	45.92	± 4.0
2560.25	H	Peak	52.39	± 4.0
	H	Average	45.50	± 4.0
2580.07	H	Peak	51.89	± 4.0
	H	Average	45.19	± 4.0
2599.89	H	Peak	52.87	± 4.0
	H	Average	46.68	± 4.0
3188.71	V	Peak	41.11	± 4.0
	V	Average	35.25	± 4.0
4959.99	V	Peak	43.22	± 4.0
	V	Average	38.75	± 4.0

Verdict: PASS

Modulation: 8-DPSK

1. CHANNEL: LOWEST (2402 MHz).

Spurious frequency (MHz)	Polarization	Detector	Emission Level (dB μ V/m)	Measurement Uncertainty (dB)
2441.94	H	Peak	50.75	± 4.0
	H	Average	44.29	± 4.0
2482.17	H	Peak	52.72	± 4.0
	H	Average	46.04	± 4.0
2501.95	H	Peak	51.35	± 4.0
	H	Average	44.46	± 4.0
2521.82	H	Peak	52.18	± 4.0
	H	Average	46.14	± 4.0
3088.35	V	Peak	39.17	± 4.0
	V	Average	34.60	± 4.0

2. CHANNEL: MIDDLE (2441 MHz).

Spurious frequency (MHz)	Polarization	Detector	Emission Level (dB μ V/m)	Measurement Uncertainty (dB)
2480.01	H	Peak	52.41	± 4.0
	H	Average	46.77	± 4.0
2449.83	H	Peak	51.48	± 4.0
	H	Average	44.84	± 4.0
2520.15	H	Peak	52.93	± 4.0
	H	Average	46.25	± 4.0
2559.79	H	Peak	51.99	± 4.0
	H	Average	45.69	± 4.0
3137.13	V	Peak	40.57	± 4.0
	V	Average	37.24	± 4.0

3. CHANNEL: HIGHEST (2480 MHz).


Spurious frequency (MHz)	Polarization	Detector	Emission Level (dB μ V/m)	Measurement Uncertainty (dB)
2519.65	H	Peak	51.85	± 4.0
	H	Average	45.98	± 4.0
2560.12	H	Peak	51.44	± 4.0
	H	Average	45.27	± 4.0
2580.09	H	Peak	51.39	± 4.0
	H	Average	45.18	± 4.0
2600.38	H	Peak	52.14	± 4.0
	H	Average	46.67	± 4.0
3188.63	V	Peak	40.98	± 4.0
	V	Average	35.66	± 4.0
4960.03	V	Peak	41.98	± 4.0
	V	Average	38.88	± 4.0

Verdict: PASS

FREQUENCY RANGE 1 GHz to 3 GHz.


Modulation: GFSK

CHANNEL: Lowest (2402 MHz).




Note: The peak shown in the plot is the carrier frequency.

CHANNEL: Middle (2441 MHz).



Note: The peak shown in the plot is the carrier frequency.


CHANNEL: Highest (2480 MHz).



Note: The peak shown in the plot is the carrier frequency.


Modulation: $\Pi/4$ -DQPSK

CHANNEL: Lowest (2402 MHz).




Note: The peak shown in the plot is the carrier frequency.

CHANNEL: Middle (2441 MHz).



Note: The peak shown in the plot is the carrier frequency.


CHANNEL: Highest (2480 MHz).



Note: The peak shown in the plot is the carrier frequency.


Modulation: 8-DPSK

CHANNEL: Lowest (2402 MHz).




Note: The peak shown in the plot is the carrier frequency.

CHANNEL: Middle (2441 MHz).



Note: The peak shown in the plot is the carrier frequency.

CHANNEL: Highest (2480 MHz).




Note: The peak shown in the plot is the carrier frequency.


FREQUENCY RANGE 3 GHz to 12.75 GHz.

Modulation: GFSK


CHANNEL: Lowest (2402 MHz).



CHANNEL: Middle (2441 MHz).




CHANNEL: Highest (2480 MHz).




Modulation: $\Pi/4$ -DQPSK


CHANNEL: Lowest (2402 MHz).



CHANNEL: Middle (2441 MHz).




CHANNEL: Highest (2480 MHz).




Modulation: 8-DPSK


CHANNEL: Lowest (2402 MHz).




CHANNEL: Middle (2441 MHz).



CHANNEL: Highest (2480 MHz).




FREQUENCY RANGE 12.75 GHz to 18 GHz.



(This plot is valid for all three channels and all modulation modes).

FREQUENCY RANGE 18 GHz to 25 GHz.




(This plot is valid for all three channels and all modulation modes).


FREQUENCY RANGE 2.31 GHz to 2.39 GHz. (RESTRICTED BAND)

CHANNEL: Lowest


Modulation: GFSK



Modulation: Π/4-DQPSK




Modulation: 8-DPSK




CHANNEL: Middle


Modulation: GFSK



Modulation: $\Pi/4$ -DQPSK




Modulation: 8-DPSK




CHANNEL: Highest


Modulation: GFSK



Modulation: Π/4-DQPSK




Modulation: 8-DPSK



FREQUENCY RANGE 2.4835 GHz to 2.5 GHz. (RESTRICTED BAND)


CHANNEL: Lowest (2402 MHz).




(This plot is valid for all modulation modes).

CHANNEL: Middle


Modulation: GFSK



Modulation: $\Pi/4$ -DQPSK




Modulation: 8-DPSK




CHANNEL: Highest (2480 MHz).

Modulation: GFSK



Modulation: $\Pi/4$ -DQPSK



Modulation: 8-DPSK

