

# RF Exposure Evaluation declaration

Product Name	Intel® Dual Band Wireless-AC 7260
Model No.	7260HMW
FCC ID	PD97260H

Applicant	INTEL CORPORATION SAS
Address	1681 route des Dolines BP293 06905 Sophia Antipolis Cedex, France

Date of Receipt	Oct. 14, 2013
Date of Declaration	Oct. 28, 2013
Report No.	13A0258R-RFUSP28V01-A

The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of QuieTek Corporation.  
This report must not be used to claim product endorsement by TAF any agency of the U.S. Government

## 1. RF Exposure Evaluation

### 1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

**LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)**

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

$P_d$  = power density in  $\text{mW/cm}^2$

$P_{out}$  = output power to antenna in mW

$G$  = gain of antenna in linear scale

$\pi = 3.1416$

$R$  = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE,  $1 \text{ mW/cm}^2$ . If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance  $r$  where the MPE limit is reached.

### 1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity:  $18^\circ\text{C}$  and 78% RH.

### 1.3. Test Result of RF Exposure Evaluation

Product : Intel® Dual Band Wireless-AC 7260  
Test Item : RF Exposure Evaluation  
Test Site : No.3 OATS

Operation Frequency Range	2412-2462MHz, 5180-5825MHz
Maximum Conducted output power	26.91dBm
Antenna gain	1.84dBi

#### Output Power Into Antenna & RF Exposure Evaluation Distance:

Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
490.9079	0.149187

Power density in column 4 is much lower than the limit (1 mW/cm<sup>2</sup>).