

ANTENNA INFORMATION

OEM	Lenovo
ODM	LCFC
Platform model name	Lenovo 500e Chromebook Gen 4s
Intel platform (ex: Yes, No or NA)	yes
Platform type (ex: regular NB, convertible PC, AIO...etc)	Convertible PC
SAR minimum separation (mm)	FCC (1g) 9.9mm
	ISED (1g) 187mm
	ISED (10g) 4.2mm

Antenna manufacturer	Company name	INPAQ TECHNOLOGY CO., LTD.
	Address	1F., No. 106, Ligong St., Beitou Dist., Taipei City 112019 , Taiwan (R.O.C.)
Test location	Company name	SPEEDWIRE
	Address	No. 138, Hi-tech District East-river, Huizhou, Guangdong, China
Test Personnel	Name(Full name)	Kevin Zhang
	E-mail	kevin_zhang@speed-hz.com
	Tel/Mobile	+886-3-3253361 ext 227
Testing date		2024/7/15

Antenna Part number	Main	DC330025900
	Aux	DC330025910
Antenna type (ex: PIFA, Dipole...etc)		PIFA

Antenna Peak gain w/ cable loss (dBi)*										
	2.4GHz 2400-2483.5 MHz	5.2GHz 5150-5250MHz	5.3GHz 5250-5350MHz	5.6GHz 5470-5725MHz	5.8GHz 5725-5850MHz	5.9GHz 5850-5895MHz	6.2GHz 5925-6425MHz	6.5GHz 6425-6525MHz	6.7GHz 6525-6875MHz	7.0 GHz 6875-7125MHz
Main	1.36	2.63	2.34	2.50	2.69	2.47	2.71	2.71	2.64	2.83
Aux	1.56	2.11	2.75	2.91	2.60	2.60	2.54	2.26	2.75	2.79

Cable Assembly Part Number and Information					
	Cable PN	Cable length(mm)	Cable diameter(mm)	Impedance(ohm)	Connector type
Main	1.13 low loss	36	1.13	50	C87P115 or equivalent
Aux	1.13 low loss	133	1.13	50	C87P115 or equivalent

* 3D Antenna Peak Gain required being test in system basis.

Table of Contents


Cover page.....	1
1. Radiation characteristics of antenna loaded in Host Platform.....	3
Annex A. Photographs	
A.1 Setup Photo.....	13
A.2 Test sample.....	14
Annex B. Antenna Location	
B.1 Antenna Host Platform Location Information.....	16
B.2 Antenna dimensional information for SAR evaluation.....	17

1. Radiation characteristics of antenna loaded in Host Platform

Main Antenna


Max Antenna 3D Radiation Pattern 2400 – 2483.5 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
2400-2483.5	1.36




Max Antenna 3D Radiation Pattern 5150-5250 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
5150-5250	2.63




Max Antenna 3D Radiation Pattern 5250-5350 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
5250-5350	2.34




Max Antenna 3D Radiation Pattern 5470-5725 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
5470-5725	2.50




Max Antenna 3D Radiation Pattern 5725-5850 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
5725-5850	2.69




Max Antenna 3D Radiation Pattern 5850-5895 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
5850-5895	2.47




Max Antenna 3D Radiation Pattern 5925-6425 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
5925-6425	2.71




Max Antenna 3D Radiation Pattern 6425-6525 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
6425-6525	2.71




Max Antenna 3D Radiation Pattern 6525-6875 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
6525-6875	2.64



Max Antenna 3D Radiation Pattern 6875-7125 MHz


Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
6875-7125	2.83



Auxiliary Antenna


Max Antenna 3D Radiation Pattern 2400 – 2483.5 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
2400-2483.5	1.56




Max Antenna 3D Radiation Pattern 5150-5250 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
5150-5250	2.11




Max Antenna 3D Radiation Pattern 5250-5350 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
5250-5350	2.75




Max Antenna 3D Radiation Pattern 5470-5725 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
5470-5725	2.91




Max Antenna 3D Radiation Pattern 5725-5850 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
5725-5850	2.60




Max Antenna 3D Radiation Pattern 5850-5895 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
5850-5895	2.60




Max Antenna 3D Radiation Pattern 5925-6425 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
5925-6425	2.54




Max Antenna 3D Radiation Pattern 6425-6525 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
6425-6525	2.26




Max Antenna 3D Radiation Pattern 6525-6875 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
6525-6875	2.75



Max Antenna 3D Radiation Pattern 6875-7125 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
6875-7125	2.79



Annex A. Photographs

A.1 Setup Photo

<insert test diagram here for test site utilized>

Test Conditions
NB under test placed on a non-conductive structure at sufficient height to be in the 'quiet zone' of the chamber
The NB under test must be fully populated with a power, motherboard, hard drive, disk drives, etc... The purpose is to characterize the antennas on a fully populated customer deliverable unit.
NB's panel should be parallel with XY-plane and face to Y-axle, see diagram below.




A.2 Test sample

Main Antenna


Antenna Drawing

*#36±2,Ø1.13 LLS MAIN BLACK




Antenna Photo

Front




Back



Note: antenna photo should include L type ruler


Aux Antenna

Antenna Drawing




Antenna Photo

Front



Back




Note: antenna photo should include L type ruler

Annex B. Antenna Location

B.1 Antenna Host Platform Location Information

Include a dimensioned photo(s) or dimensioned drawing(s) of Main and Aux antenna placements (measurements are not required for receive-only antenna).

Any antenna that transmits must show dimensions to bottom of laptop. Provide a description of the materials that are used for supporting or surrounding transmit antennas; for example, non-conductive plastics vs. conductive coated plastic or metallic materials.



3


B.2 Antenna dimensional information for SAR evaluation

Include a dimensioned photo(s) or dimensioned drawing(s) showing the distance (mm) between the transmit antennas and the user. For notebook/laptop hosts show lapheld position (example below). For tablet hosts show all orientations including lapheld, primary & secondary portrait, primary & secondary landscape positions. Include a description of any proximity sensors or power throttling implementations that limit or exclude use of any host orientation.

Antennas on the panel section


NB Mode - WLAN portion

separation distance to top side (mm)	separation distance to bottom side (mm)	SAR minimum separation (mm)
4.2	9.9	4.2



Measuring Surface	Antenna	Separation Distance(antenna-to- Surface)(mm)	1g SAR
Bottom Side	Main	9.9mm	FCC/ISED
	Aux	9.9mm	FCC/ISED

Antennas on the keyboard section



3

Measuring Surface	Antenna	Separation Distance(antenna-to-Surface)(mm)	1g or 10g SAR
Bottom Side	Main	9.9mm	1g (FCC/ISED)
	Aux	9.9mm	1g (FCC/ISED)
Front Edge	Main	187mm	1g (ISED)
	Aux	187mm	1g (ISED)
Left Edge	Main	183mm	10g (ISED)
	Aux	93mm	10g (ISED)
Right Edge	Main	75mm	10g (ISED)
	Aux	167mm	10g (ISED)
Top side of Keyboard	Main	4.2mm	10g (ISED)
	Aux	4.2mm	10g (ISED)