

Regulatory WLAN Antenna Information (Template)

English Language Required for Intel Regulatory Review / Approval

(OEM/ODM or antenna vendor is required to complete this document with platform antenna information.

Remove Intel references and make this your own document)

Platform information					
Brand	ODM	****End product model name	Intel platform (ex: Yes, No or NA)	Platform type (ex: regular NB, convertible PC, AIO...etc)	*SAR minimum separation (mm)
Intel	Samsung	NT960XFH / NP960XFH	Yes	NB	

****Please fill in exact product model name and make sure the model name is visible on product cover or any parts for end users recognize for authority inspection.

Antenna information			
Vendor	Type	Antenna Part number (Main)	Antenna Part number (Aux)
WNC	PIFA	BA42-00754A	BA42-00754A

Peak gain w/ cable loss (dBi)*										
	2.4GHz 2400-2483.5 MHz	5.2GHz 5150-5250MHz	5.3GHz 5250-5350MHz	5.6GHz 5470-5725MHz	5.8GHz 5725-5850MHz	5.9GHz 5850-5895MHz	6.2GHz 5925-6425MHz	6.5GHz 6425-6525MHz	6.7GHz 6525-6875MHz	7.0 GHz 6875-7125MHz
Main	2.79	3.14	3.18	2.92	3.42	2.31	0.81	3.1	2.72	0.97
Aux	2.96	3.29	3.21	2.08	3.12	2.05	1.34	1.74	2.91	1.32

Intel Reference Gain/Type/ Separation distance		
Antenna Type	Antenna Peak gain (In dBi)*	Distance to the end user (mm)

	2.4GHz 2400-2483.5 MHz	5.2GHz 5150-5250MHz	5.3GHz 5250-5350MHz	5.6GHz 5470-5725MHz	5.8GHz 5725-5850MHz	5.9GHz 5850-5895MHz	6.2GHz 5925-6425MHz	6.5GHz 6425-6525MHz	6.7GHz 6525-6875MHz	7.0GHz 6875-7125MHz	Generic: refer to modular FCC SAR report Mid-power: ≥ 8 mm Low power: ≥ 5 mm
Design	3.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	
PIFA	3.24	3.64	3.73	4.77	4.97	4.72	4.83	4.30	5.37	5.59	
Dipole	2.89	2.92	3.19	4.41	4.22	4.22	4.83	4.30	4.49	5.34	

Notes (marked with *)											
* SAR minimum separation (mm)											
- Regular NB: Minimum antenna-to-body (from antenna bottom to the bottom of the device)											
- Tablet / Convertible PC: Minimum antenna-to-edge (5 sides of the device)											
- Mini-tablet: Minimum antenna-to-edge (6 sides of the device)											
* 3D Peak Antenna gain should be equal or greater than -2 dBi											
- If a host integrator plans to use a lower gain antenna of the same type, additional CBP(FCC)/EDT(EU) testing need to be performed while the module is installed in the host.											

Table of contents

1. Applicable test method
2. Test & System Description
 - a. Test setup
 - b. Equipment list
3. Setup photo

[Section 1. Antenna Assembly Specifications](#)

[Section 2. Dimensioned Photos or Drawings of Antennas](#)

[Section 3. Radiation characteristics of antenna loaded in Host Platform](#)

[Section 4. Antenna Host Platform Location Information](#)

[Section 5. Antenna dimensional information for SAR evaluation](#)

[Section 6. Diagram Example of Co-Location Antenna Separation](#)

Antenna Sample / Antenna Data

Requirements for worldwide regulatory approval

Section	Description of Required OEM / ODM Antenna Information	US / IC	EU	Japan	Taiwan	S. Korea
1A	Part Number for Antenna only	Required	Required	Required	Required	Required
1B	Antenna Manufacturer Name	Required	Required	Required	Required	Required
1C	Description of Antenna Type	Required	Required	N/A	N/A	N/A
1D	Part number of Antenna Assembly / cable impedance, length & diameter.	Required	Optional	Optional	Optional	Optional
1E	Main & Aux antenna (Peak Gain W/ cable loss) *	Required	Required	Required	Required	Required
1E OR 1F, 1G, 1H						
1F	Main & Aux antenna (Peak Gain only) *	Required	Required	Required	Required	Required
1G	VSWR of cable including connector	Required	Required	Required	Required	Required
1H	Main & Aux antenna (Cable loss W/ connector) *	Required	Required	Required	Required	Required
2	Dimensioned Photographs <u>and</u> Drawings of Main & Aux antennas	Required	Required	Required	Required	Required
3	Radiation patterns of antennas loaded in the host platform.	Required	Optional	Required	Required	Required
4	Platform model name / number - correlated to antenna manufacturer and antenna part number	Required	Required	Optional	Required	Optional
5	Photograph(s) or Drawings showing location of antennas in platform. <u>(S. Korea requires photographs of antennas for approval submission). Taiwan requires pictures of each antenna type shown in the system.</u>	Required	Required	Optional	<u>Required (Photos)</u>	<u>Required (Photos)</u>
6	Mech. drawings / photos with dimensions of antenna locations and distance from end-user (For evaluation of SAR testing requirement).	Required	N/A	N/A	N/A	N/A
7	Photograph(s) or Drawings showing the location of all antennas (WLAN, other) and distance between those transmitting antennas. Information will be used to evaluate whether co-location testing is required.	Required	N/A	N/A	N/A	N/A
8	Local representative contact information for LMA/ PARS process.	Required	N/A	N/A	N/A	N/A
9	Antenna gain range should be equal or greater than -2 dBi. (2.4/5/6GHz: EU, 6GHz: FCC)	Required	Required	N/A	N/A	N/A

Antenna Information

Section 1. Antenna Assembly Specifications

1A	1B	1C	1D		1E	1F	1G	1H
Antenna Part Number	Manufacturer	Antenna Type	Cable Assembly Part Number and Information	Freq Range MHz	* Peak Gain W/ Cable loss (dBi)	Peak Gain w/o Cable Loss (dBi)	Max VSWR	Cable Loss (dB)
(P/N: BA42-00754A) Main Antenna	Example: Intel Corporation	Example: Folded Dipole or PIFA	Example: (P/N: U.FL-2LP-81XBLC15.G24) 50 ohm Coaxial length: 274cm diameter: 1.13mm	2400-2483.5	2400-2483.5MHz 2.79 dBi (peak)	2400-2483.5MHz 3.49 dBi (peak)	2400-2483.5MHz 2.0max	2400-2483.5MHz 0.7dBi (peak)
				5150-5250	5150-5250MHz 3.14dBi (peak)	5150-5250MHz 4.09dBi (peak)	5150-5250MHz 3.0 max	5150-5250MHz 0.95dBi (peak)
				5250-5350	5250-5350MHz 3.18 dBi (peak)	5250-5350MHz 4.17dBi (peak)	5250-5350MHz 3.0max	5250-5350MHz 0.99dBi (peak)
				5470-5725	5470-5725MHz 2.92dBi (peak)	5470-5725MHz 3.94dBi (peak)	5470-5725MHz 3.0 max	5470-5725MHz 1.02dBi (peak)
				5725-5850	5725-5850MHz 3.42dBi (peak)	5725-5850MHz 4.46 dBi (peak)	5725-5850MHz 2.5 max	5725-5850MHz 1.04 dBi (peak)
				5850-5895	5850-5895MHz 2.31dBi (peak)	5850-5895MHz 3.38dBi (peak)	5850-5895MHz 3.5 max	5850-5895MHz 1.07 dBi (peak)
				5925-6425	5925-6425MHz 0.81dBi (peak)	5925-6425MH 1.9dBi (peak)	5925-6425MH 4.0 max	5925-6425MH 1.09 dBi (peak)
				6425-6525	6425-6525MHz 3.1 dBi (peak)	6425-6525MHz 4.31dBi (peak)	6425-6525MHz 4.0max	6425-6525MHz 1.21dBi (peak)
				6525-6875	6525-6875MHz 2.72 dBi (peak)	6525-6875MHz 4.02dBi (peak)	6525-6875MHzz 4.0max	6525-6875MHz 1.30dBi (peak)
				6875-7125	6875-7125MHz 0.97dBi (peak)	6875-7125MHz 2.39dBi (peak)	6875-7125MHz 4.0 max	6875-7125MHz 1.42dBi (peak)
(P/N: BA42-00754A) Aux Antenna	Example: Intel Corporation	Example: Folded Dipole or PIFA	Example: (P/N: U.FL-2LP-81XBLC15.G24) 50 ohm Coaxial length: 193.5cm diameter: 1.13mm	2400-2483.5	2400-2483.5MHz 2.96 dBi (peak)	2400-2483.5MHz 3.46dBi (peak)	2400-2483.5MHz 2max	2400-2483.5MHz 0.5 dBi (peak)
				5150-5250	5150-5250MHz 3.29 dBi (peak)	5150-5250MHz 3.97dBi (peak)	5150-5250MHz 2.5 max	5150-5250MHz 0.68dBi (peak)
				5250-5350	5250-5350MHz 3.21 dBi (peak)	5250-5350MHz 3.91dBi (peak)	5250-5350MHz 2.5 max	5250-5350MHz 0.7dBi (peak)
				5470-5725	5470-5725MHz 2.08 dBi (peak)	5470-5725MHz 2.8dBi (peak)	5470-5725MHz 2.5max	5470-5725MHz 0.72dBi (peak)
				5725-5850	5725-5850MHz 3.12dBi (peak)	5725-5850MHz 3.85dBi (peak)	5725-5850MHz 2.5 max	5725-5850MHz 0.73 dBi (peak)
				5850-5895	5850-5895MHz 2.05dBi (peak)	5850-5895MHz 2.81dBi (peak)	5850-5895MHz 3 max	5850-5895MHz 0.76 dBi (peak)
				5925-6425	5925-6425MHz 1.34dBi (peak)	5925-6425MH 2.15dBi (peak)	5925-6425MH 3.5max	5925-6425MH 0.81 dBi (peak)
				6425-6525	6425-6525MHz 1.74 dBi (peak)	6425-6525MHz 2.6dBi (peak)	6425-6525MHz 4.0max	6425-6525MHz 0.86 dBi (peak)
				6525-6875	6525-6875MHz 2.91 dBi (peak)	6525-6875MHz 4.19dBi (peak)	6525-6875MHzz 4.0 max	6525-6875MHz 1.28dBi (peak)
				6875-7125	6875-7125MHz 1.32dBi (peak)	6875-7125MHz 2.14dBi (peak)	6875-7125MHz 3.0 max	6875-7125MHz 0.82 dBi (peak)


- 3D Antenna Peak Gain required being test in system basis.

Section 3. Radiation characteristics of antenna loaded in Host Platform

Main Antenna


Max Antenna 3D Radiation Pattern 2400 – 2483.5 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
2400-2483.5	2.79




Max Antenna 3D Radiation Pattern 5150-5250 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
5150-5250	3.14




Max Antenna 3D Radiation Pattern 5250-5350 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
5250-5350	3.18




Max Antenna 3D Radiation Pattern 5470-5725 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
5470-5725	2.92




Max Antenna 3D Radiation Pattern 5725-5850 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
5725-5850	3.42




Max Antenna 3D Radiation Pattern 5850-5895 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
5850-5895	2.31




Max Antenna 3D Radiation Pattern 5925-6425 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
5925-6425	0.81




Max Antenna 3D Radiation Pattern 6425-6525 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
6425-6525	3.1




Max Antenna 3D Radiation Pattern 6525-6875 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
6525-6875	2.72



Max Antenna 3D Radiation Pattern 6875-7125 MHz


Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
6875-7125	0.97



Auxiliary Antenna


Max Antenna 3D Radiation Pattern 2400 – 2483.5 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
2400-2483.5	2.96




Max Antenna 3D Radiation Pattern 5150-5250 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
5150-5250	3.29




Max Antenna 3D Radiation Pattern 5250-5350 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
5250-5350	3.21




Max Antenna 3D Radiation Pattern 5470-5725 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
5470-5725	2.08




Max Antenna 3D Radiation Pattern 5725-5850 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
5725-5850	3.12




Max Antenna 3D Radiation Pattern 5850-5895 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
5850-5895	2.05




Max Antenna 3D Radiation Pattern 5925-6425 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
5925-6425	1.34




Max Antenna 3D Radiation Pattern 6425-6525 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
6425-6525	1.74



Max Antenna 3D Radiation Pattern 6525-6875 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
6525-6875	2.91



Max Antenna 3D Radiation Pattern 6875-7125 MHz

Frequency (MHz)	Peak Gain w/ Cable Loss (dBi)
6875-7125	1.32

