

Plots of System Verification

Appendix A. Plots of System Verification

The plots for system verification are shown as follows.

Plots of System Verification

Measurement Report
S01 System Check_H2450_240930
Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
D2450V2,	10.0 x 10.0 x 290.0		Phone

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	,		CW, 0--	2450.000, 0	6.62	1.81	39.4

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V5.0 (20deg probe tilt) - 1204	H19T27N4 , 2024-09-30	EX3DV4 - SN7720, 2024-03-19	DAE4 Sn1589, 2024-04-22

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	40.0 x 96.0	35.0 x 35.0 x 30.0
Grid Steps [mm]	10.0 x 12.0	5.0 x 5.0 x 1.5
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2024-09-30	2024-09-30
psSAR1g [W/kg]	2.54	2.51
psSAR10g [W/kg]	1.18	1.17
Power Drift [dB]	-0.01	-0.01



Plots of System Verification

Measurement Report S02 System Check_H5250_240930 Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
D5GHzV2,	10.0 x 10.0 x 300.0		Phone

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	,		CW, 0--	5250.000, 0	5.07	4.57	37.3

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V5.0 (20deg probe tilt) - 1204	H50T60N4 , 2024-09-30	EX3DV4 - SN7720, 2024-03-19	DAE4 Sn1589, 2024-04-22

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	40.0 x 80.0	24.0 x 24.0 x 22.0
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 1.4
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2024-09-30	2024-09-30
psSAR1g [W/kg]	3.43	3.65
psSAR10g [W/kg]	0.964	0.996
Power Drift [dB]	0.01	-0.05



Plots of System Verification

Measurement Report S03 System Check H5600_241001 Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
D5GHzV2,	10.0 x 10.0 x 300.0		

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	,		CW, 0--	5600.000, 0	4.44	5.03	36.6

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V5.0 (20deg probe tilt) - 1204	H50T60N4 , 2024-10-01	EX3DV4 - SN7720, 2024-03-19	DAE4 Sn1589, 2024-04-22

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	40.0 x 80.0	24.0 x 24.0 x 22.0
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 1.4
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2024-10-01	2024-10-01
psSAR1g [W/kg]	4.13	4.52
psSAR10g [W/kg]	1.29	1.28
Power Drift [dB]	-0.01	-0.04



Plots of System Verification

Measurement Report S04 System Check_H5800_241001 Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
D5GHzV2,	10.0 x 10.0 x 300.0		

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	,		CW, 0--	5800.000, 0	4.36	5.27	36.3

Hardware Setu


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V5.0 (20deg probe tilt) - 1204	H50T60N4 , 2024-10-01	EX3DV4 - SN7720, 2024-03-19	DAE4 Sn1589, 2024-04-22

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	40.0 x 80.0	24.0 x 24.0 x 22.0
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 1.4
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2024-10-01	2024-10-01
psSAR1g [W/kg]	3.85	4.32
psSAR10g [W/kg]	1.16	1.23
Power Drift [dB]	0.09	0.04



Plots of System Verification

Measurement Report S05 System Check_H5800_241001

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
D5GHzV2,	10.0 x 10.0 x 300.0		

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	,		CW, 0--	5800.000, 0	4.36	5.27	36.3

Hardware Setu


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V5.0 (20deg probe tilt) - 1204	H50T60N4 , 2024-10-01	EX3DV4 - SN7720, 2024-03-19	DAE4 Sn1589, 2024-04-22

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	40.0 x 80.0	24.0 x 24.0 x 22.0
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 1.4
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2024-10-01	2024-10-01
psSAR1g [W/kg]	3.85	4.32
psSAR10g [W/kg]	1.16	1.23
Power Drift [dB]	0.09	0.04



Plots of System Verification

Measurement Report

S06 System Check_H2450_241004

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
D2450V2,	10.0 x 10.0 x 300.0		

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	,		CW, 0--	2450.000, 0	6.62	1.81	39.3

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V5.0 (20deg probe tilt) - 1204	H19T27N4 , 2024-10-04	EX3DV4 - SN7720, 2024-03-19	DAE4 Sn1589, 2024-04-22

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	48.0 x 96.0	35.0 x 35.0 x 30.0
Grid Steps [mm]	12.0 x 12.0	5.0 x 5.0 x 1.5
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2024-10-04	2024-10-04
psSAR1g [W/kg]	2.42	2.47
psSAR10g [W/kg]	1.15	1.16
Power Drift [dB]	0.09	0.06



Plots of System Verification

Measurement Report

S07 System Check_H6500_241002

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
D6.5GHzV2,	10.0 x 10.0 x 296.0		6500

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	,		CW, 0--	6500.000, 0	4.64	6.10	35.2

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V5.0 (20deg probe tilt) - 1204	H60T72N4 , 2024-10-02	EX3DV4 - SN7720, 2024-03-19	DAE4 Sn1589, 2024-04-22

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	45.0 x 90.0	22.0 x 22.0 x 22.0
Grid Steps [mm]	7.5 x 7.5	3.4 x 3.4 x 1.4
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2024-10-02	2024-10-02
psSAR1g [W/kg]	25.4	28.0
psSAR10g [W/kg]	4.97	5.18
psAPD (1.0cm2, sq) [W/m2]		280
psAPD (4.0cm2, sq) [W/m2]		127
Power Drift [dB]	0.03	-0.07



Plots of System Verification

Measurement Report S07 PD_System Check_10 GHz_241004 Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
SPEAG, 5G Verification Source 10 GHz	100.0 x 100.0 x 170.0	SN: 1025	

Exposure Conditions

Phantom Section	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor
5G Air	Front Face 10.00	Validation band	CW, 0--	10000.0, 10000	1.0

Hardware Setup


Phantom	Medium	Probe, Calibration Date	DAE, Calibration Date
mmWave- 1030	--Air--	EUmmWV4 - SN9438_F1-55GHz, 2024-07-19	DAE4 Sn1762, 2023-11-17

Scan Setup

	5G Scan
Grid Extents [mm]	60.0 x 60.0
Grid Steps [lambda]	0.125 x 0.125
Sensor Surface [mm]	10.0

Measurement Results

	5G Scan
Date	2024-10-04
Avg. Area [cm ²]	4.00
psPDn+ [W/m ²]	55.1
psPDtot+ [W/m ²]	55.4
psPDmod+ [W/m ²]	55.7
E _{max} [V/m]	150
Power Drift [dB]	-0.02



Appendix B. Plots of Measurement

The SAR plots for highest measured SAR in each exposure configuration, wireless mode and frequency band combination are shown as follows.

Plots of Measurement

Measurement Report

P01 WLAN2.4G_802.11b_Bottom of Laptop_0mm_Ch13_Ant 1

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
P24090550,	356.0 x 250.0 x 10.0		Laptop

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	Bottom of Laptop, 0.00	WLAN 2.4GHz	WLAN, 10012-CAB	2472.000, 13	6.62	1.82	39.4

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V5.0 (20deg probe tilt) - 1204	H19T27N4 , 2024-09-30	EX3DV4 - SN7720, 2024-03-19	DAE4 Sn1589, 2024-04-22

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	96.0 x 360.0	30.0 x 30.0 x 30.0
Grid Steps [mm]	12.0 x 12.0	5.0 x 5.0 x 5.0
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2024-09-30	2024-09-30
psSAR1g [W/kg]	0.723	0.845
psSAR10g [W/kg]	0.306	0.319
Power Drift [dB]	-0.06	0.03
M2/M1 [%]		36.6
Dist 3dB Peak [mm]		6.4



Plots of Measurement

Measurement Report
P02 WLAN5.3G_802.11be EHT160_Bottom of Laptop_0mm_Ch50_Ant 1
Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
P24090550,	356.0 x 250.0 x 10.0		Laptop

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	Bottom of Laptop, 0.00	WLAN 5GHz	WLAN, 10755-AAC	5250.000, 50	5.07	4.57	37.3

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V5.0 (20deg probe tilt) - 1204	H50T60N4 , 2024-09-30	EX3DV4 - SN7720, 2024-03-19	DAE4 Sn1589, 2024-04-22

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	90.0 x 360.0	24.0 x 24.0 x 22.0
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 1.4
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2024-09-30	2024-09-30
psSAR1g [W/kg]	0.558	0.562
psSAR10g [W/kg]	0.155	0.141
Power Drift [dB]	-0.06	-0.01
M2/M1 [%]		61.9
Dist 3dB Peak [mm]		4.3



Plots of Measurement

Measurement Report

P03 WLAN5.6G_802.11be EHT160_Bottom of Laptop_0mm_Ch114_Ant 1

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
P24090550,	356.0 x 250.0 x 10.0		Laptop

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	Bottom of Laptop, 0.00	WLAN 5GHz	WLAN, 10755-AAC	5570.000, 114	4.44	5.00	36.6

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V5.0 (20deg probe tilt) - 1204	H50T60N4 , 2024-10-01	EX3DV4 - SN7720, 2024-03-19	DAE4 Sn1589, 2024-04-22

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	90.0 x 360.0	24.0 x 24.0 x 22.0
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 1.4
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2024-10-01	2024-10-01
psSAR1g [W/kg]	0.938	1.06
psSAR10g [W/kg]	0.259	0.261
Power Drift [dB]	0.04	-0.01
M2/M1 [%]		62.2
Dist 3dB Peak [mm]		4.8



Plots of Measurement

Measurement Report
P04 WLAN5.8G_802.11be EHT80_Bottom of Laptop_0mm_Ch155_Ant 1
Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
P24090550,	356.0 x 250.0 x 10.0		Laptop

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	Bottom of Laptop, 0.00	WLAN 5GHz	WLAN, 10731-AAC	5775.000, 155	4.36	5.24	36.3

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V5.0 (20deg probe tilt) - 1204	H50T60N4 , 2024-10-01	EX3DV4 - SN7720, 2024-03-19	DAE4 Sn1589, 2024-04-22

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	90.0 x 360.0	24.0 x 24.0 x 22.0
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 1.4
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2024-10-01	2024-10-01
psSAR1g [W/kg]	0.785	0.885
psSAR10g [W/kg]	0.215	0.218
Power Drift [dB]	0.05	0.01
M2/M1 [%]		60.8
Dist 3dB Peak [mm]		4.8



Plots of Measurement

Measurement Report

P05 WLAN5.9G_802.11be EHT160_Bottom of Laptop_0mm_Ch163_Ant 1

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
P24090550,	356.0 x 250.0 x 10.0		Laptop

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	Bottom of Laptop, 0.00	WLAN 5GHz	WLAN, 10755-AAC	5815.000, 163	4.36	5.28	36.2

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V5.0 (20deg probe tilt) - 1204	H50T60N4 , 2024-10-01	EX3DV4 - SN7720, 2024-03-19	DAE4 Sn1589, 2024-04-22

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	90.0 x 360.0	24.0 x 24.0 x 22.0
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 1.4
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2024-10-01	2024-10-01
psSAR1g [W/kg]	0.638	0.721
psSAR10g [W/kg]	0.175	0.173
Power Drift [dB]	0.12	-0.05
M2/M1 [%]		60.5
Dist 3dB Peak [mm]		4.8



Plots of Measurement

Measurement Report
P06 Bluetooth_BR EDR_Bottom of Laptop_0mm_Ch39_Ant 1
Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
P24090550,	356.0 x 250.0 x 10.0		Laptop

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	Bottom of Laptop, 0.00	ISM 2.4 GHz Band	Bluetooth, 10032-CAA	2441.000, 39	6.62	1.81	39.3

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V5.0 (20deg probe tilt) - 1204	H19T27N4 , 2024-10-04	EX3DV4 - SN7720, 2024-03-19	DAE4 Sn1589, 2024-04-22

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	96.0 x 360.0	30.0 x 30.0 x 30.0
Grid Steps [mm]	12.0 x 12.0	5.0 x 5.0 x 5.0
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2024-10-04	2024-10-04
psSAR1g [W/kg]	0.233	0.247
psSAR10g [W/kg]	0.096	0.089
Power Drift [dB]	0.01	0.13
M2/M1 [%]		34.3
Dist 3dB Peak [mm]		6.5



Plots of Measurement

Measurement Report
P07 WLAN6G_802.11be EHT320_Bottom of Laptop_0mm_Ch191_Ant 1
Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
P24090550,	356.0 x 250.0 x 10.0		Laptop

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	Bottom of Laptop, 0.00	U-NII-8	WLAN, 11026-AAA	6905.000, 191	4.64	6.58	34.6

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V5.0 (20deg probe tilt) - 1204	H60T72N4 , 2024-10-02	EX3DV4 - SN7720, 2024-03-19	DAE4 Sn1589, 2024-04-22

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	90.0 x 360.0	22.0 x 22.0 x 22.0
Grid Steps [mm]	7.5 x 7.5	3.4 x 3.4 x 1.4
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2024-10-02	2024-10-02
psSAR1g [W/kg]	0.346	0.376
psSAR10g [W/kg]	0.084	0.099
psAPD (1.0cm2, sq) [W/m2]		3.76
psAPD (4.0cm2, sq) [W/m2]		2.33
Power Drift [dB]	-0.03	0.16
M2/M1 [%]		50.6
Dist 3dB Peak [mm]		4.1



Plots of Measurement

Measurement Report
P07 PD WLAN6G_802.11be EHT320_Bottom of Laptop_0mm_Ch191_Ant 1
Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
, P24090550	360.0 x 250.0 x 7.0		Laptop

Exposure Conditions

Phantom Section	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor
5G Air	Bottom of Laptop, 2.00	U-NII-8	WLAN, 11026-AAA	6905.0, 191	1.0

Hardware Setup


Phantom	Medium	Probe, Calibration Date	DAE, Calibration Date
mmWave- 1030	---Air	EUmmWV4 - SN9438_F1-55GHz, 2024-07-19	DAE4 Sn1762, 2023-11-17

Scan Setup

	5G Scan
Grid Extents [mm]	87.0 x 87.0
Grid Steps [lambda]	0.0575 x 0.0575
Sensor Surface [mm]	2.0

Measurement Results

	5G Scan
Date	2024-10-04
Avg. Area [cm²]	4.00
psPDn+ [W/m²]	1.63
psPDtot+ [W/m²]	3.72
psPDmod+ [W/m²]	6.19
E _{max} [V/m]	60.5
Power Drift [dB]	-0.13



Appendix C. Tissue & System Verification

The measuring results for tissue simulating liquid and system check are shown as below.

Note:

1. For Section 4.3, the dielectric properties of the tissue simulating liquid have been measured within 24 hours before the SAR testing and within $\pm 10\%$ of the target values. Liquid temperature during the SAR testing has kept within $\pm 2^\circ\text{C}$.
2. For Section 4.4, The SAR measurement system was validated according to procedures in FCC KDB 865664 D0. The validation status in tabulated summary is as below.
3. For Section 4.5, Comparing to the reference SAR value provided by SPEAG in dipole calibration certificate, the deviation of system check results is within its specification of 10 %. The result indicates the system check can meet the variation criterion and the plots please refer to Appendix A of this report.

Tissue Verification									Validation for CW			Validation for Modulation				System Check					Note			
Plot No.	Frequency (MHz)	Liquid Temp. (°C)	Conductivity (σ)	Permittivity (ϵ_r)	Targeted Conductivity (σ)	Targeted Permittivity (ϵ_r)	Deviation Conductivity (σ)	Deviation Permittivity (ϵ_r)	Sensitivity Range	Probe Linearity	Probe Isotropy	Modulation Type	Duty Factor	PAR	Date	Frequency (MHz)	Targeted 1g SAR (W/kg)	Measured 1g SAR (W/kg)	Normalized 1g SAR (W/kg)	Deviation (%)	Dipole S/N	Probe S/N	DAE S/N	Output Power (dBm)
S01	2450	21.6	1.81	39.4	1.8	39.2	0.56	0.51	Pass	Pass	Pass	OFDM	N/A	Pass	Sep. 30, 2024	2450	52.90	2.51	50.08	-5.33	737	7720	1589	17
S02	5250	21.6	4.57	37.3	4.71	35.9	-2.97	3.90	Pass	Pass	Pass	OFDM	N/A	Pass	Sep. 30, 2024	5250	80.20	3.65	72.83	-9.19	1019	7720	1589	17
S03	5600	21.7	5.03	36.6	5.07	35.5	-0.79	3.10	Pass	Pass	Pass	OFDM	N/A	Pass	Oct. 01, 2024	5600	82.90	4.52	90.19	8.79	1019	7720	1589	17
S04	5800	21.7	5.27	36.3	5.27	35.3	0.00	2.83	Pass	Pass	Pass	OFDM	N/A	Pass	Oct. 01, 2024	5800	80.30	4.32	86.20	7.34	1019	7720	1589	17
S05	5800	21.7	5.27	36.3	5.27	35.3	0.00	2.83	Pass	Pass	Pass	OFDM	N/A	Pass	Oct. 01, 2024	5800	80.30	4.32	86.20	7.34	1019	7720	1589	17
S06	2450	21.3	1.81	39.3	1.8	39.2	0.56	0.26	Pass	Pass	Pass	OFDM	N/A	Pass	Oct. 04, 2024	2450	52.90	2.47	49.28	-6.84	737	7720	1589	17
S07	6500	21.5	6.1	35.2	6.07	34.5	0.49	2.03	Pass	Pass	Pass	OFDM	N/A	Pass	Oct. 02, 2024	6500	303.00	28	280.00	-7.59	1008	7720	1589	20

System Performance Check for Incident Power Density Measurement									
Plot No.	Test Date	Frequency [GHz]	mmWave Probe S/N	Verification Source S/N	Averaging Area [cm ²]	Distance [mm]	Target Power Density [W/m ²]	Measured Power Density [W/m ²]	Deviation [%]
P07	Oct. 04, 2024	10	9438	1025	4	10.0	56.2	55.4	-1.42%

Appendix D. Maximum Target Conducted Power

The maximum conducted average power (Unit: dBm) including tune-up tolerance is shown as below.

Tune-up Power (Full)							
WLAN 2.4GHz							
Mode	Channel	Frequency	SISO Ant 1 Max Tune up	SISO Ant 2 Max Tune up	MIMO Ant 1 Tune up	MIMO Ant 2 Tune up	MIMO Ant 1+2 Max Tune up
802.11b	1	2412	17.00	17.00			
	6	2437	17.00	17.00			
	11	2462	17.00	17.00			
	12	2467	17.00	17.00			
	13	2472	17.00	17.00			
802.11g	1	2412	17.00	17.00			
	6	2437	17.00	17.00			
	11	2462	17.00	17.00			
	12	2467	15.50	16.50			
	13	2472	14.00	15.00			
802.11n HT20	1	2412	17.00	17.00	14.00	14.00	17.00
	6	2437	17.00	17.00	14.00	14.00	17.00
	11	2462	17.00	17.00	14.00	14.00	17.00
	12	2467	13.50	16.50	10.50	10.50	13.50
	13	2472	13.50	13.50	10.50	10.50	13.50
802.11n HT40	3	2422	17.00	17.00	14.00	14.00	17.00
	6	2437	17.00	17.00	14.00	14.00	17.00
	9	2452	17.00	17.00	14.00	14.00	17.00
	10	2457	13.00	15.00	12.00	12.00	15.00
	11	2462	13.00	15.75	12.75	12.75	15.75
802.11ax HE20	1	2412	17.00	17.00	14.00	14.00	17.00
	6	2437	17.00	17.00	14.00	14.00	17.00
	11	2462	17.00	17.00	14.00	14.00	17.00
	12	2467	13.50	16.50	10.50	10.50	13.50
	13	2472	13.50	13.50	10.50	10.50	13.50
802.11ax HE40	3	2422	17.00	17.00	14.00	14.00	17.00
	6	2437	17.00	17.00	14.00	14.00	17.00
	9	2452	17.00	17.00	14.00	14.00	17.00
	10	2457	13.00	15.75	12.75	12.75	15.75
	11	2462	13.00	14.00	11.00	11.00	14.00
802.11be EHT20	1	2412	17.00	17.00	14.00	14.00	17.00
	6	2437	17.00	17.00	14.00	14.00	17.00
	11	2462	17.00	17.00	14.00	14.00	17.00
	12	2467	13.50	16.50	10.50	10.50	13.50
	13	2472	13.50	13.50	10.50	10.50	13.50
802.11be EHT40	3	2422	17.00	17.00	14.00	14.00	17.00
	6	2437	17.00	17.00	14.00	14.00	17.00
	9	2452	17.00	17.00	14.00	14.00	17.00
	10	2457	13.00	15.75	12.75	12.75	15.75
	11	2462	13.00	14.00	11.00	11.00	14.00

Tune-up Power (Full)			
Bluetooth			
Mode	Channel	Frequency	Ant 1 Max Tune-up
BR / EDR	0	2402	15.00
	39	2441	15.00
	78	2480	15.00
LE	0	2402	15.00
	19	2440	15.00
	39	2480	15.00

Tune-up Power (Full)							
WLAN 5.2GHz							
Mode	Channel	Frequency	SISO Ant 1 Max Tune up	SISO Ant 2 Max Tune up	MIMO Ant 1 Tune up	MIMO Ant 2 Tune up	MIMO Ant 1+2 Max Tune up
802.11a	36	5180	13.00	13.00			
	40	5200	13.00	13.00			
	44	5220	13.00	13.00			
	48	5240	13.00	13.00			
802.11n HT20	36	5180	13.00	13.00	10.00	10.00	13.00
	40	5200	13.00	13.00	10.00	10.00	13.00
	44	5220	13.00	13.00	10.00	10.00	13.00
	48	5240	13.00	13.00	10.00	10.00	13.00
802.11n HT40	38	5190	13.00	13.00	10.00	10.00	13.00
	46	5230	13.00	13.00	10.00	10.00	13.00
802.11ac VHT20	36	5180	13.00	13.00	10.00	10.00	13.00
	40	5200	13.00	13.00	10.00	10.00	13.00
	44	5220	13.00	13.00	10.00	10.00	13.00
	48	5240	13.00	13.00	10.00	10.00	13.00
802.11ac VHT40	38	5190	13.00	13.00	10.00	10.00	13.00
	46	5230	13.00	13.00	10.00	10.00	13.00
802.11ac VHT80	42	5210	13.00	13.00	10.00	10.00	13.00
802.11ax HE20	36	5180	13.00	13.00	10.00	10.00	13.00
	40	5200	13.00	13.00	10.00	10.00	13.00
	44	5220	13.00	13.00	10.00	10.00	13.00
	48	5240	13.00	13.00	10.00	10.00	13.00
802.11ax HE40	38	5190	13.00	13.00	10.00	10.00	13.00
	46	5230	13.00	13.00	10.00	10.00	13.00
802.11ax HE80	42	5210	13.00	13.00	10.00	10.00	13.00
802.11be EHT20	36	5180	13.00	13.00	10.00	10.00	13.00
	40	5200	13.00	13.00	10.00	10.00	13.00
	44	5220	13.00	13.00	10.00	10.00	13.00
	48	5240	13.00	13.00	10.00	10.00	13.00
802.11be EHT40	38	5190	13.00	13.00	10.00	10.00	13.00
	46	5230	13.00	13.00	10.00	10.00	13.00
802.11be EHT80	42	5210	13.00	13.00	10.00	10.00	13.00

Tune-up Power (Full)							
WLAN 5.3GHz							
Mode	Channel	Frequency	SISO Ant 1 Max Tune up	SISO Ant 2 Max Tune up	MIMO Ant 1 Tune up	MIMO Ant 2 Tune up	MIMO Ant 1+2 Max Tune up
802.11a	52	5260	13.00	13.00			
	56	5280	13.00	13.00			
	60	5300	13.00	13.00			
	64	5320	13.00	13.00			
802.11n HT20	52	5260	13.00	13.00	10.00	10.00	13.00
	56	5280	13.00	13.00	10.00	10.00	13.00
	60	5300	13.00	13.00	10.00	10.00	13.00
	64	5320	13.00	13.00	10.00	10.00	13.00
802.11n HT40	54	5270	13.00	13.00	10.00	10.00	13.00
	62	5310	13.00	13.00	10.00	10.00	13.00
802.11ac VHT20	52	5260	13.00	13.00	10.00	10.00	13.00
	56	5280	13.00	13.00	10.00	10.00	13.00
	60	5300	13.00	13.00	10.00	10.00	13.00
	64	5320	13.00	13.00	10.00	10.00	13.00
802.11ac VHT40	54	5270	13.00	13.00	10.00	10.00	13.00
	62	5310	13.00	13.00	10.00	10.00	13.00
802.11ac VHT80	58	5290	13.00	13.00	10.00	10.00	13.00
802.11ac VHT160	50	5250	13.00	13.00	10.00	10.00	13.00
802.11ax HE20	52	5260	13.00	13.00	10.00	10.00	13.00
	56	5280	13.00	13.00	10.00	10.00	13.00
	60	5300	13.00	13.00	10.00	10.00	13.00
	64	5320	13.00	13.00	10.00	10.00	13.00
802.11ax HE40	54	5270	13.00	13.00	10.00	10.00	13.00
	62	5310	13.00	13.00	10.00	10.00	13.00
802.11ax HE80	58	5290	13.00	13.00	10.00	10.00	13.00
802.11ax HE160	50	5250	13.00	13.00	10.00	10.00	13.00
802.11be EHT20	52	5260	13.00	13.00	10.00	10.00	13.00
	56	5280	13.00	13.00	10.00	10.00	13.00
	60	5300	13.00	13.00	10.00	10.00	13.00
	64	5320	13.00	13.00	10.00	10.00	13.00
802.11be EHT40	54	5270	13.00	13.00	10.00	10.00	13.00
	62	5310	13.00	13.00	10.00	10.00	13.00
802.11be EHT80	58	5290	13.00	13.00	10.00	10.00	13.00
802.11be EHT160	50	5250	13.00	13.00	10.00	10.00	13.00

Tune-up Power (Full)							
WLAN 5.6GHz							
Mode	Channel	Frequency	SISO Ant 1 Max Tune up	SISO Ant 2 Max Tune up	MIMO Ant 1 Tune up	MIMO Ant 2 Tune up	MIMO Ant 1+2 Max Tune up
802.11a	100	5500	13.50	13.50			
	104	5520	13.50	13.50			
	108	5540	13.50	13.50			
	112	5560	13.50	13.50			
	116	5580	13.50	13.50			
	120	5600	13.50	13.50			
	124	5620	13.50	13.50			
	128	5640	13.50	13.50			
	132	5660	13.50	13.50			
	136	5680	13.50	13.50			
	140	5700	13.50	13.50			
	144	5720	13.50	13.50			
802.11n HT20	100	5500	13.50	13.50	10.50	10.50	13.50
	104	5520	13.50	13.50	10.50	10.50	13.50
	108	5540	13.50	13.50	10.50	10.50	13.50
	112	5560	13.50	13.50	10.50	10.50	13.50
	116	5580	13.50	13.50	10.50	10.50	13.50
	120	5600	13.50	13.50	10.50	10.50	13.50
	124	5620	13.50	13.50	10.50	10.50	13.50
	128	5640	13.50	13.50	10.50	10.50	13.50
	132	5660	13.50	13.50	10.50	10.50	13.50
	136	5680	13.50	13.50	10.50	10.50	13.50
	140	5700	13.50	13.50	10.50	10.50	13.50
	144	5720	13.50	13.50	10.50	10.50	13.50
802.11n HT40	102	5510	13.50	13.50	10.50	10.50	13.50
	110	5550	13.50	13.50	10.50	10.50	13.50
	118	5590	13.50	13.50	10.50	10.50	13.50
	126	5630	13.50	13.50	10.50	10.50	13.50
	134	5670	13.50	13.50	10.50	10.50	13.50
	142	5710	13.50	13.50	10.50	10.50	13.50
	150	5750	13.50	13.50	10.50	10.50	13.50
802.11ac VHT20	100	5500	13.50	13.50	10.50	10.50	13.50
	104	5520	13.50	13.50	10.50	10.50	13.50
	108	5540	13.50	13.50	10.50	10.50	13.50
	112	5560	13.50	13.50	10.50	10.50	13.50
	116	5580	13.50	13.50	10.50	10.50	13.50
	120	5600	13.50	13.50	10.50	10.50	13.50
	124	5620	13.50	13.50	10.50	10.50	13.50
	128	5640	13.50	13.50	10.50	10.50	13.50
	132	5660	13.50	13.50	10.50	10.50	13.50
	136	5680	13.50	13.50	10.50	10.50	13.50
	140	5700	13.50	13.50	10.50	10.50	13.50
	144	5720	13.50	13.50	10.50	10.50	13.50
802.11ac VHT40	102	5510	13.50	13.50	10.50	10.50	13.50
	110	5550	13.50	13.50	10.50	10.50	13.50
	118	5590	13.50	13.50	10.50	10.50	13.50
	126	5630	13.50	13.50	10.50	10.50	13.50
	134	5670	13.50	13.50	10.50	10.50	13.50
	142	5710	13.50	13.50	10.50	10.50	13.50
	150	5750	13.50	13.50	10.50	10.50	13.50
802.11ac VHT80	106	5530	13.50	13.50	10.50	10.50	13.50
	122	5610	13.50	13.50	10.50	10.50	13.50
	138	5690	13.50	13.50	10.50	10.50	13.50
802.11ac VHT160	114	5570	13.50	13.50	10.50	10.50	13.50
802.11ax HE20	100	5500	13.50	13.50	10.50	10.50	13.50
	104	5520	13.50	13.50	10.50	10.50	13.50
	108	5540	13.50	13.50	10.50	10.50	13.50
	112	5560	13.50	13.50	10.50	10.50	13.50
	116	5580	13.50	13.50	10.50	10.50	13.50
	120	5600	13.50	13.50	10.50	10.50	13.50
	124	5620	13.50	13.50	10.50	10.50	13.50
	128	5640	13.50	13.50	10.50	10.50	13.50
	132	5660	13.50	13.50	10.50	10.50	13.50
	136	5680	13.50	13.50	10.50	10.50	13.50
	140	5700	13.50	13.50	10.50	10.50	13.50
	144	5720	13.50	13.50	10.50	10.50	13.50
802.11ax HE40	102	5510	13.50	13.50	10.50	10.50	13.50
	110	5550	13.50	13.50	10.50	10.50	13.50
	118	5590	13.50	13.50	10.50	10.50	13.50
	126	5630	13.50	13.50	10.50	10.50	13.50
	134	5670	13.50	13.50	10.50	10.50	13.50
	142	5710	13.50	13.50	10.50	10.50	13.50
	150	5750	13.50	13.50	10.50	10.50	13.50
802.11ax HE80	106	5530	13.50	13.50	10.50	10.50	13.50
	122	5610	13.50	13.50	10.50	10.50	13.50
	138	5690	13.50	13.50	10.50	10.50	13.50
802.11ax HE160	114	5570	13.50	13.50	10.50	10.50	13.50
802.11be EHT20	100	5500	13.50	13.50	10.50	10.50	13.50
	104	5520	13.50	13.50	10.50	10.50	13.50
	108	5540	13.50	13.50	10.50	10.50	13.50
	112	5560	13.50	13.50	10.50	10.50	13.50
	116	5580	13.50	13.50	10.50	10.50	13.50
	120	5600	13.50	13.50	10.50	10.50	13.50
	124	5620	13.50	13.50	10.50	10.50	13.50
	128	5640	13.50	13.50	10.50	10.50	13.50
	132	5660	13.50	13.50	10.50	10.50	13.50
	136	5680	13.50	13.50	10.50	10.50	13.50
	140	5700	13.50	13.50	10.50	10.50	13.50
	144	5720	13.50	13.50	10.50	10.50	13.50
802.11be EHT40	102	5510	13.50	13.50	10.50	10.50	13.50
	110	5550	13.50	13.50	10.50	10.50	13.50
	118	5590	13.50	13.50	10.50	10.50	13.50
	126	5630	13.50	13.50	10.50	10.50	13.50
	134	5670	13.50	13.50	10.50	10.50	13.50
	142	5710	13.50	13.50	10.50	10.50	13.50
	150	5750	13.50	13.50	10.50	10.50	13.50
802.11be EHT80	106	5530	13.50	13.50	10.50	10.50	13.50
	122	5610	13.50	13.50	10.50	10.50	13.50
	138	5690	13.50	13.50	10.50	10.50	13.50
802.11be EHT160	114	5570	13.50	13.50	10.50	10.50	13.50

Tune-up Power (Full)							
WLAN 5.8GHz							
Mode	Channel	Frequency	SISO Ant 1 Max Tune up	SISO Ant 2 Max Tune up	MIMO Ant 1 Tune up	MIMO Ant 2 Tune up	MIMO Ant 1+2 Max Tune up
802.11a	149	5745	14.00	14.00			
	153	5765	14.00	14.00			
	157	5785	14.00	14.00			
	161	5805	14.00	14.00			
	165	5825	14.00	14.00			
802.11n HT20	149	5745	14.00	14.00	11.00	11.00	14.00
	153	5765	14.00	14.00	11.00	11.00	14.00
	157	5785	14.00	14.00	11.00	11.00	14.00
	161	5805	14.00	14.00	11.00	11.00	14.00
	165	5825	14.00	14.00	11.00	11.00	14.00
802.11n HT40	151	5755	14.00	14.00	11.00	11.00	14.00
	159	5795	14.00	14.00	11.00	11.00	14.00
	149	5745	14.00	14.00	11.00	11.00	14.00
802.11ac VHT20	153	5765	14.00	14.00	11.00	11.00	14.00
	157	5785	14.00	14.00	11.00	11.00	14.00
	161	5805	14.00	14.00	11.00	11.00	14.00
	165	5825	14.00	14.00	11.00	11.00	14.00
	151	5755	14.00	14.00	11.00	11.00	14.00
802.11ac VHT40	159	5795	14.00	14.00	11.00	11.00	14.00
802.11ac VHT80	155	5775	14.00	14.00	11.00	11.00	14.00
802.11ax HE20	149	5745	14.00	14.00	11.00	11.00	14.00
	153	5765	14.00	14.00	11.00	11.00	14.00
	157	5785	14.00	14.00	11.00	11.00	14.00
	161	5805	14.00	14.00	11.00	11.00	14.00
	165	5825	14.00	14.00	11.00	11.00	14.00
802.11ax HE40	151	5755	14.00	14.00	11.00	11.00	14.00
	159	5795	14.00	14.00	11.00	11.00	14.00
802.11ax HE80	155	5775	14.00	14.00	11.00	11.00	14.00
802.11be EHT20	149	5745	14.00	14.00	11.00	11.00	14.00
	153	5765	14.00	14.00	11.00	11.00	14.00
	157	5785	14.00	14.00	11.00	11.00	14.00
	161	5805	14.00	14.00	11.00	11.00	14.00
	165	5825	14.00	14.00	11.00	11.00	14.00
802.11be EHT40	151	5755	14.00	14.00	11.00	11.00	14.00
	159	5795	14.00	14.00	11.00	11.00	14.00
802.11be EHT80	155	5775	14.00	14.00	11.00	11.00	14.00

Tune-up Power (Full)							
WLAN 5.9GHz							
Mode	Channel	Frequency	SISO Ant 1 Max Tune up	SISO Ant 2 Max Tune up	MIMO Ant 1 Tune up	MIMO Ant 2 Tune up	MIMO Ant 1+2 Max Tune up
802.11a	169	5845	14.00	14.00			
	173	5865	14.00	14.00			
	177	5885	14.00	14.00			
802.11n HT20	169	5845	14.00	14.00	11.00	11.00	14.00
	173	5865	14.00	14.00	11.00	11.00	14.00
	177	5885	14.00	14.00	11.00	11.00	14.00
802.11n HT40	167	5835	14.00	14.00	11.00	11.00	14.00
	175	5875	14.00	14.00	11.00	11.00	14.00
	169	5845	14.00	14.00	11.00	11.00	14.00
802.11ac VHT20	173	5865	14.00	14.00	11.00	11.00	14.00
	177	5885	14.00	14.00	11.00	11.00	14.00
	167	5835	14.00	14.00	11.00	11.00	14.00
802.11ac VHT40	175	5875	14.00	14.00	11.00	11.00	14.00
	171	5855	14.00	14.00	11.00	11.00	14.00
	163	5815	14.00	14.00	11.00	11.00	14.00
802.11ac VHT80	169	5845	14.00	14.00	11.00	11.00	14.00
	173	5865	14.00	14.00	11.00	11.00	14.00
	177	5885	14.00	14.00	11.00	11.00	14.00
802.11ac VHT160	167	5835	14.00	14.00	11.00	11.00	14.00
	175	5875	14.00	14.00	11.00	11.00	14.00
	171	5855	14.00	14.00	11.00	11.00	14.00
802.11ax HE20	169	5845	14.00	14.00	11.00	11.00	14.00
	173	5865	14.00	14.00	11.00	11.00	14.00
	177	5885	14.00	14.00	11.00	11.00	14.00
802.11ax HE40	167	5835	14.00	14.00	11.00	11.00	14.00
	175	5875	14.00	14.00	11.00	11.00	14.00
	171	5855	14.00	14.00	11.00	11.00	14.00
802.11ax HE80	163	5815	14.00	14.00	11.00	11.00	14.00
	169	5845	14.00	14.00	11.00	11.00	14.00
	173	5865	14.00	14.00	11.00	11.00	14.00
802.11ax HE160	177	5885	14.00	14.00	11.00	11.00	14.00
	167	5835	14.00	14.00	11.00	11.00	14.00
	175	5875	14.00	14.00	11.00	11.00	14.00
802.11be EHT20	171	5855	14.00	14.00	11.00	11.00	14.00
	163	5815	14.00	14.00	11.00	11.00	14.00
	169	5845	14.00	14.00	11.00	11.00	14.00
802.11be EHT40	173	5865	14.00	14.00	11.00	11.00	14.00
	177	5885	14.00	14.00	11.00	11.00	14.00
	167	5835	14.00	14.00	11.00	11.00	14.00
802.11be EHT80	175	5875	14.00	14.00	11.00	11.00	14.00
	171	5855	14.00	14.00	11.00	11.00	14.00
	163	5815	14.00	14.00	11.00	11.00	14.00
802.11be EHT160	169	5845	14.00	14.00	11.00	11.00	14.00

Tune-up Power (Full)							
UNII-5 LPI							
Mode	Channel	Frequency	SISO Ant 1 Max Tune up	SISO Ant 2 Max Tune up	MIMO Ant 1 Tune up	MIMO Ant 2 Tune up	MIMO Ant 1+2 Max Tune up
802.11ax HE20	1	5955	6.00	6.00	3.00	3.00	6.00
	5	5975	6.00	6.00	3.00	3.00	6.00
	9	5995	6.00	6.00	3.00	3.00	6.00
	13	6015	6.00	6.00	3.00	3.00	6.00
	17	6035	6.00	6.00	3.00	3.00	6.00
	21	6055	6.00	6.00	3.00	3.00	6.00
	25	6075	6.00	6.00	3.00	3.00	6.00
	29	6095	6.00	6.00	3.00	3.00	6.00
	33	6115	6.00	6.00	3.00	3.00	6.00
	37	6135	6.00	6.00	3.00	3.00	6.00
	41	6155	6.00	6.00	3.00	3.00	6.00
	45	6175	6.00	6.00	3.00	3.00	6.00
	49	6195	6.00	6.00	3.00	3.00	6.00
	53	6215	6.00	6.00	3.00	3.00	6.00
	57	6235	6.00	6.00	3.00	3.00	6.00
	61	6255	6.00	6.00	3.00	3.00	6.00
	65	6275	6.00	6.00	3.00	3.00	6.00
	69	6295	6.00	6.00	3.00	3.00	6.00
	73	6315	6.00	6.00	3.00	3.00	6.00
	77	6335	6.00	6.00	3.00	3.00	6.00
	81	6355	6.00	6.00	3.00	3.00	6.00
	85	6375	6.00	6.00	3.00	3.00	6.00
	89	6395	6.00	6.00	3.00	3.00	6.00
	93	6415	6.00	6.00	3.00	3.00	6.00
802.11ax HE40	3	5965	9.00	9.00	6.00	6.00	9.00
	11	6005	9.00	9.00	6.00	6.00	9.00
	19	6045	9.00	9.00	6.00	6.00	9.00
	27	6085	9.00	9.00	6.00	6.00	9.00
	35	6125	9.00	9.00	6.00	6.00	9.00
	43	6165	9.00	9.00	6.00	6.00	9.00
	51	6205	9.00	9.00	6.00	6.00	9.00
	59	6245	9.00	9.00	6.00	6.00	9.00
	67	6285	9.00	9.00	6.00	6.00	9.00
	75	6325	9.00	9.00	6.00	6.00	9.00
	83	6365	9.00	9.00	6.00	6.00	9.00
	91	6405	9.00	9.00	6.00	6.00	9.00
802.11ax HE80	7	5985	10.50	10.50	7.50	7.50	10.50
	23	6065	10.50	10.50	7.50	7.50	10.50
	39	6145	10.50	10.50	7.50	7.50	10.50
	55	6225	10.50	10.50	7.50	7.50	10.50
	71	6305	10.50	10.50	7.50	7.50	10.50
	87	6385	10.50	10.50	7.50	7.50	10.50
802.11ax HE160	15	6025	10.50	10.50	7.50	7.50	10.50
	47	6185	10.50	10.50	7.50	7.50	10.50
	79	6345	10.50	10.50	7.50	7.50	10.50

Tune-up Power (Full)							
UNII-5 LPI							
Mode	Channel	Frequency	SISO Ant 1 Max Tune up	SISO Ant 2 Max Tune up	MIMO Ant 1 Tune up	MIMO Ant 2 Tune up	MIMO Ant 1+2 Max Tune up
802.11be EHT20	1	5955	6.00	6.00	3.00	3.00	6.00
	5	5975	6.00	6.00	3.00	3.00	6.00
	9	5995	6.00	6.00	3.00	3.00	6.00
	13	6015	6.00	6.00	3.00	3.00	6.00
	17	6035	6.00	6.00	3.00	3.00	6.00
	21	6055	6.00	6.00	3.00	3.00	6.00
	25	6075	6.00	6.00	3.00	3.00	6.00
	29	6095	6.00	6.00	3.00	3.00	6.00
	33	6115	6.00	6.00	3.00	3.00	6.00
	37	6135	6.00	6.00	3.00	3.00	6.00
	41	6155	6.00	6.00	3.00	3.00	6.00
	45	6175	6.00	6.00	3.00	3.00	6.00
	49	6195	6.00	6.00	3.00	3.00	6.00
	53	6215	6.00	6.00	3.00	3.00	6.00
	57	6235	6.00	6.00	3.00	3.00	6.00
	61	6255	6.00	6.00	3.00	3.00	6.00
	65	6275	6.00	6.00	3.00	3.00	6.00
	69	6295	6.00	6.00	3.00	3.00	6.00
	73	6315	6.00	6.00	3.00	3.00	6.00
	77	6335	6.00	6.00	3.00	3.00	6.00
	81	6355	6.00	6.00	3.00	3.00	6.00
	85	6375	6.00	6.00	3.00	3.00	6.00
	89	6395	6.00	6.00	3.00	3.00	6.00
	93	6415	6.00	6.00	3.00	3.00	6.00
802.11be EHT40	3	5965	9.00	9.00	6.00	6.00	9.00
	11	6005	9.00	9.00	6.00	6.00	9.00
	19	6045	9.00	9.00	6.00	6.00	9.00
	27	6085	9.00	9.00	6.00	6.00	9.00
	35	6125	9.00	9.00	6.00	6.00	9.00
	43	6165	9.00	9.00	6.00	6.00	9.00
	51	6205	9.00	9.00	6.00	6.00	9.00
	59	6245	9.00	9.00	6.00	6.00	9.00
	67	6285	9.00	9.00	6.00	6.00	9.00
	75	6325	9.00	9.00	6.00	6.00	9.00
	83	6365	9.00	9.00	6.00	6.00	9.00
	91	6405	9.00	9.00	6.00	6.00	9.00
802.11be EHT80	7	5985	10.50	10.50	7.50	7.50	10.50
	23	6065	10.50	10.50	7.50	7.50	10.50
	39	6145	10.50	10.50	7.50	7.50	10.50
	55	6225	10.50	10.50	7.50	7.50	10.50
	71	6305	10.50	10.50	7.50	7.50	10.50
	87	6385	10.50	10.50	7.50	7.50	10.50
802.11be EHT160	15	6025	10.50	10.50	7.50	7.50	10.50
	47	6185	10.50	10.50	7.50	7.50	10.50
	79	6345	10.50	10.50	7.50	7.50	10.50
802.11be EHT320	31	6105	10.50	10.50	7.50	7.50	10.50
	63	6265	10.50	10.50	7.50	7.50	10.50

Tune-up Power (Full)							
UNII-6 LPI							
Mode	Channel	Frequency	SISO Ant 1 Max Tune up	SISO Ant 2 Max Tune up	MIMO Ant 1 Tune up	MIMO Ant 2 Tune up	MIMO Ant 1+2 Max Tune up
802.11ax HE20	97	6435	6.00	6.00	3.00	3.00	6.00
	101	6455	6.00	6.00	3.00	3.00	6.00
	105	6475	6.00	6.00	3.00	3.00	6.00
	109	6495	6.00	6.00	3.00	3.00	6.00
	113	6515	6.00	6.00	3.00	3.00	6.00
802.11ax HE40	99	6445	9.00	9.00	6.00	6.00	9.00
	107	6485	9.00	9.00	6.00	6.00	9.00
	115	6525	9.00	9.00	6.00	6.00	9.00
802.11ax HE80	103	6465	10.50	10.50	7.50	7.50	10.50
	119	6545	10.50	10.50	7.50	7.50	10.50
802.11ax HE160	111	6505	10.50	10.50	7.50	7.50	10.50
802.11be EHT20	97	6435	6.00	6.00	3.00	3.00	6.00
	101	6455	6.00	6.00	3.00	3.00	6.00
	105	6475	6.00	6.00	3.00	3.00	6.00
	109	6495	6.00	6.00	3.00	3.00	6.00
	113	6515	6.00	6.00	3.00	3.00	6.00
802.11be EHT40	99	6445	9.00	9.00	6.00	6.00	9.00
	107	6485	9.00	9.00	6.00	6.00	9.00
	115	6525	9.00	9.00	6.00	6.00	9.00
802.11be EHT80	103	6465	10.50	10.50	7.50	7.50	10.50
	119	6545	10.50	10.50	7.50	7.50	10.50
802.11be EHT160	111	6505	10.50	10.50	7.50	7.50	10.50
802.11be EHT320	95	6425	10.50	10.50	7.50	7.50	10.50

Tune-up Power (Full)							
UNII-7 LPI							
Mode	Channel	Frequency	SISO Ant 1 Max Tune up	SISO Ant 2 Max Tune up	MIMO Ant 1 Tune up	MIMO Ant 2 Tune up	MIMO Ant 1+2 Max Tune up
802.11ax HE20	117	6535	6.00	6.00	3.00	3.00	6.00
	121	6555	6.00	6.00	3.00	3.00	6.00
	125	6575	6.00	6.00	3.00	3.00	6.00
	129	6595	6.00	6.00	3.00	3.00	6.00
	133	6615	6.00	6.00	3.00	3.00	6.00
	137	6635	6.00	6.00	3.00	3.00	6.00
	141	6655	6.00	6.00	3.00	3.00	6.00
	145	6675	6.00	6.00	3.00	3.00	6.00
	149	6695	6.00	6.00	3.00	3.00	6.00
	153	6715	6.00	6.00	3.00	3.00	6.00
	157	6735	6.00	6.00	3.00	3.00	6.00
	161	6755	6.00	6.00	3.00	3.00	6.00
	165	6775	6.00	6.00	3.00	3.00	6.00
	169	6795	6.00	6.00	3.00	3.00	6.00
	173	6815	6.00	6.00	3.00	3.00	6.00
	177	6835	6.00	6.00	3.00	3.00	6.00
	181	6855	6.00	6.00	3.00	3.00	6.00
	185	6875	6.00	6.00	3.00	3.00	6.00
802.11ax HE40	123	6565	9.00	9.00	6.00	6.00	9.00
	131	6605	9.00	9.00	6.00	6.00	9.00
	139	6645	9.00	9.00	6.00	6.00	9.00
	147	6685	9.00	9.00	6.00	6.00	9.00
	155	6725	9.00	9.00	6.00	6.00	9.00
	163	6765	9.00	9.00	6.00	6.00	9.00
	171	6805	9.00	9.00	6.00	6.00	9.00
	179	6845	9.00	9.00	6.00	6.00	9.00
	187	6885	9.00	9.00	6.00	6.00	9.00
	135	6625	10.50	10.50	7.50	7.50	10.50
802.11ax HE80	151	6705	10.50	10.50	7.50	7.50	10.50
	167	6785	10.50	10.50	7.50	7.50	10.50
	183	6865	10.50	10.50	7.50	7.50	10.50
802.11ax HE160	143	6665	10.50	10.50	7.50	7.50	10.50
	175	6825	10.50	10.50	7.50	7.50	10.50

Tune-up Power (Full)							
UNII-7 LPI							
Mode	Channel	Frequency	SISO Ant 1 Max Tune up	SISO Ant 2 Max Tune up	MIMO Ant 1 Tune up	MIMO Ant 2 Tune up	MIMO Ant 1+2 Max Tune up
802.11be EHT20	117	6535	6.00	6.00	3.00	3.00	6.00
	121	6555	6.00	6.00	3.00	3.00	6.00
	125	6575	6.00	6.00	3.00	3.00	6.00
	129	6595	6.00	6.00	3.00	3.00	6.00
	133	6615	6.00	6.00	3.00	3.00	6.00
	137	6635	6.00	6.00	3.00	3.00	6.00
	141	6655	6.00	6.00	3.00	3.00	6.00
	145	6675	6.00	6.00	3.00	3.00	6.00
	149	6695	6.00	6.00	3.00	3.00	6.00
	153	6715	6.00	6.00	3.00	3.00	6.00
	157	6735	6.00	6.00	3.00	3.00	6.00
	161	6755	6.00	6.00	3.00	3.00	6.00
	165	6775	6.00	6.00	3.00	3.00	6.00
	169	6795	6.00	6.00	3.00	3.00	6.00
	173	6815	6.00	6.00	3.00	3.00	6.00
	177	6835	6.00	6.00	3.00	3.00	6.00
	181	6855	6.00	6.00	3.00	3.00	6.00
	185	6875	6.00	6.00	3.00	3.00	6.00
802.11be EHT40	123	6565	9.00	9.00	6.00	6.00	9.00
	131	6605	9.00	9.00	6.00	6.00	9.00
	139	6645	9.00	9.00	6.00	6.00	9.00
	147	6685	9.00	9.00	6.00	6.00	9.00
	155	6725	9.00	9.00	6.00	6.00	9.00
	163	6765	9.00	9.00	6.00	6.00	9.00
	171	6805	9.00	9.00	6.00	6.00	9.00
	179	6845	9.00	9.00	6.00	6.00	9.00
	187	6885	9.00	9.00	6.00	6.00	9.00
802.11be EHT80	135	6625	10.50	10.50	7.50	7.50	10.50
	151	6705	10.50	10.50	7.50	7.50	10.50
	167	6785	10.50	10.50	7.50	7.50	10.50
	183	6865	10.50	10.50	7.50	7.50	10.50
802.11be EHT160	143	6665	10.50	10.50	7.50	7.50	10.50
	175	6825	10.50	10.50	7.50	7.50	10.50
802.11be EHT320	127	6585	10.50	10.50	7.50	7.50	10.50
	159	6745	10.50	10.50	7.50	7.50	10.50

Tune-up Power (Full)							
UNII-8 LPI							
Mode	Channel	Frequency	SISO Ant 1 Max Tune up	SISO Ant 2 Max Tune up	MIMO Ant 1 Tune up	MIMO Ant 2 Tune up	MIMO Ant 1+2 Max Tune up
802.11ax HE20	189	6895	6.00	6.00	3.00	3.00	6.00
	193	6915	6.00	6.00	3.00	3.00	6.00
	197	6935	6.00	6.00	3.00	3.00	6.00
	201	6955	6.00	6.00	3.00	3.00	6.00
	205	6975	6.00	6.00	3.00	3.00	6.00
	209	6995	6.00	6.00	3.00	3.00	6.00
	213	7015	6.00	6.00	3.00	3.00	6.00
	217	7035	6.00	6.00	3.00	3.00	6.00
	221	7055	6.00	6.00	3.00	3.00	6.00
	225	7075	6.00	6.00	3.00	3.00	6.00
	229	7095	6.00	6.00	3.00	3.00	6.00
	233	7115	-2.00	-2.00	-5.00	-5.00	-2.00
	195	6925	9.00	9.00	6.00	6.00	9.00
802.11ax HE40	203	6965	9.00	9.00	6.00	6.00	9.00
	211	7005	9.00	9.00	6.00	6.00	9.00
	219	7045	9.00	9.00	6.00	6.00	9.00
	227	7085	9.00	9.00	6.00	6.00	9.00
	199	6945	10.50	10.50	7.50	7.50	10.50
802.11ax HE80	215	7025	10.50	10.50	7.50	7.50	10.50
802.11ax HE160	207	6985	10.50	10.50	7.50	7.50	10.50
802.11be EHT20	189	6895	6.00	6.00	3.00	3.00	6.00
	193	6915	6.00	6.00	3.00	3.00	6.00
	197	6935	6.00	6.00	3.00	3.00	6.00
	201	6955	6.00	6.00	3.00	3.00	6.00
	205	6975	6.00	6.00	3.00	3.00	6.00
	209	6995	6.00	6.00	3.00	3.00	6.00
	213	7015	6.00	6.00	3.00	3.00	6.00
	217	7035	6.00	6.00	3.00	3.00	6.00
	221	7055	6.00	6.00	3.00	3.00	6.00
	225	7075	6.00	6.00	3.00	3.00	6.00
	229	7095	6.00	6.00	3.00	3.00	6.00
	233	7115	-2.00	-2.00	-5.00	-5.00	-2.00
	195	6925	9.00	9.00	6.00	6.00	9.00
802.11be EHT40	203	6965	9.00	9.00	6.00	6.00	9.00
	211	7005	9.00	9.00	6.00	6.00	9.00
	219	7045	9.00	9.00	6.00	6.00	9.00
	227	7085	9.00	9.00	6.00	6.00	9.00
	199	6945	10.50	10.50	7.50	7.50	10.50
802.11be EHT80	215	7025	10.50	10.50	7.50	7.50	10.50
802.11be EHT160	207	6985	10.50	10.50	7.50	7.50	10.50
802.11be EHT320	191	6905	10.50	10.50	7.50	7.50	10.50

Tune-up Power (Full)							
UNII-5_SP							
Mode	Channel	Frequency	SISO Ant 1 Max Tune up	SISO Ant 2 Max Tune up	MIMO Ant 1 Tune up	MIMO Ant 2 Tune up	MIMO Ant 1+2 Max Tune up
802.11ax HE20	1	5955	10.50	10.50	7.50	7.50	10.50
	5	5975	10.50	10.50	7.50	7.50	10.50
	9	5995	10.50	10.50	7.50	7.50	10.50
	13	6015	10.50	10.50	7.50	7.50	10.50
	17	6035	10.50	10.50	7.50	7.50	10.50
	21	6055	10.50	10.50	7.50	7.50	10.50
	25	6075	10.50	10.50	7.50	7.50	10.50
	29	6095	10.50	10.50	7.50	7.50	10.50
	33	6115	10.50	10.50	7.50	7.50	10.50
	37	6135	10.50	10.50	7.50	7.50	10.50
	41	6155	10.50	10.50	7.50	7.50	10.50
	45	6175	10.50	10.50	7.50	7.50	10.50
	49	6195	10.50	10.50	7.50	7.50	10.50
	53	6215	10.50	10.50	7.50	7.50	10.50
	57	6235	10.50	10.50	7.50	7.50	10.50
	61	6255	10.50	10.50	7.50	7.50	10.50
	65	6275	10.50	10.50	7.50	7.50	10.50
	69	6295	10.50	10.50	7.50	7.50	10.50
	73	6315	10.50	10.50	7.50	7.50	10.50
	77	6335	10.50	10.50	7.50	7.50	10.50
	81	6355	10.50	10.50	7.50	7.50	10.50
802.11ax HE40	85	6375	10.50	10.50	7.50	7.50	10.50
	89	6395	10.50	10.50	7.50	7.50	10.50
	93	6415	10.50	10.50	7.50	7.50	10.50
	3	5965	10.50	10.50	7.50	7.50	10.50
	11	6005	10.50	10.50	7.50	7.50	10.50
	19	6045	10.50	10.50	7.50	7.50	10.50
	27	6085	10.50	10.50	7.50	7.50	10.50
	35	6125	10.50	10.50	7.50	7.50	10.50
	43	6165	10.50	10.50	7.50	7.50	10.50
	51	6205	10.50	10.50	7.50	7.50	10.50
802.11ax HE80	59	6245	10.50	10.50	7.50	7.50	10.50
	67	6285	10.50	10.50	7.50	7.50	10.50
	75	6325	10.50	10.50	7.50	7.50	10.50
	83	6365	10.50	10.50	7.50	7.50	10.50
	91	6405	10.50	10.50	7.50	7.50	10.50
	7	5985	10.50	10.50	7.50	7.50	10.50
802.11ax HE160	23	6065	10.50	10.50	7.50	7.50	10.50
	39	6145	10.50	10.50	7.50	7.50	10.50
	55	6225	10.50	10.50	7.50	7.50	10.50
	71	6305	10.50	10.50	7.50	7.50	10.50
	87	6385	10.50	10.50	7.50	7.50	10.50
802.11ax HE160	15	6025	10.50	10.50	7.50	7.50	10.50
	47	6185	10.50	10.50	7.50	7.50	10.50
	79	6345	10.50	10.50	7.50	7.50	10.50

Tune-up Power (Full)							
UNII-5_SP							
Mode	Channel	Frequency	SISO Ant 1 Max Tune up	SISO Ant 2 Max Tune up	MIMO Ant 1 Tune up	MIMO Ant 2 Tune up	MIMO Ant 1+2 Max Tune up
802.11be EHT20	1	5955	10.50	10.50	7.50	7.50	10.50
	5	5975	10.50	10.50	7.50	7.50	10.50
	9	5995	10.50	10.50	7.50	7.50	10.50
	13	6015	10.50	10.50	7.50	7.50	10.50
	17	6035	10.50	10.50	7.50	7.50	10.50
	21	6055	10.50	10.50	7.50	7.50	10.50
	25	6075	10.50	10.50	7.50	7.50	10.50
	29	6095	10.50	10.50	7.50	7.50	10.50
	33	6115	10.50	10.50	7.50	7.50	10.50
	37	6135	10.50	10.50	7.50	7.50	10.50
	41	6155	10.50	10.50	7.50	7.50	10.50
	45	6175	10.50	10.50	7.50	7.50	10.50
	49	6195	10.50	10.50	7.50	7.50	10.50
	53	6215	10.50	10.50	7.50	7.50	10.50
	57	6235	10.50	10.50	7.50	7.50	10.50
	61	6255	10.50	10.50	7.50	7.50	10.50
	65	6275	10.50	10.50	7.50	7.50	10.50
	69	6295	10.50	10.50	7.50	7.50	10.50
	73	6315	10.50	10.50	7.50	7.50	10.50
	77	6335	10.50	10.50	7.50	7.50	10.50
	81	6355	10.50	10.50	7.50	7.50	10.50
802.11be EHT40	85	6375	10.50	10.50	7.50	7.50	10.50
	89	6395	10.50	10.50	7.50	7.50	10.50
	93	6415	10.50	10.50	7.50	7.50	10.50
	3	5965	10.50	10.50	7.50	7.50	10.50
	11	6005	10.50	10.50	7.50	7.50	10.50
	19	6045	10.50	10.50	7.50	7.50	10.50
	27	6085	10.50	10.50	7.50	7.50	10.50
	35	6125	10.50	10.50	7.50	7.50	10.50
	43	6165	10.50	10.50	7.50	7.50	10.50
	51	6205	10.50	10.50	7.50	7.50	10.50
802.11be EHT80	59	6245	10.50	10.50	7.50	7.50	10.50
	67	6285	10.50	10.50	7.50	7.50	10.50
	75	6325	10.50	10.50	7.50	7.50	10.50
	83	6365	10.50	10.50	7.50	7.50	10.50
	91	6405	10.50	10.50	7.50	7.50	10.50
	7	5985	10.50	10.50	7.50	7.50	10.50
802.11be EHT160	23	6065	10.50	10.50	7.50	7.50	10.50
	39	6145	10.50	10.50	7.50	7.50	10.50
	55	6225	10.50	10.50	7.50	7.50	10.50
	71	6305	10.50	10.50	7.50	7.50	10.50
	87	6385	10.50	10.50	7.50	7.50	10.50
802.11be EHT320	15	6025	10.50	10.50	7.50	7.50	10.50
	47	6185	10.50	10.50	7.50	7.50	10.50
802.11be EHT320	79	6345	10.50	10.50	7.50	7.50	10.50
	31	6105	10.50	10.50	7.50	7.50	10.50
802.11be EHT320	63	6265	10.50	10.50	7.50	7.50	10.50

Tune-up Power (Full)							
UNII-7_SP							
Mode	Channel	Frequency	SISO Ant 1 Max Tune up	SISO Ant 2 Max Tune up	MIMO Ant 1 Tune up	MIMO Ant 2 Tune up	MIMO Ant 1+2 Max Tune up
802.11ax HE20	117	6535	10.50	10.50	7.50	7.50	10.50
	121	6555	10.50	10.50	7.50	7.50	10.50
	125	6575	10.50	10.50	7.50	7.50	10.50
	129	6595	10.50	10.50	7.50	7.50	10.50
	133	6615	10.50	10.50	7.50	7.50	10.50
	137	6635	10.50	10.50	7.50	7.50	10.50
	141	6655	10.50	10.50	7.50	7.50	10.50
	145	6675	10.50	10.50	7.50	7.50	10.50
	149	6695	10.50	10.50	7.50	7.50	10.50
	153	6715	10.50	10.50	7.50	7.50	10.50
	157	6735	10.50	10.50	7.50	7.50	10.50
	161	6755	10.50	10.50	7.50	7.50	10.50
	165	6775	10.50	10.50	7.50	7.50	10.50
	169	6795	10.50	10.50	7.50	7.50	10.50
	173	6815	10.50	10.50	7.50	7.50	10.50
	177	6835	10.50	10.50	7.50	7.50	10.50
802.11ax HE40	181	6855	10.50	10.50	7.50	7.50	10.50
	123	6565	10.50	10.50	7.50	7.50	10.50
	131	6605	10.50	10.50	7.50	7.50	10.50
	139	6645	10.50	10.50	7.50	7.50	10.50
	147	6685	10.50	10.50	7.50	7.50	10.50
	155	6725	10.50	10.50	7.50	7.50	10.50
	163	6765	10.50	10.50	7.50	7.50	10.50
802.11ax HE80	171	6805	10.50	10.50	7.50	7.50	10.50
	179	6845	10.50	10.50	7.50	7.50	10.50
	135	6625	10.50	10.50	7.50	7.50	10.50
802.11ax HE160	151	6705	10.50	10.50	7.50	7.50	10.50
	167	6785	10.50	10.50	7.50	7.50	10.50
	143	6665	10.50	10.50	7.50	7.50	10.50

Tune-up Power (Full)							
UNII-7_SP							
Mode	Channel	Frequency	SISO Ant 1 Max Tune up	SISO Ant 2 Max Tune up	MIMO Ant 1 Tune up	MIMO Ant 2 Tune up	MIMO Ant 1+2 Max Tune up
802.11be EHT20	117	6535	10.50	10.50	7.50	7.50	10.50
	121	6555	10.50	10.50	7.50	7.50	10.50
	125	6575	10.50	10.50	7.50	7.50	10.50
	129	6595	10.50	10.50	7.50	7.50	10.50
	133	6615	10.50	10.50	7.50	7.50	10.50
	137	6635	10.50	10.50	7.50	7.50	10.50
	141	6655	10.50	10.50	7.50	7.50	10.50
	145	6675	10.50	10.50	7.50	7.50	10.50
	149	6695	10.50	10.50	7.50	7.50	10.50
	153	6715	10.50	10.50	7.50	7.50	10.50
	157	6735	10.50	10.50	7.50	7.50	10.50
	161	6755	10.50	10.50	7.50	7.50	10.50
	165	6775	10.50	10.50	7.50	7.50	10.50
	169	6795	10.50	10.50	7.50	7.50	10.50
	173	6815	10.50	10.50	7.50	7.50	10.50
	177	6835	10.50	10.50	7.50	7.50	10.50
802.11be EHT40	181	6855	10.50	10.50	7.50	7.50	10.50
	123	6565	10.50	10.50	7.50	7.50	10.50
	131	6605	10.50	10.50	7.50	7.50	10.50
	139	6645	10.50	10.50	7.50	7.50	10.50
	147	6685	10.50	10.50	7.50	7.50	10.50
	155	6725	10.50	10.50	7.50	7.50	10.50
	163	6765	10.50	10.50	7.50	7.50	10.50
802.11be EHT80	171	6805	10.50	10.50	7.50	7.50	10.50
	179	6845	10.50	10.50	7.50	7.50	10.50
	135	6625	10.50	10.50	7.50	7.50	10.50
802.11be EHT160	151	6705	10.50	10.50	7.50	7.50	10.50
	167	6785	10.50	10.50	7.50	7.50	10.50
802.11be EHT320	143	6665	10.50	10.50	7.50	7.50	10.50
	127	6585	10.50	10.50	7.50	7.50	10.50
	159	6745	10.50	10.50	7.50	7.50	10.50

Tune-up Power (Full)							
UNII-5 VLP							
Mode	Channel	Frequency	SISO Ant 1 Max Tune up	SISO Ant 2 Max Tune up	MIMO Ant 1 Tune up	MIMO Ant 2 Tune up	MIMO Ant 1+2 Max Tune up
802.11ax HE20	1	5955	2.00	2.00	-1.00	-1.00	2.00
	5	5975	2.00	2.00	-1.00	-1.00	2.00
	9	5995	2.00	2.00	-1.00	-1.00	2.00
	13	6015	2.00	2.00	-1.00	-1.00	2.00
	17	6035	2.00	2.00	-1.00	-1.00	2.00
	21	6055	2.00	2.00	-1.00	-1.00	2.00
	25	6075	2.00	2.00	-1.00	-1.00	2.00
	29	6095	2.00	2.00	-1.00	-1.00	2.00
	33	6115	2.00	2.00	-1.00	-1.00	2.00
	37	6135	2.00	2.00	-1.00	-1.00	2.00
	41	6155	2.00	2.00	-1.00	-1.00	2.00
	45	6175	2.00	2.00	-1.00	-1.00	2.00
	49	6195	2.00	2.00	-1.00	-1.00	2.00
	53	6215	2.00	2.00	-1.00	-1.00	2.00
	57	6235	2.00	2.00	-1.00	-1.00	2.00
	61	6255	2.00	2.00	-1.00	-1.00	2.00
	65	6275	2.00	2.00	-1.00	-1.00	2.00
	69	6295	2.00	2.00	-1.00	-1.00	2.00
	73	6315	2.00	2.00	-1.00	-1.00	2.00
	77	6335	2.00	2.00	-1.00	-1.00	2.00
	81	6355	2.00	2.00	-1.00	-1.00	2.00
802.11ax HE40	85	6375	2.00	2.00	-1.00	-1.00	2.00
	89	6395	2.00	2.00	-1.00	-1.00	2.00
	93	6415	2.00	2.00	-1.00	-1.00	2.00
	3	5965	5.00	5.00	2.00	2.00	5.00
	11	6005	5.00	5.00	2.00	2.00	5.00
	19	6045	5.00	5.00	2.00	2.00	5.00
	27	6085	5.00	5.00	2.00	2.00	5.00
	35	6125	5.00	5.00	2.00	2.00	5.00
	43	6165	5.00	5.00	2.00	2.00	5.00
	51	6205	5.00	5.00	2.00	2.00	5.00
802.11ax HE80	59	6245	5.00	5.00	2.00	2.00	5.00
	67	6285	5.00	5.00	2.00	2.00	5.00
	75	6325	5.00	5.00	2.00	2.00	5.00
	83	6365	5.00	5.00	2.00	2.00	5.00
	91	6405	5.00	5.00	2.00	2.00	5.00
	7	5985	8.00	8.00	5.00	5.00	8.00
802.11ax HE160	23	6065	8.00	8.00	5.00	5.00	8.00
	39	6145	8.00	8.00	5.00	5.00	8.00
	55	6225	8.00	8.00	5.00	5.00	8.00
	71	6305	8.00	8.00	5.00	5.00	8.00
	87	6385	8.00	8.00	5.00	5.00	8.00
802.11ax HE160	15	6025	9.00	9.00	6.00	6.00	9.00
	47	6185	9.00	9.00	6.00	6.00	9.00
	79	6345	9.00	9.00	6.00	6.00	9.00

Tune-up Power (Full)							
UNII-5 VLP							
Mode	Channel	Frequency	SISO Ant 1 Max Tune up	SISO Ant 2 Max Tune up	MIMO Ant 1 Tune up	MIMO Ant 2 Tune up	MIMO Ant 1+2 Max Tune up
802.11be EHT20	1	5955	2.00	2.00	-1.00	-1.00	2.00
	5	5975	2.00	2.00	-1.00	-1.00	2.00
	9	5995	2.00	2.00	-1.00	-1.00	2.00
	13	6015	2.00	2.00	-1.00	-1.00	2.00
	17	6035	2.00	2.00	-1.00	-1.00	2.00
	21	6055	2.00	2.00	-1.00	-1.00	2.00
	25	6075	2.00	2.00	-1.00	-1.00	2.00
	29	6095	2.00	2.00	-1.00	-1.00	2.00
	33	6115	2.00	2.00	-1.00	-1.00	2.00
	37	6135	2.00	2.00	-1.00	-1.00	2.00
	41	6155	2.00	2.00	-1.00	-1.00	2.00
	45	6175	2.00	2.00	-1.00	-1.00	2.00
	49	6195	2.00	2.00	-1.00	-1.00	2.00
	53	6215	2.00	2.00	-1.00	-1.00	2.00
	57	6235	2.00	2.00	-1.00	-1.00	2.00
	61	6255	2.00	2.00	-1.00	-1.00	2.00
	65	6275	2.00	2.00	-1.00	-1.00	2.00
	69	6295	2.00	2.00	-1.00	-1.00	2.00
	73	6315	2.00	2.00	-1.00	-1.00	2.00
	77	6335	2.00	2.00	-1.00	-1.00	2.00
	81	6355	2.00	2.00	-1.00	-1.00	2.00
802.11be EHT40	85	6375	2.00	2.00	-1.00	-1.00	2.00
	89	6395	2.00	2.00	-1.00	-1.00	2.00
	93	6415	2.00	2.00	-1.00	-1.00	2.00
	3	5965	5.00	5.00	2.00	2.00	5.00
	11	6005	5.00	5.00	2.00	2.00	5.00
	19	6045	5.00	5.00	2.00	2.00	5.00
	27	6085	5.00	5.00	2.00	2.00	5.00
	35	6125	5.00	5.00	2.00	2.00	5.00
	43	6165	5.00	5.00	2.00	2.00	5.00
	51	6205	5.00	5.00	2.00	2.00	5.00
802.11be EHT80	59	6245	5.00	5.00	2.00	2.00	5.00
	67	6285	5.00	5.00	2.00	2.00	5.00
	75	6325	5.00	5.00	2.00	2.00	5.00
	83	6365	5.00	5.00	2.00	2.00	5.00
	91	6405	5.00	5.00	2.00	2.00	5.00
	7	5985	8.00	8.00	5.00	5.00	8.00
802.11be EHT160	23	6065	8.00	8.00	5.00	5.00	8.00
	39	6145	8.00	8.00	5.00	5.00	8.00
	55	6225	8.00	8.00	5.00	5.00	8.00
	71	6305	8.00	8.00	5.00	5.00	8.00
	87	6385	8.00	8.00	5.00	5.00	8.00
802.11be EHT320	15	6025	9.00	9.00	6.00	6.00	9.00
	47	6185	9.00	9.00	6.00	6.00	9.00
	79	6345	9.00	9.00	6.00	6.00	9.00
802.11be EHT320	31	6105	9.00	9.00	6.00	6.00	9.00
	63	6265	9.00	9.00	6.00	6.00	9.00

Tune-up Power (Full)							
UNII-7 VLP							
Mode	Channel	Frequency	SISO Ant 1 Max Tune up	SISO Ant 2 Max Tune up	MIMO Ant 1 Tune up	MIMO Ant 2 Tune up	MIMO Ant 1+2 Max Tune up
802.11ax HE20	117	6535	2.00	2.00	-1.00	-1.00	2.00
	121	6555	2.00	2.00	-1.00	-1.00	2.00
	125	6575	2.00	2.00	-1.00	-1.00	2.00
	129	6595	2.00	2.00	-1.00	-1.00	2.00
	133	6615	2.00	2.00	-1.00	-1.00	2.00
	137	6635	2.00	2.00	-1.00	-1.00	2.00
	141	6655	2.00	2.00	-1.00	-1.00	2.00
	145	6675	2.00	2.00	-1.00	-1.00	2.00
	149	6695	2.00	2.00	-1.00	-1.00	2.00
	153	6715	2.00	2.00	-1.00	-1.00	2.00
	157	6735	2.00	2.00	-1.00	-1.00	2.00
	161	6755	2.00	2.00	-1.00	-1.00	2.00
	165	6775	2.00	2.00	-1.00	-1.00	2.00
	169	6795	2.00	2.00	-1.00	-1.00	2.00
	173	6815	2.00	2.00	-1.00	-1.00	2.00
802.11ax HE40	177	6835	2.00	2.00	-1.00	-1.00	2.00
	181	6855	2.00	2.00	-1.00	-1.00	2.00
	123	6565	5.00	5.00	2.00	2.00	5.00
	131	6605	5.00	5.00	2.00	2.00	5.00
	139	6645	5.00	5.00	2.00	2.00	5.00
	147	6685	5.00	5.00	2.00	2.00	5.00
	155	6725	5.00	5.00	2.00	2.00	5.00
802.11ax HE80	163	6765	5.00	5.00	2.00	2.00	5.00
	171	6805	5.00	5.00	2.00	2.00	5.00
	179	6845	5.00	5.00	2.00	2.00	5.00
802.11ax HE160	135	6625	8.00	8.00	5.00	5.00	8.00
	151	6705	8.00	8.00	5.00	5.00	8.00
	167	6785	8.00	8.00	5.00	5.00	8.00
802.11ax HE160	143	6665	9.00	9.00	6.00	6.00	9.00

Tune-up Power (Full)							
UNII-7 VLP							
Mode	Channel	Frequency	SISO Ant 1 Max Tune up	SISO Ant 2 Max Tune up	MIMO Ant 1 Tune up	MIMO Ant 2 Tune up	MIMO Ant 1+2 Max Tune up
802.11be EHT20	117	6535	2.00	2.00	-1.00	-1.00	2.00
	121	6555	2.00	2.00	-1.00	-1.00	2.00
	125	6575	2.00	2.00	-1.00	-1.00	2.00
	129	6595	2.00	2.00	-1.00	-1.00	2.00
	133	6615	2.00	2.00	-1.00	-1.00	2.00
	137	6635	2.00	2.00	-1.00	-1.00	2.00
	141	6655	2.00	2.00	-1.00	-1.00	2.00
	145	6675	2.00	2.00	-1.00	-1.00	2.00
	149	6695	2.00	2.00	-1.00	-1.00	2.00
	153	6715	2.00	2.00	-1.00	-1.00	2.00
	157	6735	2.00	2.00	-1.00	-1.00	2.00
	161	6755	2.00	2.00	-1.00	-1.00	2.00
	165	6775	2.00	2.00	-1.00	-1.00	2.00
	169	6795	2.00	2.00	-1.00	-1.00	2.00
	173	6815	2.00	2.00	-1.00	-1.00	2.00
	177	6835	2.00	2.00	-1.00	-1.00	2.00
802.11be EHT40	181	6855	2.00	2.00	-1.00	-1.00	2.00
	123	6565	5.00	5.00	2.00	2.00	5.00
	131	6605	5.00	5.00	2.00	2.00	5.00
	139	6645	5.00	5.00	2.00	2.00	5.00
	147	6685	5.00	5.00	2.00	2.00	5.00
	155	6725	5.00	5.00	2.00	2.00	5.00
	163	6765	5.00	5.00	2.00	2.00	5.00
802.11be EHT80	171	6805	5.00	5.00	2.00	2.00	5.00
	179	6845	5.00	5.00	2.00	2.00	5.00
	135	6625	8.00	8.00	5.00	5.00	8.00
802.11be EHT160	151	6705	8.00	8.00	5.00	5.00	8.00
	167	6785	8.00	8.00	5.00	5.00	8.00
802.11be EHT320	143	6665	9.00	9.00	6.00	6.00	9.00
	127	6585	9.00	9.00	6.00	6.00	9.00
	159	6745	9.00	9.00	6.00	6.00	9.00

Appendix E. Measured Conducted Power Result

The measuring conducted power (Unit: dBm) are shown as below.

Conducted Power (Full)			
WLAN2.4GHz Ant 1			
Mode	Channel	Frequency	SISO Ant 0 Avg. Power
802.11b	1	2412	16.75
	6	2437	16.74
	11	2462	16.82
	12	2467	16.89
	13	2472	16.93
802.11g	1	2412	16.74
	6	2437	16.64
	11	2462	16.71
	12	2467	15.42
	13	2472	13.87
802.11n HT20	1	2412	16.60
	6	2437	16.59
	11	2462	16.65
	12	2467	12.97
	13	2472	12.31
802.11n HT40	3	2422	16.69
	6	2437	16.73
	9	2452	16.81
	10	2457	12.80
	11	2462	12.64
802.11ax HE20	1	2412	16.53
	6	2437	16.52
	11	2462	16.61
	12	2467	13.01
	13	2472	12.34
802.11ax HE40	3	2422	16.64
	6	2437	16.68
	9	2452	16.71
	10	2457	12.82
	11	2462	12.67
802.11be EHT20	1	2412	16.56
	6	2437	16.43
	11	2462	16.56
	12	2467	13.02
	13	2472	12.36
802.11be EHT40	3	2422	16.63
	6	2437	16.71
	9	2452	16.73
	10	2457	12.86
	11	2462	12.68

Conducted Power (Full)			
WLAN2.4GHz Ant 2			
Mode	Channel	Frequency	SISO Ant 1 Avg. Power
802.11b	1	2412	16.65
	6	2437	16.78
	11	2462	16.76
	12	2467	16.91
	13	2472	16.96
802.11g	1	2412	16.66
	6	2437	16.78
	11	2462	16.79
	12	2467	16.48
	13	2472	14.93
802.11n HT20	1	2412	16.59
	6	2437	16.69
	11	2462	16.69
	12	2467	16.34
	13	2472	13.23
802.11n HT40	3	2422	16.83
	6	2437	16.72
	9	2452	16.73
	10	2457	14.86
	11	2462	15.66
802.11ax HE20	1	2412	16.49
	6	2437	16.62
	11	2462	16.54
	12	2467	16.18
	13	2472	13.27
802.11ax HE40	3	2422	16.71
	6	2437	16.60
	9	2452	16.61
	10	2457	15.67
	11	2462	13.94
802.11be EHT20	1	2412	16.41
	6	2437	16.56
	11	2462	16.54
	12	2467	16.24
	13	2472	13.30
802.11be EHT40	3	2422	16.77
	6	2437	16.57
	9	2452	16.56
	10	2457	15.70
	11	2462	13.96

Conducted Power (Full)					
WLAN2.4GHz Ant 1+2					
Mode	Channel	Frequency	MIMO Ant 1 Avg. Power	MIMO Ant 2 Avg. Power	MIMO Ant 1+2 Avg. Power
802.11b	1	2412			
	6	2437			
	11	2462			
	12	2467			
	13	2472			
802.11g	1	2412			
	6	2437			
	11	2462			
	12	2467			
	13	2472			
802.11n HT20	1	2412	13.57	13.66	16.62
	6	2437	13.57	13.72	16.66
	11	2462	13.58	13.64	16.62
	12	2467	9.80	9.83	12.83
	13	2472	8.72	8.81	11.78
802.11n HT40	3	2422	13.69	13.89	16.80
	6	2437	13.72	13.71	16.73
	9	2452	13.78	13.72	16.76
	10	2457	11.95	11.83	14.90
	11	2462	12.56	12.71	15.65
802.11ax HE20	1	2412	13.57	13.54	16.57
	6	2437	13.44	13.67	16.57
	11	2462	13.54	13.56	16.56
	12	2467	9.87	9.81	12.85
	13	2472	8.70	8.80	11.76
802.11ax HE40	3	2422	13.67	13.76	16.72
	6	2437	13.64	13.64	16.65
	9	2452	13.73	13.66	16.71
	10	2457	12.73	12.63	15.69
	11	2462	10.91	10.96	13.95
802.11be EHT20	1	2412	13.54	13.52	16.54
	6	2437	13.46	13.62	16.55
	11	2462	13.58	13.54	16.57
	12	2467	9.86	9.80	12.84
	13	2472	8.70	8.79	11.76
802.11be EHT40	3	2422	13.66	13.76	16.72
	6	2437	13.65	13.64	16.65
	9	2452	13.73	13.62	16.68
	10	2457	12.62	12.65	15.64
	11	2462	10.52	10.46	13.50

Conducted Power (Full)			
Bluetooth Ant 1			
Mode	Channel	Frequency	SISO Ant 0 Avg. Power
BR / EDR	0	2402	13.64
	39	2441	13.79
	78	2480	14.12
LE	0	2402	13.62
	19	2440	13.77
	39	2480	14.09

Conducted Power (Full)			
WLAN 5.2GHz Ant 1			
Mode	Channel	Frequency	SISO Ant 0 Avg. Power
802.11a	36	5180	11.82
	40	5200	11.67
	44	5220	11.84
	48	5240	11.82
802.11n HT20	36	5180	11.70
	40	5200	11.80
	44	5220	11.85
	48	5240	11.84
802.11n HT40	38	5190	11.67
	46	5230	11.69
802.11ac VHT20	36	5180	11.78
	40	5200	11.76
	44	5220	11.79
	48	5240	11.84
802.11ac VHT40	38	5190	11.67
	46	5230	11.70
802.11ac VHT80	42	5210	11.85
802.11ax HE20	36	5180	11.62
	40	5200	11.76
	44	5220	11.86
	48	5240	11.86
802.11ax HE40	38	5190	11.83
	46	5230	11.74
802.11ax HE80	42	5210	11.76
802.11be EHT20	36	5180	11.75
	40	5200	11.85
	44	5220	11.88
	48	5240	11.85
802.11be EHT40	38	5190	11.78
	46	5230	11.74
802.11be EHT80	42	5210	11.95

Conducted Power (Full)			
WLAN 5.2GHz Ant 2			
Mode	Channel	Frequency	SISO Ant 1 Avg. Power
802.11a	36	5180	11.96
	40	5200	11.96
	44	5220	11.91
	48	5240	11.92
802.11n HT20	36	5180	11.89
	40	5200	11.85
	44	5220	11.94
	48	5240	11.88
802.11n HT40	38	5190	11.84
	46	5230	11.82
802.11ac VHT20	36	5180	11.85
	40	5200	11.89
	44	5220	11.81
	48	5240	11.83
802.11ac VHT40	38	5190	11.83
	46	5230	11.82
802.11ac VHT80	42	5210	11.82
802.11ax HE20	36	5180	11.79
	40	5200	11.77
	44	5220	11.70
	48	5240	11.77
802.11ax HE40	38	5190	11.70
	46	5230	11.72
802.11ax HE80	42	5210	11.70
802.11be EHT20	36	5180	11.78
	40	5200	11.75
	44	5220	11.71
	48	5240	11.70
802.11be EHT40	38	5190	11.74
	46	5230	11.70
802.11be EHT80	42	5210	11.99

Conducted Power (Full)					
WLAN 5.2GHz Ant 1+2					
Mode	Channel	Frequency	MIMO Ant 1 Avg. Power	MIMO Ant 2 Avg. Power	MIMO Ant 1+2 Avg. Power
802.11a	36	5180			
	40	5200			
	44	5220			
	48	5240			
802.11n HT20	36	5180	8.82	8.90	11.87
	40	5200	8.89	8.87	11.89
	44	5220	8.93	8.92	11.94
	48	5240	9.02	8.87	11.95
802.11n HT40	38	5190	8.79	8.84	11.83
	46	5230	9.05	8.84	11.96
802.11ac VHT20	36	5180	8.85	8.94	11.91
	40	5200	8.85	8.88	11.87
	44	5220	8.96	8.89	11.94
	48	5240	8.96	8.84	11.91
802.11ac VHT40	38	5190	8.85	8.88	11.88
	46	5230	9.03	8.84	11.94
802.11ac VHT80	42	5210	8.85	8.83	11.85
802.11ax HE20	36	5180	8.78	8.82	11.81
	40	5200	8.72	8.81	11.78
	44	5220	8.92	8.76	11.85
	48	5240	8.87	8.80	11.84
802.11ax HE40	38	5190	8.66	8.75	11.72
	46	5230	8.89	8.77	11.84
802.11ax HE80	42	5210	8.79	8.80	11.81
802.11be EHT20	36	5180	8.74	8.84	11.80
	40	5200	8.72	8.79	11.76
	44	5220	8.85	8.77	11.82
	48	5240	8.84	8.82	11.84
802.11be EHT40	38	5190	8.63	8.76	11.70
	46	5230	8.84	8.73	11.79
802.11be EHT80	42	5210	8.97	9.06	12.03

Conducted Power (Full)			
WLAN 5.3GHz Ant 1			
Mode	Channel	Frequency	SISO Ant 0 Avg. Power
802.11a	52	5260	11.84
	56	5280	11.62
	60	5300	11.77
	64	5320	11.65
802.11n HT20	52	5260	11.81
	56	5280	11.79
	60	5300	11.70
	64	5320	11.79
802.11n HT40	54	5270	11.62
	62	5310	11.77
802.11ac VHT20	52	5260	11.70
	56	5280	11.69
	60	5300	11.75
	64	5320	11.58
802.11ac VHT40	54	5270	11.76
	62	5310	11.79
802.11ac VHT80	58	5290	11.61
802.11ac VHT160	50	5250	11.68
802.11ax HE20	52	5260	11.63
	56	5280	11.68
	60	5300	11.66
	64	5320	11.57
802.11ax HE40	54	5270	11.63
	62	5310	11.72
802.11ax HE80	58	5290	11.73
802.11ax HE160	50	5250	11.72
802.11be EHT20	52	5260	11.74
	56	5280	11.61
	60	5300	11.62
	64	5320	11.67
802.11be EHT40	54	5270	11.80
	62	5310	11.62
802.11be EHT80	58	5290	11.70
802.11be EHT160	50	5250	11.96

Conducted Power (Full)			
WLAN 5.3GHz Ant 2			
Mode	Channel	Frequency	SISO Ant 1 Avg. Power
802.11a	52	5260	11.96
	56	5280	11.94
	60	5300	11.96
	64	5320	11.94
802.11n HT20	52	5260	11.87
	56	5280	11.91
	60	5300	11.97
	64	5320	11.89
802.11n HT40	54	5270	11.87
	62	5310	11.90
802.11ac VHT20	52	5260	11.85
	56	5280	11.89
	60	5300	11.95
	64	5320	11.72
802.11ac VHT40	54	5270	11.91
	62	5310	11.95
802.11ac VHT80	58	5290	11.88
802.11ac VHT160	50	5250	11.68
802.11ax HE20	52	5260	11.75
	56	5280	11.73
	60	5300	11.85
	64	5320	11.95
802.11ax HE40	54	5270	11.73
	62	5310	11.86
802.11ax HE80	58	5290	11.84
802.11ax HE160	50	5250	11.72
802.11be EHT20	52	5260	11.72
	56	5280	11.83
	60	5300	11.85
	64	5320	11.90
802.11be EHT40	54	5270	11.69
	62	5310	11.85
802.11be EHT80	58	5290	11.85
802.11be EHT160	50	5250	12.13

Conducted Power (Full)					
WLAN 5.3GHz Ant 1+2					
Mode	Channel	Frequency	MIMO Ant 1 Avg. Power	MIMO Ant 2 Avg. Power	MIMO Ant 1+2 Avg. Power
802.11a	52	5260			
	56	5280			
	60	5300			
	64	5320			
802.11n HT20	52	5260	8.76	8.97	11.87
	56	5280	8.82	9.05	11.95
	60	5300	8.80	9.07	11.95
	64	5320	8.92	9.14	12.04
802.11n HT40	54	5270	8.75	8.87	11.82
	62	5310	8.85	8.93	11.90
802.11ac VHT20	52	5260	8.82	8.86	11.85
	56	5280	8.77	8.84	11.82
	60	5300	8.83	8.98	11.91
	64	5320	8.93	8.95	11.95
802.11ac VHT40	54	5270	8.75	8.86	11.82
	62	5310	8.84	8.95	11.90
802.11ac VHT80	58	5290	8.83	8.85	11.85
802.11ac VHT160	50	5250	8.74	8.78	11.77
802.11ax HE20	52	5260	8.56	8.75	11.67
	56	5280	8.71	8.82	11.78
	60	5300	8.69	8.81	11.76
	64	5320	8.84	8.88	11.87
802.11ax HE40	54	5270	8.64	8.73	11.69
	62	5310	8.67	8.82	11.75
802.11ax HE80	58	5290	8.75	8.81	11.79
802.11ax HE160	50	5250	8.73	8.77	11.76
802.11be EHT20	52	5260	8.67	8.81	11.75
	56	5280	8.68	8.79	11.75
	60	5300	8.78	8.84	11.82
	64	5320	8.81	8.89	11.86
802.11be EHT40	54	5270	8.66	8.78	11.73
	62	5310	8.68	8.83	11.77
802.11be EHT80	58	5290	8.75	8.85	11.81
802.11be EHT160	50	5250	9.04	9.11	12.09

Conducted Power (Full)			
WLAN 5.6GHz Ant 1			
Mode	Channel	Frequency	SISO Ant 0 Avg. Power
802.11a	100	5500	13.17
	104	5520	13.15
	108	5540	13.27
	112	5560	13.24
	116	5580	13.11
	120	5600	13.02
	124	5620	13.03
	128	5640	13.11
	132	5660	12.95
	136	5680	12.92
	140	5700	12.67
	144	5720	12.82
802.11n HT20	100	5500	13.11
	104	5520	13.14
	108	5540	13.17
	112	5560	13.14
	116	5580	13.01
	120	5600	12.97
	124	5620	12.90
	128	5640	13.02
	132	5660	12.88
	136	5680	12.80
	140	5700	12.61
	144	5720	12.77
802.11n HT40	102	5510	13.05
	110	5550	13.13
	118	5590	12.96
	126	5630	12.86
	134	5670	12.77
	142	5710	12.61
802.11ac VHT20	100	5500	13.15
	104	5520	13.22
	108	5540	13.19
	112	5560	13.17
	116	5580	13.08
	120	5600	12.99
	124	5620	12.94
	128	5640	12.98
	132	5660	12.87
	136	5680	12.79
	140	5700	12.67
	144	5720	12.79
802.11ac VHT40	102	5510	13.02
	110	5550	13.13
	118	5590	12.96
	126	5630	12.85
	134	5670	12.81
	142	5710	12.58
802.11ac VHT80	106	5530	13.11
	122	5610	12.88
	138	5690	12.72
802.11ac VHT160	114	5570	12.81
802.11ax HE20	100	5500	12.97
	104	5520	13.08
	108	5540	13.04
	112	5560	13.08
	116	5580	12.90
	120	5600	12.88
	124	5620	12.88
	128	5640	12.90
	132	5660	12.82
	136	5680	12.71
	140	5700	12.51
	144	5720	12.67
802.11ax HE40	102	5510	12.94
	110	5550	13.02
	118	5590	12.87
	126	5630	12.75
	134	5670	12.68
	142	5710	12.52

Conducted Power (Full)			
802.11ax HE80	106	5530	13.01
	122	5610	12.82
	138	5690	12.67
802.11ax HE160	114	5570	12.79
802.11be EHT20	100	5500	12.98
	104	5520	13.07
	108	5540	13.11
	112	5560	13.02
	116	5580	12.93
	120	5600	12.91
	124	5620	12.90
	128	5640	12.88
	132	5660	12.80
	136	5680	12.70
	140	5700	12.54
	144	5720	12.65
802.11be EHT40	102	5510	12.94
	110	5550	12.99
	118	5590	12.86
	126	5630	12.77
	134	5670	12.68
802.11be EHT80	142	5710	12.49
	106	5530	13.22
	122	5610	13.10
802.11be EHT160	138	5690	13.22
	114	5570	13.16

Conducted Power (Full)			
WLAN 5.6GHz Ant 2			
Mode	Channel	Frequency	SISO Ant 1 Avg. Power
802.11a	100	5500	13.10
	104	5520	13.21
	108	5540	13.20
	112	5560	13.16
	116	5580	13.17
	120	5600	13.11
	124	5620	13.06
	128	5640	13.01
	132	5660	13.03
	136	5680	12.94
	140	5700	12.82
	144	5720	12.88
802.11n HT20	100	5500	12.99
	104	5520	13.12
	108	5540	13.11
	112	5560	13.05
	116	5580	13.07
	120	5600	13.02
	124	5620	13.02
	128	5640	12.93
	132	5660	12.88
	136	5680	12.79
	140	5700	12.81
	144	5720	12.83
802.11n HT40	102	5510	12.98
	110	5550	13.06
	118	5590	13.02
	126	5630	12.90
	134	5670	12.80
802.11ac VHT20	142	5710	12.79
	100	5500	12.98
	104	5520	13.13
	108	5540	13.12
	112	5560	13.08
	116	5580	13.05
	120	5600	13.01
	124	5620	13.05
	128	5640	12.93
	132	5660	12.94
	136	5680	12.81
	140	5700	12.79
802.11ac VHT40	144	5720	12.82
	102	5510	12.95
	110	5550	12.99
	118	5590	12.93
	126	5630	12.88
802.11ac VHT80	134	5670	12.80
	142	5710	12.75
	106	5530	13.01
802.11ac VHT160	122	5610	12.90
	138	5690	12.74
802.11ax HE20	114	5570	12.86
	100	5500	12.88
	104	5520	13.07
	108	5540	12.97
	112	5560	13.04
	116	5580	12.97
	120	5600	12.95
	124	5620	12.91
	128	5640	12.83
	132	5660	12.81
	136	5680	12.75
	140	5700	12.72
802.11ax HE40	144	5720	12.70
	102	5510	12.84
	110	5550	12.93
	118	5590	12.90
	126	5630	12.80
	134	5670	12.76
	142	5710	12.73

Conducted Power (Full)			
802.11ax HE80	106	5530	12.97
	122	5610	12.87
	138	5690	12.71
802.11ax HE160	114	5570	12.85
802.11be EHT20	100	5500	12.89
	104	5520	13.06
	108	5540	12.98
	112	5560	13.03
	116	5580	12.97
	120	5600	12.93
	124	5620	12.93
	128	5640	12.82
	132	5660	12.84
	136	5680	12.82
	140	5700	12.75
	144	5720	12.75
802.11be EHT40	102	5510	12.90
	110	5550	12.99
	118	5590	12.91
	126	5630	12.82
	134	5670	12.76
	142	5710	12.72
802.11be EHT80	106	5530	13.26
	122	5610	13.08
	138	5690	12.97
802.11be EHT160	114	5570	13.19

Conducted Power (Full)					
WLAN 5.6GHz Ant 1+2					
Mode	Channel	Frequency	MIMO Ant 1 Avg. Power	MIMO Ant 2 Avg. Power	MIMO Ant 1+2 Avg. Power
802.11a	100	5500			
	104	5520			
	108	5540			
	112	5560			
	116	5580			
	120	5600			
	124	5620			
	128	5640			
	132	5660			
	136	5680			
	140	5700			
	144	5720			
802.11n HT20	100	5500	10.11	10.10	13.11
	104	5520	9.95	10.02	13.00
	108	5540	9.96	10.26	13.12
	112	5560	9.98	10.26	13.13
	116	5580	9.78	10.15	12.98
	120	5600	9.79	10.04	12.93
	124	5620	9.76	10.17	12.98
	128	5640	9.85	10.12	13.00
	132	5660	9.83	10.06	12.95
	136	5680	9.69	10.06	12.89
	140	5700	9.57	10.00	12.80
	144	5720	9.61	9.97	12.80
802.11n HT40	102	5510	9.78	10.05	12.93
	110	5550	10.01	10.15	13.09
	118	5590	9.74	10.10	12.94
	126	5630	9.69	10.09	12.91
	134	5670	9.66	9.93	12.81
	142	5710	9.51	9.87	12.70
802.11ac VHT20	100	5500	9.81	9.99	12.91
	104	5520	9.99	10.22	13.12
	108	5540	10.01	10.16	13.10
	112	5560	9.93	10.07	13.01
	116	5580	9.78	10.15	12.98
	120	5600	9.83	10.07	12.96
	124	5620	9.79	10.15	12.98
	128	5640	9.83	9.98	12.91
	132	5660	9.78	9.91	12.86
	136	5680	9.67	9.85	12.77
	140	5700	9.60	9.86	12.74
	144	5720	9.61	9.92	12.78
802.11ac VHT40	102	5510	9.85	10.05	12.96
	110	5550	10.04	10.16	13.11
	118	5590	9.86	10.08	12.98
	126	5630	9.70	10.02	12.87
	134	5670	9.62	9.91	12.78
	142	5710	9.54	9.84	12.70
802.11ac VHT80	106	5530	10.00	10.19	13.11
	122	5610	9.82	10.05	12.95
	138	5690	9.62	9.88	12.76
802.11ac VHT160	114	5570	9.73	10.00	12.87
802.11ax HE20	100	5500	9.76	9.98	12.88
	104	5520	9.89	10.10	13.01
	108	5540	9.92	10.03	12.98
	112	5560	9.89	10.03	12.97
	116	5580	9.76	10.06	12.92
	120	5600	9.72	9.97	12.86
	124	5620	10.03	9.95	13.00
	128	5640	9.98	9.87	12.93
	132	5660	9.97	9.88	12.94
	136	5680	9.86	9.75	12.82
	140	5700	9.77	9.79	12.79
	144	5720	9.80	9.77	12.80
802.11ax HE40	102	5510	9.85	9.93	12.90
	110	5550	10.08	10.09	13.09
	118	5590	10.02	10.00	13.02
	126	5630	9.96	9.90	12.94
	134	5670	9.82	9.83	12.84
	142	5710	9.71	9.74	12.73

Conducted Power (Full)					
802.11ax HE80	106	5530	10.14	10.08	13.12
	122	5610	9.99	9.93	12.97
	138	5690	9.83	9.81	12.83
802.11ax HE160	114	5570	10.00	10.00	13.01
802.11be EHT20	100	5500	9.94	9.95	12.96
	104	5520	10.11	10.05	13.09
	108	5540	10.09	10.14	13.12
	112	5560	10.05	9.98	13.03
	116	5580	10.04	10.06	13.06
	120	5600	9.94	9.97	12.97
	124	5620	9.94	10.03	13.00
	128	5640	9.95	9.86	12.92
	132	5660	9.91	9.86	12.90
	136	5680	9.88	9.80	12.85
	140	5700	9.73	9.78	12.77
	144	5720	9.81	9.74	12.78
802.11be EHT40	102	5510	10.03	9.93	12.99
	110	5550	10.10	10.05	13.08
	118	5590	9.99	10.01	13.01
	126	5630	9.92	9.86	12.90
	134	5670	9.91	9.79	12.86
	142	5710	9.66	9.76	12.72
802.11be EHT80	106	5530	10.35	10.27	13.32
	122	5610	10.15	10.17	13.17
	138	5690	10.04	9.96	13.01
802.11be EHT160	114	5570	10.21	10.19	13.21

Conducted Power (Full)			
WLAN 5.8GHz Ant 1			
Mode	Channel	Frequency	SISO Ant 0 Avg. Power
802.11a	149	5745	13.24
	153	5765	13.27
	157	5785	13.31
	161	5805	13.29
	165	5825	13.24
802.11n HT20	149	5745	13.13
	153	5765	13.19
	157	5785	13.29
	161	5805	13.19
	165	5825	13.10
802.11n HT40	151	5755	13.10
	159	5795	13.16
802.11ac VHT20	149	5745	13.13
	153	5765	13.18
	157	5785	13.30
	161	5805	13.19
	165	5825	13.12
802.11ac VHT40	151	5755	13.06
	159	5795	13.15
802.11ac VHT80	155	5775	13.16
802.11ax HE20	149	5745	13.06
	153	5765	13.09
	157	5785	13.20
	161	5805	13.10
	165	5825	13.03
802.11ax HE40	151	5755	13.04
	159	5795	13.07
802.11ax HE80	155	5775	13.07
802.11be EHT20	149	5745	13.03
	153	5765	13.10
	157	5785	13.19
	161	5805	13.10
	165	5825	13.05
802.11be EHT40	151	5755	12.99
	159	5795	13.08
802.11be EHT80	155	5775	13.31

Conducted Power (Full)			
WLAN 5.8GHz Ant 2			
Mode	Channel	Frequency	SISO Ant 1 Avg. Power
802.11a	149	5745	13.34
	153	5765	13.29
	157	5785	13.36
	161	5805	13.23
	165	5825	13.07
802.11n HT20	149	5745	13.24
	153	5765	13.24
	157	5785	13.30
	161	5805	13.12
	165	5825	12.94
802.11n HT40	151	5755	13.14
	159	5795	13.14
802.11ac VHT20	149	5745	13.25
	153	5765	13.17
	157	5785	13.32
	161	5805	13.08
	165	5825	12.97
802.11ac VHT40	151	5755	13.18
	159	5795	13.17
802.11ac VHT80	155	5775	13.14
802.11ax HE20	149	5745	13.11
	153	5765	13.13
	157	5785	13.20
	161	5805	13.05
	165	5825	12.86
802.11ax HE40	151	5755	13.08
	159	5795	13.07
802.11ax HE80	155	5775	13.07
802.11be EHT20	149	5745	13.10
	153	5765	13.09
	157	5785	13.20
	161	5805	13.00
	165	5825	12.86
802.11be EHT40	151	5755	13.09
	159	5795	13.06
802.11be EHT80	155	5775	13.42

Conducted Power (Full)					
WLAN 5.8GHz Ant 1+2					
Mode	Channel	Frequency	MIMO Ant 1 Avg. Power	MIMO Ant 2 Avg. Power	MIMO Ant 1+2 Avg. Power
802.11a	149	5745			
	153	5765			
	157	5785			
	161	5805			
	165	5825			
802.11n HT20	149	5745	10.18	10.27	13.23
	153	5765	10.27	10.30	13.29
	157	5785	10.43	10.35	13.40
	161	5805	10.21	10.11	13.17
	165	5825	10.17	10.02	13.10
802.11n HT40	151	5755	10.12	10.30	13.22
	159	5795	10.28	10.26	13.28
802.11ac VHT20	149	5745	10.17	10.28	13.23
	153	5765	10.25	10.28	13.28
	157	5785	10.35	10.35	13.36
	161	5805	10.24	10.10	13.18
	165	5825	10.14	9.97	13.07
802.11ac VHT40	151	5755	10.13	10.30	13.23
	159	5795	10.26	10.25	13.26
802.11ac VHT80	155	5775	10.26	10.25	13.27
802.11ax HE20	149	5745	10.06	10.18	13.13
	153	5765	10.13	10.23	13.19
	157	5785	10.28	10.28	13.29
	161	5805	10.13	10.03	13.09
	165	5825	10.03	9.96	13.00
802.11ax HE40	151	5755	10.02	10.21	13.13
	159	5795	10.17	10.14	13.17
802.11ax HE80	155	5775	10.16	10.16	13.17
802.11be EHT20	149	5745	10.05	10.21	13.14
	153	5765	10.13	10.19	13.17
	157	5785	10.24	10.28	13.27
	161	5805	10.15	10.04	13.10
	165	5825	10.05	9.94	13.01
802.11be EHT40	151	5755	10.02	10.19	13.12
	159	5795	10.17	10.16	13.18
802.11be EHT80	155	5775	10.39	10.38	13.40

Conducted Power (Full)			
WLAN 5.9GHz Ant 1			
Mode	Channel	Frequency	SISO Ant 0 Avg. Power
802.11a	169	5845	13.22
	173	5865	13.23
	177	5885	13.22
802.11n HT20	169	5845	13.10
	173	5865	13.12
	177	5885	13.14
802.11n HT40	167	5835	13.11
	175	5875	13.14
802.11ac VHT20	169	5845	13.13
	173	5865	13.12
	177	5885	13.13
802.11ac VHT40	167	5835	13.10
	175	5875	13.13
802.11ac VHT80	171	5855	13.06
802.11ac VHT160	163	5815	12.95
802.11ax HE20	169	5845	13.01
	173	5865	13.03
	177	5885	13.02
802.11ax HE40	167	5835	13.02
	175	5875	13.04
802.11ax HE80	171	5855	13.00
802.11ax HE160	163	5815	12.90
802.11be EHT20	169	5845	13.03
	173	5865	13.02
	177	5885	13.05
802.11be EHT40	167	5835	13.01
	175	5875	13.03
802.11be EHT80	171	5855	12.98
802.11be EHT160	163	5815	13.27

Conducted Power (Full)			
WLAN 5.9GHz Ant 2			
Mode	Channel	Frequency	SISO Ant 1 Avg. Power
802.11a	169	5845	13.18
	173	5865	13.33
	177	5885	13.28
802.11n HT20	169	5845	13.10
	173	5865	13.17
	177	5885	13.18
802.11n HT40	167	5835	12.96
	175	5875	13.18
802.11ac VHT20	169	5845	13.07
	173	5865	13.19
	177	5885	13.22
802.11ac VHT40	167	5835	12.97
	175	5875	13.16
802.11ac VHT80	171	5855	13.05
802.11ac VHT160	163	5815	13.03
802.11ax HE20	169	5845	13.01
	173	5865	13.13
	177	5885	13.07
802.11ax HE40	167	5835	12.85
	175	5875	13.11
802.11ax HE80	171	5855	13.04
802.11ax HE160	163	5815	13.01
802.11be EHT20	169	5845	12.99
	173	5865	13.06
	177	5885	13.08
802.11be EHT40	167	5835	12.88
	175	5875	13.07
802.11be EHT80	171	5855	12.98
802.11be EHT160	163	5815	13.34

Conducted Power (Full)					
WLAN 5.9GHz Ant 1+2					
Mode	Channel	Frequency	MIMO Ant 1 Avg. Power	MIMO Ant 2 Avg. Power	MIMO Ant 1+2 Avg. Power
802.11a	169	5845			
	173	5865			
	177	5885			
802.11n HT20	169	5845	10.15	10.12	13.15
	173	5865	10.16	10.23	13.20
	177	5885	10.21	10.23	13.23
802.11n HT40	167	5835	10.12	9.97	13.05
	175	5875	10.15	10.28	13.22
802.11ac VHT20	169	5845	10.15	10.11	13.14
	173	5865	10.15	10.22	13.20
	177	5885	10.17	10.21	13.20
802.11ac VHT40	167	5835	10.12	9.96	13.05
	175	5875	10.13	10.25	13.20
802.11ac VHT80	171	5855	10.10	10.05	13.08
802.11ac VHT160	163	5815	10.07	10.16	13.12
802.11ax HE20	169	5845	10.07	10.00	13.04
	173	5865	10.05	10.17	13.12
	177	5885	10.07	10.17	13.13
802.11ax HE40	167	5835	10.04	9.86	12.96
	175	5875	10.04	10.19	13.12
802.11ax HE80	171	5855	10.05	9.99	13.03
802.11ax HE160	163	5815	10.06	10.14	13.11
802.11be EHT20	169	5845	10.02	10.00	13.02
	173	5865	10.06	10.13	13.10
	177	5885	10.06	10.13	13.11
802.11be EHT40	167	5835	10.04	9.90	12.98
	175	5875	10.03	10.16	13.11
802.11be EHT80	171	5855	10.04	10.02	13.04
802.11be EHT160	163	5815	10.29	10.39	13.35

Conducted Power (Full)			
UNII-5 Ant 1_LPI			
Mode	Channel	Frequency	SISO Ant 0 Avg. Power
802.11ax HE20	1	5955	5.57
	5	5975	5.69
	9	5995	5.55
	13	6015	5.63
	17	6035	5.63
	21	6055	5.62
	25	6075	5.64
	29	6095	5.67
	33	6115	5.79
	37	6135	5.87
	41	6155	5.80
	45	6175	5.92
	49	6195	5.74
	53	6215	5.74
	57	6235	5.75
	61	6255	5.56
	65	6275	5.66
	69	6295	5.50
	73	6315	5.58
	77	6335	5.56
802.11ax HE40	81	6355	5.70
	85	6375	5.65
	89	6395	5.62
	93	6415	5.59
	3	5965	8.37
	11	6005	8.41
	19	6045	8.42
	27	6085	8.46
	35	6125	8.56
	43	6165	8.58
802.11ax HE80	51	6205	8.54
	59	6245	8.40
	67	6285	8.33
	75	6325	8.36
	83	6365	8.53
802.11ax HE160	91	6405	8.46
	7	5985	9.64
	23	6065	9.73
802.11ax HE160	39	6145	9.83
	55	6225	9.80
	71	6305	9.70
802.11ax HE160	87	6385	9.73
	15	6025	9.67
	47	6185	10.07
802.11ax HE160	79	6345	9.75

Conducted Power (Full)			
UNII-5 Ant 1_LPI			
Mode	Channel	Frequency	SISO Ant 0 Avg. Power
802.11be EHT20	1	5955	5.28
	5	5975	5.44
	9	5995	5.33
	13	6015	5.35
	17	6035	5.42
	21	6055	5.38
	25	6075	5.47
	29	6095	5.46
	33	6115	5.63
	37	6135	5.79
	41	6155	5.62
	45	6175	5.80
	49	6195	5.64
	53	6215	5.66
	57	6235	5.60
	61	6255	5.41
	65	6275	5.56
	69	6295	5.41
	73	6315	5.48
	77	6335	5.39
802.11be EHT40	81	6355	5.62
	85	6375	5.56
	89	6395	5.51
	93	6415	5.46
	3	5965	8.17
	11	6005	8.19
	19	6045	8.27
	27	6085	8.33
	35	6125	8.52
	43	6165	8.52
802.11be EHT80	51	6205	8.53
	59	6245	8.40
	67	6285	8.34
	75	6325	8.34
	83	6365	8.44
	91	6405	8.43
802.11be EHT160	7	5985	9.45
	23	6065	9.55
	39	6145	9.73
	55	6225	9.69
	71	6305	9.63
802.11be EHT320	87	6385	9.66
	15	6025	9.46
	47	6185	9.71
	79	6345	9.70
	31	6105	10.17
	63	6265	10.18

Conducted Power (Full)			
UNII-5 Ant 2_LPI			
Mode	Channel	Frequency	SISO Ant 1 Avg. Power
802.11ax HE20	1	5955	5.30
	5	5975	5.23
	9	5995	5.34
	13	6015	5.34
	17	6035	5.27
	21	6055	5.25
	25	6075	5.23
	29	6095	5.40
	33	6115	5.43
	37	6135	5.62
	41	6155	5.62
	45	6175	5.34
	49	6195	5.38
	53	6215	5.32
	57	6235	5.31
	61	6255	5.23
	65	6275	5.22
	69	6295	5.25
	73	6315	5.30
	77	6335	5.35
802.11ax HE40	81	6355	5.37
	85	6375	5.47
	89	6395	5.56
	93	6415	5.43
	3	5965	8.04
	11	6005	8.20
	19	6045	8.07
	27	6085	8.06
	35	6125	8.30
	43	6165	8.24
802.11ax HE80	51	6205	8.15
	59	6245	8.10
	67	6285	8.04
	75	6325	8.05
	83	6365	8.23
	91	6405	8.29
802.11ax HE160	7	5985	9.57
	23	6065	9.48
	39	6145	9.69
	55	6225	9.49
	71	6305	9.49
	87	6385	9.64
	15	6025	9.36
	47	6185	9.79
	79	6345	9.53

Conducted Power (Full)			
UNII-5 Ant 2_LPI			
Mode	Channel	Frequency	SISO Ant 1 Avg. Power
802.11be EHT20	1	5955	5.30
	5	5975	5.20
	9	5995	5.38
	13	6015	5.39
	17	6035	5.30
	21	6055	5.32
	25	6075	5.28
	29	6095	5.45
	33	6115	5.46
	37	6135	5.67
	41	6155	5.71
	45	6175	5.40
	49	6195	5.44
	53	6215	5.43
	57	6235	5.40
	61	6255	5.38
	65	6275	5.31
	69	6295	5.41
	73	6315	5.35
	77	6335	5.45
802.11be EHT40	81	6355	5.49
	85	6375	5.58
	89	6395	5.61
	93	6415	5.51
	3	5965	8.01
	11	6005	8.15
	19	6045	8.09
	27	6085	8.11
	35	6125	8.35
	43	6165	8.37
802.11be EHT80	51	6205	8.22
	59	6245	8.20
	67	6285	8.12
	75	6325	8.16
	83	6365	8.33
	91	6405	8.33
802.11be EHT160	7	5985	9.48
	23	6065	9.41
	39	6145	9.67
	55	6225	9.51
	71	6305	9.52
802.11be EHT320	87	6385	9.62
	15	6025	9.32
	47	6185	9.53
	79	6345	9.53
	31	6105	9.93
	63	6265	9.98

Conducted Power (Full)					
UNII-5 Ant 1+2_LPI					
Mode	Channel	Frequency	MIMO Ant 1 Avg. Power	MIMO Ant 2 Avg. Power	MIMO Ant 1+2 Avg. Power
802.11ax HE20	1	5955	2.42	2.29	5.37
	5	5975	2.52	2.12	5.33
	9	5995	2.48	2.29	5.40
	13	6015	2.53	2.33	5.44
	17	6035	2.56	2.22	5.40
	21	6055	2.54	2.24	5.40
	25	6075	2.56	2.24	5.41
	29	6095	2.59	2.41	5.52
	33	6115	2.70	2.48	5.60
	37	6135	2.84	2.64	5.75
	41	6155	2.71	2.64	5.69
	45	6175	2.84	2.45	5.66
	49	6195	2.76	2.41	5.60
	53	6215	2.74	2.41	5.59
	57	6235	2.73	2.36	5.56
	61	6255	2.56	2.32	5.45
	65	6275	2.65	2.31	5.49
	69	6295	2.55	2.35	5.46
	73	6315	2.57	2.29	5.44
	77	6335	2.53	2.29	5.42
	81	6355	2.71	2.40	5.57
	85	6375	2.65	2.44	5.56
	89	6395	2.65	2.55	5.61
	93	6415	2.60	2.36	5.50
802.11ax HE40	3	5965	5.31	5.01	8.17
	11	6005	5.34	5.12	8.24
	19	6045	5.39	5.03	8.23
	27	6085	5.50	5.09	8.31
	35	6125	5.61	5.35	8.49
	43	6165	5.67	5.34	8.52
	51	6205	5.65	5.15	8.42
	59	6245	5.47	5.10	8.30
	67	6285	5.40	5.03	8.23
	75	6325	5.44	5.10	8.28
	83	6365	5.58	5.19	8.40
	91	6405	5.50	5.32	8.42
802.11ax HE80	7	5985	6.86	6.63	9.76
	23	6065	6.93	6.59	9.77
	39	6145	7.09	6.88	10.00
	55	6225	7.08	6.69	9.90
	71	6305	6.91	6.65	9.79
	87	6385	7.04	6.84	9.95
802.11ax HE160	15	6025	6.86	6.52	9.70
	47	6185	7.31	6.95	10.14
	79	6345	7.00	6.70	9.86

Conducted Power (Full)					
UNII-5 Ant 1+2_LPI					
Mode	Channel	Frequency	MIMO Ant 1 Avg. Power	MIMO Ant 2 Avg. Power	MIMO Ant 1+2 Avg. Power
802.11be EHT20	1	5955	2.44	2.31	5.39
	5	5975	2.62	2.22	5.43
	9	5995	2.54	2.36	5.46
	13	6015	2.58	2.36	5.48
	17	6035	2.58	2.29	5.45
	21	6055	2.62	2.32	5.48
	25	6075	2.64	2.35	5.51
	29	6095	2.69	2.47	5.59
	33	6115	2.78	2.43	5.62
	37	6135	2.91	2.70	5.82
	41	6155	2.82	2.61	5.73
	45	6175	2.92	2.40	5.68
	49	6195	2.79	2.45	5.63
	53	6215	2.80	2.37	5.60
	57	6235	2.72	2.40	5.57
	61	6255	2.61	2.35	5.49
	65	6275	2.67	2.31	5.50
	69	6295	2.52	2.36	5.46
	73	6315	2.57	2.36	5.48
	77	6335	2.52	2.36	5.45
	81	6355	2.72	2.47	5.61
	85	6375	2.69	2.56	5.64
	89	6395	2.70	2.61	5.66
	93	6415	2.60	2.42	5.52
802.11be EHT40	3	5965	5.31	5.07	8.20
	11	6005	5.32	5.21	8.28
	19	6045	5.41	5.12	8.28
	27	6085	5.47	5.13	8.32
	35	6125	5.61	5.40	8.52
	43	6165	5.64	5.45	8.56
	51	6205	5.64	5.23	8.45
	59	6245	5.44	5.13	8.30
	67	6285	5.37	5.14	8.27
	75	6325	5.43	5.19	8.32
	83	6365	5.59	5.31	8.46
	91	6405	5.46	5.34	8.41
802.11be EHT80	7	5985	6.72	6.72	9.73
	23	6065	6.87	6.65	9.77
	39	6145	7.13	6.95	10.05
	55	6225	7.10	6.78	9.95
	71	6305	6.92	6.74	9.85
	87	6385	7.00	6.95	9.99
802.11be EHT160	15	6025	6.80	6.65	9.73
	47	6185	7.02	6.79	9.92
	79	6345	7.00	6.80	9.91
802.11be EHT320	31	6105	7.23	7.00	10.12
	63	6265	7.21	7.04	10.14

Conducted Power (Full)			
UNII-6 Ant 1_LPI			
Mode	Channel	Frequency	SISO Ant 0 Avg. Power
802.11ax HE20	97	6435	5.50
	101	6455	5.53
	105	6475	5.66
	109	6495	5.65
	113	6515	5.75
802.11ax HE40	99	6445	8.40
	107	6485	8.44
	115	6525	8.57
802.11ax HE80	103	6465	9.24
	119	6545	9.43
802.11ax HE160	111	6505	9.62
802.11be EHT20	97	6435	5.47
	101	6455	5.47
	105	6475	5.60
	109	6495	5.58
	113	6515	5.72
802.11be EHT40	99	6445	8.35
	107	6485	8.43
	115	6525	8.49
802.11be EHT80	103	6465	9.17
	119	6545	9.38
802.11be EHT160	111	6505	9.25
802.11be EHT320	95	6425	9.99

Conducted Power (Full)			
UNII-6 Ant 2_LPI			
Mode	Channel	Frequency	SISO Ant 1 Avg. Power
802.11ax HE20	97	6435	5.21
	101	6455	5.29
	105	6475	5.41
	109	6495	5.41
	113	6515	5.59
802.11ax HE40	99	6445	8.04
	107	6485	8.24
	115	6525	8.38
802.11ax HE80	103	6465	9.02
	119	6545	9.26
802.11ax HE160	111	6505	9.43
802.11be EHT20	97	6435	5.28
	101	6455	5.31
	105	6475	5.46
	109	6495	5.45
	113	6515	5.69
802.11be EHT40	99	6445	8.12
	107	6485	8.25
	115	6525	8.39
802.11be EHT80	103	6465	9.02
	119	6545	9.26
802.11be EHT160	111	6505	9.16
802.11be EHT320	95	6425	9.75

Conducted Power (Full)					
UNII-6 Ant 1+2_LPI					
Mode	Channel	Frequency	MIMO Ant 1 Avg. Power	MIMO Ant 2 Avg. Power	MIMO Ant 1+2 Avg. Power
802.11ax HE20	97	6435	2.57	2.11	5.36
	101	6455	2.55	2.22	5.40
	105	6475	2.60	2.31	5.47
	109	6495	2.59	2.32	5.47
	113	6515	2.74	2.56	5.66
802.11ax HE40	99	6445	5.39	4.99	8.20
	107	6485	5.49	5.23	8.37
	115	6525	5.58	5.32	8.46
802.11ax HE80	103	6465	6.55	6.22	9.40
	119	6545	6.74	6.46	9.61
802.11ax HE160	111	6505	6.85	6.65	9.76
802.11be EHT20	97	6435	2.56	2.21	5.40
	101	6455	2.58	2.30	5.45
	105	6475	2.56	2.44	5.51
	109	6495	2.59	2.38	5.49
	113	6515	2.74	2.72	5.74
802.11be EHT40	99	6445	5.42	5.14	8.29
	107	6485	5.51	5.34	8.44
	115	6525	5.59	5.42	8.52
802.11be EHT80	103	6465	6.55	6.36	9.47
	119	6545	6.74	6.58	9.67
802.11be EHT160	111	6505	6.61	6.43	9.53
802.11be EHT320	95	6425	7.23	7.01	10.13

Conducted Power (Full)			
UNII-7 Ant 1_LPI			
Mode	Channel	Frequency	SISO Ant 0 Avg. Power
802.11ax HE20	117	6535	5.79
	121	6555	5.77
	125	6575	5.87
	129	6595	5.85
	133	6615	5.99
	137	6635	5.87
	141	6655	5.75
	145	6675	5.73
	149	6695	5.66
	153	6715	5.85
	157	6735	5.92
	161	6755	5.96
	165	6775	5.99
	169	6795	5.88
	173	6815	5.69
	177	6835	5.58
802.11ax HE40	181	6855	5.55
	185	6875	5.23
	123	6565	8.58
	131	6605	8.71
	139	6645	8.56
	147	6685	8.53
	155	6725	8.47
	163	6765	8.52
802.11ax HE80	171	6805	8.28
	179	6845	8.02
	187	6885	7.63
	135	6625	9.99
802.11ax HE160	151	6705	9.86
	167	6785	9.98
	183	6865	9.00
802.11ax HE160	143	6665	10.24
	175	6825	9.34

Conducted Power (Full)			
UNII-7 Ant 1_LPI			
Mode	Channel	Frequency	SISO Ant 0 Avg. Power
802.11be EHT20	117	6535	5.71
	121	6555	5.66
	125	6575	5.82
	129	6595	5.88
	133	6615	5.95
	137	6635	5.85
	141	6655	5.73
	145	6675	5.66
	149	6695	5.63
	153	6715	5.87
	157	6735	5.97
	161	6755	5.97
	165	6775	5.95
	169	6795	5.89
	173	6815	5.75
	177	6835	5.62
802.11be EHT40	181	6855	5.53
	185	6875	5.32
	123	6565	8.53
	131	6605	8.61
	139	6645	8.51
	147	6685	8.49
	155	6725	8.48
	163	6765	8.51
802.11be EHT80	171	6805	8.30
	179	6845	8.04
	187	6885	7.71
	135	6625	9.90
802.11be EHT160	151	6705	9.82
	167	6785	9.99
	183	6865	9.04
802.11be EHT320	143	6665	9.84
	175	6825	9.42
802.11be EHT320	127	6585	10.30
	159	6745	10.45

Conducted Power (Full)			
UNII-7 Ant 2_LPI			
Mode	Channel	Frequency	SISO Ant 1 Avg. Power
802.11ax HE20	117	6535	5.58
	121	6555	5.72
	125	6575	5.60
	129	6595	5.72
	133	6615	5.89
	137	6635	5.97
	141	6655	5.72
	145	6675	5.55
	149	6695	5.43
	153	6715	5.51
	157	6735	5.67
	161	6755	5.84
	165	6775	5.98
	169	6795	5.73
	173	6815	5.38
	177	6835	5.40
802.11ax HE40	181	6855	5.36
	185	6875	5.02
	123	6565	8.35
	131	6605	8.55
	139	6645	8.40
	147	6685	8.18
	155	6725	8.19
	163	6765	8.44
802.11ax HE80	171	6805	8.01
	179	6845	7.87
	187	6885	7.52
	135	6625	9.96
802.11ax HE160	151	6705	9.71
	167	6785	9.88
	183	6865	8.86
802.11ax HE160	143	6665	10.17
	175	6825	9.23

Conducted Power (Full)			
UNII-7 Ant 2_LPI			
Mode	Channel	Frequency	SISO Ant 1 Avg. Power
802.11be EHT20	117	6535	5.54
	121	6555	5.73
	125	6575	5.63
	129	6595	5.78
	133	6615	5.84
	137	6635	5.99
	141	6655	5.71
	145	6675	5.58
	149	6695	5.43
	153	6715	5.62
	157	6735	5.75
	161	6755	5.89
	165	6775	5.91
	169	6795	5.75
	173	6815	5.48
	177	6835	5.47
802.11be EHT40	181	6855	5.36
	185	6875	5.11
	123	6565	8.41
	131	6605	8.53
	139	6645	8.38
	147	6685	8.28
	155	6725	8.24
	163	6765	8.52
802.11be EHT80	171	6805	8.07
	179	6845	7.94
	187	6885	7.60
	135	6625	9.95
802.11be EHT160	151	6705	9.71
	167	6785	9.91
	183	6865	8.87
802.11be EHT320	143	6665	9.81
	175	6825	9.28
802.11be EHT320	127	6585	10.16
	159	6745	10.34

Conducted Power (Full)					
UNII-7 Ant 1+2_LPI					
Mode	Channel	Frequency	MIMO Ant 1 Avg. Power	MIMO Ant 2 Avg. Power	MIMO Ant 1+2 Avg. Power
802.11ax HE20	117	6535	2.73	2.43	5.59
	121	6555	2.72	2.65	5.69
	125	6575	2.81	2.51	5.67
	129	6595	2.85	2.71	5.79
	133	6615	3.00	2.83	5.93
	137	6635	2.87	2.91	5.90
	141	6655	2.74	2.64	5.71
	145	6675	2.71	2.54	5.63
	149	6695	2.67	2.32	5.51
	153	6715	2.85	2.52	5.70
	157	6735	2.86	2.64	5.76
	161	6755	2.85	2.84	5.86
	165	6775	2.91	2.89	5.91
	169	6795	2.86	2.73	5.80
	173	6815	2.67	2.35	5.52
	177	6835	2.57	2.36	5.48
802.11ax HE40	181	6855	2.60	2.26	5.44
	185	6875	2.34	2.00	5.19
	123	6565	5.55	5.37	8.47
	131	6605	5.68	5.52	8.61
	139	6645	5.57	5.67	8.63
	147	6685	5.53	5.23	8.39
	155	6725	5.77	5.47	8.63
	163	6765	5.91	5.70	8.82
802.11ax HE80	171	6805	5.68	5.33	8.52
	179	6845	5.38	5.09	8.25
	187	6885	4.95	4.78	7.87
	135	6625	7.23	7.13	10.19
802.11ax HE160	151	6705	7.15	6.87	10.02
	167	6785	7.32	7.10	10.22
	183	6865	6.36	6.09	9.24
	143	6665	7.42	7.18	10.31
	175	6825	6.62	6.41	9.53

Conducted Power (Full)					
UNII-7 Ant 1+2_LPI					
Mode	Channel	Frequency	MIMO Ant 1 Avg. Power	MIMO Ant 2 Avg. Power	MIMO Ant 1+2 Avg. Power
802.11be EHT20	117	6535	2.73	2.58	5.67
	121	6555	2.74	2.70	5.73
	125	6575	2.89	2.62	5.76
	129	6595	2.86	2.80	5.84
	133	6615	2.97	2.89	5.94
	137	6635	2.93	2.94	5.95
	141	6655	2.75	2.72	5.75
	145	6675	2.72	2.60	5.67
	149	6695	2.71	2.42	5.58
	153	6715	2.91	2.61	5.77
	157	6735	2.87	2.75	5.82
	161	6755	2.92	2.86	5.90
	165	6775	2.86	2.85	5.87
	169	6795	2.84	2.75	5.81
	173	6815	2.74	2.42	5.60
	177	6835	2.63	2.43	5.54
	181	6855	2.65	2.31	5.49
	185	6875	2.32	2.09	5.22
802.11be EHT40	123	6565	5.62	5.40	8.52
	131	6605	5.75	5.60	8.69
	139	6645	5.63	5.76	8.71
	147	6685	5.56	5.34	8.46
	155	6725	5.84	5.52	8.69
	163	6765	5.94	5.76	8.86
	171	6805	5.75	5.38	8.58
	179	6845	5.45	5.18	8.33
802.11be EHT80	187	6885	5.00	4.81	7.92
	135	6625	7.18	7.27	10.23
	151	6705	7.10	7.02	10.07
	167	6785	7.31	7.22	10.28
802.11be EHT160	183	6865	6.42	6.17	9.31
	143	6665	7.14	7.07	10.12
802.11be EHT320	175	6825	6.66	6.46	9.57
	127	6585	7.47	7.41	10.45
	159	6745	7.53	7.43	10.49

Conducted Power (Full)			
UNII-8 Ant 1_LPI			
Mode	Channel	Frequency	SISO Ant 0 Avg. Power
802.11ax HE20	189	6895	4.96
	193	6915	4.75
	197	6935	4.66
	201	6955	4.81
	205	6975	4.83
	209	6995	5.03
	213	7015	5.08
	217	7035	5.01
	221	7055	4.84
	225	7075	4.86
	229	7095	4.96
	233	7115	-2.85
802.11ax HE40	195	6925	7.33
	203	6965	7.37
	211	7005	7.55
	219	7045	7.45
	227	7085	7.37
802.11ax HE80	199	6945	8.55
	215	7025	8.63
802.11ax HE160	207	6985	9.01
802.11be EHT20	189	6895	5.01
	193	6915	4.86
	197	6935	4.78
	201	6955	4.88
	205	6975	4.96
	209	6995	5.09
	213	7015	5.09
	217	7035	5.06
	221	7055	4.85
	225	7075	4.79
	229	7095	5.00
	233	7115	-2.89
802.11be EHT40	195	6925	7.39
	203	6965	7.44
	211	7005	7.59
	219	7045	7.48
	227	7085	7.42
802.11be EHT80	199	6945	8.59
	215	7025	8.64
802.11be EHT160	207	6985	8.69
802.11be EHT320	191	6905	9.78

Conducted Power (Full)			
UNII-8 Ant 2_LPI			
Mode	Channel	Frequency	SISO Ant 1 Avg. Power
802.11ax HE20	189	6895	4.83
	193	6915	4.44
	197	6935	4.27
	201	6955	4.29
	205	6975	4.51
	209	6995	4.71
	213	7015	4.70
	217	7035	4.67
	221	7055	4.64
	225	7075	4.54
	229	7095	4.59
	233	7115	-3.14
802.11ax HE40	195	6925	7.99
	203	6965	7.96
	211	7005	7.18
	219	7045	7.21
	227	7085	7.02
802.11ax HE80	199	6945	8.51
	215	7025	8.52
802.11ax HE160	207	6985	8.67
802.11be EHT20	189	6895	4.97
	193	6915	4.43
	197	6935	4.29
	201	6955	4.28
	205	6975	4.54
	209	6995	4.76
	213	7015	4.74
	217	7035	4.64
	221	7055	4.64
	225	7075	4.47
	229	7095	4.64
	233	7115	-3.15
802.11be EHT40	195	6925	7.05
	203	6965	7.02
	211	7005	7.21
	219	7045	7.23
	227	7085	7.07
802.11be EHT80	199	6945	8.51
	215	7025	8.52
802.11be EHT160	207	6985	8.68
802.11be EHT320	191	6905	9.50

Conducted Power (Full)					
UNII-8 Ant 1+2_LPI					
Mode	Channel	Frequency	MIMO Ant 1 Avg. Power	MIMO Ant 2 Avg. Power	MIMO Ant 1+2 Avg. Power
802.11ax HE20	189	6895	2.07	1.84	4.97
	193	6915	1.92	1.44	4.70
	197	6935	1.82	1.23	4.55
	201	6955	1.91	1.26	4.61
	205	6975	1.95	1.57	4.77
	209	6995	2.04	1.68	4.88
	213	7015	2.12	1.75	4.95
	217	7035	2.06	1.67	4.88
	221	7055	1.91	1.61	4.77
	225	7075	1.90	1.52	4.72
	229	7095	2.01	1.68	4.86
	233	7115	-5.78	-6.12	-2.94
802.11ax HE40	195	6925	4.71	4.70	7.71
	203	6965	4.70	4.69	7.71
	211	7005	4.86	4.96	7.92
	219	7045	4.74	5.00	7.88
	227	7085	4.64	4.81	7.74
802.11ax HE80	199	6945	6.07	5.84	8.96
	215	7025	6.21	5.93	9.08
802.11ax HE160	207	6985	6.37	6.00	9.20
802.11be EHT20	189	6895	2.07	1.90	4.99
	193	6915	1.92	1.53	4.74
	197	6935	1.78	1.35	4.58
	201	6955	1.90	1.32	4.63
	205	6975	1.91	1.59	4.76
	209	6995	2.07	1.76	4.93
	213	7015	2.07	1.76	4.93
	217	7035	2.05	1.69	4.88
	221	7055	1.89	1.66	4.79
	225	7075	1.87	1.60	4.75
	229	7095	2.00	1.64	4.84
	233	7115	-5.80	-6.11	-2.94
802.11be EHT40	195	6925	4.70	4.20	7.47
	203	6965	4.67	4.21	7.46
	211	7005	4.88	4.53	7.72
	219	7045	4.74	4.48	7.62
	227	7085	4.69	4.31	7.52
802.11be EHT80	199	6945	5.83	5.42	8.64
	215	7025	5.93	5.76	8.86
802.11be EHT160	207	6985	5.90	5.58	8.76
802.11be EHT320	191	6905	6.93	6.71	9.83

Conducted Power (Full)			
UNII-5 Ant 1_SP			
Mode	Channel	Frequency	SISO Ant 0 Avg. Power
802.11ax HE20	1	5955	9.56
	5	5975	9.73
	9	5995	9.64
	13	6015	9.66
	17	6035	9.69
	21	6055	9.66
	25	6075	9.68
	29	6095	9.73
	33	6115	9.89
	37	6135	9.96
	41	6155	9.83
	45	6175	9.93
	49	6195	9.80
	53	6215	9.81
	57	6235	9.79
	61	6255	9.65
	65	6275	9.76
	69	6295	9.61
	73	6315	9.71
	77	6335	9.63
802.11ax HE40	81	6355	9.76
	85	6375	9.72
	89	6395	9.70
	93	6415	9.67
	3	5965	9.60
	11	6005	9.61
	19	6045	9.67
	27	6085	9.72
	35	6125	9.59
	43	6165	9.79
802.11ax HE80	51	6205	9.83
	59	6245	9.65
	67	6285	9.57
	75	6325	9.64
	83	6365	9.75
	91	6405	9.62
802.11ax HE160	7	5985	9.64
	23	6065	9.73
	39	6145	9.83
	55	6225	9.80
	71	6305	9.70
	87	6385	9.73
	15	6025	9.67
	47	6185	10.07
	79	6345	9.75

Conducted Power (Full)			
UNII-5 Ant 1_SP			
Mode	Channel	Frequency	SISO Ant 0 Avg. Power
802.11be EHT20	1	5955	9.56
	5	5975	9.74
	9	5995	9.60
	13	6015	9.63
	17	6035	9.67
	21	6055	9.68
	25	6075	9.69
	29	6095	9.67
	33	6115	9.80
	37	6135	9.95
	41	6155	9.85
	45	6175	9.95
	49	6195	9.84
	53	6215	9.78
	57	6235	9.83
	61	6255	9.64
	65	6275	9.78
	69	6295	9.55
	73	6315	9.66
	77	6335	9.67
802.11be EHT40	81	6355	9.74
	85	6375	9.76
	89	6395	9.67
	93	6415	9.59
	3	5965	9.46
	11	6005	9.50
	19	6045	9.53
	27	6085	9.57
	35	6125	9.73
	43	6165	9.75
802.11be EHT80	51	6205	9.77
	59	6245	9.60
	67	6285	9.54
	75	6325	9.58
	83	6365	9.71
802.11be EHT160	91	6405	9.63
	7	5985	9.45
	23	6065	9.55
	39	6145	9.73
	55	6225	9.69
802.11be EHT320	71	6305	9.63
	87	6385	9.66
	15	6025	9.46
802.11be EHT320	47	6185	9.71
	79	6345	9.70
802.11be EHT320	31	6105	10.17
	63	6265	10.18

Conducted Power (Full)			
UNII-5 Ant 2_SP			
Mode	Channel	Frequency	SISO Ant 1 Avg. Power
802.11ax HE20	1	5955	9.59
	5	5975	9.40
	9	5995	9.59
	13	6015	9.59
	17	6035	9.48
	21	6055	9.38
	25	6075	9.47
	29	6095	9.62
	33	6115	9.58
	37	6135	9.75
	41	6155	9.77
	45	6175	9.57
	49	6195	9.57
	53	6215	9.50
	57	6235	9.44
	61	6255	9.46
	65	6275	9.41
	69	6295	9.47
	73	6315	9.45
	77	6335	9.52
802.11ax HE40	81	6355	9.54
	85	6375	9.70
	89	6395	9.76
	93	6415	9.62
	3	5965	9.36
	11	6005	9.56
	19	6045	9.47
	27	6085	9.46
	35	6125	9.66
	43	6165	9.64
802.11ax HE80	51	6205	9.47
	59	6245	9.41
	67	6285	9.34
	75	6325	9.41
	83	6365	9.53
	91	6405	9.58
802.11ax HE160	7	5985	9.57
	23	6065	9.48
	39	6145	9.69
	55	6225	9.49
	71	6305	9.49
	87	6385	9.64
	15	6025	9.36
	47	6185	9.79
	79	6345	9.53

Conducted Power (Full)			
UNII-5 Ant 2_SP			
Mode	Channel	Frequency	SISO Ant 1 Avg. Power
802.11be EHT20	1	5955	9.47
	5	5975	9.35
	9	5995	9.51
	13	6015	9.50
	17	6035	9.39
	21	6055	9.39
	25	6075	9.41
	29	6095	9.58
	33	6115	9.60
	37	6135	9.78
	41	6155	9.78
	45	6175	9.54
	49	6195	9.52
	53	6215	9.56
	57	6235	9.42
	61	6255	9.54
	65	6275	9.43
	69	6295	9.55
	73	6315	9.46
	77	6335	9.55
802.11be EHT40	81	6355	9.58
	85	6375	9.75
	89	6395	9.79
	93	6415	9.67
	3	5965	9.30
	11	6005	9.47
	19	6045	9.34
	27	6085	9.37
	35	6125	9.62
	43	6165	9.65
802.11be EHT80	51	6205	9.52
	59	6245	9.48
	67	6285	9.42
	75	6325	9.44
	83	6365	9.54
	91	6405	9.61
802.11be EHT160	7	5985	9.48
	23	6065	9.41
	39	6145	9.67
	55	6225	9.51
	71	6305	9.52
802.11be EHT320	87	6385	9.62
	15	6025	9.32
	47	6185	9.53
	79	6345	9.53
	31	6105	9.93
	63	6265	9.98

Conducted Power (Full)					
UNII-5 Ant 1+2_SP					
Mode	Channel	Frequency	MIMO Ant 1 Avg. Power	MIMO Ant 2 Avg. Power	MIMO Ant 1+2 Avg. Power
802.11ax HE20	1	5955	6.81	6.69	9.76
	5	5975	6.92	6.50	9.73
	9	5995	6.86	6.64	9.76
	13	6015	6.92	6.69	9.82
	17	6035	6.87	6.57	9.74
	21	6055	6.92	6.58	9.76
	25	6075	6.95	6.66	9.82
	29	6095	6.95	6.76	9.87
	33	6115	7.12	6.77	9.96
	37	6135	7.20	7.01	10.12
	41	6155	7.12	6.98	10.06
	45	6175	7.29	6.80	10.06
	49	6195	7.13	6.75	9.95
	53	6215	7.11	6.74	9.94
	57	6235	7.11	6.68	9.91
	61	6255	6.98	6.65	9.83
	65	6275	7.04	6.64	9.85
	69	6295	6.89	6.65	9.78
	73	6315	6.98	6.62	9.82
	77	6335	6.86	6.71	9.80
	81	6355	7.13	6.78	9.97
	85	6375	7.04	6.87	9.97
	89	6395	7.04	6.94	10.00
	93	6415	7.01	6.78	9.90
802.11ax HE40	3	5965	6.83	6.49	9.67
	11	6005	6.84	6.67	9.76
	19	6045	6.97	6.54	9.77
	27	6085	6.95	6.61	9.80
	35	6125	7.09	6.89	10.00
	43	6165	7.10	6.93	10.03
	51	6205	7.11	6.74	9.94
	59	6245	6.97	6.69	9.84
	67	6285	6.88	6.61	9.76
	75	6325	6.93	6.64	9.80
	83	6365	7.09	6.77	9.94
	91	6405	6.99	6.83	9.92
802.11ax HE80	7	5985	6.86	6.63	9.76
	23	6065	6.93	6.59	9.77
	39	6145	7.09	6.88	10.00
	55	6225	7.08	6.69	9.90
	71	6305	6.91	6.65	9.79
	87	6385	7.04	6.84	9.95
802.11ax HE160	15	6025	6.86	6.52	9.70
	47	6185	7.31	6.95	10.14
	79	6345	7.00	6.70	9.86

Conducted Power (Full)					
UNII-5 Ant 1+2_SP					
Mode	Channel	Frequency	MIMO Ant 1 Avg. Power	MIMO Ant 2 Avg. Power	MIMO Ant 1+2 Avg. Power
802.11be EHT20	1	5955	6.90	6.77	9.84
	5	5975	7.03	6.66	9.86
	9	5995	6.89	6.78	9.84
	13	6015	6.92	6.79	9.86
	17	6035	6.91	6.64	9.79
	21	6055	6.92	6.69	9.82
	25	6075	6.94	6.72	9.84
	29	6095	6.99	6.84	9.93
	33	6115	7.11	6.86	10.00
	37	6135	7.20	7.04	10.13
	41	6155	7.07	7.10	10.10
	45	6175	7.23	6.87	10.07
	49	6195	7.11	6.79	9.96
	53	6215	7.12	6.77	9.96
	57	6235	7.10	6.81	9.97
	61	6255	6.96	6.71	9.84
	65	6275	7.04	6.77	9.92
	69	6295	6.89	6.75	9.83
	73	6315	6.95	6.74	9.86
	77	6335	6.89	6.82	9.87
	81	6355	7.12	6.91	10.03
	85	6375	7.09	6.97	10.04
	89	6395	7.04	7.10	10.08
	93	6415	6.94	6.92	9.94
802.11be EHT40	3	5965	6.81	6.59	9.71
	11	6005	6.88	6.76	9.83
	19	6045	6.93	6.64	9.80
	27	6085	6.93	6.67	9.81
	35	6125	7.12	6.92	10.03
	43	6165	7.08	6.93	10.02
	51	6205	7.09	6.82	9.97
	59	6245	6.94	6.75	9.86
	67	6285	6.90	6.68	9.80
	75	6325	6.87	6.72	9.80
	83	6365	7.03	6.88	9.97
	91	6405	6.93	6.93	9.94
802.11be EHT80	7	5985	6.72	6.72	9.73
	23	6065	6.87	6.65	9.77
	39	6145	7.13	6.95	10.05
	55	6225	7.10	6.78	9.95
	71	6305	6.92	6.74	9.85
	87	6385	7.00	6.95	9.99
802.11be EHT160	15	6025	6.80	6.65	9.73
	47	6185	7.02	6.79	9.92
	79	6345	7.00	6.80	9.91
802.11be EHT320	31	6105	7.23	7.00	10.12
	63	6265	7.21	7.04	10.14

Conducted Power (Full)			
UNII-7 Ant 1_SP			
Mode	Channel	Frequency	SISO Ant 0 Avg. Power
802.11ax HE20	117	6535	9.83
	121	6555	9.85
	125	6575	9.99
	129	6595	9.97
	133	6615	10.08
	137	6635	9.92
	141	6655	9.81
	145	6675	9.82
	149	6695	9.82
	153	6715	9.89
	157	6735	10.11
	161	6755	10.13
	165	6775	10.16
	169	6795	9.94
	173	6815	9.73
	177	6835	9.64
802.11ax HE40	181	6855	9.63
	123	6565	9.80
	131	6605	9.98
	139	6645	9.74
	147	6685	9.75
	155	6725	10.03
	163	6765	10.09
802.11ax HE80	171	6805	9.85
	179	6845	9.59
	135	6625	9.99
802.11ax HE160	151	6705	9.86
	167	6785	9.98
	143	6665	10.24

Conducted Power (Full)			
UNII-7 Ant 1_SP			
Mode	Channel	Frequency	SISO Ant 0 Avg. Power
802.11be EHT20	117	6535	9.73
	121	6555	9.75
	125	6575	9.86
	129	6595	9.87
	133	6615	9.99
	137	6635	9.84
	141	6655	9.72
	145	6675	9.75
	149	6695	9.68
	153	6715	9.87
	157	6735	10.05
	161	6755	10.08
	165	6775	10.16
	169	6795	9.88
	173	6815	9.75
	177	6835	9.60
802.11be EHT40	181	6855	9.63
	123	6565	9.65
	131	6605	9.86
	139	6645	9.69
	147	6685	9.65
	155	6725	9.99
	163	6765	10.09
802.11be EHT80	171	6805	9.83
	179	6845	9.53
	135	6625	9.90
802.11be EHT160	151	6705	9.82
	167	6785	9.99
802.11be EHT320	143	6665	9.84
	127	6585	10.30
	159	6745	10.45

Conducted Power (Full)			
UNII-7 Ant 2_SP			
Mode	Channel	Frequency	SISO Ant 1 Avg. Power
802.11ax HE20	117	6535	9.78
	121	6555	9.85
	125	6575	9.71
	129	6595	9.84
	133	6615	9.93
	137	6635	10.11
	141	6655	9.81
	145	6675	9.66
	149	6695	9.53
	153	6715	9.61
	157	6735	9.85
	161	6755	9.97
	165	6775	10.14
	169	6795	9.88
	173	6815	9.57
	177	6835	9.53
	181	6855	9.47
802.11ax HE40	123	6565	9.70
	131	6605	9.82
	139	6645	9.95
	147	6685	9.45
	155	6725	9.47
	163	6765	10.02
	171	6805	9.63
	179	6845	9.44
802.11ax HE80	135	6625	9.96
	151	6705	9.71
	167	6785	9.88
802.11ax HE160	143	6665	10.17

Conducted Power (Full)			
UNII-7 Ant 2_SP			
Mode	Channel	Frequency	SISO Ant 1 Avg. Power
802.11be EHT20	117	6535	9.69
	121	6555	9.84
	125	6575	9.70
	129	6595	9.81
	133	6615	9.91
	137	6635	10.07
	141	6655	9.81
	145	6675	9.67
	149	6695	9.50
	153	6715	9.65
	157	6735	9.91
	161	6755	9.96
	165	6775	10.13
	169	6795	9.91
	173	6815	9.58
	177	6835	9.54
802.11be EHT40	181	6855	9.56
	123	6565	9.67
	131	6605	9.87
	139	6645	9.94
	147	6685	9.45
	155	6725	9.80
	163	6765	10.05
802.11be EHT80	171	6805	9.66
	179	6845	9.44
	135	6625	9.95
802.11be EHT160	151	6705	9.71
	167	6785	9.91
802.11be EHT320	143	6665	9.81
802.11be EHT320	127	6585	10.16
	159	6745	10.34

Conducted Power (Full)					
UNII-7 Ant 1+2_SP					
Mode	Channel	Frequency	MIMO Ant 1 Avg. Power	MIMO Ant 2 Avg. Power	MIMO Ant 1+2 Avg. Power
802.11ax HE20	117	6535	7.32	7.23	10.29
	121	6555	7.15	7.07	10.12
	125	6575	7.22	6.90	10.07
	129	6595	7.28	7.09	10.19
	133	6615	7.43	7.21	10.33
	137	6635	7.26	7.28	10.28
	141	6655	7.14	7.02	10.09
	145	6675	7.11	6.88	10.00
	149	6695	7.08	6.71	9.91
	153	6715	7.31	6.92	10.13
	157	6735	7.43	7.06	10.26
	161	6755	7.49	7.19	10.35
	165	6775	7.44	7.30	10.38
	169	6795	7.31	7.06	10.20
	173	6815	7.19	6.74	9.98
	177	6835	7.03	6.73	9.89
	181	6855	7.01	6.69	9.86
802.11ax HE40	123	6565	7.13	6.89	10.03
	131	6605	7.24	7.03	10.15
	139	6645	7.13	7.17	10.16
	147	6685	7.06	6.71	9.90
	155	6725	7.36	6.96	10.17
	163	6765	7.43	7.21	10.33
	171	6805	7.23	6.86	10.06
802.11ax HE80	179	6845	7.25	6.61	9.96
	135	6625	7.23	7.13	10.19
	151	6705	7.15	6.87	10.02
802.11ax HE160	167	6785	7.32	7.10	10.22
	143	6665	7.42	7.18	10.31

Conducted Power (Full)					
UNII-7 Ant 1+2_SP					
Mode	Channel	Frequency	MIMO Ant 1 Avg. Power	MIMO Ant 2 Avg. Power	MIMO Ant 1+2 Avg. Power
802.11be EHT20	117	6535	7.17	7.18	10.19
	121	6555	7.05	7.12	10.10
	125	6575	7.17	7.00	10.09
	129	6595	7.18	7.17	10.19
	133	6615	7.32	7.35	10.35
	137	6635	7.20	7.43	10.33
	141	6655	7.04	7.16	10.11
	145	6675	7.01	6.96	10.00
	149	6695	7.05	6.76	9.92
	153	6715	7.22	7.02	10.13
	157	6735	7.45	7.14	10.31
	161	6755	7.44	7.35	10.41
	165	6775	7.45	7.39	10.43
	169	6795	7.27	7.13	10.21
	173	6815	7.16	6.91	10.05
	177	6835	7.01	6.91	9.97
802.11be EHT40	181	6855	6.98	6.85	9.93
	123	6565	7.04	7.02	10.04
	131	6605	7.14	7.16	10.16
	139	6645	7.05	7.24	10.16
	147	6685	7.05	6.81	9.94
	155	6725	7.32	7.10	10.22
	163	6765	7.40	7.38	10.40
	171	6805	7.20	7.00	10.11
802.11be EHT80	179	6845	6.92	6.79	9.87
	135	6625	7.18	7.27	10.23
	151	6705	7.10	7.02	10.07
802.11be EHT160	167	6785	7.31	7.22	10.28
	143	6665	7.14	7.07	10.11
802.11be EHT320	127	6585	7.47	7.41	10.45
	159	6745	7.53	7.43	10.49

Conducted Power (Full)			
UNII-5 Ant 1_VLP			
Mode	Channel	Frequency	SISO Ant 0 Avg. Power
802.11ax HE160	15	6025	7.96
	47	6185	8.13
	79	6345	8.02

Conducted Power (Full)			
UNII-5 Ant 1_VLP			
Mode	Channel	Frequency	SISO Ant 0 Avg. Power
802.11be EHT320	31	6105	8.45
	63	6265	8.44

Conducted Power (Full)			
UNII-5 Ant 2_VLP			
Mode	Channel	Frequency	SISO Ant 1 Avg. Power
802.11ax HE160	15	6025	7.70
	47	6185	7.82
	79	6345	7.83

Conducted Power (Full)			
UNII-5 Ant 2_VLP			
Mode	Channel	Frequency	SISO Ant 1 Avg. Power
802.11be EHT320	31	6105	8.20
	63	6265	8.26

Conducted Power (Full)					
UNII-5 Ant 1+2_VLP					
Mode	Channel	Frequency	MIMO Ant 1 Avg. Power	MIMO Ant 2 Avg. Power	MIMO Ant 1+2 Avg. Power
802.11ax HE160	15	6025	5.01	4.59	7.81
	47	6185	5.24	4.74	8.01
	79	6345	5.02	4.71	7.88

Conducted Power (Full)					
UNII-5 Ant 1+2_VLP					
Mode	Channel	Frequency	MIMO Ant 1 Avg. Power	MIMO Ant 2 Avg. Power	MIMO Ant 1+2 Avg. Power
802.11be EHT320	31	6105	5.54	5.26	8.41
	63	6265	5.48	5.37	8.44

Conducted Power (Full)			
UNII-7 Ant 1_VLP			
Mode	Channel	Frequency	SISO Ant 0 Avg. Power
802.11ax HE160	143	6665	8.21

Conducted Power (Full)			
UNII-7 Ant 1_VLP			
Mode	Channel	Frequency	SISO Ant 0 Avg. Power
802.11be EHT320	127	6585	8.53
	159	6745	8.46

Conducted Power (Full)			
UNII-7 Ant 2_VLP			
Mode	Channel	Frequency	SISO Ant 1 Avg. Power
802.11ax HE160	143	6665	8.09

Conducted Power (Full)			
UNII-7 Ant 2_VLP			
Mode	Channel	Frequency	SISO Ant 1 Avg. Power
802.11be EHT320	127	6585	8.40
	159	6745	8.43

Conducted Power (Full)					
UNII-7 Ant 1+2_VLP					
Mode	Channel	Frequency	MIMO Ant 1 Avg. Power	MIMO Ant 2 Avg. Power	MIMO Ant 1+2 Avg. Power
802.11ax HE160	143	6665	5.34	5.01	8.19

Conducted Power (Full)					
UNII-7 Ant 1+2_VLP					
Mode	Channel	Frequency	MIMO Ant 1 Avg. Power	MIMO Ant 2 Avg. Power	MIMO Ant 1+2 Avg. Power
802.11be EHT320	127	6585	5.55	5.39	8.48
	159	6745	5.71	5.56	8.65

Appendix F. SAR and Incident Power Density Test Result

SAR Results for Body Exposure Condition.

Note:

1. SAR testing for WLAN / BT was performed on the maximum power mode.
2. The "< 0.001" means there is no SAR value or the SAR is too low to be measured.
3. Per KDB 388624 APPENDIX OVER6G, the minimum of 5 channels to perform IPD across U-NII 5,6,7 and 8. and measured results were scaled by factor 1.545 to reported power density when measurement uncertainty exceed 30%.

Body SAR and Power Density Test Result

Body SAR and Power Density Test Result																												
System & Position						DUT Configuration			SAR											Power Density								
Plot No.	Band	Mode	Test Position	Separation Distance (mm)	Channel	Ant Status	Data Rate	6G Power Mode	Duty Cycle	Crest Factor	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)	Measured APD W/m² (4cm²)	Scaled APD W/m² (4cm²)	Grid Step [λ]	iPD [W/m2]	Scaling Factor for Measurement Uncertainty	Averaging Area [cm2]	Power Drift [dB]	Normal psPD [W/m2]	Scaled Normal psPD [W/m2]	Total psPD [W/m2]	Scaled Total psPD [W/m2]	
1	WLAN2.4G	802.11b	Bottom of Laptop	0	13	Ant 1	1M		96.75	1.03	17.00	16.93	1.02	0.03	0.845	0.888	-	-										
	WLAN2.4G	802.11b	Back of Panel	25	13	Ant 1	1M		96.75	1.03	17.00	16.93	1.02	0	<0.001	0.000	-	-										
	WLAN2.4G	802.11b	Top Side of Panel	25	13	Ant 1	1M		96.75	1.03	17.00	16.93	1.02	0	<0.001	0.000	-	-										
	WLAN2.4G	802.11b	Left Side of Panel	25	13	Ant 1	1M		96.75	1.03	17.00	16.93	1.02	0	<0.001	0.000	-	-										
	WLAN2.4G	802.11b	Right Side of Panel	25	13	Ant 1	1M		96.75	1.03	17.00	16.93	1.02	0	<0.001	0.000	-	-										
	WLAN2.4G	802.11b	Bottom of Laptop	0	13	Ant 2	1M		96.98	1.03	17.00	16.96	1.01	0.01	0.773	0.804	-	-										
	WLAN2.4G	802.11b	Back of Panel	25	13	Ant 2	1M		96.98	1.03	17.00	16.96	1.01	0	<0.001	0.000	-	-										
	WLAN2.4G	802.11b	Top Side of Panel	25	13	Ant 2	1M		96.98	1.03	17.00	16.96	1.01	0	<0.001	0.000	-	-										
	WLAN2.4G	802.11b	Left Side of Panel	25	13	Ant 2	1M		96.98	1.03	17.00	16.96	1.01	0	<0.001	0.000	-	-										
	WLAN2.4G	802.11b	Right Side of Panel	25	13	Ant 2	1M		96.98	1.03	17.00	16.96	1.01	0	<0.001	0.000	-	-										
	WLAN2.4G	802.11n HT40	Bottom of Laptop	0	3	Ant 1+2	HT0		97.90	1.02	17.00	16.80	1.05	-0.05	0.409	0.438	-	-										
	WLAN2.4G	802.11n HT40	Back of Panel	25	3	Ant 1+2	HT0		97.90	1.02	17.00	16.80	1.05	0	<0.001	0.000	-	-										
	WLAN2.4G	802.11n HT40	Top Side of Panel	25	3	Ant 1+2	HT0		97.90	1.02	17.00	16.80	1.05	0	<0.001	0.000	-	-										
	WLAN2.4G	802.11n HT40	Left Side of Panel	25	3	Ant 1+2	HT0		97.90	1.02	17.00	16.80	1.05	0	<0.001	0.000	-	-										
	WLAN2.4G	802.11n HT40	Right Side of Panel	25	3	Ant 1+2	HT0		97.90	1.02	17.00	16.80	1.05	0	<0.001	0.000	-	-										
	WLAN2.4G	802.11b	Bottom of Laptop	0	1	Ant 1	1M		96.75	1.03	17.00	16.75	1.06	0.03	0.553	0.604	-	-										
	WLAN2.4G	802.11b	Bottom of Laptop	0	6	Ant 1	1M		96.75	1.03	17.00	16.74	1.06	0.05	0.811	0.885	-	-										
	WLAN2.4G	802.11b	Bottom of Laptop	0	11	Ant 1	1M		96.75	1.03	17.00	16.82	1.04	-0.13	0.825	0.884	-	-										
	WLAN2.4G	802.11b	Bottom of Laptop	0	12	Ant 1	1M		96.75	1.03	17.00	16.89	1.02	0.08	0.797	0.837	-	-										
	WLAN2.4G	802.11b	Bottom of Laptop	0	1	Ant 2	1M		96.98	1.03	17.00	16.65	1.08	-0.02	0.547	0.608	-	-										
	WLAN2.4G	802.11b	Bottom of Laptop	0	6	Ant 2	1M		96.98	1.03	17.00	16.78	1.05	0.13	0.591	0.639	-	-										
	WLAN2.4G	802.11b	Bottom of Laptop	0	11	Ant 2	1M		96.98	1.03	17.00	16.76	1.06	-0.12	0.666	0.727	-	-										
	WLAN2.4G	802.11b	Bottom of Laptop	0	12	Ant 2	1M		96.98	1.03	17.00	16.91	1.02	-0.16	0.751	0.789	-	-										
	WLAN2.4G	802.11b	Bottom of Laptop	0	13	Ant 1	1M		96.75	1.03	17.00	16.93	1.02	0.07	0.815	0.856	-	-										
	2	WLAN5.3G	802.11be EHT160	Bottom of Laptop	0	50	Ant 1	EHT0		100.00	1.00	13.00	11.96	1.27	-0.01	0.562	0.714	-	-									
WLAN5.3G		802.11be EHT160	Back of Panel	25	50	Ant 1	EHT0		100.00	1.00	13.00	11.96	1.27	0	<0.001	0.000	-	-										
WLAN5.3G		802.11be EHT160	Top Side of Panel	25	50	Ant 1	EHT0		100.00	1.00	13.00	11.96	1.27	0	<0.001	0.000	-	-										
WLAN5.3G		802.11be EHT160	Left Side of Panel	25	50	Ant 1	EHT0		100.00	1.00	13.00	11.96	1.27	0	<0.001	0.000	-	-										
WLAN5.3G		802.11be EHT160	Right Side of Panel	25	50	Ant 1	EHT0		100.00	1.00	13.00	11.96	1.27	0	<0.001	0.000	-	-										
WLAN5.3G		802.11be EHT160	Bottom of Laptop	0	50	Ant 2	EHT0		100.00	1.00	13.00	12.13	1.22	-0.03	0.443	0.540	-	-										
WLAN5.3G		802.11be EHT160	Back of Panel	25	50	Ant 2	EHT0		100.00	1.00	13.00	12.13	1.22	0	<0.001	0.000	-	-										
WLAN5.3G		802.11be EHT160	Top Side of Panel	25	50	Ant 2	EHT0		100.00	1.00	13.00	12.13	1.22	0	<0.001	0.000	-	-										
WLAN5.3G		802.11be EHT160	Left Side of Panel	25	50	Ant 2	EHT0		100.00	1.00	13.00	12.13	1.22	0	<0.001	0.000	-	-										
WLAN5.3G		802.11be EHT160	Right Side of Panel	25	50	Ant 2	EHT0		100.00	1.00	13.00	12.13	1.22	0	<0.001	0.000	-	-										
WLAN5.3G		802.11be EHT160	Bottom of Laptop	0	50	Ant 1+2	EHT0		100.00	1.00	13.00	12.09	1.23	-0.07	0.264	0.325	-	-										
WLAN5.3G		802.11be EHT160	Back of Panel	25	50	Ant 1+2	EHT0		100.00	1.00	13.00	12.09	1.23	0	<0.001	0.000	-	-										
WLAN5.3G		802.11be EHT160	Top Side of Panel	25	50	Ant 1+2	EHT0		100.00	1.00	13.00	12.09	1.23	0	<0.001	0.000	-	-										
WLAN5.3G		802.11be EHT160	Left Side of Panel	25	50	Ant 1+2	EHT0		100.00	1.00	13.00	12.09	1.23	0	<0.001	0.000	-	-										
WLAN5.3G		802.11be EHT160	Right Side of Panel	25	50	Ant 1+2	EHT0		100.00	1.00	13.00	12.09	1.23	0	<0.001	0.000	-	-										
3	WLAN5.6G	802.11be EHT160	Bottom of Laptop	0	114	Ant 1	EHT0		100.00	1.00	13.50	13.16	1.08	-0.01	1.060	1.145	-	-										
	WLAN5.6G	802.11be EHT160	Back of Panel	25	114	Ant 1	EHT0		100.00	1.00	13.50	13.16	1.08	0	<0.001	0.000	-	-										
	WLAN5.6G	802.11be EHT160	Top Side of Panel	25	114	Ant 1	EHT0		100.00	1.00	13.50	13.16	1.08	0	<0.001	0.000	-	-										
	WLAN5.6G	802.11be EHT160	Left Side of Panel	25	114	Ant 1	EHT0		100.00	1.00	13.50	13.16	1.08	0	<0.001	0.000	-	-										
	WLAN5.6G	802.11be EHT160	Right Side of Panel	25	114	Ant 1	EHT0		100.00	1.00	13.50	13.16	1.08	0	<0.001	0.000	-	-										
	WLAN5.6G	802.11be EHT160	Bottom of Laptop	0	114	Ant 2	EHT0		100.00	1.00	13.50	13.19	1.07	0.03	0.654	0.700	-	-										
	WLAN5.6G	802.11be EHT160	Back of Panel	25	114	Ant 2	EHT0		100.00	1.00	13.50	13.19	1.07	0	<0.001	0.000	-	-										
	WLAN5.6G	802.11be EHT160	Top Side of Panel	25	114	Ant 2	EHT0		100.00	1.00	13.50	13.19	1.07	0	<0.001	0.000	-	-										
	WLAN5.6G	802.11be EHT160	Left Side of Panel	25	114	Ant 2	EHT0		100.00	1.00	13.50	13.19	1.07	0	<0.001	0.000	-	-										
	WLAN5.6G	802.11be EHT160	Right Side of Panel	25	114	Ant 2	EHT0		100.00	1.00	13.50	13.19	1.07	0	<0.001	0.000	-	-										
	WLAN5.6G	802.11be EHT160	Bottom of Laptop	0	114	Ant 1+2	EHT0		100.00	1.00	13.50	13.21	1.07	-0.09	0.398	0.426	-	-										
	WLAN5.6G	802.11be EHT160	Back of Panel	25	114	Ant 1+2	EHT0		100.00	1.00	13.50	13.21	1.07	0	<0.001	0.000	-	-										
	WLAN5.6G	802.11be EHT160	Top Side of Panel	25	114	Ant 1+2	EHT0		100.00	1.00	13.50	13.21	1.07	0	<0.001	0.000	-	-										
	WLAN5.6G	802.11be EHT160	Left Side of Panel	25	114	Ant 1+2	EHT0		100.00	1.00	13.50	13.21	1.07	0	<0.001	0.000	-	-										
	WLAN5.6G	802.11be EHT160	Right Side of Panel	25	114	Ant 1+2	EHT0		100.00	1.00	13.50	13.21	1.07															

Body SAR and Power Density Test Result

Body SAR and Power Density Test Result																												
System & Position						DUT Configuration			SAR											Power Density								
Plot No.	Band	Mode	Test Position	Separation Distance (mm)	Channel	Ant Status	Data Rate	6G Power Mode	Duty Cycle	Crest Factor	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)	Measured APD W/m ² (4cm ²)	Scaled APD W/m ² (4cm ²)	Grid Step [λ]	iPD [W/m2]	Scaling Factor for Measurement Uncertainty	Averaging Area [cm2]	Power Drift [dB]	Normal psPD [W/m2]	Scaled Normal psPD [W/m2]	Total psPD [W/m2]	Scaled Total psPD [W/m2]	
4	WLAN5.8G	802.11be EHT80	Bottom of Laptop	0	155	Ant 1	EHT0		100.00	1.00	14.00	13.31	1.17	0.01	0.885	1.035	-	-										
	WLAN5.8G	802.11be EHT80	Back of Panel	25	155	Ant 1	EHT0		100.00	1.00	14.00	13.31	1.17	0	<0.001	0.000	-	-										
	WLAN5.8G	802.11be EHT80	Top Side of Panel	25	155	Ant 1	EHT0		100.00	1.00	14.00	13.31	1.17	0	<0.001	0.000	-	-										
	WLAN5.8G	802.11be EHT80	Left Side of Panel	25	155	Ant 1	EHT0		100.00	1.00	14.00	13.31	1.17	0	<0.001	0.000	-	-										
	WLAN5.8G	802.11be EHT80	Right Side of Panel	25	155	Ant 1	EHT0		100.00	1.00	14.00	13.31	1.17	0	<0.001	0.000	-	-										
	WLAN5.8G	802.11be EHT80	Bottom of Laptop	0	155	Ant 2	EHT0		100.00	1.00	14.00	13.42	1.14	0	0.687	0.783	-	-										
	WLAN5.8G	802.11be EHT80	Back of Panel	25	155	Ant 2	EHT0		100.00	1.00	14.00	13.42	1.14	0	<0.001	0.000	-	-										
	WLAN5.8G	802.11be EHT80	Top Side of Panel	25	155	Ant 2	EHT0		100.00	1.00	14.00	13.42	1.14	0	<0.001	0.000	-	-										
	WLAN5.8G	802.11be EHT80	Left Side of Panel	25	155	Ant 2	EHT0		100.00	1.00	14.00	13.42	1.14	0	<0.001	0.000	-	-										
	WLAN5.8G	802.11be EHT80	Right Side of Panel	25	155	Ant 2	EHT0		100.00	1.00	14.00	13.42	1.14	0	<0.001	0.000	-	-										
	WLAN5.8G	802.11be EHT80	Bottom of Laptop	0	155	Ant 1+2	EHT0		100.00	1.00	14.00	13.40	1.15	0.05	0.458	0.527	-	-										
	WLAN5.8G	802.11be EHT80	Back of Panel	25	155	Ant 1+2	EHT0		100.00	1.00	14.00	13.40	1.15	0	<0.001	0.000	-	-										
	WLAN5.8G	802.11be EHT80	Top Side of Panel	25	155	Ant 1+2	EHT0		100.00	1.00	14.00	13.40	1.15	0	<0.001	0.000	-	-										
	WLAN5.8G	802.11be EHT80	Left Side of Panel	25	155	Ant 1+2	EHT0		100.00	1.00	14.00	13.40	1.15	0	<0.001	0.000	-	-										
	WLAN5.8G	802.11be EHT80	Right Side of Panel	25	155	Ant 1+2	EHT0		100.00	1.00	14.00	13.40	1.15	0	<0.001	0.000	-	-										
	WLAN5.8G	802.11be EHT80	Bottom of Laptop	0	155	Ant 1	EHT0		100.00	1.00	14.00	13.31	1.17	-0.08	0.862	1.009	-	-										
5	WLAN5.9G	802.11be EHT160	Bottom of Laptop	0	163	Ant 1	EHT0		100.00	1.00	14.00	13.27	1.18	-0.05	0.721	0.851	-	-										
	WLAN5.9G	802.11be EHT160	Back of Panel	25	163	Ant 1	EHT0		100.00	1.00	14.00	13.27	1.18	0	<0.001	0.000	-	-										
	WLAN5.9G	802.11be EHT160	Top Side of Panel	25	163	Ant 1	EHT0		100.00	1.00	14.00	13.27	1.18	0	<0.001	0.000	-	-										
	WLAN5.9G	802.11be EHT160	Left Side of Panel	25	163	Ant 1	EHT0		100.00	1.00	14.00	13.27	1.18	0	<0.001	0.000	-	-										
	WLAN5.9G	802.11be EHT160	Right Side of Panel	25	163	Ant 1	EHT0		100.00	1.00	14.00	13.27	1.18	0	<0.001	0.000	-	-										
	WLAN5.9G	802.11be EHT160	Bottom of Laptop	0	163	Ant 2	EHT0		100.00	1.00	14.00	13.34	1.16	0.11	0.692	0.803	-	-										
	WLAN5.9G	802.11be EHT160	Back of Panel	25	163	Ant 2	EHT0		100.00	1.00	14.00	13.34	1.16	0	<0.001	0.000	-	-										
	WLAN5.9G	802.11be EHT160	Top Side of Panel	25	163	Ant 2	EHT0		100.00	1.00	14.00	13.34	1.16	0	<0.001	0.000	-	-										
	WLAN5.9G	802.11be EHT160	Left Side of Panel	25	163	Ant 2	EHT0		100.00	1.00	14.00	13.34	1.16	0	<0.001	0.000	-	-										
	WLAN5.9G	802.11be EHT160	Right Side of Panel	25	163	Ant 2	EHT0		100.00	1.00	14.00	13.34	1.16	0	<0.001	0.000	-	-										
	WLAN5.9G	802.11be EHT160	Bottom of Laptop	0	163	Ant 1+2	EHT0		100.00	1.00	14.00	13.35	1.16	0.15	0.375	0.435	-	-										
	WLAN5.9G	802.11be EHT160	Back of Panel	25	163	Ant 1+2	EHT0		100.00	1.00	14.00	13.35	1.16	0	<0.001	0.000	-	-										
	WLAN5.9G	802.11be EHT160	Top Side of Panel	25	163	Ant 1+2	EHT0		100.00	1.00	14.00	13.35	1.16	0	<0.001	0.000	-	-										
	WLAN5.9G	802.11be EHT160	Left Side of Panel	25	163	Ant 1+2	EHT0		100.00	1.00	14.00	13.35	1.16	0	<0.001	0.000	-	-										
	WLAN5.9G	802.11be EHT160	Right Side of Panel	25	163	Ant 1+2	EHT0		100.00	1.00	14.00	13.35	1.16	0	<0.001	0.000	-	-										
		Bluetooth	BR / EDR	Bottom of Laptop	0	78	Ant 1	DH5		76.47	1.31	15.00	14.12	1.22	0.01	0.228	0.364	-	-									
Bluetooth		BR / EDR	Back of Panel	25	78	Ant 1	DH5		76.47	1.31	15.00	14.12	1.22	0	<0.001	0.000	-	-										
Bluetooth		BR / EDR	Top Side of Panel	25	78	Ant 1	DH5		76.47	1.31	15.00	14.12	1.22	0	<0.001	0.000	-	-										
Bluetooth		BR / EDR	Left Side of Panel	25	78	Ant 1	DH5		76.47	1.31	15.00	14.12	1.22	0	<0.001	0.000	-	-										
Bluetooth		BR / EDR	Right Side of Panel	25	78	Ant 1	DH5		76.47	1.31	15.00	14.12	1.22	0	<0.001	0.000	-	-										
Bluetooth		BR / EDR	Bottom of Laptop	0	0	Ant 1	DH5		76.47	1.31	15.00	13.64	1.37	-0.04	0.111	0.199	-	-										
6	Bluetooth	BR / EDR	Bottom of Laptop	0	39	Ant 1	DH5		76.47	1.31	15.00	13.79	1.32	0.13	0.247	0.427	-	-										
	WLAN6G	802.11be EHT320	Bottom of Laptop	0	159	Ant 1	EHT0	SP/LPI	100.00	1.00	10.50	10.45	1.01	0.02	0.332	0.335	1.510	1.525	0.0562	3.82	1.545	4.00	-0.08	1.220	1.885	2.800	4.369	
	WLAN6G	802.11be EHT320	Back of Panel	25	159	Ant 1	EHT0	SP/LPI	100.00	1.00	10.50	10.45	1.01	0	<0.001	0.000	<0.001	0.000	0.0562	0	1.545	4.00	0	<0.001	0.000	<0.001	0.000	
	WLAN6G	802.11be EHT320	Top Side of Panel	25	159	Ant 1	EHT0	SP/LPI	100.00	1.00	10.50	10.45	1.01	0	<0.001	0.000	<0.001	0.000	0.0562	0	1.545	4.00	0	<0.001	0.000	<0.001	0.000	
	WLAN6G	802.11be EHT320	Left Side of Panel	25	159	Ant 1	EHT0	SP/LPI	100.00	1.00	10.50	10.45	1.01	0	<0.001	0.000	<0.001	0.000	0.0562	0	1.545	4.00	0	<0.001	0.000	<0.001	0.000	
	WLAN6G	802.11be EHT320	Right Side of Panel	25	159	Ant 1	EHT0	SP/LPI	100.00	1.00	10.50	10.45	1.01	0	<0.001	0.000	<0.001	0.000	0.0562	0	1.545	4.00	0	<0.001	0.000	<0.001	0.000	
	WLAN6G	802.11be EHT320	Bottom of Laptop	0	159	Ant 2	EHT0	SP/LPI	100.00	1.00	10.50	10.34	1.04	0.17	0.267	0.278	1.750	1.820	0.0562	3.17	1.545	4.00	-0.16	1.020	1.576	2.320	3.728	
	WLAN6G	802.11be EHT320	Back of Panel	25	159	Ant 2	EHT0	SP/LPI	100.00	1.00	10.50	10.34	1.04	0	<0.001	0.000	<0.001	0.000	0.0562	0	1.545	4.00	0	<0.001	0.000	<0.001	0.000	
	WLAN6G	802.11be EHT320	Top Side of Panel	25	159	Ant 2	EHT0	SP/LPI	100.00	1.00	10.50	10.34	1.04	0	<0.001	0.000	<0.001	0.000	0.0562	0	1.545	4.00	0	<0.001	0.000	<0.001	0.000	
	WLAN6G	802.11be EHT320	Left Side of Panel	25	159	Ant 2	EHT0	SP/LPI	100.00	1.00	10.50	10.34	1.04	0	<0.001	0.000	<0.001	0.000	0.0562	0	1.545	4.00	0	<0.001	0.000	<0.001	0.000	
	WLAN6G	802.11be EHT320	Right Side of Panel	25	159	Ant 2	EHT0	SP/LPI	100.00	1.00	10.50	10.34	1.04	0	<0.001	0.000	<0.001	0.000	0.0562	0	1.545	4.00	0	<0.001	0.000	<0.001	0.000	
	WLAN6G	802.11be EHT320	Bottom of Laptop	0	159	Ant 1+2	EHT0	SP/LPI	100.00	1.00	10.50	10.49	1.00	-0.11	0.148	0.148	0.961	0.961	0.0562	1.69	1.545	4.00	0.06	0.543	0.839	1.240	1.916	
	WLAN6G	802.11be EHT320	Back of Panel	25	159	Ant 1+2	EHT0	SP/LPI	100.00	1.00	10.50	10.49	1.00	0	<0.001	0.000	<0.001	0.000	0.0562	0	1.545	4.00	0	<0.001	0.000	<0.001	0.000	
	WLAN6G	802.11be EHT320	Top Side of Panel	25	159	Ant 1+2	EHT0	SP/LPI	100.00	1.00	10.50	10.49	1.00	0	<0.001	0.000	<0.001	0.000	0.0562	0	1.545	4.00	0	<0.001	0.000	<0.001	0.000	
	W																											

Appendix G. SAR Measurement Variability

SAR repeated measurement are shown as below.

Repeated SAR							
Plot	Band	Mode	Test Position	Ch.	Original Measured SAR-1g (W/kg)	1st Repeated SAR-1g (W/kg)	L/S Ratio
R01	WLAN2.4G	802.11b	Bottom of Laptop	13	0.845	0.815	1.04
R03	WLAN5.6G	802.11be EHT160	Bottom of Laptop	114	1.06	1.01	1.05
R04	WLAN5.8G	802.11be EHT80	Bottom of Laptop	155	0.885	0.862	1.03

Appendix H. Analysis of Simultaneous Transmission.

The analysis of simultaneous transmission SAR are shown as below.

<Possibilities of Simultaneous Transmission>

The simultaneous transmission possibilities for this device are listed as below.

Simultaneous TX Combination	Capable Transmit Configurations	Body / Bystander Exposure Condition
A	WLAN 2.4G_Ant 2 + BT_Ant 1	Yes
B	WLAN 5G_Ant 2 + BT_Ant 1	Yes
C	WLAN 5G_Ant1+2 + BT_Ant 1	Yes
D	WLAN 6G_Ant1+2 + BT_Ant 1	Yes

Notes

1. The WLAN 2.4G and WLAN 5G cannot transmit simultaneously.

Simultaneous Transmission SAR Evaluation									
Position	1	2	3	4	5	A(1+5)	B(2+5)	C(3+5)	D(4+5)
	WLAN 2.4GHz Ant 2	Max WLAN 5GHz Ant 2	Max WLAN 5GHz Ant 1+2	Max WLAN 6GHz Ant 1+2	Max BT Ant 1	Summimg result 1g SAR W/kg	Summimg result 1g SAR W/kg	Summimg result 1g SAR W/kg	Summimg result 1g SAR W/kg
	1g SAR W/kg	1g SAR W/kg	1g SAR W/kg	1g SAR W/kg	1g SAR W/kg				
Bottom of Laptop	0.804	0.803	0.527	0.148	0.427	1.231	1.230	0.954	0.575
Back of Panel	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
Top Side of Panel	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
Left Side of Panel	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
Right Side of Panel	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

Total Exposure Ratio			
Position	4	5	D(4+5)
	Max WLAN 6GHz Ant 1+2	Max BT Ant 1	Total Exposure Ratio
	psPD W/m2 (4cm2)	1g SAR W/kg	
Bottom of Laptop	1.916	0.427	0.458
Back of Panel	0.000	0.000	0.000
Top Side of Panel	0.000	0.000	0.000
Left Side of Panel	0.000	0.000	0.000
Right Side of Panel	0.000	0.000	0.000

Appendix Z. Calibration Certificate for Probe and Dipole

The SPEAG calibration certificates are shown as follows.



Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Client **B.V. ADT**
Taoyuan City

Certificate No. **D2450V2-737_Feb24**

CALIBRATION CERTIFICATE

Object **D2450V2 - SN:737**

Calibration procedure(s) **QA CAL-05.v12**
Calibration Procedure for SAR Validation Sources between 0.7-3 GHz

Calibration date: **February 19, 2024**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP2	SN: 104778	30-Mar-23 (No. 217-03804/03805)	Mar-24
Power sensor NRP-Z91	SN: 103244	30-Mar-23 (No. 217-03804)	Mar-24
Power sensor NRP-Z91	SN: 103245	30-Mar-23 (No. 217-03805)	Mar-24
Reference 20 dB Attenuator	SN: BH9394 (20k)	30-Mar-23 (No. 217-03809)	Mar-24
Type-N mismatch combination	SN: 310982 / 06327	30-Mar-23 (No. 217-03810)	Mar-24
Reference Probe EX3DV4	SN: 7349	03-Nov-23 (No. EX3-7349_Nov23)	Nov-24
DAE4	SN: 601	30-Jan-24 (No. DAE4-601_Jan24)	Jan-25

Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power meter E4419B	SN: GB39512475	30-Oct-14 (in house check Oct-22)	In house check: Oct-24
Power sensor HP 8481A	SN: US37292783	07-Oct-15 (in house check Oct-22)	In house check: Oct-24
Power sensor HP 8481A	SN: MY41093315	07-Oct-15 (in house check Oct-22)	In house check: Oct-24
RF generator R&S SMT-06	SN: 100972	15-Jun-15 (in house check Oct-22)	In house check: Oct-24
Network Analyzer Agilent E8358A	SN: US41080477	31-Mar-14 (in house check Oct-22)	In house check: Oct-24

Calibrated by: **Krešimir Franjić** **Laboratory Technician**

Approved by: **Sven Kühn** **Technical Manager**

Issued: February 19, 2024

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA

Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEC/IEEE 62209-1528, "Measurement Procedure For The Assessment Of Specific Absorption Rate Of Human Exposure To Radio Frequency Fields From Hand-Held And Body-Worn Wireless Communication Devices - Part 1528: Human Models, Instrumentation And Procedures (Frequency Range of 4 MHz to 10 GHz)", October 2020.
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- DASY System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:* The source is mounted in a touch configuration below the center marking of the flat phantom.
- Return Loss:* This parameter is measured with the source positioned under the liquid filled phantom (as described in the measurement condition clause). The Return Loss ensures low reflected power. No uncertainty required.
- SAR measured:* SAR measured at the stated antenna input power.
- SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY52	V52.10.4
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	2450 MHz $\pm$ 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	39.2	1.80 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	38.5 $\pm$ 6 %	1.87 mho/m $\pm$ 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	13.5 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	52.9 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	6.26 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	24.7 W/kg $\pm$ 16.5 % (k=2)

Appendix (Additional assessments outside the scope of SCS 0108)

Antenna Parameters with Head TSL

Impedance, transformed to feed point	$54.2 \Omega + 5.2 j\Omega$
Return Loss	- 23.8 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.161 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
-----------------	-------

DASY5 Validation Report for Head TSL

Date: 19.02.2024

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:737

Communication System: UID 0 - CW; Frequency: 2450 MHz

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.87$ S/m; $\epsilon_r = 38.5$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(7.96, 7.96, 7.96) @ 2450 MHz; Calibrated: 03.11.2023
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.01.2024
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.10.4(1535); SEMCAD X 14.6.14(7501)

Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 117.0 V/m; Power Drift = 0.03 dB


Peak SAR (extrapolated) = 27.0 W/kg

SAR(1 g) = 13.5 W/kg; SAR(10 g) = 6.26 W/kg


Smallest distance from peaks to all points 3 dB below = 9 mm

Ratio of SAR at M2 to SAR at M1 = 50.9%

Maximum value of SAR (measured) = 21.6 W/kg



Impedance Measurement Plot for Head TSL





Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Client **B.V. ADT**
Taoyuan City

Certificate No. **D5GHzV2-1019_Feb24**

CALIBRATION CERTIFICATE

Object **D5GHzV2 - SN:1019**

Calibration procedure(s) **QA CAL-22.v7**
Calibration Procedure for SAR Validation Sources between 3-10 GHz

Calibration date: **February 13, 2024**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP2	SN: 104778	30-Mar-23 (No. 217-03804/03805)	Mar-24
Power sensor NRP-Z91	SN: 103244	30-Mar-23 (No. 217-03804)	Mar-24
Power sensor NRP-Z91	SN: 103245	30-Mar-23 (No. 217-03805)	Mar-24
Reference 20 dB Attenuator	SN: BH9394 (20k)	30-Mar-23 (No. 217-03809)	Mar-24
Type-N mismatch combination	SN: 310982 / 06327	30-Mar-23 (No. 217-03810)	Mar-24
Reference Probe EX3DV4	SN: 3503	07-Mar-23 (No. EX3-3503_Mar23)	Mar-24
DAE4	SN: 601	30-Jan-24 (No. DAE4-601_Jan24)	Jan-25

Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power meter E4419B	SN: GB39512475	30-Oct-14 (in house check Oct-22)	In house check: Oct-24
Power sensor HP 8481A	SN: US37292783	07-Oct-15 (in house check Oct-22)	In house check: Oct-24
Power sensor HP 8481A	SN: MY41093315	07-Oct-15 (in house check Oct-22)	In house check: Oct-24
RF generator R&S SMT-06	SN: 100972	15-Jun-15 (in house check Oct-22)	In house check: Oct-24
Network Analyzer Agilent E8358A	SN: US41080477	31-Mar-14 (in house check Oct-22)	In house check: Oct-24

Calibrated by:	Name	Function	Signature
	Paulo Pina	Laboratory Technician	
Approved by:	Name	Function	Signature
	Sven Kühn	Technical Manager	

Issued: February 16, 2024

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- a) IEC/IEEE 62209-1528, "Measurement Procedure For The Assessment Of Specific Absorption Rate Of Human Exposure To Radio Frequency Fields From Hand-Held And Body-Worn Wireless Communication Devices - Part 1528: Human Models, Instrumentation And Procedures (Frequency Range of 4 MHz to 10 GHz)", October 2020.
- b) KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- c) DASY System Handbook

Methods Applied and Interpretation of Parameters:

- *Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL:* The source is mounted in a touch configuration below the center marking of the flat phantom.
- *Return Loss:* This parameter is measured with the source positioned under the liquid filled phantom (as described in the measurement condition clause). The Return Loss ensures low reflected power. No uncertainty required.
- *SAR measured:* SAR measured at the stated antenna input power.
- *SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY52	V52.10.4
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom V5.0	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy = 4.0 mm, dz = 1.4 mm	Graded Ratio = 1.4 (Z direction)
Frequency	5250 MHz $\pm$ 1 MHz 5600 MHz $\pm$ 1 MHz 5800 MHz $\pm$ 1 MHz	

Head TSL parameters at 5250 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	35.9	4.71 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	36.0 $\pm$ 6 %	4.53 mho/m $\pm$ 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL at 5250 MHz

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	100 mW input power	8.03 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	80.2 W/kg $\pm$ 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	100 mW input power	2.30 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	23.0 W/kg $\pm$ 19.5 % (k=2)

Head TSL parameters at 5600 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	35.5	5.07 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	35.3 $\pm$ 6 %	4.89 mho/m $\pm$ 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL at 5600 MHz

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	100 mW input power	8.31 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	82.9 W/kg $\pm$ 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	100 mW input power	2.37 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	23.6 W/kg $\pm$ 19.5 % (k=2)

Head TSL parameters at 5800 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	35.3	5.27 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	35.1 ± 6 %	5.12 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL at 5800 MHz

SAR averaged over 1 cm³ (1 g) of Head TSL	Condition	
SAR measured	100 mW input power	8.05 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	80.3 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm³ (10 g) of Head TSL	condition	
SAR measured	100 mW input power	2.28 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	22.7 W/kg ± 19.5 % (k=2)

Appendix (Additional assessments outside the scope of SCS 0108)

Antenna Parameters with Head TSL at 5250 MHz

Impedance, transformed to feed point	52.1 Ω - 3.6 j Ω
Return Loss	- 27.8 dB

Antenna Parameters with Head TSL at 5600 MHz

Impedance, transformed to feed point	56.8 Ω - 0.4 j Ω
Return Loss	- 23.9 dB

Antenna Parameters with Head TSL at 5800 MHz

Impedance, transformed to feed point	57.4 Ω + 5.9 j Ω
Return Loss	- 21.1 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.203 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
-----------------	-------

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN:1019

Communication System: UID 0 - CW; Frequency: 5250 MHz, Frequency: 5600 MHz, Frequency: 5800 MHz

Medium parameters used: $f = 5250$ MHz; $\sigma = 4.53$ S/m; $\epsilon_r = 36$; $\rho = 1000$ kg/m³

Medium parameters used: $f = 5600$ MHz; $\sigma = 4.89$ S/m; $\epsilon_r = 35.3$; $\rho = 1000$ kg/m³

Medium parameters used: $f = 5800$ MHz; $\sigma = 5.12$ S/m; $\epsilon_r = 35.1$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN3503; ConvF(5.5, 5.5, 5.5) @ 5250 MHz, ConvF(5.1, 5.1, 5.1) @ 5600 MHz, ConvF(5.01, 5.01, 5.01) @ 5800 MHz; Calibrated: 07.03.2023
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.01.2024
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.10.4(1535); SEMCAD X 14.6.14(7501)

Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5250 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 71.48 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 27.5 W/kg

SAR(1 g) = 8.03 W/kg; SAR(10 g) = 2.30 W/kg

Smallest distance from peaks to all points 3 dB below = 7.2 mm

Ratio of SAR at M2 to SAR at M1 = 70.4%

Maximum value of SAR (measured) = 18.2 W/kg

Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5600 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 70.93 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 31.0 W/kg


SAR(1 g) = 8.31 W/kg; SAR(10 g) = 2.37 W/kg

Smallest distance from peaks to all points 3 dB below = 7.4 mm

Ratio of SAR at M2 to SAR at M1 = 67.6%


Maximum value of SAR (measured) = 19.7 W/kg

Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5800 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 68.71 V/m; Power Drift = 0.09 dB
Peak SAR (extrapolated) = 31.9 W/kg
SAR(1 g) = 8.05 W/kg; SAR(10 g) = 2.28 W/kg
Smallest distance from peaks to all points 3 dB below = 7.5 mm
Ratio of SAR at M2 to SAR at M1 = 65.5%
Maximum value of SAR (measured) = 19.2 W/kg



0 dB = 19.7 W/kg = 12.93 dBW/kg

Impedance Measurement Plot for Head TSL





Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: SCS 0108

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Client **B.V. ADT**
Taoyuan City

Certificate No. **D6.5GHzV2-1008_Sep23**

CALIBRATION CERTIFICATE

Object **D6.5GHzV2 - SN:1008**

Calibration procedure(s) **QA CAL-22 v7**
Calibration Procedure for SAR Validation Sources between 3-10 GHz

Calibration date: **September 21, 2023**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power sensor R&S NRP33T	SN: 100967	03-Apr-23 (No. 217-03806)	Apr-24
Reference 20 dB Attenuator	SN: BH9394 (20k)	30-Mar-23 (No. 217-03809)	Mar-24
Mismatch combination	SN: 84224 / 360D	03-Apr-23 (No. 217-03812)	Apr-24
Reference Probe EX3DV4	SN: 7405	12-Jun-23 (No. EX3-7405_Jun23)	Jun-24
DAE4	SN: 908	03-Jul-23 (No. DAE4-908_Jul23)	Jul-24

Secondary Standards	ID #	Check Date (in house)	Scheduled Check
RF generator Anapico APSIN20G	SN: 827	18-Dec-18 (in house check Dec-21)	In house check: Dec-23
Power sensor NRP-Z23	SN: 100169	10-Jan-19 (in house check Nov-22)	In house check: Nov-23
Power sensor NRP-18T	SN: 100950	28-Sep-22 (in house check Nov-22)	In house check: Nov-23
Network Analyzer Keysight E5063A	SN:MY54504221	31-Oct-19 (in house check Oct-22)	In house check: Oct-25

Calibrated by:

Name	Function	Signature
Jeton Kastrati	Laboratory Technician	

Approved by:

Sven Kühn	Technical Manager
-----------	-------------------

Issued: September 21, 2023

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- a) IEC/IEEE 62209-1528, "Measurement Procedure For The Assessment Of Specific Absorption Rate Of Human Exposure To Radio Frequency Fields From Hand-Held And Body-Worn Wireless Communication Devices - Part 1528: Human Models, Instrumentation And Procedures (Frequency Range Of 4 MHz To 10 GHz)", October 2020.

Additional Documentation:

- b) DASY System Handbook

Methods Applied and Interpretation of Parameters:

- *Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The Return Loss ensures low reflected power. No uncertainty required.
- *SAR measured:* SAR measured at the stated antenna input power.
- *SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.
- *The absorbed power density (APD):* The absorbed power density is evaluated according to Samaras T, Christ A, Kuster N, "Compliance assessment of the epithelial or absorbed power density above 6 GHz using SAR measurement systems", Bioelectromagnetics, 2021 (submitted). The additional evaluation uncertainty of 0.55 dB (rectangular distribution) is considered.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY6	V16.2
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	5 mm	with Spacer
Zoom Scan Resolution	dx, dy = 3.4 mm, dz = 1.4 mm	Graded Ratio = 1.4 (Z direction)
Frequency	6500 MHz $\pm$ 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	34.5	6.07 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	33.3 $\pm$ 6 %	6.09 mho/m $\pm$ 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm³ (1 g) of Head TSL	Condition	
SAR measured	100 mW input power	29.4 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	292 W/kg $\pm$ 24.7 % (k=2)

SAR averaged over 8 cm³ (8 g) of Head TSL	Condition	
SAR measured	100 mW input power	6.65 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	65.9 W/kg $\pm$ 24.4 % (k=2)

SAR averaged over 10 cm³ (10 g) of Head TSL	condition	
SAR measured	100 mW input power	5.44 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	53.9 W/kg $\pm$ 24.4 % (k=2)

Appendix (Additional assessments outside the scope of SCS 0108)

Antenna Parameters with Head TSL

Impedance, transformed to feed point	52.2 Ω - 6.9 j Ω
Return Loss	- 23.0 dB

APD (Absorbed Power Density)

APD averaged over 1 cm ²	Condition	
APD measured	100 mW input power	291 W/m ²
APD measured	normalized to 1W	2910 W/m² $\pm$ 29.2 % (k=2)

APD averaged over 4 cm ²	condition	
APD measured	100 mW input power	133 W/m ²
APD measured	normalized to 1W	1330 W/m² $\pm$ 28.9 % (k=2)

*The reported APD values have been derived using the psSAR1g and psSAR8g.

General Antenna Parameters and Design

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
-----------------	-------

DASY6 Validation Report for Head TSL

Measurement Report for D6.5GHz-1008, UID 0 -, Channel 6500 (6500.0MHz)

Device under Test Properties

Name, Manufacturer	Dimensions [mm]	IMEI	DUT Type
D6.5GHz	10.0 x 10.0 x 10.0	SN: 1008	-

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz]	Conversion Factor	TSL Cond. [S/m]	TSL Permittivity
Flat, HSL	5.00	Band	CW,	6500	5.50	6.09	33.3

Hardware Setup


Phantom	TSL	Probe, Calibration Date	DAE, Calibration Date
MFP V8.0 Center - 1182	HBBL600-10000V6	EX3DV4 - SN7405, 2023-06-12	DAE4 Sn908, 2023-07-03

Scan Setup


	Zoom Scan
Grid Extents [mm]	22.0 x 22.0 x 22.0
Grid Steps [mm]	3.4 x 3.4 x 1.4
Sensor Surface [mm]	1.4
Graded Grid	Yes
Grading Ratio	1.4
MAIA	N/A
Surface Detection	VMS + 6p
Scan Method	Measured

Measurement Results

	Zoom Scan
Date	2023-09-21, 12:35
psSAR1g [W/Kg]	29.4
psSAR8g [W/Kg]	6.65
psSAR10g [W/Kg]	5.44
Power Drift [dB]	0.02
Power Scaling	Disabled
Scaling Factor [dB]	
TSL Correction	No correction
M2/M1 [%]	50.7
Dist 3dB Peak [mm]	4.6



Impedance Measurement Plot for Head TSL





Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Client B.V. ADT
Taoyuan City

Certificate No. 5G-Veri10-1025_Jan24

CALIBRATION CERTIFICATE

Object 5G Verification Source 10 GHz - SN: 1025

Calibration procedure(s) QA CAL-45.v4
Calibration procedure for sources in air above 6 GHz

Calibration date: January 18, 2024

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^{\circ}\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Reference Probe EUmMWV3	SN: 9374	04-Dec-23 (No. EUmMWV3-Dec23)	Dec-24
DAE4	SN: 1215	29-Jun-23 (No. DAE4-1215_Jun23)	Jun-24
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
RF generator R&S SMF100A	SN: 100184	29-Nov-23 (in house check Nov-23)	In house check: Nov-24
Power sensor R&S NRP18S-10	SN: 101258	29-Nov-23 (in house check Nov-23)	In house check: Nov-24
Network Analyzer Keysight E5063A	SN: MY54504221	31-Oct-19 (in house check Oct-22)	In house check: Oct-25

Calibrated by:	Name Joanna Lleshaj	Function Laboratory Technician
Approved by:	Sven Kühn	Technical Manager

Signature

Issued: January 19, 2024

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Glossary

Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 0108**

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

CW Continuous wave

Calibration is Performed According to the Following Standards

- Internal procedure QA CAL-45, Calibration procedure for sources in air above 6 GHz.
- IEC/IEEE 63195-1, "Assessment of power density of human exposure to radio frequency fields from wireless devices in close proximity to the head and body (frequency range of 6 GHz to 300 GHz)", May 2022

Methods Applied and Interpretation of Parameters

- *Coordinate System:* z-axis in the waveguide horn boresight, x-axis is in the direction of the E-field, y-axis normal to the others in the field scanning plane parallel to the horn flare and horn flange.
- *Measurement Conditions:* (1) 10 GHz: The radiated power is the forward power to the horn antenna minus ohmic and mismatch loss. The forward power is measured prior and after the measurement with a power sensor. During the measurements, the horn is directly connected to the cable and the antenna ohmic and mismatch losses are determined by far-field measurements. (2) 30, 45, 60 and 90 GHz: The verification sources are switched on for at least 30 minutes. Absorbers are used around the probe cub and at the ceiling to minimize reflections.
- *Horn Positioning:* The waveguide horn is mounted vertically on the flange of the waveguide source to allow vertical positioning of the EUmmW probe during the scan. The plane is parallel to the phantom surface. Probe distance is verified using mechanical gauges positioned on the flare of the horn.
- *E- field distribution:* E field is measured in two x-y-plane (10mm, 10mm + $\lambda/4$) with a vectorial E-field probe. The E-field value stated as calibration value represents the E-field-maxima and the averaged (1cm² and 4cm²) power density values at 10mm in front of the horn.
- *Field polarization:* Above the open horn, linear polarization of the field is expected. This is verified graphically in the field representation.

Calibrated Quantity

- Local peak E-field (V/m) and average of peak spatial components of the poynting vector (W/m²) averaged over the surface area of 1 cm² and 4cm² at the nominal operational frequency of the verification source. Both square and circular averaging results are listed.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY8 Module mmWave	V3.2
Phantom	5G Phantom	
Distance Horn Aperture - plane	10 mm	
Number of measured planes	2 (10mm, 10mm + $\lambda/4$)	
Frequency	10 GHz $\pm$ 10 MHz	

Calibration Parameters, 10 GHz

Circular Averaging

Distance Horn Aperture to Measured Plane	$Prad^1$ (mW)	Max E-field (V/m)	Uncertainty (k = 2)	Avg Power Density Avg (psPDn+, psPDtot+, psPDmod+) (W/m ²)		Uncertainty (k = 2)
				1 cm ²	4 cm ²	
10 mm	93.3	153	1.27 dB	60.4	56.2	1.28 dB

Distance Horn Aperture to Measured Plane	$Prad^1$ (mW)	Max E-field (V/m)	Uncertainty (k = 2)	Power Density psPDn+, psPDtot+, psPDmod+ (W/m ²)		Uncertainty (k = 2)
				1 cm ²	4 cm ²	
10 mm	93.3	153	1.27 dB	60.2, 60.4, 60.6	55.9, 56.2, 56.4	1.28 dB

Square Averaging

Distance Horn Aperture to Measured Plane	$Prad^1$ (mW)	Max E-field (V/m)	Uncertainty (k = 2)	Avg Power Density Avg (psPDn+, psPDtot+, psPDmod+) (W/m ²)		Uncertainty (k = 2)
				1 cm ²	4 cm ²	
10 mm	93.3	153	1.27 dB	60.4	56.0	1.28 dB

Distance Horn Aperture to Measured Plane	$Prad^1$ (mW)	Max E-field (V/m)	Uncertainty (k = 2)	Power Density psPDn+, psPDtot+, psPDmod+ (W/m ²)		Uncertainty (k = 2)
				1 cm ²	4 cm ²	
10 mm	93.3	153	1.27 dB	60.2, 60.4, 60.6	55.7, 56.0, 56.3	1.28 dB

Max Power Density

Distance Horn Aperture to Measured Plane	$Prad^1$ (mW)	Max E-field (V/m)	Uncertainty (k = 2)	Max Power Density Sn, Stot, Stot (W/m ²)	Uncertainty (k = 2)
10 mm	93.3	153	1.27 dB	61.9, 61.9, 62.1	1.28 dB


¹ Assessed ohmic and mismatch loss plus numerical offset: 0.30 dB

Appendix (Additional assessments outside the scope of SCS 0108)

Antenna Parameters

Impedance, transformed to feed point	52.0 Ω + 1.2 jΩ
Return Loss	- 32.4 dB

Impedance Measurement Plot



DASY Report

Measurement Report for 5G Verification Source 10 GHz, UID 0 -, Channel 10000 (10000.0MHz)

Device under Test Properties

Name, Manufacturer	Dimensions [mm]	IMEI	DUT Type
5G Verification Source 10 GHz	100.0 x 100.0 x 172.0	SN: 1025	-

Exposure Conditions

Phantom Section	Position, Test Distance [mm]	Band	Group,	Frequency [MHz], Channel Number	Conversion Factor
5G -	10.0 mm	Validation band	CW	10000.0, 10000	1.0

Hardware Setup


Phantom	Medium	Probe, Calibration Date	DAE, Calibration Date
mmWave Phantom - 1002	Air	EUmmWV3 - SN9374_F1-55GHz, 2023-12-04	DAE4 Sn1215, 2023-06-29

Scan Setup

Sensor Surface [mm]	5G Scan
MAIA	10.0 MAIA not used

Measurement Results

Date	5G Scan
2024-01-18, 12:50	
Avg. Area [cm²]	1.00
Avg. Type	Circular Averaging
psPDn+ [W/m²]	60.2
psPDtot+ [W/m²]	60.4
psPDmod+ [W/m²]	60.6
Max(Sn) [W/m²]	61.9
Max(Stot) [W/m²]	61.9
Max(Stot) [W/m²]	62.1
E _{max} [V/m]	153
Power Drift [dB]	-0.04



DASY Report

Measurement Report for 5G Verification Source 10 GHz, UID 0 -, Channel 10000 (10000.0MHz)

Device under Test Properties

Name, Manufacturer	Dimensions [mm]	IMEI	DUT Type
5G Verification Source 10 GHz	100.0 x 100.0 x 172.0	SN: 1025	-

Exposure Conditions

Phantom Section	Position, Test Distance [mm]	Band	Group,	Frequency [MHz], Channel Number	Conversion Factor
5G -	10.0 mm	Validation band	CW	10000.0, 10000	1.0

Hardware Setup


Phantom	Medium	Probe, Calibration Date	DAE, Calibration Date
mmWave Phantom - 1002	Air	EUmmWV3 - SN9374_F1-55GHz, 2023-12-04	DAE4 Sn1215, 2023-06-29

Scan Setup

Sensor Surface [mm]	5G Scan
MAIA	10.0 MAIA not used

Measurement Results

Date	5G Scan
Avg. Area [cm²]	2024-01-18, 12:50
Avg. Type	4.00
psPDn+ [W/m²]	Circular Averaging
psPDtot+ [W/m²]	55.9
psPDmod+ [W/m²]	56.2
Max(Sn) [W/m²]	56.4
Max(Stot) [W/m²]	61.9
Max(Stot) [W/m²]	61.9
E _{max} [V/m]	62.1
Power Drift [dB]	153
	-0.04



DASY Report

Measurement Report for 5G Verification Source 10 GHz, UID 0 -, Channel 10000 (10000.0MHz)

Device under Test Properties

Name, Manufacturer	Dimensions [mm]	IMEI	DUT Type
5G Verification Source 10 GHz	100.0 x 100.0 x 172.0	SN: 1025	-

Exposure Conditions

Phantom Section	Position, Test Distance [mm]	Band	Group,	Frequency [MHz], Channel Number	Conversion Factor
5G -	10.0 mm	Validation band	CW	10000.0, 10000	1.0

Hardware Setup


Phantom	Medium	Probe, Calibration Date	DAE, Calibration Date
mmWave Phantom - 1002	Air	EUmmWV3 - SN9374_F1-55GHz, 2023-12-04	DAE4 Sn1215, 2023-06-29

Scan Setup

Sensor Surface [mm]	5G Scan
MAIA	10.0 MAIA not used

Measurement Results

Date	5G Scan
2024-01-18, 12:50	2024-01-18, 12:50
Avg. Area [cm²]	1.00
Avg. Type	Square Averaging
psPDn+ [W/m²]	60.2
psPDtot+ [W/m²]	60.4
psPDmod+ [W/m²]	60.6
Max(Sn) [W/m²]	61.9
Max(Stot) [W/m²]	61.9
Max(Stot) [W/m²]	62.1
E _{max} [V/m]	153
Power Drift [dB]	-0.04



DASY Report

Measurement Report for 5G Verification Source 10 GHz, UID 0 -, Channel 10000 (10000.0MHz)

Device under Test Properties

Name, Manufacturer	Dimensions [mm]	IMEI	DUT Type
5G Verification Source 10 GHz	100.0 x 100.0 x 172.0	SN: 1025	-

Exposure Conditions

Phantom Section	Position, Test Distance [mm]	Band	Group,	Frequency [MHz], Channel Number	Conversion Factor
5G -	10.0 mm	Validation band	CW	10000.0, 10000	1.0

Hardware Setup


Phantom	Medium	Probe, Calibration Date	DAE, Calibration Date
mmWave Phantom - 1002	Air	EUmmWV3 - SN9374_F1-55GHz, 2023-12-04	DAE4 Sn1215, 2023-06-29

Scan Setup

Sensor Surface [mm]	5G Scan
MAIA	10.0 MAIA not used

Measurement Results

Date	5G Scan
2024-01-18, 12:50	
Avg. Area [cm²]	4.00
Avg. Type	Square Averaging
psPDn+ [W/m²]	55.7
psPDtot+ [W/m²]	56.0
psPDmod+ [W/m²]	56.3
Max(Sn) [W/m²]	61.9
Max(Stot) [W/m²]	61.9
Max(Stot) [W/m²]	62.1
E _{max} [V/m]	153
Power Drift [dB]	-0.04





Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Client

B.V. ADT
Taoyuan City

Certificate No.

EX-7720_Mar24

CALIBRATION CERTIFICATE

Object EX3DV4 - SN:7720

Calibration procedure(s) QA CAL-01.v10, QA CAL-12.v10, QA CAL-14.v7, QA CAL-23.v6,
QA CAL-25.v8
Calibration procedure for dosimetric E-field probes

Calibration date March 19, 2024

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^\circ\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP2	SN: 104778	30-Mar-23 (No. 217-03804/03805)	Mar-24
Power sensor NRP-Z91	SN: 103244	30-Mar-23 (No. 217-03804)	Mar-24
OCP DAK-3.5 (weighted)	SN: 1249	05-Oct-23 (OCP-DAK3.5-1249_Oct23)	Oct-24
OCP DAK-12	SN: 1016	05-Oct-23 (OCP-DAK12-1016_Oct23)	Oct-24
Reference 20 dB Attenuator	SN: CC2552 (20x)	30-Mar-23 (No. 217-03809)	Mar-24
DAE4	SN: 660	23-Feb-24 (No. DAE4-660_Feb24)	Feb-25
Reference Probe EX3DV4	SN: 7349	03-Nov-23 (No. EX3-7349_Nov23)	Nov-24

Secondary Standards	ID	Check Date (in house)	Scheduled Check
Power meter E4419B	SN: GB41293874	06-Apr-16 (in house check Jun-22)	In house check: Jun-24
Power sensor E4412A	SN: MY41498087	06-Apr-16 (in house check Jun-22)	In house check: Jun-24
Power sensor E4412A	SN: 000110210	06-Apr-16 (in house check Jun-22)	In house check: Jun-24
RF generator HP 8648C	SN: US3642U01700	04-Aug-99 (in house check Jun-22)	In house check: Jun-24
Network Analyzer E8358A	SN: US41080477	31-Mar-14 (in house check Oct-22)	In house check: Oct-24

	Name	Function	Signature
Calibrated by	Joanna Lleshaj	Laboratory Technician	
Approved by	Sven Kühn	Technical Manager	

Issued: March 19, 2024

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Calibration Laboratory of

Schmid & Partner
Engineering AG

Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Glossary

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization φ	φ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

- IEC/IEEE 62209-1528, "Measurement Procedure For The Assessment Of Specific Absorption Rate Of Human Exposure To Radio Frequency Fields From Hand-Held And Body-Worn Wireless Communication Devices – Part 1528: Human Models, Instrumentation And Procedures (Frequency Range of 4 MHz to 10 GHz)", October 2020.
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}**: Assessed for E-field polarization $\vartheta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not affect the E²-field uncertainty inside TSL (see below ConvF).
- NORM(f)_{x,y,z}** = NORM_{x,y,z} * frequency_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP_{x,y,z}**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal. DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; D_{x,y,z}; VR_{x,y,z}**: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle**: The angle is assessed using the information gained by determining the NORM_x (no uncertainty required).

Parameters of Probe: EX3DV4 - SN:7720

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k = 2)
Norm ($\mu\text{V}/(\text{V}/\text{m})^2$) ^A	0.57	0.59	0.62	±10.1%
DCP (mV) ^B	106.6	102.9	103.0	±4.7%

Calibration Results for Modulation Response

UID	Communication System Name		A dB	B dB $\sqrt{\mu\text{V}}$	C	D dB	VR mV	Max dev.	Max Unc ^E k = 2
0	CW	X	0.00	0.00	1.00	0.00	126.5	±2.8%	±4.7%
		Y	0.00	0.00	1.00		140.4		
		Z	0.00	0.00	1.00		132.4		
10352	Pulse Waveform (200Hz, 10%)	X	1.74	61.74	7.12	10.00	60.0	±2.6%	±9.6%
		Y	1.47	60.40	6.28		60.0		
		Z	1.48	60.46	6.36		60.0		
10353	Pulse Waveform (200Hz, 20%)	X	10.00	72.00	9.00	6.99	80.0	±2.4%	±9.6%
		Y	0.77	60.00	4.84		80.0		
		Z	44.00	80.00	11.00		80.0		
10354	Pulse Waveform (200Hz, 40%)	X	0.41	60.00	4.20	3.98	95.0	±2.4%	±9.6%
		Y	0.01	124.78	0.40		95.0		
		Z	0.08	134.19	0.39		95.0		
10355	Pulse Waveform (200Hz, 60%)	X	12.36	134.75	0.44	2.22	120.0	±1.8%	±9.6%
		Y	6.75	159.95	3.75		120.0		
		Z	6.36	159.63	17.38		120.0		
10387	QPSK Waveform, 1 MHz	X	0.61	65.69	14.13	1.00	150.0	±3.5%	±9.6%
		Y	0.70	65.52	13.36		150.0		
		Z	0.62	65.78	14.09		150.0		
10388	QPSK Waveform, 10 MHz	X	1.45	67.52	14.76	0.00	150.0	±1.0%	±9.6%
		Y	1.47	66.41	14.45		150.0		
		Z	1.46	67.31	14.87		150.0		
10396	64-QAM Waveform, 100 kHz	X	1.74	64.91	16.00	3.01	150.0	±1.3%	±9.6%
		Y	1.66	64.20	15.86		150.0		
		Z	1.56	63.40	15.68		150.0		
10399	64-QAM Waveform, 40 MHz	X	2.89	66.96	15.49	0.00	150.0	±1.5%	±9.6%
		Y	2.94	66.45	15.28		150.0		
		Z	2.88	66.63	15.44		150.0		
10414	WLAN CCDF, 64-QAM, 40 MHz	X	3.82	66.53	15.51	0.00	150.0	±2.8%	±9.6%
		Y	3.97	66.00	15.41		150.0		
		Z	3.99	66.81	15.79		150.0		

Note: For details on UID parameters see Appendix

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of Norm X,Y,Z do not affect the E²-field uncertainty inside TSL. (see Pages 5 and 6).
^B Linearization parameter uncertainty for maximum specified field strength.
^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

Parameters of Probe: EX3DV4 - SN:7720

Sensor Model Parameters

	C1 fF	C2 fF	α V^{-1}	T1 $ms V^{-2}$	T2 $ms V^{-1}$	T3 ms	T4 V^{-2}	T5 V^{-1}	T6
x	8.5	60.75	32.71	3.35	0.00	4.90	0.50	0.00	1.00
y	11.3	82.53	34.23	1.27	0.00	4.90	0.34	0.00	1.00
z	9.5	69.28	34.06	1.63	0.00	4.90	0.00	0.02	1.00

Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle	-67.4°
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	9 mm
Tip Diameter	2.5 mm
Probe Tip to Sensor X Calibration Point	1 mm
Probe Tip to Sensor Y Calibration Point	1 mm
Probe Tip to Sensor Z Calibration Point	1 mm
Recommended Measurement Distance from Surface	1.4 mm

Note: Measurement distance from surface can be increased to 3–4 mm for an *Area Scan* job.

Parameters of Probe: EX3DV4 - SN:7720

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity ^F (S/m)	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unc (k = 2)
750	41.9	0.89	8.70	9.52	8.50	0.39	1.27	±11.0%
835	41.5	0.90	8.59	9.47	8.01	0.38	1.27	±11.0%
1450	40.5	1.20	7.22	8.02	7.01	0.34	1.27	±11.0%
1750	40.1	1.37	7.06	7.82	6.83	0.27	1.27	±11.0%
1900	40.0	1.40	6.98	7.78	6.73	0.29	1.27	±11.0%
2000	40.0	1.40	6.84	7.70	6.68	0.31	1.27	±11.0%
2300	39.5	1.67	6.75	7.54	6.57	0.32	1.27	±11.0%
2450	39.2	1.80	6.62	7.39	6.46	0.31	1.27	±11.0%
2600	39.0	1.96	6.50	7.25	6.34	0.30	1.27	±11.0%
3300	38.2	2.71	5.85	6.91	6.69	0.35	1.27	±13.1%
3500	37.9	2.91	5.66	6.72	6.52	0.36	1.27	±13.1%
3700	37.7	3.12	5.51	6.53	6.33	0.36	1.27	±13.1%
3900	37.5	3.32	5.48	6.46	6.29	0.37	1.27	±13.1%
4100	37.2	3.53	5.44	6.35	6.23	0.38	1.27	±13.1%
4200	37.1	3.63	5.39	6.32	6.18	0.38	1.27	±13.1%
4400	36.9	3.84	5.33	6.29	6.14	0.38	1.27	±13.1%
4600	36.7	4.04	5.32	6.27	6.13	0.38	1.27	±13.1%
4800	36.4	4.25	5.29	6.24	6.10	0.37	1.27	±13.1%
4950	36.3	4.40	5.03	5.90	5.81	0.43	1.36	±13.1%
5250	35.9	4.71	5.07	5.93	5.81	0.38	1.53	±13.1%
5600	35.5	5.07	4.44	5.21	5.10	0.39	1.67	±13.1%
5800	35.3	5.27	4.36	5.10	5.05	0.38	1.78	±13.1%

^C Frequency validity above 300 MHz of ±100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ±50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ±10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Validity of ConvF assessed at 6 MHz is 4–9 MHz, and ConvF assessed at 13 MHz is 9–19 MHz. Above 5 GHz frequency validity can be extended to ±110 MHz.

^F The probes are calibrated using tissue simulating liquids (TSL) that deviate for ϵ and σ by less than ±5% from the target values (typically better than ±3%) and are valid for TSL with deviations of up to ±10% if SAR correction is applied.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ±1% for frequencies below 3 GHz and below ±2% for frequencies between 3–6 GHz at any distance larger than half the probe tip diameter from the boundary.

Parameters of Probe: EX3DV4 - SN:7720

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity ^F (S/m)	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unc (k = 2)
6500	34.5	6.07	4.64	5.13	5.12	0.20	2.00	±18.6%


^C Frequency validity at 6.5 GHz is -600/+700 MHz, and ±700 MHz at or above 7 GHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^F The probes are calibrated using tissue simulating liquids (TSL) that deviate for ϵ and σ by less than ±10% from the target values (typically better than ±6%) and are valid for TSL with deviations of up to ±10%.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ±1% for frequencies below 3 GHz; below ±2% for frequencies between 3–6 GHz; and below ±4% for frequencies between 6–10 GHz at any distance larger than half the probe tip diameter from the boundary.



Frequency Response of E-Field

(TEM-Cell:ifi110 EXX, Waveguide:R22)





Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ ($k=2$)

Receiving Pattern (ϕ), $\vartheta = 0^\circ$




Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ ($k=2$)

Dynamic Range f(SAR_{head})
(TEM cell, f_{eval} = 1900MHz)




Uncertainty of Linearity Assessment: ±0.6% (k=2)

Conversion Factor Assessment



Deviation from Isotropy in Liquid

Error (ϕ, θ), $f = 900\text{ MHz}$



Appendix: Modulation Calibration Parameters

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E $k = 2$
0		CW	CW	0.00	±4.7
10010	CAB	SAR Validation (Square, 100 ms, 10 ms)	Test	10.00	±9.6
10011	CAC	UMTS-FDD (WCDMA)	WCDMA	2.91	±9.6
10012	CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps)	WLAN	1.87	±9.6
10013	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps)	WLAN	9.46	±9.6
10021	DAC	GSM-FDD (TDMA, GMSK)	GSM	9.39	±9.6
10023	DAC	GPRS-FDD (TDMA, GMSK, TN 0)	GSM	9.57	±9.6
10024	DAC	GPRS-FDD (TDMA, GMSK, TN 0-1)	GSM	6.56	±9.6
10025	DAC	EDGE-FDD (TDMA, 8PSK, TN 0)	GSM	12.62	±9.6
10026	DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1)	GSM	9.55	±9.6
10027	DAC	GPRS-FDD (TDMA, GMSK, TN 0-1-2)	GSM	4.80	±9.6
10028	DAC	GPRS-FDD (TDMA, GMSK, TN 0-1-2-3)	GSM	3.55	±9.6
10029	DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1-2)	GSM	7.78	±9.6
10030	CAA	IEEE 802.15.1 Bluetooth (GFSK, DH1)	Bluetooth	5.30	±9.6
10031	CAA	IEEE 802.15.1 Bluetooth (GFSK, DH3)	Bluetooth	1.87	±9.6
10032	CAA	IEEE 802.15.1 Bluetooth (GFSK, DH5)	Bluetooth	1.16	±9.6
10033	CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH1)	Bluetooth	7.74	±9.6
10034	CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH3)	Bluetooth	4.53	±9.6
10035	CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH5)	Bluetooth	3.83	±9.6
10036	CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH1)	Bluetooth	8.01	±9.6
10037	CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH3)	Bluetooth	4.77	±9.6
10038	CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH5)	Bluetooth	4.10	±9.6
10039	CAB	CDMA2000 (1xRTT, RC1)	CDMA2000	4.57	±9.6
10042	CAB	IS-54 / IS-136 FDD (TDMA/FDM, PI/4-DQPSK, Halfrate)	AMPS	7.78	±9.6
10044	CAA	IS-91/EIA/TIA-553 FDD (FDMA, FM)	AMPS	0.00	±9.6
10048	CAA	DECT (TDD, TDMA/FDM, GFSK, Full Slot, 24)	DECT	13.80	±9.6
10049	CAA	DECT (TDD, TDMA/FDM, GFSK, Double Slot, 12)	DECT	10.79	±9.6
10056	CAA	UMTS-TDD (TD-SCDMA, 1.28 Mcps)	TD-SCDMA	11.01	±9.6
10058	DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1-2-3)	GSM	6.52	±9.6
10059	CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps)	WLAN	2.12	±9.6
10060	CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps)	WLAN	2.83	±9.6
10061	CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps)	WLAN	3.60	±9.6
10062	CAE	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps)	WLAN	8.68	±9.6
10063	CAE	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps)	WLAN	8.63	±9.6
10064	CAE	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps)	WLAN	9.09	±9.6
10065	CAE	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps)	WLAN	9.00	±9.6
10066	CAE	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps)	WLAN	9.38	±9.6
10067	CAE	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps)	WLAN	10.12	±9.6
10068	CAE	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps)	WLAN	10.24	±9.6
10069	CAE	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps)	WLAN	10.56	±9.6
10071	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 9 Mbps)	WLAN	9.83	±9.6
10072	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 12 Mbps)	WLAN	9.62	±9.6
10073	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 18 Mbps)	WLAN	9.94	±9.6
10074	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 24 Mbps)	WLAN	10.30	±9.6
10075	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 36 Mbps)	WLAN	10.77	±9.6
10076	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 48 Mbps)	WLAN	10.94	±9.6
10077	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 54 Mbps)	WLAN	11.00	±9.6
10081	CAB	CDMA2000 (1xRTT, RC3)	CDMA2000	3.97	±9.6
10082	CAB	IS-54 / IS-136 FDD (TDMA/FDM, PI/4-DQPSK, Fullrate)	AMPS	4.77	±9.6
10090	DAC	GPRS-FDD (TDMA, GMSK, TN 0-4)	GSM	6.56	±9.6
10097	CAC	UMTS-FDD (HSDPA)	WCDMA	3.98	±9.6
10098	CAC	UMTS-FDD (HSUPA, Subtest 2)	WCDMA	3.98	±9.6
10099	DAC	EDGE-FDD (TDMA, 8PSK, TN 0-4)	GSM	9.55	±9.6
10100	CAF	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	LTE-FDD	5.67	±9.6
10101	CAF	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM)	LTE-FDD	6.42	±9.6
10102	CAF	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM)	LTE-FDD	6.60	±9.6
10103	CAH	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	LTE-TDD	9.29	±9.6
10104	CAH	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM)	LTE-TDD	9.97	±9.6
10105	CAH	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM)	LTE-TDD	10.01	±9.6
10108	CAH	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	LTE-FDD	5.80	±9.6
10109	CAH	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM)	LTE-FDD	6.43	±9.6
10110	CAH	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, QPSK)	LTE-FDD	5.75	±9.6
10111	CAH	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM)	LTE-FDD	6.44	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E $k = 2$
10112	CAH	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM)	LTE-FDD	6.59	±9.6
10113	CAH	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM)	LTE-FDD	6.62	±9.6
10114	CAE	IEEE 802.11n (HT Greenfield, 13.5 Mbps, BPSK)	WLAN	8.10	±9.6
10115	CAE	IEEE 802.11n (HT Greenfield, 81 Mbps, 16-QAM)	WLAN	8.46	±9.6
10116	CAE	IEEE 802.11n (HT Greenfield, 135 Mbps, 64-QAM)	WLAN	8.15	±9.6
10117	CAE	IEEE 802.11n (HT Mixed, 13.5 Mbps, BPSK)	WLAN	8.07	±9.6
10118	CAE	IEEE 802.11n (HT Mixed, 81 Mbps, 16-QAM)	WLAN	8.59	±9.6
10119	CAE	IEEE 802.11n (HT Mixed, 135 Mbps, 64-QAM)	WLAN	8.13	±9.6
10140	CAF	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM)	LTE-FDD	6.49	±9.6
10141	CAF	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM)	LTE-FDD	6.53	±9.6
10142	CAF	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, QPSK)	LTE-FDD	5.73	±9.6
10143	CAF	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM)	LTE-FDD	6.35	±9.6
10144	CAF	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM)	LTE-FDD	6.65	±9.6
10145	CAG	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK)	LTE-FDD	5.76	±9.6
10146	CAG	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM)	LTE-FDD	6.41	±9.6
10147	CAG	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM)	LTE-FDD	6.72	±9.6
10149	CAF	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM)	LTE-FDD	6.42	±9.6
10150	CAF	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM)	LTE-FDD	6.60	±9.6
10151	CAH	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	LTE-TDD	9.28	±9.6
10152	CAH	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM)	LTE-TDD	9.92	±9.6
10153	CAH	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM)	LTE-TDD	10.05	±9.6
10154	CAH	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	LTE-FDD	5.75	±9.6
10155	CAH	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM)	LTE-FDD	6.43	±9.6
10156	CAH	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, QPSK)	LTE-FDD	5.79	±9.6
10157	CAH	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM)	LTE-FDD	6.49	±9.6
10158	CAH	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM)	LTE-FDD	6.62	±9.6
10159	CAH	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM)	LTE-FDD	6.56	±9.6
10160	CAF	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, QPSK)	LTE-FDD	5.82	±9.6
10161	CAF	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM)	LTE-FDD	6.43	±9.6
10162	CAF	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM)	LTE-FDD	6.58	±9.6
10166	CAG	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK)	LTE-FDD	5.46	±9.6
10167	CAG	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM)	LTE-FDD	6.21	±9.6
10168	CAG	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM)	LTE-FDD	6.79	±9.6
10169	CAF	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	LTE-FDD	5.73	±9.6
10170	CAF	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)	LTE-FDD	6.52	±9.6
10171	AAF	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM)	LTE-FDD	6.49	±9.6
10172	CAH	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	LTE-TDD	9.21	±9.6
10173	CAH	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)	LTE-TDD	9.48	±9.6
10174	CAH	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM)	LTE-TDD	10.25	±9.6
10175	CAH	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	LTE-FDD	5.72	±9.6
10176	CAH	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM)	LTE-FDD	6.52	±9.6
10177	CAJ	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, QPSK)	LTE-FDD	5.73	±9.6
10178	CAH	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM)	LTE-FDD	6.52	±9.6
10179	CAH	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM)	LTE-FDD	6.50	±9.6
10180	CAH	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM)	LTE-FDD	6.50	±9.6
10181	CAF	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, QPSK)	LTE-FDD	5.72	±9.6
10182	CAF	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM)	LTE-FDD	6.52	±9.6
10183	AAE	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM)	LTE-FDD	6.50	±9.6
10184	CAF	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, QPSK)	LTE-FDD	5.73	±9.6
10185	CAF	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM)	LTE-FDD	6.51	±9.6
10186	AAF	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM)	LTE-FDD	6.50	±9.6
10187	CAG	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK)	LTE-FDD	5.73	±9.6
10188	CAG	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM)	LTE-FDD	6.52	±9.6
10189	AAG	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM)	LTE-FDD	6.50	±9.6
10193	CAE	IEEE 802.11n (HT Greenfield, 6.5 Mbps, BPSK)	WLAN	8.09	±9.6
10194	CAE	IEEE 802.11n (HT Greenfield, 39 Mbps, 16-QAM)	WLAN	8.12	±9.6
10195	CAE	IEEE 802.11n (HT Greenfield, 65 Mbps, 64-QAM)	WLAN	8.21	±9.6
10196	CAE	IEEE 802.11n (HT Mixed, 6.5 Mbps, BPSK)	WLAN	8.10	±9.6
10197	CAE	IEEE 802.11n (HT Mixed, 39 Mbps, 16-QAM)	WLAN	8.13	±9.6
10198	CAE	IEEE 802.11n (HT Mixed, 65 Mbps, 64-QAM)	WLAN	8.27	±9.6
10219	CAE	IEEE 802.11n (HT Mixed, 7.2 Mbps, BPSK)	WLAN	8.03	±9.6
10220	CAE	IEEE 802.11n (HT Mixed, 43.3 Mbps, 16-QAM)	WLAN	8.13	±9.6
10221	CAE	IEEE 802.11n (HT Mixed, 72.2 Mbps, 64-QAM)	WLAN	8.27	±9.6
10222	CAE	IEEE 802.11n (HT Mixed, 15 Mbps, BPSK)	WLAN	8.06	±9.6
10223	CAE	IEEE 802.11n (HT Mixed, 90 Mbps, 16-QAM)	WLAN	8.48	±9.6
10224	CAE	IEEE 802.11n (HT Mixed, 150 Mbps, 64-QAM)	WLAN	8.08	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E k = 2
10225	CAC	UMTS-FDD (HSPA+)	WCDMA	5.97	±9.6
10226	CAC	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM)	LTE-TDD	9.49	±9.6
10227	CAC	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM)	LTE-TDD	10.26	±9.6
10228	CAC	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK)	LTE-TDD	9.22	±9.6
10229	CAE	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM)	LTE-TDD	9.48	±9.6
10230	CAE	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM)	LTE-TDD	10.25	±9.6
10231	CAE	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, QPSK)	LTE-TDD	9.19	±9.6
10232	CAH	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM)	LTE-TDD	9.48	±9.6
10233	CAH	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM)	LTE-TDD	10.25	±9.6
10234	CAH	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK)	LTE-TDD	9.21	±9.6
10235	CAH	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM)	LTE-TDD	9.48	±9.6
10236	CAH	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM)	LTE-TDD	10.25	±9.6
10237	CAH	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	LTE-TDD	9.21	±9.6
10238	CAG	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM)	LTE-TDD	9.48	±9.6
10239	CAG	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM)	LTE-TDD	10.25	±9.6
10240	CAG	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, QPSK)	LTE-TDD	9.21	±9.6
10241	CAC	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM)	LTE-TDD	9.82	±9.6
10242	CAC	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM)	LTE-TDD	9.86	±9.6
10243	CAC	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK)	LTE-TDD	9.46	±9.6
10244	CAE	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)	LTE-TDD	10.06	±9.6
10245	CAE	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM)	LTE-TDD	10.06	±9.6
10246	CAE	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK)	LTE-TDD	9.30	±9.6
10247	CAH	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM)	LTE-TDD	9.91	±9.6
10248	CAH	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM)	LTE-TDD	10.09	±9.6
10249	CAH	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, QPSK)	LTE-TDD	9.29	±9.6
10250	CAH	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM)	LTE-TDD	9.81	±9.6
10251	CAH	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM)	LTE-TDD	10.17	±9.6
10252	CAH	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	LTE-TDD	9.24	±9.6
10253	CAG	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM)	LTE-TDD	9.90	±9.6
10254	CAG	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM)	LTE-TDD	10.14	±9.6
10255	CAG	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, QPSK)	LTE-TDD	9.20	±9.6
10256	CAC	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM)	LTE-TDD	9.96	±9.6
10257	CAC	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM)	LTE-TDD	10.08	±9.6
10258	CAC	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK)	LTE-TDD	9.34	±9.6
10259	CAE	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM)	LTE-TDD	9.98	±9.6
10260	CAE	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM)	LTE-TDD	9.97	±9.6
10261	CAE	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, QPSK)	LTE-TDD	9.24	±9.6
10262	CAH	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM)	LTE-TDD	9.83	±9.6
10263	CAH	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM)	LTE-TDD	10.16	±9.6
10264	CAH	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, QPSK)	LTE-TDD	9.23	±9.6
10265	CAH	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM)	LTE-TDD	9.92	±9.6
10266	CAH	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM)	LTE-TDD	10.07	±9.6
10267	CAH	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	LTE-TDD	9.30	±9.6
10268	CAG	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM)	LTE-TDD	10.06	±9.6
10269	CAG	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM)	LTE-TDD	10.13	±9.6
10270	CAG	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, QPSK)	LTE-TDD	9.58	±9.6
10274	CAC	UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.10)	WCDMA	4.87	±9.6
10275	CAC	UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.4)	WCDMA	3.96	±9.6
10277	CAA	PHS (QPSK)	PHS	11.81	±9.6
10278	CAA	PHS (QPSK, BW 884 MHz, Roll-off 0.5)	PHS	11.81	±9.6
10279	CAA	PHS (QPSK, BW 884 MHz, Roll-off 0.38)	PHS	12.18	±9.6
10290	AAB	CDMA2000, RC1, SO55, Full Rate	CDMA2000	3.91	±9.6
10291	AAB	CDMA2000, RC3, SO55, Full Rate	CDMA2000	3.46	±9.6
10292	AAB	CDMA2000, RC3, SO32, Full Rate	CDMA2000	3.39	±9.6
10293	AAB	CDMA2000, RC3, SO3, Full Rate	CDMA2000	3.50	±9.6
10295	AAB	CDMA2000, RC1, SO3, 1/8th Rate 25 fr.	CDMA2000	12.49	±9.6
10297	AAE	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	LTE-FDD	5.81	±9.6
10298	AAE	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, QPSK)	LTE-FDD	5.72	±9.6
10299	AAE	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)	LTE-FDD	6.39	±9.6
10300	AAE	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM)	LTE-FDD	6.60	±9.6
10301	AAA	IEEE 802.16e WiMAX (29:18, 5 ms, 10 MHz, QPSK, PUSC)	WiMAX	12.03	±9.6
10302	AAA	IEEE 802.16e WiMAX (29:18, 5 ms, 10 MHz, QPSK, PUSC, 3 CTRL symbols)	WiMAX	12.57	±9.6
10303	AAA	IEEE 802.16e WiMAX (31:15, 5 ms, 10 MHz, 64QAM, PUSC)	WiMAX	12.52	±9.6
10304	AAA	IEEE 802.16e WiMAX (29:18, 5 ms, 10 MHz, 64QAM, PUSC)	WiMAX	11.86	±9.6
10305	AAA	IEEE 802.16e WiMAX (31:15, 10 ms, 10 MHz, 64QAM, PUSC, 15 symbols)	WiMAX	15.24	±9.6
10306	AAA	IEEE 802.16e WiMAX (29:18, 10 ms, 10 MHz, 64QAM, PUSC, 18 symbols)	WiMAX	14.67	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E k = 2
10307	AAA	IEEE 802.16e WiMAX (29:18, 10 ms, 10 MHz, QPSK, PUSC, 18 symbols)	WiMAX	14.49	±9.6
10308	AAA	IEEE 802.16e WiMAX (29:18, 10 ms, 10 MHz, 16QAM, PUSC)	WiMAX	14.46	±9.6
10309	AAA	IEEE 802.16e WiMAX (29:18, 10 ms, 10 MHz, 16QAM, AMC 2x3, 18 symbols)	WiMAX	14.58	±9.6
10310	AAA	IEEE 802.16e WiMAX (29:18, 10 ms, 10 MHz, QPSK, AMC 2x3, 18 symbols)	WiMAX	14.57	±9.6
10311	AAE	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, QPSK)	LTE-FDD	6.06	±9.6
10313	AAA	iDEN 1:3	iDEN	10.51	±9.6
10314	AAA	iDEN 1:6	iDEN	13.48	±9.6
10315	AAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 96pc duty cycle)	WLAN	1.71	±9.6
10316	AAB	IEEE 802.11g WiFi 2.4 GHz (ERP-OFDM, 6 Mbps, 96pc duty cycle)	WLAN	8.36	±9.6
10317	AAE	IEEE 802.11a WiFi 5 GHz (OFDM, 6 Mbps, 96pc duty cycle)	WLAN	8.36	±9.6
10352	AAA	Pulse Waveform (200Hz, 10%)	Generic	10.00	±9.6
10353	AAA	Pulse Waveform (200Hz, 20%)	Generic	6.99	±9.6
10354	AAA	Pulse Waveform (200Hz, 40%)	Generic	3.98	±9.6
10355	AAA	Pulse Waveform (200Hz, 60%)	Generic	2.22	±9.6
10356	AAA	Pulse Waveform (200Hz, 80%)	Generic	0.97	±9.6
10387	AAA	QPSK Waveform, 1 MHz	Generic	5.10	±9.6
10388	AAA	QPSK Waveform, 10 MHz	Generic	5.22	±9.6
10396	AAA	64-QAM Waveform, 100 kHz	Generic	6.27	±9.6
10399	AAA	64-QAM Waveform, 40 MHz	Generic	6.27	±9.6
10400	AAF	IEEE 802.11ac WiFi (20 MHz, 64-QAM, 99pc duty cycle)	WLAN	8.37	±9.6
10401	AAF	IEEE 802.11ac WiFi (40 MHz, 64-QAM, 99pc duty cycle)	WLAN	8.60	±9.6
10402	AAF	IEEE 802.11ac WiFi (80 MHz, 64-QAM, 99pc duty cycle)	WLAN	8.53	±9.6
10403	AAB	CDMA2000 (1xEV-DO, Rev. 0)	CDMA2000	3.76	±9.6
10404	AAB	CDMA2000 (1xEV-DO, Rev. A)	CDMA2000	3.77	±9.6
10406	AAB	CDMA2000, RC3, SO32, SCH0, Full Rate	CDMA2000	5.22	±9.6
10410	AAH	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9, Subframe Conf=4)	LTE-TDD	7.82	±9.6
10414	AAA	WLAN CCDF, 64-QAM, 40 MHz	Generic	8.54	±9.6
10415	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 99pc duty cycle)	WLAN	1.54	±9.6
10416	AAA	IEEE 802.11g WiFi 2.4 GHz (ERP-OFDM, 6 Mbps, 99pc duty cycle)	WLAN	8.23	±9.6
10417	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps, 99pc duty cycle)	WLAN	8.23	±9.6
10418	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 99pc duty cycle, Long preamble)	WLAN	8.14	±9.6
10419	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 99pc duty cycle, Short preamble)	WLAN	8.19	±9.6
10422	AAD	IEEE 802.11n (HT Greenfield, 7.2 Mbps, BPSK)	WLAN	8.32	±9.6
10423	AAD	IEEE 802.11n (HT Greenfield, 43.3 Mbps, 16-QAM)	WLAN	8.47	±9.6
10424	AAD	IEEE 802.11n (HT Greenfield, 72.2 Mbps, 64-QAM)	WLAN	8.40	±9.6
10425	AAD	IEEE 802.11n (HT Greenfield, 15 Mbps, BPSK)	WLAN	8.41	±9.6
10426	AAD	IEEE 802.11n (HT Greenfield, 90 Mbps, 16-QAM)	WLAN	8.45	±9.6
10427	AAD	IEEE 802.11n (HT Greenfield, 150 Mbps, 64-QAM)	WLAN	8.41	±9.6
10430	AAE	LTE-FDD (OFDMA, 5 MHz, E-TM 3.1)	LTE-FDD	8.28	±9.6
10431	AAE	LTE-FDD (OFDMA, 10 MHz, E-TM 3.1)	LTE-FDD	8.38	±9.6
10432	AAD	LTE-FDD (OFDMA, 15 MHz, E-TM 3.1)	LTE-FDD	8.34	±9.6
10433	AAD	LTE-FDD (OFDMA, 20 MHz, E-TM 3.1)	LTE-FDD	8.34	±9.6
10434	AAB	W-CDMA (BS Test Model 1, 64 DPCH)	WCDMA	8.60	±9.6
10435	AAG	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.82	±9.6
10447	AAE	LTE-FDD (OFDMA, 5 MHz, E-TM 3.1, Clipping 44%)	LTE-FDD	7.56	±9.6
10448	AAE	LTE-FDD (OFDMA, 10 MHz, E-TM 3.1, Clipping 44%)	LTE-FDD	7.53	±9.6
10449	AAD	LTE-FDD (OFDMA, 15 MHz, E-TM 3.1, Clipping 44%)	LTE-FDD	7.51	±9.6
10450	AAD	LTE-FDD (OFDMA, 20 MHz, E-TM 3.1, Clipping 44%)	LTE-FDD	7.48	±9.6
10451	AAB	W-CDMA (BS Test Model 1, 64 DPCH, Clipping 44%)	WCDMA	7.59	±9.6
10453	AAE	Validation (Square, 10 ms, 1 ms)	Test	10.00	±9.6
10456	AAD	IEEE 802.11ac WiFi (160 MHz, 64-QAM, 99pc duty cycle)	WLAN	8.63	±9.6
10457	AAB	UMTS-FDD (DC-HSDPA)	WCDMA	6.62	±9.6
10458	AAA	CDMA2000 (1xEV-DO, Rev. B, 2 carriers)	CDMA2000	6.55	±9.6
10459	AAA	CDMA2000 (1xEV-DO, Rev. B, 3 carriers)	CDMA2000	8.25	±9.6
10460	AAB	UMTS-FDD (WCDMA, AMR)	WCDMA	2.39	±9.6
10461	AAC	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.82	±9.6
10462	AAC	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.30	±9.6
10463	AAC	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.56	±9.6
10464	AAD	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.82	±9.6
10465	AAD	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.32	±9.6
10466	AAD	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.57	±9.6
10467	AAG	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.82	±9.6
10468	AAG	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.32	±9.6
10469	AAG	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.56	±9.6
10470	AAG	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.82	±9.6
10471	AAG	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.32	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E k = 2
10472	AAG	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.57	±9.6
10473	AAF	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.82	±9.6
10474	AAF	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.32	±9.6
10475	AAF	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.57	±9.6
10477	AAG	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.32	±9.6
10478	AAG	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.57	±9.6
10479	AAC	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.74	±9.6
10480	AAC	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.18	±9.6
10481	AAC	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.45	±9.6
10482	AAD	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.71	±9.6
10483	AAD	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.39	±9.6
10484	AAD	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.47	±9.6
10485	AAG	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.59	±9.6
10486	AAG	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.38	±9.6
10487	AAG	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.60	±9.6
10488	AAG	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.70	±9.6
10489	AAG	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.31	±9.6
10490	AAG	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.54	±9.6
10491	AAF	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.74	±9.6
10492	AAF	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.41	±9.6
10493	AAF	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.55	±9.6
10494	AAG	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.74	±9.6
10495	AAG	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.37	±9.6
10496	AAG	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.54	±9.6
10497	AAC	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.67	±9.6
10498	AAC	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.40	±9.6
10499	AAC	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.68	±9.6
10500	AAD	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.67	±9.6
10501	AAD	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.44	±9.6
10502	AAD	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.52	±9.6
10503	AAG	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.72	±9.6
10504	AAG	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.31	±9.6
10505	AAG	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.54	±9.6
10506	AAG	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.74	±9.6
10507	AAG	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.36	±9.6
10508	AAG	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.55	±9.6
10509	AAF	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.99	±9.6
10510	AAF	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.49	±9.6
10511	AAF	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.51	±9.6
10512	AAG	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.74	±9.6
10513	AAG	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.42	±9.6
10514	AAG	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.45	±9.6
10515	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps, 99pc duty cycle)	WLAN	1.58	±9.6
10516	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps, 99pc duty cycle)	WLAN	1.57	±9.6
10517	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps, 99pc duty cycle)	WLAN	1.58	±9.6
10518	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps, 99pc duty cycle)	WLAN	8.23	±9.6
10519	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps, 99pc duty cycle)	WLAN	8.39	±9.6
10520	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps, 99pc duty cycle)	WLAN	8.12	±9.6
10521	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps, 99pc duty cycle)	WLAN	7.97	±9.6
10522	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps, 99pc duty cycle)	WLAN	8.45	±9.6
10523	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps, 99pc duty cycle)	WLAN	8.08	±9.6
10524	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps, 99pc duty cycle)	WLAN	8.27	±9.6
10525	AAD	IEEE 802.11ac WiFi (20 MHz, MCS0, 99pc duty cycle)	WLAN	8.36	±9.6
10526	AAD	IEEE 802.11ac WiFi (20 MHz, MCS1, 99pc duty cycle)	WLAN	8.42	±9.6
10527	AAD	IEEE 802.11ac WiFi (20 MHz, MCS2, 99pc duty cycle)	WLAN	8.21	±9.6
10528	AAD	IEEE 802.11ac WiFi (20 MHz, MCS3, 99pc duty cycle)	WLAN	8.36	±9.6
10529	AAD	IEEE 802.11ac WiFi (20 MHz, MCS4, 99pc duty cycle)	WLAN	8.36	±9.6
10531	AAD	IEEE 802.11ac WiFi (20 MHz, MCS6, 99pc duty cycle)	WLAN	8.43	±9.6
10532	AAD	IEEE 802.11ac WiFi (20 MHz, MCS7, 99pc duty cycle)	WLAN	8.29	±9.6
10533	AAD	IEEE 802.11ac WiFi (20 MHz, MCS8, 99pc duty cycle)	WLAN	8.38	±9.6
10534	AAD	IEEE 802.11ac WiFi (40 MHz, MCS0, 99pc duty cycle)	WLAN	8.45	±9.6
10535	AAD	IEEE 802.11ac WiFi (40 MHz, MCS1, 99pc duty cycle)	WLAN	8.45	±9.6
10536	AAD	IEEE 802.11ac WiFi (40 MHz, MCS2, 99pc duty cycle)	WLAN	8.32	±9.6
10537	AAD	IEEE 802.11ac WiFi (40 MHz, MCS3, 99pc duty cycle)	WLAN	8.44	±9.6
10538	AAD	IEEE 802.11ac WiFi (40 MHz, MCS4, 99pc duty cycle)	WLAN	8.54	±9.6
10540	AAD	IEEE 802.11ac WiFi (40 MHz, MCS6, 99pc duty cycle)	WLAN	8.39	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E k = 2
10541	AAD	IEEE 802.11ac WiFi (40 MHz, MCS7, 99pc duty cycle)	WLAN	8.46	±9.6
10542	AAD	IEEE 802.11ac WiFi (40 MHz, MCS8, 99pc duty cycle)	WLAN	8.65	±9.6
10543	AAD	IEEE 802.11ac WiFi (40 MHz, MCS9, 99pc duty cycle)	WLAN	8.65	±9.6
10544	AAD	IEEE 802.11ac WiFi (80 MHz, MCS0, 99pc duty cycle)	WLAN	8.47	±9.6
10545	AAD	IEEE 802.11ac WiFi (80 MHz, MCS1, 99pc duty cycle)	WLAN	8.55	±9.6
10546	AAD	IEEE 802.11ac WiFi (80 MHz, MCS2, 99pc duty cycle)	WLAN	8.35	±9.6
10547	AAD	IEEE 802.11ac WiFi (80 MHz, MCS3, 99pc duty cycle)	WLAN	8.49	±9.6
10548	AAD	IEEE 802.11ac WiFi (80 MHz, MCS4, 99pc duty cycle)	WLAN	8.37	±9.6
10550	AAD	IEEE 802.11ac WiFi (80 MHz, MCS6, 99pc duty cycle)	WLAN	8.38	±9.6
10551	AAD	IEEE 802.11ac WiFi (80 MHz, MCS7, 99pc duty cycle)	WLAN	8.50	±9.6
10552	AAD	IEEE 802.11ac WiFi (80 MHz, MCS8, 99pc duty cycle)	WLAN	8.42	±9.6
10553	AAD	IEEE 802.11ac WiFi (80 MHz, MCS9, 99pc duty cycle)	WLAN	8.45	±9.6
10554	AAE	IEEE 802.11ac WiFi (160 MHz, MCS0, 99pc duty cycle)	WLAN	8.48	±9.6
10555	AAE	IEEE 802.11ac WiFi (160 MHz, MCS1, 99pc duty cycle)	WLAN	8.47	±9.6
10556	AAE	IEEE 802.11ac WiFi (160 MHz, MCS2, 99pc duty cycle)	WLAN	8.50	±9.6
10557	AAE	IEEE 802.11ac WiFi (160 MHz, MCS3, 99pc duty cycle)	WLAN	8.52	±9.6
10558	AAE	IEEE 802.11ac WiFi (160 MHz, MCS4, 99pc duty cycle)	WLAN	8.61	±9.6
10560	AAE	IEEE 802.11ac WiFi (160 MHz, MCS6, 99pc duty cycle)	WLAN	8.73	±9.6
10561	AAE	IEEE 802.11ac WiFi (160 MHz, MCS7, 99pc duty cycle)	WLAN	8.56	±9.6
10562	AAE	IEEE 802.11ac WiFi (160 MHz, MCS8, 99pc duty cycle)	WLAN	8.69	±9.6
10563	AAE	IEEE 802.11ac WiFi (160 MHz, MCS9, 99pc duty cycle)	WLAN	8.77	±9.6
10564	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 9 Mbps, 99pc duty cycle)	WLAN	8.25	±9.6
10565	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 99pc duty cycle)	WLAN	8.45	±9.6
10566	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 99pc duty cycle)	WLAN	8.13	±9.6
10567	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 99pc duty cycle)	WLAN	8.00	±9.6
10568	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 99pc duty cycle)	WLAN	8.37	±9.6
10569	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 99pc duty cycle)	WLAN	8.10	±9.6
10570	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 54 Mbps, 99pc duty cycle)	WLAN	8.30	±9.6
10571	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 90pc duty cycle)	WLAN	1.99	±9.6
10572	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps, 90pc duty cycle)	WLAN	1.99	±9.6
10573	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps, 90pc duty cycle)	WLAN	1.98	±9.6
10574	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps, 90pc duty cycle)	WLAN	1.98	±9.6
10575	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 90pc duty cycle)	WLAN	8.59	±9.6
10576	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 9 Mbps, 90pc duty cycle)	WLAN	8.60	±9.6
10577	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 90pc duty cycle)	WLAN	8.70	±9.6
10578	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 90pc duty cycle)	WLAN	8.49	±9.6
10579	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 90pc duty cycle)	WLAN	8.36	±9.6
10580	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 90pc duty cycle)	WLAN	8.76	±9.6
10581	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 90pc duty cycle)	WLAN	8.35	±9.6
10582	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 54 Mbps, 90pc duty cycle)	WLAN	8.67	±9.6
10583	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps, 90pc duty cycle)	WLAN	8.59	±9.6
10584	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps, 90pc duty cycle)	WLAN	8.60	±9.6
10585	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps, 90pc duty cycle)	WLAN	8.70	±9.6
10586	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps, 90pc duty cycle)	WLAN	8.49	±9.6
10587	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps, 90pc duty cycle)	WLAN	8.36	±9.6
10588	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps, 90pc duty cycle)	WLAN	8.76	±9.6
10589	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps, 90pc duty cycle)	WLAN	8.35	±9.6
10590	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps, 90pc duty cycle)	WLAN	8.67	±9.6
10591	AAD	IEEE 802.11n (HT Mixed, 20 MHz, MCS0, 90pc duty cycle)	WLAN	8.63	±9.6
10592	AAD	IEEE 802.11n (HT Mixed, 20 MHz, MCS1, 90pc duty cycle)	WLAN	8.79	±9.6
10593	AAD	IEEE 802.11n (HT Mixed, 20 MHz, MCS2, 90pc duty cycle)	WLAN	8.64	±9.6
10594	AAD	IEEE 802.11n (HT Mixed, 20 MHz, MCS3, 90pc duty cycle)	WLAN	8.74	±9.6
10595	AAD	IEEE 802.11n (HT Mixed, 20 MHz, MCS4, 90pc duty cycle)	WLAN	8.74	±9.6
10596	AAD	IEEE 802.11n (HT Mixed, 20 MHz, MCS5, 90pc duty cycle)	WLAN	8.71	±9.6
10597	AAD	IEEE 802.11n (HT Mixed, 20 MHz, MCS6, 90pc duty cycle)	WLAN	8.72	±9.6
10598	AAD	IEEE 802.11n (HT Mixed, 20 MHz, MCS7, 90pc duty cycle)	WLAN	8.50	±9.6
10599	AAD	IEEE 802.11n (HT Mixed, 40 MHz, MCS0, 90pc duty cycle)	WLAN	8.79	±9.6
10600	AAD	IEEE 802.11n (HT Mixed, 40 MHz, MCS1, 90pc duty cycle)	WLAN	8.88	±9.6
10601	AAD	IEEE 802.11n (HT Mixed, 40 MHz, MCS2, 90pc duty cycle)	WLAN	8.82	±9.6
10602	AAD	IEEE 802.11n (HT Mixed, 40 MHz, MCS3, 90pc duty cycle)	WLAN	8.94	±9.6
10603	AAD	IEEE 802.11n (HT Mixed, 40 MHz, MCS4, 90pc duty cycle)	WLAN	9.03	±9.6
10604	AAD	IEEE 802.11n (HT Mixed, 40 MHz, MCS5, 90pc duty cycle)	WLAN	8.76	±9.6
10605	AAD	IEEE 802.11n (HT Mixed, 40 MHz, MCS6, 90pc duty cycle)	WLAN	8.97	±9.6
10606	AAD	IEEE 802.11n (HT Mixed, 40 MHz, MCS7, 90pc duty cycle)	WLAN	8.82	±9.6
10607	AAD	IEEE 802.11ac WiFi (20 MHz, MCS0, 90pc duty cycle)	WLAN	8.64	±9.6
10608	AAD	IEEE 802.11ac WiFi (20 MHz, MCS1, 90pc duty cycle)	WLAN	8.77	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E $k = 2$
10609	AAD	IEEE 802.11ac WiFi (20 MHz, MCS2, 90pc duty cycle)	WLAN	8.57	±9.6
10610	AAD	IEEE 802.11ac WiFi (20 MHz, MCS3, 90pc duty cycle)	WLAN	8.78	±9.6
10611	AAD	IEEE 802.11ac WiFi (20 MHz, MCS4, 90pc duty cycle)	WLAN	8.70	±9.6
10612	AAD	IEEE 802.11ac WiFi (20 MHz, MCS5, 90pc duty cycle)	WLAN	8.77	±9.6
10613	AAD	IEEE 802.11ac WiFi (20 MHz, MCS6, 90pc duty cycle)	WLAN	8.94	±9.6
10614	AAD	IEEE 802.11ac WiFi (20 MHz, MCS7, 90pc duty cycle)	WLAN	8.59	±9.6
10615	AAD	IEEE 802.11ac WiFi (20 MHz, MCS8, 90pc duty cycle)	WLAN	8.82	±9.6
10616	AAD	IEEE 802.11ac WiFi (40 MHz, MCS0, 90pc duty cycle)	WLAN	8.82	±9.6
10617	AAD	IEEE 802.11ac WiFi (40 MHz, MCS1, 90pc duty cycle)	WLAN	8.81	±9.6
10618	AAD	IEEE 802.11ac WiFi (40 MHz, MCS2, 90pc duty cycle)	WLAN	8.58	±9.6
10619	AAD	IEEE 802.11ac WiFi (40 MHz, MCS3, 90pc duty cycle)	WLAN	8.86	±9.6
10620	AAD	IEEE 802.11ac WiFi (40 MHz, MCS4, 90pc duty cycle)	WLAN	8.87	±9.6
10621	AAD	IEEE 802.11ac WiFi (40 MHz, MCS5, 90pc duty cycle)	WLAN	8.77	±9.6
10622	AAD	IEEE 802.11ac WiFi (40 MHz, MCS6, 90pc duty cycle)	WLAN	8.68	±9.6
10623	AAD	IEEE 802.11ac WiFi (40 MHz, MCS7, 90pc duty cycle)	WLAN	8.82	±9.6
10624	AAD	IEEE 802.11ac WiFi (40 MHz, MCS8, 90pc duty cycle)	WLAN	8.96	±9.6
10625	AAD	IEEE 802.11ac WiFi (40 MHz, MCS9, 90pc duty cycle)	WLAN	8.96	±9.6
10626	AAD	IEEE 802.11ac WiFi (80 MHz, MCS0, 90pc duty cycle)	WLAN	8.83	±9.6
10627	AAD	IEEE 802.11ac WiFi (80 MHz, MCS1, 90pc duty cycle)	WLAN	8.88	±9.6
10628	AAD	IEEE 802.11ac WiFi (80 MHz, MCS2, 90pc duty cycle)	WLAN	8.71	±9.6
10629	AAD	IEEE 802.11ac WiFi (80 MHz, MCS3, 90pc duty cycle)	WLAN	8.85	±9.6
10630	AAD	IEEE 802.11ac WiFi (80 MHz, MCS4, 90pc duty cycle)	WLAN	8.72	±9.6
10631	AAD	IEEE 802.11ac WiFi (80 MHz, MCS5, 90pc duty cycle)	WLAN	8.81	±9.6
10632	AAD	IEEE 802.11ac WiFi (80 MHz, MCS6, 90pc duty cycle)	WLAN	8.74	±9.6
10633	AAD	IEEE 802.11ac WiFi (80 MHz, MCS7, 90pc duty cycle)	WLAN	8.83	±9.6
10634	AAD	IEEE 802.11ac WiFi (80 MHz, MCS8, 90pc duty cycle)	WLAN	8.80	±9.6
10635	AAD	IEEE 802.11ac WiFi (80 MHz, MCS9, 90pc duty cycle)	WLAN	8.81	±9.6
10636	AAE	IEEE 802.11ac WiFi (160 MHz, MCS0, 90pc duty cycle)	WLAN	8.83	±9.6
10637	AAE	IEEE 802.11ac WiFi (160 MHz, MCS1, 90pc duty cycle)	WLAN	8.79	±9.6
10638	AAE	IEEE 802.11ac WiFi (160 MHz, MCS2, 90pc duty cycle)	WLAN	8.86	±9.6
10639	AAE	IEEE 802.11ac WiFi (160 MHz, MCS3, 90pc duty cycle)	WLAN	8.85	±9.6
10640	AAE	IEEE 802.11ac WiFi (160 MHz, MCS4, 90pc duty cycle)	WLAN	8.98	±9.6
10641	AAE	IEEE 802.11ac WiFi (160 MHz, MCS5, 90pc duty cycle)	WLAN	9.06	±9.6
10642	AAE	IEEE 802.11ac WiFi (160 MHz, MCS6, 90pc duty cycle)	WLAN	9.06	±9.6
10643	AAE	IEEE 802.11ac WiFi (160 MHz, MCS7, 90pc duty cycle)	WLAN	8.89	±9.6
10644	AAE	IEEE 802.11ac WiFi (160 MHz, MCS8, 90pc duty cycle)	WLAN	9.05	±9.6
10645	AAE	IEEE 802.11ac WiFi (160 MHz, MCS9, 90pc duty cycle)	WLAN	9.11	±9.6
10646	AAH	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe=2,7)	LTE-TDD	11.96	±9.6
10647	AAG	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK, UL Subframe=2,7)	LTE-TDD	11.96	±9.6
10648	AAA	CDMA2000 (1x Advanced)	CDMA2000	3.45	±9.6
10652	AAF	LTE-TDD (OFDMA, 5 MHz, E-TM 3.1, Clipping 44%)	LTE-TDD	6.91	±9.6
10653	AAF	LTE-TDD (OFDMA, 10 MHz, E-TM 3.1, Clipping 44%)	LTE-TDD	7.42	±9.6
10654	AAE	LTE-TDD (OFDMA, 15 MHz, E-TM 3.1, Clipping 44%)	LTE-TDD	6.96	±9.6
10655	AAF	LTE-TDD (OFDMA, 20 MHz, E-TM 3.1, Clipping 44%)	LTE-TDD	7.21	±9.6
10658	AAB	Pulse Waveform (200Hz, 10%)	Test	10.00	±9.6
10659	AAB	Pulse Waveform (200Hz, 20%)	Test	6.99	±9.6
10660	AAB	Pulse Waveform (200Hz, 40%)	Test	3.98	±9.6
10661	AAB	Pulse Waveform (200Hz, 60%)	Test	2.22	±9.6
10662	AAB	Pulse Waveform (200Hz, 80%)	Test	0.97	±9.6
10670	AAA	Bluetooth Low Energy	Bluetooth	2.19	±9.6
10671	AAC	IEEE 802.11ax (20 MHz, MCS0, 90pc duty cycle)	WLAN	9.09	±9.6
10672	AAC	IEEE 802.11ax (20 MHz, MCS1, 90pc duty cycle)	WLAN	8.57	±9.6
10673	AAC	IEEE 802.11ax (20 MHz, MCS2, 90pc duty cycle)	WLAN	8.78	±9.6
10674	AAC	IEEE 802.11ax (20 MHz, MCS3, 90pc duty cycle)	WLAN	8.74	±9.6
10675	AAC	IEEE 802.11ax (20 MHz, MCS4, 90pc duty cycle)	WLAN	8.90	±9.6
10676	AAC	IEEE 802.11ax (20 MHz, MCS5, 90pc duty cycle)	WLAN	8.77	±9.6
10677	AAC	IEEE 802.11ax (20 MHz, MCS6, 90pc duty cycle)	WLAN	8.73	±9.6
10678	AAC	IEEE 802.11ax (20 MHz, MCS7, 90pc duty cycle)	WLAN	8.78	±9.6
10679	AAC	IEEE 802.11ax (20 MHz, MCS8, 90pc duty cycle)	WLAN	8.89	±9.6
10680	AAC	IEEE 802.11ax (20 MHz, MCS9, 90pc duty cycle)	WLAN	8.80	±9.6
10681	AAC	IEEE 802.11ax (20 MHz, MCS10, 90pc duty cycle)	WLAN	8.62	±9.6
10682	AAC	IEEE 802.11ax (20 MHz, MCS11, 90pc duty cycle)	WLAN	8.83	±9.6
10683	AAC	IEEE 802.11ax (20 MHz, MCS0, 99pc duty cycle)	WLAN	8.42	±9.6
10684	AAC	IEEE 802.11ax (20 MHz, MCS1, 99pc duty cycle)	WLAN	8.26	±9.6
10685	AAC	IEEE 802.11ax (20 MHz, MCS2, 99pc duty cycle)	WLAN	8.33	±9.6
10686	AAC	IEEE 802.11ax (20 MHz, MCS3, 99pc duty cycle)	WLAN	8.28	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E k = 2
10687	AAC	IEEE 802.11ax (20 MHz, MCS4, 99pc duty cycle)	WLAN	8.45	±9.6
10688	AAC	IEEE 802.11ax (20 MHz, MCS5, 99pc duty cycle)	WLAN	8.29	±9.6
10689	AAC	IEEE 802.11ax (20 MHz, MCS6, 99pc duty cycle)	WLAN	8.55	±9.6
10690	AAC	IEEE 802.11ax (20 MHz, MCS7, 99pc duty cycle)	WLAN	8.29	±9.6
10691	AAC	IEEE 802.11ax (20 MHz, MCS8, 99pc duty cycle)	WLAN	8.25	±9.6
10692	AAC	IEEE 802.11ax (20 MHz, MCS9, 99pc duty cycle)	WLAN	8.29	±9.6
10693	AAC	IEEE 802.11ax (20 MHz, MCS10, 99pc duty cycle)	WLAN	8.25	±9.6
10694	AAC	IEEE 802.11ax (20 MHz, MCS11, 99pc duty cycle)	WLAN	8.57	±9.6
10695	AAC	IEEE 802.11ax (40 MHz, MCS0, 90pc duty cycle)	WLAN	8.78	±9.6
10696	AAC	IEEE 802.11ax (40 MHz, MCS1, 90pc duty cycle)	WLAN	8.91	±9.6
10697	AAC	IEEE 802.11ax (40 MHz, MCS2, 90pc duty cycle)	WLAN	8.61	±9.6
10698	AAC	IEEE 802.11ax (40 MHz, MCS3, 90pc duty cycle)	WLAN	8.89	±9.6
10699	AAC	IEEE 802.11ax (40 MHz, MCS4, 90pc duty cycle)	WLAN	8.82	±9.6
10700	AAC	IEEE 802.11ax (40 MHz, MCS5, 90pc duty cycle)	WLAN	8.73	±9.6
10701	AAC	IEEE 802.11ax (40 MHz, MCS6, 90pc duty cycle)	WLAN	8.86	±9.6
10702	AAC	IEEE 802.11ax (40 MHz, MCS7, 90pc duty cycle)	WLAN	8.70	±9.6
10703	AAC	IEEE 802.11ax (40 MHz, MCS8, 90pc duty cycle)	WLAN	8.82	±9.6
10704	AAC	IEEE 802.11ax (40 MHz, MCS9, 90pc duty cycle)	WLAN	8.56	±9.6
10705	AAC	IEEE 802.11ax (40 MHz, MCS10, 90pc duty cycle)	WLAN	8.69	±9.6
10706	AAC	IEEE 802.11ax (40 MHz, MCS11, 90pc duty cycle)	WLAN	8.66	±9.6
10707	AAC	IEEE 802.11ax (40 MHz, MCS0, 99pc duty cycle)	WLAN	8.32	±9.6
10708	AAC	IEEE 802.11ax (40 MHz, MCS1, 99pc duty cycle)	WLAN	8.55	±9.6
10709	AAC	IEEE 802.11ax (40 MHz, MCS2, 99pc duty cycle)	WLAN	8.33	±9.6
10710	AAC	IEEE 802.11ax (40 MHz, MCS3, 99pc duty cycle)	WLAN	8.29	±9.6
10711	AAC	IEEE 802.11ax (40 MHz, MCS4, 99pc duty cycle)	WLAN	8.39	±9.6
10712	AAC	IEEE 802.11ax (40 MHz, MCS5, 99pc duty cycle)	WLAN	8.67	±9.6
10713	AAC	IEEE 802.11ax (40 MHz, MCS6, 99pc duty cycle)	WLAN	8.33	±9.6
10714	AAC	IEEE 802.11ax (40 MHz, MCS7, 99pc duty cycle)	WLAN	8.26	±9.6
10715	AAC	IEEE 802.11ax (40 MHz, MCS8, 99pc duty cycle)	WLAN	8.45	±9.6
10716	AAC	IEEE 802.11ax (40 MHz, MCS9, 99pc duty cycle)	WLAN	8.30	±9.6
10717	AAC	IEEE 802.11ax (40 MHz, MCS10, 99pc duty cycle)	WLAN	8.48	±9.6
10718	AAC	IEEE 802.11ax (40 MHz, MCS11, 99pc duty cycle)	WLAN	8.24	±9.6
10719	AAC	IEEE 802.11ax (80 MHz, MCS0, 90pc duty cycle)	WLAN	8.81	±9.6
10720	AAC	IEEE 802.11ax (80 MHz, MCS1, 90pc duty cycle)	WLAN	8.87	±9.6
10721	AAC	IEEE 802.11ax (80 MHz, MCS2, 90pc duty cycle)	WLAN	8.76	±9.6
10722	AAC	IEEE 802.11ax (80 MHz, MCS3, 90pc duty cycle)	WLAN	8.55	±9.6
10723	AAC	IEEE 802.11ax (80 MHz, MCS4, 90pc duty cycle)	WLAN	8.70	±9.6
10724	AAC	IEEE 802.11ax (80 MHz, MCS5, 90pc duty cycle)	WLAN	8.90	±9.6
10725	AAC	IEEE 802.11ax (80 MHz, MCS6, 90pc duty cycle)	WLAN	8.74	±9.6
10726	AAC	IEEE 802.11ax (80 MHz, MCS7, 90pc duty cycle)	WLAN	8.72	±9.6
10727	AAC	IEEE 802.11ax (80 MHz, MCS8, 90pc duty cycle)	WLAN	8.66	±9.6
10728	AAC	IEEE 802.11ax (80 MHz, MCS9, 90pc duty cycle)	WLAN	8.65	±9.6
10729	AAC	IEEE 802.11ax (80 MHz, MCS10, 90pc duty cycle)	WLAN	8.64	±9.6
10730	AAC	IEEE 802.11ax (80 MHz, MCS11, 90pc duty cycle)	WLAN	8.67	±9.6
10731	AAC	IEEE 802.11ax (80 MHz, MCS0, 99pc duty cycle)	WLAN	8.42	±9.6
10732	AAC	IEEE 802.11ax (80 MHz, MCS1, 99pc duty cycle)	WLAN	8.46	±9.6
10733	AAC	IEEE 802.11ax (80 MHz, MCS2, 99pc duty cycle)	WLAN	8.40	±9.6
10734	AAC	IEEE 802.11ax (80 MHz, MCS3, 99pc duty cycle)	WLAN	8.25	±9.6
10735	AAC	IEEE 802.11ax (80 MHz, MCS4, 99pc duty cycle)	WLAN	8.33	±9.6
10736	AAC	IEEE 802.11ax (80 MHz, MCS5, 99pc duty cycle)	WLAN	8.27	±9.6
10737	AAC	IEEE 802.11ax (80 MHz, MCS6, 99pc duty cycle)	WLAN	8.36	±9.6
10738	AAC	IEEE 802.11ax (80 MHz, MCS7, 99pc duty cycle)	WLAN	8.42	±9.6
10739	AAC	IEEE 802.11ax (80 MHz, MCS8, 99pc duty cycle)	WLAN	8.29	±9.6
10740	AAC	IEEE 802.11ax (80 MHz, MCS9, 99pc duty cycle)	WLAN	8.48	±9.6
10741	AAC	IEEE 802.11ax (80 MHz, MCS10, 99pc duty cycle)	WLAN	8.40	±9.6
10742	AAC	IEEE 802.11ax (80 MHz, MCS11, 99pc duty cycle)	WLAN	8.43	±9.6
10743	AAC	IEEE 802.11ax (160 MHz, MCS0, 90pc duty cycle)	WLAN	8.94	±9.6
10744	AAC	IEEE 802.11ax (160 MHz, MCS1, 90pc duty cycle)	WLAN	9.16	±9.6
10745	AAC	IEEE 802.11ax (160 MHz, MCS2, 90pc duty cycle)	WLAN	8.93	±9.6
10746	AAC	IEEE 802.11ax (160 MHz, MCS3, 90pc duty cycle)	WLAN	9.11	±9.6
10747	AAC	IEEE 802.11ax (160 MHz, MCS4, 90pc duty cycle)	WLAN	9.04	±9.6
10748	AAC	IEEE 802.11ax (160 MHz, MCS5, 90pc duty cycle)	WLAN	8.93	±9.6
10749	AAC	IEEE 802.11ax (160 MHz, MCS6, 90pc duty cycle)	WLAN	8.90	±9.6
10750	AAC	IEEE 802.11ax (160 MHz, MCS7, 90pc duty cycle)	WLAN	8.79	±9.6
10751	AAC	IEEE 802.11ax (160 MHz, MCS8, 90pc duty cycle)	WLAN	8.82	±9.6
10752	AAC	IEEE 802.11ax (160 MHz, MCS9, 90pc duty cycle)	WLAN	8.81	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E k = 2
10753	AAC	IEEE 802.11ax (160 MHz, MCS10, 90pc duty cycle)	WLAN	9.00	±9.6
10754	AAC	IEEE 802.11ax (160 MHz, MCS11, 90pc duty cycle)	WLAN	8.94	±9.6
10755	AAC	IEEE 802.11ax (160 MHz, MCS0, 99pc duty cycle)	WLAN	8.64	±9.6
10756	AAC	IEEE 802.11ax (160 MHz, MCS1, 99pc duty cycle)	WLAN	8.77	±9.6
10757	AAC	IEEE 802.11ax (160 MHz, MCS2, 99pc duty cycle)	WLAN	8.77	±9.6
10758	AAC	IEEE 802.11ax (160 MHz, MCS3, 99pc duty cycle)	WLAN	8.69	±9.6
10759	AAC	IEEE 802.11ax (160 MHz, MCS4, 99pc duty cycle)	WLAN	8.58	±9.6
10760	AAC	IEEE 802.11ax (160 MHz, MCS5, 99pc duty cycle)	WLAN	8.49	±9.6
10761	AAC	IEEE 802.11ax (160 MHz, MCS6, 99pc duty cycle)	WLAN	8.58	±9.6
10762	AAC	IEEE 802.11ax (160 MHz, MCS7, 99pc duty cycle)	WLAN	8.49	±9.6
10763	AAC	IEEE 802.11ax (160 MHz, MCS8, 99pc duty cycle)	WLAN	8.53	±9.6
10764	AAC	IEEE 802.11ax (160 MHz, MCS9, 99pc duty cycle)	WLAN	8.54	±9.6
10765	AAC	IEEE 802.11ax (160 MHz, MCS10, 99pc duty cycle)	WLAN	8.54	±9.6
10766	AAC	IEEE 802.11ax (160 MHz, MCS11, 99pc duty cycle)	WLAN	8.51	±9.6
10767	AAG	5G NR (CP-OFDM, 1 RB, 5 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	7.99	±9.6
10768	AAE	5G NR (CP-OFDM, 1 RB, 10 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.01	±9.6
10769	AAD	5G NR (CP-OFDM, 1 RB, 15 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.01	±9.6
10770	AAE	5G NR (CP-OFDM, 1 RB, 20 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.02	±9.6
10771	AAD	5G NR (CP-OFDM, 1 RB, 25 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.02	±9.6
10772	AAE	5G NR (CP-OFDM, 1 RB, 30 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.23	±9.6
10773	AAF	5G NR (CP-OFDM, 1 RB, 40 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.03	±9.6
10774	AAE	5G NR (CP-OFDM, 1 RB, 50 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.02	±9.6
10775	AAF	5G NR (CP-OFDM, 50% RB, 5 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.31	±9.6
10776	AAE	5G NR (CP-OFDM, 50% RB, 10 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.30	±9.6
10777	AAC	5G NR (CP-OFDM, 50% RB, 15 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.30	±9.6
10778	AAE	5G NR (CP-OFDM, 50% RB, 20 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.34	±9.6
10779	AAC	5G NR (CP-OFDM, 50% RB, 25 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.42	±9.6
10780	AAE	5G NR (CP-OFDM, 50% RB, 30 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.38	±9.6
10781	AAF	5G NR (CP-OFDM, 50% RB, 40 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.38	±9.6
10782	AAE	5G NR (CP-OFDM, 50% RB, 50 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.43	±9.6
10783	AAG	5G NR (CP-OFDM, 100% RB, 5 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.31	±9.6
10784	AAE	5G NR (CP-OFDM, 100% RB, 10 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.29	±9.6
10785	AAD	5G NR (CP-OFDM, 100% RB, 15 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.40	±9.6
10786	AAE	5G NR (CP-OFDM, 100% RB, 20 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.35	±9.6
10787	AAD	5G NR (CP-OFDM, 100% RB, 25 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.44	±9.6
10788	AAE	5G NR (CP-OFDM, 100% RB, 30 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.39	±9.6
10789	AAF	5G NR (CP-OFDM, 100% RB, 40 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.37	±9.6
10790	AAE	5G NR (CP-OFDM, 100% RB, 50 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.39	±9.6
10791	AAG	5G NR (CP-OFDM, 1 RB, 5 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.83	±9.6
10792	AAE	5G NR (CP-OFDM, 1 RB, 10 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.92	±9.6
10793	AAD	5G NR (CP-OFDM, 1 RB, 15 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.95	±9.6
10794	AAE	5G NR (CP-OFDM, 1 RB, 20 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.82	±9.6
10795	AAD	5G NR (CP-OFDM, 1 RB, 25 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.84	±9.6
10796	AAE	5G NR (CP-OFDM, 1 RB, 30 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.82	±9.6
10797	AAF	5G NR (CP-OFDM, 1 RB, 40 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.01	±9.6
10798	AAE	5G NR (CP-OFDM, 1 RB, 50 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.89	±9.6
10799	AAF	5G NR (CP-OFDM, 1 RB, 60 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.93	±9.6
10801	AAF	5G NR (CP-OFDM, 1 RB, 80 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.89	±9.6
10802	AAE	5G NR (CP-OFDM, 1 RB, 90 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.87	±9.6
10803	AAF	5G NR (CP-OFDM, 1 RB, 100 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.93	±9.6
10805	AAE	5G NR (CP-OFDM, 50% RB, 10 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.34	±9.6
10806	AAD	5G NR (CP-OFDM, 50% RB, 15 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.37	±9.6
10809	AAE	5G NR (CP-OFDM, 50% RB, 30 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.34	±9.6
10810	AAF	5G NR (CP-OFDM, 50% RB, 40 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.34	±9.6
10812	AAF	5G NR (CP-OFDM, 50% RB, 60 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.35	±9.6
10817	AAG	5G NR (CP-OFDM, 100% RB, 5 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.35	±9.6
10818	AAE	5G NR (CP-OFDM, 100% RB, 10 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.34	±9.6
10819	AAD	5G NR (CP-OFDM, 100% RB, 15 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.33	±9.6
10820	AAE	5G NR (CP-OFDM, 100% RB, 20 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.30	±9.6
10821	AAD	5G NR (CP-OFDM, 100% RB, 25 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.41	±9.6
10822	AAE	5G NR (CP-OFDM, 100% RB, 30 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.41	±9.6
10823	AAF	5G NR (CP-OFDM, 100% RB, 40 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.36	±9.6
10824	AAE	5G NR (CP-OFDM, 100% RB, 50 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.39	±9.6
10825	AAF	5G NR (CP-OFDM, 100% RB, 60 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.41	±9.6
10827	AAF	5G NR (CP-OFDM, 100% RB, 80 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.42	±9.6
10828	AAE	5G NR (CP-OFDM, 100% RB, 90 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.43	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E $k = 2$
10829	AAF	5G NR (CP-OFDM, 100% RB, 100 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.40	±9.6
10830	AAE	5G NR (CP-OFDM, 1 RB, 10 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.63	±9.6
10831	AAD	5G NR (CP-OFDM, 1 RB, 15 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.73	±9.6
10832	AAE	5G NR (CP-OFDM, 1 RB, 20 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.74	±9.6
10833	AAD	5G NR (CP-OFDM, 1 RB, 25 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.70	±9.6
10834	AAE	5G NR (CP-OFDM, 1 RB, 30 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.75	±9.6
10835	AAF	5G NR (CP-OFDM, 1 RB, 40 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.70	±9.6
10836	AAE	5G NR (CP-OFDM, 1 RB, 50 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.66	±9.6
10837	AAF	5G NR (CP-OFDM, 1 RB, 60 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.68	±9.6
10839	AAF	5G NR (CP-OFDM, 1 RB, 80 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.70	±9.6
10840	AAE	5G NR (CP-OFDM, 1 RB, 90 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.67	±9.6
10841	AAF	5G NR (CP-OFDM, 1 RB, 100 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.71	±9.6
10843	AAD	5G NR (CP-OFDM, 50% RB, 15 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.49	±9.6
10844	AAE	5G NR (CP-OFDM, 50% RB, 20 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.34	±9.6
10846	AAE	5G NR (CP-OFDM, 50% RB, 30 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.41	±9.6
10854	AAE	5G NR (CP-OFDM, 100% RB, 10 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.34	±9.6
10855	AAD	5G NR (CP-OFDM, 100% RB, 15 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.36	±9.6
10856	AAE	5G NR (CP-OFDM, 100% RB, 20 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.37	±9.6
10857	AAD	5G NR (CP-OFDM, 100% RB, 25 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.35	±9.6
10858	AAE	5G NR (CP-OFDM, 100% RB, 30 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.36	±9.6
10859	AAF	5G NR (CP-OFDM, 100% RB, 40 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.34	±9.6
10860	AAE	5G NR (CP-OFDM, 100% RB, 50 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.41	±9.6
10861	AAF	5G NR (CP-OFDM, 100% RB, 60 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.40	±9.6
10863	AAF	5G NR (CP-OFDM, 100% RB, 80 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.41	±9.6
10864	AAE	5G NR (CP-OFDM, 100% RB, 90 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.37	±9.6
10865	AAF	5G NR (CP-OFDM, 100% RB, 100 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.41	±9.6
10866	AAF	5G NR (DFT-s-OFDM, 1 RB, 100 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	±9.6
10868	AAF	5G NR (DFT-s-OFDM, 100% RB, 100 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.89	±9.6
10869	AAE	5G NR (DFT-s-OFDM, 1 RB, 100 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	5.75	±9.6
10870	AAE	5G NR (DFT-s-OFDM, 100% RB, 100 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	5.86	±9.6
10871	AAE	5G NR (DFT-s-OFDM, 1 RB, 100 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	5.75	±9.6
10872	AAE	5G NR (DFT-s-OFDM, 100% RB, 100 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	6.52	±9.6
10873	AAE	5G NR (DFT-s-OFDM, 1 RB, 100 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	6.61	±9.6
10874	AAE	5G NR (DFT-s-OFDM, 100% RB, 100 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	6.65	±9.6
10875	AAE	5G NR (CP-OFDM, 1 RB, 100 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	7.78	±9.6
10876	AAE	5G NR (CP-OFDM, 100% RB, 100 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	8.39	±9.6
10877	AAE	5G NR (CP-OFDM, 1 RB, 100 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	7.95	±9.6
10878	AAE	5G NR (CP-OFDM, 100% RB, 100 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	8.41	±9.6
10879	AAE	5G NR (CP-OFDM, 1 RB, 100 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	8.12	±9.6
10880	AAE	5G NR (CP-OFDM, 100% RB, 100 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	8.38	±9.6
10881	AAE	5G NR (DFT-s-OFDM, 1 RB, 50 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	5.75	±9.6
10882	AAE	5G NR (DFT-s-OFDM, 100% RB, 50 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	5.96	±9.6
10883	AAE	5G NR (DFT-s-OFDM, 1 RB, 50 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	6.57	±9.6
10884	AAE	5G NR (DFT-s-OFDM, 100% RB, 50 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	6.53	±9.6
10885	AAE	5G NR (DFT-s-OFDM, 1 RB, 50 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	6.61	±9.6
10886	AAE	5G NR (DFT-s-OFDM, 100% RB, 50 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	6.65	±9.6
10887	AAE	5G NR (CP-OFDM, 1 RB, 50 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	7.78	±9.6
10888	AAE	5G NR (CP-OFDM, 100% RB, 50 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	8.35	±9.6
10889	AAE	5G NR (CP-OFDM, 1 RB, 50 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	8.02	±9.6
10890	AAE	5G NR (CP-OFDM, 100% RB, 50 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	8.40	±9.6
10891	AAE	5G NR (CP-OFDM, 1 RB, 50 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	8.13	±9.6
10892	AAE	5G NR (CP-OFDM, 100% RB, 50 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	8.41	±9.6
10897	AAE	5G NR (DFT-s-OFDM, 1 RB, 5 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.66	±9.6
10898	AAC	5G NR (DFT-s-OFDM, 1 RB, 10 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.67	±9.6
10899	AAB	5G NR (DFT-s-OFDM, 1 RB, 15 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.67	±9.6
10900	AAC	5G NR (DFT-s-OFDM, 1 RB, 20 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	±9.6
10901	AAB	5G NR (DFT-s-OFDM, 1 RB, 25 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	±9.6
10902	AAC	5G NR (DFT-s-OFDM, 1 RB, 30 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	±9.6
10903	AAD	5G NR (DFT-s-OFDM, 1 RB, 40 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	±9.6
10904	AAC	5G NR (DFT-s-OFDM, 1 RB, 50 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	±9.6
10905	AAD	5G NR (DFT-s-OFDM, 1 RB, 60 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	±9.6
10906	AAD	5G NR (DFT-s-OFDM, 1 RB, 80 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	±9.6
10907	AAE	5G NR (DFT-s-OFDM, 50% RB, 5 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.78	±9.6
10908	AAC	5G NR (DFT-s-OFDM, 50% RB, 10 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.93	±9.6
10909	AAB	5G NR (DFT-s-OFDM, 50% RB, 15 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.96	±9.6
10910	AAC	5G NR (DFT-s-OFDM, 50% RB, 20 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.83	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E $k = 2$
10911	AAB	5G NR (DFT-s-OFDM, 50% RB, 25 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.93	±9.6
10912	AAC	5G NR (DFT-s-OFDM, 50% RB, 30 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.84	±9.6
10913	AAD	5G NR (DFT-s-OFDM, 50% RB, 40 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.84	±9.6
10914	AAC	5G NR (DFT-s-OFDM, 50% RB, 50 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.85	±9.6
10915	AAD	5G NR (DFT-s-OFDM, 50% RB, 60 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.83	±9.6
10916	AAD	5G NR (DFT-s-OFDM, 50% RB, 80 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.87	±9.6
10917	AAD	5G NR (DFT-s-OFDM, 50% RB, 100 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.94	±9.6
10918	AAE	5G NR (DFT-s-OFDM, 100% RB, 5 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.86	±9.6
10919	AAC	5G NR (DFT-s-OFDM, 100% RB, 10 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.86	±9.6
10920	AAB	5G NR (DFT-s-OFDM, 100% RB, 15 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.87	±9.6
10921	AAC	5G NR (DFT-s-OFDM, 100% RB, 20 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.84	±9.6
10922	AAB	5G NR (DFT-s-OFDM, 100% RB, 25 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.82	±9.6
10923	AAC	5G NR (DFT-s-OFDM, 100% RB, 30 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.84	±9.6
10924	AAD	5G NR (DFT-s-OFDM, 100% RB, 40 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.84	±9.6
10925	AAC	5G NR (DFT-s-OFDM, 100% RB, 50 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.95	±9.6
10926	AAD	5G NR (DFT-s-OFDM, 100% RB, 60 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.84	±9.6
10927	AAD	5G NR (DFT-s-OFDM, 100% RB, 80 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.94	±9.6
10928	AAD	5G NR (DFT-s-OFDM, 1 RB, 5 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.52	±9.6
10929	AAD	5G NR (DFT-s-OFDM, 1 RB, 10 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.52	±9.6
10930	AAC	5G NR (DFT-s-OFDM, 1 RB, 15 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.52	±9.6
10931	AAC	5G NR (DFT-s-OFDM, 1 RB, 20 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.51	±9.6
10932	AAC	5G NR (DFT-s-OFDM, 1 RB, 25 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.51	±9.6
10933	AAC	5G NR (DFT-s-OFDM, 1 RB, 30 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.51	±9.6
10934	AAC	5G NR (DFT-s-OFDM, 1 RB, 40 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.51	±9.6
10935	AAD	5G NR (DFT-s-OFDM, 1 RB, 50 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.51	±9.6
10936	AAD	5G NR (DFT-s-OFDM, 50% RB, 5 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.90	±9.6
10937	AAD	5G NR (DFT-s-OFDM, 50% RB, 10 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.77	±9.6
10938	AAC	5G NR (DFT-s-OFDM, 50% RB, 15 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.90	±9.6
10939	AAC	5G NR (DFT-s-OFDM, 50% RB, 20 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.82	±9.6
10940	AAC	5G NR (DFT-s-OFDM, 50% RB, 25 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.89	±9.6
10941	AAC	5G NR (DFT-s-OFDM, 50% RB, 30 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.83	±9.6
10942	AAC	5G NR (DFT-s-OFDM, 50% RB, 40 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.85	±9.6
10943	AAD	5G NR (DFT-s-OFDM, 50% RB, 50 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.95	±9.6
10944	AAD	5G NR (DFT-s-OFDM, 100% RB, 5 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.81	±9.6
10945	AAD	5G NR (DFT-s-OFDM, 100% RB, 10 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.85	±9.6
10946	AAC	5G NR (DFT-s-OFDM, 100% RB, 15 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.83	±9.6
10947	AAC	5G NR (DFT-s-OFDM, 100% RB, 20 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.87	±9.6
10948	AAC	5G NR (DFT-s-OFDM, 100% RB, 25 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.94	±9.6
10949	AAC	5G NR (DFT-s-OFDM, 100% RB, 30 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.87	±9.6
10950	AAC	5G NR (DFT-s-OFDM, 100% RB, 40 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.94	±9.6
10951	AAD	5G NR (DFT-s-OFDM, 100% RB, 50 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.92	±9.6
10952	AAA	5G NR DL (CP-OFDM, TM 3.1, 5 MHz, 64-QAM, 15 kHz)	5G NR FR1 FDD	8.25	±9.6
10953	AAA	5G NR DL (CP-OFDM, TM 3.1, 10 MHz, 64-QAM, 15 kHz)	5G NR FR1 FDD	8.15	±9.6
10954	AAA	5G NR DL (CP-OFDM, TM 3.1, 15 MHz, 64-QAM, 15 kHz)	5G NR FR1 FDD	8.23	±9.6
10955	AAA	5G NR DL (CP-OFDM, TM 3.1, 20 MHz, 64-QAM, 15 kHz)	5G NR FR1 FDD	8.42	±9.6
10956	AAA	5G NR DL (CP-OFDM, TM 3.1, 5 MHz, 64-QAM, 30 kHz)	5G NR FR1 FDD	8.14	±9.6
10957	AAA	5G NR DL (CP-OFDM, TM 3.1, 10 MHz, 64-QAM, 30 kHz)	5G NR FR1 FDD	8.31	±9.6
10958	AAA	5G NR DL (CP-OFDM, TM 3.1, 15 MHz, 64-QAM, 30 kHz)	5G NR FR1 FDD	8.61	±9.6
10959	AAA	5G NR DL (CP-OFDM, TM 3.1, 20 MHz, 64-QAM, 30 kHz)	5G NR FR1 FDD	8.33	±9.6
10960	AAE	5G NR DL (CP-OFDM, TM 3.1, 5 MHz, 64-QAM, 15 kHz)	5G NR FR1 TDD	9.32	±9.6
10961	AAC	5G NR DL (CP-OFDM, TM 3.1, 10 MHz, 64-QAM, 15 kHz)	5G NR FR1 TDD	9.36	±9.6
10962	AAB	5G NR DL (CP-OFDM, TM 3.1, 15 MHz, 64-QAM, 15 kHz)	5G NR FR1 TDD	9.40	±9.6
10963	AAC	5G NR DL (CP-OFDM, TM 3.1, 20 MHz, 64-QAM, 15 kHz)	5G NR FR1 TDD	9.55	±9.6
10964	AAE	5G NR DL (CP-OFDM, TM 3.1, 5 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.29	±9.6
10965	AAC	5G NR DL (CP-OFDM, TM 3.1, 10 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.37	±9.6
10966	AAB	5G NR DL (CP-OFDM, TM 3.1, 15 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.55	±9.6
10967	AAC	5G NR DL (CP-OFDM, TM 3.1, 20 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.42	±9.6
10968	AAD	5G NR DL (CP-OFDM, TM 3.1, 100 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.49	±9.6
10972	AAC	5G NR (CP-OFDM, 1 RB, 20 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	11.59	±9.6
10973	AAD	5G NR (DFT-s-OFDM, 1 RB, 100 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	9.06	±9.6
10974	AAD	5G NR (CP-OFDM, 100% RB, 100 MHz, 256-QAM, 30 kHz)	5G NR FR1 TDD	10.28	±9.6
10978	AAA	ULLA BDR	ULLA	1.16	±9.6
10979	AAA	ULLA HDR4	ULLA	8.58	±9.6
10980	AAA	ULLA HDR8	ULLA	10.32	±9.6
10981	AAA	ULLA HDRp4	ULLA	3.19	±9.6
10982	AAA	ULLA HDRp8	ULLA	3.43	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E $k = 2$
10983	AAC	5G NR DL (CP-OFDM, TM 3.1, 40 MHz, 64-QAM, 15 kHz)	5G NR FR1 TDD	9.31	±9.6
10984	AAB	5G NR DL (CP-OFDM, TM 3.1, 50 MHz, 64-QAM, 15 kHz)	5G NR FR1 TDD	9.42	±9.6
10985	AAC	5G NR DL (CP-OFDM, TM 3.1, 40 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.54	±9.6
10986	AAB	5G NR DL (CP-OFDM, TM 3.1, 50 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.50	±9.6
10987	AAC	5G NR DL (CP-OFDM, TM 3.1, 60 MHz, 64-QAM, 15 kHz)	5G NR FR1 TDD	9.53	±9.6
10988	AAB	5G NR DL (CP-OFDM, TM 3.1, 70 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.38	±9.6
10989	AAC	5G NR DL (CP-OFDM, TM 3.1, 80 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.33	±9.6
10990	AAB	5G NR DL (CP-OFDM, TM 3.1, 90 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.52	±9.6
11003	AAA	5G NR DL (CP-OFDM, TM 3.1, 30 MHz, 64-QAM, 15 kHz)	5G NR FR1 TDD	10.24	±9.6
11004	AAA	5G NR DL (CP-OFDM, TM 3.1, 30 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	10.73	±9.6
11005	AAA	5G NR DL (CP-OFDM, TM 3.1, 25 MHz, 64-QAM, 15 kHz)	5G NR FR1 FDD	8.70	±9.6
11006	AAA	5G NR DL (CP-OFDM, TM 3.1, 30 MHz, 64-QAM, 15 kHz)	5G NR FR1 FDD	8.55	±9.6
11007	AAA	5G NR DL (CP-OFDM, TM 3.1, 40 MHz, 64-QAM, 15 kHz)	5G NR FR1 FDD	8.46	±9.6
11008	AAA	5G NR DL (CP-OFDM, TM 3.1, 50 MHz, 64-QAM, 15 kHz)	5G NR FR1 FDD	8.51	±9.6
11009	AAA	5G NR DL (CP-OFDM, TM 3.1, 25 MHz, 64-QAM, 30 kHz)	5G NR FR1 FDD	8.76	±9.6
11010	AAA	5G NR DL (CP-OFDM, TM 3.1, 30 MHz, 64-QAM, 30 kHz)	5G NR FR1 FDD	8.95	±9.6
11011	AAA	5G NR DL (CP-OFDM, TM 3.1, 40 MHz, 64-QAM, 30 kHz)	5G NR FR1 FDD	8.96	±9.6
11012	AAA	5G NR DL (CP-OFDM, TM 3.1, 50 MHz, 64-QAM, 30 kHz)	5G NR FR1 FDD	8.68	±9.6
11013	AAB	IEEE 802.11be (320 MHz, MCS1, 99pc duty cycle)	WLAN	8.47	±9.6
11014	AAB	IEEE 802.11be (320 MHz, MCS2, 99pc duty cycle)	WLAN	8.45	±9.6
11015	AAB	IEEE 802.11be (320 MHz, MCS3, 99pc duty cycle)	WLAN	8.44	±9.6
11016	AAB	IEEE 802.11be (320 MHz, MCS4, 99pc duty cycle)	WLAN	8.44	±9.6
11017	AAB	IEEE 802.11be (320 MHz, MCS5, 99pc duty cycle)	WLAN	8.41	±9.6
11018	AAB	IEEE 802.11be (320 MHz, MCS6, 99pc duty cycle)	WLAN	8.40	±9.6
11019	AAB	IEEE 802.11be (320 MHz, MCS7, 99pc duty cycle)	WLAN	8.29	±9.6
11020	AAB	IEEE 802.11be (320 MHz, MCS8, 99pc duty cycle)	WLAN	8.27	±9.6
11021	AAB	IEEE 802.11be (320 MHz, MCS9, 99pc duty cycle)	WLAN	8.46	±9.6
11022	AAB	IEEE 802.11be (320 MHz, MCS10, 99pc duty cycle)	WLAN	8.36	±9.6
11023	AAB	IEEE 802.11be (320 MHz, MCS11, 99pc duty cycle)	WLAN	8.09	±9.6
11024	AAB	IEEE 802.11be (320 MHz, MCS12, 99pc duty cycle)	WLAN	8.42	±9.6
11025	AAB	IEEE 802.11be (320 MHz, MCS13, 99pc duty cycle)	WLAN	8.37	±9.6
11026	AAB	IEEE 802.11be (320 MHz, MCS0, 99pc duty cycle)	WLAN	8.39	±9.6

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Client

B.V. ADT
Taoyuan City

Certificate No.

EUmm-9438_Jul24

CALIBRATION CERTIFICATE

Object EUmmWV4 - SN:9438

Calibration procedure(s) QA CAL-02.v9, QA CAL-25.v8, QA CAL-42.v3
Calibration procedure for E-field probes optimized for close near field
evaluations in air

Calibration date July 19, 2024

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^\circ\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power sensor NRP33T	SN: 100967	28-Mar-24 (No. 217-04038)	Mar-25
Power sensor NRP110T	SN: 101244	04-Apr-24 (No. 0001A300740056)	Apr-25
Spectrum analyzer FSV40	SN: 101832	25-Jan-24 (No. 4030-315007551)	Jan-25
Harmonic mixer FS-Z75	SN: 101566	11-Apr-24 (No. 0001A300750054)	Apr-25
Marmonic mixer FS-Z110	SN: 101633	05-Apr-24 (No. 0001A300740055)	Apr-25
Ref. Probe EUmmWV3	SN: 9374	04-Dec-23 (No. EUmm-9374_Dec23)	Dec-24
DAE4ip	SN: 1662	08-Nov-23 (No. DAE4ip-1662_Nov23)	Nov-24

Secondary Standards	ID	Check Date (in house)	Scheduled Check
Generator APSIN26G	SN: 2023	30-Nov-21 (in house check Jun-24)	In house check: Jun-25
Power sensor NRP40T	SN: 101439	08-Nov-21 (in house check Jun-24)	In house check: Jun-25
Power sensor NRP110T	SN: 101226	15-Nov-21 (in house check Jun-24)	In house check: Jun-25

	Name	Function	Signature
Calibrated by	Joanna Lleshaj	Laboratory Technician	
Approved by	Sven Kühn	Technical Manager	
Issued: July 19, 2024			
This calibration certificate shall not be reproduced except in full without written approval of the laboratory.			



Accredited by the Swiss Accreditation Service (SAS)
 The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Glossary

NORM _{x,y}	sensitivity in free space
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization φ	φ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system
Sensor Angles	sensor deviation from the probe axis, used to calculate the field orientation and polarization
$\vec{k}$	is the wave propagation direction

Calibration is Performed According to the Following Standards:

- IEEE Std 1309-2005, "IEEE Standard for calibration of electromagnetic field sensors and probes, excluding antennas, from 9 kHz to 40 GHz", December 2005

Methods Applied and Interpretation of Parameters:

- NORM_{x,y}**: Assessed for E-field polarization $\vartheta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). For frequencies > 6 GHz, the far field in front of waveguide horn antennas is measured for a set of frequencies in various waveguide bands up to 110 GHz.
- DCP_{x,y}**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal. DCP does not depend on frequency nor media.
 Note: As the field is measured with a diode detector sensor, it is warranted that the probe response is linear (E^2) below the documented lowest calibrated value.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- The frequency sensor model parameters are determined prior to calibration based on a frequency sweep (sensor model involving resistors R, R_p, inductance L and capacitors C, C_p).
- A_{x,y}; B_{x,y}; C_{x,y}; D_{x,y}; VR_{x,y}**: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle**: The angle is assessed using the information gained by determining the NORM_x (no uncertainty required).
- Equivalent Sensor Angle**: The two probe sensors are mounted in the same plane at different angles. The angles are assessed using the information gained by determining the NORM_x (no uncertainty required).
- Spherical isotropy (3D deviation from isotropy)**: in a locally homogeneous field realized using an open waveguide / horn setup.

Parameters of Probe: EUmmWV4 - SN:9438

Basic Calibration Parameters

	Sensor X	Sensor Y	Unc ($k = 2$)
Norm ($\mu\text{V}/(\text{V}/\text{m})^2$)	0.01988	0.02034	$\pm 10.1\%$
DCP (mV) ^B	107.0	105.0	$\pm 4.7\%$
Equivalent Sensor Angle	-61.8	34.7	

Calibration Results for Frequency Response (750 MHz – 110 GHz)

Frequency GHz	Target E-Field V/m	Deviation Sensor X dB	Deviation Sensor Y dB	Unc ($k = 2$) dB
0.75	77.2	-0.29	-0.28	± 0.43
1.8	140.4	-0.02	-0.03	± 0.43
2.0	133.0	0.12	0.15	± 0.43
2.2	124.8	-0.06	-0.05	± 0.43
2.5	123.0	0.08	0.12	± 0.43
3.5	256.2	-0.14	-0.21	± 0.43
3.7	249.8	-0.00	-0.10	± 0.43
6.6	74.7	-0.09	-0.47	± 0.98
8.0	67.2	-0.06	-0.18	± 0.98
10.0	66.2	-0.01	0.06	± 0.98
15.0	51.2	0.16	0.19	± 0.98
26.6	112.6	0.18	0.19	± 0.98
30.0	121.9	0.01	-0.00	± 0.98
35.0	121.3	-0.14	-0.16	± 0.98
40.0	102.3	-0.23	-0.24	± 0.98
50.0	61.5	0.07	-0.03	± 0.98
55.0	75.9	-0.05	-0.06	± 0.98
60.0	80.5	0.01	0.03	± 0.98
65.0	77.1	0.20	0.18	± 0.98
70.0	74.3	0.16	0.10	± 0.98
75.0	74.8	-0.05	-0.09	± 0.98
75.0	96.6	-0.06	-0.08	± 0.98
80.0	95.4	-0.18	-0.15	± 0.98
85.0	58.0	-0.07	-0.08	± 0.98
90.0	84.0	0.02	0.02	± 0.98
92.0	83.9	0.03	0.03	± 0.98
95.0	76.2	-0.02	-0.03	± 0.98
97.0	69.1	0.01	-0.02	± 0.98
100.0	66.9	0.09	0.09	± 0.98
105.0	67.2	-0.28	-0.22	± 0.98
110.0	78.1	0.17	0.10	± 0.98

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^B Linearization parameter uncertainty for maximum specified field strength.

Parameters of Probe: EUmmWV4 - SN:9438

Calibration Results for Modulation Response

UID	Communication System Name		A dB	B dB $\sqrt{\mu V}$	C	D dB	VR mV	Max dev.	Max Unc ^E k = 2
0	CW	X	0.00	0.00	1.00	0.00	133.2	±2.7%	±4.7%
		Y	0.00	0.00	1.00		61.3		
10352	Pulse Waveform (200Hz, 10%)	X	2.98	60.00	14.72	10.00	6.0	±1.1%	±9.6%
		Y	2.77	60.00	15.32		6.0		
10353	Pulse Waveform (200Hz, 20%)	X	2.21	60.67	13.80	6.99	12.0	±1.4%	±9.6%
		Y	1.87	60.00	14.35		12.0		
10354	Pulse Waveform (200Hz, 40%)	X	1.45	61.79	13.03	3.98	23.0	±1.6%	±9.6%
		Y	1.12	60.00	13.22		23.0		
10355	Pulse Waveform (200Hz, 60%)	X	0.72	60.00	11.69	2.22	27.0	±1.3%	±9.6%
		Y	0.76	60.00	12.23		27.0		
10387	QPSK Waveform, 1 MHz	X	1.18	60.00	12.45	1.00	22.0	±1.4%	±9.6%
		Y	1.27	60.00	12.16		22.0		
10388	QPSK Waveform, 10 MHz	X	1.23	60.00	12.24	0.00	22.0	±0.8%	±9.6%
		Y	1.42	60.00	11.94		22.0		
10396	64-QAM Waveform, 100 kHz	X	3.93	67.88	17.04	3.01	17.0	±0.6%	±9.6%
		Y	4.05	66.99	16.51		17.0		
10399	64-QAM Waveform, 40 MHz	X	2.04	60.00	12.62	0.00	19.0	±1.0%	±9.6%
		Y	2.15	60.00	12.52		19.0		
10414	WLAN CCDF, 64-QAM, 40 MHz	X	3.45	60.91	13.37	0.00	12.0	±1.0%	±9.6%
		Y	3.20	60.00	12.98		12.0		

Note: For details on UID parameters see Appendix

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

Parameters of Probe: EUmmWV4 - SN:9438

Calibration Results for Linearity Response

Frequency GHz	Target E-Field V/m	Deviation Sensor X dB	Deviation Sensor Y dB	Unc ($k = 2$) dB
0.9	50.0	-0.04	0.12	± 0.2
0.9	100.0	-0.04	0.11	± 0.2
0.9	500.0	-0.00	-0.01	± 0.2
0.9	1000.0	0.02	0.01	± 0.2
0.9	1500.0	0.01	0.01	± 0.2
0.9	2100.0	-0.01	-0.01	± 0.2

Sensor Frequency Model Parameters (750 MHz – 55 GHz)

	Sensor X	Sensor Y
R (Ω)	61.63	54.92
R _p (Ω)	85.63	74.47
L (nH)	0.06122	0.05106
C (pF)	0.2615	0.3793
C _p (pF)	0.0930	0.1117

Sensor Frequency Model Parameters (55 GHz – 110 GHz)

	Sensor X	Sensor Y
R (Ω)	26.95	24.14
R _p (Ω)	115.57	96.60
L (nH)	0.05930	0.04898
C (pF)	0.0797	0.1030
C _p (pF)	0.0932	0.1077

Sensor Model Parameters


	C1 fF	C2 fF	α V^{-1}	T1 $ms V^{-2}$	T2 $ms V^{-1}$	T3 ms	T4 V^{-2}	T5 V^{-1}	T6
x	56.4	408.25	33.61	2.66	7.90	4.98	0.00	1.77	1.01
y	49.2	352.24	32.96	0.92	7.43	5.01	2.00	2.00	1.01

Other Probe Parameters


Sensor Arrangement	Rectangular
Connector Angle	-136.3°
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	320 mm
Probe Body Diameter	8 mm
Tip Length	23 mm
Tip Diameter	8.0 mm
Probe Tip to Sensor X Calibration Point	1.5 mm
Probe Tip to Sensor Y Calibration Point	1.5 mm

Deviation from Isotropy in Air

30GHz: 3D isotropy, E-field parallel to probe axis



60GHz: 3D isotropy, E-field parallel to probe axis



Probe isotropy for E_{tot} : probe rotated $\phi = 0^\circ$ to 360° , tilted from field propagation direction $\vec{k}$

Parallel to the field propagation ($\psi = 0^\circ - 90^\circ$) at 30 GHz: deviation within ± 0.43 dB

Parallel to the field propagation ($\psi = 0^\circ - 90^\circ$) at 60 GHz: deviation within ± 0.41 dB

Appendix: Modulation Calibration Parameters

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E $k = 2$
0		CW	CW	0.00	±4.7
10010	CAB	SAR Validation (Square, 100 ms, 10 ms)	Test	10.00	±9.6
10011	CAC	UMTS-FDD (WCDMA)	WCDMA	2.91	±9.6
10012	CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps)	WLAN	1.87	±9.6
10013	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps)	WLAN	9.46	±9.6
10021	DAC	GSM-FDD (TDMA, GMSK)	GSM	9.39	±9.6
10023	DAC	GPRS-FDD (TDMA, GMSK, TN 0)	GSM	9.57	±9.6
10024	DAC	GPRS-FDD (TDMA, GMSK, TN 0-1)	GSM	6.56	±9.6
10025	DAC	EDGE-FDD (TDMA, 8PSK, TN 0)	GSM	12.62	±9.6
10026	DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1)	GSM	9.55	±9.6
10027	DAC	GPRS-FDD (TDMA, GMSK, TN 0-1-2)	GSM	4.80	±9.6
10028	DAC	GPRS-FDD (TDMA, GMSK, TN 0-1-2-3)	GSM	3.55	±9.6
10029	DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1-2)	GSM	7.78	±9.6
10030	CAA	IEEE 802.15.1 Bluetooth (GFSK, DH1)	Bluetooth	5.30	±9.6
10031	CAA	IEEE 802.15.1 Bluetooth (GFSK, DH3)	Bluetooth	1.87	±9.6
10032	CAA	IEEE 802.15.1 Bluetooth (GFSK, DH5)	Bluetooth	1.16	±9.6
10033	CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH1)	Bluetooth	7.74	±9.6
10034	CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH3)	Bluetooth	4.53	±9.6
10035	CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH5)	Bluetooth	3.83	±9.6
10036	CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH1)	Bluetooth	8.01	±9.6
10037	CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH3)	Bluetooth	4.77	±9.6
10038	CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH5)	Bluetooth	4.10	±9.6
10039	CAB	CDMA2000 (1xRTT, RC1)	CDMA2000	4.57	±9.6
10042	CAB	IS-54 / IS-136 FDD (TDMA/FDM, PI/4-DQPSK, Halfrate)	AMPS	7.78	±9.6
10044	CAA	IS-91/EIA/TIA-553 FDD (FDMA, FM)	AMPS	0.00	±9.6
10048	CAA	DECT (TDD, TDMA/FDM, GFSK, Full Slot, 24)	DECT	13.80	±9.6
10049	CAA	DECT (TDD, TDMA/FDM, GFSK, Double Slot, 12)	DECT	10.79	±9.6
10056	CAA	UMTS-TDD (TD-SCDMA, 1.28 Mcps)	TD-SCDMA	11.01	±9.6
10058	DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1-2-3)	GSM	6.52	±9.6
10059	CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps)	WLAN	2.12	±9.6
10060	CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps)	WLAN	2.83	±9.6
10061	CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps)	WLAN	3.60	±9.6
10062	CAE	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps)	WLAN	8.68	±9.6
10063	CAE	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps)	WLAN	8.63	±9.6
10064	CAE	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps)	WLAN	9.09	±9.6
10065	CAE	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps)	WLAN	9.00	±9.6
10066	CAE	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps)	WLAN	9.38	±9.6
10067	CAE	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps)	WLAN	10.12	±9.6
10068	CAE	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps)	WLAN	10.24	±9.6
10069	CAE	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps)	WLAN	10.56	±9.6
10071	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 9 Mbps)	WLAN	9.83	±9.6
10072	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 12 Mbps)	WLAN	9.62	±9.6
10073	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 18 Mbps)	WLAN	9.94	±9.6
10074	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 24 Mbps)	WLAN	10.30	±9.6
10075	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 36 Mbps)	WLAN	10.77	±9.6
10076	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 48 Mbps)	WLAN	10.94	±9.6
10077	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 54 Mbps)	WLAN	11.00	±9.6
10081	CAB	CDMA2000 (1xRTT, RC3)	CDMA2000	3.97	±9.6
10082	CAB	IS-54 / IS-136 FDD (TDMA/FDM, PI/4-DQPSK, Fullrate)	AMPS	4.77	±9.6
10090	DAC	GPRS-FDD (TDMA, GMSK, TN 0-4)	GSM	6.56	±9.6
10097	CAC	UMTS-FDD (HSDPA)	WCDMA	3.98	±9.6
10098	CAC	UMTS-FDD (HSUPA, Subtest 2)	WCDMA	3.98	±9.6
10099	DAC	EDGE-FDD (TDMA, 8PSK, TN 0-4)	GSM	9.55	±9.6
10100	CAF	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	LTE-FDD	5.67	±9.6
10101	CAF	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM)	LTE-FDD	6.42	±9.6
10102	CAF	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM)	LTE-FDD	6.60	±9.6
10103	CAH	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	LTE-TDD	9.29	±9.6
10104	CAH	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM)	LTE-TDD	9.97	±9.6
10105	CAH	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM)	LTE-TDD	10.01	±9.6
10108	CAH	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	LTE-FDD	5.80	±9.6
10109	CAH	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM)	LTE-FDD	6.43	±9.6
10110	CAH	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, QPSK)	LTE-FDD	5.75	±9.6
10111	CAH	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM)	LTE-FDD	6.44	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E $k = 2$
10112	CAH	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM)	LTE-FDD	6.59	±9.6
10113	CAH	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM)	LTE-FDD	6.62	±9.6
10114	CAE	IEEE 802.11n (HT Greenfield, 13.5 Mbps, BPSK)	WLAN	8.10	±9.6
10115	CAE	IEEE 802.11n (HT Greenfield, 81 Mbps, 16-QAM)	WLAN	8.46	±9.6
10116	CAE	IEEE 802.11n (HT Greenfield, 135 Mbps, 64-QAM)	WLAN	8.15	±9.6
10117	CAE	IEEE 802.11n (HT Mixed, 13.5 Mbps, BPSK)	WLAN	8.07	±9.6
10118	CAE	IEEE 802.11n (HT Mixed, 81 Mbps, 16-QAM)	WLAN	8.59	±9.6
10119	CAE	IEEE 802.11n (HT Mixed, 135 Mbps, 64-QAM)	WLAN	8.13	±9.6
10140	CAF	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM)	LTE-FDD	6.49	±9.6
10141	CAF	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM)	LTE-FDD	6.53	±9.6
10142	CAF	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, QPSK)	LTE-FDD	5.73	±9.6
10143	CAF	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM)	LTE-FDD	6.35	±9.6
10144	CAF	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM)	LTE-FDD	6.65	±9.6
10145	CAG	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK)	LTE-FDD	5.76	±9.6
10146	CAG	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM)	LTE-FDD	6.41	±9.6
10147	CAG	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM)	LTE-FDD	6.72	±9.6
10149	CAF	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM)	LTE-FDD	6.42	±9.6
10150	CAF	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM)	LTE-FDD	6.60	±9.6
10151	CAH	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	LTE-TDD	9.28	±9.6
10152	CAH	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM)	LTE-TDD	9.92	±9.6
10153	CAH	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM)	LTE-TDD	10.05	±9.6
10154	CAH	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	LTE-FDD	5.75	±9.6
10155	CAH	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM)	LTE-FDD	6.43	±9.6
10156	CAH	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, QPSK)	LTE-FDD	5.79	±9.6
10157	CAH	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM)	LTE-FDD	6.49	±9.6
10158	CAH	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM)	LTE-FDD	6.62	±9.6
10159	CAH	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM)	LTE-FDD	6.56	±9.6
10160	CAF	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, QPSK)	LTE-FDD	5.82	±9.6
10161	CAF	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM)	LTE-FDD	6.43	±9.6
10162	CAF	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM)	LTE-FDD	6.58	±9.6
10166	CAG	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK)	LTE-FDD	5.46	±9.6
10167	CAG	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM)	LTE-FDD	6.21	±9.6
10168	CAG	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM)	LTE-FDD	6.79	±9.6
10169	CAF	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	LTE-FDD	5.73	±9.6
10170	CAF	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)	LTE-FDD	6.52	±9.6
10171	AAF	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM)	LTE-FDD	6.49	±9.6
10172	CAH	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	LTE-TDD	9.21	±9.6
10173	CAH	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)	LTE-TDD	9.48	±9.6
10174	CAH	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM)	LTE-TDD	10.25	±9.6
10175	CAH	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	LTE-FDD	5.72	±9.6
10176	CAH	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM)	LTE-FDD	6.52	±9.6
10177	CAJ	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, QPSK)	LTE-FDD	5.73	±9.6
10178	CAH	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM)	LTE-FDD	6.52	±9.6
10179	CAH	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM)	LTE-FDD	6.50	±9.6
10180	CAH	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM)	LTE-FDD	6.50	±9.6
10181	CAF	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, QPSK)	LTE-FDD	5.72	±9.6
10182	CAF	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM)	LTE-FDD	6.52	±9.6
10183	AAE	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM)	LTE-FDD	6.50	±9.6
10184	CAF	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, QPSK)	LTE-FDD	5.73	±9.6
10185	CAF	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM)	LTE-FDD	6.51	±9.6
10186	AAF	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM)	LTE-FDD	6.50	±9.6
10187	CAG	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK)	LTE-FDD	5.73	±9.6
10188	CAG	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM)	LTE-FDD	6.52	±9.6
10189	AAG	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM)	LTE-FDD	6.50	±9.6
10193	CAE	IEEE 802.11n (HT Greenfield, 6.5 Mbps, BPSK)	WLAN	8.09	±9.6
10194	CAE	IEEE 802.11n (HT Greenfield, 39 Mbps, 16-QAM)	WLAN	8.12	±9.6
10195	CAE	IEEE 802.11n (HT Greenfield, 65 Mbps, 64-QAM)	WLAN	8.21	±9.6
10196	CAE	IEEE 802.11n (HT Mixed, 6.5 Mbps, BPSK)	WLAN	8.10	±9.6
10197	CAE	IEEE 802.11n (HT Mixed, 39 Mbps, 16-QAM)	WLAN	8.13	±9.6
10198	CAE	IEEE 802.11n (HT Mixed, 65 Mbps, 64-QAM)	WLAN	8.27	±9.6
10219	CAE	IEEE 802.11n (HT Mixed, 7.2 Mbps, BPSK)	WLAN	8.03	±9.6
10220	CAE	IEEE 802.11n (HT Mixed, 43.3 Mbps, 16-QAM)	WLAN	8.13	±9.6
10221	CAE	IEEE 802.11n (HT Mixed, 72.2 Mbps, 64-QAM)	WLAN	8.27	±9.6
10222	CAE	IEEE 802.11n (HT Mixed, 15 Mbps, BPSK)	WLAN	8.06	±9.6
10223	CAE	IEEE 802.11n (HT Mixed, 90 Mbps, 16-QAM)	WLAN	8.48	±9.6
10224	CAE	IEEE 802.11n (HT Mixed, 150 Mbps, 64-QAM)	WLAN	8.08	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E $k = 2$
10225	CAC	UMTS-FDD (HSPA+)	WCDMA	5.97	±9.6
10226	CAC	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM)	LTE-TDD	9.49	±9.6
10227	CAC	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM)	LTE-TDD	10.26	±9.6
10228	CAC	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK)	LTE-TDD	9.22	±9.6
10229	CAE	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM)	LTE-TDD	9.48	±9.6
10230	CAE	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM)	LTE-TDD	10.25	±9.6
10231	CAE	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, QPSK)	LTE-TDD	9.19	±9.6
10232	CAH	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM)	LTE-TDD	9.48	±9.6
10233	CAH	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM)	LTE-TDD	10.25	±9.6
10234	CAH	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK)	LTE-TDD	9.21	±9.6
10235	CAH	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM)	LTE-TDD	9.48	±9.6
10236	CAH	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM)	LTE-TDD	10.25	±9.6
10237	CAH	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	LTE-TDD	9.21	±9.6
10238	CAG	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM)	LTE-TDD	9.48	±9.6
10239	CAG	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM)	LTE-TDD	10.25	±9.6
10240	CAG	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, QPSK)	LTE-TDD	9.21	±9.6
10241	CAC	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM)	LTE-TDD	9.82	±9.6
10242	CAC	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM)	LTE-TDD	9.86	±9.6
10243	CAC	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK)	LTE-TDD	9.46	±9.6
10244	CAE	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)	LTE-TDD	10.06	±9.6
10245	CAE	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM)	LTE-TDD	10.06	±9.6
10246	CAE	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK)	LTE-TDD	9.30	±9.6
10247	CAH	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM)	LTE-TDD	9.91	±9.6
10248	CAH	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM)	LTE-TDD	10.09	±9.6
10249	CAH	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, QPSK)	LTE-TDD	9.29	±9.6
10250	CAH	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM)	LTE-TDD	9.81	±9.6
10251	CAH	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM)	LTE-TDD	10.17	±9.6
10252	CAH	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	LTE-TDD	9.24	±9.6
10253	CAG	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM)	LTE-TDD	9.90	±9.6
10254	CAG	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM)	LTE-TDD	10.14	±9.6
10255	CAG	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, QPSK)	LTE-TDD	9.20	±9.6
10256	CAC	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM)	LTE-TDD	9.96	±9.6
10257	CAC	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM)	LTE-TDD	10.08	±9.6
10258	CAC	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK)	LTE-TDD	9.34	±9.6
10259	CAE	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM)	LTE-TDD	9.98	±9.6
10260	CAE	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM)	LTE-TDD	9.97	±9.6
10261	CAE	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, QPSK)	LTE-TDD	9.24	±9.6
10262	CAH	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM)	LTE-TDD	9.83	±9.6
10263	CAH	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM)	LTE-TDD	10.16	±9.6
10264	CAH	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, QPSK)	LTE-TDD	9.23	±9.6
10265	CAH	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM)	LTE-TDD	9.92	±9.6
10266	CAH	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM)	LTE-TDD	10.07	±9.6
10267	CAH	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	LTE-TDD	9.30	±9.6
10268	CAG	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM)	LTE-TDD	10.06	±9.6
10269	CAG	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM)	LTE-TDD	10.13	±9.6
10270	CAG	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, QPSK)	LTE-TDD	9.58	±9.6
10274	CAC	UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.10)	WCDMA	4.87	±9.6
10275	CAC	UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.4)	WCDMA	3.96	±9.6
10277	CAA	PHS (QPSK)	PHS	11.81	±9.6
10278	CAA	PHS (QPSK, BW 884 MHz, Rolloff 0.5)	PHS	11.81	±9.6
10279	CAA	PHS (QPSK, BW 884 MHz, Rolloff 0.38)	PHS	12.18	±9.6
10290	AAB	CDMA2000, RC1, SO55, Full Rate	CDMA2000	3.91	±9.6
10291	AAB	CDMA2000, RC3, SO55, Full Rate	CDMA2000	3.46	±9.6
10292	AAB	CDMA2000, RC3, SO32, Full Rate	CDMA2000	3.39	±9.6
10293	AAB	CDMA2000, RC3, SO3, Full Rate	CDMA2000	3.50	±9.6
10295	AAB	CDMA2000, RC1, SO3, 1/8th Rate 25 fr.	CDMA2000	12.49	±9.6
10297	AAE	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	LTE-FDD	5.81	±9.6
10298	AAE	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, QPSK)	LTE-FDD	5.72	±9.6
10299	AAE	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)	LTE-FDD	6.39	±9.6
10300	AAE	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM)	LTE-FDD	6.60	±9.6
10301	AAA	IEEE 802.16e WiMAX (29:18, 5 ms, 10 MHz, QPSK, PUSC)	WiMAX	12.03	±9.6
10302	AAA	IEEE 802.16e WiMAX (29:18, 5 ms, 10 MHz, QPSK, PUSC, 3 CTRL symbols)	WiMAX	12.57	±9.6
10303	AAA	IEEE 802.16e WiMAX (31:15, 5 ms, 10 MHz, 64QAM, PUSC)	WiMAX	12.52	±9.6
10304	AAA	IEEE 802.16e WiMAX (29:18, 5 ms, 10 MHz, 64QAM, PUSC)	WiMAX	11.86	±9.6
10305	AAA	IEEE 802.16e WiMAX (31:15, 10 ms, 10 MHz, 64QAM, PUSC, 15 symbols)	WiMAX	15.24	±9.6
10306	AAA	IEEE 802.16e WiMAX (29:18, 10 ms, 10 MHz, 64QAM, PUSC, 18 symbols)	WiMAX	14.67	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E $k = 2$
10307	AAA	IEEE 802.16e WiMAX (29:18, 10 ms, 10 MHz, QPSK, PUSC, 18 symbols)	WiMAX	14.49	±9.6
10308	AAA	IEEE 802.16e WiMAX (29:18, 10 ms, 10 MHz, 16QAM, PUSC)	WiMAX	14.46	±9.6
10309	AAA	IEEE 802.16e WiMAX (29:18, 10 ms, 10 MHz, 16QAM, AMC 2x3, 18 symbols)	WiMAX	14.58	±9.6
10310	AAA	IEEE 802.16e WiMAX (29:18, 10 ms, 10 MHz, QPSK, AMC 2x3, 18 symbols)	WiMAX	14.57	±9.6
10311	AAE	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, QPSK)	LTE-FDD	6.06	±9.6
10313	AAA	iDEN 1:3	iDEN	10.51	±9.6
10314	AAA	iDEN 1:6	iDEN	13.48	±9.6
10315	AAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 96pc duty cycle)	WLAN	1.71	±9.6
10316	AAB	IEEE 802.11g WiFi 2.4 GHz (ERP-OFDM, 6 Mbps, 96pc duty cycle)	WLAN	8.36	±9.6
10317	AAE	IEEE 802.11a WiFi 5 GHz (OFDM, 6 Mbps, 96pc duty cycle)	WLAN	8.36	±9.6
10352	AAA	Pulse Waveform (200Hz, 10%)	Generic	10.00	±9.6
10353	AAA	Pulse Waveform (200Hz, 20%)	Generic	6.99	±9.6
10354	AAA	Pulse Waveform (200Hz, 40%)	Generic	3.98	±9.6
10355	AAA	Pulse Waveform (200Hz, 60%)	Generic	2.22	±9.6
10356	AAA	Pulse Waveform (200Hz, 80%)	Generic	0.97	±9.6
10387	AAA	QPSK Waveform, 1 MHz	Generic	5.10	±9.6
10388	AAA	QPSK Waveform, 10 MHz	Generic	5.22	±9.6
10396	AAA	64-QAM Waveform, 100 kHz	Generic	6.27	±9.6
10399	AAA	64-QAM Waveform, 40 MHz	Generic	6.27	±9.6
10400	AAF	IEEE 802.11ac WiFi (20 MHz, 64-QAM, 99pc duty cycle)	WLAN	8.37	±9.6
10401	AAF	IEEE 802.11ac WiFi (40 MHz, 64-QAM, 99pc duty cycle)	WLAN	8.60	±9.6
10402	AAF	IEEE 802.11ac WiFi (80 MHz, 64-QAM, 99pc duty cycle)	WLAN	8.53	±9.6
10403	AAB	CDMA2000 (1xEV-DO, Rev. 0)	CDMA2000	3.76	±9.6
10404	AAB	CDMA2000 (1xEV-DO, Rev. A)	CDMA2000	3.77	±9.6
10406	AAB	CDMA2000, RC3, SO32, SCH0, Full Rate	CDMA2000	5.22	±9.6
10410	AAH	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9, Subframe Conf=4)	LTE-TDD	7.82	±9.6
10414	AAA	WLAN CCDF, 64-QAM, 40 MHz	Generic	8.54	±9.6
10415	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 99pc duty cycle)	WLAN	1.54	±9.6
10416	AAA	IEEE 802.11g WiFi 2.4 GHz (ERP-OFDM, 6 Mbps, 99pc duty cycle)	WLAN	8.23	±9.6
10417	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps, 99pc duty cycle)	WLAN	8.23	±9.6
10418	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 99pc duty cycle, Long preamble)	WLAN	8.14	±9.6
10419	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 99pc duty cycle, Short preamble)	WLAN	8.19	±9.6
10422	AAD	IEEE 802.11n (HT Greenfield, 7.2 Mbps, BPSK)	WLAN	8.32	±9.6
10423	AAD	IEEE 802.11n (HT Greenfield, 43.3 Mbps, 16-QAM)	WLAN	8.47	±9.6
10424	AAD	IEEE 802.11n (HT Greenfield, 72.2 Mbps, 64-QAM)	WLAN	8.40	±9.6
10425	AAD	IEEE 802.11n (HT Greenfield, 15 Mbps, BPSK)	WLAN	8.41	±9.6
10426	AAD	IEEE 802.11n (HT Greenfield, 90 Mbps, 16-QAM)	WLAN	8.45	±9.6
10427	AAD	IEEE 802.11n (HT Greenfield, 150 Mbps, 64-QAM)	WLAN	8.41	±9.6
10430	AAE	LTE-FDD (OFDMA, 5 MHz, E-TM 3.1)	LTE-FDD	8.28	±9.6
10431	AAE	LTE-FDD (OFDMA, 10 MHz, E-TM 3.1)	LTE-FDD	8.38	±9.6
10432	AAD	LTE-FDD (OFDMA, 15 MHz, E-TM 3.1)	LTE-FDD	8.34	±9.6
10433	AAD	LTE-FDD (OFDMA, 20 MHz, E-TM 3.1)	LTE-FDD	8.34	±9.6
10434	AAB	W-CDMA (BS Test Model 1, 64 DPCH)	WCDMA	8.60	±9.6
10435	AAG	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.82	±9.6
10447	AAE	LTE-FDD (OFDMA, 5 MHz, E-TM 3.1, Clipping 44%)	LTE-FDD	7.56	±9.6
10448	AAE	LTE-FDD (OFDMA, 10 MHz, E-TM 3.1, Clipping 44%)	LTE-FDD	7.53	±9.6
10449	AAD	LTE-FDD (OFDMA, 15 MHz, E-TM 3.1, Clipping 44%)	LTE-FDD	7.51	±9.6
10450	AAD	LTE-FDD (OFDMA, 20 MHz, E-TM 3.1, Clipping 44%)	LTE-FDD	7.48	±9.6
10451	AAB	W-CDMA (BS Test Model 1, 64 DPCH, Clipping 44%)	WCDMA	7.59	±9.6
10453	AAE	Validation (Square, 10 ms, 1 ms)	Test	10.00	±9.6
10456	AAD	IEEE 802.11ac WiFi (160 MHz, 64-QAM, 99pc duty cycle)	WLAN	8.63	±9.6
10457	AAB	UMTS-FDD (DC-HSDPA)	WCDMA	6.62	±9.6
10458	AAA	CDMA2000 (1xEV-DO, Rev. B, 2 carriers)	CDMA2000	6.55	±9.6
10459	AAA	CDMA2000 (1xEV-DO, Rev. B, 3 carriers)	CDMA2000	8.25	±9.6
10460	AAB	UMTS-FDD (WCDMA, AMR)	WCDMA	2.39	±9.6
10461	AAC	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.82	±9.6
10462	AAC	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.30	±9.6
10463	AAC	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.56	±9.6
10464	AAD	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.82	±9.6
10465	AAD	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.32	±9.6
10466	AAD	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.57	±9.6
10467	AAG	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.82	±9.6
10468	AAG	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.32	±9.6
10469	AAG	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.56	±9.6
10470	AAG	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.82	±9.6
10471	AAG	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.32	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E k = 2
10472	AAG	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.57	±9.6
10473	AAF	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.82	±9.6
10474	AAF	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.32	±9.6
10475	AAF	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.57	±9.6
10477	AAG	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.32	±9.6
10478	AAG	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.57	±9.6
10479	AAC	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.74	±9.6
10480	AAC	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.18	±9.6
10481	AAC	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.45	±9.6
10482	AAD	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.71	±9.6
10483	AAD	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.39	±9.6
10484	AAD	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.47	±9.6
10485	AAG	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.59	±9.6
10486	AAG	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.38	±9.6
10487	AAG	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.60	±9.6
10488	AAG	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.70	±9.6
10489	AAG	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.31	±9.6
10490	AAG	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.54	±9.6
10491	AAF	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.74	±9.6
10492	AAF	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.41	±9.6
10493	AAF	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.55	±9.6
10494	AAG	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.74	±9.6
10495	AAG	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.37	±9.6
10496	AAG	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.54	±9.6
10497	AAC	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.67	±9.6
10498	AAC	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.40	±9.6
10499	AAC	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.68	±9.6
10500	AAD	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.67	±9.6
10501	AAD	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.44	±9.6
10502	AAD	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.52	±9.6
10503	AAG	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.72	±9.6
10504	AAG	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.31	±9.6
10505	AAG	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.54	±9.6
10506	AAG	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.74	±9.6
10507	AAG	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.36	±9.6
10508	AAG	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.55	±9.6
10509	AAF	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.99	±9.6
10510	AAF	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.49	±9.6
10511	AAF	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.51	±9.6
10512	AAG	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.74	±9.6
10513	AAG	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.42	±9.6
10514	AAG	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.45	±9.6
10515	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps, 99pc duty cycle)	WLAN	1.58	±9.6
10516	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps, 99pc duty cycle)	WLAN	1.57	±9.6
10517	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps, 99pc duty cycle)	WLAN	1.58	±9.6
10518	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps, 99pc duty cycle)	WLAN	8.23	±9.6
10519	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps, 99pc duty cycle)	WLAN	8.39	±9.6
10520	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps, 99pc duty cycle)	WLAN	8.12	±9.6
10521	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps, 99pc duty cycle)	WLAN	7.97	±9.6
10522	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps, 99pc duty cycle)	WLAN	8.45	±9.6
10523	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps, 99pc duty cycle)	WLAN	8.08	±9.6
10524	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps, 99pc duty cycle)	WLAN	8.27	±9.6
10525	AAD	IEEE 802.11ac WiFi (20 MHz, MCS0, 99pc duty cycle)	WLAN	8.36	±9.6
10526	AAD	IEEE 802.11ac WiFi (20 MHz, MCS1, 99pc duty cycle)	WLAN	8.42	±9.6
10527	AAD	IEEE 802.11ac WiFi (20 MHz, MCS2, 99pc duty cycle)	WLAN	8.21	±9.6
10528	AAD	IEEE 802.11ac WiFi (20 MHz, MCS3, 99pc duty cycle)	WLAN	8.36	±9.6
10529	AAD	IEEE 802.11ac WiFi (20 MHz, MCS4, 99pc duty cycle)	WLAN	8.36	±9.6
10531	AAD	IEEE 802.11ac WiFi (20 MHz, MCS6, 99pc duty cycle)	WLAN	8.43	±9.6
10532	AAD	IEEE 802.11ac WiFi (20 MHz, MCS7, 99pc duty cycle)	WLAN	8.29	±9.6
10533	AAD	IEEE 802.11ac WiFi (20 MHz, MCS8, 99pc duty cycle)	WLAN	8.38	±9.6
10534	AAD	IEEE 802.11ac WiFi (40 MHz, MCS0, 99pc duty cycle)	WLAN	8.45	±9.6
10535	AAD	IEEE 802.11ac WiFi (40 MHz, MCS1, 99pc duty cycle)	WLAN	8.45	±9.6
10536	AAD	IEEE 802.11ac WiFi (40 MHz, MCS2, 99pc duty cycle)	WLAN	8.32	±9.6
10537	AAD	IEEE 802.11ac WiFi (40 MHz, MCS3, 99pc duty cycle)	WLAN	8.44	±9.6
10538	AAD	IEEE 802.11ac WiFi (40 MHz, MCS4, 99pc duty cycle)	WLAN	8.54	±9.6
10540	AAD	IEEE 802.11ac WiFi (40 MHz, MCS6, 99pc duty cycle)	WLAN	8.39	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E $k = 2$
10541	AAD	IEEE 802.11ac WiFi (40 MHz, MCS7, 99pc duty cycle)	WLAN	8.46	±9.6
10542	AAD	IEEE 802.11ac WiFi (40 MHz, MCS8, 99pc duty cycle)	WLAN	8.65	±9.6
10543	AAD	IEEE 802.11ac WiFi (40 MHz, MCS9, 99pc duty cycle)	WLAN	8.65	±9.6
10544	AAD	IEEE 802.11ac WiFi (80 MHz, MCS0, 99pc duty cycle)	WLAN	8.47	±9.6
10545	AAD	IEEE 802.11ac WiFi (80 MHz, MCS1, 99pc duty cycle)	WLAN	8.55	±9.6
10546	AAD	IEEE 802.11ac WiFi (80 MHz, MCS2, 99pc duty cycle)	WLAN	8.35	±9.6
10547	AAD	IEEE 802.11ac WiFi (80 MHz, MCS3, 99pc duty cycle)	WLAN	8.49	±9.6
10548	AAD	IEEE 802.11ac WiFi (80 MHz, MCS4, 99pc duty cycle)	WLAN	8.37	±9.6
10550	AAD	IEEE 802.11ac WiFi (80 MHz, MCS6, 99pc duty cycle)	WLAN	8.38	±9.6
10551	AAD	IEEE 802.11ac WiFi (80 MHz, MCS7, 99pc duty cycle)	WLAN	8.50	±9.6
10552	AAD	IEEE 802.11ac WiFi (80 MHz, MCS8, 99pc duty cycle)	WLAN	8.42	±9.6
10553	AAD	IEEE 802.11ac WiFi (80 MHz, MCS9, 99pc duty cycle)	WLAN	8.45	±9.6
10554	AAE	IEEE 802.11ac WiFi (160 MHz, MCS0, 99pc duty cycle)	WLAN	8.48	±9.6
10555	AAE	IEEE 802.11ac WiFi (160 MHz, MCS1, 99pc duty cycle)	WLAN	8.47	±9.6
10556	AAE	IEEE 802.11ac WiFi (160 MHz, MCS2, 99pc duty cycle)	WLAN	8.50	±9.6
10557	AAE	IEEE 802.11ac WiFi (160 MHz, MCS3, 99pc duty cycle)	WLAN	8.52	±9.6
10558	AAE	IEEE 802.11ac WiFi (160 MHz, MCS4, 99pc duty cycle)	WLAN	8.61	±9.6
10560	AAE	IEEE 802.11ac WiFi (160 MHz, MCS6, 99pc duty cycle)	WLAN	8.73	±9.6
10561	AAE	IEEE 802.11ac WiFi (160 MHz, MCS7, 99pc duty cycle)	WLAN	8.56	±9.6
10562	AAE	IEEE 802.11ac WiFi (160 MHz, MCS8, 99pc duty cycle)	WLAN	8.69	±9.6
10563	AAE	IEEE 802.11ac WiFi (160 MHz, MCS9, 99pc duty cycle)	WLAN	8.77	±9.6
10564	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 9 Mbps, 99pc duty cycle)	WLAN	8.25	±9.6
10565	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 99pc duty cycle)	WLAN	8.45	±9.6
10566	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 99pc duty cycle)	WLAN	8.13	±9.6
10567	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 99pc duty cycle)	WLAN	8.00	±9.6
10568	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 99pc duty cycle)	WLAN	8.37	±9.6
10569	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 99pc duty cycle)	WLAN	8.10	±9.6
10570	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 54 Mbps, 99pc duty cycle)	WLAN	8.30	±9.6
10571	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 90pc duty cycle)	WLAN	1.99	±9.6
10572	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps, 90pc duty cycle)	WLAN	1.99	±9.6
10573	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps, 90pc duty cycle)	WLAN	1.98	±9.6
10574	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps, 90pc duty cycle)	WLAN	1.98	±9.6
10575	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 90pc duty cycle)	WLAN	8.59	±9.6
10576	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 9 Mbps, 90pc duty cycle)	WLAN	8.60	±9.6
10577	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 90pc duty cycle)	WLAN	8.70	±9.6
10578	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 90pc duty cycle)	WLAN	8.49	±9.6
10579	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 90pc duty cycle)	WLAN	8.36	±9.6
10580	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 90pc duty cycle)	WLAN	8.76	±9.6
10581	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 90pc duty cycle)	WLAN	8.35	±9.6
10582	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 54 Mbps, 90pc duty cycle)	WLAN	8.67	±9.6
10583	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps, 90pc duty cycle)	WLAN	8.59	±9.6
10584	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps, 90pc duty cycle)	WLAN	8.60	±9.6
10585	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps, 90pc duty cycle)	WLAN	8.70	±9.6
10586	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps, 90pc duty cycle)	WLAN	8.49	±9.6
10587	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps, 90pc duty cycle)	WLAN	8.36	±9.6
10588	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps, 90pc duty cycle)	WLAN	8.76	±9.6
10589	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps, 90pc duty cycle)	WLAN	8.35	±9.6
10590	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps, 90pc duty cycle)	WLAN	8.67	±9.6
10591	AAD	IEEE 802.11n (HT Mixed, 20 MHz, MCS0, 90pc duty cycle)	WLAN	8.63	±9.6
10592	AAD	IEEE 802.11n (HT Mixed, 20 MHz, MCS1, 90pc duty cycle)	WLAN	8.79	±9.6
10593	AAD	IEEE 802.11n (HT Mixed, 20 MHz, MCS2, 90pc duty cycle)	WLAN	8.64	±9.6
10594	AAD	IEEE 802.11n (HT Mixed, 20 MHz, MCS3, 90pc duty cycle)	WLAN	8.74	±9.6
10595	AAD	IEEE 802.11n (HT Mixed, 20 MHz, MCS4, 90pc duty cycle)	WLAN	8.74	±9.6
10596	AAD	IEEE 802.11n (HT Mixed, 20 MHz, MCS5, 90pc duty cycle)	WLAN	8.71	±9.6
10597	AAD	IEEE 802.11n (HT Mixed, 20 MHz, MCS6, 90pc duty cycle)	WLAN	8.72	±9.6
10598	AAD	IEEE 802.11n (HT Mixed, 20 MHz, MCS7, 90pc duty cycle)	WLAN	8.50	±9.6
10599	AAD	IEEE 802.11n (HT Mixed, 40 MHz, MCS0, 90pc duty cycle)	WLAN	8.79	±9.6
10600	AAD	IEEE 802.11n (HT Mixed, 40 MHz, MCS1, 90pc duty cycle)	WLAN	8.88	±9.6
10601	AAD	IEEE 802.11n (HT Mixed, 40 MHz, MCS2, 90pc duty cycle)	WLAN	8.82	±9.6
10602	AAD	IEEE 802.11n (HT Mixed, 40 MHz, MCS3, 90pc duty cycle)	WLAN	8.94	±9.6
10603	AAD	IEEE 802.11n (HT Mixed, 40 MHz, MCS4, 90pc duty cycle)	WLAN	9.03	±9.6
10604	AAD	IEEE 802.11n (HT Mixed, 40 MHz, MCS5, 90pc duty cycle)	WLAN	8.76	±9.6
10605	AAD	IEEE 802.11n (HT Mixed, 40 MHz, MCS6, 90pc duty cycle)	WLAN	8.97	±9.6
10606	AAD	IEEE 802.11n (HT Mixed, 40 MHz, MCS7, 90pc duty cycle)	WLAN	8.82	±9.6
10607	AAD	IEEE 802.11ac WiFi (20 MHz, MCS0, 90pc duty cycle)	WLAN	8.64	±9.6
10608	AAD	IEEE 802.11ac WiFi (20 MHz, MCS1, 90pc duty cycle)	WLAN	8.77	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E k = 2
10609	AAD	IEEE 802.11ac WiFi (20 MHz, MCS2, 90pc duty cycle)	WLAN	8.57	±9.6
10610	AAD	IEEE 802.11ac WiFi (20 MHz, MCS3, 90pc duty cycle)	WLAN	8.78	±9.6
10611	AAD	IEEE 802.11ac WiFi (20 MHz, MCS4, 90pc duty cycle)	WLAN	8.70	±9.6
10612	AAD	IEEE 802.11ac WiFi (20 MHz, MCS5, 90pc duty cycle)	WLAN	8.77	±9.6
10613	AAD	IEEE 802.11ac WiFi (20 MHz, MCS6, 90pc duty cycle)	WLAN	8.94	±9.6
10614	AAD	IEEE 802.11ac WiFi (20 MHz, MCS7, 90pc duty cycle)	WLAN	8.59	±9.6
10615	AAD	IEEE 802.11ac WiFi (20 MHz, MCS8, 90pc duty cycle)	WLAN	8.82	±9.6
10616	AAD	IEEE 802.11ac WiFi (40 MHz, MCS0, 90pc duty cycle)	WLAN	8.82	±9.6
10617	AAD	IEEE 802.11ac WiFi (40 MHz, MCS1, 90pc duty cycle)	WLAN	8.81	±9.6
10618	AAD	IEEE 802.11ac WiFi (40 MHz, MCS2, 90pc duty cycle)	WLAN	8.58	±9.6
10619	AAD	IEEE 802.11ac WiFi (40 MHz, MCS3, 90pc duty cycle)	WLAN	8.86	±9.6
10620	AAD	IEEE 802.11ac WiFi (40 MHz, MCS4, 90pc duty cycle)	WLAN	8.87	±9.6
10621	AAD	IEEE 802.11ac WiFi (40 MHz, MCS5, 90pc duty cycle)	WLAN	8.77	±9.6
10622	AAD	IEEE 802.11ac WiFi (40 MHz, MCS6, 90pc duty cycle)	WLAN	8.68	±9.6
10623	AAD	IEEE 802.11ac WiFi (40 MHz, MCS7, 90pc duty cycle)	WLAN	8.82	±9.6
10624	AAD	IEEE 802.11ac WiFi (40 MHz, MCS8, 90pc duty cycle)	WLAN	8.96	±9.6
10625	AAD	IEEE 802.11ac WiFi (40 MHz, MCS9, 90pc duty cycle)	WLAN	8.96	±9.6
10626	AAD	IEEE 802.11ac WiFi (80 MHz, MCS0, 90pc duty cycle)	WLAN	8.83	±9.6
10627	AAD	IEEE 802.11ac WiFi (80 MHz, MCS1, 90pc duty cycle)	WLAN	8.88	±9.6
10628	AAD	IEEE 802.11ac WiFi (80 MHz, MCS2, 90pc duty cycle)	WLAN	8.71	±9.6
10629	AAD	IEEE 802.11ac WiFi (80 MHz, MCS3, 90pc duty cycle)	WLAN	8.85	±9.6
10630	AAD	IEEE 802.11ac WiFi (80 MHz, MCS4, 90pc duty cycle)	WLAN	8.72	±9.6
10631	AAD	IEEE 802.11ac WiFi (80 MHz, MCS5, 90pc duty cycle)	WLAN	8.81	±9.6
10632	AAD	IEEE 802.11ac WiFi (80 MHz, MCS6, 90pc duty cycle)	WLAN	8.74	±9.6
10633	AAD	IEEE 802.11ac WiFi (80 MHz, MCS7, 90pc duty cycle)	WLAN	8.83	±9.6
10634	AAD	IEEE 802.11ac WiFi (80 MHz, MCS8, 90pc duty cycle)	WLAN	8.80	±9.6
10635	AAD	IEEE 802.11ac WiFi (80 MHz, MCS9, 90pc duty cycle)	WLAN	8.81	±9.6
10636	AAE	IEEE 802.11ac WiFi (160 MHz, MCS0, 90pc duty cycle)	WLAN	8.83	±9.6
10637	AAE	IEEE 802.11ac WiFi (160 MHz, MCS1, 90pc duty cycle)	WLAN	8.79	±9.6
10638	AAE	IEEE 802.11ac WiFi (160 MHz, MCS2, 90pc duty cycle)	WLAN	8.86	±9.6
10639	AAE	IEEE 802.11ac WiFi (160 MHz, MCS3, 90pc duty cycle)	WLAN	8.85	±9.6
10640	AAE	IEEE 802.11ac WiFi (160 MHz, MCS4, 90pc duty cycle)	WLAN	8.98	±9.6
10641	AAE	IEEE 802.11ac WiFi (160 MHz, MCS5, 90pc duty cycle)	WLAN	9.06	±9.6
10642	AAE	IEEE 802.11ac WiFi (160 MHz, MCS6, 90pc duty cycle)	WLAN	9.06	±9.6
10643	AAE	IEEE 802.11ac WiFi (160 MHz, MCS7, 90pc duty cycle)	WLAN	8.89	±9.6
10644	AAE	IEEE 802.11ac WiFi (160 MHz, MCS8, 90pc duty cycle)	WLAN	9.05	±9.6
10645	AAE	IEEE 802.11ac WiFi (160 MHz, MCS9, 90pc duty cycle)	WLAN	9.11	±9.6
10646	AAH	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe=2,7)	LTE-TDD	11.96	±9.6
10647	AAG	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK, UL Subframe=2,7)	LTE-TDD	11.96	±9.6
10648	AAA	CDMA2000 (1x Advanced)	CDMA2000	3.45	±9.6
10652	AAF	LTE-TDD (OFDMA, 5 MHz, E-TM 3.1, Clipping 44%)	LTE-TDD	6.91	±9.6
10653	AAF	LTE-TDD (OFDMA, 10 MHz, E-TM 3.1, Clipping 44%)	LTE-TDD	7.42	±9.6
10654	AAE	LTE-TDD (OFDMA, 15 MHz, E-TM 3.1, Clipping 44%)	LTE-TDD	6.96	±9.6
10655	AAF	LTE-TDD (OFDMA, 20 MHz, E-TM 3.1, Clipping 44%)	LTE-TDD	7.21	±9.6
10658	AAB	Pulse Waveform (200Hz, 10%)	Test	10.00	±9.6
10659	AAB	Pulse Waveform (200Hz, 20%)	Test	6.99	±9.6
10660	AAB	Pulse Waveform (200Hz, 40%)	Test	3.98	±9.6
10661	AAB	Pulse Waveform (200Hz, 60%)	Test	2.22	±9.6
10662	AAB	Pulse Waveform (200Hz, 80%)	Test	0.97	±9.6
10670	AAA	Bluetooth Low Energy	Bluetooth	2.19	±9.6
10671	AAC	IEEE 802.11ax (20 MHz, MCS0, 90pc duty cycle)	WLAN	9.09	±9.6
10672	AAC	IEEE 802.11ax (20 MHz, MCS1, 90pc duty cycle)	WLAN	8.57	±9.6
10673	AAC	IEEE 802.11ax (20 MHz, MCS2, 90pc duty cycle)	WLAN	8.78	±9.6
10674	AAC	IEEE 802.11ax (20 MHz, MCS3, 90pc duty cycle)	WLAN	8.74	±9.6
10675	AAC	IEEE 802.11ax (20 MHz, MCS4, 90pc duty cycle)	WLAN	8.90	±9.6
10676	AAC	IEEE 802.11ax (20 MHz, MCS5, 90pc duty cycle)	WLAN	8.77	±9.6
10677	AAC	IEEE 802.11ax (20 MHz, MCS6, 90pc duty cycle)	WLAN	8.73	±9.6
10678	AAC	IEEE 802.11ax (20 MHz, MCS7, 90pc duty cycle)	WLAN	8.78	±9.6
10679	AAC	IEEE 802.11ax (20 MHz, MCS8, 90pc duty cycle)	WLAN	8.89	±9.6
10680	AAC	IEEE 802.11ax (20 MHz, MCS9, 90pc duty cycle)	WLAN	8.80	±9.6
10681	AAC	IEEE 802.11ax (20 MHz, MCS10, 90pc duty cycle)	WLAN	8.62	±9.6
10682	AAC	IEEE 802.11ax (20 MHz, MCS11, 90pc duty cycle)	WLAN	8.83	±9.6
10683	AAC	IEEE 802.11ax (20 MHz, MCS0, 99pc duty cycle)	WLAN	8.42	±9.6
10684	AAC	IEEE 802.11ax (20 MHz, MCS1, 99pc duty cycle)	WLAN	8.26	±9.6
10685	AAC	IEEE 802.11ax (20 MHz, MCS2, 99pc duty cycle)	WLAN	8.33	±9.6
10686	AAC	IEEE 802.11ax (20 MHz, MCS3, 99pc duty cycle)	WLAN	8.28	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E $k = 2$
10687	AAC	IEEE 802.11ax (20 MHz, MCS4, 99pc duty cycle)	WLAN	8.45	±9.6
10688	AAC	IEEE 802.11ax (20 MHz, MCS5, 99pc duty cycle)	WLAN	8.29	±9.6
10689	AAC	IEEE 802.11ax (20 MHz, MCS6, 99pc duty cycle)	WLAN	8.55	±9.6
10690	AAC	IEEE 802.11ax (20 MHz, MCS7, 99pc duty cycle)	WLAN	8.29	±9.6
10691	AAC	IEEE 802.11ax (20 MHz, MCS8, 99pc duty cycle)	WLAN	8.25	±9.6
10692	AAC	IEEE 802.11ax (20 MHz, MCS9, 99pc duty cycle)	WLAN	8.29	±9.6
10693	AAC	IEEE 802.11ax (20 MHz, MCS10, 99pc duty cycle)	WLAN	8.25	±9.6
10694	AAC	IEEE 802.11ax (20 MHz, MCS11, 99pc duty cycle)	WLAN	8.57	±9.6
10695	AAC	IEEE 802.11ax (40 MHz, MCS0, 90pc duty cycle)	WLAN	8.78	±9.6
10696	AAC	IEEE 802.11ax (40 MHz, MCS1, 90pc duty cycle)	WLAN	8.91	±9.6
10697	AAC	IEEE 802.11ax (40 MHz, MCS2, 90pc duty cycle)	WLAN	8.61	±9.6
10698	AAC	IEEE 802.11ax (40 MHz, MCS3, 90pc duty cycle)	WLAN	8.89	±9.6
10699	AAC	IEEE 802.11ax (40 MHz, MCS4, 90pc duty cycle)	WLAN	8.82	±9.6
10700	AAC	IEEE 802.11ax (40 MHz, MCS5, 90pc duty cycle)	WLAN	8.73	±9.6
10701	AAC	IEEE 802.11ax (40 MHz, MCS6, 90pc duty cycle)	WLAN	8.86	±9.6
10702	AAC	IEEE 802.11ax (40 MHz, MCS7, 90pc duty cycle)	WLAN	8.70	±9.6
10703	AAC	IEEE 802.11ax (40 MHz, MCS8, 90pc duty cycle)	WLAN	8.82	±9.6
10704	AAC	IEEE 802.11ax (40 MHz, MCS9, 90pc duty cycle)	WLAN	8.56	±9.6
10705	AAC	IEEE 802.11ax (40 MHz, MCS10, 90pc duty cycle)	WLAN	8.69	±9.6
10706	AAC	IEEE 802.11ax (40 MHz, MCS11, 90pc duty cycle)	WLAN	8.66	±9.6
10707	AAC	IEEE 802.11ax (40 MHz, MCS0, 99pc duty cycle)	WLAN	8.32	±9.6
10708	AAC	IEEE 802.11ax (40 MHz, MCS1, 99pc duty cycle)	WLAN	8.55	±9.6
10709	AAC	IEEE 802.11ax (40 MHz, MCS2, 99pc duty cycle)	WLAN	8.33	±9.6
10710	AAC	IEEE 802.11ax (40 MHz, MCS3, 99pc duty cycle)	WLAN	8.29	±9.6
10711	AAC	IEEE 802.11ax (40 MHz, MCS4, 99pc duty cycle)	WLAN	8.39	±9.6
10712	AAC	IEEE 802.11ax (40 MHz, MCS5, 99pc duty cycle)	WLAN	8.67	±9.6
10713	AAC	IEEE 802.11ax (40 MHz, MCS6, 99pc duty cycle)	WLAN	8.33	±9.6
10714	AAC	IEEE 802.11ax (40 MHz, MCS7, 99pc duty cycle)	WLAN	8.26	±9.6
10715	AAC	IEEE 802.11ax (40 MHz, MCS8, 99pc duty cycle)	WLAN	8.45	±9.6
10716	AAC	IEEE 802.11ax (40 MHz, MCS9, 99pc duty cycle)	WLAN	8.30	±9.6
10717	AAC	IEEE 802.11ax (40 MHz, MCS10, 99pc duty cycle)	WLAN	8.48	±9.6
10718	AAC	IEEE 802.11ax (40 MHz, MCS11, 99pc duty cycle)	WLAN	8.24	±9.6
10719	AAC	IEEE 802.11ax (80 MHz, MCS0, 90pc duty cycle)	WLAN	8.81	±9.6
10720	AAC	IEEE 802.11ax (80 MHz, MCS1, 90pc duty cycle)	WLAN	8.87	±9.6
10721	AAC	IEEE 802.11ax (80 MHz, MCS2, 90pc duty cycle)	WLAN	8.76	±9.6
10722	AAC	IEEE 802.11ax (80 MHz, MCS3, 90pc duty cycle)	WLAN	8.55	±9.6
10723	AAC	IEEE 802.11ax (80 MHz, MCS4, 90pc duty cycle)	WLAN	8.70	±9.6
10724	AAC	IEEE 802.11ax (80 MHz, MCS5, 90pc duty cycle)	WLAN	8.90	±9.6
10725	AAC	IEEE 802.11ax (80 MHz, MCS6, 90pc duty cycle)	WLAN	8.74	±9.6
10726	AAC	IEEE 802.11ax (80 MHz, MCS7, 90pc duty cycle)	WLAN	8.72	±9.6
10727	AAC	IEEE 802.11ax (80 MHz, MCS8, 90pc duty cycle)	WLAN	8.66	±9.6
10728	AAC	IEEE 802.11ax (80 MHz, MCS9, 90pc duty cycle)	WLAN	8.65	±9.6
10729	AAC	IEEE 802.11ax (80 MHz, MCS10, 90pc duty cycle)	WLAN	8.64	±9.6
10730	AAC	IEEE 802.11ax (80 MHz, MCS11, 90pc duty cycle)	WLAN	8.67	±9.6
10731	AAC	IEEE 802.11ax (80 MHz, MCS0, 99pc duty cycle)	WLAN	8.42	±9.6
10732	AAC	IEEE 802.11ax (80 MHz, MCS1, 99pc duty cycle)	WLAN	8.46	±9.6
10733	AAC	IEEE 802.11ax (80 MHz, MCS2, 99pc duty cycle)	WLAN	8.40	±9.6
10734	AAC	IEEE 802.11ax (80 MHz, MCS3, 99pc duty cycle)	WLAN	8.25	±9.6
10735	AAC	IEEE 802.11ax (80 MHz, MCS4, 99pc duty cycle)	WLAN	8.33	±9.6
10736	AAC	IEEE 802.11ax (80 MHz, MCS5, 99pc duty cycle)	WLAN	8.27	±9.6
10737	AAC	IEEE 802.11ax (80 MHz, MCS6, 99pc duty cycle)	WLAN	8.36	±9.6
10738	AAC	IEEE 802.11ax (80 MHz, MCS7, 99pc duty cycle)	WLAN	8.42	±9.6
10739	AAC	IEEE 802.11ax (80 MHz, MCS8, 99pc duty cycle)	WLAN	8.29	±9.6
10740	AAC	IEEE 802.11ax (80 MHz, MCS9, 99pc duty cycle)	WLAN	8.48	±9.6
10741	AAC	IEEE 802.11ax (80 MHz, MCS10, 99pc duty cycle)	WLAN	8.40	±9.6
10742	AAC	IEEE 802.11ax (80 MHz, MCS11, 99pc duty cycle)	WLAN	8.43	±9.6
10743	AAC	IEEE 802.11ax (160 MHz, MCS0, 90pc duty cycle)	WLAN	8.94	±9.6
10744	AAC	IEEE 802.11ax (160 MHz, MCS1, 90pc duty cycle)	WLAN	9.16	±9.6
10745	AAC	IEEE 802.11ax (160 MHz, MCS2, 90pc duty cycle)	WLAN	8.93	±9.6
10746	AAC	IEEE 802.11ax (160 MHz, MCS3, 90pc duty cycle)	WLAN	9.11	±9.6
10747	AAC	IEEE 802.11ax (160 MHz, MCS4, 90pc duty cycle)	WLAN	9.04	±9.6
10748	AAC	IEEE 802.11ax (160 MHz, MCS5, 90pc duty cycle)	WLAN	8.93	±9.6
10749	AAC	IEEE 802.11ax (160 MHz, MCS6, 90pc duty cycle)	WLAN	8.90	±9.6
10750	AAC	IEEE 802.11ax (160 MHz, MCS7, 90pc duty cycle)	WLAN	8.79	±9.6
10751	AAC	IEEE 802.11ax (160 MHz, MCS8, 90pc duty cycle)	WLAN	8.82	±9.6
10752	AAC	IEEE 802.11ax (160 MHz, MCS9, 90pc duty cycle)	WLAN	8.81	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E $k = 2$
10753	AAC	IEEE 802.11ax (160 MHz, MCS10, 90pc duty cycle)	WLAN	9.00	±9.6
10754	AAC	IEEE 802.11ax (160 MHz, MCS11, 90pc duty cycle)	WLAN	8.94	±9.6
10755	AAC	IEEE 802.11ax (160 MHz, MCS0, 99pc duty cycle)	WLAN	8.64	±9.6
10756	AAC	IEEE 802.11ax (160 MHz, MCS1, 99pc duty cycle)	WLAN	8.77	±9.6
10757	AAC	IEEE 802.11ax (160 MHz, MCS2, 99pc duty cycle)	WLAN	8.77	±9.6
10758	AAC	IEEE 802.11ax (160 MHz, MCS3, 99pc duty cycle)	WLAN	8.69	±9.6
10759	AAC	IEEE 802.11ax (160 MHz, MCS4, 99pc duty cycle)	WLAN	8.58	±9.6
10760	AAC	IEEE 802.11ax (160 MHz, MCS5, 99pc duty cycle)	WLAN	8.49	±9.6
10761	AAC	IEEE 802.11ax (160 MHz, MCS6, 99pc duty cycle)	WLAN	8.58	±9.6
10762	AAC	IEEE 802.11ax (160 MHz, MCS7, 99pc duty cycle)	WLAN	8.49	±9.6
10763	AAC	IEEE 802.11ax (160 MHz, MCS8, 99pc duty cycle)	WLAN	8.53	±9.6
10764	AAC	IEEE 802.11ax (160 MHz, MCS9, 99pc duty cycle)	WLAN	8.54	±9.6
10765	AAC	IEEE 802.11ax (160 MHz, MCS10, 99pc duty cycle)	WLAN	8.54	±9.6
10766	AAC	IEEE 802.11ax (160 MHz, MCS11, 99pc duty cycle)	WLAN	8.51	±9.6
10767	AAG	5G NR (CP-OFDM, 1 RB, 5 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	7.99	±9.6
10768	AAE	5G NR (CP-OFDM, 1 RB, 10 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.01	±9.6
10769	AAD	5G NR (CP-OFDM, 1 RB, 15 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.01	±9.6
10770	AAE	5G NR (CP-OFDM, 1 RB, 20 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.02	±9.6
10771	AAD	5G NR (CP-OFDM, 1 RB, 25 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.02	±9.6
10772	AAE	5G NR (CP-OFDM, 1 RB, 30 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.23	±9.6
10773	AAF	5G NR (CP-OFDM, 1 RB, 40 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.03	±9.6
10774	AAE	5G NR (CP-OFDM, 1 RB, 50 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.02	±9.6
10775	AAF	5G NR (CP-OFDM, 50% RB, 5 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.31	±9.6
10776	AAE	5G NR (CP-OFDM, 50% RB, 10 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.30	±9.6
10777	AAC	5G NR (CP-OFDM, 50% RB, 15 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.30	±9.6
10778	AAE	5G NR (CP-OFDM, 50% RB, 20 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.34	±9.6
10779	AAC	5G NR (CP-OFDM, 50% RB, 25 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.42	±9.6
10780	AAE	5G NR (CP-OFDM, 50% RB, 30 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.38	±9.6
10781	AAF	5G NR (CP-OFDM, 50% RB, 40 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.38	±9.6
10782	AAE	5G NR (CP-OFDM, 50% RB, 50 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.43	±9.6
10783	AAG	5G NR (CP-OFDM, 100% RB, 5 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.31	±9.6
10784	AAE	5G NR (CP-OFDM, 100% RB, 10 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.29	±9.6
10785	AAD	5G NR (CP-OFDM, 100% RB, 15 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.40	±9.6
10786	AAE	5G NR (CP-OFDM, 100% RB, 20 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.35	±9.6
10787	AAD	5G NR (CP-OFDM, 100% RB, 25 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.44	±9.6
10788	AAE	5G NR (CP-OFDM, 100% RB, 30 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.39	±9.6
10789	AAF	5G NR (CP-OFDM, 100% RB, 40 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.37	±9.6
10790	AAE	5G NR (CP-OFDM, 100% RB, 50 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.39	±9.6
10791	AAG	5G NR (CP-OFDM, 1 RB, 5 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.83	±9.6
10792	AAE	5G NR (CP-OFDM, 1 RB, 10 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.92	±9.6
10793	AAD	5G NR (CP-OFDM, 1 RB, 15 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.95	±9.6
10794	AAE	5G NR (CP-OFDM, 1 RB, 20 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.82	±9.6
10795	AAD	5G NR (CP-OFDM, 1 RB, 25 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.84	±9.6
10796	AAE	5G NR (CP-OFDM, 1 RB, 30 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.82	±9.6
10797	AAF	5G NR (CP-OFDM, 1 RB, 40 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.01	±9.6
10798	AAE	5G NR (CP-OFDM, 1 RB, 50 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.89	±9.6
10799	AAF	5G NR (CP-OFDM, 1 RB, 60 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.93	±9.6
10801	AAF	5G NR (CP-OFDM, 1 RB, 80 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.89	±9.6
10802	AAE	5G NR (CP-OFDM, 1 RB, 90 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.87	±9.6
10803	AAF	5G NR (CP-OFDM, 1 RB, 100 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.93	±9.6
10805	AAE	5G NR (CP-OFDM, 50% RB, 10 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.34	±9.6
10806	AAD	5G NR (CP-OFDM, 50% RB, 15 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.37	±9.6
10809	AAE	5G NR (CP-OFDM, 50% RB, 30 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.34	±9.6
10810	AAF	5G NR (CP-OFDM, 50% RB, 40 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.34	±9.6
10812	AAF	5G NR (CP-OFDM, 50% RB, 60 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.35	±9.6
10817	AAG	5G NR (CP-OFDM, 100% RB, 5 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.35	±9.6
10818	AAE	5G NR (CP-OFDM, 100% RB, 10 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.34	±9.6
10819	AAD	5G NR (CP-OFDM, 100% RB, 15 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.33	±9.6
10820	AAE	5G NR (CP-OFDM, 100% RB, 20 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.30	±9.6
10821	AAD	5G NR (CP-OFDM, 100% RB, 25 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.41	±9.6
10822	AAE	5G NR (CP-OFDM, 100% RB, 30 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.41	±9.6
10823	AAF	5G NR (CP-OFDM, 100% RB, 40 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.36	±9.6
10824	AAE	5G NR (CP-OFDM, 100% RB, 50 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.39	±9.6
10825	AAF	5G NR (CP-OFDM, 100% RB, 60 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.41	±9.6
10827	AAF	5G NR (CP-OFDM, 100% RB, 80 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.42	±9.6
10828	AAE	5G NR (CP-OFDM, 100% RB, 90 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.43	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E $k = 2$
10829	AAF	5G NR (CP-OFDM, 100% RB, 100 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.40	±9.6
10830	AAE	5G NR (CP-OFDM, 1 RB, 10 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.63	±9.6
10831	AAD	5G NR (CP-OFDM, 1 RB, 15 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.73	±9.6
10832	AAE	5G NR (CP-OFDM, 1 RB, 20 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.74	±9.6
10833	AAD	5G NR (CP-OFDM, 1 RB, 25 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.70	±9.6
10834	AAE	5G NR (CP-OFDM, 1 RB, 30 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.75	±9.6
10835	AAF	5G NR (CP-OFDM, 1 RB, 40 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.70	±9.6
10836	AAE	5G NR (CP-OFDM, 1 RB, 50 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.66	±9.6
10837	AAF	5G NR (CP-OFDM, 1 RB, 60 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.68	±9.6
10839	AAF	5G NR (CP-OFDM, 1 RB, 80 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.70	±9.6
10840	AAE	5G NR (CP-OFDM, 1 RB, 90 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.67	±9.6
10841	AAF	5G NR (CP-OFDM, 1 RB, 100 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.71	±9.6
10843	AAD	5G NR (CP-OFDM, 50% RB, 15 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.49	±9.6
10844	AAE	5G NR (CP-OFDM, 50% RB, 20 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.34	±9.6
10846	AAE	5G NR (CP-OFDM, 50% RB, 30 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.41	±9.6
10854	AAE	5G NR (CP-OFDM, 100% RB, 10 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.34	±9.6
10855	AAD	5G NR (CP-OFDM, 100% RB, 15 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.36	±9.6
10856	AAE	5G NR (CP-OFDM, 100% RB, 20 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.37	±9.6
10857	AAD	5G NR (CP-OFDM, 100% RB, 25 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.35	±9.6
10858	AAE	5G NR (CP-OFDM, 100% RB, 30 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.36	±9.6
10859	AAF	5G NR (CP-OFDM, 100% RB, 40 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.34	±9.6
10860	AAE	5G NR (CP-OFDM, 100% RB, 50 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.41	±9.6
10861	AAF	5G NR (CP-OFDM, 100% RB, 60 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.40	±9.6
10863	AAF	5G NR (CP-OFDM, 100% RB, 80 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.41	±9.6
10864	AAE	5G NR (CP-OFDM, 100% RB, 90 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.37	±9.6
10865	AAF	5G NR (CP-OFDM, 100% RB, 100 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.41	±9.6
10866	AAF	5G NR (DFT-s-OFDM, 1 RB, 100 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	±9.6
10868	AAF	5G NR (DFT-s-OFDM, 100% RB, 100 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.89	±9.6
10869	AAE	5G NR (DFT-s-OFDM, 1 RB, 100 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	5.75	±9.6
10870	AAE	5G NR (DFT-s-OFDM, 100% RB, 100 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	5.86	±9.6
10871	AAE	5G NR (DFT-s-OFDM, 1 RB, 100 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	5.75	±9.6
10872	AAE	5G NR (DFT-s-OFDM, 100% RB, 100 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	6.52	±9.6
10873	AAE	5G NR (DFT-s-OFDM, 1 RB, 100 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	6.61	±9.6
10874	AAE	5G NR (DFT-s-OFDM, 100% RB, 100 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	6.65	±9.6
10875	AAE	5G NR (CP-OFDM, 1 RB, 100 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	7.78	±9.6
10876	AAE	5G NR (CP-OFDM, 100% RB, 100 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	8.39	±9.6
10877	AAE	5G NR (CP-OFDM, 1 RB, 100 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	7.95	±9.6
10878	AAE	5G NR (CP-OFDM, 100% RB, 100 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	8.41	±9.6
10879	AAE	5G NR (CP-OFDM, 1 RB, 100 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	8.12	±9.6
10880	AAE	5G NR (CP-OFDM, 100% RB, 100 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	8.38	±9.6
10881	AAE	5G NR (DFT-s-OFDM, 1 RB, 50 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	5.75	±9.6
10882	AAE	5G NR (DFT-s-OFDM, 100% RB, 50 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	5.96	±9.6
10883	AAE	5G NR (DFT-s-OFDM, 1 RB, 50 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	6.57	±9.6
10884	AAE	5G NR (DFT-s-OFDM, 100% RB, 50 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	6.53	±9.6
10885	AAE	5G NR (DFT-s-OFDM, 1 RB, 50 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	6.61	±9.6
10886	AAE	5G NR (DFT-s-OFDM, 100% RB, 50 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	6.65	±9.6
10887	AAE	5G NR (CP-OFDM, 1 RB, 50 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	7.78	±9.6
10888	AAE	5G NR (CP-OFDM, 100% RB, 50 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	8.35	±9.6
10889	AAE	5G NR (CP-OFDM, 1 RB, 50 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	8.02	±9.6
10890	AAE	5G NR (CP-OFDM, 100% RB, 50 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	8.40	±9.6
10891	AAE	5G NR (CP-OFDM, 1 RB, 50 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	8.13	±9.6
10892	AAE	5G NR (CP-OFDM, 100% RB, 50 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	8.41	±9.6
10897	AAE	5G NR (DFT-s-OFDM, 1 RB, 5 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.66	±9.6
10898	AAC	5G NR (DFT-s-OFDM, 1 RB, 10 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.67	±9.6
10899	AAB	5G NR (DFT-s-OFDM, 1 RB, 15 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.67	±9.6
10900	AAC	5G NR (DFT-s-OFDM, 1 RB, 20 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	±9.6
10901	AAB	5G NR (DFT-s-OFDM, 1 RB, 25 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	±9.6
10902	AAC	5G NR (DFT-s-OFDM, 1 RB, 30 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	±9.6
10903	AAD	5G NR (DFT-s-OFDM, 1 RB, 40 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	±9.6
10904	AAC	5G NR (DFT-s-OFDM, 1 RB, 50 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	±9.6
10905	AAD	5G NR (DFT-s-OFDM, 1 RB, 60 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	±9.6
10906	AAD	5G NR (DFT-s-OFDM, 1 RB, 80 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	±9.6
10907	AAE	5G NR (DFT-s-OFDM, 50% RB, 5 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.78	±9.6
10908	AAC	5G NR (DFT-s-OFDM, 50% RB, 10 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.93	±9.6
10909	AAB	5G NR (DFT-s-OFDM, 50% RB, 15 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.96	±9.6
10910	AAC	5G NR (DFT-s-OFDM, 50% RB, 20 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.83	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E $k = 2$
10911	AAB	5G NR (DFT-s-OFDM, 50% RB, 25 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.93	±9.6
10912	AAC	5G NR (DFT-s-OFDM, 50% RB, 30 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.84	±9.6
10913	AAD	5G NR (DFT-s-OFDM, 50% RB, 40 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.84	±9.6
10914	AAC	5G NR (DFT-s-OFDM, 50% RB, 50 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.85	±9.6
10915	AAD	5G NR (DFT-s-OFDM, 50% RB, 60 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.83	±9.6
10916	AAD	5G NR (DFT-s-OFDM, 50% RB, 80 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.87	±9.6
10917	AAD	5G NR (DFT-s-OFDM, 50% RB, 100 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.94	±9.6
10918	AAE	5G NR (DFT-s-OFDM, 100% RB, 5 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.86	±9.6
10919	AAC	5G NR (DFT-s-OFDM, 100% RB, 10 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.86	±9.6
10920	AAB	5G NR (DFT-s-OFDM, 100% RB, 15 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.87	±9.6
10921	AAC	5G NR (DFT-s-OFDM, 100% RB, 20 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.84	±9.6
10922	AAB	5G NR (DFT-s-OFDM, 100% RB, 25 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.82	±9.6
10923	AAC	5G NR (DFT-s-OFDM, 100% RB, 30 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.84	±9.6
10924	AAD	5G NR (DFT-s-OFDM, 100% RB, 40 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.84	±9.6
10925	AAC	5G NR (DFT-s-OFDM, 100% RB, 50 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.95	±9.6
10926	AAD	5G NR (DFT-s-OFDM, 100% RB, 60 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.84	±9.6
10927	AAD	5G NR (DFT-s-OFDM, 100% RB, 80 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.94	±9.6
10928	AAD	5G NR (DFT-s-OFDM, 1 RB, 5 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.52	±9.6
10929	AAD	5G NR (DFT-s-OFDM, 1 RB, 10 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.52	±9.6
10930	AAC	5G NR (DFT-s-OFDM, 1 RB, 15 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.52	±9.6
10931	AAC	5G NR (DFT-s-OFDM, 1 RB, 20 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.51	±9.6
10932	AAC	5G NR (DFT-s-OFDM, 1 RB, 25 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.51	±9.6
10933	AAC	5G NR (DFT-s-OFDM, 1 RB, 30 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.51	±9.6
10934	AAC	5G NR (DFT-s-OFDM, 1 RB, 40 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.51	±9.6
10935	AAD	5G NR (DFT-s-OFDM, 1 RB, 50 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.51	±9.6
10936	AAD	5G NR (DFT-s-OFDM, 50% RB, 5 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.90	±9.6
10937	AAD	5G NR (DFT-s-OFDM, 50% RB, 10 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.77	±9.6
10938	AAC	5G NR (DFT-s-OFDM, 50% RB, 15 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.90	±9.6
10939	AAC	5G NR (DFT-s-OFDM, 50% RB, 20 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.82	±9.6
10940	AAC	5G NR (DFT-s-OFDM, 50% RB, 25 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.89	±9.6
10941	AAC	5G NR (DFT-s-OFDM, 50% RB, 30 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.83	±9.6
10942	AAC	5G NR (DFT-s-OFDM, 50% RB, 40 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.85	±9.6
10943	AAD	5G NR (DFT-s-OFDM, 50% RB, 50 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.95	±9.6
10944	AAD	5G NR (DFT-s-OFDM, 100% RB, 5 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.81	±9.6
10945	AAD	5G NR (DFT-s-OFDM, 100% RB, 10 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.85	±9.6
10946	AAC	5G NR (DFT-s-OFDM, 100% RB, 15 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.83	±9.6
10947	AAC	5G NR (DFT-s-OFDM, 100% RB, 20 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.87	±9.6
10948	AAC	5G NR (DFT-s-OFDM, 100% RB, 25 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.94	±9.6
10949	AAC	5G NR (DFT-s-OFDM, 100% RB, 30 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.87	±9.6
10950	AAC	5G NR (DFT-s-OFDM, 100% RB, 40 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.94	±9.6
10951	AAD	5G NR (DFT-s-OFDM, 100% RB, 50 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.92	±9.6
10952	AAA	5G NR DL (CP-OFDM, TM 3.1, 5 MHz, 64-QAM, 15 kHz)	5G NR FR1 FDD	8.25	±9.6
10953	AAA	5G NR DL (CP-OFDM, TM 3.1, 10 MHz, 64-QAM, 15 kHz)	5G NR FR1 FDD	8.15	±9.6
10954	AAA	5G NR DL (CP-OFDM, TM 3.1, 15 MHz, 64-QAM, 15 kHz)	5G NR FR1 FDD	8.23	±9.6
10955	AAA	5G NR DL (CP-OFDM, TM 3.1, 20 MHz, 64-QAM, 15 kHz)	5G NR FR1 FDD	8.42	±9.6
10956	AAA	5G NR DL (CP-OFDM, TM 3.1, 5 MHz, 64-QAM, 30 kHz)	5G NR FR1 FDD	8.14	±9.6
10957	AAA	5G NR DL (CP-OFDM, TM 3.1, 10 MHz, 64-QAM, 30 kHz)	5G NR FR1 FDD	8.31	±9.6
10958	AAA	5G NR DL (CP-OFDM, TM 3.1, 15 MHz, 64-QAM, 30 kHz)	5G NR FR1 FDD	8.61	±9.6
10959	AAA	5G NR DL (CP-OFDM, TM 3.1, 20 MHz, 64-QAM, 30 kHz)	5G NR FR1 FDD	8.33	±9.6
10960	AAE	5G NR DL (CP-OFDM, TM 3.1, 5 MHz, 64-QAM, 15 kHz)	5G NR FR1 TDD	9.32	±9.6
10961	AAC	5G NR DL (CP-OFDM, TM 3.1, 10 MHz, 64-QAM, 15 kHz)	5G NR FR1 TDD	9.36	±9.6
10962	AAB	5G NR DL (CP-OFDM, TM 3.1, 15 MHz, 64-QAM, 15 kHz)	5G NR FR1 TDD	9.40	±9.6
10963	AAC	5G NR DL (CP-OFDM, TM 3.1, 20 MHz, 64-QAM, 15 kHz)	5G NR FR1 TDD	9.55	±9.6
10964	AAE	5G NR DL (CP-OFDM, TM 3.1, 5 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.29	±9.6
10965	AAC	5G NR DL (CP-OFDM, TM 3.1, 10 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.37	±9.6
10966	AAB	5G NR DL (CP-OFDM, TM 3.1, 15 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.55	±9.6
10967	AAC	5G NR DL (CP-OFDM, TM 3.1, 20 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.42	±9.6
10968	AAD	5G NR DL (CP-OFDM, TM 3.1, 100 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.49	±9.6
10972	AAC	5G NR (CP-OFDM, 1 RB, 20 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	11.59	±9.6
10973	AAD	5G NR (DFT-s-OFDM, 1 RB, 100 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	9.06	±9.6
10974	AAD	5G NR (CP-OFDM, 100% RB, 100 MHz, 256-QAM, 30 kHz)	5G NR FR1 TDD	10.28	±9.6
10978	AAA	ULLA BDR	ULLA	1.16	±9.6
10979	AAA	ULLA HDR4	ULLA	8.58	±9.6
10980	AAA	ULLA HDR8	ULLA	10.32	±9.6
10981	AAA	ULLA HDRp4	ULLA	3.19	±9.6
10982	AAA	ULLA HDRp8	ULLA	3.43	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E $k = 2$
10983	AAC	5G NR DL (CP-OFDM, TM 3.1, 40 MHz, 64-QAM, 15 kHz)	5G NR FR1 TDD	9.31	±9.6
10984	AAB	5G NR DL (CP-OFDM, TM 3.1, 50 MHz, 64-QAM, 15 kHz)	5G NR FR1 TDD	9.42	±9.6
10985	AAC	5G NR DL (CP-OFDM, TM 3.1, 40 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.54	±9.6
10986	AAB	5G NR DL (CP-OFDM, TM 3.1, 50 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.50	±9.6
10987	AAC	5G NR DL (CP-OFDM, TM 3.1, 60 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.53	±9.6
10988	AAB	5G NR DL (CP-OFDM, TM 3.1, 70 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.38	±9.6
10989	AAC	5G NR DL (CP-OFDM, TM 3.1, 80 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.33	±9.6
10990	AAB	5G NR DL (CP-OFDM, TM 3.1, 90 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.52	±9.6
11003	AAA	5G NR DL (CP-OFDM, TM 3.1, 30 MHz, 64-QAM, 15 kHz)	5G NR FR1 TDD	10.24	±9.6
11004	AAA	5G NR DL (CP-OFDM, TM 3.1, 30 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	10.73	±9.6
11005	AAA	5G NR DL (CP-OFDM, TM 3.1, 25 MHz, 64-QAM, 15 kHz)	5G NR FR1 FDD	8.70	±9.6
11006	AAA	5G NR DL (CP-OFDM, TM 3.1, 30 MHz, 64-QAM, 15 kHz)	5G NR FR1 FDD	8.55	±9.6
11007	AAA	5G NR DL (CP-OFDM, TM 3.1, 40 MHz, 64-QAM, 15 kHz)	5G NR FR1 FDD	8.46	±9.6
11008	AAA	5G NR DL (CP-OFDM, TM 3.1, 50 MHz, 64-QAM, 15 kHz)	5G NR FR1 FDD	8.51	±9.6
11009	AAA	5G NR DL (CP-OFDM, TM 3.1, 25 MHz, 64-QAM, 30 kHz)	5G NR FR1 FDD	8.76	±9.6
11010	AAA	5G NR DL (CP-OFDM, TM 3.1, 30 MHz, 64-QAM, 30 kHz)	5G NR FR1 FDD	8.95	±9.6
11011	AAA	5G NR DL (CP-OFDM, TM 3.1, 40 MHz, 64-QAM, 30 kHz)	5G NR FR1 FDD	8.96	±9.6
11012	AAA	5G NR DL (CP-OFDM, TM 3.1, 50 MHz, 64-QAM, 30 kHz)	5G NR FR1 FDD	8.68	±9.6
11013	AAB	IEEE 802.11be (320 MHz, MCS1, 99pc duty cycle)	WLAN	8.47	±9.6
11014	AAB	IEEE 802.11be (320 MHz, MCS2, 99pc duty cycle)	WLAN	8.45	±9.6
11015	AAB	IEEE 802.11be (320 MHz, MCS3, 99pc duty cycle)	WLAN	8.44	±9.6
11016	AAB	IEEE 802.11be (320 MHz, MCS4, 99pc duty cycle)	WLAN	8.44	±9.6
11017	AAB	IEEE 802.11be (320 MHz, MCS5, 99pc duty cycle)	WLAN	8.41	±9.6
11018	AAB	IEEE 802.11be (320 MHz, MCS6, 99pc duty cycle)	WLAN	8.40	±9.6
11019	AAB	IEEE 802.11be (320 MHz, MCS7, 99pc duty cycle)	WLAN	8.29	±9.6
11020	AAB	IEEE 802.11be (320 MHz, MCS8, 99pc duty cycle)	WLAN	8.27	±9.6
11021	AAB	IEEE 802.11be (320 MHz, MCS9, 99pc duty cycle)	WLAN	8.46	±9.6
11022	AAB	IEEE 802.11be (320 MHz, MCS10, 99pc duty cycle)	WLAN	8.36	±9.6
11023	AAB	IEEE 802.11be (320 MHz, MCS11, 99pc duty cycle)	WLAN	8.09	±9.6
11024	AAB	IEEE 802.11be (320 MHz, MCS12, 99pc duty cycle)	WLAN	8.42	±9.6
11025	AAB	IEEE 802.11be (320 MHz, MCS13, 99pc duty cycle)	WLAN	8.37	±9.6
11026	AAB	IEEE 802.11be (320 MHz, MCS0, 99pc duty cycle)	WLAN	8.39	±9.6

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.