

TEST REPORT

EUT Description	WLAN and BT, 2x2 PCIe M.2 1216 adapter card
Brand Name	Intel®
Model Name	BE201D2WP
FCC/IC ID	PD2BE201D2P / 1000M-BE201D2P
Date of Test Start/End	2024-05-27 / 2024-07-04
Features	2x2 Wi-Fi - Bluetooth® (see section 5)

Applicant	Intel Corporation SAS
Address	425 Rue de Goa – Le Cargo B6 – 06600 Antibes, FRANCE
Contact Person	Benjamin Lavenant
Telephone/Fax/ Email	Benjamin.lavenant@intel.com

Reference Standards	FCC CFR Title 47 Part 15 E RSS-247 issue 3, RSS-Gen A1 issue 5 - A1 (see section 0)
---------------------	---

Test Report identification	240521-02.TR17
Revision Control	Rev. 00 This test report revision replaces any previous test report revision (see section 1)

The test results relate only to the samples tested.
Reference to accreditation shall be used only by full reproduction of test report.

Issued by _____ Reviewed by _____

Cedric REQUIN
(Test Engineer Lead)

Zayd OUACHICHA
(Technical Manager)

Intel Corporation S.A.S – WRF Lab
425 rue de Goa – Le Cargo B6 - 06600, Antibes, France
Tel. +33493001400 / Fax +33493001401

Table of Contents

1.	Standards, reference documents and applicable test methods	3
2.	General conditions, competences and guarantees.....	3
3.	Environmental Conditions.....	3
4.	Test samples.....	4
5.	EUT Features	5
6.	Remarks and comments.....	5
7.	Test Verdicts summary.....	6
7.1.	802.11 A/N/AC/AX/BE – U-NII-2C	6
8.	Document Revision History	6
Annex A.	Test & System Description.....	7
A.1	MEASUREMENT SYSTEM.....	7
A.2	TEST EQUIPMENT LIST	9
A.3	MEASUREMENT UNCERTAINTY EVALUATION	10
Annex B.	Test Results U-NII-2C	11
B.1	TEST CONDITIONS.....	11
B.2	TEST RESULTS TABLES	12
B.2.1	26dB & 99% Bandwidth	12
B.2.2	Power Limits. Maximum Output power & Maximum power spectral Density	16
B.2.3	Undesirable emission limits : out of band (Conducted).....	26
B.2.4	Radiated spurious emission.....	27
B.3	TEST RESULTS SCREENSHOTS	55
B.3.1	26dB & 99% Bandwidth	55
B.3.2	Maximum Output Power & Maximum power spectral Density	57
B.3.3	Undesirable emission limits : out of band (Conducted).....	59
Annex C.	Photographs	77
C.1	TEST SETUP	77
C.2	TEST SAMPLE	79

1. Standards, reference documents and applicable test methods

FCC	1. FCC Title 47 CFR part 15 – Subpart E – Unlicensed National Information Infrastructure Devices. 2023-10-01 Edition 2. FCC Title 47 CFR part 15 - Subpart C – §15.209 Radiated emission limits; general requirements. 2023-10-01 Edition 3. FCC OET KDB 789033 D02 v02r01 - General U-NII Test Procedures New Rules – Guidelines for compliance testing of Unlicensed National Information Infrastructure (U-NII) Devices (Part 15, Subpart E) 4. FCC OET KDB 662911 D01 v02r01 - Emissions Testing of Transmitters with Multiple Outputs in the Same Band. 5. ANSI C63.10-2020 American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.
ISED	1. RSS-Gen Issue 5 Amendment 1 - General Requirements for Compliance of Radio Apparatus. 2. RSS-247 Issue 3 - Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and License-Exempt Local Area Network (LE-LAN) Devices. 3. FCC OET KDB 789033 D02 v02r01 - General U-NII Test Procedures New Rules – Guidelines for compliance testing of Unlicensed National Information Infrastructure (U-NII) Devices (Part 15, Subpart E) 4. FCC OET KDB 662911 D01 v02r01 - Emissions Testing of Transmitters with Multiple Outputs in the Same Band. 5. ANSI C63.10-2020 American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

2. General conditions, competences and guarantees.

- ✓ Tests performed under FCC standards identified in section 1 are covered by A2LA accreditation.
- ✓ Tests performed under ISED standards identified in section 1 are covered by Cofrac accreditation.
- ✓ Intel Corporation SAS Wireless RF Lab (Intel WRF Lab) is an ISO/IEC 17025:2017 laboratory accredited by the American Association for Laboratory Accreditation (A2LA) with the certificate number 3478.01.
- ✓ Intel Corporation SAS Wireless RF Lab (Intel WRF Lab) is an Accredited Test Firm recognized by the FCC, with Designation Number FR0011.
- ✓ Intel Corporation SAS Wireless RF Lab (Intel WRF Lab) is an ISO/IEC 17025:2017 testing laboratory accredited by the French Committee for Accreditation (Cofrac) with the certificate number 1-6736.
- ✓ Intel Corporation SAS Wireless RF Lab (Intel WRF Lab) is a Registered Test Site listed by ISED, with ISED #1000Y and CAB identifier FR0005.
- ✓ Intel WRF Lab only provides testing services and is committed to providing reliable, unbiased test results and interpretations.
- ✓ Intel WRF Lab is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.
- ✓ Intel WRF Lab has developed calibration and proficiency programs for its measurement equipment to ensure correlated and reliable results to its customers.
- ✓ This report is only referred to the item that has undergone the test.
- ✓ This report does not imply an approval of the product by the Certification Bodies or competent Authorities.

3. Environmental Conditions

- ✓ At the site where the measurements were performed the following limits were not exceeded during the tests:

Temperature [C]	25.0 °C +/- 0.6 °C
Humidity [%]	47.3% +/- 3.5%

4. Test samples

Sample	Control #	Description	Model	Serial #	Date of receipt	Note
#01	240521-01.S03	WiFi 7 Module	BE201D2WP	F8FE5ECDD124	2024-05-22	Used for conducted tests
	200203-01.S09	Laptop	HP Oleander	00095101LK	2024-04-24	
	231109-03.S31	Extender Board	CRF DB 2230 BNJ	ASS00862-01-0A	2023-11-10	
#02	240521-01.S07	WiFi 7 Module	BE201D2WP	F8FE5ECDC8EB	2024-06-05	Conducted Setup for overlap test
	200203-01.S10	Laptop	HP Oleander	000951007L	2023-04-24	
	241109-03.S70	Extender Board	CRF DB 2230 BNJ	2207308398	2024-06-05	
#03	240521-02.S05	Wifi 7 Module	BE201D2WP	F8FE5ECDC9B3	2024-05-22	Used for Radiated Spurious Emissions tests
	220225-03.S07	Microwave Absorber	Eccosorb BSR-1	-	2022-03-14	
	231109-03.S48	Adaptor	PCB00866-00_A	124627	2023-11-24	
	200611-03.S31	Extender	ADEXELEC	-	2020-08-19	
	200504-04.S07	Laptop	Latitude 5401	BVHLK13	2020-06-02	
	220117-04.S11	Antenna 5GHz	ANT24-P855-00	-	2022-02-09	
	240521-01.S11	Antenna 5GHz	ANT24-P855-00	-	2022-02-09	
	231120-05.S21	WiFi 7 Module	BE201D2WP	F8FE5CDCA49	2024-02-07	
	180001-01.S21	Socket	1216SD to M.2	-	2021-06-07	
#04	240521-02.S04	Wifi 7 Module	BE201D2WP	F8FE5ECDCA08	2024-05-22	Used for Radiated Spurious Emissions tests
	220225-03.S07	Microwave Absorber	Eccosorb BSR-1	-	2022-03-14	
	231109-03.S47	Adaptor	PCB00866-00_A	124727	2023-11-24	
	220915-09.S01	Extender	ADEXELEC	-	2022-04-06	
	200611-03.S30	Laptop	Latitude 5401	6DJLK13	2020-08-19	
	220117-04.S11	Antenna 5GHz	ANT24-P855-00	-	2022-02-09	
	240521-01.S11	Antenna 5GHz	ANT24-P855-00	-	2024-05-22	
	231120-05.S20	WiFi 7 Module	BE201D2WP	F8FE5CDCA49	2024-02-07	
	180001-01.S21	Socket	1216SD to M.2	-	2021-06-07	

5. EUT Features

The herein information is provided by the customer.

Intel WRF Lab declines any responsibility for the accuracy of the stated customer provided information, especially if it has any impact on the correctness of test results presented in this report.

Brand Name	Intel®		
Model Name	BE201D2WP		
Software Version	DRTU.05726.99.0.86		
Driver Version	99.0.86.3		
Prototype / Production	Production		
Supported Radios	802.11b/g/n/ax/be 2.4GHz 802.11a/n/ac/ax/be 5.2GHz 5.6GHz 5.8GHz 802.11ax/be 6.0GHz Bluetooth 2.4GHz		
Antenna Information	Transmitter	Chain A (1)	Chain B (2)
	Manufacturer	Intel	Intel
	Antenna type	PIFA / Slot / Monopole	PIFA / Slot / Monopole
	Part number	ANT24-P855-00 / ANT24-S855-00 / ANT24-M855-00	ANT24-P855-00 / ANT24-S855-00 / ANT24-M855-00
	Declared antenna gain (dBi) – 5 GHz	+8.07	+8.07

6. Remarks and comments

1. No deviations were made from the test methods listed in section 1 of this report.
2. Only the worst-case plot per 802.11 mode and test case measurements have been reported excepted for band edge measurements where all plots are reported.
3. Conducted tests have been performed using the maximum antenna gain between the PIFA, Monopole and Slot antennas.

7. Test Verdicts summary.

The statement of conformity to applicable standards in the table below are based on the measured values, without taking into account the measurement uncertainties.

7.1. 802.11 a/n/ac/ax/be – U-NII-2C

FCC part	RSS clause	Test name	Verdict
15.407 (a) (2)	RSS-247 Clause 6.2.3.1	Power Limits. Maximum output power	Pass
15.407 (a) (2)	RSS-247 Clause 6.2.3.1	Power spectral density	Pass
15.407 (b) (3) 15.209 (a)	RSS-247 Clause 6.2.3.2 RSS-GEN A1 Clause 8.9	Undesirable emissions limits: out of band (conducted)	Pass
15.407 (b) (3) 15.209 (a)	RSS-247 Clause 6.2.3.2 RSS-GEN A1 Clause 8.9	Undesirable emissions limits: Spurious emissions (radiated)	Pass

8. Document Revision History

Revision #	Modified by	Revision Details
Rev. 00	T.MATHIEU R.SIMONINI	First Issue


Annex A. Test & System Description

A.1 Measurement System

Measurements were performed using the following setups, made in accordance to the general provisions of FCC OET KDB 789033 D02 General UNII Test Procedures.


The DUT was installed in a test fixture and this test fixture is connected to a laptop computer and AC/DC power adapter. The laptop computer was used to configure the EUT to continuously transmit at a specified output power using all different modes and modulation schemes, using the Intel proprietary tool DRTU.

Conducted test setup





Radiated test setup

TX RSE - 30 MHz - 1 GHz



Tx RSE - 1 GHz - 11 GHz





Sample Calculation

The spurious received voltage $V(\text{dB}\mu\text{V})$ in the spectrum Analyzer is converted to Electric field strength using the transducer factor F corresponding to the Rx path Loss:

$$F (\text{dB/m}) = \text{Rx Antenna Factor (dB/m)} + \text{Cable losses (dB)} - \text{Amplifiers Gain (dBi)}$$

$$E (\text{dB}\mu\text{V/m}) = V(\text{dB}\mu\text{V}) + F (\text{dB/m})$$

For field strength measurements made at other than the distance at which the applicable limit is specified, the field strength of the emission at the distance specified by the limit is deduced as follows:

$$E_{\text{SpecLimit}} = E_{\text{Meas}} + 20 \cdot \log(D_{\text{Meas}}/D_{\text{SpecLimit}})$$

where

$E_{\text{SpecLimit}}$ is the field strength of the emission at the distance specified by the limit, in $\text{dB}\mu\text{V/m}$

E_{Meas} is the field strength of the emission at the measurement distance, in $\text{dB}\mu\text{V/m}$

D_{Meas} is the measurement distance, in m

$D_{\text{SpecLimit}}$ is the distance specified by the limit, in m

A.2 Test Equipment List

Conducted setup

ID#	Device	Type/Model	Serial #	Manufacturer	Cal. Date	Cal. Due Date
266-000	Spectrum Analyzer	FSV30	103307	Rohde & Schwarz	2024-05-22	2026-05-22
273-000	Spectrum Analyzer	FSV30	103309	Rohde & Schwarz	2024-03-22	2026-03-22
018-003	RF cable 50cm	PE360-50CM	N/A	PASTERNACK	2024-02-20	2025-02-20
018-001	10dB Attenuator + MH4	N/A	N/A	N/A	2024-02-20	2025-02-20
019-000	RF cable 50cm	PE360-50CM	N/A	PASTERNACK	2024-02-21	2025-02-21
019-002	10dB Attenuator + MH4	PE7395-10	N/A	PASTERNACK	2024-02-21	2025-02-21
363-000	Temp & Humidity Logger	RA12E-TH1-RAS	RA12-D0EB1A	AVITECH	2023-09-28	2025-09-28
413-000	Measurement SW v1.5.4.2	Octopi	N/A	Step AT	N/A	N/A

Radiated Setup #1

ID#	Device	Type/Model	Serial #	Manufacturer	Cal. Date	Cal. Due Date
006-000	Anechoic Chamber	FACT3	5720	ETS-Lindgren	2024-01-17	2026-01-17
006-008	Measurement SW, v11.30	EMC32	100623	Rohde & Schwarz	N/A	N/A
259-000	Temp & Humidity Logger	RA12E-TH-RAS	RA12-B9BD70	Avtech	2022-06-27	2024-06-27*
006-001	Turn Table	ETS	-	ETS-Lindgren	N/A	N/A
006-011	Boresight antenna mast	BAM 4.0-P	P/278/2890.01	Maturo	N/A	N/A
057-000	Double Horn Ridged antenna	3117	167062	ETS-Lindgren	2022-07-08	2024-07-08
058-000	Double Horn Ridged antenna	3116C	157511	ETS-Lindgren	2022-10-21	2024-10-21
006-061	Bi-Log Periodic antenna	CBL6143A	61382	Teseq	2022-10-24	2024-10-24
147-000	Spectrum analyzer	FSW43	101847	Rohde & Schwarz	2022-11-30	2024-11-30
301-000	Amplifier 9kHz-1300MHz	8447F	3113A07440	HP	2024-03-19	2025-03-19
261-000	Amplifier 1GHz-18GHz	3117-PA	00157993	ETS-Lindgren	2024-03-14	2025-03-14
502-006	Amplifier 0.5GHz-40GHz	DEPA0540-43	2023A05	Diamond Engineering	2024-03-19	2025-03-19
009-007	RF Filter	ZHSS-k11G+	8493 1831830	Mini-Circuits	2024-03-19	2025-03-19
006-068	RF Switch	RC-2SP6T-40	02112090061	Micro-Circuits	2024-03-14	2025-03-14
006-066	Cable 7m – 25MHz to 40GHz	R286304174	20.46.370	Radiall	2024-03-14	2025-03-14
006-063	Cable 30cm – 1GHz to 40GHz	PE371-12	-	Pasternack	2024-03-14	2025-03-14
006-064	Cable 30cm – 1GHz to 40GHz	PE371-12	-	Pasternack	2024-03-14	2025-03-14
006-065	Cable 60cm – 25MHz to 1GHz	PE300-24	-	Pasternack	2024-03-12	2025-03-12

N/A: Not Applicable

*Equipment not used outside of its calibration period.

Radiated Setup #2

ID#	Device	Type/Model	Serial #	Manufacturer	Cal. Date	Cal. Due Date
007-000	Anechoic chamber	RFD-FA-100	5996	ETS Lindgren	2024-01-18	2026-01-18
127-000	Spectrum Analyzer	FSV40	101358	Rohde & Schwarz	2023-01-27	2025-01-27
007-007	Double Ridge Horn (1- 18GHz)	3117	00152266	ETS Lindgren	2024-03-26	2026-03-26
007-006	Switch & Positioner	EMCenter	00151232	ETS Lindgren	N/A	N/A
059-000	Double Ridge Horn (1- 18GHz)	3117	201542	ETS-Lindgren	2023-09-26	2025-09-26
264-000	Amplifier 1GHz-18GHz	3117-PA	00169546	ETS-Lindgren	2024-03-14	2025-03-14
007-011	RF Cable 1-18GHz - 6.5m	140-8500-11-51	001	Atem	2024-03-15	2025-03-15
007-005	Measurement SW, v11.20.00	EMC32	100401	Rohde & Schwarz	N/A	N/A
007-003	Antenna Tower	2171B-3.0M	00150123	ETS Lindgren	N/A	N/A
007-002	Turntable	-	-	ETS Lindgren	N/A	N/A
007-022	RF Cable 1-18GHz, 1.5m	0501050991200GX	19.23.493	Radiall	2024-03-12	2025-03-12
007-015	RF Cable 1GHz-18GHz 1.5m	-	-	Spirent	2024-03-12	2025-03-12
007-018	RF Cable 1-9.5GHz 1.2m	0500990991200KE	-	Radiall	2024-03-12	2025-03-12
007-020	RF Cable 1-18GHz, 1.2 m	2301761761200PJ	12.22.1104	Radiall	2024-03-15	2025-03-15
349-000	Temp & Humidity Logger	RA12E-TH1-RAS	RA12-D4F8C3	Avtech	2023-11-30	2025-11-30

N/A: Not Applicable

Shared Radiated Equipment

ID#	Device	Type/Model	Serial #	Manufacturer	Cal. Date	Cal. Due Date
412-000	DRTU Power finder V2.1	-	-	Intel	NA	NA
139-000	Power Sensor	NRP-Z81	104383	Rohde & Schwarz	2023-04-21	2025-04-21
061-000	Power Sensor	NRP-Z81	104386	Rohde & Schwarz	2024-04-09	2026-04-09

140-000	Power Sensor	NRP-Z81	104382	Rohde & Schwarz	2024-04-04	2026-04-04
---------	--------------	---------	--------	-----------------	------------	------------

A.3 Measurement Uncertainty Evaluation

The system uncertainty evaluation is shown in table below with a coverage factor of $k = 2$ to indicate a 95% level of confidence:

Measurement type	Uncertainty	Unit
Timing	± 0.12	%
Power Spectral density	± 1.47	dB
Occupied bandwidth	± 2.07	%
Conducted Power	± 1.03	dB
Conducted Spurious Emission <26.5 GHz	± 3.45	dB
Radiated tests <1GHz	± 6.23	dB
Radiated tests 1GHz – 40 GHz	± 6.40	dB

Annex B. Test Results U-NII-2C

The herein test results were performed by:

Test case measurement	Test Peronnel
Power Limits. Maximum output power	T.MATHIEU
Power spectral density	T.MATHIEU
Undesirable emissions limits: out of band (conducted)	T.MATHIEU
Undesirable emissions limits (radiated)	K.KHATIB, R.SIMONINI

B.1 Test Conditions

For 802.11a mode the EUT can transmit at both CHAIN A and CHAIN B RF outputs individually, but not simultaneously.

For 802.11n20 & 802.11ax/be20 (20 MHz channel bandwidth), 802.11n40 & 802.11ax/be40 (40MHz channel bandwidth), 802.11ac80 & 802.11ax/be80 (80MHz channel bandwidth) and 802.11ac160 &802.11ax/be160 (160MHz channel bandwidth) modes the EUT can transmit at both CHAIN A and CHAIN B RF outputs individually, and also simultaneously.

The following data rates were selected based on preliminary testing that identified those rates as the worst cases for output power and spurious levels at the band edges:

Transmission	Mode	Bandwidth (MHz)	Worst Case Data Rate
SISO	802.11a	20	6Mbps
	802.11n	20	HT0
		40	HT0
	802.11ac	80	VHT0
		160	VHT0
	802.11ax/be	20/40/80/160	MCS0
MIMO	802.11n	20/40	HT8
	802.11ac	80/160	VHT0
	802.11ax/be	20/40/80/160	MCS0

B.2 Test Results Tables

B.2.1 26dB & 99% Bandwidth

Test procedure

The conducted setup shown in section *Test & System Description* was used to measure the 26dB & 99% bandwidth. The antenna terminal of the EUT is connected to the spectrum analyzer through an attenuator, and the spectrum analyzer reading is compensated to include the RF path loss.

For the overlapped channels between U-NII-2C and U-NII-3 bands, and according to FCC OET KDB 789033 D02, the boundary frequency between the bands is used as one edge for defining the portion of the 26dB bandwidth that falls within a particular U-NII band. This rule is only applicable for the 26dB bandwidth and for those channels marked as overlapped.

Results tables

U-NII-2C channels

Mode	Rate	Antenna	Channel	Freq [MHz]	26dB BW [MHz]	99% BW [MHz]
802.11a	6Mbps	SISO A	100	5500	24.35	16.71
			120	5600	24.20	16.75
			140	5700	24.90	16.79
		SISO B	100	5500	24.15	16.86
			120	5600	24.60	16.69
			140	5700	24.40	16.71
802.11n20	HT0	SISO A	100	5500	24.85	17.77
			120	5600	25.00	17.78
			140	5700	24.85	17.77
		SISO B	100	5500	24.65	17.77
			120	5600	24.90	17.77
			140	5700	24.90	17.77
	HT8	MIMO A	100	5500	24.85	17.86
			120	5600	25.30	17.78
			140	5700	25.25	17.85
		MIMO B	100	5500	24.55	17.76
			120	5600	24.80	17.74
			140	5700	24.90	17.77
802.11n40	HT0	SISO A	102	5510	43.38	36.40
			118	5590	43.89	36.00
			134	5670	44.33	36.24
		SISO B	102	5510	43.29	36.08
			118	5590	44.55	36.08
			134	5670	44.00	36.00
	HT8	MIMO A	102	5510	44.01	36.08
			118	5590	43.56	36.00
			134	5670	43.89	36.00
		MIMO B	102	5510	42.30	36.16
			118	5590	42.02	36.16
			134	5670	42.13	36.08
802.11ac80	VHT0	SISO A	106	5530	88.73	75.24
			122	5610	86.83	75.24
		SISO B	106	5530	87.21	75.24
			122	5610	89.49	75.24
		MIMO A	106	5530	87.02	75.24
			122	5610	86.64	75.12
		MIMO B	106	5530	86.07	75.12
			122	5610	86.26	75.00
802.11ac160	VHT0	SISO A	114	5570	165.66	153.50
		SISO B			165.33	153.75
		MIMO A			165.00	153.75
		MIMO B			164.34	153.50

Max Value

Mode	Rate	Antenna	Channel	Freq[MHz]	RU config.	26dB BW [MHz]	99% BW [MHz]
802.11ax/be20	MCS0	SISO A	100	5500	Full	24.55	18.88
					26/0	20.40	18.33
					52/37	20.65	17.69
					106/53	22.45	18.24
			120	5600	Full	23.85	18.91
					26/8	24.15	18.93
					52/40	20.95	18.39
					106/54	21.20	17.98
		SISO B	100	5500	Full	22.20	17.35
					Full	24.25	18.91
					26/0	20.45	18.36
					52/37	20.80	17.44
					106/53	21.95	17.97
			120	5600	Full	24.15	18.93
					26/8	24.55	18.96
					52/40	21.10	18.33
					106/54	21.50	18.28
			140	5500	Full	23.30	18.11
					Full	24.25	18.91
					26/0	20.25	18.29
					52/37	20.55	17.93
					106/53	20.80	17.68
		MIMO A	100	5500	Full	24.55	18.94
					26/8	24.75	18.89
					52/40	21.00	18.73
					106/54	21.40	17.99
			120	5600	Full	21.75	18.13
					Full	23.65	18.95
					26/0	20.20	17.56
					52/37	20.35	18.22
					106/53	20.85	18.10
			140	5700	Full	23.90	19.00
					Full	23.25	18.91
					26/8	20.35	18.18
					52/40	20.45	18.17
					106/54	20.70	17.13
802.11ax/be40	MCS0	SISO A	102	5510	Full	42.93	37.52
					242/62	26.73	18.64
			118	5590	Full	43.65	37.60
					Full	43.11	37.60
		SISO B	102	5510	Full	43.11	37.60
					242/62	27.27	18.88
					Full	42.66	37.36
					242/62	27.00	18.88
			118	5590	Full	45.09	37.44
					Full	43.20	37.60
					242/62	24.57	18.88
					Full	43.02	37.52
		MIMO A	102	5510	Full	43.02	37.52
					242/62	25.74	18.80
					Full	43.02	37.52
					Full	43.02	37.28
			134	5670	242/62	26.46	18.64
					Full	41.85	37.44
					242/62	25.74	18.80
					Full	42.75	37.52
		MIMO B	102	5510	Full	42.48	37.44
					242/62	26.19	18.96
			118	5590	Full	42.48	37.44
					242/62	26.19	18.96

802.11ax/be80	MCS0	SISO A	106	5530	Full	84.36	76.80
					484/65	43.89	37.44
			122	5610	Full	83.79	76.80
		SISO B	106	5530	Full	83.41	76.80
					484/65	44.08	37.44
			122	5610	Full	83.98	76.68
		MIMO A	106	5530	Full	83.98	76.80
					484/65	46.74	37.32
			122	5610	Full	84.17	76.80
		MIMO B	106	5530	Full	83.98	76.80
					484/65	45.60	37.32
			122	5610	Full	85.50	76.68
802.11ax/be160	MCS0	SISO A	114	5570	Full	163.35	155.25
					996/67	83.16	77.00
					996/S67	86.13	77.00
		SISO B			Full	163.35	155.00
					996/67	84.48	77.00
					996/S67	86.13	77.00
		MIMO A			Full	164.34	155.25
					996/67	83.82	77.00
					996/S67	90.42	77.25
		MIMO B			Full	164.34	155.25
					996/67	84.15	77.00
					996/S67	88.44	77.25

Max Value

Overlapped channels between U-NII-2C and U-NII-3

Mode	Rate	Channel	Frequency (MHz)	Antenna	Chain	26dB BW [MHz] UNII2C
802.11n20	HT0	144	5720	SISO	A	17.87
					B	16.98
	HT8			MIMO	A	17.23
					B	16.92
802.11n40	HT0	142	5710	SISO	A	36.65
					B	36.45
	HT8			MIMO	A	36.55
					B	35.85
802.11ac80	VHT0	138	5690	SISO	A	77.90
					B	77.54
				MIMO	A	78.50
					B	77.66
802.11ax/be20	MCS0	144	5720	SISO	A	16.83
					B	16.92
				MIMO	A	16.98
					B	16.68
802.11ax/be40	MCS0	142	5710	SISO	A	36.05
					B	36.65
				MIMO	A	35.85
					B	36.25
				Combined	A+B	75.86
802.11ax/be80	MCS0	138	5690	SISO	A	76.46
					B	76.46
				MIMO	A	77.54
					B	17.87

Max Value

See Section B.3.1 and Section B.3.2 for the screenshot results.

B.2.2 Power Limits. Maximum Output power & Maximum power spectral Density

Test limits

Part	Limits
FCC 15.407 (a) (2)	For the 5.25–5.35 GHz and 5.47–5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the peak power spectral density shall not exceed 11 dBm in any 1 megahertz band.
RSS-247 Clause 6.2.3 (1)	The maximum conducted output power shall not exceed 250 mW or $11 + 10 \log_{10} B$, dBm, whichever is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band. The maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log_{10} B$, dBm, whichever is less. B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

Test procedure

The Maximum Conducted Output Power was measured using the channel integration method according to section E) 2) e) (Method SA-2 and SA-2 Alternative) of FCC OET KDB 789033 D02.

The maximum power spectral density (PSD) was measured using the method according to section F) (Method SA-2 and SA-2 Alternative) of FCC OET KDB 789033 D02.

In the measure-and-sum approach for MIMO mode, the conducted emission level (e.g., transmit power or power in specified bandwidth) is measured at each antenna port. The measured results at the various antenna ports are then summed mathematically in linear power units to determine the total emission level from the device.

The EIRP power (dBm) is calculated by adding the declared maximum antenna gain to the measured conducted power.

The conducted setup shown in section *Test & System Description* was used to measure the maximum conducted output power and power spectral density. The antenna terminal of the EUT is connected to the spectrum analyser through an attenuator, and the spectrum analyzer reading is compensated to include the RF path loss.

For the overlapped channels between U-NII-2C and U-NII-3, and according to FCC OET KDB 789033 D02 the power is computed based on the portion of the emission bandwidth contained within that band. This rule is only applicable for those channels marked as overlapped

Results tables

Duty cycle

Mode	Rate	Antenna	Duty Cycle [%]
802.11a	6Mbps	SISO A	97.8
		SISO B	97.8
802.11n20	HT0	SISO A	98.8
		SISO B	98.8
	HT8	MIMO A	98.8
		MIMO B	98.8
802.11ax/be20	MCS0	SISO A	98.8
		SISO B	98.8
		MIMO A	99.4
		MIMO B	99.4
802.11n40	HT0	SISO A	98.8
		SISO B	98.8
	HT8	MIMO A	98.8
		MIMO B	98.8
802.11ax/be40	MCS0	SISO A	98.8
		SISO B	98.8
		MIMO A	99.4
		MIMO B	99.4
802.11ac80	VHT0	SISO A	98.9
		SISO B	98.9
		MIMO A	99.4
		MIMO B	99.4
802.11ax/be80	MCS0	SISO A	98.8
		SISO B	98.8
		MIMO A	99.4
		MIMO B	99.4
802.11ac160	VTH0	SISO A	98.8
		SISO B	98.8
		MIMO A	99.2
		MIMO B	99.2
802.11ax/be160	MCS0	SISO A	98.8
		SISO B	98.8
		MIMO A	98.9
		MIMO B	98.9

Maximum output power – U-NII-2C Channels

Mode	Rate	#Ch	Freq [MHz]	Antenna	Average Conducted Output Power [dBm]	Avg Max* Conducted Output Power [dBm]	Avg Max*. EIRP [dBm]	Avg Max* Conducted Power [mW]
802.11a	6Mbps	100	5500	SISO A	19.61	19.71	27.78	93.47
				SISO B	19.58	19.68	27.75	92.82
		120	5600	SISO A	19.55	19.65	27.72	92.19
				SISO B	19.62	19.72	27.79	93.68
		140	5700	SISO A	19.56	19.66	27.73	92.40
				SISO B	19.57	19.67	27.74	92.61
802.11n20	HT0	100	5500	SISO A	19.82	19.82	27.89	95.94
				SISO B	19.77	19.77	27.84	94.84
		120	5600	SISO A	19.83	19.83	27.90	96.16
				SISO B	19.79	19.79	27.86	95.28
		140	5700	SISO A	19.76	19.76	27.83	94.62
				SISO B	19.79	19.79	27.86	95.28
	HT8	100	5500	MIMO A	16.42	16.42	24.49	43.85
				MIMO B	16.47	16.47	24.54	44.36
				Combined A+B	19.46	19.46	27.53	88.21
		120	5600	MIMO A	16.20	16.20	24.27	41.69
				MIMO B	16.37	16.37	24.44	43.35
				Combined A+B	19.30	19.30	27.37	85.04
		140	5700	MIMO A	16.35	16.35	24.42	43.15
				MIMO B	16.56	16.56	24.63	45.29
				Combined A+B	19.47	19.47	27.54	88.44
802.11n40	HT0	102	5510	SISO A	20.85	20.85	28.92	121.62
				SISO B	20.92	20.92	28.99	123.59
		118	5590	SISO A	21.83	21.83	29.90	152.41
				SISO B	21.72	21.72	29.79	148.59
		134	5670	SISO A	20.84	20.84	28.91	121.34
				SISO B	20.86	20.86	28.93	121.90
	HT8	102	5510	MIMO A	18.60	18.60	26.67	72.44
				MIMO B	18.78	18.78	26.85	75.51
				Combined A+B	21.70	21.70	29.77	147.95
		118	5590	MIMO A	18.71	18.71	26.78	74.30
				MIMO B	18.72	18.72	26.79	74.47
				Combined A+B	21.73	21.73	29.80	148.78
		134	5670	MIMO A	18.57	18.57	26.64	71.94
				MIMO B	18.79	18.79	26.86	75.68
				Combined A+B	21.69	21.69	29.76	147.63
802.11ac80	VHT0	106	5530	SISO A	19.82	19.82	27.89	95.94
				SISO B	19.78	19.78	27.85	95.06
				MIMO A	17.02	17.02	25.09	50.35
				MIMO B	17.31	17.31	25.38	53.83
		122	5610	Combined A+B	20.18	20.18	28.25	104.18
				SISO A	20.77	20.77	28.84	119.40
				SISO B	20.91	20.91	28.98	123.31
				MIMO A	18.66	18.66	26.73	73.45
802.11ac160	VHT0	114	5570	MIMO B	18.89	18.89	26.96	77.45
				Combined A+B	21.79	21.79	29.86	150.90
				SISO A	17.06	17.06	25.13	50.82
				SISO B	17.34	17.34	25.41	54.20
				MIMO A	15.54	15.54	23.61	35.81
				MIMO B	15.59	15.59	23.66	36.22
				Combined A+B	18.58	18.58	26.65	72.03

* Maximum values are the duty cycle compensated values calculated from the average (measured) values

Max/Min Value

Mode	Rate	#Ch	Freq [MHz]	Antenna	RU config.	Average Conducted Output Power [dBm]	Avg Max Conducted Output Power [dBm]	Avg Max . EIRP [dBm]	Avg Max Conducted Power [mW]
802.11ax/be20	MCS0	100	5500	SISO A	Full	20.00	20.00	28.07	100.00
					26/0	11.33	11.33	19.40	13.58
					52/37	13.88	13.88	21.95	24.43
					106/53	16.86	16.86	24.93	48.53
				SISO B	Full	20.06	20.06	28.13	101.39
					26/0	11.31	11.31	19.38	13.52
					52/37	14.21	14.21	22.28	26.36
					106/53	16.83	16.83	24.90	48.19
				MIMO A	Full	16.33	16.33	24.40	42.95
					26/0	8.29	8.29	16.36	6.75
					52/37	10.92	10.92	18.99	12.36
					106/53	14.01	14.01	22.08	25.18
				MIMO B	Full	16.47	16.47	24.54	44.36
					26/0	8.42	8.42	16.49	6.95
					52/37	10.95	10.95	19.02	12.45
					106/53	14.01	14.01	22.08	25.18
				Combined A+B	Full	19.41	19.41	27.48	87.31
					26/0	11.37	11.37	19.44	13.70
					52/37	13.95	13.95	22.02	24.80
					106/53	17.02	17.02	25.09	50.35
		120	5600	SISO A	Full	20.02	20.02	28.09	100.46
				SISO B	Full	20.14	20.14	28.21	103.28
				MIMO A	Full	16.59	16.59	24.66	45.60
				MIMO B	Full	16.55	16.55	24.62	45.19
				Combined A+B	Full	19.58	19.58	27.65	90.79
		140	5700	SISO A	Full	19.94	19.94	28.01	98.63
					26/0	11.10	11.10	19.17	12.88
					52/37	13.96	13.96	22.03	24.89
					106/53	16.92	16.92	24.99	49.20
				SISO B	Full	20.10	20.10	28.17	102.33
					26/0	11.27	11.27	19.34	13.40
					52/37	13.81	13.81	21.88	24.04
					106/53	16.66	16.66	24.73	46.34
				MIMO A	Full	16.26	16.26	24.33	42.27
					26/0	8.26	8.26	16.33	6.70
					52/37	10.89	10.89	18.96	12.27
					106/53	14.06	14.06	22.13	25.47
				MIMO B	Full	16.53	16.53	24.60	44.98
					26/0	8.34	8.34	16.41	6.82
					52/37	11.18	11.18	19.25	13.12
					106/53	14.25	14.25	22.32	26.61
				Combined A+B	Full	19.41	19.41	27.48	87.24
					26/0	11.31	11.31	19.38	13.52
					52/37	14.05	14.05	22.12	25.40
					106/53	17.17	17.17	25.24	52.08
802.11ax/be40	MCS0	102	5510	SISO A	Full	20.48	20.48	28.55	111.69
					242/62	18.41	18.41	26.48	69.34
				SISO B	Full	20.56	20.56	28.63	113.76
					242/62	18.34	18.34	26.41	68.23
				MIMO A	Full	18.79	18.79	26.86	75.68
					242/62	16.68	16.68	24.75	46.56
				MIMO B	Full	18.69	18.69	26.76	73.96
					242/62	16.14	16.14	24.21	41.11
		118	5590	Combined A+B	Full	21.75	21.75	29.82	149.64
					242/62	19.43	19.43	27.50	87.67
				SISO A	Full	21.80	21.80	29.87	151.36
					242/62	18.69	18.69	26.76	73.96
				SISO B	Full	21.84	21.84	29.91	152.76
					242/62	18.59	18.59	26.66	72.28
				MIMO A	Full	18.59	18.59	26.66	72.28
					242/62	18.70	18.70	26.77	74.13
		134	5670	Combined A+B	Full	21.66	21.66	29.73	146.41
					242/62	20.72	20.72	28.79	118.03
				SISO A	Full	20.72	20.72	28.79	118.03
					242/62	18.69	18.69	26.76	73.96
				SISO B	Full	20.79	20.79	28.86	119.95
					242/62	18.69	18.69	26.76	73.96

				MIMO A	242/62	19.78	19.78	27.85	95.06
					Full	18.78	18.78	26.85	75.51
				MIMO B	242/62	16.68	16.68	24.75	46.56
					Full	18.68	18.68	26.75	73.79
				Combined A+B	242/62	16.80	16.80	24.87	47.86
					Full	21.74	21.74	29.81	149.30
					242/62	19.75	19.75	27.82	94.42

Mode	Rate	#Ch	Freq [MHz]	Antenna	RU config.	Average Conducted Ouput Power [dBm]	Avg Max Conducted Ouput Power [dBm]	Avg Max . EIRP [dBm]	Avg Max Conducted Power [mW]
802.11ax/be80	MCS0	106	5530	SISO A	Full	19.79	19.79	27.86	95.28
					484/65	20.79	20.79	28.86	119.95
				SISO B	Full	19.74	19.74	27.81	94.19
					484/65	20.88	20.88	28.95	122.46
				MIMO A	Full	17.18	17.18	25.25	52.24
					484/65	15.13	15.13	23.20	32.58
				MIMO B	Full	17.18	17.18	25.25	52.24
					484/65	14.21	14.21	22.28	26.36
				Combined A+B	Full	20.19	20.19	28.26	104.48
					484/65	17.70	17.70	25.77	58.95
		122	5610	SISO A	Full	20.71	20.71	28.78	117.76
				SISO B	Full	20.79	20.79	28.86	119.95
				MIMO A	Full	18.56	18.56	26.63	71.78
				MIMO B	Full	18.84	18.84	26.91	76.56
				Combined A+B	Full	21.71	21.71	29.78	148.34
802.11ax/be160	MCS0	114	5570	SISO A	Full	17.04	17.04	25.11	50.58
					996/67	18.94	18.94	27.01	78.34
					996/S67	20.43	20.43	28.50	110.41
				SISO B	Full	17.10	17.10	25.17	51.29
					996/67	19.51	19.51	27.58	89.33
					996/S67	20.52	20.52	28.59	112.72
				MIMO A	Full	15.52	15.52	23.59	35.65
					996/67	15.22	15.22	23.29	33.27
					996/S67	17.19	17.19	25.26	52.36
				MIMO B	Full	15.56	15.56	23.63	35.97
					996/67	15.39	15.39	23.46	34.59
					996/S67	15.76	15.76	23.83	37.67
				Combined A+B	Full	18.55	18.55	26.62	71.62
					996/67	18.32	18.32	26.39	67.86
					996/S67	19.54	19.54	27.61	90.03

* Maximum values are the duty cycle compensated values calculated from the average (measured) values

Max/Min Value

Maximum output power – Overlapped channels between U-NII-2C and U-NII-3

Mode	Rate	Antenna	Chain	Channel	Frequency (MHz)	Average Cond. Output Power - UNII-2C [dBm]	Max.* Cond. Output Power - UNII-2C [dBm]	Max.* EIRP UNII2C [dBm]	Max.* Cond. Output Power - UNII-2C [mW]
802.11n20	HT0	SISO	A	144	5720	18.75	18.75	26.82	74.99
			B		5720	18.77	18.77	26.84	75.34
	HT8	MIMO	A		5720	15.69	15.69	23.76	37.07
			B		5720	15.67	15.67	23.74	36.90
		Combined	A+B		5720	18.69	18.69	26.76	73.97
			A+B		5720	18.69	18.69	26.76	73.97
802.11n40	HT0	SISO	A	142	5710	21.67	21.67	29.74	146.89
			B		5710	21.64	21.64	29.71	145.88
	HT8	MIMO	A		5710	18.67	18.67	26.74	73.62
			B		5710	18.60	18.60	26.67	72.44
		Combined	A+B		5710	21.65	21.65	29.72	146.06
			A+B		5710	21.65	21.65	29.72	146.06
802.11ac80	VHT0	SISO	A	138	5690	21.87	21.87	29.94	153.82
			B		5690	21.81	21.81	29.88	151.71
		MIMO	A		5690	18.84	18.84	26.91	76.56
			B		5690	18.78	18.78	26.85	75.51
		Combined	A+B		5690	21.82	21.82	29.89	152.07
			A+B		5690	21.82	21.82	29.89	152.07
802.11ax/be20	MCS0	SISO	A	144	5720	18.58	18.58	26.65	72.11
			B		5720	18.62	18.62	26.69	72.78
		MIMO	A		5720	15.57	15.57	23.64	36.06
			B		5720	15.54	15.54	23.61	35.81
		Combined	A+B		5720	18.57	18.57	26.64	71.87
			A+B		5720	18.57	18.57	26.64	71.87
802.11ax/be40	MCS0	SISO	A	142	5710	21.57	21.57	29.64	143.55
			B		5710	21.51	21.51	29.58	141.58
		MIMO	A		5710	18.80	18.80	26.87	75.86
			B		5710	18.73	18.73	26.80	74.64
		Combined	A+B		5710	21.78	21.78	29.85	150.50
			A+B		5710	21.78	21.78	29.85	150.50
802.11ax/be80	MCS0	SISO	A	138	5690	21.77	21.77	29.84	150.31
			B		5690	21.77	21.77	29.84	150.31
		MIMO	A		5690	18.76	18.76	26.83	75.16
			B		5690	18.71	18.71	26.78	74.30
		Combined	A+B		5690	21.75	21.75	29.82	149.46
			A+B		5690	21.75	21.75	29.82	149.46

* Maximum values are the duty cycle compensated values calculated from the average (measured) values

Max/Min Value

Maximum Power Spectral Density (PSD) – U-NII-2C channels

Mode	Rate	Channel	Freq [MHz]	Antenna	Average conducted PSD [dBm/MHz]	Maximum* conducted PSD [dBm/MHz]
802.11a	6Mbps	100	5500	SISO A	8.77	8.87
				SISO B	8.75	8.85
		120	5600	SISO A	8.51	8.61
				SISO B	8.63	8.73
		140	5700	SISO A	8.57	8.67
				SISO B	8.75	8.85
802.11n20	HT0	100	5500	SISO A	8.74	8.74
				SISO B	8.64	8.64
		120	5600	SISO A	8.70	8.70
				SISO B	8.77	8.77
		140	5700	SISO A	8.60	8.60
				SISO B	8.84	8.84
	HT8	100	5500	MIMO A	5.73	5.73
				MIMO B	5.87	5.87
				Combined A+B	8.81	8.81
		120	5600	MIMO A	5.66	5.66
				MIMO B	5.67	5.67
				Combined A+B	8.68	8.68
		140	5700	MIMO A	5.64	5.64
				MIMO B	5.87	5.87
				Combined A+B	8.77	8.77
802.11n40	HT0	102	5510	SISO A	6.73	6.73
				SISO B	6.76	6.76
		118	5590	SISO A	7.71	7.71
				SISO B	7.64	7.64
		134	5670	SISO A	6.68	6.68
				SISO B	6.78	6.78
	HT8	102	5510	MIMO A	4.62	4.62
				MIMO B	4.79	4.79
				Combined A+B	7.72	7.72
		118	5590	MIMO A	4.72	4.72
				MIMO B	4.60	4.60
				Combined A+B	7.67	7.67
		134	5670	MIMO A	4.47	4.47
				MIMO B	4.70	4.70
				Combined A+B	7.60	7.60
802.11ac80	VHT0	106	5530	SISO A	2.77	2.77
				SISO B	2.58	2.58
				MIMO A	-0.19	-0.19
				MIMO B	0.18	0.18
				Combined A+B	3.01	3.01
		122	5610	SISO A	3.47	3.47
				SISO B	3.64	3.64
				MIMO A	1.51	1.51
				MIMO B	1.72	1.72
				Combined A+B	4.63	4.63
802.11ac160	VHT0	114	5570	SISO A	-3.08	-3.08
				SISO B	-2.79	-2.79
				MIMO A	-4.29	-4.29
				MIMO B	-4.48	-4.48
				Combined A+B	-1.37	-1.37

* Maximum values are the duty cycle compensated values calculated from the average (measured) values

Mode	Rate	Channel	Freq [MHz]	Antenna	RU config.	Average conducted PSD [dBm/MHz]	Maximum* conducted PSD [dBm/MHz]	
802.11ax/be20	MCS0	100	5500	SISO A	Full	8.75	8.75	
					26/0	8.69	8.69	
					52/37	8.76	8.76	
					106/53	8.51	8.51	
				SISO B	Full	8.68	8.68	
					26/0	8.75	8.75	
					52/37	8.77	8.77	
					106/53	8.50	8.50	
				MIMO A	Full	5.56	5.56	
					26/0	5.65	5.65	
					52/37	5.52	5.52	
					106/53	5.68	5.68	
				MIMO B	Full	5.86	5.86	
					26/0	5.91	5.91	
					52/37	5.64	5.64	
					106/53	5.61	5.61	
				Combined A+B	Full	8.72	8.72	
					26/0	8.79	8.79	
					52/37	8.59	8.59	
					106/53	8.66	8.66	
		120	5600	SISO A	Full	8.72	8.72	
				SISO B	Full	8.86	8.86	
				MIMO A	Full	5.76	5.76	
				MIMO B	Full	5.88	5.88	
				Combined A+B	Full	8.83	8.83	
		140	5500 5700	SISO A	FullBW	8.64	8.64	
					26/0	8.51	8.51	
					52/37	8.70	8.70	
					106/53	8.70	8.70	
				SISO B	FullBW	8.72	8.72	
					26/0	8.81	8.81	
					52/37	8.60	8.60	
					106/53	8.37	8.37	
				MIMO A	FullBW	5.55	5.55	
					26/0	5.71	5.71	
					52/37	5.67	5.67	
					106/53	5.84	5.84	
				MIMO B	FullBW	5.65	5.65	
					26/0	5.71	5.71	
					52/37	5.89	5.89	
					106/53	5.81	5.81	
				Combined A+B	FullBW	8.61	8.61	
					26/0	8.72	8.72	
					52/37	8.79	8.79	
					106/53	8.84	8.84	
802.11ax/be40	MCS0	102	5510	SISO A	Full	6.30	6.30	
					242/62	7.53	7.53	
				SISO B	Full	6.51	6.51	
					242/62	7.63	7.63	
				MIMO A	Full	4.75	4.75	
					242/62	5.88	5.88	
				MIMO B	Full	4.46	4.46	
					242/62	5.16	5.16	
		Combined A+B	Full	7.62	7.62			
			242/62	8.55	8.55			
			118	5590	SISO A	Full	7.64	7.64
					SISO B	Full	7.69	7.69
		MIMO A			Full	4.63	4.63	
		MIMO B			Full	4.56	4.56	
		Combined A+B			Full	7.61	7.61	
		134	5670	SISO A	Full	6.70	6.70	
					242/62	7.80	7.80	
				SISO B	Full	6.55	6.55	
					242/62	8.88	8.88	

				MIMO A	Full	4.62	4.62
					242/62	5.81	5.81
				MIMO B	Full	4.58	4.58
					242/62	5.90	5.90
				Combined A+B	Full	7.61	7.61
					242/62	8.87	8.87

* Maximum values are the duty cycle compensated values calculated from the average (measured) values

Mode	Rate	Channel	Freq [MHz]	Antenna	RU config.	Average conducted PSD [dBm/MHz]	Maximum* conducted PSD [dBm/MHz]
802.11ax/be80	MCS0	106	5530	SISO A	Full	2.55	2.55
					484/65	6.53	6.53
				SISO B	Full	2.60	2.60
					484/65	6.63	6.63
				MIMO A	Full	-0.11	-0.11
					484/65	0.82	0.82
				MIMO B	Full	0.09	0.09
					484/65	0.02	0.02
				Combined A+B	Full	3.00	3.00
					484/65	3.45	3.45
802.11ax/be160	MCS0	122	5610	SISO A	Full	3.56	3.56
				SISO B	Full	3.61	3.61
				MIMO A	Full	1.51	1.51
				MIMO B	Full	1.70	1.70
				Combined A+B	Full	4.62	4.62
		114	5570	SISO A	Full	-3.06	-3.06
					996/67	1.79	1.79
					996/S67	3.29	3.29
				SISO B	Full	-2.92	-2.92
					996/67	2.37	2.37
					996/S67	3.37	3.37
				MIMO A	Full	-4.56	-4.56
					996/67	-1.99	-1.99
					996/S67	-0.09	-0.09
				MIMO B	Full	-4.33	-4.33
					996/67	-1.70	-1.70
					996/S67	-1.33	-1.33
				Combined A+B	Full	-1.43	-1.43
					996/67	1.17	1.17
					996/S67	2.34	2.34

* Maximum values are the duty cycle compensated values calculated from the average (measured) values

Maximum Power Spectral Density (PSD) – Overlapped channels between U-NII-2C and U-NII-3

Mode	Rate	Channel	Frequency (MHz)	Antenna	Chain	Average conducted PSD UNII-2C [dBm/MHz]	Maximum* conducted PSD UNII-2C [dBm/MHz]
802.11n20	HT0	144	5720	SISO	A	8.82	8.82
					B	8.85	8.85
	HT8			MIMO	A	5.72	5.72
					B	5.64	5.64
	Combined			A+B	8.69	8.69	
802.11n40	HT0	142	5710	SISO	A	7.84	7.84
					B	7.78	7.78
	HT8			MIMO	A	4.67	4.67
					B	4.73	4.73
	Combined			A+B	7.71	7.71	
802.11ac80	VHT0	138	5690	SISO	A	4.74	4.74
					B	4.62	4.62
				MIMO	A	1.64	1.64
					B	1.62	1.62
				Combined	A+B	4.64	4.64
802.11ax/be20	MCS0	144	5720	SISO	A	8.82	8.82
					B	8.55	8.55
				MIMO	A	5.52	5.52
					B	5.48	5.48
				Combined	A+B	8.51	8.51
802.11ax/be40	MCS0	142	5710	SISO	A	7.68	7.68
					B	7.67	7.67
				MIMO	A	4.84	4.84
					B	5.04	5.04
				Combined	A+B	7.95	7.95
802.11ax/be80	MCS0	138	5690	SISO	A	4.66	4.66
					B	4.74	4.74
				MIMO	A	1.63	1.63
					B	1.54	1.54
				Combined	A+B	4.60	4.60

* Maximum values are the duty cycle compensated values calculated from the average (measured) values

See Section B.3.2 for the screenshot results.

B.2.3 Undesirable emission limits : out of band (Conducted)

Test limits

FCC part	RSS clause	Limits																				
15.407 (b) (3)	RSS-247 Clause 6.2.3 (2)	For transmitters operating in the 5.47–5.725 GHz band: all emissions outside of the 5.47–5.725 GHz band shall not exceed an EIRP of -27 dBm/MHz.																				
15.209	RSS-GEN A1, Clause 8.9	Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a):																				
		<table><tr><th>Freq Range (MHz)</th><th>Field Strength (μV/m)</th><th>Field Strength (dBμV/m)</th><th>Meas. Distance (m)</th></tr><tr><td>30-88</td><td>100</td><td>40</td><td>3</td></tr><tr><td>88-216</td><td>150</td><td>43.5</td><td>3</td></tr><tr><td>216-960</td><td>200</td><td>46</td><td>3</td></tr><tr><td>Above 960</td><td>500</td><td>54</td><td>3</td></tr></table>	Freq Range (MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Meas. Distance (m)	30-88	100	40	3	88-216	150	43.5	3	216-960	200	46	3	Above 960	500	54	3
Freq Range (MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Meas. Distance (m)																			
30-88	100	40	3																			
88-216	150	43.5	3																			
216-960	200	46	3																			
Above 960	500	54	3																			
		The emission limits shown in the table above are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector. For average radiated emission measurements above 1000 MHz, there is also a limit specified when measuring with peak detector function, corresponding to 20 dB above the indicated values in the table.																				

Test procedure

The conducted setup shown in section *Test & System Description* was used to measure undesirable emissions on the out of band domain. The antenna terminal of the EUT is connected to the spectrum analyzer through an attenuator, and the spectrum analyzer reading is compensated to include the RF path loss and the declared antenna gain.

Both lower and upper side of the out of band were performed using the integration method as defined in the out of band measurements section (paragraph II.G.3.d) of FCC OET KDB 789033 D02

In case of out of band measurements falling in restricted bands, the declared antenna gain is also compensated in the graph.

The following limits in dBm were applied for the average detector after the conversion from the limits detailed above in dBμV/m, according to FCC 47 CFR part 15 - Subpart C – §15.209(a). The limits in dBm for peak detector are 20dB above the indicated values in the table.

§15.209(a)			Converted values	
Freq Range (MHz)	Distance (m)	Field strength (microvolts/meter)	Field strength (dB microvolts/meter)	Power (dBm)
Above 960	3	500	53.98	-41.2

See Section B.3.3 for the screenshot results.

B.2.4 Radiated spurious emission

Standard references

FCC part	RSS clause	Limits																				
15.407 (b) (3)	RSS-247 Clause 6.2.3 (2)	For transmitters operating in the 5.47–5.725 GHz band: all emissions outside of the 5.47–5.725 GHz band shall not exceed an EIRP of -27 dBm/MHz.																				
15.209	RSS-GEN A1, Clause 8.9	Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a): <table><tr><th>Freq Range (MHz)</th><th>Field Strength (μV/m)</th><th>Field Strength (dBμV/m)</th><th>Meas. Distance (m)</th></tr><tr><td>30-88</td><td>100</td><td>40</td><td>3</td></tr><tr><td>88-216</td><td>150</td><td>43.5</td><td>3</td></tr><tr><td>216-960</td><td>200</td><td>46</td><td>3</td></tr><tr><td>Above 960</td><td>500</td><td>54</td><td>3</td></tr></table> The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector. For average radiated emission measurements above 1000 MHz, there is also a limit specified when measuring with peak detector function, corresponding to 20 dB above the indicated values in the table.	Freq Range (MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Meas. Distance (m)	30-88	100	40	3	88-216	150	43.5	3	216-960	200	46	3	Above 960	500	54	3
Freq Range (MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Meas. Distance (m)																			
30-88	100	40	3																			
88-216	150	43.5	3																			
216-960	200	46	3																			
Above 960	500	54	3																			

Test procedure

The radiated setup shown in section *Test & System Description* was used to measure the radiated spurious emissions. Depending of the frequency range and bands being tested, different antennas and filters were used. The final measurement is done by varying the antenna height, the EUT azimuth over 360° and for both Vertical and Horizontal polarizations.

The radiated spurious emission was measured on the worst case configuration selected from the section B.2.2 and using the low, middle and high channels.

Test Results**Radiated spurious - 30 MHz – 1 GHz****Radiated Spurious – All modes**

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBµV/m	---	dBµV/m	dB	---
33.4	37.3	Quasi-Peak	40.0	2.7	V
43.8	33.5	Quasi-Peak	40.0	6.5	V
90.1	19.3	Quasi-Peak	43.5	24.2	V

Note 1: The spurious signals detected do not depend on either the operating channel or the modulation mode.

802.11a**1 GHz – 40 GHz, 802.11a, 6Mbps, Chain A****Radiated Spurious – CH100**

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBµV/m	---	dBµV/m	dB	---
5980.1	57.2	Peak	68.2	11.0	V
23919.0	49.7	Peak	74.0	24.3	V
23919.0	41.9	Average	54.0	12.1	H
39901.9	54.8	Peak	74.0	19.2	H
39901.9	48.0	Average	54.0	6.0	H

Radiated Spurious – CH120

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBµV/m	---	dBµV/m	dB	---
10500.4	57.5	Peak	68.2	10.7	H
23906.0	42.0	Average	54.0	12.0	H
23906.0	49.7	Peak	74.0	24.3	H
39996.6	56.9	Peak	74.0	17.1	V
39996.6	48.0	Average	54.0	6.0	V

Radiated Spurious – CH140

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
10500.1	57.0	Peak	68.2	11.2	H
39977.3	56.0	Peak	74.0	18.0	V
39977.3	47.9	Average	54.0	6.1	H

1 GHz – 40 GHz, 802.11a, 6Mbps, Chain B

Radiated Spurious – CH100

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
5740.1	58.0	Peak	68.2	10.2	H
16501.3	50.5	Peak	68.2	17.7	V

Radiated Spurious – CH120

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
10500.1	56.9	Peak	68.2	11.3	V
16804.8	48.8	Peak	68.2	19.4	V

Radiated Spurious – CH140

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
10500.1	56.9	Peak	68.2	11.3	V
22809.3	50.9	Peak	74.0	23.1	V
22809.3	44.1	Average	54.0	9.9	V

802.11n**1 GHz – 40 GHz, 802.11n20, HT0, Chain A**

Radiated Spurious – CH100

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
1249.7	44.5	Peak	74.0	29.5	H
1249.7	34.8	Average	54.0	19.2	H
11001.0	47.4	Peak	74.0	26.6	H
11001.0	37.8	Average	54.0	16.2	H

Radiated Spurious – CH120

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
10499.8	56.7	Peak	68.2	11.5	H
11251.3	35.3	Average	54.0	18.7	V
11251.3	46.4	Peak	74.0	27.6	V
24467.6	50.3	Peak	68.2	17.9	V

Radiated Spurious – CH140

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
1494.5	41.5	Peak	74.0	32.5	H
1494.5	32.9	Average	54.0	21.1	H
23905.5	48.9	Peak	74.0	25.1	V
23905.5	41.6	Average	54.0	12.4	H
39996.1	56.4	Peak	74.0	17.6	V
39996.1	47.9	Average	54.0	6.1	V

1 GHz – 40 GHz, 802.11n20, HT0, Chain B

Radiated Spurious – CH100

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
1296.3	45.8	Peak	74.0	28.2	V
1296.3	34.3	Average	54.0	19.7	V
16506.1	48.8	Peak	68.2	19.4	V

Radiated Spurious – CH120

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
10500.4	57.7	Peak	68.2	10.5	H
16806.3	47.7	Peak	68.2	20.5	V

Radiated Spurious – CH140

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
1494.0	42.5	Peak	74.0	31.5	V
1494.0	33.6	Average	54.0	20.4	V
22793.8	52.2	Peak	74.0	21.8	V
22800.6	43.6	Average	54.0	10.4	V

1 GHz – 40 GHz, 802.11n20, HT8, Chain A+B

Radiated Spurious – CH100

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
1294.1	47.5	Peak	74.0	26.5	V
1294.1	35.8	Average	54.0	18.2	V
11000.5	38.8	Average	54.0	15.2	H
11001.0	46.1	Peak	74.0	27.9	V
16501.3	49.5	Peak	68.2	18.7	V

Radiated Spurious – CH120

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
10500.1	57.3	Peak	68.2	10.9	V
11202.0	43.6	Peak	74.0	30.4	H
11202.0	37.7	Average	54.0	16.3	H
16795.2	48.1	Peak	68.2	20.1	V
22403.8	42.3	Average	54.0	11.7	V
22404.7	50.1	Peak	74.0	23.9	V

Radiated Spurious – CH140

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
1495.1	44.2	Peak	74.0	29.8	V
1495.1	34.6	Average	54.0	19.4	V
11404.1	46.4	Peak	74.0	27.6	V
11404.1	38.4	Average	54.0	15.6	H
22804.0	43.2	Average	54.0	10.8	V
22805.9	50.5	Peak	74.0	23.5	V

1 GHz – 40 GHz, 802.11n40, HT0, Chain A

Radiated Spurious – CH102

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
1249.7	44.4	Peak	74.0	29.6	H
1249.7	34.8	Average	54.0	19.2	H
39972.9	55.7	Peak	74.0	18.3	H
39972.9	48.0	Average	54.0	6.0	H

Radiated Spurious – CH118

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
1250.2	43.9	Peak	74.0	30.1	H
1250.2	34.7	Average	54.0	19.3	H
39991.3	56.6	Peak	74.0	17.4	H
39991.3	48.0	Average	54.0	6.0	H

Radiated Spurious – CH134

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
1249.7	44.5	Peak	74.0	29.5	V
1249.7	35.0	Average	54.0	19.0	H
23932.5	48.7	Peak	74.0	25.3	V
23932.5	41.6	Average	54.0	12.4	V
39988.4	48.0	Average	54.0	6.0	V
39988.9	56.7	Peak	74.0	17.3	H

1 GHz – 40 GHz, 802.11n40, HT0, Chain B

Radiated Spurious – CH102

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
1249.7	44.2	Peak	74.0	29.8	H
1249.7	34.9	Average	54.0	19.1	H
39999.5	56.1	Peak	74.0	17.9	H
39999.5	48.0	Average	54.0	6.0	H

Radiated Spurious – CH118

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
1249.7	43.8	Peak	74.0	30.2	H
1249.7	35.0	Average	54.0	19.0	H
39990.3	47.9	Average	54.0	6.1	H
39990.8	57.1	Peak	74.0	16.9	V

Radiated Spurious – CH134

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBµV/m	---	dBµV/m	dB	---
1249.7	43.8	Peak	74.0	30.2	H
1249.7	35.0	Average	54.0	19.0	H
23895.3	49.4	Peak	74.0	24.6	H
23895.8	41.4	Average	54.0	12.6	H
39993.7	55.8	Peak	74.0	18.2	H
39993.7	48.0	Average	54.0	6.0	V

1 GHz – 40 GHz, 802.11n40, HT8, Chain A+B

Radiated Spurious – CH102

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBµV/m	---	dBµV/m	dB	---
6887.6	56.4	Peak	68.2	11.8	V
8269.2	54.8	Peak	74.0	19.2	H
8269.2	40.7	Average	54.0	13.3	H
10499.8	53.6	Peak	68.2	14.6	V
39944.9	48.0	Average	54.0	6.0	H
39945.4	56.8	Peak	74.0	17.2	H

Radiated Spurious – CH118

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBµV/m	---	dBµV/m	dB	---
1249.7	44.4	Peak	74.0	29.6	V
1249.7	34.6	Average	54.0	19.4	H
39995.2	55.0	Peak	74.0	19.0	H
39995.2	48.0	Average	54.0	6.0	V

Radiated Spurious – CH134

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
1250.2	43.7	Peak	74.0	30.3	V
1250.2	34.1	Average	54.0	19.9	H
23938.3	48.6	Peak	74.0	25.4	H
23938.3	42.4	Average	54.0	11.6	H
39983.1	48.0	Average	54.0	6.0	H
39984.1	57.4	Peak	74.0	16.6	V

802.11ac**1 GHz – 40 GHz, 802.11ac80, VHT0, Chain A**

Radiated Spurious – CH106

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
10500.4	57.1	Peak	68.2	11.1	H
23961.1	48.4	Peak	74.0	25.6	V
23961.1	41.4	Average	54.0	12.6	H
39968.6	54.9	Peak	74.0	19.1	H
39968.6	48.0	Average	54.0	6.0	H

Radiated Spurious – CH122

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
10500.0	53.6	Peak	68.2	14.6	V
23913.7	48.3	Peak	74.0	25.7	H
23913.7	42.1	Average	54.0	11.9	H
39901.4	48.0	Average	54.0	6.0	H
39901.9	56.0	Peak	74.0	18.0	V

Radiated Spurious – CH138

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
1249.7	44.7	Peak	74.0	29.3	H
1249.7	35.7	Average	54.0	18.3	H
39996.1	55.7	Peak	74.0	18.3	H
39996.1	48.0	Average	54.0	6.0	H

1 GHz – 40 GHz, 802.11ac80, VHT0, Chain B

Radiated Spurious – CH106

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
8292.6	52.4	Peak	74.0	21.6	H
8293.4	42.3	Average	54.0	11.7	H
10500.5	53.2	Peak	68.2	15.0	V
23872.6	48.5	Peak	74.0	25.5	H
23872.6	41.5	Average	54.0	12.5	H
39630.2	55.4	Peak	74.0	18.6	H
39630.2	48.0	Average	54.0	6.0	V

Radiated Spurious – CH122

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
6060.2	55.9	Peak	68.2	12.3	H
10500.1	53.6	Peak	68.2	14.6	V
23955.3	48.7	Peak	74.0	25.3	H
23955.3	41.1	Average	54.0	12.9	V
39992.8	55.9	Peak	74.0	18.1	H
39992.8	47.9	Average	54.0	6.1	H

Radiated Spurious – CH138

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
1249.7	45.2	Peak	74.0	28.8	V
1249.7	34.5	Average	54.0	19.5	V
39984.1	56.5	Peak	74.0	17.5	H
39984.1	48.0	Average	54.0	6.0	H

1 GHz – 40 GHz, 802.11ac80, VHT0, Chain A+B

Radiated Spurious – CH106

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
6911.8	58.5	Peak	68.2	9.7	V
8290.8	53.4	Peak	74.0	20.6	H
8290.8	43.9	Average	54.0	10.1	H
10500.0	53.0	Peak	68.2	15.2	V
23946.1	50.7	Peak	74.0	23.3	H
23946.1	41.4	Average	54.0	12.6	H
39997.6	54.8	Peak	74.0	19.2	H
39997.6	47.7	Average	54.0	6.3	H

Radiated Spurious – CH122

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
5160.5	57.9	Peak	68.2	10.3	V
10500.1	54.1	Peak	68.2	14.1	V
23921.9	48.7	Peak	74.0	25.3	V
23921.9	41.6	Average	54.0	12.4	H
39971.5	55.2	Peak	74.0	18.8	V
39971.5	48.0	Average	54.0	6.0	H

Radiated Spurious – CH138

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
5160.0	59.8	Peak	68.2	8.4	V
6220.0	61.9	Peak	68.2	6.3	V
39946.8	55.1	Peak	74.0	18.9	H
39946.8	48.0	Average	54.0	6.0	V

1 GHz – 40 GHz, 802.11ac160, VHT0, Chain A

Radiated Spurious – CH114

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
10500.0	54.0	Peak	68.2	14.2	V
23976.0	48.5	Peak	74.0	25.5	V
23976.0	41.7	Average	54.0	12.3	H
39947.8	57.2	Peak	74.0	16.8	V
39948.3	48.0	Average	54.0	6.0	H

1 GHz – 40 GHz, 802.11ac160, VHT0, Chain B

Radiated Spurious – CH114

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
1249.7	43.8	Peak	74.0	30.2	H
1249.7	35.2	Average	54.0	18.8	H
23877.0	50.3	Peak	74.0	23.7	V
23877.5	41.5	Average	54.0	12.5	H
39914.0	56.7	Peak	74.0	17.3	H
39914.4	48.0	Average	54.0	6.0	V

1 GHz – 40 GHz, 802.11ac160, VHT0, Chain A+B

Radiated Spurious – CH114

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
10500.1	53.4	Peak	68.2	14.8	V
23993.0	49.4	Peak	74.0	24.6	H
23993.5	42.2	Average	54.0	11.8	V
39907.7	55.8	Peak	74.0	18.2	H
39907.7	47.9	Average	54.0	6.1	H

802.11ax/be**1 GHz – 40 GHz, 802.11ax/be20, HE0, Chain A**

Radiated Spurious – CH100

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
6864.9	56.1	Peak	68.2	12.1	V
8238.2	59.6	Peak	74.0	14.4	H
8238.2	41.3	Average	54.0	12.7	H
10500.5	53.7	Peak	68.2	14.5	V
16475.2	47.4	Peak	68.2	20.8	V
27457.5	52.5	Peak	68.2	15.7	V

Radiated Spurious – CH120

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
6990.2	54.7	Peak	68.2	13.5	V
8386.8	38.7	Average	54.0	15.3	H
8387.1	56.7	Peak	74.0	17.3	H
10500.5	53.9	Peak	68.2	14.3	H
11182.2	40.0	Average	54.0	14.0	H
11183.2	48.8	Peak	74.0	25.2	H

Radiated Spurious – CH140

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
8537.3	55.0	Peak	68.2	13.2	H
10500.1	54.0	Peak	68.2	14.2	H
11383.8	41.7	Average	54.0	12.3	H
11383.8	49.2	Peak	74.0	24.8	H

1 GHz – 40 GHz, 802.11ax/be20, HE0, Chain B

Radiated Spurious – CH100

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
6865.3	56.6	Peak	68.2	11.6	V
8237.5	62.5	Peak	74.0	11.5	H
8237.5	43.6	Average	54.0	10.4	H
10499.8	53.2	Peak	68.2	15.0	V
16475.7	52.9	Peak	68.2	15.3	V
27458.0	57.7	Peak	68.2	10.5	V

Radiated Spurious – CH120

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
6990.2	54.6	Peak	68.2	13.6	V
8386.8	45.4	Average	54.0	8.6	H
8387.3	57.6	Peak	74.0	16.4	H
10500.0	54.2	Peak	68.2	14.0	V
16772.9	54.8	Peak	68.2	13.4	V
22364.1	53.3	Peak	74.0	20.7	V
22366.5	40.5	Average	54.0	13.5	V

Radiated Spurious – CH140

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
1486.4	46.4	Peak	74.0	27.6	V
1486.4	37.0	Average	54.0	17.0	V
11383.3	39.4	Average	54.0	14.6	V
11383.8	45.5	Peak	74.0	28.5	V
17073.1	48.5	Peak	68.2	19.7	V
22765.8	45.9	Average	54.0	8.1	V
22767.2	55.9	Peak	74.0	18.1	V

1 GHz – 40 GHz, 802.11ax/be20, HE0, Chain A+B

Radiated Spurious – CH100

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
5251.5	57.4	Peak	68.2	10.8	V
6865.3	58.5	Peak	68.2	9.7	V
8236.8	51.0	Average	54.0	3.0	H
8237.5	65.2	Peak	74.0	8.8	H
10500.1	53.6	Peak	68.2	14.6	H
16474.2	53.4	Peak	68.2	14.8	V
27458.0	55.6	Peak	68.2	12.6	V

Radiated Spurious – CH120

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
6989.3	59.1	Peak	68.2	9.1	V
8386.6	61.5	Peak	74.0	12.5	H
8386.6	46.0	Average	54.0	8.0	H
10500.1	53.2	Peak	68.2	15.0	H
11182.7	49.2	Peak	74.0	24.8	H
11182.7	41.3	Average	54.0	12.7	H
16773.9	51.6	Peak	68.2	16.6	V
22364.6	54.4	Peak	74.0	19.6	V
22367.0	43.1	Average	54.0	10.9	V
27958.2	52.9	Peak	68.2	15.3	V

Radiated Spurious – CH140

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBµV/m	---	dBµV/m	dB	---
1486.4	52.5	Peak	74.0	21.5	V
1486.4	39.1	Average	54.0	14.9	V
11382.8	43.7	Average	54.0	10.3	H
11383.3	49.3	Peak	74.0	24.7	H
17075.0	50.1	Peak	68.2	18.1	V
22766.3	45.2	Average	54.0	8.8	V
22767.7	57.2	Peak	74.0	16.8	V

1 GHz – 40 GHz, 802.11ax/be40, HE0, Chain A

Radiated Spurious – CH102

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBµV/m	---	dBµV/m	dB	---
1295.2	46.8	Peak	74.0	27.2	V
1295.2	38.1	Average	54.0	15.9	H
11000.5	43.0	Average	54.0	11.0	H
11001.5	49.6	Peak	74.0	24.4	H
16500.8	47.5	Peak	68.2	20.7	V
27501.5	52.2	Peak	68.2	16.0	V

Radiated Spurious – CH118

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBµV/m	---	dBµV/m	dB	---
6974.9	56.5	Peak	68.2	11.7	V
8369.1	39.8	Average	54.0	14.2	H
8370.1	57.5	Peak	74.0	16.5	H
10500.5	54.2	Peak	68.2	14.0	V
11159.5	48.2	Peak	74.0	25.8	H
11161.0	40.0	Average	54.0	14.0	H
16740.5	47.7	Peak	68.2	20.5	V

Radiated Spurious – CH134

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
1455.0	46.8	Peak	74.0	27.2	H
1455.0	37.9	Average	54.0	16.1	H
11320.0	43.0	Average	54.0	11.0	H
11320.5	49.6	Peak	74.0	24.4	H
16980.8	48.8	Peak	68.2	19.4	H

1 GHz – 40 GHz, 802.11ax/be40, HE0, Chain B

Radiated Spurious – CH102

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
1294.7	48.3	Peak	74.0	25.7	V
1295.2	39.5	Average	54.0	14.5	V
5260.2	59.4	Peak	68.2	8.8	V
11000.0	50.4	Peak	74.0	23.6	V
11000.5	43.2	Average	54.0	10.8	V
16501.3	54.3	Peak	68.2	13.9	V
22001.2	51.9	Peak	68.2	16.3	V
27502.5	56.0	Peak	68.2	12.2	V

Radiated Spurious – CH118

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
5819.8	52.5	Peak	68.2	15.7	H
6975.4	58.1	Peak	68.2	10.1	V
8370.1	61.4	Peak	74.0	12.6	H
8370.5	42.4	Average	54.0	11.6	H
10499.7	53.6	Peak	68.2	14.6	V
16741.5	53.9	Peak	68.2	14.3	V
22317.7	55.8	Peak	74.0	18.2	V
22320.2	45.1	Average	54.0	8.9	V

27903.1	54.1	Peak	68.2	14.1	V
---------	------	------	------	------	---

Radiated Spurious – CH134

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
1455.0	47.1	Peak	74.0	26.9	V
1455.0	38.6	Average	54.0	15.4	V
11320.0	45.7	Peak	74.0	28.3	V
11320.9	37.8	Average	54.0	16.2	V
16979.8	51.4	Peak	68.2	16.8	V
22641.6	51.8	Peak	74.0	22.2	V
22642.0	45.8	Average	54.0	8.2	V
28302.8	55.0	Peak	68.2	13.2	V

1 GHz – 40 GHz, 802.11ax/be40, HE0, Chain A+B

Radiated Spurious – CH102

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
5260.8	58.9	Peak	68.2	9.3	V
5740.4	58.9	Peak	68.2	9.3	H
6875.5	59.4	Peak	68.2	8.8	V
8250.4	50.8	Average	54.0	3.2	H
8250.6	64.8	Peak	74.0	9.2	H
10500.3	53.8	Peak	68.2	14.4	V
11000.0	50.6	Peak	74.0	23.4	V
11000.5	44.5	Average	54.0	9.5	H
16501.8	55.9	Peak	68.2	12.3	V
22002.6	49.7	Peak	68.2	18.5	V
27501.5	57.0	Peak	68.2	11.2	V

Radiated Spurious – CH118

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dB μ V/m	---	dB μ V/m	dB	---
6975.4	58.0	Peak	68.2	10.2	V
8370.1	49.8	Average	54.0	4.2	H
8370.1	65.2	Peak	74.0	8.8	H
10500.3	54.4	Peak	68.2	13.8	V
11161.0	49.7	Peak	74.0	24.3	H
11161.0	42.2	Average	54.0	11.8	H
16740.5	53.1	Peak	68.2	15.1	V
22321.1	45.0	Average	54.0	9.0	V
22321.6	55.0	Peak	74.0	19.0	V
27903.1	52.9	Peak	68.2	15.3	H

Radiated Spurious – CH134

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dB μ V/m	---	dB μ V/m	dB	---
4245.7	48.5	Average	54.0	5.5	V
7075.9	66.7	Peak	68.2	1.5	V
11319.0	50.8	Peak	74.0	23.2	H
11320.5	44.5	Average	54.0	9.5	H
16981.7	50.7	Peak	68.2	17.5	V
22641.1	44.1	Average	54.0	9.9	V
22642.5	56.7	Peak	74.0	17.3	V
28302.8	54.6	Peak	68.2	13.6	V

1 GHz – 40 GHz, 802.11ax/be80, HE0, Chain A

Radiated Spurious – CH106

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
5028.1	56.6	Peak	74.0	17.4	V
5028.6	38.3	Average	54.0	15.7	V
6886.7	54.7	Peak	68.2	13.5	V
8262.8	58.2	Peak	74.0	15.8	H
8263.2	42.9	Average	54.0	11.1	H
10500.0	54.7	Peak	68.2	13.5	V
11016.9	42.9	Average	54.0	11.1	H
11017.4	49.4	Peak	74.0	24.6	H
16526.0	47.8	Peak	68.2	20.4	H
27546.0	51.9	Peak	68.2	16.3	V

Radiated Spurious – CH122

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
6017.5	58.0	Peak	68.2	10.2	V
6985.6	54.7	Peak	68.2	13.5	H
8382.2	40.5	Average	54.0	13.5	H
8382.3	56.4	Peak	74.0	17.6	H
10500.0	54.7	Peak	68.2	13.5	V
11175.9	47.8	Peak	74.0	26.2	H
11177.4	40.7	Average	54.0	13.3	H

Radiated Spurious – CH138

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dB μ V/m	---	dB μ V/m	dB	---
1463.7	45.2	Peak	74.0	28.8	H
1463.7	37.2	Average	54.0	16.8	H
11336.9	41.5	Average	54.0	12.5	H
11338.3	49.4	Peak	74.0	24.6	H
17005.4	48.6	Peak	68.2	19.6	H

1 GHz – 40 GHz, 802.11ax/be80, HE0, Chain B

Radiated Spurious – CH106

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dB μ V/m	---	dB μ V/m	dB	---
5160.5	57.5	Peak	68.2	10.7	V
5857.4	58.6	Peak	68.2	9.6	H
6886.2	57.5	Peak	68.2	10.7	V
8262.4	44.4	Average	54.0	9.6	H
8262.8	62.6	Peak	74.0	11.4	H
10500.0	54.1	Peak	68.2	14.1	H
11016.4	48.2	Peak	74.0	25.8	V
11016.9	41.4	Average	54.0	12.6	V
16526.4	54.6	Peak	68.2	13.6	V
22036.0	54.4	Peak	74.0	19.6	V
22036.0	43.0	Average	54.0	11.0	V
27543.0	56.8	Peak	68.2	11.4	V

Radiated Spurious – CH122

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
5160.0	58.9	Peak	68.2	9.3	V
6017.1	54.3	Peak	68.2	13.9	H
6986.0	56.7	Peak	68.2	11.5	V
8382.5	42.4	Average	54.0	11.6	H
8382.8	59.9	Peak	74.0	14.1	H
10499.8	53.6	Peak	68.2	14.6	H
16767.6	52.0	Peak	68.2	16.2	V
22354.5	53.6	Peak	74.0	20.4	V
22355.9	43.3	Average	54.0	10.7	V
27941.8	53.2	Peak	68.2	15.0	V

Radiated Spurious – CH138

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
1463.7	46.2	Peak	74.0	27.8	V
1463.7	38.2	Average	54.0	15.8	V
11336.4	46.0	Peak	74.0	28.0	V
11336.9	38.3	Average	54.0	15.7	V
17004.5	51.7	Peak	68.2	16.5	V
22674.4	47.6	Average	54.0	6.4	V
22675.4	54.3	Peak	74.0	19.7	V

1 GHz – 40 GHz, 802.11ax/be80, HE0, Chain A+B

Radiated Spurious – CH106

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
5028.6	39.7	Average	54.0	14.3	V
5029.1	56.4	Peak	74.0	17.6	V
5857.8	58.6	Peak	68.2	9.6	H
6886.2	58.1	Peak	68.2	10.1	V
8263.5	63.3	Peak	74.0	10.7	H
8263.5	50.7	Average	54.0	3.3	H
10500.0	53.8	Peak	68.2	14.4	H
11017.4	43.4	Average	54.0	10.6	H
11017.4	52.5	Peak	74.0	21.5	H
16526.0	54.6	Peak	68.2	13.6	V
22034.5	42.1	Average	54.0	11.9	V
22034.5	51.2	Peak	74.0	22.8	V
27544.0	53.9	Peak	68.2	14.3	V

Radiated Spurious – CH122

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
5160.0	56.9	Peak	68.2	11.3	V
6017.1	58.0	Peak	68.2	10.2	V
6986.0	58.7	Peak	68.2	9.5	V
8382.3	63.2	Peak	74.0	10.8	H
8382.5	46.5	Average	54.0	7.5	H
10500.3	53.5	Peak	68.2	14.7	V
11175.9	49.8	Peak	74.0	24.2	H
11176.9	42.6	Average	54.0	11.4	H
16766.7	53.6	Peak	68.2	14.6	V
22353.5	56.1	Peak	74.0	17.9	V
22355.0	44.8	Average	54.0	9.2	V
27942.3	53.9	Peak	68.2	14.3	V

Radiated Spurious – CH138

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
5428.4	41.5	Average	54.0	12.5	V
5428.8	57.4	Peak	74.0	16.6	V
5908.9	54.8	Peak	68.2	13.4	V
8503.7	59.9	Peak	68.2	8.3	H
10500.1	53.8	Peak	68.2	14.4	V
11336.4	51.2	Peak	74.0	22.8	H
11337.4	43.0	Average	54.0	11.0	H
17005.9	51.0	Peak	68.2	17.2	V
22675.4	55.5	Peak	74.0	18.5	V
22675.4	48.5	Average	54.0	5.5	V
28344.9	53.1	Peak	68.2	15.1	V

1 GHz – 40 GHz, 802.11ax/be160, HE0, Chain A

Radiated Spurious – CH114

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
6896.4	55.6	Peak	68.2	12.6	V
8275.6	58.2	Peak	74.0	15.8	H
8275.9	41.6	Average	54.0	12.4	H
10500.0	53.3	Peak	68.2	14.9	H
11033.8	48.8	Peak	74.0	25.2	H
11033.8	42.4	Average	54.0	11.6	H
16552.0	47.8	Peak	68.2	20.4	H

1 GHz – 40 GHz, 802.11ax/be160, HE0, Chain B

Radiated Spurious – CH114

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
5160.0	56.5	Peak	68.2	11.7	V
5874.1	58.0	Peak	68.2	10.2	V
6896.4	56.2	Peak	68.2	12.0	V
8275.7	59.9	Peak	74.0	14.1	H
8276.0	42.6	Average	54.0	11.4	H
10500.3	53.9	Peak	68.2	14.3	V
11032.9	47.8	Peak	74.0	26.2	V
11034.3	39.5	Average	54.0	14.5	V
16549.6	54.3	Peak	68.2	13.9	V
22067.8	52.6	Peak	74.0	21.4	V
22067.8	44.7	Average	54.0	9.3	V
27586.1	55.0	Peak	68.2	13.2	V


1 GHz – 40 GHz, 802.11ax/be160, HE0, Chain A+B


Radiated Spurious – CH114

Frequency	Level	Detector	Limit	Margin	Polar
MHz	dBμV/m	---	dBμV/m	dB	---
5874.1	58.5	Peak	68.2	9.7	H
6896.9	57.3	Peak	68.2	10.9	V
8275.4	45.5	Average	54.0	8.5	H
8275.7	62.9	Peak	74.0	11.1	H
10500.1	53.1	Peak	68.2	15.1	V
11034.3	44.2	Average	54.0	9.8	H
11034.3	50.7	Peak	74.0	23.3	H
16551.1	54.7	Peak	68.2	13.5	V
22067.8	51.7	Peak	74.0	22.3	V
22067.8	44.4	Average	54.0	9.6	V
27585.1	54.5	Peak	68.2	13.7	V


B.3 Test Results Screenshots

B.3.1 26dB & 99% Bandwidth






SISO A-802.11ac-160MHz-114-5570-VHT0 -26dB



SISO A-802.11ax/be-160MHz-114-5570-MCS0 99%

B.3.2 Maximum Output Power & Maximum power spectral Density


Ref Level 15.00 dBm Att 25 dB RBW 1 MHz SWT 5 s VBW 3 MHz Mode Auto Sweep SGL Count 1/1 TDF IRm AvgPwr CF 5.6 GHz 500 pts Span 38.5 MHz Channel Power Bandwidth 18.93 MHz Power 20.14 dBm Tx Total 20.14 dBm Date: 26 JUN 2024 09:50:14	
SISO B-802.11ax/be-20MHz-Ch120-5600MHz-MCS0 Ref Level 15.00 dBm Att 25 dB RBW 1 MHz SWT 1 ms VBW 3 MHz Mode Auto Sweep SGL Count 100/100 TDF IRm AvgPwr CF 5.59 GHz 500 pts Span 76.1 MHz Channel Power Bandwidth 37.44 MHz Power 21.84 dBm Tx Total 21.84 dBm Date 3 JUN 2024 10:03	
SISO B-802.11ax/be-40MHz-Ch118-5590MHz-MCS0 Ref Level 15.00 dBm Att 25 dB RBW 1 MHz SWT 1 ms VBW 3 MHz Mode Auto Sweep SGL Count 100/100 TDF IRm AvgPwr CF 5.61 GHz 500 pts Span 153.0 MHz Channel Power Bandwidth 75.12 MHz Power 18.66 dBm Tx Total 18.66 dBm Date 4 JUN 2024 15:25	Ref Level 15.00 dBm Att 25 dB RBW 1 MHz SWT 1 ms VBW 3 MHz Mode Auto Sweep SGL Count 100/100 TDF IRm AvgPwr CF 5.61 GHz 500 pts Span 153.0 MHz Channel Power Bandwidth 75.00 MHz Power 18.89 dBm Tx Total 18.89 dBm Date 3 JUN 2024 14:53
MIMO A -802.11ac-80MHz-Ch122-5610MHz-VHT0	MIMO B-802.11ac-80MHz-Ch122-5610MHz-VHT0




SISO B-802.11ax/be-160MHz-Ch114-5570MHz-MCS0
80m/S67

B.3.3 Undesirable emission limits : out of band (Conducted)


SISO A




BE-R-LOW, SISO-A, 802.11a20-6Mbps, Ch100




BE-NR-LOW, SISO-A, 802.11a20-6Mbps, Ch100




BE-NR-HIGH, SISO-A, 802.11a20-6Mbps, Ch140




BE-R-LOW, SISO-A, 802.11n20-HT0, Ch100




BE-NR-LOW, SISO-A, 802.11n20-HT0, Ch100




BE-NR-HIGH, SISO-A, 802.11n20-HT0, Ch140




BE-R-LOW, SISO-A, 802.11n40-HT0, Ch102




BE-NR-LOW, SISO-A, 802.11n40-HT0, Ch102




BE-NR-HIGH, SISO-A, 802.11n40-HT0, Ch134




BE-R-LOW, SISO-A, 802.11ac80-VHT0, Ch106




BE-NR-LOW, SISO-A, 802.11ac80-VHT0, Ch106




BE-NR-HIGH, SISO-A, 802.11ac80-VHT0, Ch122




BE-R-LOW, SISO-A, 802.11ac160-VHT0, Ch114




BE-NR-LOW, SISO-A, 802.11ac160-VHT0, Ch114




BE-NR-HIGH, SISO-A, 802.11ac160-VHT0, Ch114




BE-R-LOW, SISO-A, 802.11ax/be20-MCSO, Ch100



BE-NR-LOW, SISO-A, 802.11ax/be20-MCSO, Ch100




BE-NR-HIGH, SISO-A, 802.11ax/be20-MCSO, Ch140




DeLUNA 1212

BE-R-LOW, SISO-A, 802.11ax/be40-MCSO, Ch102




DeLUNA 1212

BE-NR-LOW, SISO-A, 802.11ax/be40-MCSO, Ch102




DeLUNA 1220

BE-NR-HIGH, SISO-A, 802.11ax/be40-MCSO, Ch134




DeLUNA 1213

BE-R-LOW, SISO-A, 802.11ax/be80-MCSO, Ch106




DeLUNA 1215

BE-NR-LOW, SISO-A, 802.11ax/be80-MCSO, Ch106




DeLUNA 1220


BE-NR-HIGH, SISO-A, 802.11ax/be80-MCSO, Ch122



BE-R-LOW, SISO-A, 802.11ax/be160-MCSO, Ch114




BE-NR-LOW, SISO-A, 802.11ax/be160-MCSO, Ch114




BE-NR-HIGH, SISO-A, 802.11ax/be160-MCSO, Ch114


SISO B




BE-R-LOW, SISO-B, 802.11a20-6Mbps, Ch100




BE-NR-LOW, SISO-B, 802.11a20-6Mbps, Ch100




BE-NR-HIGH, SISO-B, 802.11a20-6Mbps, Ch140




BE-R-LOW, SISO-B, 802.11n20-HT0, Ch100




BE-NR-LOW, SISO-B, 802.11n20-HT0, Ch100




BE-NR-HIGH, SISO-B, 802.11n20-HT0, Ch140




BE-R-LOW, SISO-B, 802.11n40-HT0, Ch102




BE-NR-LOW, SISO-B, 802.11n40-HT0, Ch102




BE-NR-HIGH, SISO-B, 802.11n40-HT0, Ch134




BE-R-LOW, SISO-B, 802.11ac80-VHT0, Ch106




BE-NR-LOW, SISO-B, 802.11ac80-VHT0, Ch106




BE-NR-HIGH, SISO-B, 802.11ac80-VHT0, Ch122




BE-R-LOW, SISO-B, 802.11ac160-VHT0, Ch114




BE-NR-LOW, SISO-B, 802.11ac160-VHT0, Ch114




BE-NR-HIGH, SISO-B, 802.11ac160-VHT0, Ch114




BE-R-LOW, SISO-B, 802.11ax/be20-MCSO, Ch100




BE-NR-LOW, SISO-B, 802.11ax/be20-MCSO, Ch100



BE-NR-HIGH, SISO-B, 802.11ax/be20-MCSO, Ch140



BE-R-LOW, SISO-B, 802.11ax/be40-MCSO, Ch102



BE-NR-LOW, SISO-B, 802.11ax/be40-MCSO, Ch102