

Annex E. TSL Dielectric Parameters

E.1 Head WiFi 6E 7000MHz

Freq.(MHz)	Target		2024-02-26	
	$\epsilon'(F/m)$	$\sigma(S/m)$	$\epsilon'1(F/m)$	$\sigma1(S/m)$
6000.0	35.07	5.48	33.38	5.26
6050.0	35.01	5.54	33.29	5.33
6100.0	34.95	5.59	33.20	5.39
6150.0	34.89	5.65	33.11	5.45
6200.0	34.83	5.71	33.02	5.51
6250.0	34.77	5.77	32.94	5.58
6300.0	34.70	5.83	32.87	5.65
6350.0	34.64	5.89	32.78	5.72
6400.0	34.58	5.95	32.69	5.79
6450.0	34.52	6.01	32.61	5.87
6500.0	34.46	6.07	32.52	5.92
6550.0	34.40	6.13	32.42	5.98
6600.0	34.34	6.19	32.32	6.04
6650.0	34.29	6.25	32.22	6.10
6700.0	34.23	6.30	32.15	6.15
6750.0	34.17	6.36	32.08	6.2
6800.0	34.11	6.42	32.00	6.25
6850.0	34.05	6.48	31.92	6.30
6900.0	33.99	6.53	31.86	6.35
6950.0	33.94	6.59	31.77	6.41
7000.0	33.88	6.65	31.66	6.47

