
GSM1900 test report for RM-1

CONTENTS

1	LABORATORY INFORMATION	3
2	CUSTOMER INFORMATION	3
3	SUMMARY OF TEST RESULTS.....	4
4	EUT INFORMATION.....	5
4.1	EUT description	5
5	EUT TEST SETUPS	5
6	APPLICABLE STANDARDS.....	5
7	BANDEDGE COMPLIANCE.....	6
7.1	Test setup	6
7.2	EUT operation mode.....	6
7.3	Limit	6
7.4	Results	7
7.5	Screen shots	7
8	SPURIOUS RADIATED EMISSION	10
8.1	Test setup	10
8.2	Test method	10
8.3	EUT operation mode.....	11
8.4	Limit	11
8.5	Results	11
9	TEST EQUIPMENT	13
9.1	Conducted measurements	13
9.2	Radiated measurements	13

Tampere

1 LABORATORY INFORMATION

Test laboratory:	TCC Tampere Sinitaival 5 FIN-33720 TAMPERE Tel. +358 7180 46800 Fax. +358 7180 46880
FCC registration number: IC file number:	94436 (June 14, 2002) IC 3608 (March 5, 2003)

2 CUSTOMER INFORMATION

Client:	TCC Tampere Sinitaival 5 FIN-33720 TAMPERE Tel. +358 7180 46800 Fax. +358 7180 46880
Contact person:	Tero Huhtala
Receipt of EUT:	22.11.2004
Date of testing:	24-25.11.2004
Date of report:	25.11.2004

The tests listed in this report have been done to demonstrate compliance with the applicable requirements in FCC rules Part 24 and IC standard RSS-133.

Contents approved:


Jan-Erik Lilja Senior Test Engineer

3 SUMMARY OF TEST RESULTS

Section in CFR 47	Section in RSS-133	Test	Result
§2.1046 (a)	6.2	Conducted RF output power	-
§24.232 (b)	6.2	Radiated RF output power	-
§2.1049 (h)	5.6	99% occupied bandwidth	-
§24.238 (a)	6.3	Bandedge compliance	PASS
§24.238 (a), §2.1051	6.3	Spurious emissions at antenna terminals	-
§24.238 (a), §2.1053	6.3	Radiated spurious emissions	PASS
§24.235, §2.1055 (a)(1)(b)	7	Frequency stability, temperature variation	-
§24.235, §2.1055 (d)(1)(2)	7	Frequency stability, voltage variation	-

4 EUT INFORMATION

The EUT and accessories used in the tests are listed below. Later in this report only EUT numbers are used as reference.

	Device	Type	S/N	HW	SW	EUT number
EUT	GSM mobile phone	RM-1	004400271747642	4100	2.39.141	40127
Accessories	Battery	BL-5C	L271720303988	-	-	40128

Notes: -

4.1 EUT description

The EUT is a triple band (GSM 900/1800/1900 EGPRS) mobile phone

The EUT was not modified during the tests.

5 EUT TEST SETUPS

For each test the EUT was exercised to find out the worst case of operation modes and device configuration

6 APPLICABLE STANDARDS


The tests were performed in guidance of CFR 47 part 24, part 2, ANSI/TIA/EIA-603-A and RSS-133. Deviations, modifications or clarifications (if any) to above mentioned documents are written in each section under "Test method" for each test case.

7 BANDEDGE COMPLIANCE

EUT	40127		
Accessories	40128		
Temp, Humidity, Air Pressure	21 °C	48 RH%	1005 mbar
Date of measurement	25.11.2004		
FCC rule part	§24.238 (a)		
RSS-133 section	6.3		
Measured by	Jari Jantunen		
Result	PASS		

7.1 Test setup

The BS simulator was used to set the TX channel and power level and modulate the TX signal with different bit patterns.



7.2 EUT operation mode

EUT operation mode	GSM, TX on, 1 time slot, PRBS 2E9-1 modulation data EGPRS, TX on, 1 time slot, PRBS 2E9-1 modulation data
EUT channel	See section 7.4
EUT TX power level	Maximum

7.3 Limit


Frequency [MHz]	Level [dBm]
<1850 or 1910<	-13

7.4 Results

The line in the screen shots is the -13dBm limit line. The results were corrected with measurement path loss set as "offset" in the spectrum analyzer. RBW/VBW was 3kHz.



EUT Channel	EUT operation mode	Level [dBm]
512	GSM	-17.07
810	GSM	-14.88
512	EGPRS	-16.89
810	EGPRS	-15.47

7.5 Screen shots




Picture 1 Lower bandedge, channel 512, GSM

Tampere

**Picture 2 Lower bandedge, channel 512, GSM****Picture 3 Lower bandedge, channel 512, EGPRS**

Tampere


**Picture 4 Lower bandedge, channel 810, EGPRS**

8 SPURIOUS RADIATED EMISSION

EUT	40127		
Accessories	40128		
Temp, Humidity, Air Pressure	21 °C	48 RH%	1005..1029 mbar
Date of measurement	24-25.11.2004		
FCC rule part	§24.238 (a), §2.1053		
RSS-133 section	6.3		
Measured by	Jari Jantunen		
Result	PASS		

8.1 Test setup

A set of LP/HP/BS filters was used to prevent overloading the spectrum analyzer. The BS simulator was used to set the TX channel and power level and modulate the TX signal with different bit patterns. The test was done using an automated test system, where the measurement devices were controlled by a computer.



8.2 Test method

- The emissions were searched and maximized by moving the turn table and measuring antenna and manipulating the EUT.
- All suspicious frequencies with emission levels were recorded.
- The EUT was replaced with a substituting antenna.
- For each frequency recorded, the substituting antenna was fed with the power (from signal generator) giving the same reading as in (b). These power levels were reported.

8.3 EUT operation mode

EUT operation mode	GSM, TX on, 1 time slot, PRBS 2E9-1 modulation data EGPRS, TX on, 1 time slot, PRBS 2E9-1 modulation data
EUT channel	661
EUT TX power level	Maximum

8.4 Limit

Frequency [MHz]	Level [dBm]
30 – 19100	-13

8.5 Results

The formula below was used to calculate the EIRP of the spurious emissions. If there were no emissions closer than 20dB below the limit line, then the emission levels were measured at the transmitter's harmonics.

$$P_{Emission[dBm]} = P_{SubstTX[dBm]} - L_{Cable[dB]} + G_{Antenna[dBi]}$$

where the variables are as follows:

$P_{Measured}$ [dBm]	Measured emission level (from step b in 8.2)
P_{Subst_TX} [dBm]	Signal generator power (from step d in 8.2) fed to the substituting antenna
L_{Cable} [dB]	Loss of the cable between antenna and signal generator (from step d in 8.2)
$G_{Antenna}$ [dBi]	Gain of the substitutive antenna over isotropic radiator

Table 1 Emission levels, channel 661, GSM

Frequency [MHz]	P _{Measured} [dBm]	P _{Subst TX} [dBm]+L _{Cable} [dB]+G _{Antenna} [dBi]	P _{Emission} [dBm]
1804.93	-42.60	2.10	-44.70
3760,02	-50.3	-9.40	-40.90

Table 2 Emission levels, channel 661, EGPRS

Frequency [MHz]	P _{Measured} [dBm]	P _{Subst TX} [dBm]+L _{Cable} [dB]+G _{Antenna} [dBi]	P _{Emission} [dBm]
3760,02	-49.0	-9.40	-39.60

9 TEST EQUIPMENT

Each test equipment is calibrated once a year.

9.1 Conducted measurements

Equipment	Manufacturer	Model
Spectrum analyzer	Rohde & Schwarz	FSU
Radio communication tester	Rohde & Schwarz	CMU-200
Attenuator 10 dB	Huber+Suhner AG	6251.17.A
Step attenuator 110dB	Hewlett-Packard	8496A
Power splitter	Hewlett-Packard	11667A
High pass filter	Trilithic	WHK2010-10SS
Low pass filter	Trilithic	WLK1750-10SS
Tunable notch filter	Wainwright	WRCD1850/1910-0.2/40
Temperature chamber	Vötsch	VT4002
DC power supply	HP	6632A
Multimeter	Fluke	87

9.2 Radiated measurements

Equipment	Manufacturer	Model
3m semi-anechoic chamber	TDK	
EMI receiver	Rohde & Schwarz	ESI 40
Preamplifier	MITEQ	AMF-5D-020180-26-10P
Preamplifier	MITEQ	AMF-4D-10M-3G-25-20P
Dipole antenna	EMCO	3125-870
Dipole antenna	EMCO	3125-1880
Biconilog antenna	Rohde & Schwarz	HL562
Double ridged waveguide antenna	EMCO	3115
Double ridged waveguide antenna	EMCO	3115
Horn antenna	EMCO	3116
Reference dipole set	Schwarzbeck	UHAP/VHAP

Communication antenna	EMC Automation	LPA-8020
Radio communication tester	Rohde & Schwarz	CMU-200
Signal generator	Hewlett-Packard	83640L
Step attenuator 110dB	Hewlett-Packard	8496A
Power splitter	Hewlett-Packard	11667A
High pass filter	Trilithic	WHK2010-10SS
Low pass filter	Trilithic	WLK1750-10SS
Tunable notch filter	Wainwright	WRCD1850/1910-0.2/40
Turntable controller	Deisel	HD-100
Turntable	Deisel	DS412
Antenna mast controller	EMCO	2090
Antenna mast	EMCO	2075
Temperature chamber	Vötsch	VT4002
DC power supply	Hewlett-Packard	6632A
Multimeter	Fluke	87