

Electromagnetic Emission

FCC MEASUREMENT REPORT

CERTIFICATION OF COMPLIANCE

FCC Part 15 Certification Measurement

PRODUCT : SETTOP BOX
MODEL/TYPE NO : DMS2004UHD W / EVY703P08971
FCC ID : PFNDMS2004UHDW
MULTIPLE MODEL : WC10HD, DMS2204UHD W, DMS2004UHDW, DMS2204UHDW
BRAND NAME : -
APPLICANT : Digital Multimedia Technology Co., Ltd.
8F Seongam Bldg, 710 Eonju-ro, Gangnam-gu,
Seoul, 06058, South Korea
Attn.: Jung Hwan Lee / Senior Research Engineer
MANUFACTURER : Hengdi Digital Technology (Shen Zhen) Co., Ltd.
A.B Building, Xin Shi Qiao Guanjie Industrial Park, Guihua Community,
Guanlan Street, Bao'an District, Shenzhen City, Guangdong Province,
China, 518-110
FCC CLASSIFICATION : HID - Part 15 TV Interface Device
RULE PART(S) : FCC Part 15 Subpart B
TEST PROCEDURE : ANSI C63.4-2014
TEST REPORT No. : ETLE171130.1127
DATES OF TEST : December 18, 2017 to December 22, 2017
REPORT ISSUE DATE : January 10, 2018
TEST LABORATORY : ETL Inc. (FCC Designation Number: KR0022)

This SETTOP BOX, Model DMS2004UHD W has been tested in accordance with the measurement procedures specified in ANSI C63.4-2014 at the ETL/EMC Test Laboratory and has been shown to be complied with the electromagnetic radiated emission limits specified in FCC Rule Part15 Subpart B:

I attest to the accuracy of data. All measurement herein was performed by me or was made under my supervision and is correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

The results of testing in this report apply to the product/system which was tested only. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Prepared by:

Chul Min, Ji (Test Engineer)

January 10, 2018

Reviewed by:

Hyung Min, Choi (Chief Engineer)

January 10, 2018

ETL Inc.

Head office: #371-51, Gasan-dong, Geumcheon-gu, Seoul, 153-803, Korea

Open site: #499-1, Sagot-ri, Seosin-myeon, Hwaseong-si, Gyeonggi-do, 445-882, Korea

Tel: 82-2-858-0786 Fax: 82-2-858-0788

The test report merely corresponds to the test sample(s).

This report shall not be reproduced, in whole or in part without the written approval of ETL Inc.

Table of Contents

FCC Measurement Report

- 1. Introduction**
- 2. Product Information**
- 3. Description of Tests**
- 4. Test Condition**
- 5. Test Results**
 - 5.1 Summary of Test Results**
 - 5.2 AC Power line Conducted Emissions Measurement**
 - 5.3 Radiated Emissions Measurement**
 - 5.4 Antenna Power Conduction Measurement**
 - 5.5 Output Signal Level Measurement**
 - 5.6 Output Terminal Conducted Spurious Emission Measurement**
 - 5.7 Antenna Transfer Switch Measurement**
- 6. Sample Calculation**
- 7. List of test Equipment used for Measurement**

Appendix B. Test Setup Photographs

FCC MEASUREMENT REPORT

Scope – Measurement and determination of electromagnetic emission(EME) of radio frequency devices including intentional radiators and/or unintentional radiators for compliance with the technical rules and regulations of the U.S Federal Communications Commission(FCC)

General Information

Applicant Name : Digital Multimedia Technology Co., Ltd.

Address : 8F Seongam Bldg, 710 Eonju-ro, Gangnam-gu,
Seoul, 06058, South Korea

Attention : Jung Hwan Lee / Senior Research Engineer

- **EUT Type :** SETTOP BOX
- **Model Number :** DMS2004UHD W
- **S/N :** EVY703P08971
- **Rule Part(s) :** FCC Part 15 Subpart B
- **Test Procedure :** ANSI C63.4-2014
- **FCC Classification :** HID - Part 15 TV Interface Device
- **Dates of Tests :** December 18, 2017 to December 22, 2017
- **Environmental of Tests:**
 - Temperature: (12.3 ± 9.2) °C
 - Humidity: (60 ± 20) % R.H.
 - Atmospheric Pressure: (101.8 ± 0.7) kPa
- **Place of Tests :** ETL Inc. Testing Lab. (FCC Designation Number : KR0022)
 - Radiated Emission test 1;
#499-1, Sagot-ri, Seosin-myeon, Hwaseong-si,
Gyeonggi-do, 445-882, Korea
 - Radiated Emission test 2 and Conducted Emission test;
#371-51, Gasan-dong, Geumcheon-gu, Seoul, 153-803, Korea
- **Test Report No. :** ETLE171130.1127

1. INTRODUCTION

The measurement tests for radiated and conducted emission test were conducted at the ETL Inc. The site is constructed in conformance with the requirements of the ANSI C63.4-2014 and CISPR Publication 16. The ETL has site descriptions on file with the FCC for 3 m and 10 m site configurations. Detailed description of test facility was found to be in compliance with the requirements of Section 2.948 FCC Rules according to the ANSI C63.4-2014 and registered to the Federal Communications Commission (FCC Designation Number : KR0022).

The measurement procedure described in American National Standard for Method of Measurement of Radio-Noise Emission from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz (ANSI C63.4-2014) was used in determining radiated and conducted emissions from the Digital Multimedia Technology Co., Ltd., Model: DMS2004UHD W.

2. PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the SETTOP BOX (model: DMS2004UHD W).

The model DMS2004UHD W is basic model that was tested.

The multi models WC10HD, DMS2204UHD W, DMS2004UHDW and DMS2204UHDW are identical to basic model, except for model designation.

The AC/DC Adapter was added. And, it was tested again.

(Add test report ETLE171130.1127 issued on January 10, 2018 to previously published test report ETLE171103.1025 on January 08, 2018.)

AC/DC Adapter types may be used the one of four type selected by manufacturer.

Model name of AC/DC Adapter	View of AD/DC Adapter		
EDF0500150A1BA (Before)			
CYUS15-050150 (Before)			
V03J0500150HU (Before)			
CYUS15-050150D (Addition)			

2.2 General Specification

Favorite channel, Parental Lock
Automatic search for newly added transponder (Network Auto Search)
Stores up to 5 000 channels
Plug-and-play data transfer system (DSR to DSR)
Timer function, automatically turns On/Off by setting function (daily, weekly, monthly and one time)
Automatic reserved channel moving system
Provide Electronic program Guide (EPG)
PAL/NTSC automatically conversion
Last channel automatically saving
Support RF4CE application
RF4CE Frequency range: 2 425 MHz ~ 2 475 MHz
Support for various video output: HDMI, RF 3/4 Mod.
HDMI 1.3a with HDCP 1.1
US3/4 Channel
MPEG-2 / MPEG-4 Part 10 / H.264
Video Display format with NTSC/480p/576p/720p/1 080i
Dolby Digital AC3
RF input frequency range: 105 MHz to 1 002 MHz
High Internal Frequency: X-tal → 54 MHz

3. DESCRIPTION OF TESTS

3.1 AC Power line Conducted Emission Measurement

AC Power line Conducted emissions measurements were made in accordance with section 12, "Measurement of unintentional radiators other than ITE" of ANSI C63.4-2014. The measurements were performed over the frequency range of 0.15 MHz to 30 MHz using a 50 Ω /50 μ H LISN as the input transducer to a Spectrum Analyzer or a Test Receiver. The measurements were made with the detector set for "Peak" amplitude within a bandwidth of 9 kHz or for "quasi-peak" within a bandwidth of 9 kHz.

The line-conducted emission test is conducted inside a shielded anechoic chamber room with 1 m x 1.5 m x 0.8 m wooden table which is placed 40 cm away from the vertical wall and 1.5 m away from the side wall of the chamber room. Two LISN are bonded to the shielded room. The EUT is powered from the LISN and the support equipment is powered from the other LISN. Powers to the LISNs are filtered by a noise cut power line filters. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and these supply lines will be connected to the LISN.

Non-inductive bundling to a 1 m length shortened all interconnecting cables more than 1 m. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the EMI Test Receiver to determine the frequency producing the maximum emission from the EUT. The frequency producing the maximum level was reexamined using to set Quasi-Peak mode by manual, after scanned by automatic Peak mode from 0.15 MHz to 30 MHz. The bandwidth of the spectrum analyzer was set to 9 kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission.

Photographs of the worst-case emission can be seen in photographs of conducted emission test setup in Appendix B.

3.2 Radiated Emission Measurement

Radiated emission measurements were made in accordance with section 12, "Measurement of unintentional radiators other than ITE" of ANSI C63.4-2014. The measurements were performed over the frequency range of 30 MHz to 40 GHz (or 5th harmonic of the highest frequency) in using antenna as the input transducer to a spectrum analyzer or a field intensity meter. The measurements below 1 GHz were made with the detector set for "Quasi-peak" within a bandwidth of 120 kHz. The measurements above 1 GHz were made with the detector set for "Peak and Average" within a bandwidth of 1 MHz.


Preliminary measurements were made at 3 m using broadband antennas, and spectrum analyzer to determined the frequency producing the maximum emission in shielded room. Appropriate precaution was taken to ensure that all emission from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth and height with respect to the antenna were noted for each frequency found. The spectrum was scanned from 30 MHz to 1 000 MHz using Log-Bicon antenna. Above 1 GHz, linearly polarized double ridge horn antennas were used. Final measurements were made open site or SVSWR chamber at 3 m. The test equipment was placed on a styrofoam table. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. Each frequency found during pre-scan measurements was re-examined by manual. The EUT, support equipment and interconnecting cables were re-configured to the set-up producing the maximum emission for the frequency and were placed on top of a 0.8 m high nonmetallic 1 m x 1.5 m table. The EUT, support equipment, and interconnecting cables were re-arranged and manipulated to maximize each emission. The turntable containing the system was rotated; the antenna height was varied 1 m to 4 m and stopped at the azimuth or height producing the maximum emission. Each emission was maximized by: varying the mode of operation to the EUT and/or support equipment and changing the polarity of the antenna, whichever determined the worst-case emission.

Photographs of the worst-case emission can be seen in Photographs of the worst-case emission test setup can be seen in Appendix B.

3.3 Antenna Power Conducted Measurements

Power on the receive antenna terminals was to be determined by measurement of the voltage present at these terminals. An antenna-conducted power measurement is performed with the EUT antenna terminals connected directly to a spectrum analyzer, if the antenna impedance matches the impedance of the measuring instrument. Otherwise, use an impedance-matching network to connect the measuring instrument to the antenna terminals of the EUT. Losses in decibels in any impedance-matching network used are added to the measured value in dBμV.

With the EUT tuned to one of the frequency over which device operates, measure both the frequency and voltage present at the antenna input terminals over the frequency range specified in the individual equipment requirements. Repeat this measurement with the receiver tuned to another frequency until the numbers of frequencies specified have been successively measured. Power on the receive antenna terminals is the ratio of V^2/R , where V is the loss-corrected voltage measured at the antenna terminals, and R is the impedance of the measuring instrument.




3.4 Output Signal Conducted Level Measurement

The output signal level is the maximum voltage level present at the output terminals of the EUT on a particular frequency during normal use of the device.

The signal level was measured by direct connection to the spectrum analyzer with 50 ohm/75 ohm matching transformer between the spectrum analyzer and the TV interface device. The RF output signal level measured was the highest RF level present at the output terminals during normal use of the device. Measurements were made of the levels of both the visual and audio carrier for each TV channel (3 and 4) on which the device operates. The Satellite Receiver was supported between the EUT and the measuring instrument in a straight horizontal line so it had at least 75 cm clearance from any conducting surface.

The EUT is provided with a typical signal consistent with normal operation. For each channel on which the EUT operates and in each mode in which the device operates, the video and audio carrier level is measured and recorded.


The voltage corresponding to the peak envelope power of the video modulated signal during maximum amplitude peaks across a resistance (R ohms) matching the rated output impedance of the device, must not exceed $692.8 R^{1/2} \mu V$ for all other TV interface device. The voltage corresponding to peak envelope power of the audio modulated signal, if provided by the TV interface device, must not exceed $155 R^{1/2} \mu V$ for Cable Receiver system terminal device of TV interface device used with a master antenna, and $77.5 R^{1/2} \mu V$ for all other TV interface device. Losses in decibels in any impedance-matching network used were added to the measured value in dB μV . The EUT was configured in accordance with ANSI C63.4-2014 Section 12.2 as below configuration block diagram.



3.5 Output Terminal Conducted Spurious Emission Measurement

The RF output signal was fed to the TV receiver via coaxial Satellite Receiver. Measurements were made by direct connection to the spectrum analyzer and TV interface device with 50 ohm/75 ohm matching transformer. The frequency range 30 MHz to 1 000 MHz was investigated for significant emission.

The maximum RMS voltage of any emission appearing on frequencies removed by more than 4.6 MHz below and 7.4 MHz above the video carrier frequency on which the TV interface device is operated must not exceed $692.8 R^{1/2} \mu V$ for Cable Receiver system terminal device or TV interface device used with a master antenna and $10.95 R^{1/2} \mu V$ for all other TV interface device when terminated with a resistance (R ohms) matching the rated output impedance of the TV interface device. The EUT was configured in accordance with ANSI C63.4-2014 Section 12.2 as below configuration block diagram.




3.6 Antenna Transfer Switch Measurement

Isolation was measured for all positions of an antenna transfer switch on all output channels of the EUT. TV interface device transfer switch isolation is the difference the levels of a signal going into one antenna input port of the switch and that of the same signal coming out of another antenna terminal of transfer switch. The isolation of an antenna transfer switch equipped with coaxial connector performed by measuring the maximum voltage of the visual carrier. Measurements were made of the maximum RMS voltage at the antenna input terminals of the switch for all positions of the transfer switch. The maximum voltage corresponds to the peak envelope power of the video signal during maximum amplitude peaks. In either position of the receiver transfer switch, the maximum voltage at the receiving antenna input terminals of the switch when terminated with a resistance (R ohms) matching the rated impedance of the antenna input of the switch, must not exceed $0.346 R^{1/2} \mu V$.

The maximum voltage corresponds to the peak envelope power of the video modulated signal during maximum amplitude.

The EUT was configured in accordance with ANSI C63.4-2014 Section 12.2 as below configuration block diagram. And the EUT configuration can also be seen in Appendix B. Photographs of the test setup.

The unused RF input/output terminals are terminated in proper impedance. The antenna input terminal is connected to the input of preamplifier through the matching transformer coaxial Satellite Receiver. And the output of preamplifier is connected to the spectrum analyzer. Then, the signal level on the antenna input terminal is measured under the EUT condition produced the maximum signal level.



4. TEST CONDITION

4.1 Test Configuration

The device was configured for testing in a typical fashion (as a customer would normally use it). During the tests, the EUT and the supported equipments were installed to meet FCC requirement and operated in a manner which tends to maximize its emission level in a typical application.

4.2 EUT operation

The EUT was set to the normal receiving mode in a TV mode during all the testing in a manner similar to a typical use. For the EUT operation, the satellite live signal was fed to the EUT through the LNB input. During the preliminary testing, the worst case condition of the operating mode was ch.3


4.3 Support Equipment Used

Description	Model Name	Serial No.	Manufacturer	FCC
Adapter (for EUT)	CYUS15-050150D	0104117460011 584	COMCAST	-
Remote Control Unit (for EUT)	NONE	NONE	NONE	-
LED LCD TV	M2380DM	203KCY Q 8V226	LG Electronics	-
Adapter (for LED LCD TV)	PA-1650-68	OC17N612314 032598	Lite-On Technology Corporation	-

4.4 Type of Cables Used

Device from	Device to	Type of I/O port	Length[m]	Type of shield	Used ferrite core
EUT	LED LCD TV	HDMI	1.5	Shielded	X
EUT	LED LCD TV	TV OUT	> 3.0	Shielded	X
EUT	Cable ANT.	Cable Tuner	> 3.0	Shielded	X
EUT	Adapter	DC Input	1.2	Shielded	X
LED LCD TV	Adapter	DC Input	1.2	Shielded	O

4.5 The setup drawing(s)



5. TEST RESULTS

5.1 Summary of Test Results

The measurement results were obtained with the EUT tested in the conditions described in this report. Detailed measurement data and plots showing the maximum emission of the EUT are reported.

FCC Rule	Measurement Required	Result
15.107(a)	AC Power line Conducted Emission Measurement	Passed by 8.58 dB
15.109(a)	Radiated Emission Measurement (Below 1 GHz)	Passed by 5.73 dB
15.109(a)	Radiated Emission Measurement (Above 1 GHz)	Passed by 15.69 dB
15.111(a)	Antenna Power Conduction Measurement	Passed by 9.00 dB
15.115(b)(1)(i)	Output Signal Level Measurement	Passed by 0.53 dB
15.115(b)(2)(ii)	Output Terminal Conducted Spurious Emission Measurement	Passed by 0.80 dB
15.115(c)(1)(ii)	Antenna Transfer Switch Measurement	Passed *

* During this test, no signal detected.

The data collected shows that the **Digital Multimedia Technology Co., Ltd. / SETTOP BOX / DMS2004UHD W** complied with technical requirements of above rules part 15.107(a) and 15.109(a), 15.111 and 15.115(b),(c) Limits.

The equipment is not modified anything, mechanical or circuits to improve EMI status during a measurement. No EMI suppression device(s) was added and/or modified during testing.

5.2 AC Power line Conducted Emissions Measurement

5.2.1 AC Power line Conducted Emissions Data

EUT	SETTOP BOX / DMS2004UHD W (S/N: EVY703P08971)
Limit apply to	FCC Part 15 Subpart B Section 15.107(a) Class B
Test Date	December 22, 2017
Environmental of Test	(21.4 ± 0.0) °C, (40 ± 0) % R.H., (101.1 ± 0.0) kPa
Operating Condition	TV Mode (Channel 3)
Result	Passed by 8.58 dB

Conducted Emission Test Data

The following data and graph shows the highest levels of conducted emissions on both polarizations of hot and neutral line.

Detector mode: CISPR Quasi-Peak mode (6 dB Bandwidth: 9 kHz)


NOTES:

1. Please see the measured data and graph in next page.
2. The Level (Result) value was included the reading, LISN factor and cable loss.
3. Delta (Margin) value = Limit - Level (Result)
4. Measurement were performed at the AC Power Inlet in the frequency band of 150 kHz ~ 30 MHz according to the FCC Part 15.107(a) Class B.
5. If the Quasi-Peak limit is met when using a Peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the Quasi-Peak detector receiver is unnecessary.
6. If the average limit is met when using a Quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.
7. Channel 3 was the worst case operation mode.

Line: HOT

ETL EMC Laboratory
Conducted Emission Test Result
EUT: ETLE171130.1127
Manuf:
Op Cond:
Operator:
Test Spec:
Comment: HOT

Prescan Measurement: Detectors: X PK / + AV
Meas Time: see scan settings
Peaks: 16
Acc Margin: 10 dB



Report no. ETLE171130.1127, Page 17 of 32

ETL EMC Laboratory

Conducted Emission Test Result

EUT: ETLE171130.1127

Manuf:

Op Cond:

Operator:

Test Spec:

Comment: HOT

Prescan Measurement: Detectors: X PK / + AV
Meas Time: see scan settings
Peaks: 16
Acc Margin: 10 dB

Peak Search Results

Frequency MHz	PK Level dBμV	PK Limit dBμV	PK Delta dB
0.15	47.74	66.00	18.26
0.157	40.60	65.62	25.02
0.186	52.56	64.21	11.65
0.191	52.29	63.99	11.70
0.211	52.34	63.17	10.83
0.245	50.64	61.92	11.28
0.25	50.40	61.76	11.36
0.257	52.95	61.53	8.58
0.266	52.09	61.24	9.15
0.275	51.38	60.97	9.59
0.282	49.73	60.76	11.03
0.318	46.99	59.76	12.77
0.32	49.58	59.71	10.13
0.34	49.21	59.20	9.99
0.38	46.48	58.28	11.80
0.39	46.20	58.06	11.86
0.401	46.05	57.83	11.78
0.447	43.12	56.93	13.81
0.451	46.05	56.86	10.81
0.46	45.11	56.69	11.58
0.469	44.27	56.53	12.26
0.484	43.85	56.27	12.42
0.579	42.80	56.00	13.20
0.712	40.35	56.00	15.65
0.74	37.99	56.00	18.01
0.924	38.08	56.00	17.92
0.953	38.39	56.00	17.61
1.05	36.88	56.00	19.12
1.155	38.14	56.00	17.86
4.29	33.30	56.00	22.70
4.355	35.22	56.00	20.78
5.155	34.60	60.00	25.40
23.27	29.03	60.00	30.97

* limit exceeded

Peak Search Results (continued)

Frequency MHz	PK Level dBμV	PK Limit dBμV	PK Delta dB
25.11	28.21	60.00	31.79


Frequency MHz	AV Level dBμV	AV Limit dBμV	AV Delta dB
0.15	15.17	56.00	40.83
0.157	16.63	55.62	38.99
0.186	34.66	54.21	19.55
0.191	36.97	53.99	17.02
0.211	18.65	53.17	34.52
0.245	28.77	51.92	23.15
0.25	34.88	51.76	16.88
0.257	33.75	51.53	17.78
0.266	33.12	51.24	18.12
0.275	26.55	50.97	24.42
0.282	15.53	50.76	35.23
0.318	27.23	49.76	22.53
0.32	26.44	49.71	23.27
0.34	21.55	49.20	27.65
0.38	27.49	48.28	20.79
0.39	26.99	48.06	21.07
0.401	26.22	47.83	21.61
0.447	25.25	46.93	21.68
0.451	24.99	46.86	21.87
0.46	24.17	46.69	22.52
0.469	23.33	46.53	23.20
0.484	14.07	46.27	32.20
0.579	23.32	46.00	22.68
0.712	19.12	46.00	26.88
0.74	23.45	46.00	22.55
0.924	20.73	46.00	25.27
0.953	18.96	46.00	27.04
1.05	19.48	46.00	26.52
1.155	16.44	46.00	29.56
4.29	23.52	46.00	22.48
4.355	20.18	46.00	25.82
5.155	20.42	50.00	29.58
23.27	19.22	50.00	30.78
25.11	17.42	50.00	32.58

* limit exceeded

Line: Neutral

ETL EMC Laboratory
Conducted Emission Test Result
EUT: ETLE171130.1127
Manuf:
Op Cond:
Operator:
Test Spec:
Comment: N

Prescan Measurement: Detectors: X PK / + AV
Meas Time: see scan settings
Peaks: 16
Acc Margin: 10 dB



ETL EMC Laboratory

Conducted Emission Test Result

EUT: ETLE171130.1127

Manuf:

Op Cond:

Operator:

Test Spec:

Comment: N

Prescan Measurement: Detectors: X PK / + AV
Meas Time: see scan settings
Peaks: 16
Acc Margin: 10 dB

Peak Search Results

Frequency MHz	PK Level dBμV	PK Limit dBμV	PK Delta dB
0.151	45.95	65.94	19.99
0.158	41.18	65.57	24.39
0.184	52.59	64.30	11.71
0.195	51.84	63.82	11.98
0.198	51.56	63.69	12.13
0.211	51.29	63.17	11.88
0.244	49.02	61.96	12.94
0.26	51.55	61.43	9.88
0.267	50.85	61.21	10.36
0.281	49.78	60.79	11.01
0.324	48.02	59.60	11.58
0.341	48.16	59.18	11.02
0.346	47.49	59.06	11.57
0.386	46.48	58.15	11.67
0.449	45.47	56.89	11.42
0.479	43.43	56.36	12.93
0.579	40.80	56.00	15.20
0.751	39.41	56.00	16.59
0.953	39.41	56.00	16.59
1.295	38.38	56.00	17.62
4.255	35.08	56.00	20.92
4.285	32.90	56.00	23.10
4.695	34.85	56.00	21.15
23.26	28.37	60.00	31.63
25.11	27.83	60.00	32.17

Frequency MHz	AV Level dBμV	AV Limit dBμV	AV Delta dB
0.151	14.93	55.94	41.01
0.158	16.00	55.57	39.57
0.184	31.02	54.30	23.28

* limit exceeded

Peak Search Results (continued)

Frequency MHz	AV Level dBμV	AV Limit dBμV	AV Delta dB
0.195	33.90	53.82	19.92
0.198	34.12	53.69	19.57
0.211	16.19	53.17	36.98
0.244	29.09	51.96	22.87
0.267	29.79	51.21	21.42
0.281	13.51	50.79	37.28
0.324	23.35	49.60	26.25
0.341	19.30	49.18	29.88
0.346	12.55	49.06	36.51
0.386	25.85	48.15	22.30
0.449	25.23	46.89	21.66
0.479	17.52	46.36	28.84
0.579	23.30	46.00	22.70
0.751	23.74	46.00	22.26
0.953	19.77	46.00	26.23
1.295	18.97	46.00	27.03
4.255	19.96	46.00	26.04
4.285	21.96	46.00	24.04
4.695	19.32	46.00	26.68
23.26	20.94	50.00	29.06
25.11	12.49	50.00	37.51

* limit exceeded

5.3 Radiated Emissions Measurement

5.3.1 Radiated Emissions Data

- Below 1 GHz

EUT	SETTOP BOX / DMS2004UHD W (S/N: EVY703P08971)
Limit apply to	FCC Part 15 Subpart B Section 15.109(a) Class B
Test Date	December 18, 2017
Environmental of Test	(4.7 ± 1.6) °C, (75 ± 4) % R.H., (102.5 ± 0.0) kPa
Operating Condition	TV Mode (Channel 3)
Result	Passed by 5.73 dB


Radiated Emission Test Data

The following table shows the highest levels of radiated emissions on both polarizations of horizontal and vertical.
Detector mode: CISPR Quasi-Peak mode (6 dB Bandwidth: 120 kHz)

Frequency [MHz]	Reading [dB(μV)]	Polarization (*H/**V)	Ant. Factor [dB/m]	Cable Loss [dB(μV)]	Height [cm]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]
38.21	53.24	V	11.55	-31.04	100	33.75	40.00	6.25
41.03	52.46	V	12.46	-31.00	100	33.92	40.00	6.08
150.02	56.81	V	8.00	-30.16	146	34.65	43.50	8.85
162.15	53.23	V	8.40	-30.09	158	31.54	43.50	11.96
195.02	50.64	V	11.06	-29.87	184	31.83	43.50	11.67
397.03	49.41	H	15.93	-28.85	153	36.49	46.00	9.51
427.13	52.54	H	16.44	-28.71	149	40.27	46.00	5.73

NOTES:

1. * H : Horizontal polarization , ** V : Vertical polarization
2. The cable loss value was included the Amp. Gain.
3. Result = Reading + Antenna factor + Cable loss
4. Margin value = Limit - Result
5. The measurement was performed for the frequency range 30 MHz ~ 1 000 MHz according to the FCC Part 15.109(a) Class B.
6. Channel 3 was the worst case operation mode.



- Above 1 GHz

EUT	SETTOP BOX / DMS2004UHD W (S/N: EVY703P08971)
Limit apply to	FCC Part 15 Subpart B Section 15.109(a) Class B
Test Date	December 18, 2017
Environmental of Test	(7.9 ± 1.4) °C, (67 ± 3) % R.H., (102.4 ± 0.0) kPa
Operating Condition	TV Mode (Channel 3)
Result	Passed by 15.69 dB

Radiated Emission Test Data

The following data and graph shows the highest levels of radiated emissions on both polarizations of horizontal and vertical.

Detector mode: CISPR Peak mode, Average mode


Frequency [MHz]	Reading [dB(μV)]		Polarity (*H/**V)	Height [cm]	Ant. Factor [dB/m]	Cable Loss [dB]	Result [dB(μV/m)]		Limit [dB(μV/m)]		Margin [dB]	
	Peak	Average					Peak	Average	Peak	Average	Peak	Average
1 020.04	62.34	40.46	H	100	25.19	-40.71	46.82	24.94	74.00	54.00	27.18	29.06
1 177.36	73.48	52.62	V	120	25.34	-40.51	58.31	37.45	74.00	54.00	15.69	16.55
1 533.03	61.70	39.34	H	100	25.65	-40.03	47.32	24.96	74.00	54.00	26.68	29.04
1 573.28	60.65	40.05	H	110	25.69	-39.96	46.38	25.78	74.00	54.00	27.62	28.22
1 783.42	64.62	51.30	V	110	25.89	-39.62	50.89	37.57	74.00	54.00	23.11	16.43
1 993.45	64.49	41.45	H	120	26.08	-39.28	51.29	28.25	74.00	54.00	22.71	25.75
2 506.51	55.61	35.44	H	130	27.42	-38.25	44.78	24.61	74.00	54.00	29.22	29.39

NOTES:


1. H : Horizontal polarization , V : Vertical polarization
2. The cable loss value was included the Amp. Gain.
3. Result = Reading + Antenna factor + Cable loss
4. Margin value = Limit - Result
5. The measurement was performed for the frequency range 1 GHz ~ 6 GHz according to FCC Part 15.109(a) Class B.
6. Upper frequency of measurement range: 5th harmonic of the highest frequency.
7. Channel 3 was the worst case operation mode.

Polarization: Horizontal

Limit : — Peak
— Average



Polarization: Vertical



Peak  Average 

5.4 Antenna Power Conduction Measurement

5.4.1 Antenna Power Conduction Measurement

EUT	SETTOP BOX / DMS2004UHD W (S/N: EVY703P08971)
Limit apply to	FCC Part 15 Subpart B Section 15.111(a)
Test Date	December 21, 2017
Environmental of Test	(20.4 ± 0.0) °C, (41 ± 0) % R.H., (101.4 ± 0.0) kPa
Operating Condition	Signal tuning mode
Result	Passed by 9.00 dB

Antenna Power Conduction Test Data

Test port	Tuned Frequency [MHz]	Meter Reading [dB(μV)]	Correction Factor [dB]	Result [dB(μV)]	Limit [dB(μV)]	Margin [dB]
CABLE IN	67.260	5.40	23.80	29.20	50.00	20.80
	189.840	5.40	23.90	29.30	50.00	20.70
	346.200	6.60	23.90	30.50	50.00	19.50
	514.200	13.30	24.00	37.30	50.00	12.70
	1 545.100	15.20	24.80	40.00	50.00	10.00
	2 046.500	16.10	24.90	41.00	50.00	9.00

NOTES:

1. Result = Meter Reading + Correction Factor (Matching Loss + Cable loss)
2. Margin value = Limit - Result
3. Measurements using the CISPR Quasi-peak mode in the frequency range 30 MHz to 6 GHz and measurements using the CISPR peak mode in the frequency range above 1 GHz.
4. The limits is 2.0 μW in the frequency range section 15.33(b)(1) of FCC Part 15.

5.5 Output Signal Level Measurement

5.5.1 Output Signal Level Measurement

EUT	SETTOP BOX / DMS2004UHD W (S/N: EVY703P08971)
Limit apply to	FCC Part15 Subpart B Section 15.115(b)(1)(i)
Test Date	December 21, 2017
Environmental of Test	(20.5 ± 0.0) °C, (41 ± 0) % R.H., (101.4 ± 0.0) kPa
Operating Condition	TV Mode (Channel 3, Channel 4)
Result	Passed by 0.53 dB

Output Signal Level Test Data

Test Channel	Emission Frequency [MHz]	Meter Reading [dB(μV)]	Correction Factor [dB]	Signal Level [dB(μV)]	Limit [dB(μV)]	Margin [dB]
3	61.250	67.37	7.60	74.97	75.50	0.53
	65.750	52.33	7.60	59.93	62.50	2.57
4	67.250	67.27	7.60	74.87	75.50	0.63
	71.750	52.15	7.60	59.75	62.50	2.75

NOTES:

1. The correction factor consist of the insertion loss of the impedance matching transformer and the coaxial Satellite Receiver used for the test.
2. The spectrum was checked in each test mode and operation mode, and the maximum measured data were reported.
3. Signal Level = Meter Reading + Correction Factor (Matching Loss + Cable loss)
4. Margin value = Limit - Signal Level

5.6 Output Terminal Conducted Spurious Emission Measurement

5.6.1 Output Terminal Conducted Spurious Emission Measurement

EUT	SETTOP BOX / DMS2004UHD W (S/N: EVY703P08971)
Limit apply to	FCC Part15 Subpart B Section 15.115(b)(2)(i)
Test Date	December 21, 2017
Environmental of Test	(20.6 ± 0.0) °C, (41 ± 0) % R.H., (101.4 ± 0.0) kPa
Operating Condition	TV Mode (Channel 3, Channel 4)
Result	Passed by 0.80 dB

Output Terminal Conducted Spurious Test Data

Test Channel	Emission Frequency [MHz]	Meter Reading [dB(μV)]	Correction Factor [dB]	Result [dB(μV)]	Limit [dB(μV)]	Margin [dB]
3	56.460	52.90	7.60	60.50	75.50	15.00
	61.320	67.10	7.60	74.70	75.50	0.80
	65.640	52.70	7.60	60.30	75.50	15.20
	107.760	16.20	7.60	23.80	75.50	51.70
	122.340	23.10	7.70	30.80	75.50	44.70
	179.040	23.50	7.70	31.20	75.50	44.30
	183.900	35.70	7.70	43.40	75.50	32.10
	188.220	22.40	7.70	30.10	75.50	45.40
	305.600	18.60	7.70	26.30	75.50	49.20
	428.800	9.40	7.80	17.20	75.50	58.30
4	980.400	15.10	8.10	23.20	75.50	52.30
	62.400	52.80	7.60	60.40	75.50	15.10
	67.260	66.70	7.60	74.30	75.50	1.20
	71.580	52.40	7.60	60.00	75.50	15.50
	107.760	15.90	7.60	23.50	75.50	52.00
	134.220	20.80	7.70	28.50	75.50	47.00
	197.400	20.90	7.70	28.60	75.50	46.90
	201.720	34.10	7.70	41.80	75.50	33.70
	206.580	19.60	7.70	27.30	75.50	48.20
	336.400	14.90	7.70	22.60	75.50	52.90
	605.200	8.90	7.80	16.70	75.50	58.80

NOTES:

1. The correction factor consists of the insertion loss of the impedance matching transformer.
2. The spectrum was checked in each test mode and operation mode, and the maximum measured data were reported.
3. Result = Meter Reading + Correction (Matching Loss+ Cable loss)
4. Margin value = Limit - Signal Level

5.7 Antenna Transfer Switch Measurement

5.7.1 Antenna Transfer Switch Measurement

EUT	SETTOP BOX / DMS2004UHD W (S/N: EVY703P08971)
Limit apply to	FCC Part15 Subpart B Section 15.115(c)(1)(ii)
Test Date	December 21, 2017
Environmental of Test	(20.7 ± 0.0) °C, (41 ± 0) % R.H., (101.4 ± 0.0) kPa
Operating Condition	TV Mode (Channel 3, Channel 4)
Result	Passed

Antenna Transfer Switch Test Data

Test Channel	Emission Frequency [MHz]	Meter Reading [dB(μV)]	Correction Factor [dB]	Result [dB(μV)]	Limit [dB(μV)]	Margin [dB]
3	61.250	During this test, no signal detected				-
4	67.250					-

NOTES:

1. No emission was observed during the test. The spectrum was checked in each test mode and operation mode Transfer switch isolation measurements were made on the Channel 3 or 4 video output frequency of 61.25 MHz or 67.25 MHz and both positions of the transfer switch were checked for compliance.
2. To clarify the emissions emanated from ANT. input terminal on the EUT, RF pre-amplifier was used. The gain of pre-amplifier at each frequency measured from the EUT was obtained after sufficient warm-up for stabilization of gain. The correction factor consists of the insertion loss of the impedance matching transformer, the coaxial Satellite Receiver used for the test and the gain of pre-amplifier.
3. Result = Meter Reading + Correction Factor (Matching Loss + Cable loss)
4. Margin value = Limit - Result
5. Spectrum analyzer setting: Frequency Span 1 MHz, Resolution bandwidth 100 kHz, Video bandwidth 300 kHz, Detector function Peak mode.

6. SAMPLE CALCULATION

Sample Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor.
The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF$$

Where FS = Field Strength

RA = Receiver Amplitude

AF = Antenna Factor

CF = Cable Attenuation Factor - Preamplifier Factor

$$dB(\mu V) = 20 \log_{10} (\mu V) : \text{Equation}$$

$$dB(\mu V) = dBm + 107$$

Example : @ 427.13 MHz

$$\text{Class B Limit} = 46.00 \text{ dB}(\mu V/m)$$

$$\text{Reading} = 52.54 \text{ dB}(\mu V)$$

$$\text{Antenna Factor} + (\text{Cable Loss} - \text{Amp. Gain.}) = 16.44 + (-28.71) = -12.27 \text{ dB}(\mu V/m)$$

$$\text{Total} = 40.27 \text{ dB}(\mu V/m)$$

$$\text{Margin} = 46.00 - 40.27 = 5.73 \text{ dB}$$

$$= 5.73 \text{ dB below Limit}$$

7. List of test equipments used for measurements

	Test Equipment	Model	Mfg.	Serial No.	Cal. Date	Cal. Due Date
☒	EMI Test Receiver	ESPI3	R&S	100478	17.08.31	18.08.31
☒	EMI Test Receiver	ESCS30	R&S	100087	17.03.13	18.03.13
☒	EMI Test Receiver	ESCI7	R&S	100851	17.08.31	18.08.31
☒	Amplifier	310N	Sonoma Instrument	284750	17.08.31	18.08.31
☒	Two-Line V-Network	ENV216	R&S	102055	17.03.13	18.03.13
☒	Two-Line V-Network	ENV216	R&S	101715	17.03.14	18.03.14
☒	Horn Antenna	BBHA 9120D	Schwarzbeck	826	16.03.23	18.03.23
☒	Amplifier	TK-PA18	TESTEK.	120020	17.09.01	18.09.01
☒	Bi-Log Antenna	VULB9163	Schwarzbeck	01069	17.02.17	19.02.17
☒	Matching Pad (RAM)	358.5414.02	R&S	101841	17.09.01	18.09.01
☒	75 Ω Directional Bridge	86207A	Agilent	3140A00678	17.09.01	18.09.01
☒	Turn-Table	TT 1.35 SI	SES	-	N/A	N/A
☒	Antenna Master	AM 4.5	SES	-	N/A	N/A