

TEST REPORT

For

2.4GHz Band Data Communication Module

In conformity with

FCC CFR 47 Part15 / RSS-210, RSS-Gen

Model: XE972

FCC ID/ IC Certification No.: PH3XE972 / 3070C-XE972

Test Item: 2.4GHz Band Data Communication Module

Report No: RY706Y08R1

Issue Date: 08 June 2007

Prepared for

ALINCO INCORPORATED.

Shin Dai Bldg. 9F, 1-2-6 Dojimahama, Kita-ku, Osaka
430-0004 Japan

Prepared by

RF Technologies Ltd.

472, Nippa-cho, Kohoku-ku, Yokohama, 223-0057, Japan

Telephone: +81+(0)45- 534-0645

FAX: +81+(0)45- 534-0646

This report shall not be reproduced, except in full, without the written permission of RF Technologies Ltd. The test results relate only to the item(s) tested.
RF Technologies Ltd. is managed to ISO17025 and has the necessary knowledge and test facilities for testing according to the referenced standards.

Table of contents

1	General information.....	3
1.1	Product description	3
1.2	Test(s) performed/ Summary of test result	3
1.3	Test facility	4
1.4	Measurement uncertainty.....	4
1.5	Summary of test results.....	5
1.5.1	Table of test summary.....	5
1.5.2	Conclusion of worst-case and operating mode	5
1.6	Setup of equipment under test (EUT)	6
1.6.1	Test configuration of EUT.....	6
1.6.2	Operating condition:	6
1.6.3	Setup diagram of tested system:.....	7
1.7	Equipment modifications.....	7
1.8	Deviation from the standard	7
2	Test procedure and test data	8
2.1	Occupied Bandwidth.....	8
2.2	Hopping Carrier Frequency Separation	12
2.3	Number of Hopping Channel.....	15
2.4	Average Time of Occupancy	18
2.5	Peak Output Power	22
2.6	Conducted Spurious Emissions (Antenna Port).....	25
2.7	Transmitter Radiated spurious emissions	28
2.7.1	Below 30 MHz.....	31
2.7.2	Between 30 – 1000 MHz	32
2.7.3	Above 1000 MHz.....	36
2.8	Transmitter AC power line conducted emissions	46
	Continuous Transmission (Worst case configuration).....	47
2.9	Receiver Radiated spurious emissions	49
2.9.1	Between 30 – 1000 MHz	49
2.9.2	Above 1000 MHz.....	53
2.10	Receiver AC power line conducted emissions.....	54
2.11	Maximum Permissible Exposure (Exposure of Humans to RF Fields)	57
3	Test setup photographs	59
3.1	Definition of the EUT axis.....	59
3.1.1	Connected Antenna Type: Printed half wave dipole antenna	59
3.1.2	Connected Antenna Type: Printed 1/4 wave monopole antenna	60
3.2	Antenna Port Measurements	62
3.3	Radiated spurious emissions.....	62
3.4	AC power line conducted emissions.....	64
4	List of utilized test equipment/ calibration	65

1 General information

1.1 Product description

Test item : 2.4GHz Band Data Communication Module
Manufacturer : ALINCO INCORPORATED.
Address : Yaesu Center Bldg. 4F, 2-3-21 Nihonbashi, Chuo-ku, Tokyo, 103-0027 Japan
Model : XE972
FCC ID : PH3XE972
IC Certification No. : 3070C-XE972
Classification : Certification
Serial numbers : T00015
Fundamental / Operated Frequency : 20 MHz, 26 MHz, Tx/Rx Freq.(2401 - 2411.5 MHz)
RF Output Power : 8.88 dBm (measured at the antenna terminal)
Antenna Gain : -0.66 dBi (Printed Half Wave Dipole Antenna: Peak Maximum Gain)
0.61 dBi (Printed 1/4 Wave Monopole Antenna: Peak Maximum Gain)
Receipt date of EUT : 28 May 2007
Nominal power source voltages : DC 3.5V (from AC Adaptor, Model:SA106A-0512-6 by Sino-American)

1.2 Test(s) performed/ Summary of test result

Test specification(s) : FCC CFR 47. Part 15 / RSS-210 Issue 6, RSS-Gen Issue 1
Test method(s) : ANSI C63.4: 2003
Test(s) started : 28 May 2007
Test(s) completed : 1 June 2007
Purpose of test(s) : Grant for Certification of FCC / IC

Summary of test result : Complied

Note: The above judgment is only based on the measurement data and it does not include the measurement uncertainty. Accordingly, the statement below is applied to the test result.
The EUT complies with the limit required in the standard in case that the margin is not less than the measurement uncertainty in the Laboratory.
Compliance of the EUT is more probable than non-compliance is case that the margin is less than the measurement uncertainty in the Laboratory.

Test engineer

: 
Y. Nakajima

Reviewer

: 
T. Ikegami

1.3 Test facility

The Federal Communications Commission has reviewed the technical characteristics of the test facilities at RF Technologies Ltd., located in 472, Nippa-cho, Kohoku-ku, Yokohama, 223-0057, Japan, and has found these test facilities to be in compliance with the requirements of 47 CFR Part 15, section 2.948, per October 23, 2000.

The description of the test facilities has been filed under registration number 879401 at the Office of the Federal Communications Commission. The facility has been added to the list of laboratories performing these test services for the public on a fee basis.

The list of all public test facilities is available on the Internet at <http://www.fcc.gov>.

Registered by Voluntary Control Council for Interference by Information Technology Equipment (VCCI).

Each registered facility number is as follows;

Test site (Anechoic chamber 3m) R-2393

Test site (Shielded room) C-2617

Registered by Industry Canada (IC). The registered facility number is as follows;

Test site No. 1 (Anechoic chamber 3m) : 6974A

1.4 Measurement uncertainty

The treatment of uncertainty is based on the general matters on the definition of uncertainty in “Guide to the expression of uncertainty in measurement (GUM)” published by ISO. The Lab’s uncertainty is determined by referring UKAS Publication LAB34: 2002 “The Expression of Uncertainty in EMC Testing” and CISPR16-4-2: 2003 “Uncertainty in EMC Measurements”.

The uncertainty of the measurement result in the level of confidence of approximately 95% (k=2) is as follows;

Conducted emission: ± 3.5 dB (10 kHz – 150 kHz), ± 3.6 dB (150 kHz – 30 MHz)

Radiated emission (9 kHz - 30MHz): ± 3.2 dB

Radiated emission (30MHz - 1000MHz): ± 4.6 dB

Radiated emission (above 1000MHz): ± 4.6 dB

1.5 Summary of test results

1.5.1 Table of test summary

Requirement of;	Section in FCC15	Section in RSS210/ RSS-Gen	Result	Section in this report
1.5.1 Occupied Bandwidth (20 dB)	15.247(a)(1)	A8.1(1)	Complied	2.1
1.5.2 Hopping Carrier Frequency Separation	15.247(a)(1)	A8.1(2)	Complied	2.2
1.5.3 Number of Hopping Channel	15.247(a)(1)(iii)	A8.1(4)	Complied	2.3
1.5.4 Average Time of Occupancy	15.247(a)(1)(iii)	A8.1(4)	Complied	2.4
1.5.5 Peak Output Power	15.247(a)(1)/(b)(1)	A8.4(2)	Complied	2.5
1.5.6 Conducted Spurious Emissions	15.247(d)	A8.5	Complied	2.6
1.5.7 Transmitter Radiated Spurious Emissions	15.205(b)/15.209	A8.5	Complied	2.7
1.5.8 Transmitter AC Power Line Conducted Emissions	15.207	RSS-Gen 7.2.2	Complied	2.8
1.5.9 Receiver Radiated Spurious Emissions	15.109	RSS-Gen 6	Complied	2.9
1.5.10 Receiver AC Power Line Conducted Emissions	15.107	RSS-Gen 7.2.2	Complied	2.10
1.5.11 Maximum Permissible Exposure (Exposure of Humans to RF Fields)	15.247(i)/ 1.1307(b)(1)	RSS-Gen 5.5/ RSS-102	Complied	2.11

1.5.2 Conclusion of warst-case and operationg mode

It is prepared the two type of antenna for the module by applicant. The each antenna information is follow;

Antenna Type	Maximum Peak Gain (dBi)		
	2401 MHz	2406 MHz	2411.5 MHz
Printed half wave dipole antenna	-2.19	-0.66	-0.83
Printed 1/4 wave monopole antenna	-0.43	0.23	0.61

Therefore radiated emission and maximum permissible exposure requirements were tested to the two type of antenna. The field strength of spurious emission was measured in three orthogonal EUT positions (X-axis, Y-axis and Z-axis). The axis defined in the photographs in clause 3.1 in this report.

1.6 Setup of equipment under test (EUT)

1.6.1 Test configuration of EUT

Equipment(s) under test:

	Item	Manufacturer	Model No.	Serial No.	FCC ID/ IC Certification No.
A	2.4GHz Band Data Communication Module	ALINCO INCORPORATED.	XE972	T00015	PH3XE972/ 3070C-XE972

The EUT has a two type of the printed antenna alternatively. One is the half wave dipole antenna model: 3148581510, the other one is 1/4 wave monopole antenna model: 3148578511.

Support Equipment(s):

	Item	Manufacturer	Model No.	Serial No.	FCC ID
B	Test Kit	-	-	-	N/A
C	AC Adaptor	Sino-American	SA106A-0512-6	None	N/A
D	Personal Computer	Compaq	Nx6310	CNU6512T73	DoC
E	AC Adaptor	Compaq	PA-1650-02HC	5978A0ARGU04TH	N/A

Connected cable(s):

No.	Item	Identification (Manu.e.t.c)	Shielded YES / NO	Ferrite Core YES / NO	Connector Type Shielded YES / NO	Length (m)
1	Control cable	-	Yes	No	No	0.1
2	DC power cable	UNICAB	Yes	No	Yes	3.1
3	RS232C cable	SANWA SUPPLY	Yes	No	Yes	2.1
4	USB/RS232C exchange cable	-	Yes	No	Yes	0.5
5	DC power cable	LL110948	Yes	No	Yes	1.8
6	AC power cable	SANWA.D.S	No	No	No	1.8


1.6.2 Operating condition:

Operating mode:

The EUT was tested under the following test mode prepared by the applicant;:

- (1-1) Continuous transmission, hopping off (0ch: 2401MHz)
- (1-2) Continuous transmission, hopping off (11ch: 2406.5MHz)
- (1-3) Continuous transmission, hopping off (21ch: 2411.5MHz)
- (1-4) Continuous transmission, hopping on (Hopping Group 0)
- (1-5) Continuous transmission, hopping on (Hopping Group 11)
- (1-6) Continuous transmission, hopping on (Hopping Group 21)
- (2-1) Continuous receiving (Same as stand-by)

1.6.3 Setup diagram of tested system:



1.7 Equipment modifications

No modifications have been made to the equipment in order to achieve compliance with the applicable standards described in clause 1.2.

1.8 Deviation from the standard


No deviations from the standards described in clause 1.2.

2 Test procedure and test data

2.1 Occupied Bandwidth

Test setup

Test setup is the following drawing. The antenna port of EUT was connected to the spectrum analyzer.



Test procedure

Measurement procedures were implemented according to the method of ANSI C63.4: 2003 clauses 13.1.7. The EUT antenna port connected to the spectrum analyzer. The RBW is set to 1% to 3% of the measured 20dB bandwidth. The VBW is set to 3 times of the RBW. The sweep time is coupled appropriate.

Limitation

There are no limitations. The measurement value is used to calculation of the limitation of the channel separation and the emission designator.

Test equipment used (refer to List of utilized test equipment)

SA06					
------	--	--	--	--	--

Test results – Reporting purpose.



Transmission Channel	Transmission Frequency	20dB Bandwidth (KHz)	99 % (KHz)
Low (0ch)	2401.0	47.0	51.0
Middle (11ch)	2406.5	46.0	48.0
High (21ch)	2411.5	108.0	240.0

Test Data



Tested Date: May 30, 2007

Temperature: 23 °C
Humidity: 61 %
Atmos. Press: 1002 hPa



Low (CH:0) 2401.0 MHz



Middle (CH: 11) 2406.5 MHz




High (CH: 21) 2411.5 MHz



2.2 Hopping Carrier Frequency Separation

Test setup

Test setup is the following drawing. The antenna port of EUT was connected to the spectrum analyzer.



Test procedure

The EUT antenna port connected to the spectrum analyzer. The RBW is set to 100 kHz. The VBW is set to appropriate in order to read carrier frequency separation. The sweep time is coupled appropriate.

Limitation

15.247(a)(1) frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. Therefore limitation value is grater than 72 kHz ($108 \text{ kHz} * 2 / 3$).

Test equipment used (refer to List of utilized test equipment)

SA06					
------	--	--	--	--	--

Test results – comply with the limitation.

The test was performed to the following three hopping group;


Hopping group	Measured Frequency (MHz)	Frequency Separation (kHz)
Group 0	2401.0	500
Group 11	2406.5	500
Group 21	2411.5	500

Test Data


Tested Date: May 30, 2007

Temperature: 23 °C
Humidity: 61 %
Atmos. Press: 1002 hPa


Hopping group 0 at 2401MHz



Hopping group 11 at 2406.5 MHz




Hopping group 21 at 2411.5 MHz



2.3 Number of Hopping Channel

Test setup

Test setup is the following drawing. The antenna port of EUT was connected to the spectrum analyzer.



Test procedure

The EUT antenna port connected to the spectrum analyzer. The RBW is set to 100 kHz. The VBW is set to appropriate in order to read carrier frequency. The sweep time is coupled appropriate. The span is set to cover the authorized band. The analyzer is set to MAX HOLD. The EUT is hopping operation.

Limitation

15.247(a)(1)(iii) Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

Test equipment used (refer to List of utilized test equipment)

SA06					
------	--	--	--	--	--

Test results – Comply with the limitation

The test was performed to the following three hopping group;


	Hopping group		
	Group 0	Group 11	Group 21
Number of Hopping channel	22	22	22

Test Data


Tested Date: May 30, 2007

Temperature: 23 °C
Humidity: 61 %
Atmos. Press: 1002 hPa


Hopping group 0



Hopping group 11




Hopping group 21



2.4 Average Time of Occupancy

Test setup

Test setup is the following drawing. The antenna port of EUT was connected to the spectrum analyzer.



Test procedure

The EUT antenna port connected to the spectrum analyzer. The RBW is set to 300 kHz. The VBW is set to appropriate in order to read the plus duration. The sweep time is coupled appropriate. The span is set to 0 MHz and single sweep with video triggered. The EUT is hopping operation.

Limitation

15.247(a)(1)(iii) The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

The measurement time is 8.8 seconds (22ch * 0.4 = 8.8 sec). The transmission pulse appears one pulse within 8.8 seconds; therefore pulse width is the average time of occupancy.

Test equipment used (refer to List of utilized test equipment)

SA06					
------	--	--	--	--	--

Test results – comply with the limitation.

The test was performed to the following three hopping group;



Hopping group	Measured Frequency (MHz)	Time of occupancy (msec)
Group 0	2401.0	389.60
Group 11	2406.5	390.40
Group 21	2411.5	388.80

Test Data



Tested Date: May 30, 2007

Temperature: 23 °C
Humidity: 61 %
Atmos. Press: 1002 hPa



Hopping group 0 at 2401.0 MHz



Hopping group 11 at 2406.5 MHz




Hopping group 21 at 2411.5 MHz



2.5 Peak Output Power

Test setup

Test setup is the following drawing. The antenna port of EUT was connected to the spectrum analyzer.



Test procedure

The EUT antenna port connected to the spectrum analyzer. The RBW is set to the greater than 20dB bandwidth. The VBW is set to three times of RBW. The sweep time is coupled appropriate. The span is set to cover the carrier output spectrum. The analyzer is set to MAX HOLD. The EUT is set measured transmission channel under hopping off mode.

The correction factor is set to the spectrum analyzer in order to correct of the connected cable loss.

Limitation

15.247(a)(1) / (b)(1) Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW (21dBm).

Test equipment used (refer to List of utilized test equipment)

SA06					
------	--	--	--	--	--

Test results – comply with the limitation.


Transmission Channel	Transmission Frequency	Output power (dBm)	Output power (mW)
Low (0ch)	2401.0	7.95	6.24
Middle (11ch)	2406.5	8.88	7.73
High (21ch)	2411.5	8.60	7.24

Test Data


Tested Date: May 30, 2007

Temperature: 23 °C
Humidity: 61 %
Atmos. Press: 1002 hPa


Low (CH:0) 2401.0 MHz



Middle (CH:11) 2406.5 MHz




High (CH:21) 2411.5 MHz



2.6 Conducted Spurious Emissions (Antenna Port)

Test setup

Test setup is the following drawing. The antenna port of EUT was connected to the spectrum analyzer.



Test procedure

The EUT antenna port connected to the spectrum analyzer. The RBW is set to 100 kHz. The VBW is set to 300 kHz. The sweep time is set to the coupled. The spectrum is checked from 30 MHz to 26 GHz. The EUT is set measured transmission channel under hopping off mode.

Limitation

15.247(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

Test equipment used (refer to List of utilized test equipment)

SA06					
------	--	--	--	--	--

Test results – comply with the limitation.



There are no conducted spurious emissions greater than the noise floor.

Test Data



Tested Date: May 28 2007

Temperature: 24.8 °C
Humidity: 35 %
Atmos. Press: 1002 hPa



Low (CH:0) 2401.0 MHz



Middle (CH:11) 2406.5 MHz






High (CH:21) 2411.5 MHz



2.7 Transmitter Radiated spurious emissions

Test setup

Test setup was implemented according to the method of ANSI C63.4: 2003 clause 6 “General requirements for EUT equipment arrangements and operation”, clause 8.2 and Annex H.3 “Radiated emission measurements setup”.



Test procedure

Measurement procedures were implemented according to the method of ANSI C63.4: 2003 clauses 8.2.

The EUT is placed on a non-conducted table which is 0.8m height from a ground plane and the measurement antenna to EUT distance is 3 meters. The turn table is rotated for 360 degrees to determine the maximum emission level.

In the frequency range of 9 kHz to 30 MHz, a calibrated loop antenna was positioned with its plane vertical at the distance 3m from the EUT with an extrapolation of corrected distance factor and rotated about its vertical axis for maximum response at each azimuth about the EUT. For certain applications, the loop antenna also needs to be positioned horizontally. The center of the loop shall be 1 m above the ground.

In the frequency above 30 MHz, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

EUT is placed at three different orientations (X, Y and Z axis) in order to find the worst orientation.

The spectrum analyzer and receiver is set to the followings;

Below 30 MHz: RBW=10 kHz, VBW= 30 kHz, final measurement is carried out receiver RBW=9 kHz QP

Between 30 - 1000 MHz: RBW=100 kHz, VBW= 300 kHz, final measurement is carried out receiver RBW=120 kHz QP

Above 1000 MHz: Peak measurement- RBW=1 MHz, VBW= 1 MHz

Average measurement – RBW=1 MHz, VBW=10 Hz

Applicable rule and limitation

§15.205 restricted bands of operation

Except as shown in paragraph 15.205 (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
0.490 - 0.510	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(1)

15.205(b) except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

15.209(a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table

Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

In the emission table above, the tighter limit applies at the band edges.

The level of any unwanted emissions from an intentional radiator operating under these general provisions shall not exceed the level of the fundamental emission.

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz.

Radiated emission limits in the above bands are based on measurements employing an average detector.

Test results - Complied with requirement.

Test Data

2.7.1 Below 30 MHz

Test equipment used (refer to List of utilized test equipment)

LP01	CL11	SA06	TR04	
------	------	------	------	--

Tested Date: May 25 2007

Temperature: 21 °C
Humidity: 55 %
Atmos. Press: 1007 hPa

Connected Antenna Type	Result
Printed half wave dipole antenna	There is no spurious emissions grater than noise floor.
Printed1/4 wave monopole antenna	There is no spurious emissions grater than noise floor.

Note: The lowest oscillator in the EUT is 20 MHz, therefore the spectrum was checked from the 20 MHz to 30 MHz. The noise floor is about 30dBuV/m at 3 meters (-10dBuV/m at 30 meters).

2.7.2 Between 30 – 1000 MHz

Test equipment used (refer to List of utilized test equipment)

BA03	CL11	PR03	SA06	TR04
------	------	------	------	------

Tested Date: May 25 2007

Temperature: 21 °C
Humidity: 55 %
Atmos. Press: 1007 hPa

2.7.2.1 Connected Antenna Type: Printed half wave dipole antenna

No.	Frequency [MHz]	Reading [dBuV]	Factor [dB/m]	Loss [dB]	Gain [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Antenna Polarization
1	63.44	37.5	5.7	4.4	29.8	17.8	40.0	22.2	Hori.
2	96.68	34.2	9.3	4.7	29.7	18.5	43.5	25.0	Hori.
3	115.12	35.6	10.7	4.9	29.7	21.5	43.5	22.0	Hori.
4	43.16	50.1	10.0	4.1	29.8	34.4	40.0	5.6	Vert.
5	58.78	43.7	5.8	4.3	29.8	24.0	40.0	16.0	Vert.
6	63.50	44.5	5.7	4.4	29.8	24.8	40.0	15.2	Vert.

Calculation method

The Correction Factors and RESULT are calculated as followings.

$$\text{Correction Factor (dB)} = \text{FACTOR (dB/m)} + \text{LOSS (dB)} - \text{GAIN (dB)}$$

$$\text{RESULT (dBuV/m)} = \text{READING (dBuV)} + \text{Correction Factor (dB/m)}$$


Sample calculation at 43.16 MHz vertical result as follow:

$$\text{Result (dBuV/m)} = \text{Reading} + \text{C.F} = 51.1 + 10.0 + 4.1 - 29.8 = 34.4$$


$$\text{Margin} = \text{Limit} - \text{Result} = 40.0 - 34.4 = 5.6 \text{ (dBuV/m)}$$

Graphical express of test result (30MHz-1000MHz)

Antenna polarization: Horizontal



Antenna polarization: Vertical



2.7.2.2 Connected Antenna Type: Printed 1/4 wave monopole antenna

No.	Frequency [MHz]	Reading [dBuV]	Factor [dB/m]	Loss [dB]	Gain [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Antenna Polarization
1	42.79	51.6	10.2	4.1	29.8	36.1	40.0	3.9	Vert.
2	58.89	44.8	5.8	4.3	29.8	25.1	40.0	14.9	Vert.
3	62.68	44.8	5.7	4.4	29.8	25.1	40.0	14.9	Vert.
4	63.00	37.4	5.7	4.4	29.8	17.7	40.0	22.3	Hori.
5	95.62	34.7	9.1	4.7	29.7	18.8	43.5	24.7	Hori.
6	116.16	35.2	10.8	4.9	29.7	21.2	43.5	22.3	Hori.

Calculation method

The Correction Factors and RESULT are calculated as followings.

$$\text{Correction Factor (dB)} = \text{FACTOR (dB/m)} + \text{LOSS (dB)} - \text{GAIN (dB)}$$

$$\text{RESULT (dBuV/m)} = \text{READING (dBuV)} + \text{Correction Factor (dB/m)}$$


Sample calculation at 42.79 MHz vertical result as follow:

$$\text{Result (dBuV/m)} = \text{Reading} + \text{C.F} = 51.6 + 10.2 + 4.1 - 29.8 = 36.1$$


$$\text{Margin} = \text{Limit} - \text{Result} = 40.0 - 36.1 = 3.9 \text{ (dBuV/m)}$$

Graphical express of test result (30MHz-1000MHz)

Antenna polarization: Horizontal



Antenna polarization: Vertical



2.7.3 Above 1000 MHz

Test equipment used (refer to List of utilized test equipment)


BRF1	HPF1	PR04	SH01	SA06	CL21	CL22	DH02
------	------	------	------	------	------	------	------

Tested Date: May 25 2007


Temperature: 21 °C
Humidity: 55 %
Atmos. Press: 1007 hPa

2.7.3.1 Connected Antenna Type: Printed half wave dipole antenna


Restricted Band Edge (Low channel, Horizontal, Peak)




Restricted Band Edge (Low channel, Horizontal, Average)




Restricted Band Edge (Low channel, Vertical, Peak)




Restricted Band Edge (Low channel, Vertical, Average)




Restricted Band Edge (High channel, Horizontal, Peak)




Restricted Band Edge (High channel, Horizontal, Average)



Restricted Band Edge (High channel, Vertical, Peak)



Restricted Band Edge (High channel, Vertical, Average)



Harmonics and Spurious Emission above 1000 MHz

TX CH (MHz)	Freq. (MHz)	Cable Loss (dB)	Antenna Factor (dB)	Meter Reading(dBuV)				Limit(dBuV)		Result (dBuV/m)		Margin (dB)		Pol.	Note
				Ave.	Peak	Ave.	Peak	Ave.	Peak	Ave	Peak	Ave.	Peak		
0ch 2401.0 (Low)	4802.0	-26.4	33.1	46.4	41.0	50.8	48.4	54.0	74.0	53.1	57.5	0.9	16.5	H	*1
	7203.0	-26.1	36.9	-	-	58.7	58.0	-	87.8	-	69.5	-	18.3	H	*2
	9604.0	-23.0	37.6	-	-	47.9	47.0	-	87.8	-	62.5	-	25.3	H	*2
	12005.0	-23.9	40.7	< 31.0	< 31.0	< 43.0	< 43.0	54.0	74.0	< 47.8	< 59.8	> 6.2	> 14.2	-	*1
11ch 2406.5 (Mid)	4813.0	-26.4	33.2	45.7	39.8	50.1	47.8	54.0	74.0	52.5	56.9	1.5	17.1	H	*1
	7219.5	-26.1	36.9	-	-	57.3	57.1	-	87.8	-	68.1	-	19.7	H	*2
	9626.0	-23.0	37.5	-	-	48.0	47.1	-	87.8	-	62.5	-	25.3	H	*2
	12032.5	-23.9	40.8	< 31.0	< 31.0	< 43.0	< 43.0	54.0	74.0	< 47.9	< 59.9	> 6.1	> 14.1	-	*1
21ch 2411.5 (High)	4823.0	-26.4	33.2	44.1	38.5	50.0	46.9	54.0	74.0	50.9	56.8	3.1	17.2	H	*1
	7234.5	-26.1	36.9	-	-	55.9	55.5	-	87.4	-	66.7	-	20.7	H	*2
	9646.0	-23.0	37.5	-	-	48.3	46.8	-	87.4	-	62.8	-	24.6	H	*2
	12057.5	-23.9	40.7	< 31.0	< 31.0	< 43.0	< 43.0	54.0	74.0	< 47.8	< 59.8	> 6.2	> 14.2	-	*1

Note1: This frequency is in the restriction band therefore it is applied the 15.209 Radiated emission limits, general requirements.

Note2: This frequency is not in the restriction band therefore these spurious emission shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power (15.247 (d)).

The radiated carrier level of each frequency is follows (RBW = 100 kHz);

- 107.8 dBuV/m at 2401 MHz
- 107.8 dBuV/m at 2406.5 MHz
- 107.4 dBuV/m at 2411.5 MHz

Calculation method

The RESULT is calculated as followings.

$$\text{RESULT (dBuV/m)} = \text{READING (dBuV)} + \text{Antenna Factor (dB/m)} + \text{Cable Loss (dB)}$$

The Cable loss include amplifier gain


Sample calculation at 4802 MHz result on the Ave.as follow:

$$\text{Result (dBuV/m)} = \text{Reading} + \text{Antenna Factor} + \text{Cable Loss} = 46.4 + 33.1 - 26.4 = 53.1$$


$$\text{Margin} = \text{Limit} - \text{Result} = 54.0 - 53.1 = 0.9 \text{ (dBuV/m)}$$

2.7.3.2 Connected Antenna Type: Printed 1/4 wave monopole antenna


Restricted Band Edge (Low channel, Horizontal, Peak)




Restricted Band Edge (Low channel, Horizontal, Average)




Restricted Band Edge (Low channel, Vertical, Peak)




Restricted Band Edge (Low channel, Vertical, Average)




Restricted Band Edge (High channel, Horizontal, Peak)




Restricted Band Edge (High channel, Horizontal, Average)



Restricted Band Edge (High channel, Vertical, Peak)



Restricted Band Edge (High channel, Vertical, Average)



Harmonics and Spurious Emission above 1000 MHz

TX CH (MHz)	Freq. (MHz)	Cable Loss (dB)	Antenna Factor (dB)	Meter Reading(dBuV)				Limit(dBuV)		Result (dBuV/m)		Margin (dB)		Pol.	Note
				Ave.	Peak	Ave.	Peak	Ave.	Peak	Ave.	Peak	Ave.	Peak		
0ch 2401.0 (Low)	4802.0	-26.4	33.1	43.4	38.3	50.0	46.6	54.0	74.0	50.1	56.7	3.9	17.3	H	*1
	7203.0	-26.1	36.9	-	-	58.4	57.2	-	85.8	-	69.2	-	16.6	H	*2
	9604.0	-23.0	37.6	-	-	46.8	45.4	-	85.8	-	61.4	-	24.4	H	*2
	12005.0	-23.9	40.7	< 31.0	< 31.0	< 43.0	< 43.0	54.0	74.0	< 47.8	< 59.8	> 6.2	> 14.2	-	*1
11ch 2406.5 (Mid)	4813.0	-26.4	33.2	35.5	36.0	45.6	46.0	54.0	74.0	42.8	52.8	11.2	21.2	V	*1
	7219.5	-26.1	36.9	-	-	53.5	53.7	-	86.2	-	64.5	-	21.7	H	*2
	9626.0	-23.0	37.5	-	-	46.6	44.2	-	86.2	-	61.1	-	25.1	H	*2
	12032.5	-23.9	40.8	< 31.0	< 31.0	< 43.0	< 43.0	54.0	74.0	< 47.9	< 59.9	> 6.1	> 14.1	-	*1
21ch 2411.5 (High)	4823.0	-26.4	33.2	35.7	36.6	45.6	45.9	54.0	74.0	43.4	52.7	10.6	21.3	V	*1
	7234.5	-26.1	36.9	-	-	50.8	51.0	-	86.3	-	61.8	-	24.5	V	*2
	9646.0	-23.0	37.5	-	-	45.5	43.7	-	86.3	-	60.0	-	26.3	H	*2
	12057.5	-23.9	40.7	< 31.0	< 31.0	< 43.0	< 43.0	54.0	74.0	< 47.8	< 59.8	> 6.2	> 14.2	-	*1

Note1: This frequency is in the restriction band therefore it is applied the 15.209 Radiated emission limits, general requirements.

Note2: This frequency is not in the restriction band therefore these spurious emission shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power (15.247 (d)).

The radiated carrier level of each frequency is follows (RBW = 100 kHz);

- 105.8 dBuV/m at 2401 MHz
- 106.2 dBuV/m at 2406.5 MHz
- 106.3 dBuV/m at 2411.5 MHz

Calculation method

The RESULT is calculated as followings.

$$\text{RESULT (dBuV/m)} = \text{READING (dBuV)} + \text{Antenna Factor (dB/m)} + \text{Cable Loss (dB)}$$

The Cable loss include amplifier gain

Sample calculation at 4802 MHz result on the Ave.as follow:

$$\begin{aligned} \text{Result (dBuV/m)} &= \text{Reading} + \text{Antenna Factor} + \text{Cable Loss} = 43.4 + 33.1 - 26.4 = 50.1 \\ \text{Margin} &= \text{Limit} - \text{Result} = 54.0 - 50.1 = 3.9 \text{ (dBuV/m)} \end{aligned}$$

2.8 Transmitter AC power line conducted emissions

Test setup

Test setup was implemented according to the method of ANSI C63.4: 2003 clause 6 “General requirements for EUT equipment arrangements and operation” and Annex H.1 “AC power line conducted emission measurements setup”.

Test procedure

Measurement procedures were implemented according to the method of ANSI C63.4: 2003 clauses 7, clause 13.1.3 and Annex H.2 “AC power line conducted emission measurements”.

Exploratory measurements were used the spectrum analyzer to identify the frequency of the emission that has the highest amplitude relative to the limit by operating the EUT in a range of typical modes of operation, cable positions, and with a typical system equipment configuration and arrangement.

Final ac power line conducted emission measurements were performed based on the exploratory tests.

The EUT cable configuration and arrangement and mode of operation that produced the emission with the highest amplitude relative to the limit are selected for the final measurement.

When the measurement value is greater than average limitation the average detection measurements were performed.

Applicable rule and limitation

§15.207 (a) AC powerline conducted limits

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56 *	56 to 46 *
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

The lower limit applies at the band edges.

Test equipment used (refer to List of utilized test equipment)

TR04	PL01	LN06 for EUT	LN05 for AE	SA06	CL11
------	------	-----------------	----------------	------	------

Test results - Complied with requirement.

Test Data

Tested Date: May 26 2007

Temperature: 24 °C
Humidity: 45 %
Atmos. Press: 1012 hPa

Continuous Transmission (Worst case configuration)

No.	Frequency [MHz]	Reading		C.F. [dB]	Result		Limit		Margin		PHASE
		QP [dBuV]	AV [dBuV]		QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	
1	0.160	47.0	32.1	0.4	47.4	32.5	65.5	55.5	18.1	23.0	N
2	0.160	46.2	34.1	0.4	46.6	34.5	65.5	55.5	18.9	21.0	L
3	0.192	42.0	31.2	0.3	42.3	31.5	63.9	53.9	21.6	22.4	L
4	0.194	42.3	27.7	0.3	42.6	28.0	63.9	53.9	21.3	25.9	N
5	0.295	32.6	23.8	0.3	32.9	24.1	60.4	50.4	27.5	26.3	N
6	0.300	31.1	20.6	0.3	31.4	20.9	60.2	50.2	28.8	29.3	L
7	0.524	33.7	28.5	0.2	33.9	28.7	56.0	46.0	22.1	17.3	L
8	10.423	37.0	27.8	0.7	37.7	28.5	60.0	50.0	22.3	21.5	L
9	10.430	34.5	24.9	0.7	35.2	25.6	60.0	50.0	24.8	24.4	N
10	26.730	39.7	32.0	1.2	40.9	33.2	60.0	50.0	19.1	16.8	N
11	26.752	41.3	33.8	1.2	42.5	35.0	60.0	50.0	17.5	15.0	L

The power line conducted emission voltage is calculated by adding the LISN factor and Cable loss attenuation from the measured reading. The calculation is as follows:


Result = Reading + C. F
where C.F = LISN Factor + Cable Loss [dB]

Sample calculation at 0.524 MHz Ave. result as follow:


Result (dBuV) = Reading + C.F = 28.5 + 0.2 = 28.7 (dBuV)
Margin = Limit – Result = 46.0 – 28.7 = 17.3 (dBuV)

Graphical express of test result (0.15 MHz-30MHz)

AC Power line conducted emission. (Phase N)



AC Power line conducted emission. (Phase L)



2.9 Receiver Radiated spurious emissions

Test setup - Same as clause 2.7

Test procedure - Same as clause 2.7

Applicable rule and limitation at 3m

§15.109 radiated emission limitation

Frequency (MHz)	Measurement Distance (m)	Field Strength (uV/m)	Field Strength (dBuV/m)
30 – 88	3	100	40.0
88 – 216	3	150	43.5
216 – 960	3	200	46.0
Above 960	3	500	54.0

In the emission table above, the tighter limit applies at the band edges.

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector.

Test results - Complied with requirement.

2.9.1 Between 30 – 1000 MHz

Test equipment used (refer to List of utilized test equipment)

BA03	CL11	PR03	SA06	TR04
------	------	------	------	------

Test Data

Tested Date: May 25 2007

Temperature: 21 °C
Humidity: 55 %
Atmos. Press: 1007 hPa

2.9.1.1 Connected Antenna Type: Printed half wave dipole antenna

No.	Frequency [MHz]	Reading [dBuV]	Factor [dB/m]	Loss [dB]	Gain [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Antenna Polarization
1	43.28	49.8	9.9	4.1	29.8	34.0	40.0	6.0	Vert.
2	59.04	42.9	5.8	4.3	29.8	23.2	40.0	16.8	Vert.
3	62.76	44.3	5.7	4.4	29.8	24.6	40.0	15.4	Vert.
4	63.29	37.3	5.7	4.4	29.8	17.6	40.0	22.4	Hori.
5	95.27	32.4	9.1	4.7	29.7	16.5	43.5	27.0	Hori.
6	116.16	35.2	10.8	4.9	29.7	21.2	43.5	22.3	Hori.

Calculation method

The Correction Factors and RESULT are calculated as followings.

$$\text{Correction Factor (dB/m)} = \text{FACTOR (dB/m)} + \text{LOSS (dB)} - \text{GAIN (dB)}$$


$$\text{RESULT (dBuV/m)} = \text{READING (dBuV)} + \text{Correction Factor (dB/m)}$$

Sample calculation at 42.28 MHz Vertical result as follow:


$$\begin{aligned} \text{Result (dBuV/m)} &= \text{Reading} + \text{C.F} = 49.8 + 9.9 + 4.1 - 29.8 = 34.0 \\ \text{Margin} &= \text{Limit} - \text{Result} = 40.0 - 34.0 = 6.0 \text{ (dBuV/m)} \end{aligned}$$

Graphical express of test result (30MHz-1000MHz)

Antenna polarization: Horizontal



Antenna polarization: Vertical



2.9.1.2 Connected Antenna Type: Printed 1/4 wave monopole antenna

No.	Frequency [MHz]	Reading [dBuV]	Factor [dB/m]	Loss [dB]	Gain [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Antenna Polarization
1	42.79	51.3	10.2	4.1	29.8	35.8	40.0	4.2	Vert.
2	58.05	44.3	5.9	4.3	29.8	24.7	40.0	15.3	Vert.
3	62.80	44.4	5.7	4.4	29.8	24.7	40.0	15.3	Vert.
4	62.89	37.3	5.7	4.4	29.8	17.6	40.0	22.4	Hori.
5	95.56	32.4	9.1	4.7	29.7	16.5	43.5	27.0	Hori.
6	115.26	35.0	10.7	4.9	29.7	20.9	43.5	22.6	Hori.
7	234.04	33.5	11.8	5.7	29.6	21.4	46.0	24.6	Vert.

Calculation method

The Correction Factors and RESULT are calculated as followings.

$$\text{Correction Factor} = \text{FACTOR} + \text{LOSS} - \text{GAIN}$$

(dB/m) (dB/m) (dB) (dB)

$$\text{RESULT} = \text{READING} + \text{Correction Factor}$$

(dBuV/m) (dBuV) (dB/m)


Sample calculation at 42.79 MHz Vertical result as follow:

$$\text{Result (dBuV/m)} = \text{Reading} + \text{C.F} = 51.3 + 10.2 + 4.1 - 29.8 = 35.8$$


$$\text{Margin} = \text{Limit} - \text{Result} = 40.0 - 35.8 = 4.2 \text{ (dBuV/m)}$$

Graphical express of test result (30MHz-1000MHz)

Antenna polarization: Horizontal



Antenna polarization: Vertical



2.9.2 Above 1000 MHz**Test equipment used (refer to List of utilized test equipment)**

PR04	SH01	SA06	CL21	CL22	DH02		
------	------	------	------	------	------	--	--

Tested Date: May 25 2007

Temperature: 21 °C
Humidity: 55 %
Atmos. Press: 1007 hPa**2.9.2.1 Connected Antenna Type: Printed half wave dipole antenna**

There are no spurious emissions greater than noise floor

2.9.2.2 Connected Antenna Type: Printed 1/4 wave monopole antenna

There are no spurious emissions greater than noise floor

2.10 Receiver AC power line conducted emissions

Test setup - Same as clause 2.8

Test procedure - Same as clause 2.8

Applicable rule and limitation

§15.107 (a) AC power line conducted limits

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56 *	56 to 46 *
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.
The lower limit applies at the band edges.

Test equipment used (refer to List of utilized test equipment)

TR04	PL01	LN06 for EUT	LN05 for AE	SA06	CL11
------	------	-----------------	----------------	------	------

Test results - Complied with requirement.

Test Data

Tested Date: May 26 2007

Temperature: 24 °C
Humidity: 45 %
Atmos. Press: 1012 hPa

Operating Mode: Continuous Reception (Worst case configuration)

No.	Frequency [MHz]	Reading		C.F. [dB]	Result		Limit		Margin		PHASE
		QP [dBuV]	AV [dBuV]		QP [dBuV]	QP [dBuV]	QP [dBuV]	QP [dBuV]	QP [dBuV]	QP [dBuV]	
1	0.162	45.2	29.0	0.4	45.6	29.4	65.4	55.4	19.8	26.0	N
2	0.163	44.9	30.3	0.4	45.3	30.7	65.3	55.3	20.0	24.6	L
3	0.183	41.9	26.0	0.4	42.3	26.4	64.3	54.3	22.0	27.9	N
4	0.188	41.3	28.5	0.3	41.6	28.8	64.1	54.1	22.5	25.3	L
5	0.301	29.6	21.1	0.3	29.9	21.4	60.2	50.2	30.3	28.8	N
6	0.368	31.2	24.7	0.2	31.4	24.9	58.6	48.6	27.2	23.7	L
7	0.516	33.7	29.2	0.2	33.9	29.4	56.0	46.0	22.1	16.6	L
8	0.900	15.0	8.0	0.3	15.3	8.3	56.0	46.0	40.7	37.7	N
9	10.230	35.5	25.9	0.7	36.2	26.6	60.0	50.0	23.8	23.4	L
10	10.442	33.8	24.6	0.7	34.5	25.3	60.0	50.0	25.5	24.7	N
11	26.729	40.4	32.8	1.2	41.6	34.0	60.0	50.0	18.4	16.0	L
12	26.731	39.5	32.1	1.2	40.7	33.3	60.0	50.0	19.3	16.7	N

The power line conducted emission voltage is calculated by adding the LISN factor and Cable loss attenuation from the measured reading. The calculation is as follows:


Result = Reading + C. F
where C.F = LISN Factor + Cable Loss [dB]

Sample calculation at 26.729 MHz Ave. result as follow:


Result (dBuV) = Reading + C.F = 32.8 + 1.2 = 34.0 (dBuV)
Margin = Limit – Result = 50.0 – 34.0 = 16.0 (dBuV)

Graphical express of test result (0.15 MHz-30MHz)

AC Power line conducted emission. (Phase N)



AC Power line conducted emission. (Phase L)



2.11 Maximum Permissible Exposure (Exposure of Humans to RF Fields)

Limitation

15.247(i) systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines.

See 1.1307(b) (1) of this Chapter.

1.1310 The criteria of "General Population/ Uncontrolled Exposure" listed in the below table shall be used to evaluate the environmental impact of human exposure to radio-frequency radiation as specified in 1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of 2.1093 of this chapter.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/1500	30
1500-100,000	--	--	1.0	30

f = frequency in MHz

*Plane-wave equivalent power density

NOTE 2: *General population/uncontrolled* exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

The MPE distance calculations:

The Maximum Permissible Exposure (MPE) distance between the EUT's antenna and human body is calculated in accordance with FCC OET Bulletin 65 and Safety Code 6 of IC.

The MPE distance where the exposure level reaches the permitted exposure level can be calculated as below;

$$S = P * G / 4\pi R^2$$

Rearranging terms to calculate the MPE Distance

$$R = (P * G / 4\pi S)^{1/2}$$

Where:

In case of printed half wave dipole antenna

R = MPE Distance in cm

**P = Power in dBm (8.88 mW, Refer to page 22 in this report) at 2406.5 MHz
(worst case)**

G = Antenna Gain in numeric

(0.859 = -0.66dBi, Max. Antenna Gain, Refer to the submitted antenna spec.)

S = Power Density Limit in mW/cm²

(1.0 mW/cm², Max. permissible exposure limit above)

Then MPE Distance is 0.779 cm.

In case of printed 1/4 wave monopole antenna

R = MPE Distance in cm

**P = Power in dBm (8.88 mW, Refer to page 22 in this report) at 2406.5 MHz
(worst case)**

G = Antenna Gain in numeric

(1.151 = 0.61dBi, Max. Antenna Gain, Refer to the submitted antenna spec.)

S = Power Density Limit in mW/cm²

(1.0 mW/cm², Max. permissible exposure limit above)

Then MPE Distance is 0.902 cm.

Test results - Complied with requirement.

4 List of utilized test equipment/ calibration

RFT ID No.	Kind of Equipment and Precision	Manufacturer	Model No.	Serial Number	Calibration Date	Calibrated until
AC01	Anechoic Chamber	Japan Shiled Closure	203397C		2007/5/8	2008/5/6
BA03	Biological Antenna	CAHSE	CBL6111	1309	2007/5/14	2008/5/12
BI01	Biconical Antenna	SCHWARZBECK	VHA9103	2359	2007/5/21	2008/5/19
BRF1	Band Reject Filter (WCDMA2000)		BRF2000-06	VT0001	2007/4/24	2008/4/22
BRF2	Band Reject Filter (Bluetooth)	MICRO TRONICS	BRM50701	024	2007/4/26	2008/4/24
CL11	Antenna Cable	RFT	-	-	2006/6/7	2007/6/6
DC01	Directional Coupler	KRYTAR	1850	77202	2007/4/24	2008/4/22
HPF1	High Pass Filter (3500MHz)	TOKIMEC	TF323DCA	603	2007/4/24	2008/4/22
LA01	Logperiodic Antenna	SCHWARZBECK	USLP 9143	338	2007/5/21	2008/5/19
LN02	LISN (3ph 32A)	SCHWARZBECK	NSLK8128	8128-212	2007/2/2	2008/2/1
LN05	LISN	Kyoritsu	KNW-407	8-1773-2	2007/5/14	2008/5/12
LN06	LISN	Kyoritsu	KNW-407	8-1773-3	2007/5/14	2008/5/12
LN08	LISN (5uF)	SCHWARZBECK	NNBM8125	8126A-9262	2006/9/4	2007/9/3
LP01	Loop Antenna	EMCO	6502	3436	2007/1/16	2008/1/15
MA01	Active Monopole Antenna	SCHWARZBECK	VAMP9243	9438	2007/2/8	2008/2/7
PL01	Pulse Limiter	PMM	PL-01	0000J10109	2007/1/30	2008/1/29
PR03	Pre. Amplifier	Anritsu	HM648A	M41984	2007/5/14	2008/5/12
PR04	Pre. Amplifier (1-26G)	RFT	LNP126	060208-01	2007/2/6	2008/2/5
PR08	Pre. Amplifier	Sonoma Instrument	315	263504	2007/2/23	2008/2/22
SA06	Spectrum Analyzer (F/W: 3.60 SP1)	Rohde & Schwarz	FSP40	100071	2006/11/13	2007/11/12
SH01	Standard Horn Antenna (18-26G)	A.H. Systems	SAS-572	208	2006/5/3	2008/5/1
SH02	Standard Horn Antenna (18-26G)	A.H. Systems	SAS-572	209	2006/5/3	2008/5/1
SH03	Standard Horn Antenna (26-40G)	A.H. Systems	SAS-573	150	2006/5/3	2008/5/1
SH04	Standard Horn Antenna (26-40G)	A.H. Systems	SAS-573	151	2006/5/3	2008/5/1
TL01	Transient Limiter	Agilent Technologies	11947A	3107A04000	2006/11/6	2007/11/5
CL21	RF Cable(0.5m)	Suhner	-	-	2007/5/14	2008/5/13
CL22	RF Cable(4m)	Suhner	-	-	2007/5/14	2008/5/13
TR04	Test Receiver (F/W : 3.82 SP1)	Rohde & Schwarz	ESCI	100447	2006/9/27	2007/9/26

RFT ID No.	Kind of Equipment and Precision	Manufacturer	Model No.	Serial Number	Calibration Date	Calibrated until
AT05	Attenuator 3dB 50W	Weinschel	45-3-33	LC530	2007/2/5	2008/2/4
AT12	Attenuator 6dB 30W	FUJISOKU	FAT-530A	63454	2007/2/5	2008/2/4
AT14	Attenuator	JFW	50HF-003N	—	2007/4/25	2008/4/23
AT15	Attenuator	JFW	50HF-006N	—	2007/4/25	2008/4/23
AT20	Attenuator	JFW	50HF-010N	—	2007/3/16	2008/3/14
AT21	Attenuator 6dB 5W 18GHz	Weinschel	WA2-6-34	A1020	2007/3/9	2008/3/7
AT22	Attenuator 6dB 5W 18GHz	Weinschel	WA2-6-34	A1021	2007/3/9	2008/3/7
AT23	Attenuator 6dB 5W 18GHz	Weinschel	WA2-6-34	A1022	2007/3/9	2008/3/7
AT24	Attenuator 6dB 5W 18GHz	Weinschel	WA2-6-34	A1023	2007/3/9	2008/3/7
AT25	Attenuator 6dB 5W 18GHz	Weinschel	WA2-6-34	A1024	2007/3/9	2008/3/7
AT26	Attenuator 6dB 5W 18GHz	Weinschel	WA2-6-34	A1025	2007/3/9	2008/3/7
AT27	Attenuator 10dB 5W 18GHz	Weinschel	WA2-10-34	A1026	2007/3/9	2008/3/7
AT28	Attenuator 10dB 5W 18GHz	Weinschel	WA2-10-34	A1027	2007/3/9	2008/3/7
AT29	Attenuator 10dB 5W 18GHz	Weinschel	WA2-10-34	A1028	2007/3/9	2008/3/7
AT30	Attenuator 20dB 5W 18GHz	Weinschel	WA2-20-34	A1029	2007/3/9	2008/3/7
AT31	Attenuator 20dB 5W 18GHz	Weinschel	WA2-20-34	A1030	2007/3/9	2008/3/7
AT32	Attenuator 20dB 5W 18GHz	Weinschel	WA2-20-34	A1031	2007/3/9	2008/3/7
DH01	DRG Horn Antenna	A.H. Systems	SAS-571	785	2006/2/6	2008/2/5
DH02	DRG Horn Antenna	A.H. Systems	SAS-200/571	239	2007/4/20	2008/4/18
PM01	Power Meter	Rohde & Schwarz	NRVS	100055	2007/1/29	2008/1/28
PU01	Power Meter Insertion Unit	Rohde & Schwarz	URV5-Z4	100055	2007/1/29	2008/1/28
RC02	Radio communication tester (F/W : V4.10)	Rohde & Schwarz	CMU200	105097	2006/9/14	2007/9/13
SG01	Signal Generator	Rohde & Schwarz	SML03	100325	2007/2/2	2008/2/1
SG05	Signal Generator	Rohde & Schwarz	SMR20	100905	2006/10/17	2007/10/16
TA02	Dummy Load	Mini-Circuits	DL-30N	-	2007/2/23	2008/2/22
TA03	Dummy Load	Mini-Circuits	DL-30N	-	2007/2/23	2008/2/22
TA04	Dummy Load (4GHz, 50W)	Weinschel	WA1423-4	A462	2007/3/9	2008/3/7
TA05	Dummy Load (4GHz, 50W)	Weinschel	WA1423-4	A463	2007/3/9	2008/3/7
TC01	Temperature Chamber	ESPEC	SH-641	92000964	2007/4/23	2008/4/21

RFT ID No.	Kind of Equipment and Precision	Manufacturer	Model No.	Serial Number	Calibration Date	Calibrated until
AC51	AC power supply	TAKASAGO	AA2000D	506960030014	not applicable	not applicable
AC52	AC power supply	KIKUSUI	PCR6000W		not applicable	not applicable
AF51	Active Filter	NF corp.	DV-04	434339	not applicable	not applicable
BC51	Burst Clamp	SCHAFFNER	CDN8015	21369	not applicable	not applicable
CG51	Comb Generator	tsj	TG-C2	TGC2-0009	not applicable	not applicable
CG52	Comb Generator	tsj	TG-R2	TGR2-0009	not applicable	not applicable
CJ51	CDN Calibration JIG 1	RFT	-	-	not applicable	not applicable
CJ52	CDN Calibration JIG 2	RFT	-	-	not applicable	not applicable
CJ53	EM clamp Calibration JIG 1	RFT	-	-	not applicable	not applicable
CJ54	EM clamp Calibration JIG 2	RFT	-	-	not applicable	not applicable
DC51	DC power supply	KIKUSUI	PMC18-3A	DF002941	not applicable	not applicable
DC52	DC power supply	KIKUSUI			not applicable	not applicable
MP51	Microphone	G.R.A.S	26AK + 12AK	50941 + 58712	not applicable	not applicable
MS51	Mouth Simulator	G.R.A.S	44AA	52222	not applicable	not applicable
TS51	TEMSEL	KYORITSU	KTC-5055	8S-688-6	not applicable	not applicable

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.