

Report No. : AD009566-1 Date : 2003 July 19

Applicant : Mattel Asia Pacific Sourcing Ltd.

13/F., South Tower, World Finance Centre,

Harbour City, Tsim Sha Tsui, Kowloon, Hong Kong.

Sample Description : One(1) submitted sample stated to be <u>1/64 Hot Wheels R/C</u>

of Model No. C0640 Motor Crossed.

Rating : 4 x 1.5 V button cells No. of sample(s) : Three(3) pieces ***

Date Received : 2003 May 27.

2003 May 30.

Test Period : 2003 May 30 – 2003 July 18.

Test Requested : FCC Part 15 Certification

Test Method : FCC Rules and Regulations Part 15 – May 2002

ANSI C63.4 – 1992

Test Result : See attached sheet(s) from page 2 to 11.

Conclusion : The submitted sample was found to comply with requirement of FCC

Part 15 Subpart C.

For and on behalf of

CMA Testing and Certification Laboratories

Authorized Signature: Page 1 of 11

Danny Chui EMC Engineer - EL. Division

FCC ID: PIYC0640-03A4T



Report No. : AD009566-1 Date : 2003 July 19

Table of Contents

1	G	eneral Information	
	1.1	General Description	3
	1.2	Related Submittal Grants	
	1.3	Location of the test site	
	1.4	List of measuring equipment	
2	D	escription of the radiated emission test	
	2.1	Test Procedure	
	2.2	Test Result	6
	2.3	Radiated Emission Measurement Data	
3	D	escription of the Line-conducted Test	8
	3.1	Test Procedure	8
	3.2	Test Result	8
	3.3	Graph and Table of Conducted Emission Measurement Data	8
4	Pł	hotograph	
	4.1	Photographs of the Test Setup for Radiated Emission and Conduction Emission	9
	4.2	Photographs of the External and Internal Configurations of the EUT	
5	Su	ipplementary document	
	5.1	Bandwidth	10
	6	Appendices	11



Report No. : AD009566-1 Date : 2003 July 19

1 General Information

1.1 General Description

The equipment under test (EUT) is a transmitter for 1/64 Hot Wheels R/C operating at 49.860 MHz which is controlled by a crystal. The EUT is powered by 4 x 1.5 V button cells. There two joystick in the front of the EUT. When the forward / backward joystick pushed once, it transmit a radio frequency for receiver going forward / backward. When the left / right joystick pushed once, it transmit a radio frequency for receiver turn left / right.

The brief circuit description is listed as follows:

- Q7, X1 and associated circuit act as oscillator
- Q5 and associated circuit act as amplifier
- U1 and associated circuit act as encode
- Q1, Q2 and associated circuit act as power control

1.2 Related Submittal Grants

This is a single application for certification of a transmitter. The receiver for this transmitter is authorized by Certification procedure.



Report No. : AD009566-1 Date : 2003 July 19

1.3 Location of the test site

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 1992. An Open Area Testing Site is set up for investigation and located at :

Top of the Roof, Yan Hing Centre, 9 – 13 Wong Chuk Yeung Street, Fo Tan, Shatin, New Territories, Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 1992. A double shielded room is located at :

Roof Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.



Report No. : AD009566-1 Date : 2003 July 19

1.4 List of measuring equipment

Equipment	Manufacturer	Model No.	Serial No.	Calibration Certification No.
EMI Test Receiver	R&S	ESCS30	100001	S21141
Broadband Antenna	Schaffner	CBL6113B	2718	AC1753
Signal Generator	IFR	2023B	202302/938	Nil
LISN	R&S	ESH3-Z5	100038	S21142
Pulse Limiter	R&S	ESH3-Z2	100001	20-73194
Biconical Antenna	R&S	HK116	837414/004	4000.7752.02



Report No. : AD009566-1 Date : 2003 July 19

2 Description of the radiated emission test

2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 1992.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

The device was rotated through three orthogonal axes to determine which attitude and configuration produce the highest emission during measurement.

2.2 Test Result

Peak Detector data was measured unless otherwise stated.

* Emissions appearing within the restricted bands shall follow the requirement of section 15.205.

It was found that the EUT meet the FCC requirement.



Report No. : AD009566-1 Date : 2003 July 19

2.3 Radiated Emission Measurement Data

Radiated emission

pursuant to

the requirement of FCC Part 15 subpart C

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dBµV/m)	Antenna and Cable factor (dB)	Averaging factor (-dB)	Field Strength (dBµV/m)	Limit at 3m (dBµV/m)	Margin (dB)
49.861	V	65.3	11.4	4.7	72.0	80.0	-8.0
99.720	Н	14.8	10.0		24.8	43.5	-18.7
149.578	Н	15.6	12.2		27.8	43.5	-15.7
199.440	Н	14.6	10.5		25.1	43.5	-18.4
*249.302	Н	13.8	10.7		24.5	46.0	-21.5
299.163	Н	11.8	13.9		25.7	46.0	-20.3
349.023	Н	16.9	15.3		32.2	46.0	-13.8
398.880	Н	18.1	15.3		33.4	46.0	-12.6
448.743	Н	15.3	18.6		33.9	46.0	-12.1
498.603	Н	17.0	18.6		35.6	46.0	-10.4

Page 7 of 11

FCC ID: PIYC0640-03A4T



Report No. : AD009566-1 Date : 2003 July 19

3 Description of the Line-conducted Test

3.1 Test Procedure

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 1992. The EUT was setup as described in the procedures, and both lines were measured.

3.2 Test Result

No measurement is required as the EUT is a battery-operated product.

3.3 Graph and Table of Conducted Emission Measurement Data

Not Applicable



Report No. : AD009566-1 Date : 2003 July 19

- 4 Photograph
- 4.1 Photographs of the Test Setup for Radiated Emission and Conduction Emission

For electronic filing, the photos are saved with filename TSup1.jpg to TSup2.jpg

4.2 Photographs of the External and Internal Configurations of the EUT

For electronic filing, the photos are saved with filename ExtPho1.jpg to ExtPho2.jpg and IntPho1.jpg to IntPho2.jpg.



Report No. : AD009566-1 Date : 2003 July 19

5 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

Document	Filename
ID Label/Location	LabelSmpl.pdf
Block Diagram	BlkDia.pdf
Schematic Diagram	Schem.pdf
Users Manual	UserMan.pdf
Operational Description	OpDes.pdf

5.1 Bandwidth

The plot on saved in TestRpt2.pdf shows the fundamental emission is confined in the specified band. The field strength of any emission appearing between the band edges and up to 10 kHz above and below the band edges (49.81 and 49.91 MHz) is at least 26 dB below the carrier level. It meets the requirement of Section 15.235(b).

5.2 The duty cycle is simply the on-time divided by the period :

The duration of one cycle = 15.72 ms.

Effective period of the cycle = (1.29 x 4) ms. + (0.4 x 10) ms.

 $= 9.16 \, \text{ms}.$

Duty Cycle = 9.16/15.72 ms.

= 0.582

Therefore, the average factor is found by $20 \log_{10} 0.582 = -4.7 \text{ dB}$



Report No. : AD009566-1 Date : 2003 July 19

6 Appendices

Photos of the set-up of Radiated Emissions	1 page
Photos of External Configurations	1 page
Photos of Internal Configurations	1 page
ID Label/Location	1 page
Bandwidth Plot	1 page
Average Factor	2 pages
Block Diagram	1 page
Schematics	1 page
User Manual	6 pages
Operation Description	1 page
	Photos of External Configurations Photos of Internal Configurations ID Label/Location Bandwidth Plot Average Factor Block Diagram Schematics User Manual

***** End of Report *****