



**TEST REPORT**

Report No. : AM0064511(6) Date : 2010-12-24

Application No. : LM022712(3)

Applicant : Mattel Asia Pacific Sourcing Ltd.  
13/F., South Tower,  
World Finance Center,  
Harbour City, Tsimshatsui,  
Kowloon, Hong Kong.

Sample Description : One(1) item of submitted sample stated to be:

Sample Description	Model no.
RC CARS 2 EZ DRIVER-MCMISSLE	T9477
RC CARS 2 EZ DRIVER-MCQUEEN	T9478

Radio Frequency : 27.145MHz Transmitter  
Rating : 2 x 1.5V AA size batteries  
No. of submitted sample : Two (2) piece (s)

Date Received : 2010-11-11.

Test Period : 2010-11-22 to 2010-11-23.

Test Requested : FCC Part 15 Certification.

Test Method : 47 CFR Part 15 (10-1-09 Edition)  
ANSI C63.4 – 2003

Test Result : See attached sheet(s) from page 2 to 11.

Conclusion : The submitted sample was found to comply with requirement of FCC Part 15 Subpart C.

Remark : All two models are the same in circuitry, components and construction. Therefore, model T9478 was chosen to be the representative of the test sample.

*For and on behalf of*  
CMA Industrial Development Foundation Limited

Authorized Signature : \_\_\_\_\_

  
Mr. WONG Lap-pong, Andrew  
Assistant Manager  
Electrical Division

Page 1 of 11

FCC ID: PIYT9477-11A2T



**TEST REPORT**

Report No. : AM0064511(6)

Date : 2010-12-24

**Table of Contents**

1 General Information ..... 3

    1.1 General Description..... 3

    1.2 Location of the test site ..... 4

    1.3 List of measuring equipment..... 5

    1.4 Measurement Uncertainty ..... 5

2 Description of the radiated emission test..... 6

    2.1 Test Procedure..... 6

    2.2 Test Result..... 6

    2.3 Radiated Emission Measurement Data..... 7

3 Description of the Line-conducted Test ..... 8

    3.1 Test Procedure..... 8

    3.2 Test Result..... 8

    3.3 Graph and Table of Conducted Emission Measurement Data ..... 8

4 Photograph..... 9

    4.1 Photographs of the Test Setup for Radiated Emission and Conducted Emission ..... 9

    4.2 Photographs of the External and Internal Configurations of the EUT ..... 9

5 Supplementary document ..... 10

    5.1 Bandwidth ..... 10

    5.2 Duty cycle ..... 10

    5.3 Transmission time ..... 10

6 Appendices ..... 11



## **TEST REPORT**

Report No. : AM0064511(6)

Date : 2010-12-24

### **1 General Information**

#### **1.1 General Description**

The equipment under test (EUT) is a transmitter for RC CARS 2 EZ DRIVER-MCQUEEN. It operates at 27.145MHz and the oscillation of radio control is generated by a crystal. The EUT is powered by 2 x 1.5V AA size batteries. There are two buttons and a steering wheel on the EUT. When the button is pressed or the steering wheel is turned, the EUT will transmit control signal to the receiver.

The antenna is permanently attached in EUT and the radio output power is unable to adjust.

The brief circuit description is listed as follows:

- U1 and its associated circuit act as an encoder.
- Y1 and its associated circuit act as an oscillator.



## **TEST REPORT**

Report No. : AM0064511(6)

Date : 2010-12-24

### **1.2 Location of the test site**

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003. A Semi-Anechoic Chamber Testing Site is set up for investigation and located at:

Ground Floor, Yan Hing Centre,  
9 – 13 Wong Chuk Yeung Street,  
Fo Tan, Shatin,  
New Territories,  
Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. A shielded room is located at:

Ground Floor, Yan Hing Centre,  
9 – 13 Wong Chuk Yeung Street,  
Fo Tan, Shatin,  
New Territories,  
Hong Kong.



## TEST REPORT

Report No. : AM0064511(6)

Date : 2010-12-24

### 1.3 List of measuring equipment

Equipment	Manufacturer	Model No.	Serial No.	Calibration Due Date
EMI Test Receiver	R&S	ESCI	100152	2010 December 23
Loop Antenna	EMCO	6502	00056620	2011 August 24
Broadband Antenna	Schaffner	CBL6112B	2692	2011 May 31
Coaxial Cable	Schaffner	RG 213/U	N/A	2012 August 03
Coaxial Cable	Suhner	RG 214/U	N/A	2012 August 03

### 1.4 Measurement Uncertainty

The reported uncertainty is based on a standard uncertainty multiplied by a coverage factor  $k=2$ , providing a level of confidence of approximately 95%.

#### Radiated emissions

Frequency	Uncertainty ( $U_{lab}$ )
30MHz ~ 200MHz (Horizontal)	4.63dB
30MHz ~ 200MHz (Vertical)	4.64dB
200MHz ~ 1000MHz (Horizontal)	4.65dB
200MHz ~ 1000MHz (Vertical)	4.64dB

#### Conducted emissions

Frequency	Uncertainty ( $U_{lab}$ )
150kHz ~ 30MHz	3.04dB



## **TEST REPORT**

Report No. : AM0064511(6)

Date : 2010-12-24

### **2 Description of the radiated emission test**

#### **2.1 Test Procedure**

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

For below 30MHz, a loop antenna with its vertical plane is placed 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1 m above the ground.

The device was rotated through three orthogonal axes to determine which attitude and configuration produce the highest emission during measurement.

#### **2.2 Test Result**

Peak Detector data was measured unless otherwise stated.

“#” means emissions appearing within the restricted bands shall follow the requirement of section 15.205.

The frequencies from fundamental up to the tenth harmonics were investigated, and emissions more 20dB below limit were not reported. Thus, those highest emissions were presented in next page (section 2.3).

It was found that the EUT meet the FCC requirement.



## TEST REPORT

Report No. : AM0064511(6)

Date : 2010-12-24

### 2.3 Radiated Emission Measurement Data

#### Radiated emission

pursuant to

the requirement of FCC Part 15 subpart C

Environmental conditions:

Parameter	Recorded value	
Ambient temperature:	23	° C
Relative humidity:	60	%

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dBμV)	Antenna Factor and Cable Loss (dB/m)	Average Factor (dB)	Field Strength at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
27.145	V	57.0	9.9	-5.8	61.1	80.0	-18.9
54.290	V	24.2	8.4	-	32.6	40.0	-7.4
81.433	V	19.8	7.5	-	27.3	40.0	-12.7
#108.581	V	14.5	11.3	-	25.8	43.5	-17.7
#135.724	V	14.0	12.6	-	26.6	43.5	-16.9
#162.874	V	11.9	10.9	-	22.8	43.5	-20.7
190.014	V	14.0	10.0	-	24.0	43.5	-19.5
217.162	H	19.7	10.5	-	30.2	46.0	-15.8
#244.306	H	26.8	10.5	-	37.3	46.0	-8.7
#271.452	H	25.2	14.3	-	39.5	46.0	-6.5

FCC ID: PIYT9477-11A2T

Page 7 of 11



## **TEST REPORT**

Report No. : AM0064511(6)

Date : 2010-12-24

### **3 Description of the Line-conducted Test**

#### **3.1 Test Procedure**

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. The EUT was setup as described in the procedures, and both lines were measured.

#### **3.2 Test Result**

No measurement is required as the EUT is a battery-operated product.

#### **3.3 Graph and Table of Conducted Emission Measurement Data**

Not Applicable



## **TEST REPORT**

Report No. : AM0064511(6)

Date : 2010-12-24

### **4 Photograph**

#### **4.1 Photographs of the Test Setup for Radiated Emission and Conducted Emission**

For electronic filing, the photos are saved with filename TSup1.jpg to TSup2.jpg.

#### **4.2 Photographs of the External and Internal Configurations of the EUT**

For electronic filing, the photos are saved with filename ExPho1.jpg to ExPho2.jpg and InPho1.jpg to InPho2.jpg.



## TEST REPORT

Report No. : AM0064511(6)

Date : 2010-12-24

### 5 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

Document	Filename
ID Label/Location	LabelSmp.jpg
Block Diagram	BlkDia.pdf
Schematic Diagram	Schem.pdf
Users Manual	UserMan.pdf
Operational Description	OpDes.pdf

#### 5.1 Bandwidth

The plot on saved in TestRpt2.pdf shows the fundamental emission is confined in the specified band. It also shows that the band edge met the 15.209 requirement at 26.9599 and 27.2801 MHz.

#### 5.2 Duty cycle

The duty cycle is simply the on-time divided by the period:

$$\begin{aligned} \text{The duration of one cycle} &= 32.40\text{ms} \\ \text{Effective period of the cycle} &= 0.98\text{ms} \times 8 + 0.49\text{ms} \times 18 \\ &= 16.66\text{ms} \\ \text{Duty Cycle} &= 16.66\text{ms} / 32.40\text{ms} \\ &= 0.51 \end{aligned}$$

Therefore, the average factor is found by  $20 \log_{10} 0.51 = -5.8\text{dB}$

#### 5.3 Transmission time

Not Applicable



# CMA Testing and Certification Laboratories

廠商會檢定中心

## TEST REPORT

Report No. : AM0064511(6)

Date : 2010-12-24

### 6 Appendices

A1.	Photos of the set-up of Radiated Emissions	1	page
A2.	Photos of External Configurations	1	page
A3.	Photos of Internal Configurations	1	page
A4.	ID Label/Location	1	page
A5.	Bandwidth Plot	1	page
A6.	Average Factor	2	pages
A7.	Block Diagram	1	page
A8.	Schematics Diagram	1	page
A9.	User Manual	2	pages
A10.	Operation Description	1	page

\*\*\*\*\* End of Report \*\*\*\*\*