



**CMA Testing
and Certification
Laboratories**

廠商會檢定中心

TEST REPORT

Report No. : AM0064466(4) Date : 2010-12-22

Application No. : LM022698(5)

Applicant : Mattel Asia Pacific Sourcing Ltd.
13/F., South Tower,
World Finance Center,
Harbour City, Tsimshatsui,
Kowloon, Hong Kong.

Sample Description : One(1) item of submitted sample stated to be RC Cars 2 EZ Driver-Mater
of Model No. T9479
Radio Frequency : 49.860MHz Receiver
Rating : 3 x 1.5V AA size batteries
No. of submitted sample : Six (6) piece (s)

Date Received : 2010-11-11.

Test Period : 2010-11-23 to 2010-11-26.

Test Requested : FCC Part 15 Certification.

Test Method : 47 CFR Part 15 (10-1-09 Edition)
ANSI C63.4 – 2003

Test Result : See attached sheet(s) from page 2 to 11.

Conclusion : The submitted sample was found to comply with requirement of FCC Part 15
Subpart B.

For and on behalf of
CMA Industrial Development Foundation Limited

Authorized Signature : _____


Mr. WONG Lap-pong, Andrew
Assistant Manager
Electrical Division

Page 1 of 11

FCC ID: PIYT9479-11A4R



TEST REPORT

Report No. : AM0064466(4)

Date : 2010-12-22

Table of Contents

1 General Information 3

 1.1 General Description 3

 1.2 Location of the test site 4

 1.3 List of measuring equipment 5

 1.4 Measurement Uncertainty 5

2 Description of the radiated emission test 6

 2.1 Test Procedure 6

 2.2 Test Result 6

 2.3 Radiated Emission Measurement Data 7

3 Description of the Line-conducted Test 8

 3.1 Test Procedure 8

 3.2 Test Result 8

 3.3 Graph and Table of Conducted Emission Measurement Data 8

4 Photograph 9

 4.1 Photographs of the Test Setup for Radiated Emission and Conducted Emission 9

 4.2 Photographs of the External and Internal Configurations of the EUT 9

5 Supplementary document 10

 5.1 Bandwidth 10

 5.2 Duty cycle 10

 5.3 Transmission time 10

6 Appendices 11



TEST REPORT

Report No. : AM0064466(4)

Date : 2010-12-22

1 General Information

1.1 General Description

The equipment under test (EUT) is a receiver for RC Cars 2 EZ Driver-Mater. It operates at 49.860MHz and the oscillation of radio control is generated by a LRC circuit. The EUT is powered by 3 x 1.5V AA size batteries. When the EUT received a radio control signal, it will take the corresponding action.

The brief circuit description is listed as follows:

- Q1 and its associated circuit act as a super-regenerative receiver.
- Q2, Z1 and its associated circuit act as a voltage regulator.
- U1 and its associated circuit act as a decoder.
- Q4 ~ Q9 and its associated circuit act as a motor driver for M1.
- Q10 ~ Q15 and its associated circuit act as a motor driver for M2.



TEST REPORT

Report No. : AM0064466(4)

Date : 2010-12-22

1.2 Location of the test site

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003. A Semi-Anechoic Chamber Testing Site is set up for investigation and located at:

Ground Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. A shielded room is located at :

Ground Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.



TEST REPORT

Report No. : AM0064466(4)

Date : 2010-12-22

1.3 List of measuring equipment

Equipment	Manufacturer	Model No.	Serial No.	Calibration Due Date
EMI Test Receiver	R&S	ESCI	100152	2010 December 23
Broadband Antenna	Schaffner	CBL6112B	2692	2011 May 31
Coaxial Cable	Schaffner	RG213/U	N/A	2012 August 03
Coaxial Cable	Suhner	RG214/U	N/A	2012 August 03

1.4 Measurement Uncertainty

The reported uncertainty is based on a standard uncertainty multiplied by a coverage factor $k=2$, providing a level of confidence of approximately 95%.

Radiated emissions

Frequency	Uncertainty (U_{lab})
30MHz ~ 200MHz (Horizontal)	4.63dB
30MHz ~ 200MHz (Vertical)	4.64dB
200MHz ~1000MHz (Horizontal)	4.65dB
200MHz ~1000MHz (Vertical)	4.64dB

Conducted emissions

Frequency	Uncertainty (U_{lab})
150kHz ~ 30MHz	3.04dB



TEST REPORT

Report No. : AM0064466(4)

Date : 2010-12-22

2 Description of the radiated emission test

2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

For below 30MHz, a loop antenna with its vertical plane is placed 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1 m above the ground.

A signal generator was used to radiate an unmodulated continuous wave (CW) signal to the EUT (superregenerative receiver) at its operating frequency in order to “cohere” the characteristic broadband emissions from the receiver.

2.2 Test Result

The frequencies from 30MHz to 1000MHz were investigated, and emissions more 20dB below limit were not reported. Thus, those highest emissions were presented in next page (section 2.3)

The emissions meeting the requirement of section 15.109 are based on measurements employing the CISPR quasi-peak detector below 1000MHz and average detector for frequencies above 1000MHz.

It was found that the EUT meet the FCC requirement.



TEST REPORT

Report No. : AM0064466(4)

Date : 2010-12-22

2.3 Radiated Emission Measurement Data

Radiated emission

pursuant to

the requirement of FCC Part 15 subpart B

Environmental conditions:

Parameter	Recorded value	
Ambient temperature:	24	° C
Relative humidity:	59	%

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dBµV)	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dBµV/m)	Limit at 3m (dBµV/m)	Margin (dB)
50.786	V	22.7	8.4	31.1	40.0	- 8.9
51.245	V	26.9	8.4	35.3	40.0	- 4.7
51.702	V	28.1	8.4	36.5	40.0	- 3.5
52.156	V	27.5	8.4	35.9	40.0	- 4.1
52.635	V	25.2	8.4	33.6	40.0	- 6.4
102.985	V	14.8	11.3	26.1	43.5	- 17.4
103.443	V	15.4	11.3	26.7	43.5	- 16.8
103.920	V	15.1	11.3	26.4	43.5	- 17.1
155.657	V	9.5	12.2	21.7	43.5	- 21.8
156.139	V	9.1	12.2	21.3	43.5	- 22.2

FCC ID: PIYT9479-11A4R

Page 7 of 11



TEST REPORT

Report No. : AM0064466(4)

Date : 2010-12-22

3 Description of the Line-conducted Test

3.1 Test Procedure

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. The EUT was setup as described in the procedures, and both lines were measured.

3.2 Test Result

No measurement is required as the EUT is a battery-operated product.

3.3 Graph and Table of Conducted Emission Measurement Data

Not Applicable



TEST REPORT

Report No. : AM0064466(4)

Date : 2010-12-22

4 Photograph

4.1 Photographs of the Test Setup for Radiated Emission and Conducted Emission

For electronic filing, the photos are saved with filename TSup1.jpg to TSup2.jpg.

4.2 Photographs of the External and Internal Configurations of the EUT

For electronic filing, the photos are saved with filename ExPho1.jpg to ExPho2.jpg and InPho1.jpg to InPho2.jpg.



TEST REPORT

Report No. : AM0064466(4)

Date : 2010-12-22

5 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

Document	Filename
ID Label/Location	LabelSmp.jpg
Block Diagram	BlkDia.pdf
Schematic Diagram	Schem.pdf
Users Manual	UserMan.pdf
Operational Description	OpDes.pdf

5.1 Bandwidth

Not Applicable

5.2 Duty cycle

Not Applicable

5.3 Transmission time

Not Applicable



TEST REPORT

Report No. : AM0064466(4)

Date : 2010-12-22

6 Appendices

A1.	Photos of the set-up of Radiated Emissions	1	page
A2.	Photos of External Configurations	1	page
A3.	Photos of Internal Configurations	1	page
A4.	ID Label/Location	1	page
A5.	Block Diagram	1	page
A6.	Schematics Diagram	1	page
A7.	User Manual	2	pages
A8.	Operation Description	1	page

***** End of Report *****