



HYUNDAI CALIBRATION & CERTIFICATION TECH. CO., LTD.

Product Compliance Division, EMC Team
SAN 136-1, AMI-RI, BUBAL-EUP, ICHEON-SI, KYOUNKI-DO, 467-701, KOREA
TEL : +82 31 639 8518 FAX : +82 31 639 8525

CERTIFICATION

Manufacture:
IMAGEQUEST CO., LTD.

**SAN 136-1, AMI-RI, BUBAL-EUP, ICHEON-SI,
KYOUNKI-DO, 467-701, KOREA**

IMAGEQUEST FRN : 0005-8664-39

Date of Issue : APRIL 24, 2003

Test Report No.: HCT-F03-0409

**Test Site: HYUNDAI CALIBRATION & CERTIFICATION
TECHNOLOGIES CO., LTD.**

HCT FRN : 0005-8664-21

FCC ID :

PJIL19C0D060

MODEL / TYPE :

L90D/L19C0D060

Rule Part(s):	Part 15 & 2; ET Docket 95-19
Equipment Class:	FCC Class B Peripheral Device (JBP)
Standard(s):	FCC Class B: 1998 (CISPR 22)
EUT Type:	19" LCD Monitor
Max. Resolution(s):	Analog:1280 X 1024(@80.0KHz/75Hz), Digital: 1280 X 1024(@63.9KHz/60Hz)
Model(s):	L90D
Port/Connector(s)	15-pin D-sub VGA, 20-pin DVI-D (Digital RGB) connector, AUDIO IN/OUT.
LCD Panel	Samsung Electronics (LTM190E1-L01)

This equipment has been shown to be in compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-1992 (Grant Notes: #19, #28).

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Ki Soo Kim

Report prepared by : Ki-Soo Kim

Manager of EMC Tech. Part



HYUNDAI CALIBRATION & CERTIFICATION TECH. CO., LTD.



TABLE OF CONTENTS

	PAGE
REPORT COVER	1
TABLE OF CONTENTS	2
1.1 SCOPE	3
2.1 INTRODUCTION (SITE DESCRIPTION)	4
3.1 PRODUCTION INFORMATION	5
4.1 DESCRIPTION OF TESTS (CONDUCTED)	6
4.3 DESCRIPTION OF TESTS (RADIATED)	7
5.1 LIST OF SUPPORT EQUIPMENT	8-9
6.1 TEST DATA (CONDUCTED)	10-14
7.1 TEST DATA (RADIATED)	15
8.1 SIMPLE CALCULATIONS	16
9.1 TEST EQUIPMENT	17
10.1 TEST SOFTWARE USED	18
11.1 CONCLUSION	19

ATTACHMENT A: FCC ID LABEL & LOCATION

ATTACHMENT B: EXTERNAL PHOTOGRAPHS

ATTACHMENT C: BLOCK DIAGRAM(S)

ATTACHMENT D: TEST SETUP PHOTOGRAPHS

ATTACHMENT E: USER'S MANUAL

ATTACHMENT F-1: INTERNAL PHOTOGRAPHS

ATTACHMENT F-2: INTERNAL PHOTOGRAPHS

ATTACHMENT G: CIRCUIT

MEASUREMENT REPORT

1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission.

Applicant Name: IMAGEQUEST

Address: SAN 136-1, AMI-RI , BUBAL-EUP, ICHEON-SI,
KYOUWKI-DO, 467-701,KOREA

- **FCC ID : PJIL19C0D060**

- Equipment Class: FCC Class B Peripheral Device (JBP)
- EUT Type: 19" LCD MONITOR
- Model(s): L90D
- LCD Panel: Samsung Electronics (LTM190E1-L01)
- Max. Resolution: Analog:1280 X 1024(@80.0KHz/75Hz), Digital: 1280 X 1024(@63.9KHz/60Hz)
- Frequency Range: V-Sync: 56Hz – 75Hz , H-Sync: 31KHz – 80KHz
- Cable(s): Shielded D-Sub (with ferrite on both ends), Shielded DVI-D (with ferrite on both ends)
- Power Cord: Unshielded
- Rule Part(s): FCC Part 15 Subpart B
- Test Procedure(s): ANSI C63.4 (1992)
- Dates of Tests: March 29, 2003 ~ April 14, 2003
- Place of Tests: 254-1,MAEKOK-RI,HOBUP-MYUN,ICHON-SI,KYOUWKI-DO,467-701,KOREA

2.1 INTRODUCTION

The measurement procedure described in American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40GHz (ANSIC63.4-1992) was used in determining radiated and conducted emissions emanating from **IMAGEQUEST CO.,LTD. 19-inch LCD Monitor FCC ID: PJIL19C0D060**

The open area test site and conducted measurement facility used to collect the radiated data are located at the 254-1, MAEKOK-RI, HOBUP-MYUN, ICHON-SI, KYOUNGKI-DO, 467-701, KOREA. The site is constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22. Detailed description of test facility was submitted to the Commission and accepted dated July 24, 2000 (Confirmation Number: EA90661)

3.1 PRODUCT INFORMATION

3.2 Equipment Description

Equipment Under Test (EUT) is the **IMAGEQUEST CO.,Ltd. (Model : L90D) 19-inch LCD Monitor**

FCC ID: : **PJIL19C0D060**

Maximum Resolution(s): Analog:1280 X 1024(@80.0KHz/75Hz),
Digital: 1280 X 1024(@63.9KHz/60Hz)

Frequency Range(s): H-Sync: 31KHz – 80KHz
V-Sync: 56Hz – 75 Hz

Pixel Pitch: 0.264mm

Power Supply: AC 100-240V 60/ 50Hz 1.0A

Power Cord: *Unshielded* AC power cord

Port(s)/Input Connector(s): 15-pin D-sub VGA connector, 20-pin DVI-D connector, AUDIO IN/OUT

Cable(s): Shielded D-Sub (with ferrite on both ends), Shielded DVI-D (with ferrite on both ends)

Dimensions (W×H×D): 420x441x185mm(W×H×D)

Weight (Net):6.2Kg unpacked

EMI Suppression Devices:

~ No modifications were made to the device.

4.1 Description of Tests(Conducted)

4.2 Powerline Conducted RFI (150kHz- 30MHz)

The power line conducted RFI measurements were performed according to CISPR 22.

The EUT was placed on a non-conducting 1.0 by 1.5 meter table which is 0.8 meters in height and 0.40 meters away from the vertical wall of the shielded enclosure. Power to the EUT is provided through a Rohde & Schwarz 50 Ω / 50 uH Line Impedance Stabilization Network (LISN) and the support equipment through a separate Solar 50 Ω / 50 uH Line- Conducted Test Facility LISN. Sufficient time for the EUT, support equipment, and test equipment were allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer to determine the frequency producing the maximum EME. The spectrum was scanned from 150kHz to 30 MHz. Each maximum EME was remeasured using an EMI receiver. The detector function of the receiver was set to CISPR quasi- peak and average mode with the bandwidth set to 9 kHz. Each emission was maximized consistent with the typical applications by varying the configuration of the test sample. Interface cables were connected to the available interface ports of the test unit. The effect of varying the position of cables was investigated to find the configuration that produces maximum Diagram emission. Excess cable lengths were bundled at the centre with 30- 40cm. in length. The worst-case configuration is noted in the test report and the photographs are attached. Each EME reported was calibrated using the Rohde & Schwarz SMX signal generator and are listed on Table 1. RFI Conducted FCC Class B

RFI CONDUCTED	FCC CLASS B Limits dB(uV/m)	CISPR 22 CLASS B Limits dB(uV/m)	
Freq. Range	FCC Class B Quasi-Peak	CISPR 22 Quasi-Peak	CISPR 22 Average
150kHz - 0.5MHz	48*	66-56**	56-46**
0.5MHz - 5MHz	48	56	46
5MHz - 30MHz	48	60	50

*FCC Class B limits starts from 450kHz
 **Limits decreases linearly with the logarithm of frequency

Table 1. RFI Conducted Limits

4.3 Description of Tests(Radiated)

Radiated Emissions

Preliminary measurements were made indoors at 1 meter using broadband antennas, broadband amplifier, and spectrum analyzer to determine the frequency producing the maximum EME. Appropriate precaution was taken to ensure that all EME from the EUT were maximized and investigated. The spectrum was scanned from 30 to 300 MHz using biconical antenna, 300 to 1000 MHz using log- periodic antenna, and above 1 GHz using linearly polarized horn antennas. Final measurements were made outdoors at 10-meter test range using Dipole antennas and EMI receiver. For frequencies above 1 GHz, horn antennas were used. Sufficient time for the EUT, support equipment, and test equipment were allowed in order for them to warm up to their normal operating condition. The EMI receiver detector function was set to CISPR quasi-peak mode and the bandwidth of the receiver was set to 120 kHz. The EUT, support equipment, and interconnecting cables were arranged to the configuration that produces the maximum EME emission found during preliminary scan. The turntable containing the system was rotated; the antenna height was varied 1 to 4 meters and stopped at the azimuth or height producing the maximum emission. Horizontal and vertical antenna polarizations were checked. Each emission was maximized by: varying the mode of operation or resolution; clock or data exchange speed; scrolling H pattern to the EUT and/ or support equipment, and powering the monitor the computer aux AC outlet, if applicable; and changing the polarity of the antenna, whichever determined the worst-case emission.

ITE Radiated Limits			
Frequency (MHz)	FCC Limit @ 3m. Quasi- Peak dB[μ V/m]	FCC Limit @ 10m.* Quasi – Peak dB [μ V/m]	CISPR Limit @ 10m. Quasi-Peak dB [μ V/m]
30-88	40.0	29.5	30.0
88-216	43.5	33.0	30.0
216-230	46.0	35.6	30.0
230-960	46.0	35.6	37.0
960-1000	54.0	43.5	37.0
> 1000	54.0	43.5	No Specified Limit
* Limit extrapolated 20 dB/decade			

Table 2. Radiated Class B limits @ 10-meters

5.1 Support Equipment Used

DEVICE TYPE	MANUFACTURER	MODEL NUMBER	FCC ID / DoC	CONNECTED TO
MONITOR (EUT)	IMAGEQUEST CO., LTD.	L90D	PJIL19C0D060	P.C
P.C	H.P	HP Pavilion 730K	DoC	N/A
KEY BOARD	H.P	5181	DoC	P.C
MOUSE	H.P	M-S48a	DoC	P.C
PRINTER	H/P	C4569A	DoC	P.C
SERIAL MOUSE	LOGITECH	M-M28	DoC	P.C
HEADSET	SAMBO COMPUTER	DW-400M	DoC	EUT

5.2 Cable Description

	Power Cord Shielded (Y/N)	I/O Cable Shielded (Y/N)	Length (M)
MONITOR(EUT)	N	Y	1.8(P), 1.5(D)
PC(HOST)	N	N/A	1.8(P)
KEY BOARD	N/A	Y	1.8(D)
MOUSE	N/A	Y	1.8(D)
PRINTER	N	Y	1.8(P),1.8(D)
SERIAL MOUSE	N/A	Y	1.8(D)
AUDIO IN	N/A	N	1.5(D)
HEADSET	N/A	N	1.8(D)

The marked "(D)" means the Data Cable and "(P)" means the Power Cable.

5.3 Noise Suppression Parts on Cable. (I/O CABLE)

	Ferrite Bead (Y/N)	Location	Metal Hood (Y/N)	Location
MONITOR(EUT)	Y	BOTH END	Y	BOTH END
KEY BOARD	N	N/A	Y	P.C END
MOUSE	Y	P.C END	Y	P.C END
PRINTER	N	N/A	Y	BOTH END
SERIAL MOUSE	N	N/A	Y	EUT END
AUDIO IN	Y	BOTH END	N	N/A
HEADSET	Y	P.C END	N	N/A


6.1 LINE-CONDUCTED TEST DATA

HYUNDAI C-TECH.
EMC Testing Laboratory

EUT: L90D
 Manufacturer: IMAGEQUEST
 Operating Condition: 1280X1024 (A)
 Test Site: SHIELD ROOM
 Operator: BK, HAM
 Test Specification: CISPR 22 CLASS B
 Comment: H(110)
 Start of Test: 4/3/03 / 9:09:41AM

SCAN TABLE: "CISPR 22 Voltage"

CISPR 22 Voltage						
Start Frequency	Stop Frequency	Step Width	Detector	Meas.	IF Time	Transducer
150.0 kHz	500.0 kHz	5.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			
500.0 kHz	5.0 MHz	5.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			



MEASUREMENT RESULT: "L90D_fin_QP"

4/3/03 9:12AM

Frequency MHz	Level dBpV	Transd dB	Limit dBpV	Margin dB	Line	PE
0.205000	49.60	10.1	63	13.8	1	---
1.745000	23.90	10.3	56	32.1	1	---
6.910000	42.60	10.3	60	17.4	1	---

MEASUREMENT RESULT: "L90D_fin_AV"

4/3/03 9:12AM


Frequency MHz	Level dBpV	Transd dB	Limit dBpV	Margin dB	Line	PE
0.205000	42.10	10.1	53	11.3	1	---
2.890000	35.50	10.2	46	10.5	1	---
6.705000	38.50	10.3	50	11.5	1	---

HYUNDAI C-TECH.
 EMC Testing Laboratory

EUT: L90D
 Manufacturer: IMAGEQUEST
 Operating Condition: 1280X1024 (A)
 Test Site: SHIELD ROOM
 Operator: BK, HAM
 Test Specification: CISPR 22 CLASS B
 Comment: N(110)
 Start of Test: 4/3/03 / 9:14:14AM

SCAN TABLE: "CISPR 22 Voltage"

CISPR 22 Voltage						
Start Frequency	Stop Frequency	Step Width	Detector	Meas.	IF Time	Transducer
150.0 kHz	500.0 kHz	5.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			
500.0 kHz	5.0 MHz	5.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			



MEASUREMENT RESULT: "L90D_fin QP"

4/3/03 9:16AM

Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Line	PE
0.205000	47.80	10.1	63	15.6	1	---
4.955000	37.50	10.3	56	18.5	1	---
7.015000	44.60	10.3	60	15.4	1	---

MEASUREMENT RESULT: "L90D_fin AV"

4/3/03 9:16AM


Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Line	PE
0.205000	40.20	10.1	53	13.2	1	---
1.340000	38.80	10.2	46	7.2	1	---
14.130000	40.70	10.5	50	9.3	1	---

HYUNDAI C TECH
EMC TESTING Laboratory

EUT: L90D
 Manufacturer: IMAGEQUEST
 Operating Condition: 1280X1024 (D)
 Test Site: SHIELD ROOM
 Operator: BK, HAM
 Test Specification: CISPR 22 CLASS B
 Comment: H(110)
 Start of Test: 3/29/03 / 9:47:01AM

SCAN TABLE: "CISPR 22 Voltage"

Short Description: CISPR 22 Voltage
 Start Stop Step Detector Meas. IF Transducer
 Frequency Frequency Width Time Bandw.
 150.0 kHz 500.0 kHz 5.0 kHz MaxPeak 10.0 ms 9 kHz None
 Average
 500.0 kHz 5.0 MHz 5.0 kHz MaxPeak 10.0 ms 9 kHz None
 Average


MEASUREMENT RESULT: "L90D_fin QP"

3/29/03 9:49AM

Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Line	PE
0.205000	48.80	10.1	63	14.6	1	---
3.195000	40.60	10.4	56	15.4	1	---
10.925000	45.50	10.9	60	14.5	1	---

MEASUREMENT RESULT: "L90D_fin AV"

3/29/03 9:49AM


Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Line	PE
0.205000	39.10	10.1	53	14.3	1	---
3.195000	33.30	10.4	46	12.7	1	---
10.925000	39.30	10.9	50	10.7	1	---

**HYUNDAI C TECH
 EMC TESTING Laboratory**

EUT: L90D
 Manufacturer: IMAGEQUEST
 Operating Condition: 1280X1024 (D)
 Test Site: SHIELD ROOM
 Operator: BK, HAM
 Test Specification: CISPR 22 CLASS B
 Comment: N(110)
 Start of Test: 3/29/03 / 9:50:14AM

SCAN TABLE: "CISPR 22 Voltage"

CISPR 22 Voltage						
Start Frequency	Stop Frequency	Step Width	Detector	Meas.	IF Time	Transducer
150.0 kHz	500.0 kHz	5.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			
500.0 kHz	5.0 MHz	5.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			


MEASUREMENT RESULT: "L90D_fin_QP"

3/29/03 9:52AM

Frequency MHZ	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Line	PE
0.205000	47.40	10.1	63	16.0	1	---
3.195000	41.90	10.4	56	14.1	1	---
6.905000	45.60	10.6	60	14.4	1	---

MEASUREMENT RESULT: "L90D_fin_AV"

3/29/03 9:52AM

Frequency MHZ	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Line	PE
0.205000	38.90	10.1	53	14.5	1	---
0.825000	35.50	10.2	46	10.5	1	---
14.120000	40.00	11.1	50	10.0	1	---

NOTES:

1. All modes of operation were investigated and the worst-case emissions are reported.
2. The CISPR RFI conducted limits are listed on Table 1 (Page 6).
3. Line A = Phase Line B = Neutral

** Measurements using CISPR quasi-peak mode.

7.1 RADIATED TEST DATA

Frequency MHz	Reading dBuV	Ant. Factor dB	Cable Loss dB	ANT POL (H/V)	Total dBuV/m	Limit dBuV/m	Margin dB
67.1	16.47	6.57	1.8	V	24.8	30	-5.2
96.2	10.52	9.55	2.2	H	22.3	30	-7.7
366.5	11.00	16.60	4.4	V	32.0	37	-5.0
860.0	3.48	23.40	5.6	H	32.5	37	-4.5
205.4	6.36	16.41	3.2	H	26.0	30	-4.0
211.6	6.53	16.58	3.3	V	26.4	30	-3.6
326.3	10.05	16.35	4.2	H	30.6	37	-6.4
541.1	4.73	20.03	5.3	V	30.1	37	-6.9
650.0	4.21	22.74	5.9	H	32.8	37	-4.2
758.5	3.01	22.96	6.3	H	32.2	37	-4.8

Radiated Measurements at 10-meters.

Analog mode: 1280 X 1024 (@80.0KHz/ 75Hz)

Frequency MHz	Reading dBuV	Ant. Factor dB	Cable Loss dB	ANT POL (H/V)	Total dBuV/m	Limit dBuV/m	Margin dB
63.3	14.15	7.21	1.8	V	23.2	30	-6.8
89.4	13.00	8.70	2.1	V	23.8	30	-6.2
96.8	10.40	9.55	2.2	H	22.2	30	-7.8
119.1	9.70	12.68	2.4	V	24.8	30	-5.2
205.4	6.36	16.41	3.2	H	26.0	30	-4.0
211.6	6.53	16.58	3.3	V	26.4	30	-3.6
326.3	10.05	16.35	4.2	H	30.6	37	-6.4
541.1	4.73	20.03	5.3	V	30.1	37	-6.9
650.0	4.21	22.74	5.9	H	32.8	37	-4.2
758.5	3.01	22.96	6.3	H	32.2	37	-4.8

Radiated Measurements at 10-meters.

Digital Mode: 1280 X 1024 (@63.9KHz/ 60Hz)

NOTES:

1. All modes of operation were investigated, and the worst-case emissions are reported.
2. The radiated limits are listed on Table 2 (Page 7).

** AFCL = Antenna Factor (Roberts dipole) and Cable Loss .

*** Measurements using CISPR quasi-peak mode. Above 1GHz, peak detector function mode is used using a resolution bandwidth of 1MHz and a video bandwidth of 1MHz. The peak level complies with the average limit. Peak mode is used with linearly polarized horn antenna and low-loss microwave cable.

8.1 Sample Calculations

$$\text{dB } \square = 20 \log_{10} (\text{mV/m})$$

8.2 Example 1:

@ 15.2 MHz

Class B limit	= 250 μ V = 47.96 dB μ V
Reading	= 33.4 dB μ V (calibrated level)

Margin = 33.4 - 47.96 = - 14.56
= 14.6 dB below limit

8.3 Example 2:

@ 55.7 MHz

Class B limit	= 100 μ V/m = 40.0 dB μ V/m
Reading	= 21.3 dB μ V/m (calibrated level)
Antenna Factor + Cable Loss	= 11.1 dB
Total	= 32.4 dB μ V/m

Margin = 32.4 - 40.0 = - 7.6
= 7.6 dB below limit

9.1 Test Equipment

<u>Type</u>	<u>Manufacture</u>	<u>Model Number</u>	<u>CAL Date</u>
EMI Test Receiver	Rohde & Schwarz	ESH3	2002.07.16
EMI Test Receiver	Rohde & Schwarz	ESVP	2002.10.01
EMI Test Receiver	Rohde & Schwarz	ESI40	2002.11.16
EMI Test Receiver	Rohde & Schwarz	ESVS30	2002.07.16
LISN	EMCO	3816/2	2002.11.29
LISN	EMCO	3816/2	2002.08.22
Amplifier	Hewlett-Packard	8447E	2002.08.23
Absorbing Clamp	Rohde & Schwarz	MDS-21	2003.04.24
Dipole Antennas	Rohde & Schwarz	VHAP	2002.07.16
Dipole Antennas	Rohde & Schwarz	UHAP	2002.07.16
Biconical Antenna	Rohde & Schwarz	VHA9103	2002.07.12
Log-Periodic Antenna	Rohde & Schwarz	UHALP9107	2002.07.12
Antenna Position Tower	EMCO	1051-12	N/A
Turn Table	EMCO	1060-06	N/A
Power Analyzer	Voltech	PM 3300	2003.2.15
Reference Network	Impedance Voltech	IEC 555	N/A
AC Power Source	PACIFIC	Magnetic Module	N/A
AC Power Source	PACIFIC	360AMX	2002.11.25
Controller	HD GmbH	HD 100	N/A
EMI in Motion	HD GmbH	KMS 560	N/A

10.1 Test Software Used

The EUT exercise program used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use. The software, contained on a 3-1/2 inch disc, was inserted into drive A and is auto starting on power-up. Once loaded, the program sequentially exercises each system component in turn. The sequence used is :(1) Display test, (2) RS 232 test (3) Key board test,(4) Printer test,(5) FDD test,(6) HDD test. The complete cycle takes about 20 seconds and is repeated continuously. As the keyboard and mouse are strictly input devices, no data is transmitted to them during test. They are however, continuously scanned for data input activity. The video resolution modes setup and change program was used during the radiated and conducted emission testing.

NOTE: This is a sample of the basic program used during the test. However, during testing, a different software program may be used; whichever determines the worst-case condition. In addition, the program used also depends on the number and type of devices being tested.

Actual program used is the "H" pattern in Notepad under Windows environment. All resolution modes (Analog: 1280×1024, 1152×864, 1024×768, 832×624, 800×600, 640×480, 720×400
Digital:1280×1024, 1024×768, 800×600, 640×480) were investigated and tested

11.1 Conclusion

The data collected shows that the IMAGEQUEST CO., LTD. 19-inch LCD Monitor **FCC ID: PJIL19C0D060**. complies with §15.107 and §15.109 of the FCC Rules.