

**Sub-Test Report* acc. to FCC Title 47 CFR Part 15
relating to**
FEIG ELECTRONIC GmbH
ID ISC.ANT171090-1.0 Crystal Gate Excellence

**Title 47 - Telecommunication
Part 15 - Radio Frequency Devices
Subpart C – Intentional Radiators
Measurement Procedure:
ANSI C63.4-2014
ANSI C63.10-2013**



* The EUT has not been tested according to all relevant parts of the test specification. This report does not allow a conclusion about the conformity of the EUT.

MANUFACTURER	
Manufacturer name	FEIG ELECTRONIC GmbH
Manufacturer's grantee code	PJM
Manufacturer's address	Lange Str. 4 35781 Weilburg Germany
Phone	+49 (0) 6471 31 09 0
Fax	+49 (0) 6471 31 09 99
Email	Wolfgang.Meissner@feig.de

TESTING LABORATORY	
Test engineer	Mr. Ralf Trepper
Testing laboratory name	TÜV NORD Hochfrequenztechnik GmbH & Co. KG
Testing laboratory address	LESKANPARK, Gebäude 10 Waltherstr. 49-51, 51069 Köln, Germany
Phone	+49 221 8888 950
Email	rtrepper@tuev-nord.de

RELEVANT STANDARD	
Title	47 - Telecommunication
Part	15 - Radio Frequency Devices
Subpart	Subpart C – Intentional Radiators - Section 15.225
Measurement procedure	ANSI C63.4-2014 & ANSI C63.10-2013

Equipment Under Test (EUT)	
Equipment category	RFID- Equipment
Trade name	IDENTIFICATION
Type designation	ID ISC.ANT171090-1.0 Crystal Gate Excellence
Serial no.	6798950
Variants	---

1. Test results

Clause	Requirements headline	Test result			Report page number
8.1	Antenna Requirement	Pass	Fail	N.t. [*]	9
8.2	Conducted limits	Pass	Fail	N.t. ⁵	10 – 11
8.3	Restricted bands of operation	Pass	Fail	N.t. [*]	12 – 13
8.4	Radiated emission limits	Pass	Fail	N.t. [*]	14 – 21
8.5	Frequency tolerance	Pass	Fail	N.t. [*]	22 – 24
8.6	20 dB Bandwidth	Pass	Fail	N.t. [*]	25 – 26

* Not tested

The equipment passed all the conducted tests	Yes	No
--	-----	----

Signature		
Name	Mr. Ralf Trepper	Mr. Abdelouahid Ftouhi
Designation	RF Test engineer	Laboratory-Manager
Date of issue	2019-05-29	2019-05-29

Table of contents

1. Test results	3
2. Introduction.....	5
3. Testing laboratory	5
4. Applicant.....	6
5. Product and product documentation	6
6. Conclusions, observations and comments	7
7. Operational description	8
8. Compliance assessment.....	9
8.1 Antenna requirement	9
8.1.1 Regulation	9
8.1.2 Result.....	9
8.2 Conducted limits	10
8.2.1 Regulation	10
8.2.2 Test procedures.....	10
8.2.3 Result.....	11
8.3 Restricted bands of operation.....	12
8.2.1 Regulation	12
8.2.2 Result.....	13
8.4 Radiated emission limits.....	14
8.4.1 Regulation	14
8.4.2 Test procedure.....	16
8.4.3 Calculation of the field strength.....	17
8.4.4 Result.....	18
8.5 Frequency tolerance	22
8.5.1 Regulation	22
8.5.2 Test procedures.....	22
8.5.3 Result.....	24
8.6 Bandwidth (20 dB)	25
8.6.1 Regulation	25
8.6.2 Calculation of the 20 dB bandwidth limit.....	25
8.6.3 Test procedure.....	25
8.6.4 Result.....	26
9. Additional information to the test report	27
10. List of test equipment.....	28
11. Cable list	29

2. Introduction

This test report **is not an expert opinion** and consists of:

- Test result summary
- List of contents
- Introduction and further information
- Performance assessment
- Detailed test information

All pages have been numbered consecutively and bear the TÜV NORD Hochfrequenztechnik GmbH & Co. KG logo, the test report number, the date, the test specification in its current version as well as the type designation of the EUT. The total number of pages in this report is **30**.

The tests were carried out at:

**- TÜV NORD Hochfrequenztechnik GmbH & Co. KG
LESKANPARK, Gebäude 10, Waltherstr. 49-51, 51069 Köln, Germany**

in a representative assembly and in accordance with the test methods and/or requirements stated in:

FCC Title 47 CFR Part 15 Subpart C Section 15.225, ANSI C63.4-2014 & ANSI C63.10-2013

The sample of the product was received on:

- 2019-04-23

The tests were carried out in the following period of time:

- 2019-04-26 - 2019-05-06

3. Testing laboratory

TÜV NORD Hochfrequenztechnik GmbH & Co. KG
LESKANPARK, Gebäude 10
Waltherstr. 49-51
51069 Köln
Germany

Phone: +49 - (0) 22 07 / 96 89-0

- FCC Registration Number: 763407

Accredited by:

**DAkkS Deutsche Akkreditierungsstelle GmbH
DAkkS accreditation number: D-PL-12053-01**

4. Applicant

Company name : FEIG ELECTRONIC GmbH
Address : Lange Str. 4
 35781 Weilburg
Country : Germany
Telephone : +49 (0) 6471 31 09 0
Fax : +49 (0) 6471 31 09 99
Email : Wolfgang.Meissner@feig.de
Date of order : 2019-05-07
References : Mr. Wolfgang Meissner

5. Product and product documentation

Samples of the following apparatus were submitted for testing:

Manufacturer	: FEIG ELECTRONIC GmbH
Trademark	: IDENTIFICATION
Type designation	: ID ISC.ANT171090-1.0 Crystal Gate Excellence
Variants	: ---
Antennas	: ID ISC.ANT171090-1.0 Crystal Gate Excellence Type A ID ISC.ANT171090-1.0 Crystal Gate Excellence Type B
Serial number	: 6798950
Hardware version	: 2019
Software version	: 2.04
Type of equipment	: RFID- Equipment
Power supply used	: 24.0 V DC
Frequency used	: 13.560 MHz
Generated frequencies	: 32.768 kHz (crystal), 25 MHz (crystal), 81.36 MHz (crystal), 13.56 MHz (crystal) // 13.560 MHz (carrier)
ITU emission class	: 550HA1D
FCC-ID	: PJMLRM2500

EUT: ID ISC.ANT1710690-1.0
Crystal Gate Excellence

FCC ID: PJMLRM2500 **FCC Title 47 CFR Part 15** **Date of issue: 2019-05-29**

For issuing this report the following product documentation was used:

Title	Description	Version
---	---	---

For issuing this report the following product documentation was used:

Description	Date	Identifications
External photographs of the Equipment Under Test (EUT)	2019-05-29	Annex no. 1
Internal photographs of the Equipment Under Test (EUT)	2019-05-29	Annex no. 2
Channel occupancy / bandwidth	2019-05-29	Annex no. 3
Label sample	2019-05-29	Annex no. 4
Functional description / User manual	2019-05-29	Annex no. 5
Test setup photos	2019-05-29	Annex no. 6
Block diagram	2019-05-29	Annex no. 7
Operational description	2019-05-29	Annex no. 8
Schematics	2019-05-29	Annex no. 9
Parts list	2019-05-29	Annex no. 10

6. Conclusions, observations and comments

The test report will be filed at TÜV NORD Hochfrequenztechnik GmbH & Co. KG for a period of 10 years following the issue of this report. It may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of TÜV NORD Hochfrequenztechnik GmbH & Co. KG.

The results of the tests as stated in this report are exclusively applicable to the EUT as identified in this report. TÜV NORD Hochfrequenztechnik GmbH & Co. KG cannot be held liable for properties of the EUT that have not been observed during these tests.

TÜV NORD Hochfrequenztechnik GmbH & Co. KG assumes the sample to comply with the requirements of FCC Title 47 CFR Part 15 for the respective test sector, if the test results turn out positive.

Comments: ---

7. Operational description

7.1 EUT details

The EUT is a RFID- Equipment.

7.2 EUT configuration

After connecting to the power supply 24.0 V DC the EUT starts to run.

7.3 EUT measurement description

Radiated measurements

The EUT was tested in a typical fashion. During preliminary emission tests the EUT was operated in the continuous measuring mode for worst case emission mode investigation. Therefore, the final qualification testing was completed with the EUT operated in continuous measuring mode. All tests were performed with the EUT's typical voltage: 24.0 V DC.

In order to establish the maximum radiation, firstly, there have been viewed all orthogonal adjustments of the test samples, secondly the test ample have been rotated at all adjustments around the own axis between 0° and 360°, and thirdly, the antenna polarization between horizontal and vertical had been varied.

Radiated measurement above 1 GHz is made by placing loose-laid RF absorber material on the ground plane as mentioned in ANSI C63.4-2014.

Additionally, radiated emission measurements above 1 GHz are made using calibrated linearly polarized antennas as specified in ANSI C63.4-2014, which may have a smaller beamwidth (main lobe) than do the antennas used for frequencies below 1 GHz. The measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal.

EUT: ID ISC.ANT1710690-1.0
Crystal Gate Excellence

FCC ID: PJMLRM2500

FCC Title 47 CFR Part 15

Date of issue: 2019-05-29

8. Compliance assessment

8.1 Antenna requirement

8.1.1 Regulation

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

8.1.2 Result

Antenna Type	Antenna description	Frequency	Number of Antennas
Loop Gate	ID ISC.ANT171090-1.0 Crystal Gate Excellence Type A	13.560 MHz	1
Loop Gate	ID ISC.ANT171090-1.0 Crystal Gate Excellence Type B	13.560 MHz	1

The equipment passed the conducted tests	Yes	No	N.t.*
Test setup photos / test results are attached	Yes	No	Annex no. 1 and 2

N.t.* see clause: 9

Date: 2019-03-11

Created: P4

Reviewed: P9

Released: P1

Vers. No. 1.19

TÜV NORD Hochfrequenztechnik GmbH & Co. KG
LESKANPARK, Gebäude 10, Waltherstr. 49-51, 51069 Köln, Germany

Tel.: +49 221 88889500

8.2 Conducted limits

8.2.1 Regulation

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission(MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56*	56 to 46*
0.5 - 5	56	46
5 -30	60	50

*Decreases with the logarithm of the frequency

(b) The shown limit in paragraph (a) of this Section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:

(1) For carrier current systems containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000 μ V within the frequency band 535-1705 kHz, as measured using a 50 μ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in Section 15.205 and Section 15.209, 15.221, 15.223, 15.225 or 15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provision for, the use of battery chargers which permit operating while charging, AC adaptors or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

8.2.2 Test procedures

The EUT and the additional equipment (if required) are connected to the main power through a line impedance stabilization network (LISN). The LISN must be appropriate to ANSI C63.4-2014 Section 7.

Additional equipment must also be connected to a second LISN with the same specifications described in the above section (if required).

8.2.3 Result

Tested with external AC power supply

Conducted emissions (Section 15.207)						
Tested line	f MHz	Bandwidth kHz	Noted receiver level dB μ V	Spec. limit (average) dB μ V	Margin dB μ V	Remarks
L1		9		56.0		
N		9		56.0		
L1		9		46.0		
N		9		46.0		
L1		9		50.0		
N		9		50.0		
Measurement uncertainty			< ± 2 dB			

Remark: ^{*1} Noise level of the measuring instrument \leq -2dB μ V (0.009 – 30MHz)Remark: ^{*2} Quasi peak measurements lower than "Specified Average Limit"

Test Cables used			
Test equipment used			

The equipment passed the conducted tests	Yes	No	N.t. ⁵
--	-----	----	-------------------

Test setup photos / test results are attached	Yes	No	Annex no.:
---	-----	----	------------

N.t.* see clause: 9

8.3 Restricted bands of operation

8.2.1 Regulation

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)
13.36 - 13.41			

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

(c) Except as provided in paragraphs (d) and (e), regardless of the field strength limits specified elsewhere in this Subpart, the provisions of this Section apply to emissions from any intentional radiator.

(d) The following devices are exempt from the requirements of this Section:

(1) Swept frequency field disturbance sensors operating between 1.705 and 37 MHz provided their emissions only sweep through the bands listed in paragraph (a), the sweep is never stopped with the fundamental emission within the bands listed in paragraph (a), and the fundamental emission is outside of the bands listed

EUT: ID ISC.ANT1710690-1.0
Crystal Gate Excellence

FCC ID: PJMLRM2500 **FCC Title 47 CFR Part 15** **Date of issue: 2019-05-29**

in paragraph (a) more than 99% of the time the device is actively transmitting, without compensation for duty cycle.

(2) Transmitters used to detect buried electronic markers at 101.4 kHz which are employed by telephone companies.

(3) Cable locating equipment operated pursuant to Section 15.213.

(4) Any equipment operated under the provisions of § 15.253, § 15.255 or § 15.256 of this part.

(5) Biomedical telemetry devices operating under the provisions of Section 15.242 of this part are not subject to the restricted band 608-614 MHz but are subject to compliance within the other restricted bands.

(6) Transmitters operating under the provisions of Subpart D or F of this part.

(7) Devices operated pursuant to § 15.225 are exempt from complying with this section for the 13.36-13.41 MHz band only.

(8) Devices operated in the 24.075-24.175 GHz band under § 15.245 are exempt from complying with the requirements of this section for the 48.15-48.35 GHz and 72.225-72.525 GHz bands only, and shall not exceed the limits specified in § 15.245(b).

(9) Devices operated in the 24.0-24.25 GHz band under § 15.249 are exempt from complying with the requirements of this section for the 48.0-48.5 GHz and 72.0-72.75 GHz bands only, and shall not exceed the limits specified in § 15.249(a).

(10) White space devices operating under subpart H of this part are exempt from complying with the requirements of this section for the 608-614 MHz band.

(e) Harmonic emissions appearing in the restricted bands above 17.7 GHz from field disturbance sensors operating under the provisions of Section 15.245 shall not exceed the limits specified in Section 15.245(b).

8.2.2 Result

Test Cables used	K1b, K40, K56, K83, K120		
Test equipment used	23, 103, 166a, 406, 502		

The equipment passed the conducted tests	Yes	No	N.t.*
--	-----	----	-------

Test setup photos / test results are attached	Yes	No	Annex no. 6
---	-----	----	-------------

****All emissions fall under restricted band are mentioned in the clause 8.4 and are marked blue!**

N.t.* see clause: 9

Date: 2019-03-11

Created: P4

Reviewed: P9

Released: P1

Vers. No. 1.19

8.4 Radiated emission limits

8.4.1 Regulation

The device operating in the frequency band 13.110-14.010, the field strength of any emission shall not exceed the following limits.

Frequency	Field Strength	Measurements Distance
MHz	dB μ V/m	m
13.553 - 13.567	84	30
13.410 - 13.553 and 13.567 - 13.710	50.5	30
13.110 - 13.410 and 13.710 - 14.010	40.5	30

(a) Outside the band 13.110-14.010, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54–72 MHz, 76–88 MHz, 174–216 MHz or 470–806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§15.231 and 15.241.

(c) In the emission table above, the tighter limit applies at the band edges.

(d) The level of any unwanted emissions from an intentional radiator operating under these general provisions shall not exceed the level of the fundamental emission. For intentional radiators, which operate under the provisions of other sections within this part and which are required to reduce their unwanted emissions to the limits specified in this table, the limits in this table are based on the frequency of the unwanted emission and not the fundamental frequency. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.

(e) The emission limits shown in the above table are based on measurements employing a CISPR quasi peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

EUT: ID ISC.ANT1710690-1.0 **FCC ID: PJMLRM2500** **FCC Title 47 CFR Part 15** **Date of issue: 2019-05-29**
Crystal Gate Excellence

(f) The provisions in §§ 15.31, 15.33, and 15.35 for measuring emissions at distances other than the distances specified in the above table, determining the frequency range over which radiated emissions are to be measured, and limiting peak emissions apply to all devices operated under this part.

(g) In accordance with §15.33(a), in some cases the emissions from an intentional radiator must be measured to beyond the tenth harmonic of the highest fundamental frequency designed to be emitted by the intentional radiator because of the incorporation of a digital device. If measurements above the tenth harmonic are so required, the radiated emissions above the tenth harmonic shall comply with the general radiated emission limits applicable to the incorporated digital device, as shown in §15.109 and as based on the frequency of the emission being measured, or, except for emissions contained in the restricted frequency bands shown in §15.205, the limit on spurious emissions specified for the intentional radiator, whichever is the higher limit. Emissions which must be measured above the tenth harmonic of the highest fundamental frequency designed to be emitted by the intentional radiator and which fall within the restricted bands shall comply with the general radiated emission limits in §15.109 that are applicable to the incorporated digital device.

(h) Perimeter protection systems may operate in the 54–72 MHz and 76–88 MHz bands under the provisions of this section. The use of such perimeter protection systems is limited to industrial, business and commercial applications.

8.4.2 Test procedure

The EUT and this peripheral (when additional equipment exists) are placed on a turn table which is 0.8 m above the ground. The turn table would be allowed to rotate 360° to determine the position of the maximum emission level. The test distance between the EUT and the receiving antenna are 3m. To find the maximum emission, the polarization of the receiving antenna is changed in horizontal and vertical polarization; the position of the EUT was changed in different orthogonal determinations.

ANSI C63.4-2014 Section 8 “Radiated Emissions Testing”

Measurement procedures for electric field radiated emissions from 9 kHz - 1 GHz & 1 GHz - 40 GHz are covered in Clause 8 of ANSI C63.4-2014. The ANSI C63.4-2014 measurement procedure consists of both an exploratory test and a final measurement. The exploratory test is critical to determine the frequency of all significant emissions. For each mode of operation required to be tested, the frequency spectrum is monitored. Variations in antenna height, antenna orientation, antenna polarization, EUT azimuth, and cable or wire placement is explored to produce the emission that has the highest amplitude relative to the limit.

The final measurements are made based on the findings in the exploratory testing. When making exploratory and final measurements it is necessary to maximize the measured radiated emission. Sub clause 8.3.2 of ANSI C63.4-2014 states that the measurement is to be made “while keeping the antenna in the ‘cone of radiation’ from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response.” We consider the “cone of radiation” to be the 3 dB beam width of the measurement antenna.

While the “bore-sighting” technique is not explicitly mentioned in ANSI C63.4-2014, it is a useful technique for measurements using a directional antenna, such as a double-ridged waveguide antenna. Several precautions must be observed, including: knowledge of the beam width of the antenna and the resulting illumination area relative to the size of the EUT, estimation for source of the emission and general location within larger EUTs, measuring system sensitivity, etc.

ANSI C63.4-2014 requires that the measurement antenna is kept pointed at the source of the emission both in azimuth and elevation, with the polarization of the antenna oriented for maximum response. That means that if the directional radiation pattern of the EUT results in a maximum emission at an upwards angle from the EUT, when a directional antenna is used to make the measurement it will be necessary for it to be pointed towards the source of the emission within the EUT. This can be done by either pointing the antenna at an angle towards the source of the emission, or by rotating the EUT, in both height and polarization, to maximize the measured emission. The emission must be kept within the illumination area of the 3 dB beamwidth of the antenna so that the maximum emission from the EUT is measured.

Radiated Emissions Test Characteristics	
Frequency range	30 MHz - 1,000 MHz
Test distance	10 m, 3 m*
Test instrumentation resolution bandwidth	9 kHz (20 kHz – 30 MHz)
	120 kHz (30 MHz – 1.000 MHz)
Receive antenna height	1 m (20 kHz – 30 MHz)
Receive antenna polarization	0° or 90° (20 kHz – 30 MHz)
Receive antenna scan height	1 m - 4 m (30 MHz – 1.000 MHz)
Receive antenna polarization	Vertical or Horizontal (30 MHz – 1.000 MHz)

* According to Section 15.31 (f) (1): At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

8.4.3 Calculation of the field strength

The field strength is calculated by the following calculation:

Corrected Level = Receiver Level + Correction Factor (without the use of a pre-amplifier)

Corrected Level = Receiver Level + Correction Factor – Pre-amplifier (with the use of a pre-amplifier)

Receiver Level : Receiver reading without correction factors
Correction Factor : Antenna factor + cable loss

For example:

The receiver reading is 32.7 dB μ V. The antenna factor for the measured frequency is +2.5 dB (1/m) and the cable factor for the measured frequency is 0.71 dB, giving a field strength of 35.91 dB μ V/m.

The 35.91 dB μ V value can be mathematically converted to its corresponding level in μ V/m.

Level in μ V/m = Common Antilogarithm (35.91/20) = 62.44

For test distance other than what is specified, but fulfilling the requirements of Section 15.31 (f) (1) the field strength is calculated by adding additionally an extrapolation factor of 20 dB/decade (inverse linear distance for field strength measurements).

EUT: ID ISC.ANT1710690-1.0
Crystal Gate Excellence
FCC ID: PJMLRM2500**FCC Title 47 CFR Part 15****Date of issue: 2019-05-29**

8.4.4 Result

RADIATION EMISSIONS BELOW 30 MHz (Section 15.225, 15.205 and 15.209)									
f	Bandwidth, Type of detector	Noted receiver level	Test distance	Correction factor	Distance extrapol. factor	Level corrected	Limit	Margin	Polaris. EUT / antenna orientation
MHz		dBμV	m	dB	dB	dBμV/m	dBμV/m @ meter	dBμV/m	height/cm
0.2500	QPK/10kHz	< 4.0	10	20.2	-59.1	-34.9	AV19.6 @ 300	54.5	V, H/0-360° 100
0.3750	QPK/10kHz	< 4.0	10	20.2	-59.1	-34.9	AV16.1 @ 300	51.0	V, H/0-360° 100
0.5000	QPK/9.0kHz	< 4.0	10	20.2	-19.1	5.1	AV33.6 @ 30	28.5	V, H/0-360° 100
0.6250	QPK/9.0kHz	< 4.0	10	20.2	-19.1	5.1	AV31.7 @ 30	26.6	V, H/0-360° 100
0.7500	QPK/9.0kHz	< 4.0	10	20.2	-19.1	5.1	AV30.1 @ 30	25.0	V, H/0-360° 100
0.8750	QPK/9.0kHz	< 4.0	10	20.2	-19.1	5.1	AV28.6 @ 30	23.5	V, H/0-360° 100
1.0000	QPK/9.0kHz	< 4.0	10	20.2	-19.1	5.1	AV27.6 @ 30	22.5	V, H/0-360° 100
1.1250	QPK/9.0kHz	< 4.0	10	20.2	-19.1	5.1	AV27.6 @ 30	22.5	V, H/0-360° 100
1.2500	QPK/9.0kHz	< 4.0	10	20.2	-19.1	5.1	AV25.6 @ 30	28.5	V, H/0-360° 100
1.5000	QPK/9.0kHz	< 4.0	10	20.2	-19.1	5.1	AV24.1 @ 30	19.00	V, H/0-360° 100
3.0000	QPK/9.0kHz	< 4.0	10	20.2	-19.1	5.1	AV29.5 @ 30	24.4	V, H/0-360° 100
5.0000	QPK/9.0kHz	< 4.0	10	20.2	-19.1	5.1	AV29.5 @ 30	24.4	V, H/0-360° 100
8.0000	QPK/9.0kHz	< 4.0	10	20.2	-19.1	5.1	AV29.5 @ 30	24.4	V, H/0-360° 100
10.0000	QPK/9.0kHz	< 4.0	10	20.2	-19.1	5.1	AV29.5 @ 30	24.4	V, H/0-360° 100
20.0000	QPK/9.0kHz	< 4.0	10	20.2	-19.1	5.1	AV29.5 @ 30	24.4	V, H/0-360° 100
30.0000	QPK/9.0kHz	< 4.0	10	20.2	-19.1	5.1	AV29.5 @ 30	24.4	V, H/0-360° 100

Measurement uncertainty ± 4 dBRemark: *¹ Noise level of the measuring instrument ≤ 4.0 dB μ V @ 10m distance (0.009 MHz –30 MHz)

Remark: * Peak Limit according to Section 15.35 (b).

Test Cables used	K1b, K56, K83
Test equipment used	23, 103, 166a, 502

The equipment passed the conducted tests	Yes	No	N.t.*
--	-----	----	-------

Test setup photos / test results are attached	Yes	No	Annex no. 3 and 6
---	-----	----	-------------------

N.t.* see clause: 9

Date: 2019-03-11

Created: P4

Reviewed: P9

Released: P1

Vers. No. 1.19

TÜV NORD Hochfrequenztechnik GmbH & Co. KG
LESKANPARK, Gebäude 10, Waltherstr. 49-51, 51069 Köln, Germany

Tel.: +49 221 88889500

RADIATION EMISSIONS ABOVE 30 MHz (Section 15.225, 15.205 and 15.209)

f	Bandwidth Type of detector	Noted receiver level	Test distance	Correction factor	Distance extrapol. factor	AV Correction factor	Level corrected	Limit	Margin	Polaris. EUT / antenna	Antenna height
MHz		dB μ V	m	dB	dB	dB	dB μ V/m	dB μ V/m	dB μ V/m		cm
30.0000	100, AV	≤ 3.5	3	-2.60	0	0	0.90	40.00	39.10	H,V/H,V	100-400
88.0000	100, AV	≤ 3.5	3	-10.80	0	0	-7.30	40.00	47.30	H,V/H,V	100-400
216.0000	100, AV	≤ 3.5	3	-10.30	0	0	-6.80	43.50	50.30	H,V/H,V	100-400
960.0000	100, AV	≤ 3.5	3	8.50	0	0	12.00	43.50	31.50	H,V/H,V	100-400
Measurement uncertainty				± 4 dB							

Bandwidth = the measuring receiver bandwidth

Remark: *¹ noise floor noise level of the measuring instrument ≤ 3.5dB μ V @ 3m distance (30 – 1,000 MHz)Remark: *² noise floor noise level of the measuring instrument ≤ 4.5dB μ V @ 3m distance (1,000 – 2,000 MHz)Remark: *³ noise floor noise level of the measuring instrument ≤ 10dB μ V @ 3m distance (2,000 – 5,500 MHz)Remark: *⁴ noise floor noise level of the measuring instrument ≤ 14dB μ V @ 3m distance (5,500 – 14,500 MHz)Remark: *⁵ for using a pre-amplifier in the range between 100 kHz and 1,000 MHzRemark: *⁶ for using a pre-amplifier in the range between 1.0 GHz and 18.0 GHz

Test Cables used K1b, K40, K56, K83, K120

Test equipment used 103, 166a, 406, 502

The equipment passed the conducted tests Yes No N.t.*

Test setup photos / test results are attached Yes No Annex no. 6

N.t.* see clause: 9

EUT: ID ISC.ANT1710690-1.0
Crystal Gate Excellence

FCC ID: PJMLRM2500

FCC Title 47 CFR Part 15

Date of issue: 2019-05-29

FUNDAMENTAL EMISSION & HARMONICS (Section 15.225, 15.205 and 15.209)

Frequency	Bandwidth Type of detector	Noted receiver level	Test distance	Correction factor	Distance extrapol. factor	Level corrected	Limit @ meter	Margin	Polaris. EUT antenna orientation	
MHz	kHz	dB μ V	m	dB	dB	dB μ V/m	dB μ V/m	dB μ V/m	H / V	cm
13.560	QPK/9kHz	84.3	10	17.7	-19.1	82.9	84.0 @ 30	1.1	0°	100
27.120	QPK/9kHz	17.9	10	18.5	-19.1	17.3	29.5 @ 30	12.2	0°	100
40.680	QPK/120kHz	41.5	3	-7.6	0	33.9	40.0 @ 3	6.1	V; 0°	152
54.240	QPK/120kHz	42.0	3	-8.6	0	33.4	40.0 @ 3	6.6	V; 180°	168
67.800	QPK/120kHz	41.9	3	-10.0	0	31.9	40.0 @ 3	8.1	V; 180°	152
81.360	QPK/120kHz	47.1	3	-11.9	0	35.2	40.0 @ 3	4.8	V; 0°	183
94.920	QPK/120 kHz	42.2	3	-11.3	0	30.9	43.5 @ 3	12.6	H; 180°	187
108.480	QPK/120 kHz	45.5	3	-10.0	0	35.5	43.5 @ 3	8.0	V; 95°	164
122.040	QPK/120 kHz	45.7	3	-8.5	0	37.2	43.5 @ 3	6.3	V; 180°	214
135.600	QPK/120 kHz	45.7	3	-7.9	0	37.8	43.5 @ 3	5.7	H; 180°	141
149.160	QPK/120 kHz	33.6	3	-6.7	0	26.9	43.5 @ 3	16.6	V; 180°	194
162.720	QPK/120 kHz	38.9	3	-8.2	0	30.7	43.5 @ 3	12.8	H; 180°	105
176.280	QPK/120 kHz	35.9	3	-8.9	0	27.0	43.5 @ 3	16.5	V; 180°	116
189.840	QPK/120 kHz	42.5	3	-10.8	0	32.2	43.5 @ 3	11.3	V; 165°	147
203.400	QPK/120 kHz	44.5	3	-10.7	0	33.8	43.5 @ 3	9.7	H; 180°	107
216.960	QPK/120 kHz	44.9	3	-9.3	0	35.6	43.5 @ 3	7.9	H; 180°	251
230.520	QPK/120 kHz	43.5	3	-8.7	0	34.8	43.5 @ 3	8.7	H; 180°	110
244.080	QPK/120 kHz	47.8	3	-8.7	0	39.1	43.5 @ 3	4.4	H; 180°	143
257.640	QPK/120 kHz	45.0	3	-8.3	0	36.7	43.5 @ 3	6.8	H; 180°	139
271.200	QPK/120 kHz	50.6	3	-7.6	0	43.0	43.5 @ 3	0.5	H; 180°	172
298.320	QPK/120 kHz	49.3	3	-6.8	0	42.5	46.0 @ 3	3.5	H; 180°	106
325.440	QPK/120 kHz	46.1	3	-5.7	0	40.4	46.0 @ 3	5.6	H; 180°	100
406.800	QPK/120 kHz	40.4	3	-4.3	0	36.1	46.0 @ 3	9.9	H; 180°	122
610.200	QPK/120 kHz	39.4	3	-0.5	0	38.9	46.0 @ 3	7.1	H; 130°	132
678.000	QPK/120 kHz	33.6	3	0.7	0	34.3	46.0 @ 3	11.7	H; 150°	132
732.240	QPK/120 kHz	39.4	3	1.9	0	41.3	46.0 @ 3	4.7	H; 180°	100
827.160	QPK/120 kHz	40.9	3	2.7	0	43.6	46.0 @ 3	2.4	V; 175°	160
840.720	QPK/120 kHz	41.4	3	2.7	0	44.1	46.0 @ 3	1.9	V; 175°	166
881.400	QPK/120 kHz	41.1	3	3.1	0	44.2	46.0 @ 3	1.8	V; 155°	154
908.520	QPK/120 kHz	37.7	3	4.1	0	41.8	46.0 @ 3	4.2	V; 175°	163
Measurement uncertainty						± 4 dB				

Blue marked: restricted bands

Date: 2019-03-11

Created: P4

Reviewed: P9

Released: P1

Vers. No. 1.19

EUT: ID ISC.ANT1710690-1.0
Crystal Gate Excellence**FCC ID: PJMLRM2500****FCC Title 47 CFR Part 15****Date of issue: 2019-05-29**

Bandwidth = the measuring receiver bandwidth

Remark: *¹ noise floor noise level of the measuring instrument $\leq 4.0 \text{ dB}\mu\text{V}$ @ 10m distance (0.009 – 30 MHz)Remark: *² noise floor noise level of the measuring instrument $\leq 6.5 \text{ dB}\mu\text{V}$ @ 3m distance (30 – 1,000 MHz)Remark: *³ noise floor noise level of the measuring instrument $\leq 10 \text{ dB}\mu\text{V}$ @ 3m distance (1,000 – 2,000 MHz)Remark: *⁴ noise floor noise level of the measuring instrument $\leq 17 \text{ dB}\mu\text{V}$ @ 3m distance (2,000 – 5,500 MHz)Remark: *⁵ for using a pre-amplifier in the range between 100 kHz and 1,000 MHz

Test Cables used	K1b, K40, K56, K83, K120
Test equipment used	23, 103, 166a, 406, 502

The equipment passed the conducted tests	Yes	No	N.t.*
--	------------	-----------	--------------

Test setup photos / test results are attached	Yes	No	Annex no. 6
---	------------	-----------	-------------

N.t.* see clause: 9

Date: 2019-03-11

Created: P4

Reviewed: P9

Released: P1

Vers. No. 1.19

TÜV NORD Hochfrequenztechnik GmbH & Co. KG
LESKANPARK, Gebäude 10, Waltherstr. 49-51, 51069 Köln, Germany

Tel.: +49 221 88889500

8.5 Frequency tolerance

8.5.1 Regulation

The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency over a temperature variation of $-20\text{ }^{\circ}\text{C}$ to $+55\text{ }^{\circ}\text{C}$ at normal supply voltage, and for a variation in the primary supply voltage from 85 % to 115 % of the rated supply voltage at a temperature of $20\text{ }^{\circ}\text{C}$.

8.5.2 Test procedures

Stability with respect to ambient temperature:

Supply the EUT with nominal ac voltage, or install a new or fully charged battery in the EUT. If possible, a dummy load should be connected to the EUT, because an antenna near the metallic walls of an environmental test chamber could affect the output frequency of the EUT. If the EUT is equipped with a permanently attached, adjustable-length antenna, the EUT should be placed in the center of the chamber with the antenna adjusted to the shortest length possible. Turn the EUT on, and tune it to one of the number of frequencies required

Couple the intentional radiator output to the measuring instrument by connecting an antenna to the measurement instrument with a suitable length of coaxial cable and placing the measurement antenna near the EUT (e.g., 15 cm away) or by connecting a dummy load to the measuring instrument through an attenuator, if necessary.

Supply the EUT with nominal ac voltage, or install a new or fully charged battery in the EUT. Turn the EUT on, and couple its output to the measuring instrument by connecting an antenna to the measurement instrument with a suitable length of coaxial cable.

Adjust the location of the measurement antenna and the controls on the measuring instrument to obtain a suitable signal level (i.e., a level that will not overload the measuring instrument, but is strong enough to allow measurement of the operating or fundamental frequency of the EUT).

Tune the EUT to any one of the number of frequencies specified. Turn the EUT off, and place it inside an environmental chamber if appropriate. Allow the chamber to stabilize at $+20\text{ }^{\circ}\text{C}$ before proceeding. Turn on the EUT, and record the operating frequency of the intentional radiator at startup and two, five, and ten minutes after startup. Turn the EUT off and allow it to cool to the ambient temperature, and then repeat this procedure for the number of the frequencies specified. Four measurements are made at each operating frequency.

Stability with respect to input voltage:

Supply the EUT with nominal ac voltage, or install a new or fully charged battery in the EUT. If possible, a dummy load should be connected to the EUT, because an antenna near the metallic walls of an environmental test chamber could affect the output frequency of the EUT. If the EUT is equipped with a permanently attached, adjustable-length antenna, the EUT should be placed in the center of the chamber with the antenna adjusted to the shortest length possible. Turn the EUT on, and tune it to one of the number of frequencies required.

Couple the intentional radiator output to the measuring instrument by connecting an antenna to the measurement instrument with a suitable length of coaxial cable and placing the measurement antenna near the EUT (e.g., 15 cm away) or by connecting a dummy load to the measuring instrument through an attenuator, if necessary.

Adjust the location of the measurement antenna and the controls on the measuring instrument to obtain a suitable signal level (i.e., a level that will not overload the measuring instrument, but is strong enough to allow measurement of the operating or fundamental frequency of the EUT). Turn the EUT off, and place it inside an environmental temperature chamber. For devices that are normally operated continuously, the EUT may be energized while inside the test chamber. For devices that have oscillator heaters, energize only the heater circuit while the EUT is inside the chamber.

Set the temperature control on the chamber to the highest specified EUT operating temperature, and allow the temperature inside the chamber to stabilize at the set temperature before starting frequency measurements.

While maintaining a constant temperature inside the environmental chamber, turn the EUT on and record the operating frequency at startup and two, five, and ten minutes after the EUT is energized. Four measurements in total are made.

Repeat the above procedure until the number of frequencies specified has been measured. After all measurements have been made at the highest specified temperature, turn the EUT off. Repeat the above measurement process for the EUT with the test chamber set at the lowest temperature specified by the regulatory or procuring agency. Measurements shall be made at the number of frequencies specified.

8.5.3 Result

Frequency tolerance (Section 15.225)			
Test conditions	Frequency Measured (MHz)	Frequency Error	
		(kHz)	ppm
V _{min} = 20.4 V DC	13.560190	0.190	14.0
V _{nom} = 24.0 V DC	13.560179	0.179	13.2
V _{max} = 27.6 V DC	13.560190	0.190	14.0
Maximum Frequency error		0.190	14.0
Measurement uncertainty		$\pm 5 \cdot 10^{-8}$	

Frequency tolerance (Section 15.225)			
Test conditions	Frequency Measured (MHz)	Frequency Error	
		(kHz)	ppm
T _{min} -20 °C	13.560170	0.170	12.5
T _{min} -10 °C	13.560210	0.210	15.5
T _{min} 0 °C	13.560210	0.210	15.5
T _{min} +10 °C	13.560200	0.200	14.7
T _{min} +20 °C	13.560179	0.179	13.2
T _{min} +30 °C	13.560170	0.170	12.5
T _{min} +40 °C	13.560130	0.130	9.6
T _{min} +50 °C	13.560070	0.070	5.2
Maximum frequency error		0.210	15.5
Measurement uncertainty		$\pm 5 \cdot 10^{-8}$	

Test Cables used	K64, K102
Test equipment used	23, 144, 214, 226, 375, 502

The equipment passed the conducted tests	Yes	No	N.t.*
--	-----	----	-------

Test setup photos / test results are attached	Yes	No	Annex no. 3
---	-----	----	-------------

N.t.* see clause: 9

8.6 Bandwidth (20 dB)

8.6.1 Regulation

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. In the case of intentional radiators operating under the provisions of subpart E, the emission bandwidth may span across multiple contiguous frequency bands identified in that subpart. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

8.6.2 Calculation of the 20 dB bandwidth limit

Within the specified band!

8.6.3 Test procedure

ANSI C63.10-2013 Section 6.9.3 Occupied bandwidth measurements.

The occupied bandwidth is measured as the width of the spectral envelope of the modulated signal, at an amplitude level reduced from a reference value by a specified ratio (or in decibels, a specified number of dB down from the reference value). Typical ratios, expressed in dB, are -6 dB, -20 dB, and -26 dB, corresponding to 6 dB BW, 20 dB BW, and 26 dB BW, respectively. In this sub-clause, the ratio is designated by “-xx dB.” The reference value is either the level of the unmodulated carrier or the highest level of the spectral envelope of the modulated signal, as stated by the applicable requirement. Some requirements might specify a specific maximum or minimum value for the “-xx dB” bandwidth; other requirements might specify that the “-xx dB” bandwidth be entirely contained within the authorized or designated frequency band.

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (\text{OBW}/\text{RBW})]$ below the reference level. Specific guidance is given in 4.1.5.2.
- d) Steps a) through c) might require iteration to adjust within the specified tolerances.
- e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “-xx dB down” requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value.

f) Set detection mode to peak and trace mode to max hold.

g) Determine the reference value: Set the EUT to transmit an unmodulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyser marker to the highest level of the displayed trace (this is the reference value).

h) Determine the “-xx dB down amplitude” using [(reference value) – xx]. Alternatively, this calculation may be made by using the marker-delta function of the instrument.

i) If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum Analyser and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j).

j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “- xx dB down amplitude” determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “-xx dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.

k) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labelled. Tabular data may be reported in addition to the plot(s).

8.6.4 Result

The measured 20 dB bandwidth is: 0.550 kHz

The measured 99 % bandwidth is: 0.463 kHz

Test Cables used	K64, K102
Test equipment used	23, 144, 214, 226, 375, 502

The equipment passed the conducted tests	Yes	No	N.t.*
--	-----	----	-------

Test setup photos / test results are attached	Yes	No	Annex no. 3
---	-----	----	-------------

N.t.* see clause: 9

9. Additional information to the test report

Remark	Description
N.t. ¹	Not tested, because the antenna is part of the PCB
N.t. ²	Not tested, because the EUT is directly battery powered
N.t. ³	Not tested, because not applicable to the EUT
N.t. ⁴	Not tested, because not ordered
N.t. ⁵	Not tested, because permissive Class II Change

10. List of test equipment

Type	Manufacturer/ Model no.	Serial no.	Last calibration	Next calibration	Calibration executed by
Test fixture	Dudde	---	---	---	---
Magnetic loop antenna (9 kHz - 30 MHz)	Schwarzbeck FMZB 1516 (23)	---	05/2016	05/2019	Seibersdorf
OATS	Dudde (103)	---	06/2018	06/2021	TÜV Nord
Digital Multimeter	GW GDM-8045G (144)	0090256	08/2016	08/2019	Testo
Pre-amplifier (100kHz - 1.3GHz)	Hewlett Packard 8447 E (166a)	1726A00705	07/2018	07/2020	TÜV Nord
Hornantenna (2.0-14.0 GHz)	Schwarzbeck BBHA 9120 C (169)	305	09/2016	09/2020	Seibersdorf
Temerature Chamber	Heraeus Vötsch VMT 04/35	102a	03/2019	03/2021	TÜV Nord
Pre-amplifier (1GHz - 18GHz)	Narda (345)	---	07/2018	07/2020	TÜV Nord
Bilog-antenna (30- 1000 MHz)	Schwarzbeck VULP 9168 (406)	---	05/2019	05/2021	Seibersdorf
Log. Per, Antenne (1- 18 GHz)	Schwarzbeck STLP 9148 (445a)	---	05/2019	05/2021	Seibersdorf
Signal Analyzer (9 kHz -30.0 GHz)	Rohde & Schwarz FSV 30 (502)	100932	06/2016	06/2019	Rohde & Schwarz

11. Cable list

Type	Manufacturer/ Model no.	Cable no.	Last calibration	Next calibration	Verification executed by
RF- cable	Kabelmetal 18m [N]	K1a	10/2018	10/2019	TÜV Nord
RF- cable	Aircell 0.5m [BNC]	K40	10/2018	10/2019	TÜV Nord
RF- cable	Sucoflex 104 Suhner [N] 1 m	K50	10/2018	10/2019	TÜV Nord
RF- cable	Aircell 1m [BNC/N]	K56	10/2018	10/2019	TÜV Nord
RF- cable	Sucoflex 100 Suhner [N] 1 m	K51	10/2018	10/2019	TÜV Nord
RF- cable	Sucoflex 106 Suhner 8.5m [N]	K83	10/2018	10/2019	TÜV Nord
RF- cable	Jabao 14m [N]	K120	10/2018	10/2019	TÜV Nord
RF- cable	Sucoflex Suhner 13 m [N]	K144	10/2018	10/2019	TÜV Nord
RF- cable	Sucoflex Suhner 8m [SMA]	K145	10/2018	10/2019	TÜV Nord
RF- cable	Sucoflex Suhner 8m [SMA]	K146	10/2018	10/2019	TÜV Nord

End of test report