

cetecom
advanced

TEST REPORT

Test report no.: 1-7365-24-01-08_TR1-R02



Testing laboratory

cetecom advanced GmbH

Untertuerkheimer Strasse 6 – 10
66117 Saarbruecken / Germany

Phone: + 49 681 5 98 - 0

Fax: + 49 681 5 98 - 9075

Internet: <https://www.cetecomadvanced.com>

e-mail: mail@cetecomadvanced.com

Accredited Testing Laboratory:

The testing laboratory (area of testing) is accredited according to DIN EN ISO/IEC 17025 (2018-03) by the Deutsche Akkreditierungsstelle GmbH (DAkkS).

The accreditation is valid for the scope of testing procedures as stated in the accreditation certificate with the registration number:

D-PL-12047-01-00.

ISED Testing Laboratory Recognized Listing Number: DE0001

FCC designation number: DE0002

Applicant

FEIG ELECTRONIC GmbH

Industriestraße 1a
35781 Weilburg / GERMANY

Phone: +49 6471 31 09-0

Contact: Christian Lenz

e-mail: christian.lenz@feig.de

Phone: +49 6471 3109 487

Manufacturer

FEIG ELECTRONIC GmbH

Industriestraße 1a
35781 Weilburg / GERMANY

Test standard/s

FCC - Title 47 CFR Part 15 FCC - Title 47 of the Code of Federal Regulations; Chapter I; Part 15 - Radio frequency devices

For further applied test standards please refer to section 3 of this test report.

Test Item

Kind of test item: Radar scanner

Model name: MWD SBP

FCC ID: PJMMWDSBP

IC: 6633A-MWDSBP

Frequency: 57 – 64 GHz

Technology tested: UWB


Antenna: Integrated antenna

Power supply: 9 V to 30 V DC by external power supply

Temperature range: -30°C to +60°C


This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

Test report authorized:



Meheza Walla
Lab Manager
Radio Labs

Test performed:



Frank Heussner
Lab Manager
Radio Labs

1 Table of contents

1	Table of contents.....	2
2	General information.....	3
2.1	Notes and disclaimer	3
2.2	Application details	3
2.3	Test laboratories sub-contracted	3
3	Test standard/s, references and accreditations	4
4	Reporting statements of conformity – decision rule	5
5	Test environment	5
6	Test item	6
6.1	General description	6
6.2	Additional information	7
7	Description of the test setup.....	8
7.1	Shielded semi anechoic chamber.....	9
7.2	Shielded fully anechoic chamber.....	11
7.3	Radiated measurements > 18 GHz	13
7.4	Radiated measurements > 50/85 GHz	13
7.5	AC conducted.....	15
8	Sequence of testing.....	16
8.1	Sequence of testing radiated spurious 9 kHz to 30 MHz	16
8.2	Sequence of testing radiated spurious 30 MHz to 1 GHz.....	17
8.3	Sequence of testing radiated spurious 1 GHz to 18 GHz	18
8.4	Sequence of testing radiated spurious above 18 GHz.....	19
8.5	Sequence of testing radiated spurious above 50 GHz with external mixers	20
9	Measurement uncertainty	21
10	Summary of measurement results	22
11	Additional comments	22
12	Basic information of the DUT & selection of applicable rule parts	23
13	Measurement results	28
13.1	Occupied bandwidth & emission bandwidth & frequency stability.....	28
13.2	Radiated power (EIRP)	30
13.3	Peak transmitter conducted output power	34
13.4	Time domain requirements: Continuous transmitter off-times & transmit duty cycle	35
13.5	Spurious emissions radiated.....	38
13.6	Conducted emissions < 30 MHz (AC power line).....	52
14	Glossary.....	55
15	Document history.....	56

2 General information

2.1 Notes and disclaimer

The test results of this test report relate exclusively to the test item specified in this test report. cetecom advanced GmbH does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item.

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of cetecom advanced GmbH.

The testing service provided by cetecom advanced GmbH has been rendered under the current "General Terms and Conditions for cetecom advanced GmbH".

cetecom advanced GmbH will not be liable for any loss or damage resulting from false, inaccurate, inappropriate or incomplete product information provided by the customer.

Under no circumstances does the cetecom advanced GmbH test report include any endorsement or warranty regarding the functionality, quality or performance of any other product or service provided.

Under no circumstances does the cetecom advanced GmbH test report include or imply any product or service warranties from cetecom advanced GmbH, including, without limitation, any implied warranties of merchantability, fitness for purpose, or non-infringement, all of which are expressly disclaimed by cetecom advanced GmbH.

All rights and remedies regarding vendor's products and services for which cetecom advanced GmbH has prepared this test report shall be provided by the party offering such products or services and not by cetecom advanced GmbH.

In no case this test report can be considered as a Letter of Approval.

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

This test report replaces the test report with the number 1-7365-24-01-08_TR1-R01 and dated 2024-07-26.

2.2 Application details

Date of receipt of order:	2024-04-16
Date of receipt of test item:	2024-04-29
Start of test:*	2024-04-29
End of test:*	2024-07-17
Person(s) present during the test:	Christian Lenz (2024-04-29)

*Date of each measurement, if not shown in the plot, can be requested. Dates are stored in the measurement software.

2.3 Test laboratories sub-contracted

None

3 Test standard/s, references and accreditations


Test standard	Date	Description
FCC - Title 47 CFR Part 15	-/-	FCC - Title 47 of the Code of Federal Regulations; Chapter I; Part 15 - Radio frequency devices
Guidance	Version	Description
ANSI C63.4-2014	-/-	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
ANSI C63.10-2020	-/-	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
57-71 GHz (60 GHz) frequency band	V01	364244 D01 Meas 15.255 Radars v01: RADAR DEVICES CERTIFYING UNDER THE PROVISIONS OF §15.255

4 Reporting statements of conformity – decision rule

Only the measured values related to their corresponding limits will be used to decide whether the equipment under test meets the requirements of the test standards listed in chapter 3.

The measurement uncertainty is mentioned in this test report, see chapter 9, but is not taken into account - neither to the limits nor to the measurement results. Measurement results with a smaller margin to the corresponding limits than the measurement uncertainty have a potential risk of more than 5% that the decision might be wrong.

measured value, measurement uncertainty, verdict



5 Test environment

Temperature :	T_{nom}	+20 °C to +22 °C during room temperature tests
	T_{max}	+50 °C during high temperature tests
	T_{min}	-20 °C during low temperature tests
Relative humidity content :		49 %
Barometric pressure :		990 hPa to 1010 hPa
Power supply :	V_{nom}	24.0 V DC by external power supply
	V_{max}	27.6 V DC by external power supply ($1.15 * V_{\text{nom}}$)
	V_{min}	20.4 V DC by external power supply ($0.85 * V_{\text{nom}}$)

6 Test item

6.1 General description

Kind of test item	:	Radar scanner
Model name	:	MWD SBP
HMN	:	-/-
PMN	:	MWD SBP
HVIN	:	MWD SBP-A
FVIN	:	-/-
S/N serial number	:	EUT1: 9452357 EUT3: 9452358
Hardware status	:	FE1156-5
Software status	:	EUT 1 - Used for testing: MWD S V01.E1 (see note) EUT 3 - Used for testing: MWD S V01.E8 (see note) (Info - Normal operation: MWD S V01.01 / MWD S V01.08)
Firmware status	:	-/-
Frequency band	:	57 – 64 GHz
Type of modulation	:	FMCW
Number of modes	:	1
Antenna	:	Integrated antenna
Power supply	:	9 V to 30 V DC by external power supply
Temperature range	:	-30°C to +60°C

Note:

- Software status - Difference in software versions as declared by customer:
 - MWD S V01.01 / MWD S V01.08 is the version for normal operation.
 - MWD S V01.E1 / MWD S V01.E8 is essentially identical to MWD S V01.01 / MWD S V01.08 (especially for the 60 GHz technology), only BLE is deactivated after 30 seconds to enable separate testing of the 60 GHz technology.
 - MWD S V01.E8 is an updated version (for reduced spurious emissions)
As declared by the customer, the timing characteristics of the wanted signal in the 60 GHz range are the same as in version MWD S V01.E1, so the software update has no influence on the "Off Time Requirements" tests (15.255(c)(2)(iii)(B)).

6.2 Additional information

The content of the following annexes is defined in the QA. It may be that not all of the listed annexes are necessary for this report, thus some values in between may be missing.

Test setup and EUT photos are included in test report:

- 1-7365-24-01-03_TR1-A101-R01 (External photographs of EUT)
- 1-7365-24-01-01_TR1-A102-R01 (Internal photographs of EUT)
- 1-7365-24-01-08_TR1-A103-R01 (Test set-up photographs)
- Note: The referenced photos show EUT delivered by the customer in this project, not necessarily the exact one used for the specific tests. EUT identification shown in the photos may differ.

Additional measurement reports:

- 1-7365-24-01-08_TR1-A201-R01

Additional declarations (manufacturer's declarations, declarations of conformity, etc.):

- none

7 Description of the test setup

Typically, the calibrations of the test apparatus are commissioned to and performed by an accredited calibration laboratory. The calibration intervals are determined in accordance with the DIN EN ISO/IEC 17025. In addition to the external calibrations, the laboratory executes comparison measurements with other calibrated test systems or effective verifications. Weekly chamber inspections and range calibrations are performed. Where possible, RF generating and signaling equipment as well as measuring receivers and analyzers are connected to an external high-precision 10 MHz reference (GPS-based or rubidium frequency standard).


In order to simplify the identification of the equipment used at some special tests, some items of test equipment and ancillaries can be provided with an identifier or number in the equipment list below (Lab/Item).

Agenda: Kind of Calibration

k	calibration / calibrated	EK	limited calibration
ne	not required (k, ev, izw, zw not required)	zw	cyclical maintenance (external cyclical maintenance)
ev	periodic self verification	izw	internal cyclical maintenance
Ve	long-term stability recognized	g	blocked for accredited testing
vlkl!	Attention: extended calibration interval		
NK!	Attention: not calibrated	*	next calibration ordered / currently in progress

7.1 Shielded semi anechoic chamber

The radiated measurements are performed in vertical and horizontal plane in the frequency range from 30 MHz to 1 GHz in semi-anechoic chambers. The EUT is positioned on a non-conductive support with a height of 0.80 m above a conductive ground plane that covers the whole chamber. The receiving antennas are conform to specifications ANSI C63. These antennas can be moved over the height range between 1.0 m and 4.0 m in order to search for maximum field strength emitted from EUT. The measurement distances between EUT and receiving antennas are indicated in the test setups for the various frequency ranges. For each measurement, the EUT is rotated in all three axes until the maximum field strength is received. The wanted and unwanted emissions are received by spectrum analyzers where the detector modes and resolution bandwidths over various frequency ranges are set according to requirement ANSI C63.



Measurement distance: tri-log antenna 10 meter;

FS = UR + CL + AF

(FS-field strength; UR-voltage at the receiver; CL-loss of the cable; AF-antenna factor)


Example calculation:

$$\text{FS [dB}\mu\text{V/m]} = 12.35 \text{ [dB}\mu\text{V/m]} + 1.90 \text{ [dB]} + 16.80 \text{ [dB/m]} = 31.05 \text{ [dB}\mu\text{V/m]} (35.69 \mu\text{V/m})$$

Equipment table:

No.	Lab / Item	Equipment	Type	Manufacturer	Serial No.	INV. No.	Kind of Calibration	Last Calibration	Next Calibration
1	n. a.	Analyzer-Impedance-System	AIS16/1	Spitzenberger + Spies GmbH & Co. KG	U02076 07/0 1023	400001751	k	19.10.2023	31.10.2025
2	n. a.	Antenna Tower	Model 2175	ETS-Lindgren	64762	300003745	izw	-/-	-/-
3	n. a.	DC power supply, 60Vdc, 50A, 1200 W	6032A	HP	2920A04466	300000580	ne	-/-	-/-
4	n. a.	EMI Test Receiver	ESR3	Rohde & Schwarz	102587	300005771	k	06.12.2023	31.12.2024
5	n. a.	Positioning Controller	Model 2090	ETS-Lindgren	64672	300003746	izw	-/-	-/-
6	n. a.	Semi anechoic chamber	3000023	MWB AG		300000551	ne	-/-	-/-
7	n. a.	Switch-Unit	3488A	HP	2719A14505	300000368	ev	-/-	-/-
8	n. a.	TRILOG Broadband Test-Antenna 30 MHz - 3 GHz	VULB9163	Schwarzbeck Mess-Elektronik	216	300003288	viKI!	31.08.2023	31.08.2025
9	n. a.	Turntable	2089-4.0	EMCO		300004394	ne	-/-	-/-
10	n. a.	Turntable Interface-Box	Model 105637	ETS-Lindgren	44583	300003747	izw	-/-	-/-

7.2 Shielded fully anechoic chamber



Measurement distance: horn antenna 3 meter; loop antenna 3 meter

FS = UR + CA + AF

(FS-field strength; UR-voltage at the receiver; CA-loss of the signal path; AF-antenna factor)

Example calculation:

$$FS [\text{dB}\mu\text{V}/\text{m}] = 40.0 [\text{dB}\mu\text{V}/\text{m}] + (-35.8) [\text{dB}] + 32.9 [\text{dB}/\text{m}] = 37.1 [\text{dB}\mu\text{V}/\text{m}] (71.61 \mu\text{V}/\text{m})$$

OP = AV + D - G + CA

(OP-radiated output power; AV-analyzer value; D-free field attenuation of measurement distance; G-antenna gain+amplifier gain; CA-loss signal path)


Example calculation:

$$OP [\text{dBm}] = -65.0 [\text{dBm}] + 50 [\text{dB}] - 20 [\text{dBi}] + 5 [\text{dB}] = -30 [\text{dBm}] (1 \mu\text{W})$$


Equipment table:

No.	Lab / Item	Equipment	Type	Manufacturer	Serial No.	INV. No.	Kind of Calibration	Last Calibration	Next Calibration
1	n. a.	4U RF Switch Platform	L4491A	Agilent Technologies	MY50000037	300004509	ne	-/-	-/-
2	n. a.	Active Loop Antenna 9 kHz to 30 MHz	6502	EMCO/2	8905-2342	300000256	vlKI!	19.07.2023	31.07.2025
3	n. a.	Anechoic chamber	FAC 3/5m	MWB / TDK	87400/02	300000996	ev	-/-	-/-
4	n. a.	Broadband Amplifier 0.5-18 GHz	CBLU5184540	CERNEX	22049	300004481	ev	-/-	-/-
5	n. a.	DC power supply, 60Vdc, 50A, 1200 W	6032A	HP	2818A03450	300001040	vlKI!	05.12.2023	31.12.2026
6	n. a.	Double-Ridged Waveguide Horn Antenna 1-18.0GHz	3115	EMCO	8812-3088	300001032	vlKI!	10.10.2023	31.10.2025
7	n. a.	EMI Test Receiver 20Hz- 26,5GHz	ESU26	R&S	100037	300003555	k	11.12.2023	31.12.2024
8	n. a.	Highpass Filter	WHKX7.0/18G-8SS	Wainwright	19	300003790	ne	-/-	-/-
9	n. a.	NEXIO EMV-Software	BAT EMC V2022.0.32.0	Nexio		300004682	ne	-/-	-/-
10	n. a.	RF-Amplifier	AMF-6F06001800-30-10P-R	NARDA-MITEQ Inc	2011572	300005241	ev	-/-	-/-
11	n. a.	Switch / Control Unit	3488A	HP	*	300000199	ne	-/-	-/-
12	n. a.	Variable isolating transformer	MPL IEC625 Bus Variable isolating transformer	Erfi	91350	300001155	ne	-/-	-/-

7.3 Radiated measurements > 18 GHz



7.4 Radiated measurements > 50/85 GHz



Measurement distance: horn antenna e.g. 75 cm

$$FS = UR + CA + AF$$

(FS-field strength; UR-voltage at the receiver; CA-loss signal path & distance correction; AF-antenna factor)

Example calculation:

$$FS [dB\mu V/m] = 40.0 [dB\mu V/m] + (-60.1) [dB] + 36.74 [dB/m] = 16.64 [dB\mu V/m] (6.79 \mu V/m)$$

$$OP = AV + D - G + CA$$

(OP-radiated output power; AV-analyzer value; D-free field attenuation of measurement distance; G-antenna gain+amplifier gain; CA-loss signal path)

Example calculation:


$$OP [dBm] = -59.0 [dBm] + 44.0 [dB] - 20.0 [dBi] + 5.0 [dB] = -30 [dBm] (1 \mu W)$$

Note: conversion loss of mixer is already included in analyzer value.

Equipment table:

No.	Lab / Item	Equipment	Type	Manufacturer	Serial No.	INV. No.	Kind of Calibration	Last Calibration	Next Calibration
1	n. a.	Broadband LNA 18-50 GHz	CBL18503070PN	CERNEX	25240	300004948	ev	22.04.2024	21.04.2026
2	n. a.	Harmonic Mixer 3-Port, 110-170 GHz	FS-Z170	Radiometer Physics GmbH	100014	300004156	k	21.07.2023	31.07.2024
3	n. a.	Harmonic Mixer 3-Port, 140-220 GHz	SAM-220	Radiometer Physics GmbH	200001	300004157	k	02.08.2023	31.08.2024
4	n. a.	Harmonic Mixer 3-Port, 50-75 GHz	FS-Z75	Rohde & Schwarz	101578	300005788	k	19.07.2023	31.07.2024
5	n. a.	Harmonic Mixer 3-Port, 60-90 GHz	FS-Z90	R&S	101555	300004691	k	25.08.2023	31.08.2024
6	n. a.	Harmonic Mixer 3-Port, 75-110 GHz	FS-Z110	Rohde & Schwarz	101411	300004959	k	21.07.2023	31.07.2024
7	n. a.	Harmonic Mixer 3-port, 90-140 GHz	FS-Z140	Rohde & Schwarz	101119	300005581	k	03.08.2023	31.08.2024
8	n. a.	Horn Antenna 18,0-40,0 GHz	LHAF180	Microw.Devel	39180-103-021	300001747	vIKI!	24.01.2024	23.01.2026
9	n. a.	Oscilloscope	DPO5054	Tektronix	C010174	300004169	k	05.12.2023	31.12.2025
10	n. a.	Power supply	N5767A	Agilent Technologies	US14J1569P	300004851	vIKI!	06.12.2023	31.12.2026
11	n. a.	Signal- and Spectrum Analyzer 2 Hz - 50 GHz	FSW50	Rohde&Schwarz	101560	300006179	k	17.01.2024	31.01.2025
12	n. a.	Signal- and Spectrum Analyzer 2 Hz - 85 GHz	FSW85	Rohde&Schwarz	101333	300005568	k	02.08.2023	31.08.2024
13	n. a.	Std. Gain Horn Antenna 114-173 GHz	2924-20	Flann	*	300001999	ne	-/-	-/-
14	n. a.	Std. Gain Horn Antenna 145-220 GHz	3024-20	Flann	*	300002000	ne	-/-	-/-
15	n. a.	Std. Gain Horn Antenna 33.0-50.1 GHz	2324-20	Flann	57	400000683	ne	-/-	-/-
16	n. a.	Std. Gain Horn Antenna 49.9-75.8 GHz	2524-20	Flann	*	300001983	ne	-/-	-/-
17	n. a.	Std. Gain Horn Antenna 60-90 GHz	COR 60_90	Thomson CSF		300000814	ev	-/-	-/-
18	n. a.	Std. Gain Horn Antenna 73.8-112 GHz	2724-20	Flann	*	300001988	ne	-/-	-/-
19	n. a.	Std. Gain Horn Antenna 92.3-140 GHz	2824-20	Flann	*	300001993	ne	-/-	-/-
20	n. a.	Temperature Test Chamber	T-40/50	CTS GmbH	064023	300003540	ev	09.05.2022	31.08.2024
21	n. a.	V-Band Positive Amplitude Detector	SFD-503753-15SF-P1	Sage Millimeter Inc.	07353-1	300006118	ev	-/-	-/-

7.5 AC conducted



FS = UR + CF + VC

(FS-field strength; UR-voltage at the receiver; CR-loss of the cable and filter; VC-correction factor of the ISN)

Example calculation:

$$FS [\text{dB}\mu\text{V/m}] = 37.62 [\text{dB}\mu\text{V/m}] + 9.90 [\text{dB}] + 0.23 [\text{dB}] = 47.75 [\text{dB}\mu\text{V/m}] (244.06 \mu\text{V/m})$$

Equipment table:

No.	Lab / Item	Equipment	Type	Manufacturer	Serial No.	INV. No.	Kind of Calibration	Last Calibration	Next Calibration
1	n. a.	Two-line V-Network (LISN) 9 kHz to 30 MHz	ESH3-Z5	Rohde & Schwarz	892475/017	300002209	viKI!	12.12.2023	31.12.2025
2	n. a.	DC power supply, 60Vdc, 50A, 1200 W	6032A	HP	2920A04466	300000580	ne	-/-	-/-
3	n. a.	Hochpass 150 kHz	EZ-25	R&S	100010	300003798	ev	-/-	-/-
4	n. a.	PC	TecLine	F+W		300003532	ne	-/-	-/-
5	n. a.	Analyzer-Impedance-System	AIS16/1	Spitzenberger + Spies GmbH & Co. KG	U02076 07/0 1023	400001751	k	19.10.2023	31.10.2025
6	n. a.	EMI Test Receiver 3.6 GHz	ESR3	Rohde & Schwarz	102981	300006318	k	08.12.2023	31.12.2024

8 Sequence of testing

8.1 Sequence of testing radiated spurious 9 kHz to 30 MHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, it is placed on a table with 0.8 m height.
- If the EUT is a floor standing device, it is placed directly on the turn table.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 3 m (see ANSI C 63.4) – see test details.
- EUT is set into operation.

Premereasurement*

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 1 m.
- At each turntable position the analyzer sweeps with positive-peak detector to find the maximum of all emissions.

Final measurement

- Identified emissions during the pre-measurement are maximized by the software by rotating the turntable from 0° to 360°.
- Loop antenna is rotated about its vertical axis for maximum response at each azimuth about the EUT. (For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT)
- The final measurement is done in the position (turntable and elevation) causing the highest emissions with quasi-peak (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. A plot with the graph of the premeasurement and the limit is stored.

*)Note: The sequence will be repeated three times with different EUT orientations.

8.2 Sequence of testing radiated spurious 30 MHz to 1 GHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 10 m or 3 m (see ANSI C 63.4) – see test details.
- EUT is set into operation.

Premereasurement

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 m to 3 m.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement

- The final measurement is performed for at least six highest peaks according to the requirements of the ANSI C63.4.
- Based on antenna and turntable positions at which the peak values are measured the software maximize the peaks by changing turntable position $\pm 45^\circ$ and antenna height between 1 and 4 m.
- The final measurement is done with quasi-peak detector (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement with marked maximum final results and the limit is stored.

8.3 Sequence of testing radiated spurious 1 GHz to 18 GHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, a 2-axis positioner with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed directly on the turn table.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 3 m (see ANSI C 63.4) – see test details.
- EUT is set into operation.

Premereasurement

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height is 1.5 m.
- At each turntable position and antenna polarization the analyzer sweeps with positive peak detector to find the maximum of all emissions.

Final measurement

- The final measurement is performed for at least six highest peaks according to the requirements of the ANSI C63.4.
- Based on antenna and turntable positions at which the peak values are measured the software maximizes the peaks by rotating the turntable from 0° to 360°. This measurement is repeated for different EUT-table positions (0° to 150° in 30°-steps) and for both antenna polarizations.
- The final measurement is done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and RMS detector (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement with marked maximum final results and the limit is stored.

8.4 Sequence of testing radiated spurious above 18 GHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet.
- The measurement distance is as appropriate (e.g. 0.5 m).
- The EUT is set into operation.

Premeasurement

- The test antenna is handheld and moved carefully over the EUT to cover the EUT's whole sphere and different polarizations of the antenna.

Final measurement

- The final measurement is performed at the position and antenna orientation causing the highest emissions with Peak and RMS detector (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement and the limit is stored.

8.5 Sequence of testing radiated spurious above 50 GHz with external mixers

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet.
- The measurement distance is as appropriate for far field (e.g. 0.25 m).
- The EUT is set into operation.

Premereasurement

- The test antenna with external mixer is handheld and moved carefully over the EUT to cover the EUT's whole sphere and different polarizations of the antenna.
- Caution is taken to reduce the possible overloading of the external mixer.

Final measurement

- The final measurement is performed at the position and antenna orientation causing the highest emissions with Peak and RMS detector (as described in ANSI C 63.4).
- As external mixers may generate false images care is taken to ensure that any emission measured by the spectrum analyzer does indeed originate in the EUT. Signal identification feature of spectrum analyzer is used to eliminate false mixer images (i.e., it is not the fundamental emission or a harmonic falling precisely at the measured frequency).
- Final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement and the limit is stored.

9 Measurement uncertainty

Test case	Uncertainty
Equivalent isotropically radiated power (e.i.r.p.)	Conducted value ± 1 dB Radiated value ± 3 dB
Permitted range of operating frequencies	± 100 kHz
Conducted unwanted emissions in the spurious domain (up to 18 GHz)	± 1 dB
Radiated unwanted emissions in the spurious domain (up to 18 GHz)	± 3 dB
Conducted unwanted emissions in the spurious domain (18 to 40 GHz)	± 4 dB
Radiated unwanted emissions in the spurious domain (18 to 40 GHz)	± 4 dB
Conducted unwanted emissions in the spurious domain (40 to 50 GHz)	± 4.5 dB
Radiated unwanted emissions in the spurious domain (40 to 50 GHz)	± 4.5 dB
Conducted unwanted emissions in the spurious domain (above 50 GHz)	± 5 dB
Radiated unwanted emissions in the spurious domain (above 50 GHz)	± 5 dB
DC and low frequency voltages	± 3 %
Temperature	± 1 °C
Humidity	± 3 %

10 Summary of measurement results

<input checked="" type="checkbox"/>	No deviations from the technical specifications were ascertained
<input type="checkbox"/>	There were deviations from the technical specifications ascertained
<input type="checkbox"/>	This test report is only a partial test report. The content and verdict of the performed test cases are listed below.

TC identifier	Description	verdict	date	Remark
RF-Testing	FCC 47 CFR Part 15 (dated 2023-08-23)	see below	2024-09-04	-/-

Test specification clause	Test case	Temperature conditions	Power supply	Pass	Fail	NA	NP	Remark
47 CFR 15.215(b) & (c), 47 CFR 15.255(f)	Occupied bandwidth & Frequency stability	Nominal Extreme	Nominal Extreme	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
47 CFR 15.255(b)(3) & (c)	Radiated power (EIRP)	Nominal	Nominal	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
47 CFR 15.255(c)(2) 47 CFR 15.255(e)	Peak transmitter conducted output power	Nominal	Nominal	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	-/-
47 CFR 15.255(b)(3), 47 CFR 15.255(c)	Time domain requirements	Nominal	Nominal	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
47 CFR 15.255(d)	Spurious emissions radiated	Nominal	Nominal	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
47 CFR 15.207	Conducted emissions < 30 MHz (AC power line)	Nominal	Nominal	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies

Note: NA = Not applicable; NP = Not performed

11 Additional comments

Reference documents: None

Special test descriptions: None

Configuration descriptions: None

12 Basic information of the DUT & selection of applicable rule parts

Basic information of the DUT:

General: see chapter "6 Test item"

Operation condition: Operation on aircraft (47 CFR 15.255(b))
 Unmanned aircraft (47 CFR 15.255(b)(3))
 Not unmanned aircraft
 No operation on aircraft

Note: Operation under the provisions of this section is not permitted for equipment used on satellites (47 CFR 15.255(a)).

Kind of DUT: Devices other than field disturbance sensors and other than fixed point-to-point transmitters located outdoors
 Fixed point-to-point transmitters located outdoors
 Field disturbance sensors/radars
 Pulsed field disturbance sensors/radars
 Other than pulsed field disturbance sensors/radars

Frequency band: Operating within band 59.3 – 71.0 GHz (47 CFR 15.255(b)(2)(iii))
 Operating within band 60 – 64 GHz (47 CFR 15.255(b)(3))
 Operating within band 57 – 71 GHz (47 CFR 15.255(c)(1) / (c)(2))
 Operating within band 57.0 – 59.4 GHz (47 CFR 15.255(c)(2)(i))
 Operating within band 57.0 – 61.56 GHz (47 CFR 15.255(c)(2)(ii))
 Operating within band 57 – 64 GHz (47 CFR 15.255(c)(2)(iii) / (c)(3))
 Operating within band 61.0 – 61.5 GHz (47 CFR 15.255(c)(2)(v))

Note: See results in chapter 13.1

Selection of applicable rule parts:

Applicable rule parts and limits depend on the basic information of the DUT (see chapter 12).

The comparison of the basic information of the DUT with the rule parts lead to the following conclusions:

Rule Part	Applicable?	
	Yes	No
47 CFR 15.255:		
(a) General: Operation under the provisions of this section is not permitted for equipment used on satellites .	<input checked="" type="checkbox"/>	
(b) Operation on aircraft: Operation on aircraft is permitted under the following conditions:	<input type="checkbox"/>	<input checked="" type="checkbox"/>
(1) When the aircraft is on the ground.	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
(2) While airborne, only in closed exclusive on-board communication networks within the aircraft, with the following exceptions:	<input type="checkbox"/>	<input checked="" type="checkbox"/>
(i) Equipment shall not be used in wireless avionics intra-communication (WAIC) applications where external structural sensors or external cameras are mounted on the outside of the aircraft structure.	<input type="checkbox"/>	<input checked="" type="checkbox"/>
(ii) Except as permitted in paragraph (b)(3) of this section, equipment shall not be used on aircraft where there is little attenuation of RF signals by the body/fuselage of the aircraft.	<input type="checkbox"/>	<input checked="" type="checkbox"/>
(iii) Field disturbance sensor/radar devices may only operate in the frequency band 59.3–71.0 GHz while installed in passengers' personal portable electronic equipment (e.g., smartphones, tablets) and shall comply with paragraph (b)(2)(i) of this section, and relevant requirements of paragraphs (c)(2) through (c)(4) of this section.	<input type="checkbox"/>	<input checked="" type="checkbox"/>
(3) Field disturbance sensors/radar devices deployed on unmanned aircraft may operate within the frequency band 60–64 GHz , provided that the transmitter not exceed 20 dBm peak EIRP. The sum of continuous transmitter off-times of at least two milliseconds shall equal at least 16.5 milliseconds within any contiguous interval of 33 milliseconds. Operation shall be limited to a maximum of 121.92 meters (400 feet) above ground level.	<input type="checkbox"/>	<input checked="" type="checkbox"/>
(c) Radiated power limits: Within the 57–71 GHz band , emission levels shall not exceed the following equivalent isotropically radiated power (EIRP):	<input checked="" type="checkbox"/>	
(1) Devices other than field disturbance sensors shall comply with one of the following power limits, as measured during the transmit interval:	<input type="checkbox"/>	<input checked="" type="checkbox"/>
(i) The average power of any emission shall not exceed 40 dBm and the peak power of any emission shall not exceed 43 dBm; or	<input type="checkbox"/>	<input checked="" type="checkbox"/>
(ii) For fixed point-to-point transmitters located outdoors , the average power of any emission shall not exceed 82 dBm, and shall be reduced by 2 dB for every dB that the antenna gain is less than 51 dBi. The peak power of any emission shall not exceed 85 dBm, and shall be reduced by 2 dB for every dB that the antenna gain is less than 51 dBi.	<input type="checkbox"/>	<input checked="" type="checkbox"/>
(A) The provisions in this paragraph (c) for reducing transmit power based on antenna gain shall not require that the power levels be reduced below the limits specified in paragraph (c)(1)(i) of this section.	<input type="checkbox"/>	<input checked="" type="checkbox"/>
(B) The provisions of § 15.204(c)(2) and (4) that permit the use of different antennas of the same type and of equal or less directional gain do not apply to intentional radiator systems operating under this provision. In lieu thereof, intentional radiator systems shall be certified using the specific antenna(s) with which the system will be marketed and operated. Compliance testing shall be performed using the highest gain and the lowest gain antennas for which certification is sought and with the intentional radiator operated at its maximum available output power level. The responsible party, as defined in § 2.909 of this chapter, shall supply a list of acceptable antennas with the application for certification.	<input type="checkbox"/>	<input checked="" type="checkbox"/>

(2) Field disturbance sensors/radars shall not exceed -10 dBm peak conducted output power and 10 dBm peak EIRP except that field disturbance sensors/radars that limit their operation to all or part of the specified frequency band may operate without being subject to a transmitter conducted output power limit if they operate in compliance with paragraph (b)(3) of this section or with one or more of the provisions below:	<input checked="" type="checkbox"/>	<input type="checkbox"/>
(i) 57.0–59.4 GHz : the peak EIRP level shall not exceed 20 dBm for indoor operation or 30 dBm for outdoor operation ;	<input type="checkbox"/>	<input checked="" type="checkbox"/>
(ii) 57.0–61.56 GHz : the peak EIRP shall not exceed 3 dBm except that the peak EIRP shall not exceed 20 dBm if the sum of continuous transmitter off-times of at least two milliseconds equals at least 16.5 milliseconds within any contiguous interval of 33 milliseconds;	<input type="checkbox"/>	<input checked="" type="checkbox"/>
(iii) 57.0–64.0 GHz :	<input type="checkbox"/>	<input type="checkbox"/>
(A) The peak EIRP shall not exceed 14 dBm, and the sum of continuous transmitter off-times of at least two milliseconds shall equal at least 25.5 milliseconds within any contiguous interval of 33 milliseconds, except as specific in paragraph (c)(2)(iii)(B) of this section;	<input type="checkbox"/>	<input checked="" type="checkbox"/>
(B) The peak EIRP shall not exceed 20 dBm, and the sum of continuous transmitter off-times of at least two milliseconds shall equal at least 16.5 milliseconds within any contiguous interval of 33 milliseconds when operated outdoors:	<input checked="" type="checkbox"/>	<input type="checkbox"/>
(1) As part of a temporary or permanently fixed application ; or	<input checked="" type="checkbox"/>	<input type="checkbox"/>
(2) When being used in vehicular applications to perform specific tasks of moving something or someone, except for in-cabin applications ;	<input checked="" type="checkbox"/>	<input type="checkbox"/>
(iv) A field disturbance sensor may operate in any of the modes in the above subsections so long as the device operates in only one mode at any time and does so for at least 33 milliseconds before switching to another mode.	<input checked="" type="checkbox"/>	<input type="checkbox"/>
(v) 61.0–61.5 GHz : For field disturbance sensors/radars that occupy 500 MHz bandwidth or less that are contained wholly within the frequency band 61.0–61.5 GHz , the average power of any emission, measured during the transmit interval, shall not exceed 40 dBm, and the peak power of any emission shall not exceed 43 dBm. In addition, the average power of any emission outside of the 61.0–61.5 GHz band , measured during the transmit interval, but still within the 57–71 GHz band, shall not exceed 10 dBm, and the peak power of any emission shall not exceed 13 dBm.	<input type="checkbox"/>	<input checked="" type="checkbox"/>
(3) For pulsed field disturbance sensors/radars operating in the 57–64 GHz band that have a maximum pulse duration of 6 ns, the average EIRP shall not exceed 13 dBm and the transmit duty cycle shall not exceed 10% during any 0.3 μ s time window. In addition, the average integrated EIRP within the frequency band 61.5–64.0 GHz shall not exceed 5 dBm in any 0.3 μ s time window. Peak emissions shall not exceed 20 dB above the maximum permitted average emission limit applicable to the equipment under test. The radar bandwidth is the frequency band bounded by the points that are 10 dB below the highest radiated emission, as based on the complete transmission system including the antenna	<input type="checkbox"/>	<input checked="" type="checkbox"/>
(4) The provisions in § 15.35(b) and (c) that require emissions to be averaged over a 100 millisecond period and that limits the peak power to 20 dB above the average limit do not apply to devices operating under paragraphs (c)(2) and (3) of this section.	<input checked="" type="checkbox"/>	<input type="checkbox"/>
(d) Limits on spurious emissions:	<input checked="" type="checkbox"/>	
(1) The power density of any emissions outside the 57–71 GHz band shall consist solely of spurious emissions.	<input checked="" type="checkbox"/>	
(2) Radiated emissions below 40 GHz shall not exceed the general limits in § 15.209.	<input checked="" type="checkbox"/>	
(3) Between 40 GHz and 200 GHz, the level of these emissions shall not exceed 90 pW/cm ² at a distance of 3 meters.	<input checked="" type="checkbox"/>	
(4) The levels of the spurious emissions shall not exceed the level of the fundamental emission.	<input checked="" type="checkbox"/>	
(e) Limits on transmitter conducted output power.	<input type="checkbox"/>	<input checked="" type="checkbox"/>

(1) Except as specified in paragraph (e)(2) of this section, the peak transmitter conducted output power of devices other than field disturbance sensors/radars shall not exceed 500 mW. Depending on the gain of the antenna, it may be necessary to operate the intentional radiator using a lower peak transmitter output power in order to comply with the EIRP limits specified in paragraph (c) of this section.	<input type="checkbox"/>	<input checked="" type="checkbox"/>
(2) Devices other than field disturbance sensors/radars with an emission bandwidth of less than 100 megahertz must limit their peak transmitter conducted output power to the product of 500 mW times their emission bandwidth divided by 100 megahertz. For the purposes of this paragraph, emission bandwidth is defined as the instantaneous frequency range occupied by a steady state radiated signal with modulation, outside which the radiated power spectral density never exceeds 6 dB below the maximum radiated power spectral density in the band, as measured with a 100 kilohertz resolution bandwidth spectrum analyzer. The center frequency must be stationary during the measurement interval, even if not stationary during normal operation (e.g., for frequency hopping devices).	<input type="checkbox"/>	<input checked="" type="checkbox"/>
(f) Frequency stability: Fundamental emissions must be contained within the frequency bands specified in this section during all conditions of operation. Equipment is presumed to operate over the temperature range -20 to + 50 degrees Celsius with an input voltage variation of 85% to 115% of rated input voltage, unless justification is presented to demonstrate otherwise.	<input checked="" type="checkbox"/>	
(g) Radio frequency radiation exposure: Radio frequency devices operating under the provisions of this part are subject to the radio frequency radiation exposure requirements specified in §§ 1.1307(b), 1.1310, 2.1091, and 2.1093 of this chapter, as appropriate. Applications for equipment authorization of mobile or portable devices operating under this section must contain a statement confirming compliance with these requirements. Technical information showing the basis for this statement must be submitted to the Commission upon request.	<input checked="" type="checkbox"/>	
(h) Group installation: Any transmitter that has received the necessary FCC equipment authorization under the rules of this chapter may be mounted in a group installation for simultaneous operation with one or more other transmitter(s) that have received the necessary FCC equipment authorization, without any additional equipment authorization. However, no transmitter operating under the provisions of this section may be equipped with external phase-locking inputs that permit beam-forming arrays to be realized.	<input checked="" type="checkbox"/>	
(i) Compliance measurement: Measurement procedures that have been found to be acceptable to the Commission in accordance with § 2.947 of this chapter may be used to demonstrate compliance.	<input checked="" type="checkbox"/>	
(1) For purposes of demonstrating compliance with this section, corrections to the transmitter conducted output power may be made due to the antenna and circuit loss.	<input checked="" type="checkbox"/>	
(2) Compliance measurements of frequency-agile field disturbance sensors/radars shall be performed with any related frequency sweep, step, or hop function activated.	<input checked="" type="checkbox"/>	<input type="checkbox"/>
47 CFR 15.215		
(c) Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission , or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. In the case of intentional radiators operating under the provisions of subpart E, the emission bandwidth may span across multiple contiguous frequency bands identified in that subpart. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.	<input checked="" type="checkbox"/>	

47 CFR 15.209	<input checked="" type="checkbox"/>	
47 CFR 15.207		
(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the table of this paragraph (see chapter 13.6), as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.	<input checked="" type="checkbox"/>	
(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtainig their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.	<input type="checkbox"/>	<input checked="" type="checkbox"/>

13 Measurement results

13.1 Occupied bandwidth & emission bandwidth & frequency stability

Description:

Measurement of the bandwidth and the frequency stability of the wanted signal (fundamental emission) under temperature and supply voltage variations.

Limits and provisions:

Selection of applicable rule parts: see 12

Bandwidth & Applicable limits of designated frequency band			
Applicable	Rule part	Method of bandwidth measurement	Limit of designated frequency band
<input type="checkbox"/>	15.255(b)(2)(iii)	20 dB bandwidth or 99% bandwidth	59.3 - 71.0 GHz
<input type="checkbox"/>	15.255(b)(3)	20 dB bandwidth or 99% bandwidth	60 - 64 GHz
<input type="checkbox"/>	15.255(c)(1)(i)	20 dB bandwidth or 99% bandwidth	57 - 71 GHz
<input type="checkbox"/>	15.255(c)(1)(ii)	20 dB bandwidth or 99% bandwidth	57 - 71 GHz
<input type="checkbox"/>	15.255(c)(2)	20 dB bandwidth or 99% bandwidth	57 - 71 GHz
<input type="checkbox"/>	15.255(c)(2)(i)	20 dB bandwidth or 99% bandwidth	57.0 - 59.4 GHz
<input type="checkbox"/>	15.255(c)(2)(ii)	20 dB bandwidth or 99% bandwidth	57.0 - 61.56 GHz
<input checked="" type="checkbox"/>	15.255(c)(2)(iii)	20 dB bandwidth or 99% bandwidth	57.0 - 64.0 GHz
<input type="checkbox"/>	15.255(c)(2)(v)	20 dB bandwidth or 99% bandwidth	61.0 - 61.5 GHz
<input type="checkbox"/>	15.255(c)(3)	10 dB bandwidth	57 - 64 GHz
<input type="checkbox"/>	15.255(e)(2)	6 dB emission bandwidth (EBW_{6dB})	None (required for calculation in chapter 13.3)

Note:

- Definition of 6dB emission bandwidth (15.255(e)(2)): the instantaneous frequency range occupied by a steady state radiated signal with modulation, outside which the radiated power spectral density never exceeds 6 dB below the maximum radiated power spectral density in the band, as measured with a 100 kilohertz resolution bandwidth spectrum analyzer. The center frequency must be stationary during the measurement interval, even if not stationary during normal operation (e.g., for frequency hopping devices).

Measurement:

Measurement parameter	
Detector:	Pos-Peak
Resolution bandwidth:	50 MHz
Video bandwidth:	80 MHz
Trace-Mode:	Max Hold

Measurement procedures:

- Bandwidth: ANSI C63.10-2020 6.9 / 9.3 / 9.4
- Frequency stability: ANSI C63.10-2020 6.8 / 9.5

Measurement results:**20 dB bandwidth at normal conditions:**

EUT	SW	Test condition	f _L [GHz]	f _H [GHz]	Bandwidth [GHz]
1	MWD S V01.E1	T _{nom} / V _{nom}	60.010	63.400	3.390

99% bandwidth at normal conditions:

EUT	SW	Test condition	f _L [GHz]	f _H [GHz]	Bandwidth [GHz]
1	MWD S V01.E1	T _{nom} / V _{nom}	60.073	63.337	3.264

Frequency stability (RSS-210 J.6):

Mode for frequency stability tests: Normal Operation mode (Mode with the widest bandwidth, ANSI C63.10-2020 5.6.2.2)

Bandwidth measurement for frequency stability tests: 20 dB bandwidth / 99% bandwidth

Note:

- Detailed measurement results: see measurement report 1-7365-24-01-08_TR1-A201-R01

Verdict: Compliant

13.2 Radiated power (EIRP)

Description:

Measurement of the maximum radiated E.I.R.P. of the wanted signal.

Limits and provisions:

Selection of applicable rule parts: see 12

Applicable limits of radiated power (EIRP)			
Applicable	Rule part	Limit average EIRP	Limit peak EIRP
<input type="checkbox"/>	15.255(b)(3)	none	20 dBm
<input type="checkbox"/>	15.255(c)(1)(i)	40 dBm (see note 1)	43 dBm
<input type="checkbox"/>	15.255(c)(1)(ii)	Calculation depending on EUT antenna gain (see note 1, 2.1 & 2.3)	Depending on EUT antenna gain (see note 1, 2.2 & 2.3)
<input type="checkbox"/>	15.255(c)(2)	none	10 dBm
<input type="checkbox"/>	15.255(c)(2)(i)	none	20 dBm (indoor) 30 dBm (outdoor)
<input type="checkbox"/>	15.255(c)(2)(ii)	none	3 dBm (general) 20 dBm (+ off-time requirement)
<input type="checkbox"/>	15.255(c)(2)(iii)(A)	none	14 dBm (+ off-time requirement)
<input checked="" type="checkbox"/>	15.255(c)(2)(iii)(B)	none	20 dBm (+ off-time requirement)
<input type="checkbox"/>	15.255(c)(2)(v)	40 dBm (within 61-61.5 GHz) (see note 1)	43 dBm (within 61.0-61.5 GHz)
		10 dBm (outside 61-61.5 GHz, but within 57-71GHz) (see note 1)	13 dBm (outside 61-61.5 GHz, but within 57-71GHz)
<input type="checkbox"/>	15.255(c)(3)	13 dBm (average EIRP during any 0.3 µs time window) (+ time domain requirement)	applicable average limit + 20 dB
		5 dBm (average integrated EIRP within 61.5–64.0 GHz in any 0.3 µs time window)	

Note:

1. Measured during the transmit interval
2. Calculation depending on EUT antenna gain:
 - 2.1. The average power of any emission shall not exceed 82 dBm, and shall be reduced by 2 dB for every dB that the antenna gain is less than 51 dBi.
 - 2.2. The peak power of any emission shall not exceed 85 dBm, and shall be reduced by 2 dB for every dB that the antenna gain is less than 51 dBi.
 - 2.3. Reducing the transmit power based on the antenna gain shall not require that the power levels be reduced below the limits specified in 15.255(c)(1)(i).

Measurement:**Spectrum analyzer:**

Measurement parameter	
Detector:	Pos-Peak
Resolution bandwidth:	50 MHz
Video bandwidth:	80 MHz
Trace-Mode:	Max Hold

Measurement procedures:

- Fundamental emission using an RF detector: ANSI C63.10-2020 9.8

Measurement results:


EUT	SW	Test condition	Max. Peak E.I.R.P.	Limit Peak E.I.R.P	Average E.I.R.P	Limit Average EIRP
1	MWD S V01.E1	T_{nom} / V_{nom}	18.4 dBm	20 dBm	-/-	none
3	MWD S V01.E1	T_{nom} / V_{nom}	18.4 dBm	20 dBm	-/-	none
1	MWD S V01.E8	T_{nom} / V_{nom}	18.5 dBm	20 dBm	-/-	none

Note concerning software update:

- MWD S V01.E1 → MWD S V01.E8
- Software update shows no significant influence on Peak E.I.R.P. of the fundamental emission.


Spectrum analyzer:**Plot 1: Max. PEAK E.I.R.P (FSW50), EUT 1, SW MWD S V01.E1**

01:43:24 PM 04/29/2024

Plot 2: Max. PEAK E.I.R.P (FSW85), EUT 3, SW MWD S V01.E1

03:47:26 PM 07/10/2024

Plot 3: Max. PEAK E.I.R.P (FSW85), EUT 1, SW MWD S V01.E8



Verdict: Compliant

13.3 Peak transmitter conducted output power

Description:

Measurement or calculation of the transmitter conducted output power.

Limits and provisions:

Selection of applicable rule parts: see 12

Applicable limits of peak transmitter conducted output power		
Applicable	Rule part	Limit peak transmitter conducted output power
<input type="checkbox"/>	15.255(c)(2)	-10 dBm
<input type="checkbox"/>	15.255(e)(1)	500 mW
<input type="checkbox"/>	15.255(e)(2)	500 mW * (EBW _{6dB} /100 MHz)
<input checked="" type="checkbox"/>	other	none

Note:

- EBW_{6dB} (6 dB emission bandwidth): see chapter 13.1

Results:

EUT	Mode	Test condition	Peak E.I.R.P.	Gain of EUT antenna G _{EUT}	Peak transmitter conducted output power	Limit Peak transmitter conducted output power
-/-	-/-	T _{nom} / V _{nom}	-/-	-/-	-/-	-/-

Note:

- Peak transmitter conducted output power = Peak E.I.R.P – Gain of EUT antenna G_{EUT}
- Peak EIRP: see chapter 13.2

Verdict: Not applicable

13.4 Time domain requirements: Continuous transmitter off-times & transmit duty cycle

Description:

Measurement of the time domain parameter.

Limits and provisions:

Selection of applicable rule parts: see 12

Applicable time domain requirements		
Applicable	Rule part	Time domain requirement
<input type="checkbox"/>	15.255(b)(3)	sum of continuous transmitter off-times of at least two milliseconds shall equal at least 16.5 milliseconds within any contiguous interval of 33 milliseconds
<input type="checkbox"/>	15.255(c)(2)(ii)	Peak EIRP \leq 3 dBm: none
		Peak EIRP \leq 20 dBm: sum of continuous transmitter off-times of at least two milliseconds equals at least 16.5 milliseconds within any contiguous interval of 33 milliseconds
<input type="checkbox"/>	15.255(c)(2)(iii)(A)	sum of continuous transmitter off-times of at least two milliseconds shall equal at least 25.5 milliseconds within any contiguous interval of 33 milliseconds
<input checked="" type="checkbox"/>	15.255(c)(2)(iii)(B)	sum of continuous transmitter off-times of at least two milliseconds shall equal at least 16.5 milliseconds within any contiguous interval of 33 milliseconds
<input type="checkbox"/>	15.255(c)(3)	maximum pulse duration of 6 ns; transmit duty cycle shall not exceed 10% during any 0.3 μ s time window
<input type="checkbox"/>	other	none

Note:


- Continuous transmitter off-times:
Off-times are only taken into account if they are larger than the specified minimum value (e.g. 2 ms). Off-times smaller than the specified minimum value are not considered when checking the specified limit (e.g. "at least 25.5 ms within any contiguous interval of 33 ms").



Measurement:

Measurement parameter	
Detector:	Pos-Peak (RF-Detector)
Video bandwidth:	Video bandwidth:

Measurement results:

EUT	SW	Test condition	Maximum sum of continuous transmitter off-times of at least two milliseconds within any contiguous interval of 33 milliseconds.	
1	MWD S V01.E1	$T_{\text{nom}} / V_{\text{nom}}$	Measured value	
			29 ms	16.5 ms

Verdict: Compliant
Plot 4: Continuous transmitter off-time within interval of 33 ms, EUT1, MWD S V01.E1


Plot 5: Interval of 33 ms, EUT1, MWD S V01.E1**Plot 6: Burst duration within interval of 33 ms, EUT1, MWD S V01.E1**

13.5 Spurious emissions radiated

Description:

Measurement of the radiated spurious emissions.

Limits and provisions:

Selection of applicable rule parts: see 12

47CFR Part 15.209(a)		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 – 960	200	3
Above 960	500	3
47 CFR 15.255(d)		
Frequency (GHz)	Power density [pW/cm ²]	Equivalent isotropically radiated power: EIRP [dBm]
Below 40	See §15.209	-/-
40 - 200	90 @ distance of 3 m	-10

The power density of any emissions outside the 57-71 GHz band shall consist solely of spurious emissions.

The levels of the spurious emissions shall not exceed the level of the fundamental emission.

47 CFR 15.255(i)(2)
Compliance measurements of frequency-agile field disturbance sensors/radars shall be performed with any related frequency sweep, step, or hop function activated.

47 CFR 15.33(a)(3)
If the intentional radiator operates at or above 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 200 GHz, whichever is lower, unless specified otherwise elsewhere in the rules.

Limit conversion (ANSI C63.10-2020 9.2.3):

$$\text{EIRP[dBm]} = 10 \times \log(4 \times \pi \times d^2 \times \text{PD[W/m}^2\text{]})$$

- Power density at the distance specified by the limit: PD [W/m²]
- Equivalent isotropically radiated power: EIRP [dBm]
- Distance at which the power density limit is specified: d [m]

According to this formula, an emission limit of PD = 90 pW/cm² at a distance of d = 3 m corresponds to an equivalent isotropically radiated power of EIRP = -10 dBm.

Measurement:

Measurement parameter	
Detector:	Quasi Peak / Pos-Peak / RMS
Resolution bandwidth:	F < 1 GHz: 100 kHz F > 1 GHz: 1 MHz
Video bandwidth:	F < 1 GHz: 300 kHz F > 1 GHz: 3 MHz
Trace-Mode:	Max Hold


Measurement results:

EUT	SW	Frequency [GHz]	Detector	Bandwidth [MHz]	Level	Limit	Margin [dB]
		-/-	-/-	-/-	-/-	-/-	-/-


Please refer to the following plots for more information on the level of spurious emissions

Verdict: Compliant

Plot 7: 9 kHz – 30 MHz, EUT1, MWD S V01.E1




Plot 8: 30 MHz – 1GHz, EUT1, MWD S V01.E1




Frequency (MHz)	QuasiPeak (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
33.530	6.55	30.0	23.5	1000	120.0	109.0	V	14	13
47.284	4.22	30.0	25.8	1000	120.0	200.0	V	24	15
64.344	5.24	30.0	24.8	1000	120.0	185.0	V	10	12
400.012	31.30	36.0	4.7	1000	120.0	203.0	H	90	18
733.055	16.63	36.0	19.4	1000	120.0	103.0	V	45	23
900.907	19.07	36.0	16.9	1000	120.0	400.0	H	90	25


Plot 9: 30 MHz – 1GHz, EUT1, MWD S V01.E8





Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
32.056	9.82	30.0	20.2	1000	120.0	104.0	V	129	13
44.263	8.88	30.0	21.1	1000	120.0	186.0	V	64	15
62.709	4.87	30.0	25.1	1000	120.0	400.0	V	45	13
399.992	23.51	36.0	12.5	1000	120.0	400.0	V	315	18
726.693	10.97	36.0	25.0	1000	120.0	400.0	V	79	23
894.169	18.37	36.0	17.6	1000	120.0	132.0	H	16	25


Plot 10: 1GHz – 18 GHz, EUT1, MWD S V01.E1

EUT	SW	Frequency [GHz]	Detector	Bandwidth [MHz]	Level [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
1	MWD S V01.E1	14.4	Peak	1	56.2	74	17.8
1	MWD S V01.E1	14.4	Average	1	51.9	54	2.1



Plot 11: 1GHz – 18 GHz, EUT1, MWD S V01.E8


EUT	SW	Frequency [GHz]	Detector	Bandwidth [MHz]	Level [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
1	MWD S V01.E8	14.4	Peak	1	53.8	74	20.2
1	MWD S V01.E8	14.4	Average	1	44.4	54	9.6

Plot 12: 18 GHz – 33 GHz, EUT1, MWD S V01.E1

Plot 13: 18 GHz – 33 GHz, EUT1, MWD S V01.E1, detail


Plot 14: 18 GHz – 33 GHz, EUT1, MWD S V01.E1, detail zero


EUT	SW	Frequency [GHz]	Detector	Bandwidth [MHz]	Level [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
1	MWD S V01.E1	28.8	Peak	1	55.9	74	18.1
1	MWD S V01.E1	28.8	Average	1	53.8	54	0.2

Plot 15: 18 GHz – 33 GHz, EUT1, MWD S V01.E8

Plot 16: 18 GHz – 33 GHz, EUT1, MWD S V01.E8, detail



Plot 17: 18 GHz – 33 GHz, EUT1, MWD S V01.E8, detail zero

EUT	SW	Frequency [GHz]	Detector	Bandwidth [MHz]	Level [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
1	MWD S V01.E8	28.8	Peak	1	51.6	74	22.4
1	MWD S V01.E8	28.8	Average	1	47.0	54	7


Plot 18: 33 GHz – 40 GHz, EUT1, MWD S V01.E1




Plot 19: 40 GHz – 50 GHz, EUT1, MWD S V01.E1




Plot 20: 50 GHz – 75 GHz, EUT1, MWD S V01.E1

Plot 21: 75 GHz – 110 GHz, EUT1, MWD S V01.E1


Plot 22: 110 GHz – 140 GHz, EUT1, MWD S V01.E1



Plot 23: 140 GHz – 200 GHz, EUT1, MWD S V01.E1



13.6 Conducted emissions < 30 MHz (AC power line)

Description:

Measurement of the conducted spurious emissions in transmit mode below 30 MHz. Both power lines, phase and neutral line, are measured. Found peaks are re-measured with average and quasi peak detection to show compliance to the limits.

Limits and provisions:


Selection of applicable rule parts: see 12

47 CFR 15.207(a)		
Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50


* Decreases with the logarithm of the frequency

Measurement:

Parameter	
Detector:	Peak - Quasi Peak / Average
Sweep time:	Auto
Video bandwidth:	F < 150 kHz: 200 Hz F > 150 kHz: 9 kHz
Resolution bandwidth:	F < 150 kHz: 1 kHz F > 150 kHz: 100 kHz
Span:	9 kHz to 30 MHz
Trace-Mode:	Max Hold

Measurement results:
Plot 24: Phase line


Frequency	Quasi peak level	Margin quasi peak	Limit QP	Average level	Margin average	Limit AV
MHz	dB μ V	dB	dB μ V	dB μ V	dB	dB μ V
0.164925	38.96	26.26	65.212	15.09	40.48	55.574
1.385044	36.52	19.48	56.000	5.30	40.70	46.000
1.672350	35.60	20.40	56.000	5.50	40.50	46.000
1.896225	33.72	22.28	56.000	5.36	40.64	46.000
2.176069	30.17	25.83	56.000	3.53	42.47	46.000
2.426063	30.47	25.53	56.000	4.37	41.63	46.000
2.724563	28.41	27.59	56.000	3.62	42.38	46.000
5.120025	25.11	34.89	60.000	3.11	46.89	50.000

Plot 25: Neutral line


Frequency	Quasi peak level	Margin quasi peak	Limit QP	Average level	Margin Average	Limit AV
MHz	dB μ V	dB	dB μ V	dB μ V	dB	dB μ V
0.224625	41.99	20.66	62.646	15.13	38.73	53.868
1.101469	27.87	28.13	56.000	2.50	43.50	46.000
1.422356	36.23	19.77	56.000	5.18	40.82	46.000
1.679812	34.43	21.57	56.000	4.90	41.10	46.000
1.933537	33.75	22.25	56.000	6.07	39.93	46.000
2.149950	30.48	25.52	56.000	3.41	42.59	46.000
2.440987	30.44	25.56	56.000	4.60	41.40	46.000
5.105100	25.28	34.72	60.000	3.33	46.67	50.000

Verdict: Compliant

14 Glossary

EUT	Equipment under test
DUT	Device under test
UUT	Unit under test
GUE	GNSS User Equipment
ETSI	European Telecommunications Standards Institute
EN	European Standard
FCC	Federal Communications Commission
FCC ID	Company Identifier at FCC
IC	Industry Canada
PMN	Product marketing name
HMN	Host marketing name
HVIN	Hardware version identification number
FVIN	Firmware version identification number
EMC	Electromagnetic Compatibility
HW	Hardware
SW	Software
Inv. No.	Inventory number
S/N or SN	Serial number
C	Compliant
NC	Not compliant
NA	Not applicable
NP	Not performed
PP	Positive peak
QP	Quasi peak
AVG	Average
OC	Operating channel
OCW	Operating channel bandwidth
OBW	Occupied bandwidth
OOB	Out of band
DFS	Dynamic frequency selection
CAC	Channel availability check
OP	Occupancy period
NOP	Non occupancy period
DC	Duty cycle
PER	Packet error rate
CW	Clean wave
MC	Modulated carrier
WLAN	Wireless local area network
RLAN	Radio local area network
DSSS	Dynamic sequence spread spectrum
OFDM	Orthogonal frequency division multiplexing
FHSS	Frequency hopping spread spectrum
GNSS	Global Navigation Satellite System
C/N₀	Carrier to noise-density ratio, expressed in dB-Hz

15 Document history

Version	Applied changes	Date of release
R01	Initial release	2024-07-26
R02	HMN and FVIN information removed from the report	2024-09-04

END OF TEST REPORT