

Radiated Emissions Test Result Data**Base and Handset, 30 MHz to 25GHz, 3 meters**

INDICATED		TABLE	ANTENNA		CORRECTION FACTOR			CORRECTED AMPLITUDE	FCC 15 Subpart C	
Frequency MHz	Ampl. dBμV/m	Angle Degree	Height Meter	Polar H/ V	Antenna dBμV/m	Cable dB	Amp. dB	Corr. Ampl. dBμV/m	Limit dBμV/m	Margin dB
359.40	31.9	90	1.2	h	15.5	4.3	25.0	26.7	46	-19.3
61.76	33.8	90	1.2	h	9.7	1.3	25.0	19.8	40	-20.2
238.50	37.5	110	1.5	v	12.0	1.2	25.0	25.7	46	-20.3
334.70	32.5	270	1.5	v	15.0	2.6	25.0	25.1	46	-20.9
452.55	28.7	0	1.5	v	17.8	3.2	25.0	24.7	46	-21.3
359.40	29.7	130	1.5	v	15.5	4.3	25.0	24.5	46	-21.5
50.13	31.2	260	1.2	v	10.5	1.0	25.0	17.7	40	-22.3
238.50	34.6	150	1.5	h	12.0	1.2	25.0	22.8	46	-23.2
124.25	30.9	0	1.5	v	12.1	2.2	25.0	20.2	43.5	-23.3
61.76	30.4	60	1.0	v	9.7	1.3	25.0	16.4	40	-23.6
50.13	29.4	310	1.0	h	10.5	1.0	25.0	15.9	40	-24.1
334.70	29.2	310	1.2	h	15.0	2.6	25.0	21.8	46	-24.2
124.25	28.6	30	1.2	h	12.1	2.2	25.0	17.9	43.5	-25.6