

RF EXPOSURE

FCCID : PJZW550CA

1. FCC Regulation

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this Chapter.

Limits for Maximum Permissible Exposure: RF exposure is calculated.

Frequency Range	Electric Field Strength [V/m]	Magnetic Field Strength [A/m]	Power Density [mW/cm ²]	Averaging Time [minute]
Limits for General Population / Uncontrolled Exposure				
0.3 ~ 1.34	614	1.63	*(100)	30
1.34 ~ 30	824/f	2.19/f	*(180/f ²)	30
30 ~ 300	27.5	0.073	0.2	30
300 ~ 1 500	/	/	f/1 500	30
1 500 ~ 15 000	/	/	1	30

f=frequency in MHz, *= plane-wave equivalent power density

MPE (Maximum Permissible Exposure) Prediction

Predication of MPE limit at a given distance: Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2 \quad (\Rightarrow R = \sqrt{PG/4\pi S})$$

S = power density [mW/cm²]

P = Power input to antenna [mW]

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna [cm]

2. RF Exposure Compliance Issue

The information should be included in the user's manual:

This appliance and its antenna must not be co-located or operation in conjunction with any other antenna or transmitter. A minimum separation distance of 20 cm must be maintained between the antenna and the person for this appliance to satisfy the RF exposure requirements.

MPE Calculations : WLAN2.4G

- Frequency Range : 2412 MHz ~ 2462 MHz
- Measured RF Maximum Output Power : 28.31 dBm
- Target Power & Tolerance 28.00 dBm & $\pm$ 1.00 dB
(Maximum : 29.00 dBm & Minimum : 27.00 dBm)
- Maximum Peak Antenna Gain : 2.90 dBi
- Maximum Output Power for the Calculation : 29.00 dBm

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the
The MPE Calculations for this exposure is shown below.

- EIRP = P + G = <u>29.00</u> dBm + <u>2.90</u> dBi = <u>31.90</u> dBm = <u>1548.82</u> mW	- NOTE P : Max tuneup Power (dBm) G : Maximum Peak Antenna Gain (dBi)
--	--

Power Density at the specific separation

- S = EIRP / (4 X R²π) = 1548.82 / (4 X ^2 X π) = <u>0.308 127</u> mW/cm² (Limit : 1.00)	- NOTE S : Maximum Power Density (mW/cm²) EIRP : Equivalent Isotropic Radiated Power (mW) R : Distance to the center of the radiation of the antenna (<u>20</u> cm)
--	--

MPE Calculations : WLAN5G

- Frequency Range : 5180 MHz ~ 5825 MHz
- Measured RF Maximum Output Power : 25.23 dBm
- Target Power & Tolerance 25.00 dBm & $\pm$ 1.00 dB
(Maximum : 26.00 dBm & Minimum : 24.00 dBm)
- Maximum Peak Antenna Gain : 3.90 dBi
- Maximum Output Power for the Calculation : 26.00 dBm

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the
The MPE Calculations for this exposure is shown below.

- EIRP = P + G = <u>26.00</u> dBm + <u>3.90</u> dBi = <u>29.90</u> dBm = <u>977.24</u> mW	- NOTE P : Max tuneup Power (dBm) G : Maximum Peak Antenna Gain (dBi)
---	--

Power Density at the specific separation

- S = EIRP / (4 X R²π) = 977.24 / (4 X ^2 X π) = <u>0.194 415</u> mW/cm² (Limit : 1.00)	- NOTE S : Maximum Power Density (mW/cm²) EIRP : Equivalent Isotropic Radiated Power (mW) R : Distance to the center of the radiation of the antenna (<u>20</u> cm)
---	--

MPE Calculations : WLAN2.4G + WLAN5G

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the
The MPE Calculations for this exposure is shown below.

simultaneous MPE for Wi-Fi

WLAN2.4G + WLAN5G

- Total (%) = $[\text{WLAN2.4G Result(mW/cm}^2\text{)} / \text{Limit(mW/cm}^2\text{)}] +$ $[\text{WLAN5G Result(mW/cm}^2\text{)} / \text{Limit(mW/cm}^2\text{)}] * 100$ $= [\underline{0.308\ 127} / 1] +$ $[\underline{0.194\ 415} / 1] * 100$ $= \underline{50.254} \%$	- NOTE WLAN2.4G + WLAN5G WLAN2.4G = <u>0.308 127</u> mW/cm² WLAN5G = <u>0.194 415</u> mW/cm² Distance to the center of the radiation of the antenna (<u>20</u> cm) Limit : ≤ 100 %
--	--