



FCC Radio Test Report

FCC ID: PKNCM-198

This report concerns (check one): Original Grant Class II Change

Issued Date : Jan. 28, 2013
Project No. : 1301C092
Equipment : Optical 2.4GHz Wireless Mouse
Model Name : CM-198; OM4750W; OM6750W
Applicant : Zhuoheng Electronics Co., Limited
Address : No.8.Lane 5.shangnan Road,The 5Th Industrial Area,
Nance,Humen Town, Dongguan, China

Tested by:


Neutron Engineering Inc. EMC Laboratory

Date of Receipt: Jan. 10, 2013


Date of Test:

Jan. 10, 2013 ~ Jan. 28, 2013

Testing Engineer :


(David Mao)

Technical Manager :


(Leo Hung)

Authorized Signatory :


(Steven Lu)

Neutron Engineering Inc.

No.3,Jinshagang 1st Road, ShiXia, Dalang
Town, Dong Guan, China.
TEL : (0769) 8318-3000 FAX : (0769) 8319-6000



Declaration

Neutron represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with the standards traceable to National Measurement Laboratory (**NML**) of **CHINA**, or National Institute of Standards and Technology (**NIST**) of **U.S.A**.

Neutron's reports apply only to the specific samples tested under conditions. It is manufacturer's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **Neutron** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **Neutron** issued reports.

Neutron's reports must not be used by the client to claim product endorsement by the authorities or any agency of the Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **Neutron-self**, extracts from the test report shall not be reproduced except in full with **Neutron**'s authorized written approval.

Neutron's laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.



Table of Contents	Page
1 . CERTIFICATION	6
2 . SUMMARY OF TEST RESULTS	7
2.1 TEST FACILITY	8
2.2 MEASUREMENT UNCERTAINTY	8
3 . GENERAL INFORMATION	9
3.1 GENERAL DESCRIPTION OF EUT	9
3.2 DESCRIPTION OF TEST MODES	11
3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	11
3.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	12
3.5 DESCRIPTION OF SUPPORT UNITS	13
4 . EMC EMISSION TEST	14
4.1 CONDUCTED EMISSION MEASUREMENT	14
4.1.1 POWER LINE CONDUCTED EMISSION LIMITS	14
4.1.2 MEASUREMENT INSTRUMENTS LIST AND SETTING	14
4.1.3 TEST PROCEDURE	15
4.1.4 DEVIATION FROM TEST STANDARD	15
4.1.5 TEST SETUP	15
4.1.6 EUT OPERATING CONDITIONS	15
4.1.7 TEST RESULTS	16
4.2 RADIATED EMISSION MEASUREMENT	17
4.2.1 RADIATED EMISSION LIMITS	17
4.2.2 MEASUREMENT INSTRUMENTS LIST ANS SETTING	18
4.2.3 TEST PROCEDURE	20
4.2.4 DEVIATION FROM TEST STANDARD	20
4.2.5 TEST SETUP	21
4.2.6 EUT OPERATING CONDITIONS	22
4.2.7 TEST RESULTS (BELOW 30MHZ)	23
4.2.8 TEST RESULTS (BETWEEN30 – 1000 MHZ)	24
4.2.9 TEST RESULTS (ABOVE 1000 MHZ)	31
5 . NUMBER OF HOPPING CHANNEL	43
5.1 APPLIED PROCEDURES / LIMIT	43
5.1.1 MEASUREMENT INSTRUMENTS LIST AND SETTING	43
5.1.2 TEST PROCEDURE	43
5.1.3 DEVIATION FROM STANDARD	43
5.1.4 TEST SETUP	43
5.1.5 EUT OPERATION CONDITIONS	43
5.1.6 TEST RESULTS	44



Table of Contents

	Page
6 . AVERAGE TIME OF OCCUPANCY	45
6.1 APPLIED PROCEDURES / LIMIT	45
6.1.1 MEASUREMENT INSTRUMENTS LIST	45
6.1.2 TEST PROCEDURE	45
6.1.3. TEST SETUP LAYOUT	45
6.1.4. TEST DEVIATION	45
6.1.5. EUT OPERATION DURING TEST	45
6.1.6. TEST RESULTS	46
7 . HOPPING CHANNEL SEPARATION MEASUREMENT	48
7.1 APPLIED PROCEDURES / LIMIT	48
7.1.1 MEASUREMENT INSTRUMENTS LIST AND SETTING	48
7.1.2 TEST PROCEDURE	48
7.1.3 DEVIATION FROM STANDARD	48
7.1.4 TEST SETUP	48
7.1.5 EUT OPERATION CONDITIONS	48
7.1.6 TEST RESULTS	49
8 . BANDWIDTH TEST	50
8.1 APPLIED PROCEDURES / LIMIT	50
8.1.1 MEASUREMENT INSTRUMENTS LIST AND SETTING	50
8.1.2 TEST PROCEDURE	50
8.1.3 DEVIATION FROM STANDARD	50
8.1.4 TEST SETUP	50
8.1.5 EUT OPERATION CONDITIONS	50
8.1.6 TEST RESULTS	51
9 . PEAK OUTPUT POWER TEST	53
9.1 APPLIED PROCEDURES / LIMIT	53
9.1.1 MEASUREMENT INSTRUMENTS LIST AND SETTING	53
9.1.2 TEST PROCEDURE	53
9.1.3 DEVIATION FROM STANDARD	53
9.1.4 TEST SETUP	53
9.1.5 EUT OPERATION CONDITIONS	53
9.1.6 TEST RESULTS	54
10 . ANTENNA CONDUCTED SPURIOUS EMISSION	55
10.1 APPLIED PROCEDURES / LIMIT	55
10.1.1 MEASUREMENT INSTRUMENTS LIST AND SETTING	55
10.1.2 TEST PROCEDURE	55
10.1.3 DEVIATION FROM STANDARD	55
10.1.4 TEST SETUP	55
10.1.5 EUT OPERATION CONDITIONS	55
10.1.6 TEST RESULTS	56



Table of Contents

	Page
11 . EUT PHOTOS	62



1. CERTIFICATION

Equipment : Optical 2.4GHz Wireless Mouse
Brand Name : NA
Model Name : CM-198; OM4750W; OM6750W
Applicant : Zhuoheng Electronics Co., Limited
Date of Test : Jan. 10, 2013 ~ Jan. 28, 2013
Test Item : ENGINEERING SAMPLE
Standards : FCC Part15, Subpart C(15.247) / ANSI C63.4 : 2009
FCC Public Notice DA 00-705, March 30, 2000.

The above equipment has been tested and found compliance with the requirement of the relative standards by Neutron Engineering Inc. EMC Laboratory.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. NEI-FCCP-1-1301C092) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of NVLAP and TAF according to the ISO-17025 quality assessment standard and technical standard(s).



2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

APPLIED STANDARD: 47 CFR Part 15, Subpart C			
Standard Section 47 CFR Part 15	Test Item	Judgment	Remark
15.207	Conducted Emission	-	N/A
15.247(d)	Antenna conducted Spurious Emission	PASS	
15.247 (a)(1)	Hopping Channel Separation	PASS	
15.247 (a)(2)	20dB Bandwidth	PASS	
15.247 (b)(1)	Peak Output Power	PASS	
15.247(d) 15.209	Radiated Spurious Emission	PASS	
15.247 (a)(1)(iii)	Number of Hopping Frequency	PASS	
15.247 (a)(1)(iii)	Dwell Time	PASS	
15.205	Restricted Bands	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this test report.

(2) According to FCC Public Notice DA 00-705, March 30, 2000.



2.1 TEST FACILITY

The test facilities used to collect the test data in this report is **DG-CB03** at the location of No.3,Jinshagang 1st Road, ShiXia, Dalang Town, Dong Guan, China.523792
Neutron's test firm number for FCC 319330

2.2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

The reported uncertainty of measurement $y \pm U$, where expended uncertainty **U** is based on a standard uncertainty multiplied by a coverage factor of **k=2** , providing a level of confidence of approximately **95 %** .

A. Conducted Measurement :

Test Site	Method	Measurement Frequency Range	U , (dB)	NOTE
DG-C02	CISPR	150 KHz ~ 30MHz	1.94	

B. Radiated Measurement :

Test Site	Method	Measurement Frequency Range	Ant. H / V	U , (dB)	NOTE
DG-CB03	CISPR	30MHz ~ 200MHz	V	3.82	
		30MHz ~ 200MHz	H	3.60	
		200MHz ~ 1,000MHz	V	3.86	
		200MHz ~ 1,000MHz	H	3.94	
		1GHz~18GHz	V	3.12	
		1GHz~18GHz	H	3.68	
		18GHz~40GHz	V	4.15	
		18GHz~40GHz	H	4.14	



3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Equipment	Optical 2.4GHz Wireless Mouse														
Brand Name	NA														
Model Name	CM-198; OM4750W; OM6750W														
Model Difference	All models are identical, except model name differ due to marketing purpose.														
Product Description	<p>The EUT is a Optical 2.4GHz Wireless Mouse.</p> <table border="1"><tr><td>Operation Frequency:</td><td>2402~2480MHz</td></tr><tr><td>Modulation Technology:</td><td>GFSK</td></tr><tr><td>Bit Rate of Transmitter:</td><td>1Mbps</td></tr><tr><td>Number Of Channel</td><td>16 CH, Please see note 2. (Page 9)</td></tr><tr><td>Antenna Designation:</td><td>Please see note 3. (Page 9)</td></tr><tr><td>Antenna Gain(Peak)</td><td></td></tr><tr><td>Output Power:</td><td>-11.51dBm (Max)</td></tr></table> <p>Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.</p>	Operation Frequency:	2402~2480MHz	Modulation Technology:	GFSK	Bit Rate of Transmitter:	1Mbps	Number Of Channel	16 CH, Please see note 2. (Page 9)	Antenna Designation:	Please see note 3. (Page 9)	Antenna Gain(Peak)		Output Power:	-11.51dBm (Max)
Operation Frequency:	2402~2480MHz														
Modulation Technology:	GFSK														
Bit Rate of Transmitter:	1Mbps														
Number Of Channel	16 CH, Please see note 2. (Page 9)														
Antenna Designation:	Please see note 3. (Page 9)														
Antenna Gain(Peak)															
Output Power:	-11.51dBm (Max)														
Power Source	DC voltage supplied from 2*AA battery														
Power Rating	DC 3V														
Connecting I/O Port(s)	Please refer to the User's Manual														

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



2

... Channel List

Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2480
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

Note: 16 channels hops per sequence at random
3 .Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	N/A	N/A	Printed	N/A	0



3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	TX Mode NOTE (1)

The EUT system operated these modes were found to be the worst case during the pre-scanning test as following:

For Conducted Emission	
Final Test Mode	Description
-	" N/A" denotes test is not applicable in this test report.

For Radiated Emission	
Final Test Mode	Description
Mode 1	TX Mode NOTE (1)

Note:

- (1) The measurements are performed at the high, middle, low available channels.


3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS

Test software version	N/A		
Frequency	2402MHz	2442MHz	2480MHz
Parameters-1Mbps	N/A	N/A	N/A



3.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



**3.5 DESCRIPTION OF SUPPORT UNITS**

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.	Note
E-1	Optical 2.4GHz Wireless Mouse	N/A	CM-198	PKNCM-198	N/A	EUT

Item	Shielded Type	Ferrite Core	Length	Note
-	-	-	-	-

Note:

- (1) For detachable type I/O cable should be specified the length in m in『Length』column.



4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
	Quasi-peak	Average	Quasi-peak	Average	
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR

0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

4.1.2 MEASUREMENT INSTRUMENTS LIST AND SETTING

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	LISN	EMCO	3816/2	00052765	May.04.2013
2	LISN	R&S	ENV216	100087	May.04.2013
3	Test Cable	N/A	C_17	N/A	Mar.28.2013
4	EMI TEST RECEIVER	R&S	ESCS30	826547/022	May.04.2013
5	50Ω Terminator	SHX	TF2-3G-A	08122902	May.04.2013

Remark: "N/A" denotes no model name, serial no. or calibration specified.

All calibration period of Equipment List is One Year.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz




4.1.3 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

4.1.6 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

The EUT is continued Transmitter/Receive data or Hopping on mode.



4.1.7 TEST RESULTS

Remark

(1) All readings are QP Mode value unless otherwise stated AVG in column of [¶]Note . If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform . In this case, a “ * ” marked in AVG Mode column of Interference Voltage Measured .

(2) Measuring frequency range from 150KHz to 30MHz.

E.U.T :	Optical 2.4GHz Wireless Mouse	Model Name :	CM-198
Temperature :	-	Relative Humidity :	-
Pressure :	-	Test Power :	-
Test Mode :	N/A	Phase:	-

Note: This EUT is powered by battery only, so this test item is not applicable.



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	(dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower

**4.2.2 MEASUREMENT INSTRUMENTS LIST AND SETTING**

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Antenna	Schwarzbeck	VULB9160	9160-3232	May.25.2013
2	Amplifier	HP	8447D	2944A09673	May.04.2013
3	Test Receiver	R&S	ESCI	100382	May.04.2013
4	Test Cable	N/A	C-01_CB03	N/A	Jul.01.2013
5	Antenna	ETS	3115	00075789	May.25.2013
6	Amplifier	Agilent	8449B	3008A02274	May.04.2013
7	Spectrum	Agilent	E4408B	US39240143	Nov.25.2013
8	Test Cable	HUBER+SUH NER	C-45	N/A	May.02.2013
9	Controller	CT	SC100	N/A	N/A
10	Active Loop Antenna	R&S	HFH2-Z2	830749/020	May.04.2013
11	Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170319	Oct.12.2013
12	Horn Antenna	EMCO	3115	9605-4803	May.25.2013

Remark: "N/A" denotes no model name, serial no. or calibration specified.

All calibration period of Equipment List is One Year.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~90kHz for PK/AVG detector
Start ~ Stop Frequency	90kHz~110kHz for QP detector
Start ~ Stop Frequency	110kHz~490kHz for PK/AVG detector
Start ~ Stop Frequency	490kHz~30MHz for QP detector
Start ~ Stop Frequency	30MHz~1000MHz for QP detector




DUTY CYCLE: TX 2402MHz

Dwell time=ON/ON+OFF=0.56/2.6

Dwell time: 12.5%

AV=PK+20 log(Dwell time)

AV=PK-13.34





4.2.3 TEST PROCEDURE


- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1GHz)
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.2.4 DEVIATION FROM TEST STANDARD


No deviation

4.2.5 TEST SETUP

(A) Radiated Emission Test Set-Up Frequency Below 1 GHz




(B) Radiated Emission Test Set-Up Frequency Above 1 GHz





(C) For radiated emissions below 30MHz



4.2.6 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.



4.2.7 TEST RESULTS (BELOW 30MHZ)

EUT :	Optical 2.4GHz Wireless Mouse	Model Name :	CM-198
Temperature :	26 °C	Relative Humidity :	53 %
Pressure :	1010 hPa	Test Voltage :	DC 3V
Test Mode :	TX 2402MHz		

Freq. (MHz)	Ant. 0°/90°	Reading(RA) (dBuV)	Corr.Factor(CF) (dB)	Measured(FS) (dBuV/m)	Limits(QP) (dBuV/m)	Margin (dB)	Note
0.00951	0°	20.22	24.30	44.52	128.04	-83.52	AV
0.00951	0°	22.35	24.30	46.65	148.04	-101.39	PK
0.02354	0°	18.33	24.08	42.41	120.17	-77.76	AV
0.02354	0°	21.42	24.08	45.50	140.17	-94.67	PK
0.03748	0°	18.27	23.19	41.46	116.13	-74.67	AV
0.03748	0°	22.52	23.19	45.71	136.13	-90.42	PK
0.0675	0°	19.37	22.05	41.42	111.02	-69.60	AV
0.0675	0°	24.18	22.05	46.23	131.02	-84.79	PK
0.2559	0°	21.40	20.39	41.79	99.44	-57.65	AV
0.2559	0°	23.69	20.39	44.08	119.44	-75.36	PK
1.2568	0°	24.53	19.57	44.10	65.62	-21.52	QP

Freq. (MHz)	Ant. 0°/90°	Reading(RA) (dBuV)	Corr.Factor(CF) (dB)	Measured(FS) (dBuV/m)	Limits(QP) (dBuV/m)	Margin (dB)	Note
0.00975	90°	17.24	24.30	41.54	127.82	-86.28	AV
0.00975	90°	21.61	24.30	45.91	147.82	-101.91	PK
0.02573	90°	15.37	23.94	39.31	119.40	-80.09	AV
0.02573	90°	19.58	23.94	43.52	139.40	-95.88	PK
0.03492	90°	18.49	23.36	41.85	116.74	-74.89	AV
0.03492	90°	22.54	23.36	45.90	136.74	-90.84	PK
0.06472	90°	20.68	22.11	42.79	111.38	-68.59	AV
0.06472	90°	24.52	22.11	46.63	131.38	-84.75	PK
0.2358	90°	21.31	20.43	41.74	100.15	-58.41	AV
0.2358	90°	23.68	20.43	44.11	120.15	-76.04	PK
1.2533	90°	23.75	19.57	43.32	65.64	-22.32	QP

Remark :

- (1) The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported .
- (2) Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB); .
- (3) Limit line = specific limits (dBuV) + distance extrapolation factor. .




4.2.8 TEST RESULTS (BETWEEN30 – 1000 MHZ)

Remark :

- (1) Reading in which marked as QP or Peak means measurements by using are Quasi-Peak Mode or Peak Mode with Detector BW=120KHz ; SPA setting in RBW=120KHz, VBW =120KHz, Swp. Time = 0.3 sec./MHz .
- (2) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (3) Measuring frequency range from 30MHz to 1000MHz .
- (4) If the peak scan value lower limit more than 20dB, then this signal data does not show in table .




EUT :	Optical 2.4GHz Wireless Mouse	Model Name :	CM-198
Temperature :	25 °C	Relative Humidity :	58 %
Pressure :	1010 hPa	Test Voltage :	DC 3V
Test Mode :	TX Mode 2402MHz	Polarization:	Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector Comment
1		66.3750	45.36	-17.81	27.55	40.00	-12.45	peak
2		112.4500	46.00	-18.34	27.66	43.50	-15.84	peak
3		384.0500	35.23	-9.60	25.63	46.00	-20.37	peak
4		524.7000	35.35	-6.44	28.91	46.00	-17.09	peak
5		730.8250	36.72	-2.80	33.92	46.00	-12.08	peak
6	*	873.9000	34.69	-0.50	34.19	46.00	-11.81	peak




EUT :	Optical 2.4GHz Wireless Mouse	Model Name :	CM-198
Temperature :	25 °C	Relative Humidity :	58 %
Pressure :	1010 hPa	Test Voltage :	DC 3V
Test Mode :	TX Mode 2402MHz	Polarization:	Horizontal



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
1		80.9250	42.48	-19.07	23.41	40.00	-16.59	peak	
2		165.8000	45.63	-17.45	28.18	43.50	-15.32	peak	
3		337.9750	38.50	-11.14	27.36	46.00	-18.64	peak	
4		466.5000	37.84	-7.87	29.97	46.00	-16.03	peak	
5		650.8000	34.40	-3.34	31.06	46.00	-14.94	peak	
6	*	835.1000	33.27	-1.17	32.10	46.00	-13.90	peak	




EUT :	Optical 2.4GHz Wireless Mouse	Model Name :	CM-198
Temperature :	25 °C	Relative Humidity :	58 %
Pressure :	1010 hPa	Test Voltage :	DC 3V
Test Mode :	TX Mode 2442MHz	Polarization:	Vertical



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
1		66.3750	44.36	-17.81	26.55	40.00	-13.45	peak	
2		112.4500	44.00	-18.34	25.66	43.50	-17.84	peak	
3		466.5000	36.34	-7.87	28.47	46.00	-17.53	peak	
4		604.7250	34.43	-4.18	30.25	46.00	-15.75	peak	
5		738.1000	35.62	-2.71	32.91	46.00	-13.09	peak	
6	*	864.2000	34.40	-0.65	33.75	46.00	-12.25	peak	




EUT :	Optical 2.4GHz Wireless Mouse	Model Name :	CM-198
Temperature :	25 °C	Relative Humidity :	58 %
Pressure :	1010 hPa	Test Voltage :	DC 3V
Test Mode :	TX Mode 2442MHz	Polarization:	Horizontal



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
1		78.5000	42.73	-18.99	23.74	40.00	-16.26	peak	
2		168.2250	44.02	-17.35	26.67	43.50	-16.83	peak	
3		226.4250	42.73	-15.69	27.04	46.00	-18.96	peak	
4		284.6250	39.90	-12.37	27.53	46.00	-18.47	peak	
5		466.5000	38.34	-7.87	30.47	46.00	-15.53	peak	
6 *		650.8000	34.40	-3.34	31.06	46.00	-14.94	peak	




EUT :	Optical 2.4GHz Wireless Mouse	Model Name :	CM-198
Temperature :	25 °C	Relative Humidity :	58 %
Pressure :	1010 hPa	Test Voltage :	DC 3V
Test Mode :	TX Mode 2480MHz	Polarization:	Vertical



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		66.3750	43.86	-17.81	26.05	40.00	-13.95	peak	
2		112.4500	44.50	-18.34	26.16	43.50	-17.34	peak	
3		204.6000	38.40	-16.44	21.96	43.50	-21.54	peak	
4		318.5750	35.62	-11.61	24.01	46.00	-21.99	peak	
5		478.6250	36.38	-7.68	28.70	46.00	-17.30	peak	
6 *		660.5000	36.14	-3.30	32.84	46.00	-13.16	peak	



EUT :	Optical 2.4GHz Wireless Mouse	Model Name :	CM-198
Temperature :	25 °C	Relative Humidity :	58 %
Pressure :	1010 hPa	Test Voltage :	DC 3V
Test Mode :	TX Mode 2480MHz	Polarization:	Horizontal



No. Mk.	Freq. MHz	Reading Level	Correct Factor	Measure- ment	Limit	Over	Comment
		dBuV	dB	dBuV/m	dB	Detector	
1	80.9250	41.98	-19.07	22.91	40.00	-17.09	peak
2	165.8000	42.63	-17.45	25.18	43.50	-18.32	peak
3	337.9750	38.50	-11.14	27.36	46.00	-18.64	peak
4	466.5000	36.84	-7.87	28.97	46.00	-17.03	peak
5	578.0500	34.59	-4.81	29.78	46.00	-16.22	peak
6 *	650.8000	33.90	-3.34	30.56	46.00	-15.44	peak

**4.2.9 TEST RESULTS (ABOVE 1000 MHZ)**

EUT :	Optical 2.4GHz Wireless Mouse			Model Name :		CM-198	
Temperature :	25 °C			Relative Humidity :		58 %	
Pressure :	1010 hPa			Test Voltage :		DC 3V	
Test Mode :	TX 2402MHz						



Freq. (MHz)	Ant.Pol. H/V	Reading		Ant./CF CF(dB)	Act.		Limit		Margin		Note
		Peak (dBuV)	AV (dBuV)		Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	
2390.00	V	22.74	9.40	32.28	55.02	41.68	74.00	54.00	-18.98	-12.32	X/E
2402.25	V	44.57	31.23	32.27	76.84	63.50					X/F
4804.30	V	53.55	40.21	6.11	59.66	46.32	74.00	54.00	-14.34	-7.68	X/H

Remark :

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency . "F" denotes fundamental frequency; "H" denotes spurious frequency . "E" denotes band edge frequency . (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis :
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (8) The average value of fundamental frequency is:
Average = Peak value + 20log(Duty cycle) , Final AV=PK-45.80



TX 2402MHz(Above 1000 MHz, Vertical)





EUT :	Optical 2.4GHz Wireless Mouse	Model Name :	CM-198
Temperature :	25 °C	Relative Humidity :	58 %
Pressure :	1010hPa	Test Voltage :	DC 3V
Test Mode :	TX 2402MHz		



Freq. (MHz)	Ant.Pol. H/V	Reading		Ant./CF CF(dB)	Act.		Limit		Margin		Note
		Peak (dBuV)	AV (dBuV)		Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	
2390.00	H	22.41	9.07	32.28	54.69	41.35	74.00	54.00	-19.31	-12.65	X/E
2402.38	H	50.26	36.92	32.27	82.53	69.19					X/F
4804.25	H	49.36	35.02	6.11	55.47	41.13	74.00	54.00	-18.53	-12.87	X/H

Remark :

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency. "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission.
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis :
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (8) The average value of fundamental frequency is:
Average = Peak value + 20log(Duty cycle) · Final AV=PK-45.80



TX 2402MHz(Above 1000 MHz, Horizontal)





EUT :	Optical 2.4GHz Wireless Mouse	Model Name :	CM-198
Temperature :	25 °C	Relative Humidity :	58 %
Pressure :	1010 hPa	Test Voltage :	DC 3V
Test Mode :	TX 2442MHz		



Freq. (MHz)	Ant.Pol. H/V	Reading		Ant./CF		Act.		Limit		Margin		Note
		Peak (dBuV)	AV (dBuV)	CF(dB)	(dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	
2441.75	V	45.55	32.21	32.23	77.78	64.44						X/F
4884.35	V	52.42	39.08	6.43	58.85	45.51	74.00	54.00	-15.15	-8.49		X/H

Remark :

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency . "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis :
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (8) The average value of fundamental frequency is:
Average = Peak value + 20log(Duty cycle) → Final AV=PK-45.80



TX 2442MHz (Above 1000 MHz, Vertical)





EUT :	Optical 2.4GHz Wireless Mouse	Model Name :	CM-198
Temperature :	25 °C	Relative Humidity :	58 %
Pressure :	1010 hPa	Test Voltage :	DC 3V
Test Mode :	TX 2442MHz		



Freq. (MHz)	Ant.Pol. H/V	Reading		Ant./CF		Act.		Limit		Margin		Note
		Peak (dBuV)	AV (dBuV)	CF(dB)	(dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	
2442.25	H	50.27	36.93	32.23	82.50	69.16						X/F
4884.35	H	50.25	36.91	6.43	56.68	43.34	74.00	54.00	-17.32	-10.66		X/H

Remark :

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency . "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis :
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (8) The average value of fundamental frequency is:
Average = Peak value + 20log(Duty cycle) , Final AV=PK-45.80



TX 2442MHz (Above 1000 MHz, Horizontal)





EUT :	Optical 2.4GHz Wireless Mouse	Model Name :	CM-198
Temperature :	25 °C	Relative Humidity :	58 %
Pressure :	1010hPa	Test Voltage :	DC 3V
Test Mode :	TX 2480MHz		



Freq. (MHz)	Ant.Pol. H/V	Reading		Ant./CF		Act.		Limit		Margin		Note
		Peak (dBuV)	AV (dBuV)	CF(dB)	(dBuV/m)							
2480.50	V	45.14	31.80	32.18	77.32	63.98						X/F
2483.50	V	22.17	8.83	32.17	54.34	41.00	74.00	54.00	-19.66	-13.00		X/E
4959.29	V	52.69	39.35	6.73	59.42	46.08	74.00	54.00	-14.58	-7.92		X/H

Remark :

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency . "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis :
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (8) The average value of fundamental frequency is:
Average = Peak value + 20log(Duty cycle) · Final AV=PK-45.80



TX 2480MHz(Above 1000 MHz, Vertical)





EUT :	Optical 2.4GHz Wireless Mouse	Model Name :	CM-198
Temperature :	25 °C	Relative Humidity :	58 %
Pressure :	1010 hPa	Test Voltage :	DC 3V
Test Mode :	TX 2480MHz		



Freq. (MHz)	Ant.Pol. H/V	Reading		Ant./CF CF(dB)	Act.		Limit		Margin		Note
		Peak (dBuV)	AV (dBuV)		Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)	
2479.75	H	49.22	35.88	32.18	81.40	68.06					X/F
2483.50	H	22.48	9.14	32.17	54.65	41.31	74.00	54.00	-19.35	-12.69	X/E
4959.35	H	49.30	35.96	6.73	56.03	42.69	74.00	54.00	-17.97	-11.31	X/H

Remark :

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency . "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis :
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (8) The average value of fundamental frequency is:
Average = Peak value + 20log(Duty cycle) · Final AV=PK-45.80



TX 2480MHz(Above 1000 MHz, Horizontal)





5. NUMBER OF HOPPING CHANNEL

5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C			
Section	Test Item	Frequency Range (MHz)	Result
15.247 (a)(1)(iii)	Number of Hopping Channel	2400-2483.5	PASS

5.1.1 MEASUREMENT INSTRUMENTS LIST AND SETTING

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov.25.2013

Remark: "N/A" denotes no model name, serial no. or calibration specified.

All calibration period of Equipment List is One Year.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> Operating Frequency Range
RB	100 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


5.1.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 100KHz, VBW=100KHz, Sweep time = Auto.

5.1.3 DEVIATION FROM STANDARD

No deviation.

5.1.4 TEST SETUP



5.1.5 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.



5.1.6 TEST RESULTS

EUT :	Optical 2.4GHz Wireless Mouse	Model Name :	CM-198
Temperature :	25 °C	Relative Humidity :	58 %
Pressure :	1009 hPa	Test Voltage :	DC 3V
Test Mode :	Hopping Mode		

Number of Hopping Channel	16
---------------------------	----





6. AVERAGE TIME OF OCCUPANCY

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(1)(iii)	Average Time of Occupancy	0.4sec	2400-2483.5	PASS

6.1.1 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov.25.2013


Remark: "N/A" denotes no model name, serial no. or calibration specified.

All calibration period of Equipment List is One Year.

6.1.2 TEST PROCEDURE

- a. The transmitter output (antenna port) was connected to the spectrum analyzer
- b. Set RBW of spectrum analyzer to 1MHz and VBW to 1MHz.
- c. Use a video trigger with the trigger level set to enable triggering only on full pulses.
- d. Sweep Time is more than once pulse time.
- e. Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- f. Measure the maximum time duration of one single pulse.
- g. Set the EUT for packet transmitting.
- h. Measure the maximum time duration of one single pulse.
- i. Dwell time = [spreading rate/16] x duty-cycle x 0.4 seconds

6.1.3. TEST SETUP LAYOUT



6.1.4. TEST DEVIATION

There is no deviation with the original standard.

6.1.5. EUT OPERATION DURING TEST

The EUT was programmed to be in continuously transmitting/Hopping mode.




6.1.6. TEST RESULTS

EUT :	Optical 2.4GHz Wireless Mouse	Model Name :	CM-198
Temperature :	25 °C	Relative Humidity :	58 %
Pressure :	1009 hPa	Test Voltage :	DC 3V
Test Mode :	Hopping Mode		

Mode	Number of transmission in a 6.4 (16 Hopping*0.4)	Length of transmission time (msec)	Result (msec)	Limit (msec)
2402 MHz	(7/1) *6.4=44.8 times Note1	0.36	16.128	400

Note1: 7 times of occupied channels per 1 second.

	Results
Measured cycle (sec)	16 CH*0.4=6.4
The total number of frequency-hopping per second	((7/1)*6.4)=44.8
The number of occupied channels per second	44.8/6.4=7(number/sec)
occupied time for each channel(1)	0.36ms
The total number of channels occupied within one cycle (2)	(7/1) *6.4=44.8 times
The average time of occupancy within one cycle(1)*(2)	16.128msec
LIMIT (msec)	400msec





7. HOPPING CHANNEL SEPARATION MEASUREMENT

7.1 APPLIED PROCEDURES / LIMIT

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

7.1.1 MEASUREMENT INSTRUMENTS LIST AND SETTING

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov.25.2013

Remark: "N/A" denotes no model name, serial no. or calibration specified.

All calibration period of Equipment List is One Year.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	30 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


7.1.2 TEST PROCEDURE

- The EUT must have its hopping function enabled
- Span = wide enough to capture the peaks of two adjacent channels
Resolution (or IF) Bandwidth (RBW) \geq 1% of the span
Video (or Average) Bandwidth (VBW) \geq RBW
Sweep = auto
Detector function = peak
Trace = max hold

7.1.3 DEVIATION FROM STANDARD

No deviation.

7.1.4 TEST SETUP



7.1.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in hopping mode.




7.1.6 TEST RESULTS

EUT :	Optical 2.4GHz Wireless Mouse	Model Name :	CM-198
Temperature :	25 °C	Relative Humidity :	58 %
Pressure :	1009 hPa	Test Voltage :	DC 3V
Test Mode :	2402MHz / 2442MHz / 2480MHz		

Frequency	Ch. Separation (MHz)	20dB Bandwidth (MHz)	Result
2471.5MHz	1.02	1.3	Complies

Ch. Separation Limits: >20dB bandwidth or >2/3 of 20dB bandwidth





8. BANDWIDTH TEST

8.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(2)	Bandwidth	<= 1 MHz (20dB bandwidth)	2400-2483.5	PASS

8.1.1 MEASUREMENT INSTRUMENTS LIST AND SETTING

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov.25.2013

Remark: "N/A" denotes no model name, serial no. or calibration specified.

All calibration period of Equipment List is One Year.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	30 kHz (20dB Bandwidth) / 30 kHz (Channel Separation)
VB	100 kHz (20dB Bandwidth) / 100 kHz (Channel Separation)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

8.1.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 30KHz, VBW=100KHz, Sweep time = Auto.

8.1.3 DEVIATION FROM STANDARD

No deviation.

8.1.4 TEST SETUP



8.1.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.



8.1.6 TEST RESULTS


EUT :	Optical 2.4GHz Wireless Mouse	Model Name :	CM-198
Temperature :	25 °C	Relative Humidity :	58 %
Pressure :	1009 hPa	Test Voltage :	DC 3V
Test Mode :	2402MHz / 2442MHz / 2480MHz		

Frequency (MHz)	20dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Channel Separation (MHz)	Result
2402	1.30	1.30	<= 1MHz	PASS
2442	1.22	1.24	<= 1MHz	PASS
2480	1.19	1.20	<= 1MHz	PASS





Date: 16.JAN.2013 14:28:46



Date: 16.JAN.2013 14:29:49



9. PEAK OUTPUT POWER TEST

9.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (b)(1)	Peak Output Power	0.125 watt or 21dBm	2400-2483.5	PASS

9.1.1 MEASUREMENT INSTRUMENTS LIST AND SETTING

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	P-series Power meter	Agilent	N1911A	MY45100473	Apr.28.2013
2	Wireband Power sensor	Agilent	N1921A	MY51100041	Apr.28.2013

Remark: "N/A" denotes no model name, serial no. or calibration specified.

All calibration period of Equipment List is One Year.

9.1.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum meter and antenna output port as show in the block diagram below,

9.1.3 DEVIATION FROM STANDARD

No deviation.

9.1.4 TEST SETUP



9.1.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.



9.1.6 TEST RESULTS

EUT :	Optical 2.4GHz Wireless Mouse	Model Name :	CM-198
Temperature :	25 °C	Relative Humidity :	58 %
Pressure :	1009 hPa	Test Voltage :	DC 3V
Test Mode :	2402MHz / 2442MHz / 2480MHz		

Test Channel	Frequency (MHz)	Peak Output Power (dBm)	LIMIT (dBm)	LIMIT (W)
2402MHz	2402	-11.63	21	0.125
2442MHz	2442	-11.61	21	0.125
2480MHz	2480	-11.51	21	0.125



10. ANTENNA CONDUCTED SPURIOUS EMISSION

10.1 APPLIED PROCEDURES / LIMIT

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

10.1.1 MEASUREMENT INSTRUMENTS LIST AND SETTING

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov.25.2013

Remark: "N/A" denotes no model name, serial no. or calibration specified.

All calibration period of Equipment List is One Year.

10.1.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 100KHz, VBW=100KHz, Sweep time = Auto.

10.1.3 DEVIATION FROM STANDARD

No deviation.

10.1.4 TEST SETUP




10.1.5 EUT OPERATION CONDITIONS



The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.


**10.1.6 TEST RESULTS**

EUT :	Optical 2.4GHz Wireless Mouse	Model Name :	CM-198
Temperature :	25 °C	Relative Humidity :	58 %
Pressure :	1009 hPa	Test Voltage :	DC 3V
Test Mode :	2402MHz / 2442MHz / 2480MHz & Hopping on mode		


The max. radio frequency power in any 100kHz bandwidth within the frequency band	The max. radio frequency power in any 100 kHz bandwidth within the frequency band.		
FREQUENCY(MHz)	POWER(dBm)	FREQUENCY(MHz)	POWER(dBm)
2400.00	-50.42	2483.50	-56.06
Result			
In any 100kHz bandwidth outside the frequency band, the radio frequency power is at least 20dB below that in the 100kHz bandwidth within the band that contains the highest lever of the desired power.			









Date: 16.JAN.2013 14:34:13




Date: 16.JAN.2013 14:35:15



Date: 16.JAN.2013 14:38:14



Date: 16.JAN.2013 14:38:36






11. EUT PHOTOS

Radiated Measurement Photos 9K~30MHz





**Radiated Measurement Photos
30M~1000MHz**





**Radiated Measurement Photos
Above 1000MHz**

