


RF Exposure Evaluation Report

APPLICANT : Inseego Corp.
EQUIPMENT : wireless device
BRAND NAME : Inseego
MODEL NAME : FG2000-3, FG2000e-3
FCC ID : PKRISGFG20003
STANDARD : 47 CFR Part 2.1091
FCC KDB 447498 D01 v06

We, Sporton International (Kunshan) Inc., would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and FCC KDB 447498 D01 v06, and pass the limit. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.



Reviewed by: Nick Hu / Supervisor



Approved by: Kat Yin / Manager



Sporton International (Kunshan) Inc.

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China**



Table of Contents

1. ADMINISTRATION DATA	4
1.1. Testing Laboratory	4
2. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	5
3. MAXIMUM RF TUNE UP POWER AMONG PRODUCTION UNITS	8
4. RF EXPOSURE LIMIT INTRODUCTION	11
5. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION	12
5.1. Standalone Power Density Calculation	12
5.2. Collocated Power Density Calculation.....	14



Revision History

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA082811-03	Rev. 01	Initial issue of report.	Nov. 08, 2021



1. Administration Data

1.1. Testing Laboratory

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Testing Laboratory			
Test Firm	Sporton International (Kunshan) Inc.		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	SAR01-KS	CN1257	314309

Applicant	
Company Name	Inseego Corp.
Address	9710 Scranton Road, Suite 200 San Diego, CA 92121

Manufacturer	
Company Name	MeiG Smart Technology Co., Ltd
Address	Floor 2, Office Building No.5, Lingxia Road, Fenghuang Community, Fuyong Street, Bao 'an District, Shenzhen



2. Description of Equipment Under Test (EUT)

Product Feature & Specification	
EUT Type	wireless device
Brand Name	Inseego
Model Name	FG2000-3, FG2000e-3
FCC ID	PKRISGFG20003
Wireless Technology and Frequency Range	WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz WCDMA Band IV: 1712.4 MHz ~ 1752.6 MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz LTE Band 2: 1850.7 MHz ~ 1909.3 MHz LTE Band 4: 1710.7 MHz ~ 1754.3 MHz LTE Band 5: 824.7 MHz ~ 848.3 MHz LTE Band 7: 2502.5 MHz ~ 2567.5MHz LTE Band 12: 699.7 MHz ~ 715.3 MHz LTE Band 13: 779.5 MHz ~ 784.5 MHz LTE Band 14: 790.5 MHz ~ 795.5 MHz LTE Band 17: 706.5 MHz ~ 713.5 MHz LTE Band 25: 1850.7 MHz ~ 1914.3 MHz LTE Band 26: 814.7 MHz ~ 848.3 MHz LTE Band 30: 2307.5 MHz ~ 2312.5 MHz LTE Band 38: 2572.5 MHz ~ 2617.5 MHz LTE Band 41: 2498.5 MHz ~ 2687.5 MHz LTE Band 42: 3552.5 MHz ~ 3597.5 MHz LTE Band 43: 3652.5 MHz ~ 3672.5 MHz LTE Band 48: 3552.5 MHz ~ 3697.5 MHz LTE Band 66: 1710.7 MHz ~ 1779.3 MHz LTE Band 71: 665.5 MHz ~ 695.5 MHz 5G NR n2 : 1850 MHz ~ 1910 MHz 5G NR n5 : 824 MHz ~ 849 MHz 5G NR n12 : 699 MHz ~ 716 MHz 5G NR n25 : 1850 MHz ~ 1915 MHz 5G NR n41 : 2496 MHz ~ 2690 MHz 5G NR n66 : 1710 MHz ~ 1780 MHz 5G NR n71 : 663 MHz ~ 698 MHz WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz WLAN 5.2GHz Band: 5180 MHz ~ 5240 MHz WLAN 5.8GHz Band: 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Mode	RMC 12.2Kbps HSDPA/HSUPA DC-HSDPA HSPA+ (16QAM uplink is not supported) LTE: QPSK, 16QAM, 64QAM, 256QAM DFT-s-OFDM (PI/2 BPSK / QPSK / 16QAM / 64QAM / 256QAM) CP-OFDM (QPSK / 16QAM / 64QAM / 256QAM) WLAN 2.4GHz 802.11b/g/n/ax HT20/ HT40/ HE20/ HE40 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac/ax VHT20/VHT40/VHT80/HE20/HE40/HE80 Bluetooth LE
Antenna Gain	<For WWAN/5G NR> WCDMA Band II : 3.94 dBi WCDMA Band IV : 3.22 dBi WCDMA Band V : 1.67 dBi LTE Band 2 : 3.90 dBi LTE Band 4 : 3.20 dBi LTE Band 5 : 1.70 dBi LTE Band 7 : 4.80 dBi LTE Band 12 : 2.10 dBi LTE Band 13 : 2.80 dBi



<p>LTE Band 14 : 1.80 dBi LTE Band 17 : 2.10 dBi LTE Band 25 : 3.90 dBi LTE Band 26 : 1.70 dBi LTE Band 30 : 4.70 dBi LTE Band 38 : 4.80 dBi LTE Band 41 : 4.80 dBi LTE Band 42 : 3.10 dBi LTE Band 43 : 3.30 dBi LTE Band 48 : 3.30 dBi LTE Band 66 : 3.50 dBi LTE Band 71 : 1.80 dBi n2: 1.70 dBi n5: 2.50 dBi n12: 2.11 dBi n25: 1.70 dBi n41 : 2.60 dBi n66: 2.80 dBi n71 : 1.70 dBi</p> <p><For Non-Beamforming></p> <p><Ant. 1> WLAN 2.4GHz: gain 4.16 dBi WLAN 5.2GHz: gain 2.96 dBi WLAN 5.8GHz: gain 3.90 dBi</p> <p><Ant. 2> WLAN 2.4GHz: gain 2.85 dBi WLAN 5.2GHz: gain 2.70 dBi WLAN 5.8GHz: gain 3.05 dBi</p> <p><Ant. 3> WLAN 2.4GHz: gain 3.00 dBi WLAN 5.2GHz: gain 4.57 dBi WLAN 5.8GHz: gain 4.25 dBi</p> <p><Ant. 4> WLAN 2.4GHz: gain 3.27 dBi WLAN 5.2GHz: gain 4.30 dBi WLAN 5.8GHz: gain 4.30 dBi</p> <p><For Beamforming MIMO> WLAN 2.4GHz: gain 9.36 dBi WLAN 5.2GHz: gain 9.69 dBi WLAN 5.8GHz: gain 9.91 dBi</p> <p><For Bluetooth> Bluetooth: gain 1.60 dBi</p>	<p>WWAN : PCB Antenna 5G NR : PCB Antenna WLAN : PCB Antenna Bluetooth: PCB Antenna</p>
Antenna Type	
HW Version	FG20003_SRT860H_V2.1
SW Version	2.52
EUT Stage	Identical Prototype

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. For LTE Band 43 support up to 64QAM, all other LTE bands support up to 256QAM.
3. This device supports HPUE for LTE band 41 with class 2 power level, so HPUE has been performed standalone power density calculation.
4. LTE band 42/43 covered by LTE band 48 with the same power level, so only chose LTE band 48 to perform standalone power density calculation.
5. For DFT-s-OFDM and CP-OFDM output power measurement reduction, according to maximum power reduction for the CP-OFDM mode will not higher than DFT-s-OFDM mode, therefore, CP-OFDM measurement is unnecessary. We always chose higher power (DFT-s-OFDM mode) to perform MPE analysis.



6. 5GNR supports NSA mode.
7. This device support beamforming for WLAN 2.4GHz 802.11ax HE20/HE40 and WLAN 5GHz 802.11ac/ax VHT20/VHT40/VHT80/HE20/HE40/HE80.
8. For WLAN SISO & MIMO mode, the whole testing has assessed only MIMO mode by referring to the higher conducted power.
9. For WLAN CDD & Beamforming mode, the MPE calculation performed separately.
10. Beamforming Gain is calculated according to KDB662911.
11. This is a variant report. For model change note, Please refer to the FG2000-3, FG2000e-3_ Class II Permissive Change letter exhibit separately. The difference is that enabled new ENDC combination and enabled LTE Band 43 by software. According to the difference, added new ENDC combination and LTE Band 43 evaluation based on original report (Sporton Report Number FA082811).

Comments and Explanations:

1. The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.
2. The maximum RF output tune up power, antenna gain also the safe distance used for evaluate RF exposure were declared by manufacturer.



3. Maximum RF Tune Up power among production units

<WCDMA>

Mode		Maximum Average power(dBm)
WCDMA	Band II	24.00
	Band IV	24.00
	Band V	24.00

<LTE>

Mode		Maximum Average power(dBm)
LTE	Band 2	24.00
	Band 4	24.00
	Band 5	24.00
	Band 7	24.00
	Band 12	24.00
	Band 13	24.00
	Band 14	24.00
	Band 17	24.00
	Band 25	24.00
	Band 26	24.00
	Band 30	21.00
	Band 38	24.00
	Band 41	24.00
	Band 41-HPUE	26.50
	Band 42	19.50
	Band 43	19.50
	Band 48	19.50
Band66	24.00	
Band71	24.00	

<5G NR>

Mode		Maximum Average power(dBm)
5G NR	n2	24.00
	n5	24.00
	n12	24.00
	n25	24.00
	n41	24.00
	n66	24.00
	n71	24.00



<Bluetooth>

Mode	Maximum Average Power (dBm)
Bluetooth LE	0

<For CDD Mode>

<2.4GHz WLAN >

Mode	Maximum Average Power (dBm)					
	ANT1	ANT2	ANT3	ANT4	ANT1+2+3+4	
2.4GHz	802.11b	20.00	20.00	20.00	20.00	
	802.11g	19.00	19.00	19.00	19.00	
	802.11n-HT20	19.00	19.00	19.00	19.00	25.00
	802.11n-HT40	19.00	19.00	19.00	19.00	25.00
	802.11ax-HE20	15.00	15.00	15.00	15.00	21.00
	802.11ax-HE40	15.00	15.00	15.00	15.00	21.00

<5GHz WLAN >

Mode	Maximum Average Power (dBm)					
	ANT1	ANT2	ANT3	ANT4	ANT1+2+3+4	
5.2GHz	802.11a	19.00	19.00	19.00	19.00	
	802.11n-HT20	19.00	19.00	19.00	19.00	25.00
	802.11n-HT40	19.00	19.00	19.00	19.00	25.00
	802.11ac-VHT20	17.00	17.00	17.00	17.00	23.00
	802.11ac-VHT40	17.00	17.00	17.00	17.00	23.00
	802.11ac-VHT80	17.00	17.00	17.00	17.00	23.00
	802.11ax-HE20	15.00	15.00	15.00	15.00	21.00
	802.11ax-HE40	15.00	15.00	15.00	15.00	21.00
5.8GHz	802.11a	13.00	13.00	13.00	13.00	
	802.11n-HT20	19.00	19.00	19.00	19.00	25.00
	802.11n-HT40	19.00	19.00	19.00	19.00	25.00
	802.11ac-VHT20	17.00	17.00	17.00	17.00	23.00
	802.11ac-VHT40	17.00	17.00	17.00	17.00	23.00
	802.11ac-VHT80	17.00	17.00	17.00	17.00	23.00
	802.11ax-HE20	15.00	15.00	15.00	15.00	21.00
	802.11ax-HE40	15.00	15.00	15.00	15.00	21.00
802.11ax-HE80	15.00	15.00	15.00	15.00	21.00	

Note:

1. WLAN2.4GHz/WLAN5GHz(except 802.11b/g/a) all support SISO/MIMO mode, we only chose MIMO tune up power to perform MPE calculation conservatively for MIMO power is higher.



<For Beamforming Mode>

<2.4GHz WLAN >

Mode		Maximum Average Power (dBm)
		MIMO
2.4GHz	802.11ax-HE20	17.00
	802.11ax-HE40	17.00

<5GHz WLAN >

Mode		Maximum Average Power (dBm)
		MIMO
5.2GHz	802.11ac-VHT20	19.00
	802.11ac-VHT40	19.00
	802.11ac-VHT80	19.00
	802.11ax-HE20	17.00
	802.11ax-HE40	16.00
	802.11ax-HE80	16.00
5.8GHz	802.11ac-VHT20	18.00
	802.11ac-VHT40	18.00
	802.11ac-VHT80	18.00
	802.11ax-HE20	16.00
	802.11ax-HE40	16.00
	802.11ax-HE80	16.00

Note: This device support beamforming for WLAN 2.4GHz 802.11ax HE20/HE40 and WLAN 5GHz 802.11ac/ax VHT20/VHT40/VHT80/HE20/HE40/HE80.



4. RF Exposure Limit Introduction

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

The MPE was calculated at **20 cm** to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

- S = Power Density
- P = Output Power at Antenna Terminals
- G = Gain of Transmit Antenna (linear gain)
- R = Distance from Transmitting Antenna



5. Radio Frequency Radiation Exposure Evaluation

5.1. Standalone Power Density Calculation

Table with 10 columns: Band, Frequency (MHz), Antenna Gain (dBi), Maximum Power (dBm), Maximum EIRP (dBm), Maximum EIRP (W), Average EIRP (mW), Power Density at 20cm (mW/cm^2), Limit (mW/cm^2), Power Density / Limit. Rows include WCDMA, LTE, and 5G NR bands, along with WLAN and Bluetooth.



<For Beamforming mode>

Band	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum EIRP (dBm)	Maximum EIRP (W)	Average EIRP (mW)	Power Density at 20cm (mW/cm ²)	Limit (mW/cm ²)	Power Density / Limit
2.4GHz WLAN	2412.0	9.36	17.00	26.360	0.433	432.514	0.086	1.000	0.086
5.2GHz WLAN	5180.0	9.69	19.00	28.690	0.740	739.605	0.147	1.000	0.147
5.8GHz WLAN	5745.0	9.91	18.00	27.910	0.618	618.016	0.123	1.000	0.123

Note:

1. For conservativeness, the lowest frequency of each band is used to determine the MPE limit of that band.
2. This device supports HPUE for LTE band 41 with class 2 power level, so HPUE has been performed standalone power density calculation.
3. LTE band 42/43 covered by LTE band 48 with the same power level, so only chose LTE band 48 to perform standalone power density calculation.
4. This device support beamforming for WLAN 2.4GHz 802.11ax HE20/HE40 and WLAN 5GHz 802.11 ac/ax VHT20/VHT40/VHT80/HE20/HE40/HE80.
5. Beamforming Gain is calculated according to FCC KDB662911.
6. Chose the maximum power density to do MPE analysis.



5.2. Collocated Power Density Calculation

Table with 4 columns: WWAN Power Density / Limit, 5G NR Power Density / Limit, WLAN 2.4GHz Power Density / Limit, and Σ(Power Density / Limit) of WWAN + 5G NR + WLAN 2.4GHz. It contains three rows of data for different combinations of WWAN, 5G NR, and WLAN/BT.

Note:

- 1. For collocation analysis, LTE Band41-HPUE is chosen for summation due to the highest (power density/limit) among all WWAN wireless modes.
2. For collocation analysis, 5G NR n12 is chosen for summation due to the highest (power density/limit) among all 5G NR modes.
3. Chose the worst power density among WLAN2.4/5GHz to do co-located.
4. Σ(Power Density / Limit): This is a summation of [(power density for each transmitter/antenna included in the simultaneous transmission)/ (corresponding MPE limit)], for WWAN + 5G NR + WLAN, and WWAN + 5G NR + BT.
5. Considering the WWAN and 5G NR module collocation with the WLAN/BT transmitter of the EIRP performance listed in the table above, the aggregated (power density /limit) is smaller than 1.

Conclusion:

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.

-----THE END-----