



FCC RADIO TEST REPORT

FCC ID : PKRISGFW2000
Equipment : 5G CPE Wireless Solution
Brand Name : Inseego
Model Name : FW2000
Marketing Name : FW2000, FW2000e
Applicant : Inseego Corp.
9710 Scranton Road Suite 200, San Diego, CA 92121
Manufacturer : Inseego Corp.
9710 Scranton Road Suite 200, San Diego, CA 92121
Standard : FCC Part 15 Subpart C §15.247

The product was received on Sep. 03, 2020 and testing was started from Sep. 28, 2020 and completed on Oct. 13, 2020. We, SPORTON INTERNATIONAL INC., EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Louis Wu

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description.....	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT	5
1.3 Testing Location	5
1.4 Applicable Standards.....	6
2 Test Configuration of Equipment Under Test.....	7
2.1 Carrier Frequency Channel	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System	9
2.4 Support Unit used in test configuration and system	9
2.5 EUT Operation Test Setup	9
2.6 Measurement Results Explanation Example.....	10
3 Test Result.....	11
3.1 6dB and 99% Bandwidth Measurement	11
3.2 Output Power Measurement.....	20
3.3 Power Spectral Density Measurement	21
3.4 Conducted Band Edges and Spurious Emission Measurement	30
3.5 Radiated Band Edges and Spurious Emission Measurement	39
3.6 AC Conducted Emission Measurement.....	43
3.7 Antenna Requirements.....	45
4 List of Measuring Equipment	46
5 Uncertainty of Evaluation.....	48
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission	
Appendix D. Radiated Spurious Emission Plots	
Appendix E. Duty Cycle Plots	
Appendix F. Setup Photographs	



History of this test report



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Reporting only	-
3.2	15.247(b)(3)	Output Power	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	Pass	Under limit 7.40 dB at 2483.520 MHz
3.6	15.207	AC Conducted Emission	Pass	Under limit 2.41 dB at 0.305 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	Pass	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Wii Chang

Report Producer: Ruby Zou



1 General Description

1.1 Product Feature of Equipment Under Test

LTE/5G NR, Bluetooth and GNSS.

Product Specification subjective to this standard	
Antenna Type	WWAN: Fixed Internal Antenna Bluetooth: Fixed Internal Antenna GPS/Glonass/Galileo/BDS : Fixed Internal Antenna

1.2 Modification of EUT

No modifications are made to the EUT during all test items.

1.3 Testing Location

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory	
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No.	
	TH05-HY	CO05-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory	
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855	
Test Site No.	Sporton Site No.	
	03CH15-HY	

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW0007



1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-




2.2 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X Plane for 1Mbps and Z plane for 2Mbps) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	Data Rate / Modulation
	Bluetooth – LE / GFSK
Conducted Test Cases	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps
Radiated Test Cases	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps
AC Conducted Emission	Mode 1: Bluetooth-LE Link + RJ-45 Link + POE Adapter

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Notebook	Dell	Latitude3400	FCC DoC	N/A	AC I/P : Unshielded, 1.2m DC O/P : Shielded, 1.8m
2.	Mobile Phone	SAMSUNG	SM-A730F/DS	A3LSMA730F	N/A	N/A

2.5 EUT Operation Test Setup

The RF test items, utility “ADB” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.



2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)} \end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) $\geq 3 * \text{RBW}$.
6. Measure and record the results in the test report.

3.1.4 Test Setup




3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.


<1Mbps>

6 dB Bandwidth Plot on Channel 00




Date: 1.OCT.2020 01:57:06

6 dB Bandwidth Plot on Channel 19



Date: 1.OCT.2020 02:15:43

6 dB Bandwidth Plot on Channel 39




Date: 1.OCT.2020 02:48:06




<2Mbps>

6 dB Bandwidth Plot on Channel 00




Date: 2.OCT.2020 16:39:43

6 dB Bandwidth Plot on Channel 19



Date: 2.OCT.2020 16:52:28

6 dB Bandwidth Plot on Channel 39




Date: 2.OCT.2020 16:59:35

3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.


<1Mbps>

99% Bandwidth Plot on Channel 00




Date: 1.OCT.2020 02:09:23

99% Occupied Bandwidth Plot on Channel 19



Date: 1.OCT.2020 02:18:10

99% Occupied Bandwidth Plot on Channel 39




Date: 1.OCT.2020 02:50:39

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.




<2Mbps>

99% Bandwidth Plot on Channel 00




Date: 2.OCT.2020 16:42:56

99% Occupied Bandwidth Plot on Channel 19



Date: 2.OCT.2020 16:53:50

99% Occupied Bandwidth Plot on Channel 39



Date: 2.OCT.2020 17:01:17

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

See list of measuring equipment of this test report.

3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
2. The RF output of EUT was connected to the power meter by RF cable and attenuator.
3. The path loss was compensated to the results for each measurement.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Average Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup




3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.3.6 Test Result of Power Spectral Density Plots (100kHz)


<1Mbps>

PSD 100kHz Plot on Channel 00



Date: 1.OCT.2020 01:58:13


PSD 100kHz Plot on Channel 19



Date: 1.OCT.2020 02:16:58



PSD 100kHz Plot on Channel 39




Date: 1.OCT.2020 02:48:56




<2Mbps>

PSD 100kHz Plot on Channel 00



Date: 2.OCT.2020 16:41:02


PSD 100kHz Plot on Channel 19



Date: 2.OCT.2020 16:53:03



PSD 100kHz Plot on Channel 39




Date: 2.OCT.2020 17:00:12

3.3.7 Test Result of Power Spectral Density Plots (3kHz)


<1Mbps>

PSD 3kHz Plot on Channel 00



Date: 1.OCT.2020 01:57:46


PSD 3kHz Plot on Channel 19



Date: 1.OCT.2020 02:16:24



PSD 3kHz Plot on Channel 39




Date: 1.OCT.2020 02:48:43




<2Mbps>

PSD 3kHz Plot on Channel 00



Date: 2.OCT.2020 16:40:29


PSD 3kHz Plot on Channel 19



Date: 2.OCT.2020 16:52:46



PSD 3kHz Plot on Channel 39



Date: 2.OCT.2020 17:00:00

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

3.4.3 Test Procedure

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges Plots


<1Mbps>

Low Band Edge Plot on Channel 00



Date: 1.OCT.2020 01:58:31


High Band Edge Plot on Channel 39



Date: 1.OCT.2020 02:49:11


<2Mbps>

Low Band Edge Plot on Channel 00



Date: 2.OCT.2020 16:42:03


High Band Edge Plot on Channel 39



Date: 2.OCT.2020 17:00:30


3.4.6 Test Result of Conducted Spurious Emission Plots

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00




Date: 1.OCT.2020 02:08:48

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00




Date: 1.OCT.2020 02:09:04

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19




Date: 1.OCT.2020 02:17:22

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19




Date: 1.OCT.2020 02:17:37

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39




Date: 1.OCT.2020 02:50:07

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39




Date: 1.OCT.2020 02:50:21

Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 00



Date: 2.OCT.2020 16:42:25


Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 00



Date: 2.OCT.2020 16:42:41




Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 19



Date: 2.OCT.2020 16:53:21


Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 19



Date: 2.OCT.2020 16:53:36




**Conducted Spurious Emission Plot on Bluetooth LE 2Mbps
GFSK Channel 39**



Date: 2.OCT.2020 17:00:47

**Conducted Spurious Emission Plot on Bluetooth LE 2Mbps
GFSK Channel 39**



Date: 2.OCT.2020 17:01:02



3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

See list of measuring equipment of this test report.



3.5.3 Test Procedures


1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.

For average measurement:


 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

3.5.7 Duty Cycle

Please refer to Appendix E.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.



3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

See list of measuring equipment of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Jan. 09, 2020	Sep. 29, 2020~Oct. 05, 2020	Jan. 08, 2021	Radiation (03CH15-HY)
Bilog Antenna	TESEQ	CBL6111D&0 0800N1D01N-06	41912&05	30MHz to 1GHz	Feb. 09, 2020	Sep. 29, 2020~Oct. 05, 2020	Feb. 08, 2021	Radiation (03CH15-HY)
Amplifier	SONOMA	310N	363440	9kHz~1GHz	Dec. 27, 2019	Sep. 29, 2020~Oct. 05, 2020	Dec. 26, 2020	Radiation (03CH15-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1620	1-18GHz	Oct. 28, 2019	Sep. 29, 2020~Oct. 05, 2020	Oct. 27, 2020	Radiation (03CH15-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170 584	18GHz- 40GHz	Dec. 10, 2019	Sep. 29, 2020~Oct. 05, 2020	Dec. 09, 2020	Radiation (03CH15-HY)
Preamplifier	Jet-Power	JPA0118-55-3 03	171000180 0055006	1GHz~18GHz	May 07, 2020	Sep. 29, 2020~Oct. 05, 2020	May 06, 2021	Radiation (03CH15-HY)
Preamplifier	Keysight	83017A	MY532701 95	1GHz~26.5GHz	Aug. 21, 2020	Sep. 29, 2020~Oct. 05, 2020	Aug. 20, 2021	Radiation (03CH15-HY)
Preamplifier	EMEC	EM18G40G	060715	18GHz ~ 40GHz	Dec. 13, 2019	Sep. 29, 2020~Oct. 05, 2020	Dec. 12, 2020	Radiation (03CH15-HY)
EMI Test Receiver	Keysight	N9038A(MXE)	MY541300 85	20MHz~8.4GHz	Nov. 01, 2019	Sep. 29, 2020~Oct. 05, 2020	Oct. 31, 2020	Radiation (03CH15-HY)
Spectrum Analyzer	Agilent	E4446A	MY501801 36	3Hz~44GHz	May 04, 2020	Sep. 29, 2020~Oct. 05, 2020	May 03, 2021	Radiation (03CH15-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Sep. 29, 2020~Oct. 05, 2020	N/A	Radiation (03CH15-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Sep. 29, 2020~Oct. 05, 2020	N/A	Radiation (03CH15-HY)
Software	Audix	E3 6.2009-8-24(k 5)	RK-00045 1	N/A	N/A	Sep. 29, 2020~Oct. 05, 2020	N/A	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY36980/4	30M-18G	Apr. 14, 2020	Sep. 29, 2020~Oct. 05, 2020	Apr. 13, 2021	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9838/4 PE	30M-18G	Apr. 14, 2020	Sep. 29, 2020~Oct. 05, 2020	Apr. 13, 2021	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY37710/4	30M-18G	Apr. 17, 2020	Sep. 29, 2020~Oct. 05, 2020	Apr. 16, 2021	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	505134/2	30MHz-40GHz	Feb. 25, 2020	Sep. 29, 2020~Oct. 05, 2020	Feb. 24, 2021	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	800740/2	30MHz-40GHz	Feb. 25, 2020	Sep. 29, 2020~Oct. 05, 2020	Feb. 24, 2021	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4 PE	9kHz~30MHz	Mar. 12, 2020	Sep. 29, 2020~Oct. 05, 2020	Mar. 11, 2021	Radiation (03CH15-HY)
Filter	Wainwright	WLK4-1000-1 530-8000-40SS	SN4	1.53G Low Pass	Jul. 03, 2020	Sep. 29, 2020~Oct. 05, 2020	Jul. 02, 2021	Radiation (03CH15-HY)
Filter	Wainwright	WPKX12-270 0-3000-18000-60ST	SN4	3GHz High Pass Filter	Sep. 16, 2020	Sep. 29, 2020~Oct. 05, 2020	Sep. 15, 2021	Radiation (03CH15-HY)



Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	Testo	608-H1	34893241	N/A	Mar. 02, 2020	Sep. 28, 2020~Oct. 02, 2020	Mar. 01, 2021	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	16I00054S NO10	10MHz~6GHz	Dec. 23, 2019	Sep. 28, 2020~Oct. 02, 2020	Dec. 22, 2020	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101397	10Hz~40GHz	Nov. 15, 2019	Sep. 28, 2020~Oct. 02, 2020	Nov. 14, 2020	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz-40GHz	Dec. 30, 2019	Sep. 28, 2020~Oct. 02, 2020	Dec. 29, 2020	Conducted (TH05-HY)
Switch Box & RF Cable	EM Electronics	EMSW18SE	SW200302	N/A	Mar. 17, 2020	Sep. 28, 2020~Oct. 02, 2020	Mar. 16, 2021	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Oct. 13, 2020	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Nov. 15, 2019	Oct. 13, 2020	Nov. 14, 2020	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Nov. 07, 2019	Oct. 13, 2020	Nov. 06, 2020	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 20, 2019	Oct. 13, 2020	Nov. 19, 2020	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Oct. 13, 2020	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Jan. 02, 2020	Oct. 13, 2020	Jan. 01, 2021	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Jan. 02, 2020	Oct. 13, 2020	Jan. 01, 2021	Conduction (CO05-HY)



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{C(y)}$)	2.3
---	-----

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{C(y)}$)	5.0
---	-----

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{C(y)}$)	5.4
---	-----

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{C(y)}$)	5.0
---	-----

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Mina Liu				Temperature:	23.3~23.6		°C
Test Date:	2020/9/28~2020/10/02				Relative Humidity:	54.1~54.5		%

<u>TEST RESULTS DATA</u> <u>6dB and 99% Occupied Bandwidth</u>								
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.062	0.732	0.50	Pass
BLE	1Mbps	1	19	2440	1.076	0.752	0.50	Pass
BLE	1Mbps	1	39	2480	1.064	0.738	0.50	Pass

<u>TEST RESULTS DATA</u> <u>Average Power Table</u>										
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	-0.04	30.00	4.60	4.56	36.00	Pass
BLE	1Mbps	1	19	2440	2.26	30.00	4.60	6.86	36.00	Pass
BLE	1Mbps	1	39	2480	-0.24	30.00	4.60	4.36	36.00	Pass

<u>TEST RESULTS DATA</u> <u>Peak Power Density</u>									
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	-0.52	-13.85	4.60	8.00	Pass
BLE	1Mbps	1	19	2440	1.47	-11.02	4.60	8.00	Pass
BLE	1Mbps	1	39	2480	-1.02	-13.81	4.60	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	2Mbps	1	0	2402	2.092	1.268	0.50	Pass
BLE	2Mbps	1	19	2440	2.088	1.216	0.50	Pass
BLE	2Mbps	1	39	2480	2.092	1.240	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	2Mbps	1	0	2402	-0.20	30.00	4.60	4.40	36.00	Pass
BLE	2Mbps	1	19	2440	2.20	30.00	4.60	6.80	36.00	Pass
BLE	2Mbps	1	39	2480	-0.20	30.00	4.60	4.40	36.00	Pass

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	2Mbps	1	0	2402	-1.09	-16.91	4.60	8.00	Pass
BLE	2Mbps	1	19	2440	1.34	-14.58	4.60	8.00	Pass
BLE	2Mbps	1	39	2480	-1.10	-17.05	4.60	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.




Appendix B. AC Conducted Emission Test Results

Test Engineer :	Tom Lee	Temperature :	24~26°C
		Relative Humidity :	42~50%

EUT Information

Report NO : 082512
 Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Line

Full Spectrum



Final Result


Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.211560	---	41.87	53.14	11.27	L1	OFF	19.5
0.211560	45.96	---	63.14	17.18	L1	OFF	19.5
0.300750	---	45.08	50.22	5.14	L1	OFF	19.5
0.300750	51.95	---	60.22	8.27	L1	OFF	19.5
0.423060	---	39.24	47.39	8.15	L1	OFF	19.5
0.423060	42.92	---	57.39	14.47	L1	OFF	19.5
0.494250	---	35.63	46.10	10.47	L1	OFF	19.5
0.494250	42.63	---	56.10	13.47	L1	OFF	19.5
0.546000	---	37.14	46.00	8.86	L1	OFF	19.5
0.546000	43.98	---	56.00	12.02	L1	OFF	19.5
0.600000	---	35.98	46.00	10.02	L1	OFF	19.5
0.600000	43.63	---	56.00	12.37	L1	OFF	19.5
0.635730	---	37.23	46.00	8.77	L1	OFF	19.5
0.635730	43.34	---	56.00	12.66	L1	OFF	19.5
0.849750	---	36.38	46.00	9.62	L1	OFF	19.5
0.849750	43.59	---	56.00	12.41	L1	OFF	19.5
0.926250	---	35.95	46.00	10.05	L1	OFF	19.5
0.926250	42.94	---	56.00	13.06	L1	OFF	19.5
0.982500	---	35.08	46.00	10.92	L1	OFF	19.5
0.982500	42.20	---	56.00	13.80	L1	OFF	19.5
1.196250	---	33.34	46.00	12.66	L1	OFF	19.6

1.196250	40.86	---	56.00	15.14	L1	OFF	19.6
1.264560	---	34.78	46.00	11.22	L1	OFF	19.6
1.264560	42.31	---	56.00	13.69	L1	OFF	19.6
1.349250	---	34.77	46.00	11.23	L1	OFF	19.6
1.349250	41.56	---	56.00	14.44	L1	OFF	19.6
1.613670	---	33.67	46.00	12.33	L1	OFF	19.6
1.613670	40.92	---	56.00	15.08	L1	OFF	19.6
1.954500	---	31.39	46.00	14.61	L1	OFF	19.6
1.954500	40.30	---	56.00	15.70	L1	OFF	19.6
15.934830	---	24.05	50.00	25.95	L1	OFF	19.8
15.934830	28.66	---	60.00	31.34	L1	OFF	19.8

EUT Information

Report NO : 082512
 Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Neutral

Full Spectrum



Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.210750	---	41.65	53.18	11.53	N	OFF	19.5
0.210750	46.11	---	63.18	17.07	N	OFF	19.5
0.304980	---	47.70	50.11	2.41	N	OFF	19.5
0.304980	53.17	---	60.11	6.94	N	OFF	19.5
0.422430	---	39.47	47.40	7.93	N	OFF	19.5
0.422430	43.39	---	57.40	14.01	N	OFF	19.5
0.503250	---	37.27	46.00	8.73	N	OFF	19.5
0.503250	44.08	---	56.00	11.92	N	OFF	19.5
0.543750	---	37.65	46.00	8.35	N	OFF	19.5
0.543750	44.35	---	56.00	11.65	N	OFF	19.5
0.566250	---	37.99	46.00	8.01	N	OFF	19.5
0.566250	44.82	---	56.00	11.18	N	OFF	19.5
0.629250	---	36.09	46.00	9.91	N	OFF	19.5
0.629250	42.95	---	56.00	13.05	N	OFF	19.5
0.847500	---	37.78	46.00	8.22	N	OFF	19.6
0.847500	44.80	---	56.00	11.20	N	OFF	19.6
0.894750	---	36.78	46.00	9.22	N	OFF	19.6
0.894750	43.95	---	56.00	12.05	N	OFF	19.6
0.978000	---	35.77	46.00	10.23	N	OFF	19.6
0.978000	42.94	---	56.00	13.06	N	OFF	19.6
1.198500	---	34.95	46.00	11.05	N	OFF	19.6

1.198500	42.49	---	56.00	13.51	N	OFF	19.6
1.272570	---	35.96	46.00	10.04	N	OFF	19.6
1.272570	43.25	---	56.00	12.75	N	OFF	19.6
1.383450	---	34.10	46.00	11.90	N	OFF	19.6
1.383450	41.14	---	56.00	14.86	N	OFF	19.6
1.614750	---	34.05	46.00	11.95	N	OFF	19.6
1.614750	41.46	---	56.00	14.54	N	OFF	19.6
1.965750	---	33.48	46.00	12.52	N	OFF	19.6
1.965750	41.91	---	56.00	14.09	N	OFF	19.6
16.314000	---	21.22	50.00	28.78	N	OFF	19.9
16.314000	26.33	---	60.00	33.67	N	OFF	19.9



Appendix C. Radiated Spurious Emission

Test Engineer :	Leo Lee, Mancy Chou and Bigshow Wang	Temperature :	22.6~23.2°C
		Relative Humidity :	50~55%



<1Mbps>

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dB μ V/m)	(dB)	(dB μ V/m)	(dB μ V)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2342.13	55.83	-18.17	74	41.5	28.02	17.25	30.94	100	352	P	H
		2310.105	44.96	-9.04	54	30.64	28.08	17.19	30.95	100	352	A	H
	*	2402	96.61	-	-	82.45	27.7	17.37	30.91	100	352	P	H
	*	2402	96.03	-	-	81.87	27.7	17.37	30.91	100	352	A	H
													H
													H
		2386.86	55.76	-18.24	74	41.56	27.78	17.34	30.92	100	40	P	V
		2334.36	44.96	-9.04	54	30.63	28.03	17.24	30.94	100	40	A	V
	*	2402	95.71	-	-	81.55	27.7	17.37	30.91	100	40	P	V
	*	2402	95.08	-	-	80.92	27.7	17.37	30.91	100	40	A	V
BLE CH 19 2440MHz													V
		2341.2	55.67	-18.33	74	41.34	28.02	17.25	30.94	100	223	P	H
		2337.84	45.03	-8.97	54	30.71	28.02	17.24	30.94	100	223	A	H
	*	2440	99.89	-	-	85.73	27.62	17.44	30.9	100	223	P	H
	*	2440	99.29	-	-	85.13	27.62	17.44	30.9	100	223	A	H
		2484.79	55.29	-18.71	74	41.12	27.53	17.52	30.88	100	223	P	H
		2485.24	44.93	-9.07	54	30.76	27.53	17.52	30.88	100	223	A	H
		2336.4	55.87	-18.13	74	41.54	28.03	17.24	30.94	100	49	P	V
		2335.76	44.98	-9.02	54	30.65	28.03	17.24	30.94	100	49	A	V
	*	2440	98.2	-	-	84.04	27.62	17.44	30.9	100	49	P	V
	*	2440	97.59	-	-	83.43	27.62	17.44	30.9	100	49	A	V
		2487.85	55.41	-18.59	74	41.25	27.52	17.52	30.88	100	49	P	V
		2484.25	44.83	-9.17	54	30.66	27.53	17.52	30.88	100	49	A	V



BLE CH 39 2480MHz	*	2480	98.75	-	-	84.58	27.54	17.51	30.88	100	224	P	H
	*	2480	98.19	-	-	84.02	27.54	17.51	30.88	100	224	A	H
		2487	56.09	-17.91	74	41.92	27.53	17.52	30.88	100	224	P	H
		2483.52	45.17	-8.83	54	31	27.53	17.52	30.88	100	224	A	H
													H
													H
	*	2480	94	-	-	79.83	27.54	17.51	30.88	100	125	P	V
	*	2480	93.47	-	-	79.3	27.54	17.51	30.88	100	125	A	V
		2484.4	55.02	-18.98	74	40.85	27.53	17.52	30.88	100	125	P	V
		2483.56	44.95	-9.05	54	30.78	27.53	17.52	30.88	100	125	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	Note	Frequency (MHz)	Level (dB μ V/m)	Over Limit (dB)	Limit Line (dB μ V/m)	Read Level (dB μ V)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		4804	41.36	-32.64	74	58.62	31.21	10.61	59.08	100	0	P	H
													H
													H
													H
		4804	40.71	-33.29	74	57.97	31.21	10.61	59.08	100	0	P	V
													V
													V
													V
BLE CH 19 2440MHz		4880	41.43	-32.57	74	58.71	31.24	10.61	59.13	100	0	P	H
		7320	45.5	-28.5	74	54.91	36.54	12.6	58.55	100	0	P	H
													H
													H
		4880	40.9	-33.1	74	58.18	31.24	10.61	59.13	100	0	P	V
		7320	45.69	-28.31	74	55.1	36.54	12.6	58.55	100	0	P	V
													V
													V
BLE CH 39 2480MHz		4960	40.39	-33.61	74	57.4	31.54	10.63	59.18	100	0	P	H
		7440	46.47	-27.53	74	55.55	36.56	12.74	58.38	100	0	P	H
													H
													H
		4960	41.16	-32.84	74	58.17	31.54	10.63	59.18	100	0	P	V
		7440	46.85	-27.15	74	55.93	36.56	12.74	58.38	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



<2Mbps>

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dB μ V/m)	(dB)	(dB μ V/m)	(dB μ V)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2327.43	56.29	-17.71	74	41.96	28.05	17.22	30.94	400	157	P	H
		2334.045	44.98	-9.02	54	30.65	28.03	17.24	30.94	400	157	A	H
	*	2402	96.49	-	-	82.33	27.7	17.37	30.91	400	157	P	H
	*	2402	94.93	-	-	80.77	27.7	17.37	30.91	400	157	A	H
													H
													H
		2312.52	56.31	-17.69	74	42	28.07	17.19	30.95	174	204	P	V
		2325.54	45.05	-8.95	54	30.72	28.05	17.22	30.94	174	204	A	V
	*	2402	99.62	-	-	85.46	27.7	17.37	30.91	174	204	P	V
	*	2402	98.16	-	-	84	27.7	17.37	30.91	174	204	A	V
BLE CH 19 2440MHz													V
		2334.8	56.8	-17.2	74	42.47	28.03	17.24	30.94	398	182	P	H
		2341.2	44.97	-9.03	54	30.64	28.02	17.25	30.94	398	182	A	H
	*	2440	97.78	-	-	83.62	27.62	17.44	30.9	398	182	P	H
	*	2440	96.28	-	-	82.12	27.62	17.44	30.9	398	182	A	H
		2493.25	56.4	-17.6	74	42.23	27.51	17.53	30.87	398	182	P	H
		2484.43	44.99	-9.01	54	30.82	27.53	17.52	30.88	398	182	A	H
		2332.4	57.53	-16.47	74	43.2	28.04	17.23	30.94	202	210	P	V
		2311.44	45.06	-8.94	54	30.74	28.08	17.19	30.95	202	210	A	V
	*	2440	101.65	-	-	87.49	27.62	17.44	30.9	202	210	P	V
	*	2440	100.19	-	-	86.03	27.62	17.44	30.9	202	210	A	V
		2496.94	56.94	-17.06	74	42.76	27.51	17.54	30.87	202	210	P	V
		2484.25	45.06	-8.94	54	30.89	27.53	17.52	30.88	202	210	A	V



BLE CH 39 2480MHz	*	2480	97.75	-	-	83.58	27.54	17.51	30.88	400	181	P	H
	*	2480	96.29	-	-	82.12	27.54	17.51	30.88	400	181	A	H
		2484.48	56.6	-17.4	74	42.43	27.53	17.52	30.88	400	181	P	H
		2483.52	46.11	-7.89	54	31.94	27.53	17.52	30.88	400	181	A	H
													H
													H
	*	2480	100.03	-	-	85.86	27.54	17.51	30.88	233	213	P	V
	*	2480	98.24	-	-	84.07	27.54	17.51	30.88	233	213	A	V
		2483.68	56.27	-17.73	74	42.1	27.53	17.52	30.88	233	213	P	V
		2483.52	46.6	-7.4	54	32.43	27.53	17.52	30.88	233	213	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	Note	Frequency (MHz)	Level (dB μ V/m)	Over Limit (dB)	Limit Line (dB μ V/m)	Read Level (dB μ V)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		4804	40.38	-33.62	74	57.64	31.21	10.61	59.08	100	0	P	H
													H
													H
													H
		4804	42.09	-31.91	74	59.35	31.21	10.61	59.08	100	0	P	V
													V
													V
													V
BLE CH 19 2440MHz		4880	39.32	-34.68	74	56.6	31.24	10.61	59.13	100	0	P	H
		7320	45.36	-28.64	74	54.77	36.54	12.6	58.55	100	0	P	H
													H
													H
		4880	40.39	-33.61	74	57.67	31.24	10.61	59.13	100	0	P	V
		7320	44.75	-29.25	74	54.16	36.54	12.6	58.55	100	0	P	V
													V
													V
BLE CH 39 2480MHz		4960	40.02	-33.98	74	57.03	31.54	10.63	59.18	100	0	P	H
		7320	45.04	-28.96	74	54.45	36.54	12.6	58.55	100	0	P	H
													H
													H
		4960	39.57	-34.43	74	56.58	31.54	10.63	59.18	100		P	V
		7320	45.45	-28.55	74	54.86	36.54	12.6	58.55	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

2.4GHz BLE (LF)

**Note symbol**

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
			Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.		
		(MHz)	(dB μ V/m)	(dB)	(dB μ V/m)	(dB μ V)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)

2. Level(dB μ V/m) =

Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dB μ V) - Preamp Factor(dB)

3. Over Limit(dB) = Level(dB μ V/m) – Limit Line(dB μ V/m)

For Peak Limit @ 2390MHz:

1. Level(dB μ V/m)

= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dB μ V) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dB μ V) – 35.86 (dB)

= 55.45 (dB μ V/m)

2. Over Limit(dB)

= Level(dB μ V/m) – Limit Line(dB μ V/m)

= 55.45(dB μ V/m) – 74(dB μ V/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dB μ V/m)

= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dB μ V) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dB μ V) – 35.86 (dB)

= 43.54 (dB μ V/m)

2. Over Limit(dB)

= Level(dB μ V/m) – Limit Line(dB μ V/m)

= 43.54(dB μ V/m) – 54(dB μ V/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.



Appendix D. Radiated Spurious Emission Plots

Test Engineer :	Leo Lee, Mancy Chou and Bigshow Wang	Temperature :	22.6~23.2°C
		Relative Humidity :	50~55%

Note symbol





-L	Low channel location
-R	High channel location





<1Mbps>

2.4GHz 2400~2483.5MHz



BLE (Band Edge @ 3m)


BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL : RBW:1000.000KHz VBW:3000.000Hz SWT:Auto Detector : Peak Project : 082512	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL : RBW:1000.000KHz VBW:3000.000Hz SWT:Auto Detector : Peak Project : 082512
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL : RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak Project : 082512	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 HORIZONTAL : RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak Project : 082512












BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - R	
	Horizontal	Fundamental
Peak	 <p>Site : 03CH15-HY Condition : PCMK_BE_74 3m 91200_I5_1620 HORIZONTAL Detector : R8W:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak : 082512</p>	Left blank
Avg.	 <p>Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_I5_1620 HORIZONTAL Detector : R8W:1000.000KHz VBW:0.010KHz SWT:Auto Project : Peak : 082512</p>	Left blank









BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - R	
	Vertical	Fundamental
Peak	 <p>Site : 03CH15-HY Condition : PCMK_BE_74 3m 91200_I5_1620 VERTICAL Detector : R8W1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak : 082512</p>	Left blank
Avg.	 <p>Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_I5_1620 VERTICAL Detector : R8W1000.000KHz VBW:0.010KHz SWT:Auto Project : Peak : 082512</p>	Left blank



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH39 2480MHz	
	Horizontal	Fundamental
Peak	 <p>Site : 03CH15-HY Condition : PCAK_BE_74 3m 91200_I5_1620 HORIZONTAL Detector : R8W:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 082512</p>	 <p>Site : 03CH15-HY Condition : PCAK_I74 3m 91200_I5_1620 HORIZONTAL Detector : R8W:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 082512</p>
Avg.	 <p>Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_I5_1620 HORIZONTAL Detector : R8W:1000.000KHz VBW:0.010KHz SWT:Auto Project : 082512</p>	 <p>Site : 03CH15-HY Condition : AVG_I54 3m 91200_I5_1620 HORIZONTAL Detector : R8W:1000.000KHz VBW:0.010KHz SWT:Auto Project : 082512</p>






BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH39 2480MHz	
	Vertical	Fundamental
Peak	 <p>14 Level (dBuV/m) Date: 2020-10-05 2460 2463.2465.2467.2469.2471.2473.2475.2477.2479.2481.2483.2485.2487.2489.2491.2493.2495.2497. 2500 Frequency (MHz) Site : 03CH15-HY Condition : PCAK_BE_74 3m 91200_I5_1620 VERTICAL Detector : R8W:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 082512</p>	 <p>14 Level (dBuV/m) Date: 2020-10-05 1000 1300. 1500. 1700. 1900. 2100. 2300. 2500. 2700. 3000 Frequency (MHz) Site : 03CH15-HY Condition : PCAK_BE_74 3m 91200_I5_1620 VERTICAL Detector : R8W:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 082512</p>
Avg.	 <p>14 Level (dBuV/m) Date: 2020-10-05 2460 2463.2465.2467.2469.2471.2473.2475.2477.2479.2481.2483.2485.2487.2489.2491.2493.2495.2497. 2500 Frequency (MHz) Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_I5_1620 VERTICAL Detector : R8W:1000.000KHz VBW:0.010KHz SWT:Auto Project : 082512</p>	 <p>14 Level (dBuV/m) Date: 2020-10-05 1000 1300. 1500. 1700. 1900. 2100. 2300. 2500. 2700. 3000 Frequency (MHz) Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_I5_1620 VERTICAL Detector : R8W:1000.000KHz VBW:0.010KHz SWT:Auto Project : 082512</p>




2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Vertical
Peak	 Site : 03CH15-HY Condition : PEAK_74 3m 9120D_15_1620 HORIZONTAL Detector : Peak Project : 082512	 Site : 03CH15-HY Condition : PEAK_74 3m 9120D_15_1620 VERTICAL Detector : Peak Project : 082512
Avg.		












<2Mbps>

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Fundamental
Peak	 <p>Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL : RBW:1000.000kHz VBW:3000.000Hz SWT:Auto Detector : Peak Project : 082512</p>	 <p>Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL : RBW:1000.000kHz VBW:3000.000Hz SWT:Auto Detector : Peak Project : 082512</p>
Avg.	 <p>Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL : RBW:1000.000kHz VBW:0.010KHz SWT:Auto Detector : Peak Project : 082512</p>	 <p>Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 HORIZONTAL : RBW:1000.000kHz VBW:0.010KHz SWT:Auto Detector : Peak Project : 082512</p>








BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - L	
	Horizontal	Fundamental
Peak	<p>Site : 034-H5-HV Condition : PEAK_BE_74_3m_91200,_15,_1620_HORIZONTAL Detector : RBW:1000.0000Hz VBW:3000.0000Hz SWT:Auto Project : Peak : 082512</p>	<p>Site : 034-H5-HV Condition : PEAK_74_3m_91200,_15,_1620_HORIZONTAL Detector : RBW:1000.0000Hz VBW:3000.0000Hz SWT:Auto Project : Peak : 082512</p>
Avg.	<p>Site : 034-H5-HV Condition : AVG_BE_54_3m_91200,_15,_1620_HORIZONTAL Detector : RBW:1000.0000Hz VBW:0.010KHz SWT:Auto Project : Peak : 082512</p>	<p>Site : 034-H5-HV Condition : AVG_54_3m_91200,_15,_1620_HORIZONTAL Detector : RBW:1000.0000Hz VBW:0.010KHz SWT:Auto Project : Peak : 082512</p>




BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - R	
	Horizontal	Fundamental
Peak	 <p>Site : 03CH15-HY Condition : PCMK_BE_74 3m 91200_I5_1620 HORIZONTAL Detector : R8W:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak : 082512</p>	Left blank
Avg.	 <p>Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_I5_1620 HORIZONTAL Detector : R8W:1000.000KHz VBW:0.010KHz SWT:Auto Project : Peak : 082512</p>	Left blank







BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - L	
	Vertical	Fundamental
Peak	 <p>Site : 03CH15-HY Condition : PCAK_BE_74 3m 91200_I5_1620 VERTICAL Detector : R8W:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Project : 082512</p>	 <p>Site : 03CH15-HY Condition : PCAK_BE_74 3m 91200_I5_1620 VERTICAL Detector : R8W:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Project : 082512</p>
Avg.	 <p>Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_I5_1620 VERTICAL Detector : R8W:1000.000KHz VBW:0.010KHz SWT:Auto Project : Peak Project : 082512</p>	 <p>Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_I5_1620 VERTICAL Detector : R8W:1000.000KHz VBW:0.010KHz SWT:Auto Project : Peak Project : 082512</p>






BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - R	
	Vertical	Fundamental
Peak	 <p>Site : 03CH15-HV Condition : PCMK_BE_74 3m 91200_I5_1620 VERTICAL Detector : R8W:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 082512</p>	Left blank
Avg.	 <p>Site : 03CH15-HV Condition : AVG_BE_54 3m 91200_I5_1620 VERTICAL Detector : R8W:1000.000KHz VBW:0.010KHz SWT:Auto Project : 082512</p>	Left blank



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH39 2480MHz	
	Horizontal	Fundamental
Peak	 <p>Site : 03CH15-HY Condition : PCAK_BE_74 3m 91200_I5_1620 HORIZONTAL Detector : R8W:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 082512</p>	 <p>Site : 03CH15-HY Condition : PCAK_74 3m 91200_I5_1620 HORIZONTAL Detector : R8W:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 082512</p>
Avg.	 <p>Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_I5_1620 HORIZONTAL Detector : R8W:1000.000KHz VBW:0.010KHz SWT:Auto Project : 082512</p>	 <p>Site : 03CH15-HY Condition : AVG_54 3m 91200_I5_1620 HORIZONTAL Detector : R8W:1000.000KHz VBW:0.010KHz SWT:Auto Project : 082512</p>






BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH39 2480MHz	
	Vertical	Fundamental
Peak	 Site : 03CH15-HY Condition : PCAK_BE_74 3m 91200_I5_1620 VERTICAL Detector : R8W:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 082512	 Site : 03CH15-HY Condition : PCAK_BE_74 3m 91200_I5_1620 VERTICAL Detector : R8W:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 082512
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_I5_1620 VERTICAL Detector : R8W:1000.000KHz VBW:0.010KHz SWT:Auto Project : 082512	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_I5_1620 VERTICAL Detector : R8W:1000.000KHz VBW:0.010KHz SWT:Auto Project : 082512



2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Vertical
Peak	 <p>Site : 03CH15-HY Condition : PEAK_74 3m 9120D_15_1620 HORIZONTAL Detector : Peak Project : 082512</p>	 <p>Site : 03CH15-HY Condition : PEAK_74 3m 9120D_15_1620 VERTICAL Detector : Peak Project : 082512</p>
Avg.		







BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH39 2480MHz	
	Horizontal	Vertical
Peak	<p>Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 082512</p>	<p>Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 082512</p>



Emission below 1GHz

2.4GHz BLE (LF)

BLE	2.4GHz 2400~2483.5MHz	
	BLE LF	
	Horizontal	Vertical
QP / Peak	 <p>Site : 03CH15-HY Condition : QP 3m B1L06_15_41912 HORIZONTAL Detector : Peak Project : 082512</p>	 <p>Site : 03CH15-HY Condition : QP 3m B1L06_15_41912 VERTICAL Detector : Peak Project : 082512</p>



Appendix E. Duty Cycle Plots

Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting	Duty Factor(dB)
Bluetooth -LE 1Mbps	100	-	-	10Hz	0.00
Bluetooth -LE 2Mbps	100	-	-	10Hz	0.00

