



toll-free: (866) 311-3268  
fax: (480) 926-3598  
<http://www.flomlabs.com>  
[info@flomlabs.com](mailto:info@flomlabs.com)

Date: June 7, 2007

Federal Communications Commission  
Via: Electronic Filing

Attention: Authorization & Evaluation Division

Applicant: Novatel Wireless Inc.  
Equipment: PKRNVWE725 Collocated with QDS-BRCM1020 802.11.b,g  
FCC ID: PKRNVWE725  
FCC Rules: Radio Frequency Radiation Exposure Limits  
47 CFR 1.1310

MPE - Mobiles

X

Fixed Based Station       

Gentlemen:

On behalf of the Applicant, enclosed please find the Supplemental Test Data Report, the whole for Environmental Assessment (MPE) of the referenced equipment as shown.

We trust the same is in order. Should you need any further information, kindly contact the writer who is authorized to act as agent.

Sincerely yours,

Hoosamuddin S. Bandukwala, Lab Director

enclosure(s)  
cc: Applicant  
HSB/jhe

Flom Test Labs  
3356 N. San Marcos Place, Suite 107  
Chandler, Arizona 85225-7176  
(866) 311-3268 phone, (480) 926-3598 fax

p0750023, d0760016

## Environmental Assessment

for

### Mobiles

for

**FCC ID:** FCC ID: PKRNVWE725

Model:PKRNVWE725

to

**Federal Communications Commission**

**47 CFR 1.1310 (MPE)**

Radio Frequency Radiation Exposure Limits


**Date Of Report:** June 7, 2007

**On the Behalf of the Applicant:** Novatel Wireless Inc.

**At the Request of:** Novatel Wireless Inc.  
9645 Scranton Rd, Suite 205  
San Diego, CA 92121

Attention of: John Jiang, Project Manager  
888-888-9231; FAX: -2888  
Email: [jjiang@novatelwireless.com](mailto:jjiang@novatelwireless.com)

Supervised By:



Hoosamuddin S. Bandukwala, Lab Director

## Table of Contents

Rule	Description	Page
	Test Report	1
	Identification of the Equipment Under Test	2
	Standard Test Conditions and Engineering Practices	3
1.1310	Environmental Assessment	4

Required information per ISO 17025-2005, paragraph 5.0:

a)

**Test Report (Supplemental)**

b) Laboratory:  
(FCC: 31040/SIT)  
(Canada: IC 2044)

Flom Test Labs  
3356 N. San Marcos Place, Suite 107  
Chandler, AZ 85225

c) Report Number:

d0760016

d) Client:

Novatel Wireless Inc.  
9645 Scranton Rd, Suite 205  
San Diego, CA 92121

e) Identification:

PKRNVWE725  
FCC ID: PKRNVWE725

Description:

Dell laptop XPS M1330

f) EUT Condition:

Not required unless specified in individual tests.

g) Report Date:

June 7, 2007

h, j, k):

As indicated in individual tests.


i) Sampling method:

No sampling procedure used.

l) Uncertainty:

In accordance with MFA internal quality manual.

m) Supervised by:



Hoosamuddin S. Bandukwala, Lab Director

n) Results:

The results presented in this report relate only to the item tested.

o) Reproduction:

This report must not be reproduced, except in full, without written permission from this laboratory.

**Identification of the Equipment Under Test (EUT)**

**Name and Address of Applicant:** Novatel Wireless Inc.  
 9645 Scranton Rd, Suite 205  
 San Diego, CA 92121

**Manufacturer:** Novatel Wireless Inc.  
 9645 Scranton Rd, Suite 205  
 San Diego, CA 92121

**FCC ID:** PKRNVWE725

**Model Number:** PKRNVWE725

**Description:** Dell laptop XPS M1330

**Type of Emission:** CDMA collocated with 802.11.b,g

**Frequency Range, MHz:** CDMA 824 - 848 and 1851 - 1908  
 802.11.b,g 2412 – 2472

**Power Rating, Watts:** 0.296  
 Switchable       Variable       N/A

**Modulation:**  
 AMPS  
 TDMA  
 CDMA  
 OTHER

**Antenna:**  
 Helical  
 Monopole  
 Whip  
 Other

**Note:** For RF Safety test antenna gain taken at the upper range of expected gain (i.e. 0 dBd) and RF Power set to highest nominal power across all channels.

## Standard Test Conditions and Engineering Practices

Except as noted herein, the following conditions and procedures were observed during the testing:

In accordance with ANSI C63.4-1992/2000, section 6.1.9, and unless otherwise indicated in the specific measurement results, the ambient temperature of the actual EUT was maintained within the range of 10° to 40°C (50° to 104 °F) unless the particular equipment requirements specify testing over a different temperature range. Also, unless otherwise indicated, the humidity levels were in the range of 10% to 90% relative humidity.

Prior to testing, the EUT was tuned up in accordance with the manufacturer's alignment procedures. All external gain controls were maintained at the position of maximum and/or optimum gain throughout the testing.

Measurement results, unless otherwise noted, are worst-case measurements.

### A2LA

"A2LA has accredited Flom Test Labs, Inc. Chandler, AZ for technical competence in the field of Electrical testing. The accreditation covers the specific tests and types of tests listed on the agreed scope of accreditation. This laboratory meets the requirements of ISO 17025:2005 'General Requirements for the Competence of Testing and Calibration Laboratories' and any additional program requirements in the identified field of testing."

Please refer to [www.a2la.org](http://www.a2la.org) for current scope of accreditation.

Certificate number: 2152.01



<b>Name of Test:</b>	Environmental Assessment	
<b>Specification:</b>	FCC: 47 CFR 1.1310	
<b>Measurement Guide:</b>	ANSI/IEEE C95.1 1992	
<b>Name of Test:</b>	R.F. Radiation Exposure	
FCC Rules:	1.1307, 1.1310, 1.1311, 2.1091	
Description, EUT:	See page 2 of Test Report	
Limits: Uncontrolled Exposure 47 CFR 1.1310 Table 1, (B)	0.3-1.234 MHz: 1.34-30 MHz: 30-300 MHz: 300-1500 MHz: 1500-100,000 MHz:	Limit [ $\text{mW/cm}^2$ ] = 100 Limit [ $\text{mW/cm}^2$ ] = $(180/f^2)$ Limit [ $\text{mW/cm}^2$ ] = 0.2 Limit [ $\text{mW/cm}^2$ ] = $f/1500$ Limit [ $\text{mW/cm}^2$ ] = 1.0
Test Frequencies, MHz Power, Conducted, mW Antenna Gain Antenna Model Distance cm	824 – 848 = 291 = 3 dBi Planer Inverted F Antenna 20	
Limit Calculations	Limit <sub>[mW/cm<sup>2</sup>]</sub> = 0.549	
Test Frequencies, MHz Power, Conducted, mW Antenna Gain Antenna Model Distance cm	1851 - 1908 = 296 = 3 dBi Planer Inverted F Antenna 20	
Limit Calculations	Limit <sub>[mW/cm<sup>2</sup>]</sub> = 1.0	

**PKRNVWE725 CDMA**

CDMA Frequency MHz	TX Power (m)W	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
824 – 848	291	0.173	0.549	Pass
1851 - 1908	296	0.177	1.0	Pass


**QDS-BRCM1020 802.11.b,g**

802.11 b,g Frequency MHz	TX Power (mW)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
2412 - 2472	414	0.247	1.0	Pass

**PKRNVWE725 CDMA Collocated with QDS-BRCM1020 802.11.b,g**

CDMA Frequency MHz	802.11.b,g Frequency MHz	CDMA Power Density (mW/cm <sup>2</sup> )	802.11.b,g Power Density (mW/cm <sup>2</sup> )	Total Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
824 – 848	2412 – 2472	0.173	0.247	0.420	0.549	Pass
1851 - 1908	2412 – 2472	0.177	0.247	0.424	1.0	Pass

End of Test Report



Supervised By:


Hoosamuddin S. Bandukwala, Lab Director

**Testimonial  
and  
Statement of Certification**

**This is to certify that:**

1. **That** the application was prepared either by, or under the direct supervision of, the undersigned.
2. **That** the technical data supplied with the application was taken under my direction and supervision.
3. **That** the data was obtained on representative units, randomly selected.
4. **That**, to the best of my knowledge and belief, the facts set forth in the application and accompanying technical data are true and correct.

Certifying Engineer:



Hoosamuddin S. Bandukwala, Lab Director