

## RF Exposure Evaluation - Maximum Permissible Exposure (MPE)

### 1. Introduction

In this document, we try to prove the safety of radiation harmfulness to the human body. The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1210 is followed. The Gain of the antenna used in this product is measured by power meter. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

### 2. RF Exposure Limit

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b).

#### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (Minutes)
(A) Limits For Occupational / Control Exposures				
30-300	61.4	.163	1.0	6
300-1500	...	...	F/300	6
1500-100,000	...	...	5	6
(B) Limits For General Population / Uncontrolled Exposure				
30-300	27.5	.073	.2	30
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

### 3. Friis Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4\pi r^2)$

Where

$P_d$  = power density in  $\text{mW/cm}^2$

$P_{out}$  = output power to antenna in mW

$G$  = gain of antenna in linear scale

$\pi = 3.1416$

$r$  = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1  $\text{mW/cm}^2$ . If we know the maximum Gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance  $r$  where the MPE limit is reached.

Ref.: David K. Cheng, Field and Wave Electromagnetics, Second Edition, Page 640, Eq. (11.133)

PCTEST MPE REPORT	FCC CERTIFICATION REPORT			REVIEWED BY: Quality Manager
TEST REPORT S/N: 90.230808390-R1.PM3	TEST DATES: Aug. 19-20, 2003	EUT TYPE: Genex VHF FM Transceiver	FCC ID: PM3MT800	Page 1 of 2
© 2003 PCTEST Engineering Laboratory, Inc.				



#### 4. EUT Operating Condition

Software provided by the client enabled the EUT to transmit and receive data at lowest, middle, and highest channel individually.

#### 5. Climate Condition

The temperature and related humidity: 22°C and 78% RH

#### 6. Test Results (Antenna Configuration)

6.1 Output Power into Antenna & RF Exposure Distance: With 0 dBi antenna

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm <sup>2</sup> )
17	153.03	24,000	.0865

#### 7. Conclusion

The device meets the mobile 60cm. separation distance as specified in Section 2.1091 of the FCC Rules and an appropriate RF exposure compliance statement will be placed in the users manual.

PCTEST MPE REPORT	FCC CERTIFICATION REPORT			REVIEWED BY: Quality Manager
TEST REPORT S/N: 90.230808390-R1.PM3	TEST DATES: Aug. 19-20, 2003	EUT TYPE: Genex VHF FM Transceiver	FCC ID: PM3MT800	Page 2 of 2