



SENTON

Choose certainty.
Add value.

November 10,
2009

Prüfbericht / Test Report

Nr. / No. 69555-00838-1 (Edition 1)

Applicant: Amphony (Deutschland) GmbH

Type of equipment: Transmitter for Wireless Headphones

Type designation: 5.8 GHz Digital Wireless Headphones-Transmitter

Order No.:

Test standards: FCC Code of Federal Regulations,
CFR 47, Part 15,
Sections 15.205, 15.207, 15.215 and 15.249

Industry Canada Radio Standards Specifications
RSS-Gen Issue 2, Section 7.2.2 and
RSS-210 Issue 7, Sections 2.2, A2.9 (Category I Equipment)

Table of Contents

1	Description of the Equipment Under Test (EUT).....	3
2	Administrative Data	4
3	Identification of the Test Laboratory.....	5
4	Summary	6
5	Operation Mode and Configuration of EUT.....	7
6	Measurement Procedures	8
6.1	Bandwidth Measurements	8
6.2	Radiated Emission Measurement 9 kHz to 30 MHz.....	9
6.3	Radiated Emission in Fully or Semi Anechoic Room.....	11
6.4	Radiated Emission at Open Field Test Site	13
7	Photographs Taken During Testing.....	15
8	Test Results	20
8.1	Occupied Bandwidth	22
8.2	Bandwidth of the Emission.....	26
8.3	Designation of Emissions.....	28
8.4	Restricted Bands of Operation.....	29
8.5	Radiated Emission Measurement 9 kHz to 30 MHz.....	31
8.6	Radiated Emission Measurement 30 MHz to 40 GHz.....	32
8.7	Exposure of Humans to RF Fields	34
9	Referenced Regulations	36
10	Revision History	38
11	Charts taken during testing	39

1 Description of the Equipment Under Test (EUT)

General data of EUT	
Type designation ¹ :	5.8 GHz Digital Wireless Headphones-Transmitter
Parts ² :	
Serial number(s):	0001
Manufacturer:	Amphony (Deutschland) GmbH
Type of equipment:	Transmitter for Wireless Headphones
Version:	As received
FCC ID:	
Additional parts/accessories:	
Technical data of EUT	
Application frequency range:	5725 - 5875 MHz
Frequency range:	5800 MHz
Operating frequency:	5800 MHz
Type of modulation:	ASK
Pulse train:	Not applicable
Pulse width:	Not applicable
Number of RF-channels:	1
Channel spacing:	Not applicable
Designation of emissions ³ :	47M0A9D
Type of antenna:	Integrated
Size/length of antenna:	2.5 x 1.7 cm
Connection of antenna:	<input type="checkbox"/> detachable <input checked="" type="checkbox"/> not detachable
Type of power supply:	DC supply
Specifications for power supply:	nominal voltage: 28 V

¹ Type designation of the system if EUT consists of more than one part.

² Type designations of the parts of the system, if applicable.

³ Also known as "Class of Emission".

2 Administrative Data

Application details

Applicant (full address):	Amphony (Deutschland) GmbH Annenstraße 26 D-10179 Berlin
Contact person:	Mr. Jens Kurrat
Order number:	
Receipt of EUT:	October 19, 2009
Date(s) of test:	October - November 2009
Note(s):	

Report details

Report number:	69555-00838-1
Edition:	1
Issue date:	November 10, 2009

3 Identification of the Test Laboratory

Details of the Test Laboratory	
Company name:	TÜV SÜD SENTON GmbH
Address:	Aeussere Fruehlingstrasse 45 D-94315 Straubing Germany
Laboratory accreditation:	DAR-Registration No. DAT-PL-171/94-03
FCC test site registration number	90926
Industry Canada test site registration:	3050A-1
Contact person:	Mr. Johann Roidt
	Phone: +49 9421 5522-0 Fax: +49 9421 5522-99

4 Summary

Summary of test results

The tested sample complies with the requirements set forth in the
Code of Federal Regulations CFR 47, Part 15, Sections 15.205, 15.215 and 15.249
of the Federal Communication Commission (FCC) and the
**Radio Standards Specifications
RSS-210 Issue 7, Sections 2.2, A2.9 (Category I Equipment)**
of Industry Canada (IC).

Personnel involved in this report

Laboratory Manager:



Mr. Johann Roidt

Responsible for testing:



Mr. Martin Steindl

Responsible for test report:

Mr. Martin Steindl

5 Operation Mode and Configuration of EUT

Operation Mode

The EUT was set to continuous transmitting mode.

Configuration of EUT

The EUT was configured as stand alone device. The EUT was configured with the original shielded wiring harness.

List of ports and cables

Port	Description	Classification ⁴	Cable type	Cable length
1	DC 28 V supply	dc power	Shielded	1.2 m
2	Audio interface	signal/control port	Shielded	1.2 m

List of devices connected to EUT

Item	Description	Type Designation	Serial no. or ID	Manufacturer
	Not applicable			

List of support devices

Item	Description	Type Designation	Serial no. or ID	Manufacturer
	Not applicable			

⁴ Ports shall be classified as ac power, dc power or signal/control port

6 Measurement Procedures

6.1 Bandwidth Measurements

Measurement Procedure:	
Rules and specifications:	CFR 47 Part 2, section 2.202(a) CFR 47 Part 15, section 15.215(c) IC RSS-Gen Issue 2, sections 4.6.1 and 4.6.2 IC RSS-210 Issue 7, section A1.1.3 ANSI C63.4, annex H.6
Guide:	ANSI C63.4 / IC RSS-Gen Issue 2, sections 4.6.1 and 4.6.2
Measurement setup:	<input type="checkbox"/> Conducted: See below <input checked="" type="checkbox"/> Radiated: Radiated Emission in Fully or Semi Anechoic Room (6.3)
<p>If antenna is detachable bandwidth measurements shall be performed at the antenna connector (conducted measurement) when the transmitter is adjusted in accordance with the tune-up procedure, if applicable. The RF output terminals are connected to a spectrum analyzer. If required, a resistive matching network equal to the impedance specified or employed for the antenna is used as well as dc block and appropriate attenuators (50 Ohms). The electrical characteristics of the radio frequency load attached to the output terminals shall be stated, if applicable.</p> <p>If radiated measurements are performed the same test setups and instruments are used as with radiated emission measurements for the appropriate frequency range.</p> <p>The analyzer settings are specified by the test description of the appropriate test record(s).</p>	

6.2 Radiated Emission Measurement 9 kHz to 30 MHz

Measurement Procedure:

Rules and specifications: CFR 47 Part 15, sections 15.215(b) and 15.249(d)
 IC RSS-210 Issue 7, section A2.9(b)

Guide: ANSI C63.4

Radiated emission in the frequency range 9 kHz to 30 MHz is measured using an active loop antenna. First the whole spectrum of emission caused by the equipment is recorded at a distance of 3 meters in a fully or semi anechoic room with the detector of the spectrum analyzer or EMI receiver set to peak. This configuration is also used for recording the spectrum of intentional radiators.


Hand-held or body-worn devices are rotated through three orthogonal axes to determine which attitude and configuration produces the highest emission relative to the limit and therefore shall be used for final testing.

EUT is rotated all around to find the maximum levels of emissions. Equipment and cables are placed and moved within the range of position likely to find their maximum emissions.

If worst case emission of the EUT cannot be recorded with EUT in standard position and loop antenna in vertical polarization the EUT (or the radiating part of the EUT) is rotated by 90 degrees instead of changing the loop antenna to horizontal polarization. This procedure is selected to minimize the influence of the environment (e.g. effects caused by the floor especially with longer distances).

Final measurement is performed at a test distance D of 30 meters using an open field test site. In case the regulation requires testing at other distances, the result is extrapolated by either making measurements at an additional distance D of 10 meters to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). In cases of very low emissions measurements are performed at shorter distances and results are extrapolated to the required distance. The provisions of CFR 47 Part 15 sections 15.31(d) and (f)(2) apply. According to CFR 47 Part 15 section 15.209(d) final measurement is performed with detector function set to quasi-peak except for the frequency bands 9 to 90 kHz and 110 to 490 kHz where, for non-pulsed operation, average detector is employed.

If the radiated emission limits are expressed in terms of the average value of the emission there also is a peak limit corresponding to 20 dB above the maximum permitted average limit. Additionally, if pulsed operation is employed, the average field strength is determined by averaging over one complete pulse train, including blanking intervals, as specified in CFR 47 Part 15 section 15.35(c). If the pulse train exceeds 0.1 second that 0.1 second interval during which the value of the emission is at its maximum is selected for calculation. The pulse train correction is added to the peak value of the emission to get the average value.



Test instruments used:

Used	Type	Model	Serial No. or ID	Manufacturer
<input checked="" type="checkbox"/>	Spectrum Analyzer	FSP 30	100063	Rohde & Schwarz
<input type="checkbox"/>	EMI test receiver	ESMI	839379/013 839587/006	Rohde & Schwarz
<input checked="" type="checkbox"/>	Test receiver	ESHS 10	860043/016	Rohde & Schwarz
<input type="checkbox"/>	Preamplifier	CPA9231A	3393	Schaffner
<input checked="" type="checkbox"/>	Loop antenna	HFH2-Z2	882964/1	Rohde & Schwarz
<input checked="" type="checkbox"/>	Fully anechoic room	No. 2	1452	Albatross Projects
<input type="checkbox"/>	Semi-anechoic room	No. 3	1453	Siemens
<input checked="" type="checkbox"/>	Open field test site	EG 1	1450	Senton

6.3 Radiated Emission in Fully or Semi Anechoic Room

Measurement Procedure:

Rules and specifications: CFR 47 Part 15, sections 15.215(b) and 15.249
IC RSS-210 Issue 7, section A2.9

Guide: ANSI C63.4

Radiated emission in fully or semi anechoic room is measured in the frequency range from 30 MHz to the maximum frequency as specified in CFR 47 Part 15 section 15.33.

Measurements are made in both the horizontal and vertical planes of polarization in a fully anechoic room using a spectrum analyzer with the detector function set to peak and resolution as well as video bandwidth set to 100 kHz (below 1 GHz) or 1 MHz (above 1 GHz).

Testing up to 1 GHz is performed with a linear polarized logarithmic periodic antenna combined with a 4:1 broadband dipole ("Trilog broadband antenna"). For testing above 1 GHz horn antennas are used.


All tests below 8.2 GHz are performed at a test distance D of 3 meters. For higher frequencies the test distance may be reduced (e.g. to 1 meter) due to the sensitivity of the measuring instrument(s) and the test results are calculated according to CFR 47 Part 15 section 15.31(f)(1) using an extrapolation factor of 20 dB/decade. If required, preamplifiers are used for the whole frequency range. Special care is taken to avoid overload, using appropriate attenuators and filters, if necessary.

If the radiated emission limits are expressed in terms of the average value of the emission there also is a peak limit corresponding to 20 dB above the maximum permitted average limit. Additionally, if pulsed operation is employed, the average field strength is determined by averaging over one complete pulse train, including blanking intervals, as specified in CFR 47 Part 15 section 15.35(c). If the pulse train exceeds 0.1 second that 0.1 second interval during which the value of the emission is at its maximum is selected for calculation. The pulse train correction is added to the peak value of the emission to get the average value.

Hand-held or body-worn devices are rotated through three orthogonal axes to determine which attitude and configuration produces the highest emission relative to the limit and therefore shall be used for final testing.

During testing the EUT is rotated all around to find the maximum levels of emissions. Equipment and cables are placed and moved within the range of position likely to find their maximum emissions.

For final testing below 1 GHz an open field test-site is used and the plots recorded in the fully or semi anechoic room are indicated as prescans.



Test instruments used:

Used	Type	Model	Serial No. or ID	Manufacturer
<input checked="" type="checkbox"/>	Spectrum Analyzer	FSP 30	100063	Rohde & Schwarz
<input type="checkbox"/>	EMI test receiver	ESPI7	101018	Rohde & Schwarz
<input checked="" type="checkbox"/>	EMI test receiver	ESMI	839379/013 839587/006	Rohde & Schwarz
<input checked="" type="checkbox"/>	Preamplifier	CPA9231A	3393	Schaffner
<input type="checkbox"/>	Preamplifier	R14601		Advantest
<input checked="" type="checkbox"/>	Preamplifier 1-8 GHz	AFS3-00100800-32-LN	847743	Miteq
<input type="checkbox"/>	Preamplifier 0.5-8 GHz	AMF-4D-005080-25-13P	860149	Miteq
<input checked="" type="checkbox"/>	Preamplifier 8-18 GHz	ACO/180-3530	32641	CTT
<input checked="" type="checkbox"/>	External Mixer	WM782A	845881/005	Tektronix
<input checked="" type="checkbox"/>	Harmonic Mixer Accessories	FS-Z30	843389/007	Rohde & Schwarz
<input checked="" type="checkbox"/>	Trilog broadband antenna	VULB 9163	9163-188	Schwarzbeck
<input checked="" type="checkbox"/>	Horn antenna	3115	9508-4553	EMCO
<input type="checkbox"/>	Horn antenna	3160-03	9112-1003	EMCO
<input type="checkbox"/>	Horn antenna	3160-04	9112-1001	EMCO
<input type="checkbox"/>	Horn antenna	3160-05	9112-1001	EMCO
<input checked="" type="checkbox"/>	Horn antenna	3160-06	9112-1001	EMCO
<input checked="" type="checkbox"/>	Horn antenna	3160-07	9112-1008	EMCO
<input checked="" type="checkbox"/>	Horn antenna	3160-08	9112-1002	EMCO
<input checked="" type="checkbox"/>	Horn antenna	3160-09	9403-1025	EMCO
<input checked="" type="checkbox"/>	Horn antenna	3160-10	399185	EMCO
<input checked="" type="checkbox"/>	Fully anechoic room	No. 2	1452	Albatross Projects
<input checked="" type="checkbox"/>	Semi-anechoic room	No. 3	1453	Siemens

6.4 Radiated Emission at Open Field Test Site

Measurement Procedure:

Rules and specifications: CFR 47 Part 15, sections 15.215(b) and 15.249
 IC RSS-210 Issue 7, section A2.9


Guide: ANSI C63.4

Radiated emission at open field test site is measured in the frequency range 30 MHz to 1 GHz using a biconical antenna up to 300 MHz and a logarithmic periodic antenna above. The measurement bandwidth of the test receiver is set to 120 kHz with quasi-peak detector selected.

If the radiated emission limits are expressed in terms of the average value of the emission there also is a peak limit corresponding to 20 dB above the maximum permitted average limit. Additionally, if pulsed operation is employed, the average field strength is determined by averaging over one complete pulse train, including blanking intervals, as specified in CFR 47 Part 15 section 15.35(c). If the pulse train exceeds 0.1 second that 0.1 second interval during which the value of the emission is at its maximum is selected for calculation. The pulse train correction is added to the peak value of the emission to get the average value.

Hand-held or body-worn devices are tested in the position producing the highest emission relative to the limit as verified by prescans in the fully anechoic room. EUT is rotated all around and receiving antenna is raised and lowered within 1 meter to 4 meters to find the maximum levels of emission. Equipment and cables are placed and moved within the range of position likely to find their maximum emissions.

For measuring emissions of intentional radiators and receivers a test distance D of 3 meters is selected. Testing of unintentional radiators is performed at a distance of 10 meters. If limits specified for 3 meters shall be used for measurements performed at 10 meters distance the limits are calculated according to CFR 47 Part 15 section 15.31(d) and (f)(1) using an inverse linear-distance extrapolation factor of 20 dB/decade.





Test instruments used:


Used	Type	Model	Serial No. or ID	Manufacturer
<input checked="" type="checkbox"/>	EMI receiver	EG 1	ESVP	Rohde & Schwarz
<input type="checkbox"/>	EMI receiver		ESVP	Rohde & Schwarz
<input checked="" type="checkbox"/>	Biconical antenna	EG 1	HK 116	Rohde & Schwarz
<input checked="" type="checkbox"/>	Log. per. antenna	EG 1	HL 223	Rohde & Schwarz
<input checked="" type="checkbox"/>	Open field test site		EG 1	Senton

7 Photographs Taken During Testing

Test setup for radiated emission measurement 9 kHz – 30 MHz



Test setup for radiated emission measurement (fully anechoic room)



Test setup for radiated emission measurement (open field test site)



**Test setup for radiated emission measurement
(open field test site) - continued -**



8 Test Results

FCC CFR 47 Parts 2 and 15			
<i>Section(s)</i>	<i>Test</i>	<i>Page</i>	<i>Result</i>
2.1046(a)	Conducted output power	---	Not applicable
2.202(a)	Occupied bandwidth	22	Recorded
15.215(c)	Bandwidth of the emission	26	Test passed
2.201, 2.202	Class of emission	28	Calculated
15.35(c)	Pulse train measurement for pulsed operation	---	Not applicable
15.205(a)	Restricted bands of operation	29	Test passed
15.207	Conducted AC powerline emission 150 kHz to 30 MHz	---	Not applicable
15.205(b) 15.249	Radiated emission 9 kHz to 30 MHz	31	Test passed
15.205(b) 15.215(b) 15.249	Radiated emission 30 MHz to 40 GHz	32	Test passed

IC RSS-Gen Issue 2

Section(s)	Test	Page	Result
4.8	Transmitter output power (conducted)	---	Not applicable
4.6.1	Occupied Bandwidth	22	Recorded
3.2(h), 8	Designation of emissions	28	Calculated
4.5	Pulsed operation	---	Not applicable
7.2.2	Transmitter AC power lines conducted emissions 150 kHz to 30 MHz	---	Not applicable
5.5	Exposure of Humans to RF Fields	34	Exempted from SAR and RF evaluation

IC RSS-210 Issue 7


Section(s)	Test	Page	Result
2.2(a)	Restricted bands and unwanted emission frequencies	29	Test passed
2.2(b)(c), 2.6 A2.9	Unwanted emissions 9 kHz to 30 MHz	31	Test passed
2.2(b)(c), 2.6 A2.9	Unwanted emissions 30 MHz to 40 GHz	32	Test passed

8.1 Occupied Bandwidth

Rules and specifications:	CFR 47 Part 2, section 2.202(a) ANSI C63.4, annex H.6								
Guide:	ANSI C63.4								
Description:	<p>The occupied bandwidth according to CFR 47 Part 2, section 2.202(a), is measured as the 99% emission bandwidth, i.e. below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5% of the total mean power radiated by a given emission.</p> <p>The occupied bandwidth according to ANSI C63.4, annex H.6; is measured as the frequency range defined by the points that are 26 dB down relative to the maximum level of the modulated carrier.</p> <p>The resolution bandwidth of the spectrum analyzer shall be set to a value greater than 5.0% of the allowed bandwidth. If no bandwidth specifications are given, the following guidelines are used:</p> <table border="1"><thead><tr><th>Fundamental frequency</th><th>Minimum resolution bandwidth</th></tr></thead><tbody><tr><td>9 kHz to 30 MHz</td><td>1 kHz</td></tr><tr><td>30 MHz to 1000 MHz</td><td>10 kHz</td></tr><tr><td>1000 MHz to 40 GHz</td><td>100 kHz</td></tr></tbody></table> <p>The video bandwidth shall be at least three times greater than the resolution bandwidth.</p>	Fundamental frequency	Minimum resolution bandwidth	9 kHz to 30 MHz	1 kHz	30 MHz to 1000 MHz	10 kHz	1000 MHz to 40 GHz	100 kHz
Fundamental frequency	Minimum resolution bandwidth								
9 kHz to 30 MHz	1 kHz								
30 MHz to 1000 MHz	10 kHz								
1000 MHz to 40 GHz	100 kHz								
Measurement procedure:	Bandwidth Measurements (6.1)								

Comment:	
Date of test:	October 27, 2009
Test site:	Fully anechoic room, cabin no. 2

Occupied Bandwidth (99 %):



Date: 27.OCT.2009 10:15:43


Occupied Bandwidth (99 %): **54.4 MHz**

Occupied Bandwidth (continued)

Rules and specifications:	IC RSS-Gen Issue 2, section 4.6.1
Guide:	IC RSS-Gen Issue 2, section 4.6.1
Description:	<p>If not specified in the applicable RSS the occupied bandwidth is measured as the 99% emission bandwidth.</p> <p>The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts. The resolution bandwidth shall be set to as close to 1% of the selected span as is possible without being below 1%. The video bandwidth shall be set to 3 times the resolution bandwidth.</p> <p>The trace data points are recovered and are directly summed in linear terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached and that frequency recorded. The process is repeated for the highest frequency data points. This frequency is also recorded. The span between the two recorded frequencies is the occupied bandwidth.</p>
Measurement procedure:	Bandwidth Measurements (6.1)

Comment:	
Date of test:	October 27, 2009
Test site:	Fully anechoic room, cabin no. 2

Occupied Bandwidth (99 %):




Date: 27.OCT.2009 10:15:43

Occupied Bandwidth (99 %): **54.4 MHz**

8.2 Bandwidth of the Emission

Rules and specifications:	CFR 47 Part 15, section 15.215(c)								
Guide:	ANSI C63.4								
Description:	<p>The 20 dB bandwidth of the emission is measured as the frequency range defined by the points that are 20 dB down relative to the maximum level of the modulated carrier.</p> <p>For intentional radiators operating under the alternative provisions to the general emission limits the requirement to contain the 20 dB bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.</p> <p>The resolution bandwidth of the spectrum analyzer shall be set to a value greater than 5.0% of the allowed bandwidth. If no bandwidth specifications are given, the following guidelines are used:</p> <table border="1"><thead><tr><th>Fundamental frequency</th><th>Minimum resolution bandwidth</th></tr></thead><tbody><tr><td>9 kHz to 30 MHz</td><td>1 kHz</td></tr><tr><td>30 MHz to 1000 MHz</td><td>10 kHz</td></tr><tr><td>1000 MHz to 40 GHz</td><td>100 kHz</td></tr></tbody></table> <p>The video bandwidth shall be at least three times greater than the resolution bandwidth.</p>	Fundamental frequency	Minimum resolution bandwidth	9 kHz to 30 MHz	1 kHz	30 MHz to 1000 MHz	10 kHz	1000 MHz to 40 GHz	100 kHz
Fundamental frequency	Minimum resolution bandwidth								
9 kHz to 30 MHz	1 kHz								
30 MHz to 1000 MHz	10 kHz								
1000 MHz to 40 GHz	100 kHz								
Measurement procedure:	Bandwidth Measurements (6.1)								

Comment:	
Date of test:	October 27, 2009
Test site:	Fully anechoic room, cabin no. 2



Date: 27.OCT.2009 10:14:08

Permitted frequency band:	5725 - 5875 MHz	
20 dB bandwidth:	54.8 MHz	
Carrier frequency stability:	<input type="checkbox"/> specified	<input checked="" type="checkbox"/> not specified
Maximum frequency tolerances:		
Bandwidth of the emission:	54.8 MHz	within permitted frequency band⁵: <input checked="" type="checkbox"/> yes <input type="checkbox"/> no

Test Result: Test passed

⁵ If a frequency stability is not specified, it is recommended that the fundamental emission is kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

8.3 Designation of Emissions

Rules and specifications:	CFR 47 Part 2, sections 2.201 and 2.202 IC RSS-Gen Issue 2, sections 3.2(h) and 8
Guide:	ANSI C63.4 / TRC-43

Type of modulation:	Amplitude Modulation with Frequency Modulated Carrier
---------------------	---

$B_n = \text{Necessary Bandwidth}$	$B_n = 2BK$
$B = \text{Modulation rate}$	$B = 18.43 \text{ MHz}$
$K = \text{Overall numerical factor}$	$K = 2.5$
Calculation:	$B_n = 2 \cdot (18.43 \text{ MHz}) \cdot 1 = 47.0 \text{ MHz}$


Designation of Emissions:	47M0A9D
---------------------------	----------------

8.4 Restricted Bands of Operation

Rules and specifications:	CFR 47 Part 15, section 15.205(a) IC RSS-210 Issue 7, section 2.2(a)
Guide:	ANSI C63.4
Limit:	Only spurious emissions are permitted in any of the frequency bands listed in CFR 47 Part 15, section 15.205(a) or IC RSS-210 Issue 7, section 2.2(a).
Measurement procedure:	Radiated Emission in Fully or Semi Anechoic Room (6.3)

Comment:	
Date of test:	October 27, 2009
Test site:	Fully anechoic room, cabin no. 2
Test distance:	3 meters

Test Result:	Test passed
--------------	-------------



Date: 27.OCT.2009 10:18:24

Test Result:

Test passed

8.5 Radiated Emission Measurement 9 kHz to 30 MHz

Rules and specifications:	CFR 47 Part 15, sections 15.215(b) and 15.249(d) IC RSS-210 Issue 7, section A2.9(b)			
Guide:	ANSI C63.4			
Limit:	Frequency of Emission (MHz)	Field Strength (μ V/m)	Field Strength ($\text{dB}\mu\text{V}/\text{m}$)	Measurement Distance d (meters)
	0.009 - 0.490	2400/F(kHz)	67.6 - 20 · log(F(kHz))	300
	0.490 - 1.705	24000/F(kHz)	87.6 - 20 · log(F(kHz))	30
	1.705 - 30.000	30	29.5	30
	Additionally, the level of any unwanted emissions shall not exceed the level of the fundamental emission.			
Measurement procedure:	Radiated Emission Measurement 9 kHz to 30 MHz (6.2)			

Comment:	
Date of test:	October 27, 2009
Test site:	Open field test site

Test Result:	Test passed
--------------	-------------

All emissions show more than 20 dB margin to the limit

Sample calculation of final values:

$$\text{Extrapolation Factor (dB/decade)} = \begin{cases} -40 \text{ (dB/decade)} & \text{if } d_1 = d_2 \\ \frac{\text{Reading Value } d_2 \text{ (dB}\mu\text{V)} - \text{Reading Value } d_1 \text{ (dB}\mu\text{V)}}{\text{Log}(d_2) - \text{Log}(d_1)} & \text{if } d_1 \neq d_2 \end{cases}$$

$$\text{Extrapolation Factor (dB)} = (\text{Log}(d) - \text{Log}(d_2)) \cdot \text{Extrapolation Factor (dB/decade)}$$

$$\begin{aligned} \text{Final Value (dB}\mu\text{V/m)} &= \text{Reading Value } d_2 \text{ (dB}\mu\text{V)} + \text{Correction Factor (dB/m)} \\ &\quad + \text{Extrapolation Factor (dB)} + \text{Pulse Train Correction (dB)} \end{aligned}$$

Note: Extrapolation factor (dB) and final value (dB}\mu\text{V/m) are relating to distance d.

8.6 Radiated Emission Measurement 30 MHz to 40 GHz

Rules and specifications:	CFR 47 Part 15, sections 15.215(b) and 15.249 IC RSS-210 Issue 7, section A2.9		
Guide:	ANSI C63.4		
Limit:	Frequency of Emission (MHz)	Field Strength (μ V/m)	Field Strength (dB μ V/m)
	30 - 88	100	40.0
	88 - 216	150	43.5
	216 - 960	200	46.0
	Above 960	500	54.0
	Additionally, the level of any unwanted emissions shall not exceed the level of the fundamental emission.		
Measurement procedures:	Radiated Emission in Fully or Semi Anechoic Room (6.3) Radiated Emission at Open Field Test Site (6.4)		

Comment:			
Date of test:	October 23, 2009; October 26, 2009; October 27, 2009; November 6, 2009		
Test site:	Frequencies \leq 1 GHz: Open field test site Frequencies $>$ 1 GHz: Fully anechoic room, cabin no. 2		
Test distance:	Frequencies \leq 8.2 GHz: 3 meters Frequencies $>$ 8.2 GHz to \leq 18 GHz: 1 meter Frequencies $>$ 18 GHz to \leq 26.5 GHz: 0.5 meters Frequencies $>$ 26.5 GHz: 0.25 meters		

Test Result:	Test passed
--------------	-------------

Frequency (MHz)	Antenna Polarization	Detector	Receiver Reading (dB μ V)	Correction Factor (dB/m)	Pulse Train Correction (dB)	Final Value (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
32.000	vertical	Quasi-Peak	22.8	13.5		36.3	40.0	3.7
32.016	horizontal	Quasi-Peak	4.0	13.5		17.5	40.0	22.5
36.600	vertical	Quasi-Peak	27.3	12.5		39.8	40.0	0.2
41.180	vertical	Quasi-Peak	28.3	11.6		39.9	40.0	0.1
175.250	horizontal	Quasi-Peak	1.6	15.0		16.6	43.5	26.9
2905.000	vertical	Peak	15.3	35.5		50.8	63.5	12.7
5781.900	vertical	Average	47.4	43.0		90.4	94.0	3.6
5784.600	vertical	Peak	52.6	43.0		95.6	114.0	18.4
5798.600	vertical	Average	50.6	43.0		93.6	94.0	0.4
5800.600	vertical	Peak	57.2	43.0		100.2	114.0	13.8
5812.800	vertical	Average	42.0	43.0		85.0	94.0	9.0
5817.400	vertical	Peak	48.4	43.0		91.4	114.0	22.6
11400.400	vertical	Peak	8.6	45.5		54.1	63.5	9.4
11564.200	horizontal	Peak	15.4	45.6		61.0	63.5	2.5

Sample calculation of final values:

$$\text{Final Value (dB}\mu\text{V/m)} = \text{Reading Value (dB}\mu\text{V)} + \text{Correction Factor (dB/m)} + \text{Pulse Train Correction (dB)}$$

8.7 Exposure of Humans to RF Fields

Rules and specifications:	IC RSS-Gen Issue 2, section 5.5
Guide:	IC RSS-102 Issue 2, section 2.5

Exposure of Humans to RF Fields		Applicable	Declared by applicant	Measured	Exemption
The antenna is					
<input type="checkbox"/> detachable <p>The conducted output power (CP in watts) is measured at the antenna connector:</p> $CP = \dots \text{ W}$ <p>The effective isotropic radiated power (EIRP in watts) is calculated using</p> <p><input type="checkbox"/> the numerical antenna gain: $G = \dots$</p> $EIRP = G \cdot CP \Rightarrow EIRP = \dots \text{ W}$ <p><input type="checkbox"/> the field strength⁶ in V/m: $FS = \dots \text{ V/m}$</p> $EIRP = \frac{(FS \cdot D)^2}{30} \Rightarrow EIRP = \dots \text{ W}$ <p>with:</p> <p>Distance between the antennas in m: $D = \dots \text{ m}$</p>					
<input checked="" type="checkbox"/> not detachable <p>A field strength measurement is used to determine the effective isotropic radiated power (EIRP in watts) given by⁶:</p> $EIRP = \frac{(FS \cdot D)^2}{30} \Rightarrow EIRP = 687.26 \cdot 10^{-6} \text{ W}$ <p>with:</p> <p>Field strength in V/m: $FS = 47.86 \cdot 10^{-3} \text{ V/m}$</p> <p>Distance between the two antennas in m: $D = 3 \text{ m}$</p>					
Selection of output power					
<p>The output power TP is the higher of the conducted or effective isotropic radiated power (e.i.r.p.):</p> $TP = 687.26 \cdot 10^{-6} \text{ W}$					

⁶ The conversion formula is valid only for properly matched antennas. In other cases the transmitter output power may have to be measured by a terminated measurement when applying the exemption clauses. If an open area test site is used for field strength measurement, the effect due to the metal ground reflecting plane should be subtracted from the maximum field strength value in order to reference it to free space, before calculating TP.

Exposure of Humans to RF Fields (continued)		Applicable	Declared by applicant	Measured	Exemption
Separation distance between the user and the transmitting device is					
<input type="checkbox"/> less than or equal to 20 cm <input checked="" type="checkbox"/> greater than 20 cm			<input checked="" type="checkbox"/>		
Transmitting device is					
<input type="checkbox"/> in the vicinity of the human head <input type="checkbox"/> body-worn			<input checked="" type="checkbox"/>		
SAR evaluation					
SAR evaluation is required if the separation distance between the user and the device is less than or equal to 20 cm.					
<input type="checkbox"/> The device operates from 3 kHz up to 1 GHz inclusively and its source-based time-averaged output power is less than, or equal to 200 mW for General Public Use and 1000 mW for Controlled Use.					<input type="checkbox"/>
<input type="checkbox"/> The device operates above 1 GHz up to 2.2 GHz inclusively and its source-based time-averaged output power is less than, or equal to 100 mW for General Public Use and 500 mW for Controlled Use.					<input type="checkbox"/>
<input type="checkbox"/> The device operates above 2.2 GHz up to 3 GHz inclusively and its source-based time-averaged output power is less than, or equal to 20 mW for General Public Use and 100 mW for Controlled Use.					<input type="checkbox"/>
<input type="checkbox"/> The device operates above 3 GHz up to 6 GHz inclusively and its source-based time-averaged output power) is less than, or equal to 10 mW for General Public Use and 50 mW for Controlled Use.					<input type="checkbox"/>
<input type="checkbox"/> SAR evaluation is documented in test report no.					
RF exposure evaluation					
RF exposure evaluation is required if the separation distance between the user and the device is greater than 20 cm.					
<input type="checkbox"/> The device operates below 1.5 GHz and its e.i.r.p. is equal to or less than 2.5 W.					<input type="checkbox"/>
<input checked="" type="checkbox"/> The device operates at or above 1.5 GHz and the e.i.r.p. of the device is equal to or less than 5 W.					<input checked="" type="checkbox"/>
<input type="checkbox"/> RF exposure evaluation is documented in test report no.					

9 Referenced Regulations

All tests were performed with reference to the following regulations and standards:

<input checked="" type="checkbox"/>	CFR 47 Part 2	Code of Federal Regulations Part 2 (Frequency allocation and radio treaty matters; General rules and regulations) of the Federal Communication Commission (FCC)	October 1, 2008
<input checked="" type="checkbox"/>	CFR 47 Part 15	Code of Federal Regulations Part 15 (Radio Frequency Devices) of the Federal Communication Commission (FCC)	October 1, 2008
<input checked="" type="checkbox"/>	ANSI C63.4	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	December 11, 2003 (published on January 30, 2004)
<input checked="" type="checkbox"/>	RSS-Gen	Radio Standards Specification RSS-Gen Issue 2 containing General Requirements and Information for the Certification of Radiocommunication Equipment, published by Industry Canada	June 2007
<input checked="" type="checkbox"/>	RSS-210	Radio Standards Specification RSS-210 Issue 7 for Low Power Licence-Exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment, published by Industry Canada	June 2007
<input type="checkbox"/>	RSS-310	Radio Standards Specification RSS-310 Issue 2 for Low-power Licence-exempt Radiocommunication Devices (All Frequency Bands): Category II Equipment, published by Industry Canada	June 2007
<input checked="" type="checkbox"/>	RSS-102	Radio Standards Specification RSS-102 Issue 3: Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) , published by Industry Canada	June 2009
<input type="checkbox"/>	ICES-003	Interference-Causing Equipment Standard ICES-003 Issue 4 for Digital Apparatus, published by Industry Canada	February 7, 2004
<input checked="" type="checkbox"/>	CISPR 22	Third Edition of the International Special Committee on Radio Interference (CISPR), Pub. 22, "Information Technology Equipment – Radio Disturbance Characteristics – Limits and Methods of Measurement"	1997
<input type="checkbox"/>	CAN/CSA-CEI/IEC CISPR 22	Limits and Methods of Measurement of Radio Disturbance Characteristics of Information Technology Equipment	2002

TRC-43 Notes Regarding Designation of Emission (Including Necessary Bandwidth and Classification), Class of Station and Nature of Service, published by Industry Canada October 9, 1982


10 Revision History

Revision History			
<i>Edition</i>	<i>Date</i>	<i>Issued by</i>	<i>Modifications</i>
1	10.11.09	Martin Steindl (cj)	First Edition

11 Charts taken during testing

Radiated Emission Test 9 kHz - 30 MHz
acc. to FCC Part 15 Subpart C (FAR)

Model: Funkkopfhörerset - Transmitter	Comment: - DC 28 V power supply
Serial no.: ---	- With grounding
Applicant: Amphony GmbH	- Transmitting continuously
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres	
Date of test: 10/27/2009	Operator: M. Steindl
Test performed: by hand	File name: default.emi
Detector: Peak	List of values: Selected by hand




Result:
Prescan

Project file:
69555-00838-1

Radiated Emission Test 30 MHz - 1 GHz
 acc. to FCC Part 15 Subpart C (FAR)

Model: Funkkopfhörerset - Transmitter	Comment: - DC 28 V power supply
Serial no.: ---	- With grounding
Applicant: Amphony GmbH	- Transmitting continuously
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres Horizontal Polarization	
Date of test: 10/23/2009	Operator: M. Steindl
Test performed: automatically	File name: default.emi
Detector: Peak	List of values: Selected by hand




Result:
Prescan

Project file:
69555-00838-1

Radiated Emission Test 30 MHz - 1 GHz
 acc. to FCC Part 15 Subpart C (FAR)


Model: Funkkopfhörerset - Transmitter	Comment: - DC 28 V power supply
Serial no.: ---	- With grounding
Applicant: Amphony GmbH	- Transmitting continuously
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres Vertical Polarization	
Date of test: 10/23/2009	Operator: M. Steindl
Test performed: automatically	File name: default.emi
Detector: Peak	List of values: Selected by hand



Result: Prescan	Project file: 69555-00838-1
--------------------	--------------------------------

Radiated Emission Test 1 GHz - 6 GHz
 acc. to FCC Part 15 Subpart C (FAR)

Model: Funkkopfhörerset - Transmitter	Comment: - DC 28 V power supply
Serial no.: ---	- With grounding
Applicant: Amphony GmbH	- Transmitting continuously
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres Horizontal Polarization	
Date of test: 10/27/2009	Operator: M. Steindl
Test performed: automatically	File name: default.emi
Detector: Peak	List of values: Selected by hand




Result:
Prescan

Project file:
69555-00838-1

Radiated Emission Test 1 GHz - 6 GHz
acc. to FCC Part 15 Subpart C (FAR)

Model: Funkkopfhörerset - Transmitter	Comment: - DC 28 V power supply
Serial no.: ---	- With grounding
Applicant: Amphony GmbH	- Transmitting continuously
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres Vertical Polarization	
Date of test: 10/27/2009	Operator: M. Steindl
Test performed: automatically	File name: default.emi
Detector: Peak	List of values: Selected by hand




Result: Prescan	Project file: 69555-00838-1
--------------------	--------------------------------

Radiated Emission Test 1 GHz - 6 GHz
 acc. to FCC Part 15 Subpart C (FAR)

Model: Funkkopfhörerset - Transmitter	Comment: - DC 28 V power supply
Serial no.: ---	- With grounding
Applicant: Amphony GmbH	- Transmitting continuously
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres Vertical Polarization	
Date of test: 10/27/2009	Operator: M. Steindl
Test performed: by hand	File name: default.emi
Detector: Average	List of values: Selected by hand

Limit1: FCC 15.209 (3 m) Transducer: EMCO 3115




Result:
Prescan (VBW = 1 kHz)

Project file:
69555-00838-1

Radiated Emission Test 6 GHz - 8.2 GHz
acc. to FCC Part 15 Subpart C (FAR)


Model: Funkkopfhörerset - Transmitter	Comment: - DC 28 V power supply
Serial no.: ---	- With grounding
Applicant: Amphony GmbH	- Transmitting continuously
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres Horizontal Polarization	
Date of test: 10/27/2009	Operator: M. Steindl
Test performed: automatically	File name: default.emi
Detector: Peak	List of values: 10 dB Margin 50 Subranges



Result: Prescan	Project file: 69555-00838-1
--------------------	--------------------------------

Radiated Emission Test 8.2 GHz - 12.4 GHz
acc. to FCC Part 15 Subpart C (FAR)


Model: Funkkopfhörerset - Transmitter	Comment: - DC 28 V power supply
Serial no.: ---	- With grounding
Applicant: Amphony GmbH	- Transmitting continuously
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 1 meter Horizontal Polarization	
Date of test: 10/27/2009	Operator: M. Steindl
Test performed: automatically	File name: default.emi
Detector: Peak	List of values: 10 dB Margin 50 Subranges



Result: Prescan	Project file: 69555-00838-1
--------------------	--------------------------------

Radiated Emission Test 6 GHz - 8.2 GHz
 acc. to FCC Part 15 Subpart C (FAR)


Model: Funkkopfhörerset - Transmitter	Comment: - DC 28 V power supply
Serial no.: ---	- With grounding
Applicant: Amphony GmbH	- Transmitting continuously
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres Vertical Polarization	
Date of test: 10/27/2009	Operator: M. Steindl
Test performed: automatically	File name: default.emi
Detector: Peak	List of values: 10 dB Margin 50 Subranges



Result: Prescan	Project file: 69555-00838-1
--------------------	--------------------------------

Radiated Emission Test 8.2 GHz - 12.4 GHz
acc. to FCC Part 15 Subpart C (FAR)


Model: Funkkopfhörerset - Transmitter	Comment: - DC 28 V power supply
Serial no.: ---	- With grounding
Applicant: Amphony GmbH	- Transmitting continuously
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 1 meter Vertical Polarization	
Date of test: 10/27/2009	Operator: M. Steindl
Test performed: automatically	File name: default.emi
Detector: Peak	List of values: 10 dB Margin 50 Subranges



Project file:
69555-00838-1

Radiated Emission Test 12.4 GHz - 18 GHz
acc. to FCC Part 15 Subpart C (FAR)


Model: Funkkopfhörerset - Transmitter	Comment: - DC 28 V power supply
Serial no.: ---	- With grounding
Applicant: Amphony GmbH	- Transmitting continuously
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 1 meter Horizontal Polarization	
Date of test: 10/27/2009	Operator: M. Steindl
Test performed: automatically	File name: default.emi
Detector: Peak	List of values: Selected by hand



Result: Prescan	Project file: 69555-00838-1
--------------------	--------------------------------


Radiated Emission Test 12.4 GHz - 18 GHz
acc. to FCC Part 15 Subpart C (FAR)

Model: Funkkopfhörerset - Transmitter	Comment: - DC 28 V power supply
Serial no.: ---	- With grounding
Applicant: Amphony GmbH	- Transmitting continuously
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 1 meter Horizontal Polarization	
Date of test: 10/27/2009	Operator: M. Steindl
Test performed: automatically	File name: default.emi
Detector: Peak	List of values: Selected by hand




Radiated Emission Test 12.4 GHz - 18 GHz
acc. to FCC Part 15 Subpart C (FAR)

Model: Funkkopfhörerset - Transmitter	Comment: - DC 28 V power supply
Serial no.: ---	- With grounding
Applicant: Amphony GmbH	- Transmitting continuously
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 1 meter Vertical Polarization	
Date of test: 10/27/2009	Operator: M. Steindl
Test performed: automatically	File name: default.emi
Detector: Peak	List of values: Selected by hand



Radiated Emission Test 12.4 GHz - 18 GHz
 acc. to FCC Part 15 Subpart C (FAR)

Model: Funkkopfhörerset - Transmitter	Comment: - DC 28 V power supply
Serial no.: ---	- With grounding
Applicant: Amphony GmbH	- Transmitting continuously
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 1 meter Vertical Polarization	
Date of test: 10/27/2009	Operator: M. Steindl
Test performed: automatically	File name: default.emi
Detector: Peak	List of values: Selected by hand



Result: Prescan (VBW = 100 kHz)	Project file: 69555-00838-1
------------------------------------	--------------------------------

Radiated Emission Test acc. to FCC Part 15 Subpart C

Model:
Funkkopfhörerset - Transmitter

Serial No.:


Applicant:
Amphony GmbH

Mode:
- DC 28 V power supply
- Transmitting continuously
- Test parameters:
Distance: 0.3 m
Polarisation: horizontal

Ref. Level 85 dB μ V
5 dB/Div.

ATT 10 dB

Ref. Offset 43 dB



Start 18.000 GHz
RBW 1 MHz

VBW 1 MHz

Stop 26.500 GHz
SWP 40 ms

Tested by:
M. Steindl

Project-No.:
69555-00838-1

Date:
2009/11/06

Radiated Emission Test acc. to FCC Part 15 Subpart C


Model: Funkkopfhörerset - Transmitter
Serial No.: ---
Applicant: Amphony GmbH

Mode: - DC 28 V power supply
- Transmitting continuously
- Test parameters: Distance: 0.3 m Polarisation: vertical

Ref.Level 85 dB μ V
5 dB/Div.

ATT 10 dB

Ref. Offset 43 dB



Start 18.000 GHz
RBW 1 MHz

VBW 1 MHz

Stop 26.500 GHz
SWP 40 ms

Tested by: M. Steindl
Date: 2009/11/06

Project-No.: 69555-00838-1


Radiated Emission Test acc. to FCC Part 15 Subpart C

Model: Funkkopfhörerset - Transmitter
Serial No.: ---
Applicant: Amphony GmbH

Mode: - DC 28 V power supply
- Transmitting continuously
- Test parameters: Distance: 0.25 m Polarisation: horizontal

Ref.Level 32 dB μ V
5 dB/Div.

ATT 0 dB



Start 26.500 GHz
RBW 1 MHz

VBW 1 MHz

Stop 40.000 GHz
SWP 60 ms

Tested by: M. Steindl	Project-No.: 69555-00838-1
Date: 2009/11/06	

Radiated Emission Test acc. to FCC Part 15 Subpart C

Model:
Funkkopfhörerset - Transmitter

Serial No.:

Applicant:
Amphony GmbH

Mode:
- DC 28 V power supply
- Transmitting continuously
- Test parameters:
Distance: 0.25 m
Polarisation: vertical

Ref.Level 32 dB μ V
5 dB/Div.

ATT 0 dB

