

Power in: Power Class 6
(IEEE 802.3bt Type 3)
PoE: 50-57 VDC /
0.76-0.666A, max 38W
DC: 10-28VDC /
0.65-0.232A, max 6.4W
Power out: Power Class 4
(IEEE 802.3at Type 2)
PoE: 50-57VDC /
0.6-0.53A, max 30W
CAN ICES (B) / NMB (B)
IC: 3919A-D2210VE
HVIN: D2210-VE
FCC, see manual
FCC ID: PNB-AXISD2210-VE
IFT: AXAXAX23-44842
U/A: 2671051 ID: AJ

AXIS D2210-VE Radar Black

P/N: 02770-001-02

S/N: B8A44F000000



2744595r10



Axis Communications AB
Gränden 1
SE-22369 Lund
SWEDEN
R-R-PNB-D2210-VE

Engineered
in Sweden

IP66/67
Type 4X



Country of Origin: POLAND

P/N: 02770-001-02
S/N: B8A44F000000



CCAL24LP0100T5



03479-24-05509



TA-2023/2605
APPROVED



VI 038 23



RGSL/03A/0224/S(24-0709)



C-30282



NR: 2024-04-I-0373

UAE -TRA
ER28352/24
DA74725/18

2744596r6