



EMISSION TEST REPORT

Test report file No. : 03-IST-135/FB

Date of issue : May 06, 2003

Model / Type No. : IMP400

☒ Basic ☐ Alternate

Kind of product : MP3 Player

Brand name : InterMagic

Applicant : InterMagic Corporation

Manufacturer : InterMagic Corporation

License holder : InterMagic Corporation

Address : #37-2 Yoojin Bldg., 6F. Daebang-dong, Dongjak-gu, Seoul Korea

Test result according to the regulation(s)

☒ Positive ☐ Negative

at page 3.

This test report with appendix consists of 23 pages. The test result only responds to the tested sample. It is not allowed to copy this report even partly without the allowance of the Test Laboratory. This equipment is complied with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-1992.

D I R E C T O R Y

A) Documentation.

Page

Directory	<u>2</u>
Test regulations	<u>3</u>
Information of Test Regulation	<u>3</u>
Equipment under Test	<u>4</u>
Test Conditions	<u>5 ~ 6</u>
Test Result	<u>7</u>
Measurement Uncertainty	<u>8</u>
Test-setup	<u>9 ~ 13</u>
Summary	<u>23</u>

B) Test Data.

Conducted emissions (Mains)	: 150 kHz - 30 MHz	<u>14 ~ 16</u>
Radiated emissions	: 30 MHz – 1 GHz	
	Play Mode	<u>17 ~ 18</u>
	Download Mode	<u>19 ~ 20</u>
	Encoding Mode	<u>21 ~ 22</u>

C) Appendix

TEST REGULATIONS

The tests were performed according to the following regulations ;

- - FCC Part 15, Subpart B (Unintentional Radiators, Class B)

Information of Test Laboratory

IST EMC Lab.

San 21-8 Goan-Ri, Baekam-Myun, Yongin-Si, Kyunggi-Do, Korea

International - Tel : 82-31 - 333 - 4093. Fax : 82-31 - 333 - 4094.

Domestic - Tel : 031 - 333 - 4093. Fax : 031 - 333 - 4094.

Equipment Description:

PC interface	USB 1.1, over 4 Mbps
Audio format	MP2, MP3, MP3Pro, WMA
Encoding quality	High (128 kbps) / Low (32 kbps)
Download speed	12 Mbps
Frequency range	20 Hz ~ 20 kHz
S/N ratio of DAC	96 dB
THD	-88 dB
Power consumption	90 mA (at MP3 mode)
File system	FAT 32/16 compatible

☒ Table-Top. ☐ Floor-Standing.
☐ Table-Top and Floor-Standing(Combination).

The equipment under test was operated during the measurement under following conditions :

- ☐ Standby.
- ☒ Operational Condition : 1) Play Mode 2) Files Download Mode
 3) Encoding Mode

Following peripheral devices and interface cables were connected during the measurement :

Equipment	Type	Brand	Serial No.
PC	Vectra VL420MT	HP	SG23101784
Monitor	103F	Daewoo	Unknown
Keyboard	SK-2502C	HP	M020321066
PS/2 Mouse	M-S48a	HP	LZC20602926
Serial Mouse	M-S428	Logitech	LCA53305547
Printer	A0302384	Northern Telecom	26633S60168

- Unshielded AC power cable : 1.8 m
- Shielded monitor's signal cable (with two ferrite core) : 1.5 m
- Shielded printer's signal cable (with two ferrite core) : 1.8 m
- Unshielded USB cable (with two ferrite core) : 0.8 m
- Unshielded Audio I/O cable : 0.7 m

TEST CONDITIONS

The measurement of the conducted emissions (Interference voltage) was performed in a shielded room.

Test location :

☒ Shielded room. No.1

☐ Compact chamber 2

Used testing instruments :

Name	Type	Manufacturer	Calibration. Date	Serial Number
ESH 3	Test Receiver	Rohde & Schwarz	Jul. 25, 2002	892108/018
3725/2	LISN	EMCO	Aug. 22, 2002	9101-2068
KNW-407	LISN	Hyup-Rip	Aug. 21, 2002	8-883-10
ESH 3-Z2	Pulse Limiter	Rohde & Schwarz	Jul. 25, 2002	357.8810.52

Test - accessories :

Type	Manufacturer
Aneroid Barometer	Sato
Hygrometer	Sato

Measurement Procedures :

Conducted emissions measurements were made in accordance with ANSI G63.4-1992, "Method of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz". The measurement were performed over the frequency range of 0.15MHz to 30MHz using a 50 Ω /50uH LISN as the input transducer to an EMI/Field Intensity Meter. The measurements were made with the detector set for "Peak" amplitude within an IF bandwidth of 10kHz or for "quasi-peak" within a bandwidth of 9kHz.

All used test-instruments as well as the test-accessories are calibrated regularly.

Test engineer :



S. G. Kim / Research Engineer
IST EMC Lab.

TEST CONDITIONS

The **measurement of the radiated emissions (Electric field)** in the frequency range from 30 MHz to 1GHz was performed in horizontal and vertical antenna polarization at a open-site which meet the site attenuation requirement of ANSI C63.4-1992 and a test distance of :

Location : ☒ Open Site No. 1 ☐ Open Site No. 2 ☐ Open Site No. 3
 Distance : ☒ 3 meters ☐ 10 meters

Used testing instruments :

Name	Type	Manufacturer	Calibration. Date	Serial Number
ESVP	Test Receiver	Rohde & Schwarz	Aug. 16, 2002	861744/004
VULB 9160	Antenna	Schwarzbeck	Jul. 10, 2002	3048

Test - accessories :

Type	Manufacturer
Aneroid Barometer	Sato
Hygrometer	Sato

Measurement procedures

Radiated measurements were in accordance with ANSI C63.4-1992 "Method of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz". The measurements were performed over the frequency range of 30MHz to 1GHz using antenna as the input transducer to a EMI/Field Intensity Meter. The measurements were made with the detector set for "quasi-peak" within a bandwidth of 120kHz.

All used test-instruments as well as the test-accessories are calibrated regularly.

Test engineer :


 S. G. Kim / Research Engineer
 IST EMC Lab.

TEST RESULT

Conducted emissions : 150 kHz - 30 MHz

Operational Condition : Files Download Mode

The requirements are.

☒ KEPT ☐ NOT KEPT

Min. limit margin 10.2 dB at 2.870 MHz

Remarks : See test-data at pages 14 ~ 16.

Radiated emissions (electric field) 30 MHz - 1000 MHz

Operational Condition : Play Mode

The requirements are.

☒ KEPT ☐ NOT KEPT

Min. limit margin 6.2 dB at 184.0 MHz

Remarks : See test-data at page 17 ~ 18.

Radiated emissions (electric field) 30 MHz - 1000 MHz

Operational Condition : Files Download Mode

The requirements are.

☒ KEPT ☐ NOT KEPT

Min. limit margin 3.3 dB at 84.0 MHz

Remarks : See test-data at page 19 ~ 20.

Radiated emissions (electric field) 30 MHz - 1000 MHz

Operational Condition : Encoding Mode

The requirements are.

☒ KEPT ☐ NOT KEPT

Min. limit margin 9.0 dB at 64.0 MHz

Remarks : See test-data at page 21 ~ 22.

Measurement Uncertainty Calculation

The measurement uncertainties stated were calculated in accordance with the requirements of NIST Technical Note 1297 and NIS 81 (1994).

Contribution (Conducted Emissions)	Probability Distribution	Uncertainty ($\pm$ dB)
		0.15-30MHz
Receiver Specification	Rectangular	1.5
LISN Coupling Specification	Rectangular	1.5
Cable and Input Attenuator Calibration	Normal (k=2)	0.5
Mismatch to Reciver	U-Shaped	-0.8 / +0.7
System Repeatability	Normal (k=1)	0.2
Combined Standard Uncertainty	Normal (k=2)	-1.85 / +1.71
Expanded Uncertainty U	Normal (k=2)	-3.7 / +3.42

$$U_{c,min\ us} = -1.85, \ U_{c,plus} = 1.71$$

$$U = -3.70 / +3.42 \ (k=2, \ 95.45\% \text{ confidence level})$$


Contribution (Radiated Emissions)	Probability Distribution	Uncertainties($\pm$ dB)
		3 m
Antenna		
Factor	Normal (k=2)	0.9968
Frequency Interpolation	Rectangular	0.1039
Height Variation	Rectangular	-2.6 / +1.5
Directivity Difference	Rectangular	-1.0 / +0
Phase Center Location	Rectangular	1.0
Cable Loss	Normal (k=2)	0.5
Receiver		
Voltage Accuracy	Normal (k=2)	2.0
Pulse Response	Rectangular	1.5
Absolute Repetition Rate	Rectangular	1.5
Mismatch to Receiver		
$G_{antenna}$ = 0.33	U-Shaped	-1.0 / +0.9
$G_{receiver}$ = 0.33		
System Repeatability	Std Deviation	0.5
Combined Standard Uncertainty	Normal	-2.6048 / 2.2775
Expanded Uncertainty U	Normal (k=2)	-5.21 / +4.55

$$U_{c,min\ us} = -2.6048, \ U_{c,plus} = 2.2775$$

$$U = -5.21 / +4.55 \ (k=2, \ 95.45\% \text{ confidence level})$$

TEST SETUP (Drawings)


Type : WTN-15B2




Conducted Emissions 150kHz - 30 MHz

TEST SETUP (Drawings)

Type : IMP400



Radiated Emissions (Play Mode)



Radiated Emissions (Files Download / Encoding Mode)

TEST SETUP (Photos)

Type : IMP400



Conducted Emissions 150kHz - 30 MHz



Page 11 of 23

TEST SETUP (Photos)

Type : IMP400



Radiated Emissions 30MHz - 1000 MHz (Play Mode)




Page 12 of 23

TEST SETUP (Photos)

Type : IMP400



Radiated Emissions 30MHz - 1000 MHz (Files Download / Encoding Mode)



Conducted Emission Test Data

Type IMP400
 Manufacturer InterMagic Corporation
 Operation mode Files Download Mode
 Environmental Condition Temperature : 21 °C
 Humidity : 45 %
 Atmospheric pressure : 1000 mbar
 Date Apr. 30, 2003

Highest Emissions relative to the limit


Frequency [MHz]	Reading [dB?V]		Phase	Insertion Loss (LISN)	Limit [dB? V]		Margin [dB]	
	Q-peak	AV			Q-peak	AV	Q-peak	AV
0.267	38.0	37.0	L 1	0.8	61.2	51.2	22.4	13.4
0.397	33.9	33.0		0.8	57.9	47.9	23.2	14.1
1.162	33.2	33.0		0.8	56.0	46.0	22.0	12.2
1.305	35.1	32.1		0.8	56.0	46.0	20.1	13.1
6.767	35.1	20.9		0.8	60.0	50.0	24.1	28.3
15.622	34.5	30.1		0.8	60.0	50.0	24.7	19.1
0.266	33.4	32.2		N	0.8	61.2	51.2	17.0
0.397	28.3	26.3	0.8		57.9	47.9	28.8	20.8
1.162	33.5	32.3	0.8		56.0	46.0	21.7	12.9
1.307	35.3	34.4	0.8		56.0	46.0	19.9	10.8
6.769	28.0	19.8	0.8		60.0	50.0	31.2	29.4
15.623	34.6	29.9	0.8		60.0	50.0	24.6	19.3
Cable loss are less than 0.1 dB								


*L1 : Live Line

**N : Neutral Line

*** Please refer to data graphs at page 15 ~ 16.

Coverage factor of k=2 will ensure that the level of confidence will be approximately 95.45%,
 Uncertainty U = -3.70 / +3.42 [dB]





Radiation Test Data


Type	IMP400		
Manufacturer	InterMagic Corporation		
Operation mode	Play Mode		
Environmental Condition	Temperature	:	21 °C
	Humidity	:	43 %
	Atmospheric pressure	:	1000 mbar
Test distance	3 m		
Antenna	VULB9160		
Date	Apr. 28, 2003		

Highest Emissions relative to the limit

Freq. [MHz]	Reading [dBuV]	Antenna Factor [dB]	Cable Loss [dB]	Angle [deg]	Height [cm]	Polar [H/V]	Result [dBuV]	Limit [dBuV]	Margin [dB]
172.8	21.6	11.9	2.4	63	100	V	35.9	43.5	7.6
176.6	20.2	11.2	2.4	58	100	V	33.8	43.5	9.7
184.0	24.9	10.0	2.4	135	112	H	37.3	43.5	6.2
187.8	24.2	9.5	2.5	130	100	H	36.2	43.5	7.3
188.6	22.7	9.5	2.5	133	100	H	34.7	43.5	8.8
335.5	18.4	11.7	3.5	2	110	H	33.6	46.0	12.4
395.6	15.6	13.1	4.2	0	120	H	32.9	46.0	13.1

Coverage factor of k=2 will ensure that the level of confidence will be approximately 95.45%,
 Uncertainty U = -5.21 / +4.55 [dB]

MEASUREMENT OF DISTURBANCE RADIATION



Radiation Test Data


Type	IMP400		
Manufacturer	InterMagic Corporation		
Operation mode	Files Download Mode		
Environmental Condition	Temperature	:	22 °C
	Humidity	:	44 %
	Atmospheric pressure	:	1000 mbar
Test distance	3 m		
Antenna	VULB9160		
Date	Apr. 30, 2003		

Highest Emissions relative to the limit

Freq. [MHz]	Reading [dBuV]	Antenna Factor [dB]	Cable Loss [dB]	Angle [deg]	Height [cm]	Polar [H/V]	Result [dBuV]	Limit [dBuV]	Margin [dB]
36.0	14.1	13.4	1.0	0	100	V	28.5	40.0	11.5
48.0	18.5	10.2	1.3	106	100	V	30.0	40.0	10.0
60.0	22.4	11.3	1.4	0	342	H	35.1	40.0	4.9
64.0	21.4	10.7	1.5	0	322	H	33.6	40.0	6.4
72.0	25.5	9.4	1.6	10	279	H	36.5	40.0	3.5
84.0	27.7	7.4	1.6	62	256	H	36.7	40.0	3.3
172.8	15.5	11.9	2.4	63	180	H	29.8	43.5	13.7
183.4	17.5	10.1	2.4	58	145	H	30.0	43.5	13.5
247.4	24.4	10.5	2.9	135	147	H	37.8	46.0	8.2
300.8	10.4	11.7	3.3	0	100	H	25.4	46.0	20.6
356.2	11.4	11.7	3.6	0	100	H	26.7	46.0	19.3
383.9	14.8	12.5	3.8	2	110	H	31.1	46.0	14.9

Coverage factor of k=2 will ensure that the level of confidence will be approximately 95.45%,
Uncertainty U = -5.21 / +4.55 [dB]

MEASUREMENT OF DISTURBANCE RADIATION



Radiation Test Data


Type	IMP400		
Manufacturer	InterMagic Corporation		
Operation mode	Encoding Mode		
Environmental Condition	Temperature	:	22 °C
	Humidity	:	45 %
	Atmospheric pressure	:	1000 mbar
Test distance	3 m		
Antenna	VULB9160		
Date	Apr. 30, 2003		

Highest Emissions relative to the limit

Freq. [MHz]	Reading [dBuV]	Antenna Factor [dB]	Cable Loss [dB]	Angle [deg]	Height [cm]	Polar [H/V]	Result [dBuV]	Limit [dBuV]	Margin [dB]
48.0	16.4	10.2	1.3	106	100	V	27.9	40.0	12.1
64.0	18.8	10.7	1.5	0	322	H	31.0	40.0	9.0
72.0	19.9	9.4	1.6	10	279	H	30.9	40.0	9.1
84.0	20.1	7.4	1.6	62	256	H	29.1	40.0	10.9
172.8	12.7	11.9	2.4	63	180	H	27.0	43.5	16.5
183.4	14.9	10.1	2.4	58	145	H	27.4	43.5	16.1
247.4	20.3	10.5	2.9	135	147	H	33.7	46.0	12.3
356.2	12.8	11.7	3.6	0	100	H	28.1	46.0	17.9

Coverage factor of $k=2$ will ensure that the level of confidence will be approximately 95.45%,
 Uncertainty $U = -5.21 / +4.55$ [dB]

MEASUREMENT OF DISTURBANCE RADIATION



SUMMARY

GENERAL REMARKS :

The equipment is not modified anything, mechanical or circuit to improve EMI status during a measurement and complied the regulation "Part 15 subpart B Class B of CFR 47"

FINAL JUDGMENT :

The requirements according to the technical regulations are

☒ Kept ☐ Not kept

The equipment under test does

☒ Fulfill the general approval requirements mentioned on page 3.
☐ Not fulfill the general approval requirements mentioned on page 3.

Begin of testing : Apr. 25, 2003

End of testing : Apr. 30, 2003

Reviewed by


Joon H. Lee / EMC Group Manager

Issued by


G. Chung / Chief