

User Manual
'93-'96 CORVETTE REPLACEMENT FOB MODELS
GM10282929 and GM10282930

PROGRAMMING INSTRUCTIONS:

1. Remove transmitter from package. Place transmitter and any optional transmitter 10 feet or more away from the car.
2. Turn the ignition key to the ON position.
3. Push the TRIP/ODO button on the Driver Information Center (DIC) twice.
4. WITHIN 5 SECONDS, push and hold the FUEL/INFO button on the DIC until the PKE light on the DIC comes on and stays on.
5. Turn the ignition to the OFF position, but leave the key in the ignition. The PKE light will come on and begin flashing.
6. Bring one transmitter into range. When the system recognizes the transmitter, the PKE light will stay on.
7. To program an optional transmitter, move the newly programmed transmitter out of range and repeat step 6.
8. Remove the key from the ignition or turn the ignition ON. The transmitter(s) are now programmed to the vehicle.

Battery:

Use a Renata CR2450 3V lithium coin cell type battery or equivalent.

To remove battery, use a non-metallic tool to pry battery from holder. Protect your eyes at all times while using any force to remove battery. Note polarity (+) positive is facing up, snap new battery into place. Re-assemble case, do not over tighten screws. Also ensure button decals are oriented correctly.

FCC INFO:

FCC ID: PNZ0202T

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) This device must accept any interference received, including interference that may cause undesired operation.

This equipment has been tested and found to comply with the limits for a Class-B digital device, pursuant to Part 15 of the FCC rules.

These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or

television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- 1) Reorient or relocate the receiving antenna
- 2) Increase the separation between the equipment and receiver.
- 3) Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- 4) Consult the dealer or an experienced radio/TV technician for help.

This equipment has been certified to comply with the limits for a Class-B computing device, pursuant to FCC Rules. In order to maintain compliance with FCC regulations, shielded cables must be used with this equipment. Operation with non-approved equipment or unshielded cables is likely to result in interference to radio and TV reception.

Changes and modifications by the user to the equipment without the approval of the manufacturer could void the user's authority to operate this equipment.

(C)2003 Xilor Inc