

FCC PART 15.247

TEST REPORT

For

Shenzhen Rapoo Technology Co., Ltd.

22, Jinxiu Road East, Pingshan District, Shenzhen, China

FCC ID: PP2A500

Report Type: Original Report	Product Type: Bluetooth Portable NFC Speaker
Test Engineer: Ares Liu	<i>Ares Liu</i>
Report Number: R2DG130922001-00A	
Report Date: 2013-10-09	
Reviewed By: Ivan Cao RF Leader	<i>Ivan Cao</i>
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP*, or any agency of the Federal Government.

* This report may contain data that are not covered by the NVLAP accreditation and shall be marked with an asterisk "★" (Rev.2)
This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE.....	4
RELATED SUBMITTAL(S)/GRANT(S)	4
TEST METHODOLOGY	4
TEST FACILITY	5
SYSTEM TEST CONFIGURATION	6
DESCRIPTION OF TEST CONFIGURATION.....	6
EUT EXERCISE SOFTWARE.....	6
EQUIPMENT MODIFICATIONS.....	6
LOCAL SUPPORT EQUIPMENT LIST AND DETAILS	6
EXTERNAL I/O CABLE	6
BLOCK DIAGRAM OF TEST SETUP.....	7
SUMMARY OF TEST RESULTS.....	8
FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE	9
APPLICABLE STANDARD.....	9
FCC §15.203 - ANTENNA REQUIREMENT	10
APPLICABLE STANDARD.....	10
ANTENNA CONNECTOR CONSTRUCTION.....	10
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS.....	11
APPLICABLE STANDARD.....	11
MEASUREMENT UNCERTAINTY	11
EUT SETUP.....	11
EMI TEST RECEIVER SETUP	12
TEST PROCEDURE	12
CORRECTED AMPLITUDE & MARGIN CALCULATION	12
TEST EQUIPMENT LIST AND DETAILS	13
TEST RESULTS SUMMARY	13
TEST DATA	13
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS	16
APPLICABLE STANDARD.....	16
MEASUREMENT UNCERTAINTY	16
EUT SETUP.....	16
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP.....	17
TEST PROCEDURE.....	17
TEST EQUIPMENT LIST AND DETAILS	18
CORRECTED AMPLITUDE & MARGIN CALCULATION.....	18
TEST RESULTS SUMMARY	19
TEST DATA.....	19
FCC §15.247(a) (1) - CHANNEL SEPARATION TEST.....	28
APPLICABLE STANDARD.....	28
TEST EQUIPMENT LIST AND DETAILS	28
TEST PROCEDURE	28
TEST DATA.....	28
FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING	34

APPLICABLE STANDARD.....	34
TEST PROCEDURE.....	34
TEST EQUIPMENT LIST AND DETAILS	34
TEST DATA	34
FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST.....	40
APPLICABLE STANDARD.....	40
TEST PROCEDURE.....	40
TEST EQUIPMENT LIST AND DETAILS	40
TEST DATA	40
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)	44
APPLICABLE STANDARD.....	44
TEST PROCEDURE.....	44
TEST EQUIPMENT LIST AND DETAILS	44
TEST DATA	44
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT	60
APPLICABLE STANDARD.....	60
TEST PROCEDURE.....	60
TEST EQUIPMENT LIST AND DETAILS	60
TEST DATA	60
FCC §15.247(d) - BAND EDGES TESTING	66
APPLICABLE STANDARD.....	66
TEST PROCEDURE.....	66
TEST EQUIPMENT LIST AND DETAILS	66
TEST DATA	66

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Shenzhen Rapoo Technology Co., Ltd.*'s product, model number: *A500 (FCC ID: PP2A500)* or ("EUT") in this report is a *Bluetooth Portable NFC Speaker*, which was measured approximately: 14.0 cm (L) x 6.0 cm (W) x 3.5cm (H), rated input voltage: DC 5.0V from system.

** All measurement and test data in this report was gathered from production sample serial number: 130922001 (Assigned by BACL, Dongguan). The EUT was received on 2013-09-23.*

Objective

This report is prepared on behalf of *Shenzhen Rapoo Technology Co., Ltd.* in accordance with Part 2, Subpart J, Part 15, Subparts A, B and C of the Federal Communication Commission's rules.

The tests were performed in order to determine the Bluetooth of EUT compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DTS submissions with FCC ID: PP2A500 for LE mode of bluetooth.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 02, 2012. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Dongguan) is an ISO/IEC 17025 accredited laboratory, and is accredited by National Voluntary Laboratory Accredited Program (Lab Code 500069-0).



The current scope of accreditations can be found at <http://ts.nist.gov/standards/scopes/5000690.htm>

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode, which was provided by manufacturer.

EUT Exercise Software

The software “CSR_2.5” was used, which was provided by manufacture. The maximum power setting was set by the software as following table:

Test Software Version	CSR_2.5		
Test Frequency	2402MHz	2441MHz	2480MHz
GFSK	63	63	63
4-DQPSK	100	100	100
8-DPSK	100	100	100

Equipment Modifications

No modification was made to the EUT tested.


Local Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
HP	Printer	C3941A	JPTVOB2337
SAST	Modem	AEM-2100	0293
DELL	Keyboard	L100	CNORH656658907BL05DC
DELL	Laptop	PP11L	QDS-BRCM1017

External I/O Cable

Manufacturer	Length (m)	Form/Port	To
Shielded Detachable Printer Cable	1.2	Parallel Port of Laptop	Printer
Shielded Detachable Serial Cable	1.2	Serial Port of Laptop	Modem
Shielded Detachable Keyboard Cable	1.5	Keyboard Port of Laptop	Keyboard
Un-shielded Detachable USB Cable	1.2	Laptop	EUT

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i) & §1.1310 & §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Emissions	Compliance
§15.247 (a)(1)	20 dB Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band Edges	Compliance

FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE

Applicable Standard

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 Mobile Portable RF Exposure V05 Appendix A, SAR can be exempted if the output power is less than the SAR exclusion threshold:

For $f=2450\text{MHz}$, the output power is less 10mW at distance of 5mm.

Measurement Result

Peak conducted output power= 6.33 dBm

SAR exclusion threshold 10 mW (10dBm) > 6.33 dBm

So the SAR evaluation is not necessary.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has an internal Antenna, the maximum gain was 1.7 dBi, which complied with 15.203, please refer to the internal photos.

Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cisp} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cisp} of Table 1, then:


- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit.

Based on CISPR 16-4-2: 2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Dongguan) is 3.46 dB (150 kHz to 30 MHz).

Table 1 – Values of U_{cisp}

Measurement	U_{cisp}
Conducted disturbance at mains port using AMN (150 kHz to 30 MHz)	3.4 dB

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the first LISN and the other support equipments were connected to the outlet of the second LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

Herein,

V_C : corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN or ISN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI TEST RECEIVER	ESCS 30	830245/006	2012-11-29	2013-11-28
R&S	Two-line V-network	ENV216	3560.6550.12	2013-2-18	2014-2-17
R&S	L.I.S.N	ESH3-Z5	100113	2012-11-29	2013-11-28
BACL	Test Software	BACL-EMC	V1.0-2010	N/A	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, with the worst margin reading of:

6.50 dB at 0.300 MHz in the Neutral conducted mode.


Test Data**Environmental Conditions**

Temperature:	26.5 °C
Relative Humidity:	53 %
ATM Pressure:	100.3 kPa


The testing was performed by Ares Liu on 2013-09-27.

Test Mode: Transmitting

AC 120V/60 Hz, Line



Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/ QP/Ave.)
0.160	47.46	0.46	65.46	18.00	QP
0.160	37.89	0.46	55.46	17.57	AV
0.190	40.27	0.44	64.04	23.77	QP
0.190	38.03	0.44	54.04	16.01	AV
0.320	45.76	0.34	59.71	13.95	QP
0.320	41.52	0.34	49.71	8.19	AV
0.540	40.84	0.31	56.00	15.16	QP
0.540	27.91	0.31	46.00	18.09	AV
0.600	41.60	0.31	56.00	14.40	QP
0.600	33.30	0.31	46.00	12.70	AV
0.850	35.78	0.32	56.00	20.22	QP
0.850	26.12	0.32	46.00	19.88	AV

AC 120V/60 Hz, Neutral

Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/ QP/Ave.)
0.190	48.63	0.25	64.04	15.41	QP
0.190	38.15	0.25	54.04	15.89	AV
0.300	50.78	0.23	60.24	9.46	QP
0.300	43.74	0.23	50.24	6.50	AV
0.600	42.88	0.21	56.00	13.12	QP
0.600	38.55	0.21	46.00	7.45	AV
0.730	36.63	0.22	56.00	19.37	QP
0.730	29.81	0.22	46.00	16.19	AV
0.920	36.14	0.23	56.00	19.86	QP
0.920	28.42	0.23	46.00	17.58	AV
1.230	34.70	0.24	56.00	21.30	QP
1.230	28.23	0.24	46.00	17.77	AV

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard

FCC §15.247 (d); §15.209; §15.205;

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cisp} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cisp} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit.

Based on CISPR 16-4-2: 2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Dongguan) is:

30M~200MHz: 5.0 dB

200M~1GHz: 6.2 dB

1G~6GHz: 4.45 dB


6G~18GHz: 5.23 dB


Table 1 – Values of U_{cisp}

Measurement	U_{cisp}
Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB

EUT Setup

Below 1GHz:



Above 1GHz:

The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.4-2003. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30MHz – 1000 MHz	120 kHz	300 kHz	120kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	Ave.

Test Procedure

During the radiated emissions, the adapter was connected to the AC floor outlet and the other support equipments were connected to the second AC floor outlet. #

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz - 1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI TEST RECEIVER	ESCI	100224	2013-5-6	2014-5-5
Sunol Sciences	Antenna	JB3	A060611-1	2011-9-6	2014-9-5
HP	HP AMPLIFIER	8447E	2434A02181	N/A	N/A
R&S	Spectrum analyzer	FSEM 30	849016/001	2012-12-7	2013-12-6
ETS LINDGREN	horn antenna	3115	000 527 35	2012-9-6	2015-9-5
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	N/A	N/A
R&S	Spectrum analyzer	FSP 38	100478	2013-6-16	2014-6-15
mun Technologies	Horn antenna	ARH-4223-02	1007726-02-1304	2013-6-16	2014-6-15
QUINSTAR	Amplifier	QLW-18045536-J0	15964001001	N/A	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, and section 15.205, 15.209 and 15.247, with the worst margin reading of:

8.33 dB at 7440 MHz in the Vertical polarization of BDR Mode

Test Data

Environmental Conditions

Temperature:	26.6 °C
Relative Humidity:	64 %
ATM Pressure:	100.3 kPa

** The testing was performed by Ares Liu on 2013-09-30.*

Mode: Transmitting

BDR Mode (GFSK):


Frequency	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	FCC 15.247	
(MHz)	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)				Limit (dBμV/m)	Margin (dB)
Low Channel: 2402(MHz)									
2402	69.56	PK	V	25.65	3.90	0.00	99.11	N/A	N/A
2402	59.13	AV	V	25.65	3.90	0.00	88.68	N/A	N/A
2402	67.49	PK	H	25.65	3.90	0.00	97.04	N/A	N/A
2402	58.38	AV	H	25.65	3.90	0.00	87.93	N/A	N/A
2390	26.76	PK	V	25.61	3.84	0.00	56.21	74.00	17.79
2390	14.03	AV	V	25.61	3.84	0.00	43.48	54.00	10.52
4804	48.01	PK	V	30.59	4.67	27.26	56.01	74.00	17.99
4804	26.34	AV	V	30.59	4.67	27.26	34.34	54.00	19.66
7206	47.54	PK	V	34.09	6.50	26.30	61.83	74.00	12.17
7206	26.61	AV	V	34.09	6.50	26.30	40.90	54.00	13.10
9608	32.15	PK	V	35.96	8.75	26.22	50.64	74.00	23.36
9608	19.52	AV	V	35.96	8.75	26.22	38.01	54.00	15.99
1593.66	45.37	PK	V	23.79	3.16	26.90	45.42	74.00	28.58
1593.66	21.74	AV	V	23.79	3.16	26.90	21.79	54.00	32.21
327	28.6	QP	V	14.63	2.16	21.59	23.80	46.00	22.20
Middle Channel: 2441(MHz)									
2441	63.45	PK	H	25.75	3.99	0.00	93.19	N/A	N/A
2441	50.09	AV	H	25.75	3.99	0.00	79.83	N/A	N/A
2441	72.36	PK	V	25.75	3.99	0.00	102.10	N/A	N/A
2441	53.52	AV	V	25.75	3.99	0.00	83.26	N/A	N/A
4882	42.19	PK	V	30.79	4.75	27.26	50.47	74.00	23.53
4882	24.96	AV	V	30.79	4.75	27.26	33.24	54.00	20.76
7323	50.43	PK	V	34.38	6.72	26.53	65.00	74.00	9.00
7323	27.29	AV	V	34.38	6.72	26.53	41.86	54.00	12.14
9764	32.78	PK	V	36.33	8.58	25.62	52.07	74.00	21.93
9764	18.67	AV	V	36.33	8.58	25.62	37.96	54.00	16.04
1721	31.19	PK	V	24.04	3.26	26.97	31.52	74.00	42.48
1721	13.8	AV	V	24.04	3.26	26.97	14.13	54.00	39.87
1593.66	39.67	PK	V	23.79	3.16	26.90	39.72	74.00	34.28
1593.66	19.02	AV	V	23.79	3.16	26.90	19.07	54.00	34.93
327	27.6	QP	V	14.63	2.16	21.59	22.80	46.00	23.20
High Channel: 2480(MHz)									
2480	63.57	PK	H	25.85	3.82	0.00	93.24	N/A	N/A
2480	50.3	AV	H	25.85	3.82	0.00	79.97	N/A	N/A
2480	72.38	PK	V	25.85	3.82	0.00	102.05	N/A	N/A
2480	53.36	AV	V	25.85	3.82	0.00	83.03	N/A	N/A
2483.5	29.7	PK	V	25.86	3.80	0.00	59.36	74.00	14.64
2483.5	15.52	AV	V	25.86	3.80	0.00	45.18	54.00	8.82
4960	42.89	PK	V	31.00	4.70	27.27	51.32	74.00	22.68
4960	24.94	AV	V	31.00	4.70	27.27	33.37	54.00	20.63
7440	50.62	PK	V	34.66	6.95	26.56	65.67	74.00	8.33
7440	27.41	AV	V	34.66	6.95	26.56	42.46	54.00	11.54
9920	32.29	PK	V	36.71	8.41	25.50	51.91	74.00	22.09
9920	18.47	AV	V	36.71	8.41	25.50	38.09	54.00	15.91
1593.6	38.18	PK	V	23.79	3.16	26.90	38.23	74.00	35.77
1593.6	18.94	AV	V	23.79	3.16	26.90	18.99	54.00	35.01
327	28.6	QP	V	14.63	2.16	21.59	23.80	46.00	22.20

EDR Mode ($\pi/4$ -DQPSK):


Frequency	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	FCC 15.247	
(MHz)	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)				Limit (dBμV/m)	Margin (dB)
Low Channel: 2402(MHz)									
2402	69.06	PK	V	25.65	3.90	0.00	98.61	N/A	N/A
2402	58.83	AV	V	25.65	3.90	0.00	88.38	N/A	N/A
2402	67.05	PK	H	25.65	3.90	0.00	96.60	N/A	N/A
2402	57.92	AV	H	25.65	3.90	0.00	87.47	N/A	N/A
2390	28.25	PK	V	25.61	3.84	0.00	57.70	74.00	16.30
2390	14.55	AV	V	25.61	3.84	0.00	44.00	54.00	10.00
4804	47.51	PK	V	30.59	4.67	27.26	55.51	74.00	18.49
4804	25.89	AV	V	30.59	4.67	27.26	33.89	54.00	20.11
7206	47.31	PK	V	34.09	6.50	26.30	61.60	74.00	12.40
7206	26.08	AV	V	34.09	6.50	26.30	40.37	54.00	13.63
9608	31.28	PK	V	35.96	8.75	26.22	49.77	74.00	24.23
9608	19.09	AV	V	35.96	8.75	26.22	37.58	54.00	16.42
1593.66	44.82	PK	V	23.79	3.16	26.90	44.87	74.00	29.13
1593.66	21.24	AV	V	23.79	3.16	26.90	21.29	54.00	32.71
327	28.1	QP	V	14.63	2.16	21.59	23.30	46.00	22.70
Middle Channel: 2441(MHz)									
2441	62.94	PK	H	25.75	3.99	0.00	92.68	N/A	N/A
2441	49.63	AV	H	25.75	3.99	0.00	79.37	N/A	N/A
2441	71.82	PK	V	25.75	3.99	0.00	101.56	N/A	N/A
2441	53.01	AV	V	25.75	3.99	0.00	82.75	N/A	N/A
4882	41.7	PK	V	30.79	4.75	27.26	49.98	74.00	24.02
4882	24.44	AV	V	30.79	4.75	27.26	32.72	54.00	21.28
7323	49.93	PK	V	34.38	6.72	26.53	64.50	74.00	9.50
7323	26.85	AV	V	34.38	6.72	26.53	41.42	54.00	12.58
9764	32.36	PK	V	36.33	8.58	25.62	51.65	74.00	22.35
9764	18.91	AV	V	36.33	8.58	25.62	38.20	54.00	15.80
1721	30.71	PK	V	24.04	3.26	26.97	31.04	74.00	42.96
1721	14.32	AV	V	24.04	3.26	26.97	14.65	54.00	39.35
1593.66	39.12	PK	V	23.79	3.16	26.90	39.17	74.00	34.83
1593.66	20.01	AV	V	23.79	3.16	26.90	20.06	54.00	33.94
327	27.1	QP	V	14.63	2.16	21.59	22.30	46.00	23.70
High Channel: 2480(MHz)									
2480	63.07	PK	H	25.85	3.82	0.00	92.74	N/A	N/A
2480	49.86	AV	H	25.85	3.82	0.00	79.53	N/A	N/A
2480	71.96	PK	V	25.85	3.82	0.00	101.63	N/A	N/A
2480	52.83	AV	V	25.85	3.82	0.00	82.50	N/A	N/A
2483.5	29.25	PK	V	25.86	3.80	0.00	58.91	74.00	15.09
2483.5	15.01	AV	V	25.86	3.80	0.00	44.67	54.00	9.33
4960	42.4	PK	V	31.00	4.70	27.27	50.83	74.00	23.17
4960	24.48	AV	V	31.00	4.70	27.27	32.91	54.00	21.09
7440	50.15	PK	V	34.66	6.95	26.56	65.20	74.00	8.80
7440	26.9	AV	V	34.66	6.95	26.56	41.95	54.00	12.05
9920	31.85	PK	V	36.71	8.41	25.50	51.47	74.00	22.53
9920	18.92	AV	V	36.71	8.41	25.50	38.54	54.00	15.46
1593.6	29.73	PK	V	23.79	3.16	26.90	29.78	74.00	44.22
1593.6	13.91	AV	V	23.79	3.16	26.90	13.96	54.00	40.04
327	27.2	QP	V	14.63	2.16	21.59	22.40	46.00	23.60

EDR Mode (8-DPSK):

Frequency	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	FCC 15.247	
(MHz)	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)				Limit (dBμV/m)	Margin (dB)
Low Channel: 2402(MHz)									
2402	69.34	PK	V	25.65	3.90	0.00	98.89	N/A	N/A
2402	58.92	AV	V	25.65	3.90	0.00	88.47	N/A	N/A
2402	67.25	PK	H	25.65	3.90	0.00	96.80	N/A	N/A
2402	58.14	AV	H	25.65	3.90	0.00	87.69	N/A	N/A
2390	27.5	PK	V	25.61	3.84	0.00	56.95	74.00	17.05
2390	14.06	AV	V	25.61	3.84	0.00	43.51	54.00	10.49
4804	47.73	PK	V	30.59	4.67	27.26	55.73	74.00	18.27
4804	26.18	AV	V	30.59	4.67	27.26	34.18	54.00	19.82
7206	47.35	PK	V	34.09	6.50	26.30	61.64	74.00	12.36
7206	26.32	AV	V	34.09	6.50	26.30	40.61	54.00	13.39
9608	31.99	PK	V	35.96	8.75	26.22	50.48	74.00	23.52
9608	19.2	AV	V	35.96	8.75	26.22	37.69	54.00	16.31
1593.66	45.13	PK	V	23.79	3.16	26.90	45.18	74.00	28.82
1593.66	21.56	AV	V	23.79	3.16	26.90	21.61	54.00	32.39
327	29.4	QP	V	14.63	2.16	21.59	24.60	46.00	21.40
Middle Channel: 2441(MHz)									
2441	63.21	PK	H	25.75	3.99	0.00	92.95	N/A	N/A
2441	49.83	AV	H	25.75	3.99	0.00	79.57	N/A	N/A
2441	72.14	PK	V	25.75	3.99	0.00	101.88	N/A	N/A
2441	53.27	AV	V	25.75	3.99	0.00	83.01	N/A	N/A
4882	41.95	PK	V	30.79	4.75	27.26	50.23	74.00	23.77
4882	24.79	AV	V	30.79	4.75	27.26	33.07	54.00	20.93
7323	50.24	PK	V	34.38	6.72	26.53	64.81	74.00	9.19
7323	27.05	AV	V	34.38	6.72	26.53	41.62	54.00	12.38
9764	32.53	PK	V	36.33	8.58	25.62	51.82	74.00	22.18
9764	18.42	AV	V	36.33	8.58	25.62	37.71	54.00	16.29
1721	31.96	PK	V	24.04	3.26	26.97	32.29	74.00	41.71
1721	14.07	AV	V	24.04	3.26	26.97	14.40	54.00	39.60
1593.66	39.42	PK	V	23.79	3.16	26.90	39.47	74.00	34.53
1593.66	19.13	AV	V	23.79	3.16	26.90	19.18	54.00	34.82
327	27.36	QP	V	14.63	2.16	21.59	22.56	46.00	23.44
High Channel: 2480(MHz)									
2480	63.38	PK	H	25.85	3.82	0.00	93.05	N/A	N/A
2480	50.04	AV	H	25.85	3.82	0.00	79.71	N/A	N/A
2480	72.11	PK	V	25.85	3.82	0.00	101.78	N/A	N/A
2480	53.18	AV	V	25.85	3.82	0.00	82.85	N/A	N/A
2483.5	29.44	PK	V	25.86	3.80	0.00	59.10	74.00	14.90
2483.5	15.24	AV	V	25.86	3.80	0.00	44.90	54.00	9.10
4960	42.61	PK	V	31.00	4.70	27.27	51.04	74.00	22.96
4960	24.75	AV	V	31.00	4.70	27.27	33.18	54.00	20.82
7440	50.33	PK	V	34.66	6.95	26.56	65.38	74.00	8.62
7440	27.15	AV	V	34.66	6.95	26.56	42.20	54.00	11.80
9920	32.03	PK	V	36.71	8.41	25.50	51.65	74.00	22.35
9920	18.27	AV	V	36.71	8.41	25.50	37.89	54.00	16.11
1593.6	37.91	PK	V	23.79	3.16	26.90	37.96	74.00	36.04
1593.6	18.73	AV	V	23.79	3.16	26.90	18.78	54.00	35.22
327	28.42	QP	V	14.63	2.16	21.59	23.62	46.00	22.38


Conducted Spurious Emissions at Antenna Port*BDR Mode (GFSK):***Low Channel**

Date: 30.SEP.2013 10:09:27

Middle Channel

Date: 30.SEP.2013 10:16:50


High Channel



Date: 30.SEP.2013 10:29:47


EDR Mode ($\pi/4$ -DQPSK):

Low Channel




Date: 30.SEP.2013 11:15:58

Middle Channel



Date: 30.SEP.2013 11:00:12


High Channel



Date: 30.SEP.2013 10:53:09


EDR Mode (8-DPSK):

Low Channel




Date: 30.SEP.2013 11:22:43

Middle Channel



Date: 30.SEP.2013 11:26:23

High Channel



Date: 30.SEP.2013 11:30:40

FCC §15.247(a) (1) - CHANNEL SEPARATION TEST**Applicable Standard**

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.50 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum analyzer	FSP 38	100478	2013-6-16	2014-6-15

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

1. Set the EUT in transmitting mode, spectrum Bandwidth was set at 30 kHz, maxhold the channel.
2. Set the adjacent channel of the EUT maxhold another truce
3. Measure the channel separation.

Test Data**Environmental Conditions**

Temperature:	27.8 ° C
Relative Humidity:	57 %
ATM Pressure:	100.3 kPa

The testing was performed by Ares Liu on 2013-09-30.


Test Result: Compliance.

Please refer to following tables and plots

Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)	Result
BDR Mode (GFSK)	Low	2402	1.003	0.61	Pass
	Adjacent	2403			
	Middle	2441	1.003	0.59	Pass
	Adjacent	2442			
	High	2480	1.001	0.61	Pass
	Adjacent	2479			
EDR Mode ($\pi/4$ -DQPSK):	Low	2402	1.001	0.81	Pass
	Adjacent	2403			
	Middle	2441	1.003	0.81	Pass
	Adjacent	2442			
	High	2480	1.000	0.81	Pass
	Adjacent	2479			
EDR Mode (8-DPSK):	Low	2402	1.001	0.81	Pass
	Adjacent	2403			
	Middle	2441	1.003	0.81	Pass
	Adjacent	2442			
	High	2480	1.000	0.81	Pass
	Adjacent	2479			

BDR Mode (GFSK):



Date: 30.SEP.2013 10:08:49

Ref 11.5 dBm * Att 20 dB

* RBW 30 kHz Delta 1 [T1] 0.05 dB
 * VBW 100 kHz
 SWT 5 ms 1.002539460 MHz

Offset 1.5 dB


Marker 1 [T1] 6.11 dBm
 2.440958000 GHz

1 PK MAXH


3dB

Center 2.4415 GHz 200 kHz/ Span 2 MHz


High Channel



Page 30 of 69


*EDR Mode ($\pi/4$ -DQPSK):***Low Channel**

Date: 30.SEP.2013 11:15:15

Middle Channel

Date: 30.SEP.2013 10:58:25


High Channel



Date: 30.SEP.2013 10:51:45


EDR Mode (8-DPSK):

Low Channel




Date: 30.SEP.2013 11:21:49

Middle Channel



Date: 30.SEP.2013 11:25:38

High Channel



Date: 30.SEP.2013 11:29:13

FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING**Applicable Standard**

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum analyzer	FSP 38	100478	2013-6-16	2014-6-15

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	27.8 ° C
Relative Humidity:	57 %
ATM Pressure:	100.3 kPa

The testing was performed by Ares Liu on 2013-09-30.

Test Result: Compliance.


Please refer to following tables and plots

Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
BDR Mode (GFSK)	Low	2402	0.917
	Middle	2441	0.879
	High	2480	0.917
EDR Mode ($\pi/4$ -DQPSK):	Low	2402	1.215
	Middle	2441	1.217
	High	2480	1.221
EDR Mode (8-DPSK):	Low	2402	1.209
	Middle	2441	1.211
	High	2480	1.209


Please refer to the following plots.

BDR Mode (GFSK):




Date: 30.SEP.2013 10:07:16

Middle Channel




Date: 30.SEP.2013 10:11:35


High Channel



Date: 30.SEP.2013 10:20:17


*EDR Mode ($\pi/4$ -DQPSK):***Low Channel**

Date: 30.SEP.2013 11:14:31

Middle Channel

Date: 30.SEP.2013 10:56:23


High Channel



Date: 30.SEP.2013 10:51:00


EDR Mode (8-DPSK):

Low Channel




Date: 30.SEP.2013 11:20:53

Middle Channel



Date: 30.SEP.2013 11:24:44

High Channel



Date: 30.SEP.2013 11:28:05

FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST**Applicable Standard**

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the Max-Hold function record the Quantity of the channel.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum analyzer	FSP 38	100478	2013-6-16	2014-6-15

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	27.8 ° C
Relative Humidity:	57 %
ATM Pressure:	100.3 kPa

The testing was performed by Ares Liu on 2013-09-30.


Test Result: Compliance.

Please refer to following tables and plots

Test Mode: Transmitting

BDR Mode (GFSK):


Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥ 15



Date: 30.SEP.2013 13:11:47

EDR Mode ($\pi/4$ -DQPSK):


Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥ 15



Date: 30.SEP.2013 13:10:03

EDR Mode (8-DPSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥ 15



Date: 30.SEP.2013 13:07:24

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)

Applicable Standard

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT was worked in channel hopping; Spectrum SPAN was set as 0. Sweep was set as 0.4 * channel no. (s), the quantity of pulse was get from single sweep. In addition, the time of single pulses was tested.

Dwell Time= time slot length * hope rate/ number of hopping channels * 31.6s
Hop rate=1600/s

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum analyzer	FSP 38	100478	2013-6-16	2014-6-15

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	27.8 ° C
Relative Humidity:	57 %
ATM Pressure:	100.3 kPa

The testing was performed by Ares Liu on 2013-09-30.

Test Result: Compliance.


Please refer to following tables and plots

Test Mode: Transmitting

BDR Mode (GFSK):


Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
DH1	Low	0.408	0.130	0.4	Pass
	Middle	0.409	0.131	0.4	Pass
	High	0.408	0.131	0.4	Pass
	Note: Dwell time=Pulse time (ms) $\times$ (1600/2/79) $\times$ 31.6 s				
DH3	Low	1.675	0.268	0.4	Pass
	Middle	1.675	0.268	0.4	Pass
	High	1.675	0.268	0.4	Pass
	Note: Dwell time=Pulse time (ms) $\times$ (1600/4/79) $\times$ 31.6 s				
DH5	Low	2.925	0.312	0.4	Pass
	Middle	2.925	0.312	0.4	Pass
	High	2.925	0.312	0.4	Pass
	Note: Dwell time=Pulse time (ms) $\times$ (1600/6/79) $\times$ 31.6 s				

DH1: Low Channel




Date: 30.SEP.2013 10:09:13

DH1: Middle Channel




Date: 30.SEP.2013 10:14:22

DH1: High Channel




Date: 30.SEP.2013 10:28:20

DH3: Low Channel




Date: 30.SEP.2013 13:15:47

DH3: Middle Channel




Date: 30.SEP.2013 13:16:16

DH3: High Channel




Date: 30.SEP.2013 13:18:56

DH5: Low Channel




Date: 30.SEP.2013 13:26:02

DH5: Middle Channel



Date: 30.SEP.2013 13:25:39

DH5: High Channel




Date: 30.SEP.2013 13:25:30

EDR Mode ($\pi/4$ -DQPSK):


Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
DH1	Low	0.422	0.135	0.4	Pass
	Middle	0.420	0.134	0.4	Pass
	High	0.422	0.135	0.4	Pass
	Note: Dwell time=Pulse time (ms) $\times$ (1600/2/79) $\times$ 31.6 s				
DH3	Low	1.685	0.270	0.4	Pass
	Middle	1.675	0.268	0.4	Pass
	High	1.685	0.270	0.4	Pass
	Note: Dwell time=Pulse time (ms) $\times$ (1600/4/79) $\times$ 31.6 s				
DH5	Low	2.925	0.312	0.4	Pass
	Middle	2.925	0.312	0.4	Pass
	High	2.925	0.312	0.4	Pass
	Note: Dwell time=Pulse time (ms) $\times$ (1600/6/79) $\times$ 31.6 s				

DH1: Low Channel




Date: 30.SEP.2013 11:15:37

DH1: Middle Channel




Date: 30.SEP.2013 10:59:51

DH1: High Channel




Date: 30.SEP.2013 10:52:49

DH3: Low Channel




Date: 30.SEP.2013 13:21:11

DH3: Middle Channel




Date: 30.SEP.2013 13:20:56

DH3: High Channel




Date: 30.SEP.2013 13:21:45

DH5: Low Channel




Date: 30.SEP.2013 13:29:07

DH5: Middle Channel



Date: 30.SEP.2013 13:28:54


DH5: High Channel



Date: 30.SEP.2013 13:28:46


EDR Mode (8-DPSK):

Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
DH1	Low	0.420	0.134	0.4	Pass
	Middle	0.420	0.134	0.4	Pass
	High	0.422	0.135	0.4	Pass
	Note: Dwell time=Pulse time (ms) $\times$ (1600/2/79) $\times$ 31.6 s				
DH3	Low	1.685	0.270	0.4	Pass
	Middle	1.685	0.270	0.4	Pass
	High	1.685	0.270	0.4	Pass
	Note: Dwell time=Pulse time (ms) $\times$ (1600/4/79) $\times$ 31.6 s				
DH5	Low	2.925	0.312	0.4	Pass
	Middle	2.925	0.312	0.4	Pass
	High	2.925	0.312	0.4	Pass
	Note: Dwell time=Pulse time (ms) $\times$ (1600/6/79) $\times$ 31.6 s				

DH1: Low Channel


Date: 30.SEP.2013 11:22:09

DH1: Middle Channel




Date: 30.SEP.2013 11:26:03

DH1: High Channel




Date: 30.SEP.2013 11:30:19

DH3: Low Channel




Date: 30.SEP.2013 13:23:32

DH3: Middle Channel




Date: 30.SEP.2013 13:23:43

DH3: High Channel




Date: 30.SEP.2013 13:24:02

DH5: Low Channel




Date: 30.SEP.2013 13:27:23

DH5: Middle Channel



Date: 30.SEP.2013 13:27:30

DH5: High Channel



Date: 30.SEP.2013 13:27:36

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT**Applicable Standard**

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts

Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to an EMI test receiver.
3. Add a correction factor to the display.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum analyzer	FSP 38	100478	2013-6-16	2014-6-15

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	27.8 ° C
Relative Humidity:	57 %
ATM Pressure:	100.3 kPa

The testing was performed by Ares Liu on 2013-09-30.


Test Result: Compliance.

Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	Output power (dBm)	Limit (dBm)
BDR Mode (GFSK)	Low	2402	5.14	30
	Middle	2441	5.58	30
	High	2480	6.33	30
EDR Mode ($\pi/4$ -DQPSK)	Low	2402	4.02	30
	Middle	2441	5.27	30
	High	2480	5.91	30
EDR Mode (8-DPSK)	Low	2402	4.30	30
	Middle	2441	5.00	30
	High	2480	5.40	30


Note: The data above was tested in conducted mode.

BDR Mode (GFSK):




Date: 30.SEP.2013 10:07:08

Output Power, Middle



Date: 30.SEP.2013 10:11:28


Output Power, High



Date: 30.SEP.2013 10:20:09


EDR Mode ($\pi/4$ -DQPSK):

Output Power, Low




Date: 30.SEP.2013 11:14:19

Output Power, Middle



Date: 30.SEP.2013 10:56:12


Output Power, High



Date: 30.SEP.2013 10:50:49


EDR Mode (8-DPSK):

Output Power, Low




Date: 30.SEP.2013 11:20:42

Output Power, Middle



Date: 30.SEP.2013 11:24:33

Output Power, High



Date: 30.SEP.2013 11:27:54

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum analyzer	FSP 38	100478	2013-6-16	2014-6-15


* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data


Environmental Conditions

Temperature:	27.8 °C
Relative Humidity:	57 %
ATM Pressure:	100.3 kPa


The testing was performed by Ares Liu on 2013-09-30.

Test Result: Compliance*BDR Mode (GFSK):***Band Edge, Left Side**


Date: 30.SEP.2013 10:09:40

Band Edge, Right Side


Date: 30.SEP.2013 10:32:00

*EDR Mode ($\pi/4$ -DQPSK):***Band Edge, Left Side**


Date: 30.SEP.2013 11:16:18

Band Edge, Right Side

Date: 30.SEP.2013 10:53:29

*EDR Mode (8-DPSK):***Band Edge, Left Side**

Date: 30.SEP.2013 11:23:02

Band Edge, Right Side

Date: 30.SEP.2013 11:31:00

******* END OF REPORT *******