

Output Power by Radio Configuration (**CDMA**)

		RC1	RC2	RC3		RC4		RC5
Spreading Rate		1	1	1		1		3
Rate Set, bps (R-FCH)								
Code Rate		$\frac{1}{3}$	$\frac{1}{2}$	$\frac{1}{4}$	$\frac{1}{2}$	$\frac{1}{4}$		$\frac{1}{4}$ $\frac{1}{3}$
Modulation		64-ray orthogonal	64-ray orthogonal	BPSK + pilot		BPSK + pilot		BPSK + pilot
Service Option	Type	Power (dBm)	Power (dBm)	Power (dBm)		Power (dBm)		Power (dBm)
1	Voice	N/A	N/A	N/A		N/A		N/A
2	Loop Back	24.9	N/A	24.8		N/A		N/A
3	Voice	24.9	N/A	24.8		N/A		N/A
9	Loop Back	N/A	24.9	N/A		24.8		N/A
17	Voice	N/A	25.0	N/A		N/A		N/A
32	+F-SCH	N/A	N/A	24.8		N/A		N/A
32	+SCH	N/A	N/A	24.9		N/A		N/A
33	---	N/A	N/A	TBD		N/A		N/A
33	+F-SCH	N/A	N/A	TBD		N/A		N/A
55	Loop Back	24.9	24.9	24.8		24.8		N/A
032768	Voice	N/A	25.0	N/A		24.8		N/A

SO33: Lab application upgrade

EVDO:EVDO - 24.9dBm (153.6Kbps Reverse Data Rate)

Output Power by Radio Configuration (**PCS**)

		RC1	RC2	RC3		RC4		RC5
Spreading Rate		1	1	1		1		3
Rate Set, bps (R-FCH)								
Code Rate		$\frac{1}{3}$	$\frac{1}{2}$	$\frac{1}{4}$	$\frac{1}{2}$	$\frac{1}{4}$		$\frac{1}{4}$ $\frac{1}{3}$
Modulation		64-ray orthogonal	64-ray orthogonal	BPSK + pilot		BPSK + pilot		BPSK + pilot
Service Option	Type	Power (dBm)	Power (dBm)	Power (dBm)		Power (dBm)		Power (dBm)
1	Voice	N/A	N/A	N/A		N/A		N/A
2	Loop Back	25.0	N/A	24.9		N/A		N/A
3	Voice	25.0	N/A	N/A		N/A		N/A
9	Loop Back	N/A	25.0	N/A		24.9		N/A
17	Voice	N/A	25.0	N/A		N/A		N/A
32	+F-SCH	N/A	N/A	24.9		N/A		N/A
32	+SCH	N/A	N/A	24.7		N/A		N/A
33	---	N/A	N/A	TBD		N/A		N/A
33	+F-SCH	N/A	N/A	TBD		N/A		N/A
55	Loop Back	25.0	25.0	25.0		24.9		N/A
032768	Voice	N/A	25.0	N/A		N/A		N/A

SO33: Lab application upgrade

EVDO:EVDO - 25.0dBm (153.6Kbps Reverse Data Rate)