



# FCC Doc TEST REPORT

**REPORT NO. :** FD991126E02

**MODEL NO. :** AR5B225

**RECEIVED :** Nov. 25, 2010

**TESTED :** Dec. 22, 2010 to Jan. 03, 2011

**ISSUED:** Jan. 26, 2011

**APPLICANT :** Atheros Communications, Inc.

**ADDRESS :** 1700 Technology Drive, San Jose, CA 95110

**ISSUED BY:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch Hsin Chu Laboratory

**LAB ADDRESS:** No. 81-1, Lu Liao Keng, 9th Ling,Wu Lung Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan

**TEST LOCATION (1):** No. 81-1, Lu Liao Keng, 9th Ling,Wu Lung Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan

**TEST LOCATION (2):** No. 49, Ln. 206, Wende Rd., Shangshan Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan

This test report consists of 28 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval, or endorsement by TAF, NVLAP, NIST, or any government agency. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.





## Table of Contents

<b>RELEASE CONTROL RECORD .....</b>	<b>3</b>
<b>1      CERTIFICATION.....</b>	<b>4</b>
<b>2      SUMMARY OF TEST RESULTS .....</b>	<b>5</b>
2.1    MEASUREMENT UNCERTAINTY .....	5
<b>3      GENERAL INFORMATION .....</b>	<b>6</b>
3.1    GENERAL DESCRIPTION OF EUT .....	6
3.2    ANTENNA SPECIFICATIONS .....	7
3.3    GENERAL DESCRIPTION OF TEST MODE .....	7
3.4    DESCRIPTION OF SUPPORT UNITS.....	8
3.5    CONFIGURATION OF SYSTEM UNDER TEST .....	8
<b>4      EMISSION TEST .....</b>	<b>9</b>
4.1    CONDUCTED EMISSION MEASUREMENT .....	9
4.1.1   LIMITS OF CONDUCTED EMISSION MEASUREMENT .....	9
4.1.2   TEST INSTRUMENTS .....	9
4.1.3   TEST PROCEDURE .....	10
4.1.4   DEVIATION FROM TEST STANDARD .....	10
4.1.5   TEST SETUP .....	11
4.1.6   EUT OPERATING CONDITIONS.....	11
4.1.7   TEST RESULTS.....	12
4.2    RADIATED EMISSION MEASUREMENT.....	14
4.2.1   LIMITS OF RADIATED EMISSION MEASUREMENT .....	14
4.2.2   TEST INSTRUMENTS .....	15
4.2.3   TEST PROCEDURE .....	17
4.2.4   DEVIATION FROM TEST STANDARD .....	17
4.2.5   TEST SETUP .....	18
4.2.6   EUT OPERATING CONDITIONS.....	18
4.2.7   TEST RESULTS (MODE 1) .....	19
4.2.8   TEST RESULTS (MODE 2) .....	23
<b>5      INFORMATION ON THE TESTING LABORATORIES.....</b>	<b>27</b>
<b>6      APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB.....</b>	<b>28</b>



A D T

## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
Original release	NA	Jan. 26, 2011



A D T

## 1 CERTIFICATION

**PRODUCT :** 1X1 802.11b/g/n - BT Combo PCIe minicard

**BRAND NAME :** Atheros

**MODEL NO.:** AR5B225

**TESTED :** Dec. 22, 2010 to Jan. 03, 2011

**TEST SAMPLE :** R&D SAMPLE

**APPLICANT :** Atheros Communications, Inc.

**STANDARDS :** FCC Part 15, Subpart B, Class B

ANSI C63.4-2003

The above equipment (Model: AR5B225) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and was in compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**PREPARED BY** : Carol Liao , **DATE:** Jan. 26, 2011  
( Carol Liao, Specialist )

**APPROVED BY** : May Chen , **DATE:** Jan. 26, 2011  
( May Chen, Deputy Manager )



## 2 SUMMARY OF TEST RESULTS

Standard	Test Type	Result	Remarks
FCC Part 15, Subpart B, Class B	Conducted Test	<b>PASS</b>	Meets Class B Limit Minimum passing margin is -12.70 dB at 0.314 MHz
	Radiated Test	<b>PASS</b>	Meets Class B Limit Minimum passing margin is -0.70 dB at 165.95 MHz

### 2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Value
Conducted emissions	2.45 dB
Radiated emissions (30MHz-1GHz)	3.76 dB
Radiated emissions (1GHz -18GHz)	2.19 dB
Radiated emissions (18GHz -40GHz)	2.55 dB



### 3 GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	1X1 802.11b/g/n - BT Combo PCIe minicard
MODEL NO.	AR5B225
POWER SUPPLY	DC 3.3V from host equipment
POWER CORD	NA
DATA CABLE SUPPLIED	NA
I/O PORTS	NA
ASSOCIATED DEVICES	NA

##### NOTE:

1. There are Bluetooth technology and WLAN technology used for the EUT.
2. The EUT is 1 \* 1 spatial SISO without beam forming function.
3. For radiated : The EUT's antenna was pre-tested under the following modes:

Test Mode	Description
Mode A	X-Y axis
Mode B	Y-Z axis
Mode C	X-Z axis

From the above modes, the worst case was found in **Mode A**. Therefore only the test data of the mode was recorded in this report.

4. The EUT complies with 802.11n standards and backwards compatible with 802. 11a, 802.11b, 802.11g products.
5. The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.



A D T

## 3.2 ANTENNA SPECIFICATIONS

There are five sets of antennas provided to this EUT, please refer to the following table:

No.	Brand	Model	Gain(dBi) (included cable loss)	Antenna Type	Connector	Cable Loss(dB)	Cable Length
1	WNC	81-EBJ15.005	3.62	PIFA	IPEX	1.15	300mm
2	INPAQ	DAMA1BM30000402	3.2	Dipole	SMA Reverse	0.5	N.A.
3	Tyco	TBN009	2.06	PIFA	U.FL	0.96	300mm
4	Tyco	TBN010	2.64	PIFA	U.FL	0.95	300mm
5	Hitachi Cable	HBY17	1.97	PIFA	IPEX	0.99	306mm

Note: 1. Main – Wireless / Aux – BT  
2. Antenna (model: 81-EBJ15.005) were chosen for final test.

## 3.3 GENERAL DESCRIPTION OF TEST MODE

The EUT was tested under following test modes:

Conducted test	
Test Mode	Description
Mode 1	With antenna 1: PIFA antenna
Radiated test	
Test Mode	Description
Mode 1	With antenna 1: PIFA antenna
Mode 2	With antenna 2: Dipole antenna



### 3.4 DESCRIPTION OF SUPPORT UNITS


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK COMPUTER	Lenovo	3000 N200	NA	NA
2	EXTENSION CARD	Atheros	NA	NA	NA

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	NA

**NOTE:** All power cords of the above support units are non shielded (1.8m).

### 3.5 CONFIGURATION OF SYSTEM UNDER TEST





## 4 EMISSION TEST

### 4.1 CONDUCTED EMISSION MEASUREMENT

#### 4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

##### TEST STANDARD:

FCC Part 15, Subpart B (Section: 15.107)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 - 56	56 - 46
0.50 - 5.0	73	60	56	46
5.0 - 30.0	73	60	60	50

NOTE: (1) The lower limit shall apply at the transition frequencies.

(2) The limit decreases linearly with the logarithm of the frequency in the range 0.15 to 0.50 MHz

(3) All emanation from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

#### 4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
ROHDE & SCHWARZ Test Receiver	ESCS 30	100287	Mar. 01, 2010	Feb. 28, 2011
Line-Impedance Stabilization Network (for EUT)	NSLK 8127	8127-523	Sep. 17, 2010	Sep. 16, 2011
Line-Impedance Stabilization Network (for Peripheral)	ENV-216	100072	June 11, 2010	June 10, 2011
RF Cable (JYEBAO)	5DFB	CONCAB-003	Aug. 06, 2010	Aug. 05, 2011
50 ohms Terminator	50	3	Nov. 03, 2010	Nov. 02, 2011
Software	BV ADT_Cond_V7.3.7	NA	NA	NA

##### Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Shielded Room No. A.
3. The VCCI Con A Registration No. is C-817.



A D T

#### 4.1.3 TEST PROCEDURE


The basic test procedure was in accordance with ANSI C63.4-2003 (section 7)

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels over 10dB under the prescribed limits could not be reported.

#### 4.1.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.1.5 TEST SETUP



**Note:**

1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

#### 4.1.6 EUT OPERATING CONDITIONS

1. Connect the EUT with the support unit 1 (Notebook Computer) which is placed on a testing table.
2. The communication partner run test program “ArcMfgTool 2.0.0.9” to enable EUT under transmission/receiving condition continuously at specific channel frequency.


#### 4.1.7 TEST RESULTS

TEST MODE	Mode 1	6dB BANDWIDTH	9kHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	28deg. C, 67%RH, 1011hPa	TESTED BY	Wen Yu

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
	[MHz]	Factor (dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.158	0.36	48.79	-	49.15	-	65.58	55.58	-16.42	-
2	0.252	0.36	45.20	-	45.56	-	61.71	51.71	-16.15	-
3	0.314	0.36	46.80	-	47.16	-	59.86	49.86	-12.70	-
4	0.505	0.37	34.88	-	35.25	-	56.00	46.00	-20.75	-
5	0.951	0.41	30.86	-	31.27	-	56.00	46.00	-24.73	-
6	1.855	0.45	31.22	-	31.67	-	56.00	46.00	-24.33	-
7	15.207	1.00	34.53	-	35.53	-	60.00	50.00	-24.47	-

**REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.






A D T

TEST MODE	Mode 1	6dB BANDWIDTH	9kHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	28deg. C, 67%RH, 1011hPa	TESTED BY	Wen Yu

No	Freq. [MHz]	Corr. (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.154	0.10	45.91	-	46.01	-	65.78	55.78	-19.78	-
2	0.263	0.10	46.71	-	46.81	-	61.33	51.33	-14.51	-
3	0.287	0.10	44.36	-	44.46	-	60.62	50.62	-16.15	-
4	0.560	0.12	35.17	-	35.29	-	56.00	46.00	-20.71	-
5	0.896	0.15	32.34	-	32.49	-	56.00	46.00	-23.51	-
6	1.504	0.18	31.76	-	31.94	-	56.00	46.00	-24.06	-
7	15.168	0.95	35.38	-	36.33	-	60.00	50.00	-23.67	-

**REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.





A D T

## 4.2 RADIATED EMISSION MEASUREMENT

### 4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

#### TEST STANDARD:

FCC Part 15, Subpart B (Section: 15.109)

FOR FREQUENCY BELOW 1000 MHz (47 CFR Part 15 Subpart B)

FREQUENCY (MHz)	Class A (at 10m)		Class B (at 3m)	
	uV/m	dBuV/m	uV/m	dBuV/m
30 – 88	90	39.1	100	40.0
88 – 216	150	43.5	150	43.5
216 - 960	210	46.4	200	46.0
Above 960	300	49.5	500	54.0

### LIMIT OF RADIATED EMISSION OF FCC PART 15, SUBPART B FOR FREQUENCY ABOVE 1000 MHz

FREQUENCY (MHz)	Class A (dBuV/m) (at 3m)		Class B (dBuV/m) (at 3m)	
	PEAK	AVERAGE	PEAK	AVERAGE
Above 1000	80.0	60.0	74.0	54.0

**Note:** (1) The lower limit shall apply at the transition frequencies.  
(2) Emission level (dBuV/m) = 20 log Emission level (uV/m).  
(3) All emanation from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

### FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement Range (MHz)
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5 <sup>th</sup> harmonic of the highest frequency or 40 GHz, whichever is lower



A D T

## 4.2.2 TEST INSTRUMENTS

For Below 1GHz: Test date: Dec. 22, 2010

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Agilent Spectrum Analyzer	E4446A	MY48250253	Aug. 23, 2010	Aug. 22, 2011
Agilent Pre-Selector	N9039A	MY46520310	Aug. 23, 2010	Aug. 22, 2011
Agilent Signal Generator	N5181A	MY49060347	July 30, 2010	July 29, 2011
LIG NEX1 Test Receiver	ER-265	L09068005	Oct. 25, 2010	Oct. 24, 2011
Mini-Circuits Pre-Amplifier	ZFL-1000VH2B	AMP-ZFL-04	Nov. 16, 2010	Nov. 15, 2011
Agilent Pre-Amplifier	8449B	3008A02465	Mar. 01, 2010	Feb. 28, 2011
Miteq Pre-Amplifier	AFS33-1800265 0-30-8P-44	881786	NA	NA
SCHWARZBECK Trilog Broadband Antenna	VULB 9168	9168-361	Apr. 28, 2010	Apr. 27, 2011
AISI Horn_Antenna	AIH.8018	0000220091110	Nov. 22, 2010	Nov. 21, 2011
SCHWARZBECK Horn_Antenna	BBHA 9170	9170-424	Oct. 08, 2010	Oct. 07, 2011
RF CABLE	NA	RF104-205 RF104-207 RF104-208	Dec. 24, 2009	Dec. 23, 2010
RF Cable	NA	CHHCAB_001	NA	NA
Software	ADT_Radiated_V8.7.05	NA	NA	NA
CT Antenna Tower & Turn Table	NA	NA	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.  
2. The horn antenna, preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.  
3. The test was performed in 966 Chamber No. H.  
4. The FCC Site Registration No. is 797305.  
5. The CANADA Site Registration No. is IC 7450H-3.



A D T

For Above 1GHz: Test date: Dec. 15, 2010

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Agilent Spectrum Analyzer	E4446A	MY48250254	July 14, 2010	July 13, 2011
Agilent Pre-Selector	N9039A	MY46520311	July 14, 2010	July 13, 2011
Agilent Signal Generator	N5181A	MY49060517	July 14, 2010	July 13, 2011
Mini-Circuits Pre-Amplifier	ZFL-1000VH2B	AMP-ZFL-03	Nov. 16, 2010	Nov. 15, 2011
Agilent Pre-Amplifier	8449B	3008A02578	July 05, 2010	July 04, 2011
Miteq Pre-Amplifier	AFS33-1800265 0-30-8P-44	881786	NA	NA
SCHWARZBECK Trilog Broadband Antenna	VULB 9168	9168-360	Apr. 29, 2010	Apr. 28, 2011
AISI Horn_Antenna	AIH.8018	0000320091110	Nov. 12, 2010	Nov. 11, 2011
SCHWARZBECK Horn_Antenna	BBHA 9170	9170-424	Oct. 08, 2010	Oct. 07, 2011
RF CABLE	NA	RF104-201 RF104-203 RF104-204	Dec. 24, 2009	Dec. 23, 2010
RF Cable	NA	CHGCAB_001	NA	NA
Software	ADT_Radiated_V8.7.05	NA	NA	NA
CT Antenna Tower & Turn Table	NA	NA	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.  
2. The horn antenna, preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.  
3. The test was performed in 966 Chamber No. G.  
4. The FCC Site Registration No. is 966073.  
5. The VCCI Site Registration No. is G-137.  
6. The CANADA Site Registration No. is IC 7450H-2.



A D T

### 4.2.3 TEST PROCEDURE

The basic test procedure was in accordance with ANSI C63.4-2003 (section 8)

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the turn table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.


**NOTE:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth is 1MHz and video bandwidth of test receiver/spectrum analyzer is 3MHz for Peak detection at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz for Average detection (AV) at frequency above 1GHz.
3. For measurement of frequency above 1000 MHz, the EUT was set 3 meters away from the interference-receiving antenna.

### 4.2.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

#### 4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6


## 4.2.7 TEST RESULTS (MODE 1)

TEST MODE	Mode 1	FREQUENCY RANGE	Below 1GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION & BANDWIDTH	Quasi-Peak, 120kHz
ENVIRONMENTAL CONDITIONS	20 deg. C, 70 %RH, 1011hPa	TESTED BY	Eric Lee

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	148.42	39.44 QP	43.50	-4.06	1.00 H	349	25.20	14.24
2	<b>165.95</b>	<b>42.80 QP</b>	<b>43.50</b>	<b>-0.70</b>	<b>1.50 H</b>	<b>9</b>	<b>28.79</b>	<b>14.01</b>
3	199.23	41.18 QP	43.50	-2.32	1.50 H	190	29.94	11.24
4	499.55	36.85 QP	46.00	-9.15	1.00 H	253	16.90	19.95
5	593.81	34.89 QP	46.00	-11.11	1.50 H	251	12.67	22.22
6	896.38	39.02 QP	46.00	-6.98	1.00 H	265	12.52	26.50

**REMARKS:**

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.






A D T

TEST MODE	Mode 1	FREQUENCY RANGE	Below 1GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION & BANDWIDTH	Quasi-Peak, 120kHz
ENVIRONMENTAL CONDITIONS	20 deg. C, 70 %RH, 1011hPa	TESTED BY	Eric Lee

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	148.19	32.11 QP	43.50	-11.39	1.00 V	347	17.87	14.24
2	165.95	35.24 QP	43.50	-8.26	1.00 V	151	21.23	14.01
3	298.92	34.68 QP	46.00	-11.32	1.75 V	23	19.79	14.89
4	399.54	35.40 QP	46.00	-10.60	1.00 V	108	17.55	17.85
5	499.56	39.80 QP	46.00	-6.20	1.00 V	96	19.85	19.95
6	739.62	32.45 QP	46.00	-13.55	1.25 V	48	8.71	23.74

**REMARKS:** 1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)  
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)  
3. The other emission levels were very low against the limit.  
4. Margin value = Emission level – Limit value.






A D T

TEST MODE	Mode 1	FREQUENCY RANGE	1000~12500MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION & BANDWIDTH	Peak (PK) Average (AV) 1 MHz
ENVIRONMENTAL CONDITIONS	20 deg. C, 70 %RH, 1011hPa	TESTED BY	Eric Lee

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	4924.00	46.80 PK	74.00	-27.20	1.02 H	45	6.22	40.58
2	4924.00	37.40 AV	54.00	-16.60	1.02 H	45	-3.18	40.58
3	7386.00	53.65 PK	74.00	-20.35	1.11 H	26	8.53	45.12
4	7386.00	39.80 AV	54.00	-14.20	1.11 H	26	-5.32	45.12
5	9848.00	54.24 PK	74.00	-19.76	1.24 H	51	6.67	47.57
6	9848.00	42.10 AV	54.00	-11.90	1.24 H	51	-5.47	47.57

**REMARKS:** 1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)  
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)  
3. The other emission levels were very low against the limit.  
4. Margin value = Emission level – Limit value.






A D T

TEST MODE	Mode 1	FREQUENCY RANGE	1000~12500MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION & BANDWIDTH	Peak (PK) Average (AV) 1 MHz
ENVIRONMENTAL CONDITIONS	20 deg. C, 70 %RH, 1011hPa	TESTED BY	Eric Lee

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	4924.00	45.23 PK	74.00	-28.77	1.60 V	236	4.65	40.58
2	4924.00	34.60 AV	54.00	-19.40	1.60 V	236	-5.98	40.58
3	7386.00	51.24 PK	74.00	-22.76	1.65 V	236	6.12	45.12
4	7386.00	38.50 AV	54.00	-15.50	1.65 V	236	-6.62	45.12
5	9848.00	52.10 PK	74.00	-21.90	1.24 V	51	4.53	47.57
6	9848.00	40.00 AV	54.00	-14.00	1.24 V	51	-7.57	47.57

**REMARKS:**

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.




## 4.2.8 TEST RESULTS (MODE 2)

TEST MODE	Mode 2	FREQUENCY RANGE	Below 1GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION & BANDWIDTH	Quasi-Peak, 120kHz
ENVIRONMENTAL CONDITIONS	20 deg. C, 70 %RH, 1011hPa	TESTED BY	Eric Lee

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	149.20	38.60 QP	43.50	-4.90	1.25 H	24	24.35	14.25
2	165.99	42.40 QP	43.50	-1.10	1.00 H	256	28.40	14.00
3	199.35	42.10 QP	43.50	-1.40	1.75 H	45	30.87	11.23
4	499.62	37.80 QP	46.00	-8.20	1.75 H	84	17.85	19.95
5	593.81	34.89 QP	46.00	-11.11	1.50 H	251	12.67	22.22
6	896.45	38.40 QP	46.00	-7.60	1.25 H	62	11.90	26.50

**REMARKS:**

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.






A D T

TEST MODE	Mode 2	FREQUENCY RANGE	Below 1GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION & BANDWIDTH	Quasi-Peak, 120kHz
ENVIRONMENTAL CONDITIONS	20 deg. C, 70 %RH, 1011hPa	TESTED BY	Eric Lee

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	148.19	32.11 QP	43.50	-11.39	1.00 V	347	17.87	14.24
2	165.95	35.24 QP	43.50	-8.26	1.00 V	151	21.23	14.01
3	298.82	33.27 QP	46.00	-12.73	1.50 V	292	18.39	14.88
4	399.48	34.05 QP	46.00	-11.95	1.50 V	119	16.21	17.84
5	499.55	38.68 QP	46.00	-7.32	1.50 V	296	18.73	19.95
6	739.59	31.66 QP	46.00	-14.34	1.00 V	360	7.92	23.74

**REMARKS:**

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.






A D T

TEST MODE	Mode 2	FREQUENCY RANGE	1000~12500MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION & BANDWIDTH	Peak (PK) Average (AV) 1 MHz
ENVIRONMENTAL CONDITIONS	20 deg. C, 70 %RH, 1011hPa	TESTED BY	Eric Lee

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	4924.00	46.85 PK	74.00	-27.15	1.00 H	223	5.70	41.15
2	4924.00	36.30 AV	54.00	-17.70	1.00 H	223	-4.85	41.15
3	7386.00	53.84 PK	74.00	-20.16	1.54 H	123	8.18	45.66
4	7386.00	38.60 AV	54.00	-15.40	1.54 H	123	-7.06	45.66
5	9848.00	52.24 PK	74.00	-21.76	1.54 H	326	4.33	47.91
6	9848.00	41.23 AV	54.00	-12.77	1.54 H	326	-6.68	47.91

**REMARKS:**

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.






A D T

TEST MODE	Mode 2	FREQUENCY RANGE	1000~12500MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION & BANDWIDTH	Peak (PK) Average (AV) 1 MHz
ENVIRONMENTAL CONDITIONS	20 deg. C, 70 %RH, 1011hPa	TESTED BY	Eric Lee

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	4924.00	44.15 PK	74.00	-29.85	1.42 V	153	3.00	41.15
2	4924.00	34.80 AV	54.00	-19.20	1.42 V	153	-6.35	41.15
3	7386.00	51.84 PK	74.00	-22.16	1.58 V	236	6.18	45.66
4	7386.00	37.66 AV	54.00	-16.34	1.58 V	236	-8.00	45.66
5	9848.00	54.20 PK	74.00	-19.80	1.54 V	74	6.29	47.91
6	9848.00	43.10 AV	54.00	-10.90	1.54 V	74	-4.81	47.91

**REMARKS:**

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.





## 5 INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025:

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site: [www.adt.com.tw/index.5.phtml](http://www.adt.com.tw/index.5.phtml). If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab:**

Tel: 886-2-26052180  
Fax: 886-2-26052943

**Hsin Chu EMC/RF Lab:**

Tel: 886-3-5935343  
Fax: 886-3-5935342

**Hwa Ya EMC/RF/Safety/Telecom Lab:**

Tel: 886-3-3183232  
Fax: 886-3-3185050

**Email:** [service@adt.com.tw](mailto:service@adt.com.tw)

**Web Site:** [www.adt.com.tw](http://www.adt.com.tw)

The address and road map of all our labs can be found in our web site also.



A D T

## 6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

--- END ---