



2010/9/8

FCC ID: PPD-AR5BHB116

| Item | Requirements | EUT |
|------|--|--|
| 1 | The modular transmitter must have its own RF shielding. | The module has been installed in host device, and does not have own shielding case for Limited Modular Approval, please see exhibition external photos. |
| 2 | The modular transmitter must have buffered modulation / data inputs. | The EUT has buffer modulation / data inputs. |
| 3 | The modular transmitter must have its own power supply regulation. | The EUT has its own power supply regulation. |
| 4 | The modular transmitter must comply with the antenna requirements of the Section 15.203 and 15.204(c). | The EUT meets the FCC antenna requirements. The spurious emission, unique antenna connector and photo of antennas are shown in the External and Internal photos. |
| 5 | The modular transmitter must be tested in a stand-alone configuration. | The module was tested in notebook because this is limited module approval with this notebook. |
| 6 | The modular transmitter must be labeled with its own FCC ID number. | The module FCC ID will be put on the notebook label because this is limited module approval with this notebook. |
| 7 | The modular transmitter must comply with any specific rule or operating requirements applicable to the transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. | This module will be integrated with the notebook before shipping to the users. The end users has no chance to install this module. |
| 8 | The modular transmitter must comply with any applicable RF exposure requirement. | The modular transmitter complies with RF exposure on the notebook. |

Effective Date: Immediately.

Michael Green / Manager, Global Product Compliance
Atheros Communications, Inc.

Atheros Communications, Inc. 1700 Technology Drive, San Jose, CA 95110
t 408 773 5200 f 408-773-9940 www.atheros.com