

## FCC SAR TEST REPORT

For

Product Name: 802.11a/b/g/n/ac + BT 4.1 M.2 2230 Type Card

Brand Name: Qualcomm Atheros

Model No.: QCNFA344A

Series Model: N/A

FCCID: PPD-QCNFA344AH

Test Report Number:

C170915S01-SF

Issued for

Qualcomm Atheros, Inc.

1700 Technology Drive, San Jose, CA 95110

Issued by

Compliance Certification Services Inc.

Kun shan Laboratory

No.10 Weiye Rd., Innovation park, Eco&Tec,  
Development Zone, Kunshan City, Jiangsu, China

TEL: 86-512-57355888

FAX: 86-512-57370818



**Note:** This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by A2LA or any government agencies. The test results in the report only apply to the tested sample.

## Revision History

| Revision | REPORT NO.    | Date               | Page Revised | Contents                                   |
|----------|---------------|--------------------|--------------|--|
| Original | C170915S01-SF | September 15, 2017 | N/A          | N/A  |
| 01       | C170915S01-SF | September 18, 2017 | 5            | Update Modulation Technique.               |
|          |               |                    | 7            | Update BT & 2.4GHz Target Power table.     |
|          |               |                    | 48           | Update EQUIPMENT LIST & CALIBRATION table. |

## TABLE OF CONTENTS

|   |           |
|---|-----------|
| <b>1. CERTIFICATE OF COMPLIANCE (SAR EVALUATION) .....</b>            | <b>4</b>  |
| <b>2. EUT DESCRIPTION.....</b>  | <b>5</b>  |
| 2.1 TARGET RF OUTPUT POWER WITH TEST CHANNEL .....                    | 7         |
| 2.2 STATEMENT OF COMPLIANCE.....                                      | 8         |
| <b>3. REQUIREMENTS FOR COMPLIANCE TESTING DEFINED BY THE FCC.....</b> | <b>9</b>  |
| <b>4. TEST METHODOLOGY.....</b>                                       | <b>9</b>  |
| <b>5. TEST CONFIGURATION.....</b>                                     | <b>9</b>  |
| <b>6. DOSIMETRIC ASSESSMENT SETUP.....</b>                            | <b>10</b> |
| 6.1 MEASUREMENT SYSTEM DIAGRAM .....                                  | 11        |
| 6.2 SYSTEM COMPONENTS.....  | 12        |
| <b>7. EVALUATION PROCEDURES.....</b>                                  | <b>15</b> |
| <b>8. MEASUREMENT UNCERTAINTY.....</b>                                | <b>19</b> |
| <b>9. EXPOSURE LIMIT .....</b>  | <b>20</b> |
| <b>10. MEASUREMENT RESULTS.....</b>                                   | <b>21</b> |
| 10.1 TEST LIQUIDS CONFIRMATION .....                                  | 21        |
| 10.2 LIQUID MEASUREMENT RESULTS .....                                 | 22        |
| 10.3 SYSTEM PERFORMANCE CHECK .....                                   | 23        |
| 10.4 EUT TUNE-UP PROCEDURES AND TEST MODE .....                       | 25        |
| 10.5 SAR TEST CONFIGURATIONS.....                                     | 39        |
| 10.6 STANDALONE SAR TEST EXCLUSION .....                              | 40        |
| 10.7 ANTENNA LOCATION .....   | 41        |
| 10.8 SAR MEASUREMENT RESULTS .....                                    | 43        |
| 10.9 REPEATED SAR MEASUREMENT .....                                   | 45        |
| 10.10 SAR MULTI XMITER ASSESSMENT .....                               | 46        |
| <b>11. EQUIPMENT LIST &amp; CALIBRATION STATUS .....</b>              | <b>48</b> |
| <b>12. FACILITIES.....</b>  | <b>49</b> |
| <b>13. REFERENCES.....</b>  | <b>49</b> |
| <b>Appendix A: DUT AND SAR SETUP Photo.....</b>                       | <b>50</b> |
| <b>Appendix B: Plots of Performance Check.....</b>                    | <b>50</b> |
| <b>Appendix C: DASY Calibration Certificate .....</b>                 | <b>57</b> |
| <b>Appendix D: Plots of SAR Test Result .....</b>                     | <b>57</b> |

## 1. CERTIFICATE OF COMPLIANCE (SAR EVALUATION)

|                           |  |
|---------------------------|--|
| <b>Product Name:</b>      | 802.11a/b/g/n/ac + BT 4.1 M.2 2230 Type Card                               |
| <b>Brand name:</b>        | Qualcomm Atheros   |
| <b>Model Name.:</b>       | QCNFA344A  |
| <b>Series Model:</b>      | N/A  |
| <b>Device Category:</b>   | PORTABLE DEVICES   |
| <b>Exposure Category:</b> | GENERAL POPULATION/UNCONTROLLED EXPOSURE                                   |
| <b>Date of Test:</b>      | September 14, 2017 & September 15, 2017                                    |
| <b>Applicant:</b>         | <b>Qualcomm Atheros, Inc.</b><br>1700 Technology Drive, San Jose, CA 95110 |
| <b>Manufacturer:</b>      | <b>Qualcomm Atheros, Inc.</b><br>1700 Technology Drive, San Jose, CA 95110 |
| <b>Application Type:</b>  | Certification  |

### APPLICABLE STANDARDS AND TEST PROCEDURES

| STANDARDS AND TEST PROCEDURES   | TEST RESULT             |
|---|-------------------------|
| FCC 47 CFR Part 2 ( 2.1093)<br>IEEE 1528-2013<br>KDB 248227<br>KDB 865664<br>KDB 447498<br>KDB 616217 | No non-compliance noted |

### Deviation from Applicable Standard

None

The device was tested by Compliance Certification Services Inc. in accordance with the measurement methods and procedures specified in KDB 865664. The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

**Approved by:**

Jeff fang

Jeff.fang  
RF Manager  
Compliance Certification Services Inc.

**Tested by:**

Sam. ye.

Sam.ye  
Test Engineer  
Compliance Certification Services Inc.

## 2. EUT DESCRIPTION

|                              |   |
|------------------------------|---|
| <b>Product Name:</b>         | 802.11a/b/g/n/ac + BT 4.1 M.2 2230 Type Card  |
| <b>Brand name:</b>           | Qualcomm Atheros  |
| <b>Model Name.:</b>          | QCNFA344A   |
| <b>Series Model:</b>         | N/A   |
| <b>FCC ID:</b>               | PPD-QCNFA344AH  |
| <b>Power reduction:</b>      | No  |
| <b>DTM Description:</b>      | N/A   |
| <b>Device Category:</b>      | Production unit   |
| <b>Frequency Range:</b>      | WLAN 2.4GHz Band: 2412 MHz ~ 2472 MHz<br>WLAN 5.2GHz Band: 5180 MHz ~ 5240 MHz<br>WLAN 5.3GHz Band: 5260 MHz ~ 5320 MHz<br>WLAN 5.5GHz Band: 5500 MHz ~ 5700 MHz<br>WLAN 5.8GHz Band: 5745 MHz ~ 5825 MHz<br>Bluetooth: 2402 MHz ~ 2480 MHz   |
| <b>Modulation Technique:</b> | IEEE 802.11a:Orthogonal Frequency Division Multiplexing(OFDM)<br>IEEE 802.11b:Direct Sequence Spread Spectrum(DSSS)<br>IEEE 802.11g:Orthogonal Frequency Division Multiplexing(OFDM)<br>IEEE 802.11n:Orthogonal Frequency Division Multiplexing(OFDM)<br>IEEE 802.11ac:Orthogonal Frequency Division Multiplexing(OFDM)<br>Bluetooth 2.1+EDR:GFSK for 1Mbps;π/4-DQPSK for 2Mbps;<br>8DPSK for 3Mbps<br>Bluetooth 4.1:GFSK |
| <b>Operating Mode:</b>       | Maximum continuous output   |

|                               |      |             |                          |
|-------------------------------|------|-------------|--------------------------|
| <b>Antenna Specification:</b> | Ant1 | Brand       | SPEED                    |
|                               |      | Part Number | Main:F.0G.FN-6038-003-00 |
|                               |      |             | Aux:F.0G.FN-6038-003-00  |
|                               | Ant2 | Type        | PIFA                     |
|                               |      | Brand       | WNC                      |
|                               |      | Part Number | Main:81EAA515.G27        |
|                               |      |             | Aux:81EAA515.G27         |
|                               |      | Type        | PIFA                     |

## Tested System Details

| Product           | Manufacturer | Model No. |
|-------------------|--------------|-----------|
| Notebook Computer | DELL         | P61F      |

## Note:

1. The above EUT information is declared by manufacturer and for more detailed features description please refers to the manufacturer's specifications or User's Manual.

## 2.1 TARGET RF OUTPUT POWER WITH TEST CHANNEL

| Band / Mode | Max. tune-up Power(dBm) |                            |                    |
|-------------|-------------------------|----------------------------|--------------------|
|             | V2.1 + EDR, GFSK        | V2.1 + EDR, $\pi/4$ -DQPSK | V2.1 + EDR, 8-DPSK |
|             | Bluetooth               | 7                          | 7                  |

| Band / Mode | Max. tune-up Power(dBm) |  |
|-------------|-------------------------|--|
|             | BLE4.1, GFSK            |  |
| Bluetooth   | 4.5                     |  |

| Band / Mode          | Channel | SISO Max. tune-up Power (dBm) | MIMO Max. tune-up Power (dBm) |
|----------------------|---------|-------------------------------|-------------------------------|
| 802.11b              | 1 -11   | 20.5                          | 23.5                          |
|                      | 12      | 12.5                          | 15.5                          |
|                      | 13      | 11.5                          | 14.5                          |
| 802.11g              | 1       | 18                            | 21                            |
|                      | 6       | 19.5                          | 22.5                          |
|                      | 11      | 18                            | 21                            |
|                      | 12      | 14                            | 17                            |
|                      | 13      | 3                             | 6                             |
| 802.11n 20MHz        | 1       | 17                            | 20                            |
|                      | 6       | 19.5                          | 22.5                          |
|                      | 11      | 16                            | 19                            |
|                      | 12      | 14                            | 17                            |
|                      | 13      | 1.5                           | 4.5                           |
| 802.11n 40MHz        | 3       | 13                            | 16                            |
|                      | 6       | 18.5                          | 21.5                          |
|                      | 9       | 11                            | 14                            |
|                      | 10      | 11                            | 14                            |
|                      | 11      | 2.5                           | 5.5                           |
| 802.11 a U-NII-1     | 36-48   | 15                            | 18                            |
| 802.11 a U-NII-2A    | 52-64   | 15                            | 18                            |
| 802.11 a U-NII-2C    | 100-140 | 15                            | 18                            |
| 802.11 a U-NII-3     | 149-165 | 15                            | 18                            |
| 802.11 n20 U-NII-1   | 36-48   | 15                            | 18                            |
| 802.11 n20 U-NII-2A  | 52-64   | 15                            | 18                            |
| 802.11 n20 U-NII-2C  | 100-140 | 15                            | 18                            |
| 802.11 n20 U-NII-3   | 149-165 | 15                            | 18                            |
| 802.11 n40 U-NII-1   | 38-46   | 14.5                          | 17.5                          |
| 802.11 n40 U-NII-2A  | 54-62   | 14.5                          | 17.5                          |
| 802.11 n40 U-NII-2C  | 102-134 | 14.5                          | 17.5                          |
| 802.11 n40 U-NII-3   | 151-159 | 14.5                          | 17.5                          |
| 802.11 ac80 U-NII-1  | 42      | 10.5                          | 13.5                          |
| 802.11 ac80 U-NII-2A | 58      | 12.0                          | 15                            |
| 802.11 ac80 U-NII-2C | 106-138 | 14.5                          | 17.5                          |
| 802.11 ac80 U-NII-3  | 155     | 10.0                          | 13                            |

## 2.2 STATEMENT OF COMPLIANCE

The maximum results of Specific Absorption Rate (SAR) found during testing for **Qualcomm Atheros, Single Stream 802.11a/b/g/n/ac + BT 4.1 M.2 Type Card, QCNFA344A**, are as follows.

| Equipment Class | Frequency Band | Highest SAR Summary |   |
|-----------------|----------------|---------------------|---|
|                 |                | Body 1g SAR (W/kg)  | Simultaneous Transmission 1g SAR (W/kg) |
| DTS             | 2.4GHz WLAN    | 0.772               | 0.917                                   |
| NII             | 5.2GHz WLAN    | --                  | 0.575                                   |
|                 | 5.3GHz WLAN    | 0.284               |   |
|                 | 5.5GHz WLAN    | 0.524               |   |
|                 | 5.8GHz WLAN    | 0.408               |   |
| DSSS(BT)        | 2.4GHz         | 0.210               | 0.575                                   |

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR part 2 (2.1093), and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013.

### 3. REQUIREMENTS FOR COMPLIANCE TESTING DEFINED BY THE FCC

The order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 W/Kg for an uncontrolled environment and 8.0 W/Kg for an occupational/controlled environment as recommended by the FCC 47 CFR part 2 (2.1093).

### 4. TEST METHODOLOGY

The Specific Absorption Rate (SAR) testing specification, method and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 ( 2.1093)
- IEEE 1528-2013
- KDB 447498 D01v06 General RF Exposure Guidance
- KDB 865664 D01v01r04 Measurement 100 MHz to 6 GHz
- KDB 865664 D02 v01r02 RF Exposure Reporting
- KDB 248227 D01v02r02 802.11 Wi-Fi SAR
- KDB 616217 D04v01r02 SAR for laptop and tablets

### 5. TEST CONFIGURATION

During WLAN SAR testing EUT is configured with the WLAN continuous TX tool, and the transmission duty factor was monitored on the spectrum analyzer with zero-span setting. For WLAN SAR testing, WLAN engineering test software installed on the EUT can provide continuous transmitting RF signal.

Duty cycle Form

QC/NFA344A

| Band   | Mode          | Duty cycle(100%) |
|--------|---------------|------------------|
| 2.4GHz | Bluetooth     | N/A              |
|        | 802.11b       | 100              |
|        | 802.11g       | 100              |
|        | 802.11n 20MHz | 100              |
|        | 802.11n 40MHz | 100              |
| 5GHz   | 802.11a       | 100              |
|        | 802.11 20MHz  | 100              |
|        | 802.11 40MHz  | 100              |
|        | 802.11 ac80   | 100              |

## 6. DOSIMETRIC ASSESSMENT SETUP

These measurements were performed with the automated near-field scanning system DASY 5 from SPEAG. The system is based on a high precision robot (working range greater than 0.9 m), which positions the probes with a positional repeatability of better than  $\pm 0.02$  mm. Special E- and H-field probes have been developed for measurements close to material discontinuity, the sensors of which are directly loaded with a Schottky diode and connected via highly resistive lines to the data acquisition unit. The SAR measurements were conducted with the E-field PROBE EX3DV4 (manufactured by SPEAG), designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe has been calibrated according to the procedure described in [7] with accuracy of better than  $\pm 10\%$ . The spherical isotropy was evaluated with the procedure described in [8] and found to be better than  $\pm 0.25$  dB. The phantom used was the SAM Twin Phantom as described in FCC supplement C, IEE P1528 and CENELEC IEC 62209.


The following table gives the recipes for tissue simulating liquids.

| Ingredients<br>(% by weight) | Frequency<br>(MHz) |       |       |      |       |       |       |      |      |      |
|------------------------------|--------------------|-------|-------|------|-------|-------|-------|------|------|------|
|                              | 450                |       | 835   |      | 915   |       | 1900  |      | 2450 |      |
| Tissue Type                  | Head               | Body  | Head  | Body | Head  | Body  | Head  | Body | Head | Body |
| Water                        | 38.56              | 51.16 | 41.45 | 52.4 | 41.05 | 56.0  | 54.9  | 40.4 | 62.7 | 73.2 |
| Salt (NaCl)                  | 3.95               | 1.49  | 1.45  | 1.4  | 1.35  | 0.76  | 0.18  | 0.5  | 0.5  | 0.04 |
| Sugar                        | 56.32              | 46.78 | 56.0  | 45.0 | 56.5  | 41.76 | 0.0   | 58.0 | 0.0  | 0.0  |
| HEC                          | 0.98               | 0.52  | 1.0   | 1.0  | 1.0   | 1.21  | 0.0   | 1.0  | 0.0  | 0.0  |
| Bactericide                  | 0.19               | 0.05  | 0.1   | 0.1  | 0.1   | 0.27  | 0.0   | 0.1  | 0.0  | 0.0  |
| Triton X-100                 | 0.0                | 0.0   | 0.0   | 0.0  | 0.0   | 0.0   | 0.0   | 0.0  | 36.8 | 0.0  |
| DGBE                         | 0.0                | 0.0   | 0.0   | 0.0  | 0.0   | 0.0   | 44.92 | 0.0  | 0.0  | 26.7 |
| Dielectric Constant          | 43.42              | 58.0  | 42.54 | 56.1 | 42.0  | 56.8  | 39.9  | 54.0 | 39.8 | 52.5 |
| Conductivity (S/m)           | 0.85               | 0.83  | 0.91  | 0.95 | 1.0   | 1.07  | 1.42  | 1.45 | 1.88 | 1.78 |

### Simulating Liquids for 5 GHz, Manufactured by SPEAG

| Ingredients        | (% by weight) |
|--------------------|---------------|
| Water              | 78            |
| Mineral oil        | 11            |
| Emulsifiers        | 9             |
| Additives and Salt | 2             |

## 6.1 MEASUREMENT SYSTEM DIAGRAM



**The DASY5 system for performing compliance tests consists of the following items:**

- A standard high precision 6-axis robot (Staubli RX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion between optical and electrical of the signals for the digital communication to the DAE and for the analog signal from the optical surface detection. The EOC is connected to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
- A computer operating Windows 7.
- DASY5 software.
- Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The SAM twin phantom enabling testing left-hand and right-hand usage.
- The device holder for handheld mobile phones.
- Tissue simulating liquid mixed according to the given recipes.
- Validation dipole kits allowing validating the proper functioning of the system.

## 6.2 SYSTEM COMPONENTS



The DASY5 measurement server is based on a PC/104 CPU board with a 400MHz intel ULV celeron, 128MB chip-disk and 128 MB RAM. The necessary circuits for communication with either the DAE4 (or DAE3) electronic box as well as the 16-bit AD-converter system for optical detection and digital I/O interface are contained on the DASY5 I/O-board, which is directly connected to the PC/104 bus of the CPU board.

The measurement server performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation.



The PC-operating system cannot interfere with these time critical processes. All connections are supervised by a watchdog, and disconnection of any of the cables to the measurement server will automatically disarm the robot and disable all program-controlled robot movements. Furthermore, the measurement server is equipped with two expansion slots which are reserved for future applications. Please note that the expansion slots do not have a standardized pinout and therefore only the expansion cards provided by SPEAG can be inserted. Expansion cards from any other supplier could seriously damage the measurement server. Calibration: No calibration required.

### Data Acquisition Electronics (DAE)



The data acquisition electronics (DAE4) consists of a highly sensitive electrometer grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock. The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection. The input impedance of the DAE4 box is 200MΩ; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.

### EX3DV4 Isotropic E-Field Probe for Dosimetric Measurements




**Construction:** Symmetrical design with triangular core  
Built-in shielding against static charges  
PEEK enclosure material (resistant to organic solvents, e.g., DGBE)

**Calibration:** Basic Broad Band Calibration in air: 10-3000 MHz.  
Conversion Factors (CF) for HSL 900 and HSL 1800  
CF-Calibration for other liquids and frequencies upon request.

**Frequency:** 10 MHz to > 6 GHz; Linearity: ± 0.2 dB (30 MHz to 3 GHz)

**Directivity:** ± 0.3 dB in HSL (rotation around probe axis)  
± 0.5 dB in HSL (rotation normal to probe axis)

**Dynamic Range:** 10 μW/g to > 100 mW/g; Linearity: ± 0.2 dB  
(noise: typically < 1 μW/g)

|   |   |
|---|---|
| <p><b>Dimensions:</b> Overall length: 337 mm (Tip: 9 mm)<br/>Tip diameter: 2.5 mm (Body: 10 mm)<br/>Distance from probe tip to dipole centers: 1 mm</p> <p><b>Application:</b> High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 6 GHz with precision of better 30%.</p>   |  <p>Interior of probe</p> |
| <b>SAM Twin Phantom</b>   |   |
| <p><b>Construction:</b></p> <p>The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528-200X, CENELEC 50360 and IEC 62209. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points with the robot.</p> <p><b>Shell Thickness:</b> 2 ±0.2 mm</p> <p><b>Filling Volume:</b> Approx. 25 liters</p> <p><b>Dimensions:</b> Height: 850mm; Length: 1000mm; Width: 750mm</p>  |                          |
| <p><b>SAM Phantom (ELI4 v4.0)</b></p> <p><b>Description Construction:</b></p> <p>Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with the latest draft of the standard IEC 62209 Part II and all known tissue simulating liquids. ELI4 has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is supported by software version DASY4/DASY5.5 and higher and is compatible with all SPEAG dosimetric probes and dipoles</p> <p><b>Shell Thickness:</b> 2.0 ± 0.2 mm (sagging: &lt;1%)</p> <p><b>Filling Volume:</b> Approx. 25 liters</p> <p><b>Dimensions:</b> Major ellipse axis: 600 mm</p> <p><b>Minor axis:</b> 400 mm 500mm</p> |                         |

**Device Holder for SAM Twin Phantom**

**Construction:** In combination with the Twin SAM Phantom, the Mounting Device (made from POM) enables the rotation of the mounted transmitter in spherical coordinates, whereby the rotation point is the ear opening. The devices can be easily and accurately positioned according to IEC, IEEE, CENELEC, FCC or other specifications. The device holder can be locked at different phantom locations (left head, right head, and flat phantom).

**System Validation Kits for SAM Twin Phantom**

**Construction:** Symmetrical dipole with I/4 balun Enables measurement of feedpoint impedance with NWA Matched for use near flat phantoms filled with brain simulating solutions Includes distance holder and tripod adaptor.

**Frequency:** 900, 1800, 2450, 5800 MHz

**ReTune loss:** > 20 dB at specified validation position

**Power capability:** > 100 W (f < 1GHz); > 40 W (f > 1GHz)

**Dimensions:**

D835V2: dipole length: 161 mm; overall height: 340 mm

D1800V2: dipole length: 72.5 mm; overall height: 300 mm

D1900V2: dipole length: 67.7 mm; overall height: 300 mm

D2450V2: dipole length: 51.5 mm; overall height: 290 mm

D5GHzV2: dipole length: 20.6 mm; overall height: 300mm

**System Validation Kits for ELI4 phantom**

**Construction:** Symmetrical dipole with I/4 balun Enables measurement of feedpoint impedance with NWA Matched for use near flat phantoms filled with brain simulating solutions Includes distance holder and tripod adaptor.

**Frequency:** 900, 1800, 2450, 5800 MHz

**ReTune loss:** > 20 dB at specified validation position

**Power capability:** > 100 W (f < 1GHz); > 40 W (f > 1GHz)

**Dimensions:**

D835V2: dipole length: 161 mm; overall height: 340 mm

D1800V2: dipole length: 72.5 mm; overall height: 300 mm

D1900V2: dipole length: 67.7 mm; overall height: 300 mm

D2450V2: dipole length: 51.5 mm; overall height: 290 mm

D5GHzV2: dipole length: 20.6 mm; overall height: 300 mm



## 7. EVALUATION PROCEDURES

### DATA EVALUATION

The DASY 5 post processing software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

|                    |                           |                                  |
|--------------------|---------------------------|----------------------------------|
| Probe parameters:  | - Sensitivity             | $Norm_i, a_{i0}, a_{i1}, a_{i2}$ |
|                    | - Conversion factor       | $ConvF_i$                        |
|                    | - Diode compression point | $dcp_i$                          |
| Device parameters: | - Frequency               | $f$                              |
|                    | - Crest factor            | $cf$                             |
| Media parameters:  | - Conductivity            | $\sigma$                         |
|                    | - Density                 | $\rho$                           |

These parameters must be set correctly in the software. They can be found in the component documents or be imported into the software from the configuration files issued for the DASY 5 components. In the direct measuring mode of the multi-meter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

with  $V_i$  = Compensated signal of channel  $i$  ( $i = x, y, z$ )  
 $U_i$  = Input signal of channel  $i$  ( $i = x, y, z$ )  
 $cf$  = Crest factor of exciting field (DASY 5 parameter)  
 $dcp_i$  = Diode compression point (DASY 5 parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

E-field probes: 
$$E_i = \sqrt{\frac{V_i}{Norm_i \cdot ConvF}}$$

H-field probes: 
$$H_i = \sqrt{V_i} \cdot \frac{a_{i0} + a_{i1}f + a_{i2}f^2}{f}$$

with  $V_i$  = Compensated signal of channel  $i$  ( $i = x, y, z$ )  
 $Norm_i$  = Sensor sensitivity of channel  $i$  ( $i = x, y, z$ )  
 $\mu\text{V}/(\text{V}/\text{m})^2$  for E0field Probes  
 $ConvF$  = Sensitivity enhancement in solution  
 $a_{ij}$  = Sensor sensitivity factors for H-field probes  
 $f$  = Carrier frequency (GHz)  
 $E_i$  = Electric field strength of channel  $i$  in  $\text{V}/\text{m}$   
 $H_i$  = Magnetic field strength of channel  $i$  in  $\text{A}/\text{m}$

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{tot}^2 \cdot \frac{\sigma}{\rho \cdot 1000}$$

with  $SAR$  = local specific absorption rate in mW/g

$E_{tot}$  = total field strength in V/m

$\sigma$  = conductivity in [mho/m] or [Siemens/m]

$\rho$  = equivalent tissue density in g/cm<sup>3</sup>

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid.

The power flow density is calculated assuming the excitation field as a free space field.

$$P_{pwe} = \frac{E_{tot}^2}{3770} \quad \text{or} \quad P_{pwe} = H_{tot}^2 \cdot 37.7$$

with  $P_{pwe}$  = Equivalent power density of a plane wave in mW/cm<sup>2</sup>

$E_{tot}$  = total electric field strength in V/m

$H_{tot}$  = total magnetic field strength in A/m

## SAR EVALUATION PROCEDURES

The procedure for assessing the peak spatial-average SAR value consists of the following steps:

- **Power Reference Measurement**

The reference and drift jobs are useful jobs for monitoring the power drift of the device under test in the batch process. Both jobs measure the field at a specified reference position, at a selectable distance from the phantom surface. The reference position can be either the selected section's grid reference point or a user point in this section. The reference job projects the selected point onto the phantom surface, orients the probe perpendicularly to the surface, and approaches the surface using the selected detection method.

- **Area Scan**

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a finer measurement around the hot spot. The sophisticated interpolation routines implemented in DASY 5 software can find the maximum locations even in relatively coarse grids. The scan area is defined by an editable grid. This grid is anchored at the grid reference point of the selected section in the phantom. When the area scan's property sheet is brought-up, grid was at to 15 mm by 15 mm and can be edited by a user.

- **Zoom Scan**

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The default zoom scan measures 5 x 5 x 7 points within a cube whose base faces are centered around the maximum found in a preceding area scan job within the same procedure. If the preceding Area Scan job indicates more than one maximum, the number of Zoom Scans has to be enlarged accordingly (The default number inserted is 1).

- **Power Drift measurement**

The drift job measures the field at the same location as the most recent reference job within the same procedure, and with the same settings. The drift measurement gives the field difference in dB from the reading conducted within the last reference measurement. Several drift measurements are possible for one reference measurement. This allows a user to monitor the power drift of the device under test within a batch process. In the properties of the Drift job, the user can specify a limit for the drift and have DASY 5 software stop the measurements if this limit is exceeded.

- **Z-Scan**

The Z Scan job measures points along a vertical straight line. The line runs along the Z-axis of a one-dimensional grid. A user can anchor the grid to the current probe location. As with any other grids, the local Z-axis of the anchor location establishes the Z-axis of the grid.

## SPATIAL PEAK SAR EVALUATION

The procedure for spatial peak SAR evaluation has been implemented according to the IEEE1529 standard. It can be conducted for 1 g and 10 g.

The DASY 5 system allows evaluations that combine measured data and robot positions, such as:

- maximum search
- extrapolation
- boundary correction
- peak search for averaged SAR

During a maximum search, global and local maximum searches are automatically performed in 2-D after each Area Scan measurement with at least 6 measurement points. It is based on the evaluation of the local SAR gradient calculated by the Quadratic Shepard's method. The algorithm will find the global maximum and all local maxima within -2 dB of the global maxima for all SAR distributions.

### Extrapolation

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. Several measurements at different distances are necessary for the extrapolation.

Extrapolation routines require at least 10 measurement points in 3-D space. They are used in the Cube Scan to obtain SAR values between the lowest measurement points and the inner phantom surface. The routine uses the modified Quadratic Shepard's method for extrapolation. For a grid using 5x5x7 measurement points with 5mm resolution amounting to 343 measurement points, the uncertainty of the extrapolation routines is less than 1% for 1 g and 10 g cubes.

### Boundary effect

For measurements in the immediate vicinity of a phantom surface, the field coupling effects between the probe and the boundary influence the probe characteristics. Boundary effect errors of different dosimetric probe types have been analyzed by measurements and using a numerical probe model. As expected, both methods showed an enhanced sensitivity in the immediate vicinity of the boundary. The effect strongly depends on the probe dimensions and disappears with increasing distance from the boundary. The sensitivity can be approximately given as:

$$S \approx S_o + S_b \exp\left(-\frac{z}{a}\right) \cos\left(\pi \frac{z}{\lambda}\right)$$

Since the decay of the boundary effect dominates for small probes ( $a \ll \lambda$ ), the cos-term can be omitted. Factors  $S_b$  (parameter Alpha in the DASY 5 software) and  $a$  (parameter Delta in the DASY 5 software) are assessed during probe calibration and used for numerical compensation of the boundary effect. Several simulations and measurements have confirmed that the compensation is valid for different field and boundary configurations.

This simple compensation procedure can largely reduce the probe uncertainty near boundaries. It works well as long as:

- the boundary curvature is small
- the probe axis is angled less than 30° to the boundary normal
- the distance between probe and boundary is larger than 25% of the probe diameter
- the probe is symmetric (all sensors have the same offset from the probe tip)

Since all of these requirements are fulfilled in a DASY 5 system, the correction of the probe boundary effect in the vicinity of the phantom surface is performed in a fully automated manner via the measurement data extraction during post processing.

## 8. MEASUREMENT UNCERTAINTY

Per KDB865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2003 is not required in SAR reports submitted for equipment approval. The equivalent ratio (1.5/1.6) is applied to extremity and occupational exposure conditions.

## 9. EXPOSURE LIMIT

(A). Limits for Occupational/Controlled Exposure (W/kg)

| Whole-Body | Partial-Body | Hands, Wrists, Feet and Ankles |
|------------|--------------|--------------------------------|
| 0.4        | 8.0          | 20.0                           |

(B). Limits for General Population/Uncontrolled Exposure (W/kg)

| Whole-Body | Partial-Body | Hands, Wrists, Feet and Ankles |
|------------|--------------|--------------------------------|
| 0.08       | 1.6          | 4.0                            |

**Note:** **Whole-Body SAR** is averaged over the entire body, **partial-body SAR** is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. **SAR for hands, wrists, feet and ankles** is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

**Population/Uncontrolled Environments** are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

**Occupational/Controlled Environments** are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

**NOTE**  
**GENERAL POPULATION/UNCONTROLLED EXPOSURE**  
**PARTIAL BODY LIMIT**  
**1.6 W/kg**

## 10. MEASUREMENT RESULTS

### 10.1 TEST LIQUIDS CONFIRMATION

#### SIMULATED TISSUE LIQUID PARAMETER CONFIRMATION

The dielectric parameters were checked prior to assessment using the SPEAG DAK3.5 dielectric probe kit. The dielectric parameters measured are reported in each correspondent section.

#### IEEE SCC-34/SC-2 P1528 RECOMMENDED TISSUE DIELECTRIC PARAMETERS

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in P1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in P1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations and extrapolated according to the head parameters specified in P1528

| Target Frequency<br>(MHz) | Head         |                | Body         |                |
|---------------------------|--------------|----------------|--------------|----------------|
|                           | $\epsilon_r$ | $\sigma$ (S/m) | $\epsilon_r$ | $\sigma$ (S/m) |
| 150                       | 52.3         | 0.76           | 61.9         | 0.80           |
| 300                       | 45.3         | 0.87           | 58.2         | 0.92           |
| 450                       | 43.5         | 0.87           | 56.7         | 0.94           |
| 835                       | 41.5         | 0.90           | 55.2         | 0.97           |
| 900                       | 41.5         | 0.97           | 55.0         | 1.05           |
| 915                       | 41.5         | 0.98           | 55.0         | 1.06           |
| 1450                      | 40.5         | 1.20           | 54.0         | 1.30           |
| 1610                      | 40.3         | 1.29           | 53.8         | 1.40           |
| 1800-2000                 | 40.0         | 1.40           | 53.3         | 1.52           |
| 2450                      | 39.2         | 1.80           | 52.7         | 1.95           |
| 3000                      | 38.5         | 2.40           | 52.0         | 2.73           |
| 5800                      | 35.3         | 5.27           | 48.2         | 6.00           |

( $\epsilon_r$  = relative permittivity,  $\sigma$  = conductivity and  $\rho = 1000 \text{ kg/m}^3$ )

## 10.2 LIQUID MEASUREMENT RESULTS

The following table show the measuring results for simulating liquid:


| Liquid Type | Liquid Temp. (°C) | Parameters                | Target | Measured | Deviation (%) | Limited (%) | Measured Date |
|-------------|-------------------|---------------------------|--------|----------|---------------|-------------|---------------|
| Body2450    | 21.5              | Permitivity( $\epsilon$ ) | 52.70  | 51.70    | -1.90         | $\pm 5$     | 2017-9-15     |
|             |                   | Conductivity( $\sigma$ )  | 1.95   | 1.94     | -0.36         | $\pm 5$     |               |
| Body5200    | 21.5              | Permitivity( $\epsilon$ ) | 49.03  | 48.91    | -0.25         | $\pm 5$     | 2017-9-14     |
|             |                   | Conductivity( $\sigma$ )  | 5.35   | 5.23     | -2.27         | $\pm 5$     |               |
| Body5300    | 21.5              | Permitivity( $\epsilon$ ) | 48.90  | 48.67    | -0.46         | $\pm 5$     | 2017-9-14     |
|             |                   | Conductivity( $\sigma$ )  | 5.46   | 5.36     | -1.84         | $\pm 5$     |               |
| Body5500    | 21.5              | Permitivity( $\epsilon$ ) | 48.62  | 48.20    | -0.86         | $\pm 5$     | 2017-9-14     |
|             |                   | Conductivity( $\sigma$ )  | 5.68   | 5.63     | -0.88         | $\pm 5$     |               |
| Body5600    | 21.5              | Permitivity( $\epsilon$ ) | 48.48  | 47.97    | -1.04         | $\pm 5$     | 2017-9-14     |
|             |                   | Conductivity( $\sigma$ )  | 5.79   | 5.77     | -0.28         | $\pm 5$     |               |
| Body5800    | 21.5              | Permitivity( $\epsilon$ ) | 48.20  | 47.52    | -1.41         | $\pm 5$     | 2017-9-14     |
|             |                   | Conductivity( $\sigma$ )  | 6.00   | 6.07     | 1.18          | $\pm 5$     |               |

### 10.3 SYSTEM PERFORMANCE CHECK

The system performance check is performed prior to any usage of the system in order to guarantee reproducible results. The system performance check verifies that the system operates within its specifications of  $\pm 10\%$ . The system performance check results are tabulated below. And also the corresponding SAR plot is attached as well in the SAR plots files.

#### SYSTEM PERFORMANCE CHECK MEASUREMENT CONDITIONS

- The measurements were performed in the flat section of the SAM twin phantom filled with head and body simulating liquid of the following parameters.
- The DASY5 system within E-field probe EX3DV4 SN: 3798 was used for the measurements.
- The dipole was mounted on the small tripod so that the dipole feed point was positioned below the center marking of the flat phantom section and the dipole was oriented parallel to the body axis (the long side of the phantom). The standard measuring distance was 15 mm (below 1 GHz) and 10 mm (above 1 GHz) from dipole center to the simulating liquid surface.
- The coarse grid with a grid spacing of 10mm was aligned with the dipole.
- Special 7x7x7 fine cube was chosen for cube integration ( $dx = 5$  mm,  $dy = 5$  mm,  $dz = 5$  mm).
- Distance between probe sensors and phantom surface was set to 2 mm.
- The dipole less than 3G input power was  $250\text{mW} \pm 3\%$ .
- The dipole above than 3G input power was  $100\text{mW} \pm 3\%$ .
- The results are normalized to 1 W input power.



- Note: For SAR testing, less than 3G the liquid depth is 15cm shown above
- Note: For SAR testing, above than 3G the liquid depth is 10cm shown above

**SYSTEM PERFORMANCE CHECK RESULTS**

| Liquid Type | Ambient Temp. (°C) | Liquid Temp. (°C) | Input Power (W) | Measured SAR <sub>1g</sub> (W/Kg) | 1W Target SAR <sub>1g</sub> (W/Kg) | 1W Normalized SAR <sub>1g</sub> (W/Kg) | Deviation (%) | Limited (%) | Date      |
|-------------|--------------------|-------------------|-----------------|-----------------------------------|------------------------------------|--|---------------|-------------|-----------|
| Body2450    | 22                 | 21.5              | 0.25            | 12.70                             | 51.50                              | 50.80                                  | -1.36         | ± 10        | 2017-9-15 |
| Body5200    | 22                 | 21.5              | 0.1             | 7.38                              | 74.50                              | 73.8                                   | -0.94         | ± 10        | 2017-9-14 |
| Body5300    | 22                 | 21.5              | 0.1             | 7.63                              | 77.20                              | 76.3                                   | -1.17         | ± 10        | 2017-9-14 |
| Body5500    | 22                 | 21.5              | 0.1             | 8.04                              | 81.10                              | 80.4                                   | -0.86         | ± 10        | 2017-9-14 |
| Body5600    | 22                 | 21.5              | 0.1             | 8.15                              | 79.80                              | 81.5                                   | 2.13          | ± 10        | 2017-9-14 |
| Body5800    | 22                 | 21.5              | 0.1             | 7.84                              | 77.20                              | 78.4                                   | 1.55          | ± 10        | 2017-9-14 |

## 10.4 EUT TUNE-UP PROCEDURES AND TEST MODE

### Conducted output power(dBm):

#### General Note:

- 1 Power must be measured at each transmit antenna port according to the DSSS and OFDM transmission configurations in each standalone and aggregated frequency band.
- 2 Power measurement is required for the transmission mode configuration with the highest maximum output power specified for production units.
  - 1) When the same highest maximum output power specification applies to multiple transmission modes, the largest channel bandwidth configuration with the lowest order modulation and lowest data rate is measured.
  - 2) When the same highest maximum output power is specified for multiple largest channel bandwidth configurations with the same lowest order modulation or lowest order modulation and lowest data rate, power measurement is required for all equivalent 802.11 configurations with the same maximum output power.
- 3 For each transmission mode configuration, power must be measured for the highest and lowest channels; and at the mid-band channel(s) when there are at least 3 channels. For configurations with multiple mid-band channels, due to an even number of channels, both channels should be measured.
- 4 Apply the default power measurement procedures to measure maximum output power for each standalone and aggregated frequency band.
  - a) When band gap channels between U-NII-2C band and U-NII-3 band or §15.247 5.8 GHz band are supported and the bands are aggregated for SAR testing according to KDB 248227D01 sections 2.3 and 3.3, apply the following to determine high, middle and low channels for power measurement and SAR test reduction.
    - i) channels in U-NII-2C band below 5.65 GHz are considered as one band
    - ii) channels above 5.65 GHz, together with channels in 5.8 GHz U-NII-3 or §15.247 band, are considered as a separate band
  - b) The maximum output power of band gap channels is limited to the lowest maximum output power certified for the adjacent bands regardless of whether band aggregation is applied for SAR testing.
  - c) The measured maximum output power results are used to reduce the number of channels that need testing.

## WLAN 2.4G Chain0

| Mode           | Channel | Frequency (MHz) | Chain0 Target power(dBm) | Turn up tolerance (dBm) | Maximum Turn up power (dBm) | Average power (dBm) |
|----------------|---------|-----------------|--------------------------|-------------------------|-----------------------------|---------------------|
| 802.11 b       | 1       | 2412            | 19                       | ±1.5                    | 20.5                        | 19.8                |
|                | 6       | 2437            | 19                       | ±1.5                    | 20.5                        | 19.8                |
|                | 11      | 2462            | 19                       | ±1.5                    | 20.5                        | 19.9                |
|                | 12      | 2467            | 11                       | ±1.5                    | 12.5                        | 12.0                |
|                | 13      | 2472            | 10                       | ±1.5                    | 11.5                        | 11.0                |
| 802.11 g       | 1       | 2412            | 16.5                     | ±1.5                    | 18.0                        | Not required        |
|                | 6       | 2437            | 18                       | ±1.5                    | 19.5                        |                     |
|                | 11      | 2462            | 16.5                     | ±1.5                    | 18.0                        |                     |
|                | 12      | 2467            | 12.5                     | ±1.5                    | 14.0                        |                     |
|                | 13      | 2472            | 1.5                      | ±1.5                    | 3.0                         |                     |
| 802.11 n 20MHz | 1       | 2412            | 15.5                     | ±1.5                    | 17.0                        |                     |
|                | 6       | 2437            | 18                       | ±1.5                    | 19.5                        |                     |
|                | 11      | 2462            | 14.5                     | ±1.5                    | 16.0                        |                     |
|                | 12      | 2467            | 12.5                     | ±1.5                    | 14.0                        |                     |
|                | 13      | 2472            | 0                        | ±1.5                    | 1.5                         |                     |
| 802.11 n 40MHz | 3       | 2422            | 11.5                     | ±1.5                    | 13                          |                     |
|                | 6       | 2437            | 17                       | ±1.5                    | 18.5                        |                     |
|                | 9       | 2452            | 9.5                      | ±1.5                    | 11.0                        |                     |
|                | 10      | 2457            | 9.5                      | ±1.5                    | 11.0                        |                     |
|                | 11      | 2462            | 1                        | ±1.5                    | 2.5                         |                     |

## WLAN 2.4G Chain1

| Mode           | Channel | Frequency (MHz) | Chain1 Target power(dBm) | Turn up tolerance (dBm) | Maximum Turn up power (dBm) | Average power (dBm) |
|----------------|---------|-----------------|--------------------------|-------------------------|-----------------------------|---------------------|
| 802.11 b       | 1       | 2412            | 19                       | ±1.5                    | 20.5                        | 19.6                |
|                | 6       | 2437            | 19                       | ±1.5                    | 20.5                        | 19.6                |
|                | 11      | 2462            | 19                       | ±1.5                    | 20.5                        | 19.7                |
|                | 12      | 2467            | 11                       | ±1.5                    | 12.5                        | 12.0                |
|                | 13      | 2472            | 10                       | ±1.5                    | 11.5                        | 11.0                |
| 802.11 g       | 1       | 2412            | 16.5                     | ±1.5                    | 18.0                        | Not required        |
|                | 6       | 2437            | 18                       | ±1.5                    | 19.5                        |                     |
|                | 11      | 2462            | 16.5                     | ±1.5                    | 18.0                        |                     |
|                | 12      | 2467            | 12.5                     | ±1.5                    | 14.0                        |                     |
|                | 13      | 2472            | 1.5                      | ±1.5                    | 3.0                         |                     |
| 802.11 n 20MHz | 1       | 2412            | 15.5                     | ±1.5                    | 17.0                        |                     |
|                | 6       | 2437            | 18                       | ±1.5                    | 19.5                        |                     |
|                | 11      | 2462            | 14.5                     | ±1.5                    | 16.0                        |                     |
|                | 12      | 2467            | 12.5                     | ±1.5                    | 14.0                        |                     |
|                | 13      | 2472            | 0                        | ±1.5                    | 1.5                         |                     |
| 802.11 n 40MHz | 3       | 2422            | 11.5                     | ±1.5                    | 13                          |                     |
|                | 6       | 2437            | 17                       | ±1.5                    | 18.5                        |                     |
|                | 9       | 2452            | 9.5                      | ±1.5                    | 11.0                        |                     |
|                | 10      | 2457            | 9.5                      | ±1.5                    | 11.0                        |                     |
|                | 11      | 2462            | 1                        | ±1.5                    | 2.5                         |                     |

## WLAN 2.4G Chain0+1

| Mode           | Channel | Frequency (MHz) | Chain0+1 Target power(dBm) | Turn up tolerance (dBm) | Maximum Turn up power (dBm) | Average power (dBm) |
|----------------|---------|-----------------|----------------------------|-------------------------|-----------------------------|---------------------|
| 802.11 b       | 1       | 2412            | 22                         | ±1.5                    | 23.5                        | 22.7                |
|                | 6       | 2437            | 22                         | ±1.5                    | 23.5                        | 22.7                |
|                | 11      | 2462            | 22                         | ±1.5                    | 23.5                        | 22.8                |
|                | 12      | 2467            | 14                         | ±1.5                    | 15.5                        | 15.0                |
|                | 13      | 2472            | 13                         | ±1.5                    | 14.5                        | 14.0                |
| 802.11 g       | 1       | 2412            | 19.5                       | ±1.5                    | 21.0                        | Not required        |
|                | 6       | 2437            | 21                         | ±1.5                    | 22.5                        |                     |
|                | 11      | 2462            | 19.5                       | ±1.5                    | 21.0                        |                     |
|                | 12      | 2467            | 15.5                       | ±1.5                    | 17.0                        |                     |
|                | 13      | 2472            | 4.5                        | ±1.5                    | 6.0                         |                     |
| 802.11 n 20MHz | 1       | 2412            | 18.5                       | ±1.5                    | 20.0                        |                     |
|                | 6       | 2437            | 21                         | ±1.5                    | 22.5                        |                     |
|                | 11      | 2462            | 17.5                       | ±1.5                    | 19.0                        |                     |
|                | 12      | 2467            | 15.5                       | ±1.5                    | 17.0                        |                     |
|                | 13      | 2472            | 3                          | ±1.5                    | 4.5                         |                     |
| 802.11 n 40MHz | 3       | 2422            | 14.5                       | ±1.5                    | 16.0                        |                     |
|                | 6       | 2437            | 20                         | ±1.5                    | 21.5                        |                     |
|                | 9       | 2452            | 12.5                       | ±1.5                    | 14.0                        |                     |
|                | 10      | 2457            | 12.5                       | ±1.5                    | 14.0                        |                     |
|                | 11      | 2462            | 4                          | ±1.5                    | 5.5                         |                     |

## WLAN Conducted output power(dBm):

## U-NII-1 Chain0

| Mode           | Channel | Frequency (MHz) | Chain0 Target power(dBm) | Tune up tolerance (dBm) | Maximum Tune up power (dBm) | Average Power (dBm) |
|----------------|---------|-----------------|--------------------------|-------------------------|-----------------------------|---------------------|
| 802.11 a       | 36      | 5180            | 13                       | ±2                      | 15                          | Not required        |
|                | 40      | 5200            | 13                       | ±2                      | 15                          |                     |
|                | 44      | 5220            | 13                       | ±2                      | 15                          |                     |
|                | 48      | 5240            | 13                       | ±2                      | 15                          |                     |
| 802.11 n 20MHz | 36      | 5180            | 13                       | ±2                      | 15                          | Not required        |
|                | 40      | 5200            | 13                       | ±2                      | 15                          |                     |
|                | 44      | 5220            | 13                       | ±2                      | 15                          |                     |
|                | 48      | 5240            | 13                       | ±2                      | 15                          |                     |
| 802.11 n 40MHz | 38      | 5190            | 12.5                     | ±2                      | 14.5                        | Not required        |
|                | 46      | 5230            | 12.5                     | ±2                      | 14.5                        |                     |
| 802.11 ac80    | 42      | 5210            | 8.5                      | ±2                      | 10.5                        |                     |

## U-NII-1 Chain1

| Mode           | Channel | Frequency (MHz) | Chain1 Target power(dBm) | Tune up tolerance (dBm) | Maximum Tune up power (dBm) | Average Power (dBm) |
|----------------|---------|-----------------|--------------------------|-------------------------|-----------------------------|---------------------|
| 802.11 a       | 36      | 5180            | 13                       | ±2                      | 15                          | Not required        |
|                | 40      | 5200            | 13                       | ±2                      | 15                          |                     |
|                | 44      | 5220            | 13                       | ±2                      | 15                          |                     |
|                | 48      | 5240            | 13                       | ±2                      | 15                          |                     |
| 802.11 n 20MHz | 36      | 5180            | 13                       | ±2                      | 15                          | Not required        |
|                | 40      | 5200            | 13                       | ±2                      | 15                          |                     |
|                | 44      | 5220            | 13                       | ±2                      | 15                          |                     |
|                | 48      | 5240            | 13                       | ±2                      | 15                          |                     |
| 802.11 n 40MHz | 38      | 5180            | 12.5                     | ±2                      | 14.5                        | Not required        |
|                | 46      | 5230            | 12.5                     | ±2                      | 14.5                        |                     |
| 802.11 ac80    | 42      | 5210            | 8.5                      | ±2                      | 10.5                        |                     |

## U-NII-1 Chain0+1

| Mode           | Channel | Frequency (MHz) | Chain0+1 Target power(dBm) | Tune up tolerance (dBm) | Maximum Tune up power (dBm) | Average Power (dBm) |
|----------------|---------|-----------------|----------------------------|-------------------------|-----------------------------|---------------------|
| 802.11 a       | 36      | 5180            | 16                         | ±2                      | 18                          | Not required        |
|                | 40      | 5200            | 16                         | ±2                      | 18                          |                     |
|                | 44      | 5220            | 16                         | ±2                      | 18                          |                     |
|                | 48      | 5240            | 16                         | ±2                      | 18                          |                     |
| 802.11 n 20MHz | 36      | 5180            | 16                         | ±2                      | 18                          | Not required        |
|                | 40      | 5200            | 16                         | ±2                      | 18                          |                     |
|                | 44      | 5220            | 16                         | ±2                      | 18                          |                     |
|                | 48      | 5240            | 16                         | ±2                      | 18                          |                     |
| 802.11 n 40MHz | 38      | 5180            | 15.5                       | ±2                      | 17.5                        | Not required        |
|                | 46      | 5230            | 15.5                       | ±2                      | 17.5                        |                     |
| 802.11 ac80    | 42      | 5210            | 11.5                       | ±2                      | 13.5                        |                     |

Remark: For devices that operate in both U-NII-1 and U-NII-2A bands using the same transmitter and antenna(s), SAR test reduction is determined according to the following

1) When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is  $\leq 1.2$  W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition); otherwise, each band is tested independently for SAR.

2) When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is  $\leq 1.2$  W/kg, SAR is not required for the band with lower maximum output power in that test configuration; otherwise, each band is tested independently for SAR.

The highest reported SAR for U-NII is adjusted by the ratio of U-NII-1 to U-NII-2A specified maximum output power and the adjusted SAR is  $\leq 1.2$  W/kg. So U-NII-1 mode is not required.

## U-NII-2A Chain0

| Mode           | Channel | Frequency (MHz) | Chain0 Target power(dBm) | Tune up tolerance (dBm) | Maximum Tune up power (dBm) | Average Power (dBm) |
|----------------|---------|-----------------|--------------------------|-------------------------|-----------------------------|---------------------|
| 802.11 a       | 52      | 5260            | 13                       | ±2                      | 15                          | 14.2                |
|                | 56      | 5280            | 13                       | ±2                      | 15                          | 14.3                |
|                | 60      | 5300            | 13                       | ±2                      | 15                          | 14.1                |
|                | 64      | 5320            | 13                       | ±2                      | 15                          | 14.3                |
| 802.11 n 20MHz | 52      | 5260            | 13                       | ±2                      | 15                          | Not required        |
|                | 56      | 5280            | 13                       | ±2                      | 15                          |                     |
|                | 60      | 5300            | 13                       | ±2                      | 15                          |                     |
|                | 64      | 5320            | 13                       | ±2                      | 15                          |                     |
| 802.11 n 40MHz | 54      | 5270            | 12.5                     | ±2                      | 14.5                        |                     |
|                | 62      | 5310            | 12.5                     | ±2                      | 14.5                        |                     |
| 802.11 ac80    | 58      | 5290            | 10                       | ±2                      | 12                          |                     |

## U-NII-2A Chain1

| Mode           | Channel | Frequency (MHz) | Chain1 Target power(dBm) | Tune up tolerance (dBm) | Maximum Tune up power (dBm) | Average Power (dBm) |
|----------------|---------|-----------------|--------------------------|-------------------------|-----------------------------|---------------------|
| 802.11 a       | 52      | 5260            | 13                       | ±2                      | 15                          | 14.5                |
|                | 56      | 5280            | 13                       | ±2                      | 15                          | 14.6                |
|                | 60      | 5300            | 13                       | ±2                      | 15                          | 14.4                |
|                | 64      | 5320            | 13                       | ±2                      | 15                          | 14.2                |
| 802.11 n 20MHz | 52      | 5260            | 13                       | ±2                      | 15                          | Not required        |
|                | 56      | 5280            | 13                       | ±2                      | 15                          |                     |
|                | 60      | 5300            | 13                       | ±2                      | 15                          |                     |
|                | 64      | 5320            | 13                       | ±2                      | 15                          |                     |
| 802.11 n 40MHz | 54      | 5270            | 12.5                     | ±2                      | 14.5                        |                     |
|                | 62      | 5310            | 12.5                     | ±2                      | 14.5                        |                     |
| 802.11 ac80    | 58      | 5290            | 10                       | ±2                      | 12                          |                     |

## U-NII-2A Chain0+1

| Mode           | Channel | Frequency (MHz) | Chain0+1 Target power(dBm) | Tune up tolerance (dBm) | Maximum Tune up power (dBm) | Average Power (dBm) |
|----------------|---------|-----------------|----------------------------|-------------------------|-----------------------------|---------------------|
| 802.11 a       | 52      | 5260            | 16                         | ±2                      | 18                          | 17.4                |
|                | 56      | 5280            | 16                         | ±2                      | 18                          | 17.5                |
|                | 60      | 5300            | 16                         | ±2                      | 18                          | 17.3                |
|                | 64      | 5320            | 16                         | ±2                      | 18                          | 17.3                |
| 802.11 n 20MHz | 52      | 5260            | 16                         | ±2                      | 18                          | Not required        |
|                | 56      | 5280            | 16                         | ±2                      | 18                          |                     |
|                | 60      | 5300            | 16                         | ±2                      | 18                          |                     |
|                | 64      | 5320            | 16                         | ±2                      | 18                          |                     |
| 802.11 n 40MHz | 54      | 5270            | 15.5                       | ±2                      | 17.5                        |                     |
|                | 62      | 5310            | 15.5                       | ±2                      | 17.5                        |                     |
| 802.11 ac80    | 58      | 5290            | 13                         | ±2                      | 15                          |                     |

## U-NII-2C Chain0

| Mode           | Channel | Frequency (MHz) | Chain0 Target power(dBm) | Tune up tolerance (dBm) | Maximum Tune up power (dBm) | Average Power (dBm) |
|----------------|---------|-----------------|--------------------------|-------------------------|-----------------------------|---------------------|
| 802.11 a       | 100     | 5500            | 13                       | ±2                      | 15                          | 14.6                |
|                | 104     | 5520            | 13                       | ±2                      | 15                          | 14.4                |
|                | 108     | 5540            | 13                       | ±2                      | 15                          | 14.3                |
|                | 112     | 5560            | 13                       | ±2                      | 15                          | 14.1                |
|                | 116     | 5580            | 13                       | ±2                      | 15                          | 14.0                |
|                | 120     | 5600            | 13                       | ±2                      | 15                          | 13.9                |
|                | 124     | 5620            | 13                       | ±2                      | 15                          | 13.9                |
|                | 128     | 5640            | 13                       | ±2                      | 15                          | 13.9                |
|                | 132     | 5660            | 13                       | ±2                      | 15                          | 14.7                |
|                | 136     | 5680            | 13                       | ±2                      | 15                          | 14.6                |
|                | 140     | 5700            | 13                       | ±2                      | 15                          | 14.5                |
| 802.11 n 20MHz | 100     | 5500            | 13                       | ±2                      | 15                          | Not required        |
|                | 104     | 5520            | 13                       | ±2                      | 15                          |                     |
|                | 108     | 5540            | 13                       | ±2                      | 15                          |                     |
|                | 112     | 5560            | 13                       | ±2                      | 15                          |                     |
|                | 116     | 5580            | 13                       | ±2                      | 15                          |                     |
|                | 120     | 5600            | 13                       | ±2                      | 15                          |                     |
|                | 124     | 5620            | 13                       | ±2                      | 15                          |                     |
|                | 128     | 5640            | 13                       | ±2                      | 15                          |                     |
|                | 132     | 5660            | 13                       | ±2                      | 15                          |                     |
|                | 136     | 5680            | 13                       | ±2                      | 15                          |                     |
|                | 140     | 5700            | 13                       | ±2                      | 15                          |                     |
| 802.11 n 40MHz | 102     | 5510            | 12.5                     | ±2                      | 14.5                        |                     |
|                | 110     | 5550            | 12.5                     | ±2                      | 14.5                        |                     |
|                | 118     | 5590            | 12.5                     | ±2                      | 14.5                        |                     |
|                | 126     | 5630            | 12.5                     | ±2                      | 14.5                        |                     |
|                | 134     | 5670            | 12.5                     | ±2                      | 14.5                        |                     |
| 802.11 ac80    | 106     | 5530            | 12.5                     | ±2                      | 14.5                        |                     |
|                | 122     | 5610            | 12.5                     | ±2                      | 14.5                        |                     |
|                | 138     | 5690            | 12.5                     | ±2                      | 14.5                        |                     |

## U-NII-2C Chain1

| Mode           | Channel | Frequency (MHz) | Chain1 Target power(dBm) | Tune up tolerance (dBm) | Maximum Tune up power (dBm) | Average Power (dBm) |
|----------------|---------|-----------------|--------------------------|-------------------------|-----------------------------|---------------------|
| 802.11 a       | 100     | 5500            | 13                       | ±2                      | 15                          | 14.0                |
|                | 104     | 5520            | 13                       | ±2                      | 15                          | 14.2                |
|                | 108     | 5540            | 13                       | ±2                      | 15                          | 14.3                |
|                | 112     | 5560            | 13                       | ±2                      | 15                          | 14.1                |
|                | 116     | 5580            | 13                       | ±2                      | 15                          | 14.0                |
|                | 120     | 5600            | 13                       | ±2                      | 15                          | 13.9                |
|                | 124     | 5620            | 13                       | ±2                      | 15                          | 13.9                |
|                | 128     | 5640            | 13                       | ±2                      | 15                          | 13.9                |
|                | 132     | 5660            | 13                       | ±2                      | 15                          | 14.6                |
|                | 136     | 5680            | 13                       | ±2                      | 15                          | 14.4                |
|                | 140     | 5700            | 13                       | ±2                      | 15                          | 14.5                |
| 802.11 n 20MHz | 100     | 5500            | 13                       | ±2                      | 15                          | Not required        |
|                | 104     | 5520            | 13                       | ±2                      | 15                          |                     |
|                | 108     | 5540            | 13                       | ±2                      | 15                          |                     |
|                | 112     | 5560            | 13                       | ±2                      | 15                          |                     |
|                | 116     | 5580            | 13                       | ±2                      | 15                          |                     |
|                | 120     | 5600            | 13                       | ±2                      | 15                          |                     |
|                | 124     | 5620            | 13                       | ±2                      | 15                          |                     |
|                | 128     | 5640            | 13                       | ±2                      | 15                          |                     |
|                | 132     | 5660            | 13                       | ±2                      | 15                          |                     |
|                | 136     | 5680            | 13                       | ±2                      | 15                          |                     |
|                | 140     | 5700            | 13                       | ±2                      | 15                          |                     |
| 802.11 n 40MHz | 102     | 5510            | 12.5                     | ±2                      | 14.5                        |                     |
|                | 110     | 5550            | 12.5                     | ±2                      | 14.5                        |                     |
|                | 118     | 5590            | 12.5                     | ±2                      | 14.5                        |                     |
|                | 126     | 5630            | 12.5                     | ±2                      | 14.5                        |                     |
|                | 134     | 5670            | 12.5                     | ±2                      | 14.5                        |                     |
| 802.11 ac80    | 106     | 5530            | 12.5                     | ±2                      | 14.5                        |                     |
|                | 122     | 5610            | 12.5                     | ±2                      | 14.5                        |                     |
|                | 138     | 5690            | 12.5                     | ±2                      | 14.5                        |                     |

## U-NII-2C Chain0+1

| Mode           | Channel | Frequency (MHz) | Chain0+1 Target power(dBm) | Tune up tolerance (dBm) | Maximum Tune up power (dBm) | Average Power (dBm) |
|----------------|---------|-----------------|----------------------------|-------------------------|-----------------------------|---------------------|
| 802.11 a       | 100     | 5500            | 16                         | ±2                      | 18                          | 17.3                |
|                | 104     | 5520            | 16                         | ±2                      | 18                          | 17.3                |
|                | 108     | 5540            | 16                         | ±2                      | 18                          | 17.3                |
|                | 112     | 5560            | 16                         | ±2                      | 18                          | 17.1                |
|                | 116     | 5580            | 16                         | ±2                      | 18                          | 17.0                |
|                | 120     | 5600            | 16                         | ±2                      | 18                          | 16.9                |
|                | 124     | 5620            | 16                         | ±2                      | 18                          | 16.9                |
|                | 128     | 5640            | 16                         | ±2                      | 18                          | 16.9                |
|                | 132     | 5660            | 16                         | ±2                      | 18                          | 17.7                |
|                | 136     | 5680            | 16                         | ±2                      | 18                          | 17.5                |
|                | 140     | 5700            | 16                         | ±2                      | 18                          | 17.5                |
| 802.11 n 20MHz | 100     | 5500            | 16                         | ±2                      | 18                          | Not required        |
|                | 104     | 5520            | 16                         | ±2                      | 18                          |                     |
|                | 108     | 5540            | 16                         | ±2                      | 18                          |                     |
|                | 112     | 5560            | 16                         | ±2                      | 18                          |                     |
|                | 116     | 5580            | 16                         | ±2                      | 18                          |                     |
|                | 120     | 5600            | 16                         | ±2                      | 18                          |                     |
|                | 124     | 5620            | 16                         | ±2                      | 18                          |                     |
|                | 128     | 5640            | 16                         | ±2                      | 18                          |                     |
|                | 132     | 5660            | 16                         | ±2                      | 18                          |                     |
|                | 136     | 5680            | 16                         | ±2                      | 18                          |                     |
|                | 140     | 5700            | 16                         | ±2                      | 18                          |                     |
| 802.11 n 40MHz | 102     | 5510            | 15.5                       | ±2                      | 17.5                        |                     |
|                | 110     | 5550            | 15.5                       | ±2                      | 17.5                        |                     |
|                | 118     | 5590            | 15.5                       | ±2                      | 17.5                        |                     |
|                | 126     | 5630            | 15.5                       | ±2                      | 17.5                        |                     |
|                | 134     | 5670            | 15.5                       | ±2                      | 17.5                        |                     |
| 802.11 ac80    | 106     | 5530            | 15.5                       | ±2                      | 17.5                        |                     |
|                | 122     | 5610            | 15.5                       | ±2                      | 17.5                        |                     |
|                | 138     | 5690            | 15.5                       | ±2                      | 17.5                        |                     |

## U-NII-3 Chain0

| Mode           | Channel | Frequency | Chain0 Target power(dBm) | Tune up tolerance (dBm) | Maximum Tune up power (dBm) | Average power (dBm) |
|----------------|---------|-----------|--------------------------|-------------------------|-----------------------------|---------------------|
| 802.11 a       | 149     | 5745      | 13                       | ±2                      | 15                          | 14.5                |
|                | 153     | 5765      | 13                       | ±2                      | 15                          | 14.2                |
|                | 157     | 5785      | 13                       | ±2                      | 15                          | 14.3                |
|                | 161     | 5805      | 13                       | ±2                      | 15                          | 14.3                |
|                | 165     | 5825      | 13                       | ±2                      | 15                          | 14.4                |
| 802.11 n 20MHz | 149     | 5745      | 13                       | ±2                      | 15                          | Not required        |
|                | 153     | 5765      | 13                       | ±2                      | 15                          |                     |
|                | 157     | 5785      | 13                       | ±2                      | 15                          |                     |
|                | 161     | 5805      | 13                       | ±2                      | 15                          |                     |
|                | 165     | 5825      | 13                       | ±2                      | 15                          |                     |
| 802.11 n 40MHz | 151     | 5755      | 12.5                     | ±2                      | 14.5                        |                     |
|                | 159     | 5795      | 12.5                     | ±2                      | 14.5                        |                     |
| 802.11 ac80    | 155     | 5775      | 8                        | ±2                      | 10                          |                     |

## U-NII-3 Chain1

| Mode           | Channel | Frequency | Chain1 Target power(dBm) | Tune up tolerance (dBm) | Maximum Tune up power (dBm) | Average power (dBm) |
|----------------|---------|-----------|--------------------------|-------------------------|-----------------------------|---------------------|
| 802.11 a       | 149     | 5745      | 13                       | ±2                      | 15                          | 14.5                |
|                | 153     | 5765      | 13                       | ±2                      | 15                          | 14.5                |
|                | 157     | 5785      | 13                       | ±2                      | 15                          | 14.6                |
|                | 161     | 5805      | 13                       | ±2                      | 15                          | 14.3                |
|                | 165     | 5825      | 13                       | ±2                      | 15                          | 14.3                |
| 802.11 n 20MHz | 149     | 5745      | 13                       | ±2                      | 15                          | Not required        |
|                | 153     | 5765      | 13                       | ±2                      | 15                          |                     |
|                | 157     | 5785      | 13                       | ±2                      | 15                          |                     |
|                | 161     | 5805      | 13                       | ±2                      | 15                          |                     |
|                | 165     | 5825      | 13                       | ±2                      | 15                          |                     |
| 802.11 n 40MHz | 151     | 5755      | 12.5                     | ±2                      | 14.5                        |                     |
|                | 159     | 5795      | 12.5                     | ±2                      | 14.5                        |                     |
| 802.11 ac80    | 155     | 5775      | 8                        | ±2                      | 10                          |                     |

## U-NII-3 Chain0+1

| Mode              | Channel | Frequency | Chain0+1<br>Target<br>power(dBm) | Tune up<br>tolerance<br>(dBm) | Maximum<br>Tune up<br>power (dBm) | Average<br>power (dBm) |
|-------------------|---------|-----------|----------------------------------|-------------------------------|-----------------------------------|------------------------|
| 802.11 a          | 149     | 5745      | 16                               | ±2                            | 18                                | 17.5                   |
|                   | 153     | 5765      | 16                               | ±2                            | 18                                | 17.4                   |
|                   | 157     | 5785      | 16                               | ±2                            | 18                                | 17.5                   |
|                   | 161     | 5805      | 16                               | ±2                            | 18                                | 17.3                   |
|                   | 165     | 5825      | 16                               | ±2                            | 18                                | 17.4                   |
| 802.11 n<br>20MHz | 149     | 5745      | 16                               | ±2                            | 18                                | Not required           |
|                   | 153     | 5765      | 16                               | ±2                            | 18                                |                        |
|                   | 157     | 5785      | 16                               | ±2                            | 18                                |                        |
|                   | 161     | 5805      | 16                               | ±2                            | 18                                |                        |
|                   | 165     | 5825      | 16                               | ±2                            | 18                                |                        |
| 802.11 n<br>40MHz | 151     | 5755      | 15.5                             | ±2                            | 17.5                              |                        |
|                   | 159     | 5795      | 15.5                             | ±2                            | 17.5                              |                        |
| 802.11 ac80       | 155     | 5775      | 11                               | ±2                            | 13                                |                        |

## Note:

Chain0 is the Main Antenna

Chain1 is the Aux Antenna.

## Bluetooth

| Band    | Mode                    | Channel | Frequency | Averaged Power (dBm) |
|---------|-------------------------|---------|-----------|----------------------|
| 2.4 GHz | Bluetooth BR (GFSK)     | 0       | 2402      | 5.0                  |
|         |                         | 39      | 2441      | 5.1                  |
|         |                         | 78      | 2480      | 5.8                  |
|         | Bluetooth EDR3 (8-DPSK) | 0       | 2402      | 3.2                  |
|         |                         | 39      | 2441      | 3.9                  |
|         |                         | 78      | 2480      | 4.3                  |
|         | Bluetooth LE            | 0       | 2402      | 0.0                  |
|         |                         | 39      | 2441      | 0.3                  |
|         |                         | 78      | 2480      | 0.4                  |

## 10.5 SAR TEST CONFIGURATIONS

According to KDB 616217 D04, SAR testing for laptop PC is required for bottom surface. This EUT was tested in the base of EUT directly against the flat phantom.




Fig. Illustration for Laptop Setup

## 10.6 STANDALONE SAR TEST EXCLUSION

According to KDB447498 D01: The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances*  $\leq$  50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR,<sup>24</sup> where


- $f_{(\text{GHz})}$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation<sup>25</sup>
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below
- If the test separation distance (antenna-user) is  $< 5\text{mm}$ , 5mm is used for excluded SAR calculation

|                                  | Wireless Interface      | Bluetooth |
|----------------------------------|-------------------------|-----------|
| Tune-up Maximum power (dBm)      |                         | 7         |
| Tune-up Maximum rated power (mW) |                         | 5.012     |
| Body                             | Antenna to user (mm)    | 5         |
|                                  | Frequency(GHz)          | 2480      |
|                                  | SAR exclusion threshold | 1.579     |

Per KDB 447498 D01 exclusion thresholds is  $1.579 < 3$ , Bluetooth RF exposure evaluation is not required.

## 10.7 ANTENNA LOCATION

<Notebook>



Note: The distance between antenna and user is 8.37 mm

Device dimensions (H x W): 360 x 248 mm

| Antennas                 | Wireless Interface   |
|--------------------------|--|
| Bluetooth & WLAN Antenna | WLAN 2.4GHz<br>WLAN 5.2GHz<br>WLAN 5.3GHz<br>WLAN 5.5GHz<br>WLAN 5.8GHz<br>Bluetooth |
| Main Antenna             | WLAN TX/RX   |
| Aux Antenna              | WLAN TX/RX+ Bluetooth  |

**Test Mode**

|             |                                    |
|-------------|------------------------------------|
| IEEE 802.11 | Data transmission mode(802.11a;b;) |
|-------------|------------------------------------|

## 10.8 SAR MEASUREMENT RESULTS

### Note:

1. Per KDB 447498 D01, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
  - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
  - b. For WLAN: Reported SAR(W/kg)= Measured SAR(W/kg)\* Duty Cycle scaling factor \* Tune-up scaling factor
2. Per KDB 447498 D01, for each exposure position, if the highest output channel reported SAR  $\leq 0.8\text{W/kg}$ , other channels SAR testing is not necessary.
3. Per KDB 447498 D01, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the *reported* 1-g or 10-g SAR for the mid-band or highest output power channel is:
  - $\leq 0.8\text{ W/kg}$  or  $2.0\text{ W/kg}$ , for 1-g or 10-g respectively, when the transmission band is  $\leq 100\text{ MHz}$
  - $\leq 0.6\text{ W/kg}$  or  $1.5\text{ W/kg}$ , for 1-g or 10-g respectively, when the transmission band is between  $100\text{ MHz}$  and  $200\text{ MHz}$
  - $\leq 0.4\text{ W/kg}$  or  $1.0\text{ W/kg}$ , for 1-g or 10-g respectively, when the transmission band is  $\geq 200\text{ MHz}$

### SAR Results for Test Records

#### 2.4GHz

##### Ant1 (SPEED)

| Band        | Mode    | Configure | Test Position | Dist. (mm) | Freq. (MHz) | Chain | measured Power (dBm) | Tune-Up Limit (dBm) | Scaling Factor | Power Drift (dB) | Duty Cycle Scaling Factor | SAR1g (mW/g) | Scaled SAR1g (mW/g) |
|-------------|---------|-----------|---------------|------------|-------------|-------|----------------------|---------------------|----------------|------------------|---------------------------|--------------|---------------------|
| WLAN 2.4Ghz | 802.11b | NB        | Bottom        | 0          | 2462        | Main  | 19.9                 | 20.5                | 1.148          | 0.04             | 1                         | 0.616        | 0.707               |
| WLAN 2.4Ghz | 802.11b | NB        | Bottom        | 0          | 2462        | Aux   | 19.7                 | 20.5                | 1.202          | -0.08            | 1                         | 0.642        | 0.772               |

##### Ant2 (WNC)

| Band        | Mode    | Configure | Test Position | Dist. (mm) | Freq. (MHz) | Chain | measured Power (dBm) | Tune-Up Limit (dBm) | Scaling Factor | Power Drift (dB) | Duty Cycle Scaling Factor | SAR1g (mW/g) | Scaled SAR1g (mW/g) |
|-------------|---------|-----------|---------------|------------|-------------|-------|----------------------|---------------------|----------------|------------------|---------------------------|--------------|---------------------|
| WLAN 2.4Ghz | 802.11b | NB        | Bottom        | 0          | 2462        | Aux   | 19.7                 | 20.5                | 1.202          | 0.14             | 1                         | 0.592        | 0.712               |

**Note:** Ant1 and Ant2 are the same type and location. Ant1 was found to be worst case so full measurements were taken. The Worst case test configuration was then measured for Ant2.

Remark: SAR is not required for the following 2.4 GHz OFDM conditions.

- 1) When KDB Publication 447498 SAR test exclusion applies to the OFDM configuration.
- 2) When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is  $\leq 1.2\text{ W/kg}$ .

The highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is  $\leq 1.2\text{ W/kg}$ . So 2.4 GHz OFDM mode is not required.

## 5GHz

## Ant1 (SPEED)

| Band     | Mode    | Configure | Test Position | Dist. (mm) | Freq. (MHz) | Chain | measured Power (dBm) | Tune-Up Limit (dBm) | Scaling Factor | Power Drift (dB) | Duty Cycle Scaling Factor | SAR1g (mW/g) | Scaled SAR1g (mW/g) |
|----------|---------|-----------|---------------|------------|-------------|-------|----------------------|---------------------|----------------|------------------|---------------------------|--------------|---------------------|
| U-NII-2A | 802.11a | NB        | Bottom        | 0          | 5280        | Main  | 14.3                 | 15                  | 1.175          | -0.02            | 1                         | 0.235        | 0.276               |
| U-NII-2C | 802.11a | NB        | Bottom        | 0          | 5660        | Main  | 14.7                 | 15                  | 1.072          | 0.05             | 1                         | 0.341        | 0.365               |
| U-NII-3  | 802.11a | NB        | Bottom        | 0          | 5745        | Main  | 14.5                 | 15                  | 1.122          | -0.12            | 1                         | 0.320        | 0.359               |
| U-NII-2A | 802.11a | NB        | Bottom        | 0          | 5280        | Aux   | 14.6                 | 15                  | 1.096          | -0.06            | 1                         | 0.259        | 0.284               |
| U-NII-2C | 802.11a | NB        | Bottom        | 0          | 5660        | Aux   | 14.6                 | 15                  | 1.096          | 0.06             | 1                         | 0.478        | 0.524               |
| U-NII-3  | 802.11a | NB        | Bottom        | 0          | 5785        | Aux   | 14.6                 | 15                  | 1.096          | 0.13             | 1                         | 0.372        | 0.408               |

## Ant2 (WNC)

| Band     | Mode    | Configure | Test Position | Dist. (mm) | Freq. (MHz) | Chain | measured Power (dBm) | Tune-Up Limit (dBm) | Scaling Factor | Power Drift (dB) | Duty Cycle Scaling Factor | SAR1g (mW/g) | Scaled SAR1g (mW/g) |
|----------|---------|-----------|---------------|------------|-------------|-------|----------------------|---------------------|----------------|------------------|---------------------------|--------------|---------------------|
| U-NII-2C | 802.11a | NB        | Bottom        | 0          | 5660        | Aux   | 14.6                 | 15                  | 1.096          | 0.04             | 1                         | 0.361        | 0.396               |

**Note:** Ant1 and Ant2 are the same type and location. Ant1 was found to be worst case so full measurements were taken.

The Worst case test configuration was then measured for Ant2.

Remark: For devices that operate in both U-NII-1 and U-NII-2A bands using the same transmitter and antenna(s), SAR test reduction is determined according to the following

1) When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is  $\leq 1.2 \text{ W/kg}$ , SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition); otherwise, each band is tested independently for SAR.

2) When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is  $\leq 1.2 \text{ W/kg}$ , SAR is not required for the band with lower maximum output power in that test configuration; otherwise, each band is tested independently for SAR.

The highest reported SAR for U-NII is adjusted by the ratio of U-NII-1 to U-NII-2A specified maximum output power and the adjusted SAR is  $\leq 1.2 \text{ W/kg}$ . So U-NII-1 mode is not required.

## 10.9 REPEATED SAR MEASUREMENT

**Note:**

1. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is  $\geq 0.8\text{W/Kg}$
2. Per KDB 865664 D01v01r04, if the ratio of largest to smallest SAR for the original and first repeated measurement is  $\leq 1.2$  and the measured SAR  $< 1.45\text{W/Kg}$ , only one repeated measurement is required.
3. The ratio is the difference in percentage between original and repeated measured SAR.

| Band | Mode | Configure | Test Position | Freq (MHZ) | Original Measured SAR1g (mW/g) | 1st Repeated SAR1g (mW/g) | Ratio | Original Measured SAR1g (mW/g) | 2nd Repeated SAR1g (mW/g) | Ratio |
|------|------|-----------|---------------|------------|--------------------------------|---------------------------|-------|--------------------------------|---------------------------|-------|
| --   | --   | --        | --            | --         | --                             | --                        |       | --                             | --                        | --    |

## 10.10 SAR MULTI XMITER ASSESSMENT

|                           | Position | Applicable Combination |
|---------------------------|----------|------------------------|
| Simultaneous Transmission | Body     | Main Ant + Aux Ant     |
|                           |          | Main Ant + BT          |

**Note:**

1. Aux Antenna 2.4GHz WLAN and BT share the same antenna, and cannot transmit simultaneously.
2. For simultaneous transmission analysis, Bluetooth SAR is estimated per KDB 447498 D01 based on the formula below.  
(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] • [ √ f(GHz)/x] W/kg for test separation distances ≤ 50 mm; where x = 7.5 for 1-g SAR, and x = 18.75 for 10-g SAR.  
0.4 W/kg for 1-g SAR and 1.0 W/kg for 10-g SAR, when the test separation distances is > 50 mm.

**Bluetooth:**

|                      | Max power | Body (5mm distance) |
|----------------------|-----------|---------------------|
| Estimated SAR (W/kg) | 7 dBm     | 0.210 W/kg          |

3. Bluetooth & Wi-Fi estimated SAR is conservatively determined by 5mm separation, for all applicable exposure positions
4. Per KDB 447498 D01v06, simultaneous transmission SAR is compliant if,
  - 1) Scalar SAR summation < 1.6W/kg.
  - 2) SPLSR = (SAR1 + SAR2)1.5 / (min. separation distance, mm), and the peak separation distance is determined from the square root of [(x1-x2)² + (y1-y2)² + (z1-z2)²], where (x1, y1, z1) and (x2, y2, z2) are the coordinates of the extrapolated peak SAR locations in the zoom scan  
If SPLSR ≤ 0.04, simultaneously transmission SAR is compliant
  - 3) Simultaneously transmission SAR measurement, and the reported multi-band SAR < 1.6W/kg

| SUM $\sum$ SAR1g Chain0 WLAN 2.4G + Chain1 Bluetooth |                  |                           | Stand alone SAR(1g) [W/kg] |                          |                                |                                     | SUM SAR(1g)[W/kg]          |                   |
|--|------------------|---------------------------|----------------------------|--------------------------|--------------------------------|-------------------------------------|----------------------------|-------------------|
| Position   | Distance<br>[mm] | Main Antenna<br>WLAN 2.4G | Aux Antenna<br>WLAN 2.4G   | Aux Antenna<br>Bluetooth | Main ant 2.4G+<br>Aux ant 2.4G | Main ant<br>WLAN 2.4+<br>Aux ant BT | Stand alone SAR(1g) [W/kg] |                   |
|  |                  |                           |                            |                          |                                |                                     | Sum SAR(1g)[W/kg]          | Sum SAR(1g)[W/kg] |
| Bottom   | 0                | 0.707                     | 0.772                      | 0.210                    | 1.479                          | 0.917                               |                            |                   |

| SUM $\sum$ SAR1g Chain0 WLAN U-NII-2A + Chain1 WLAN U-NII-2A / Bluetooth |                  |                           | Stand alone SAR(1g) [W/kg] |                          |                                |                                     | SUM SAR(1g)[W/kg]          |                   |
|--|------------------|---------------------------|----------------------------|--------------------------|--------------------------------|-------------------------------------|----------------------------|-------------------|
| Position   | Distance<br>[mm] | Main Antenna<br>WLAN 5.3G | Aux Antenna<br>WLAN 5.3G   | Aux Antenna<br>Bluetooth | Main ant 5.3G+<br>Aux ant 5.3G | Main ant<br>WLAN 5.3+<br>Aux ant BT | Stand alone SAR(1g) [W/kg] |                   |
|  |                  |                           |                            |                          |                                |                                     | Sum SAR(1g)[W/kg]          | Sum SAR(1g)[W/kg] |
| Bottom   | 0                | 0.276                     | 0.284                      | 0.210                    | 0.560                          | 0.486                               |                            |                   |

| SUM $\sum$ SAR1g Chain0 WLAN U-NII-2C + Chain1 WLAN U-NII-2C / Bluetooth |                  |                            |                          |                          |                                |                                     |
|--|------------------|----------------------------|--------------------------|--------------------------|--------------------------------|-------------------------------------|
| Position   | Distance<br>[mm] | Stand alone SAR(1g) [W/kg] |                          |                          | SUM SAR(1g)[W/kg]              |                                     |
|  |                  | Main Antenna<br>WLAN 5.6G  | Aux Antenna<br>WLAN 5.6G | Aux Antenna<br>Bluetooth | Main ant 5.6G+<br>Aux ant 5.6G | Main ant<br>WLAN 5.6+<br>Aux ant BT |
| Bottom   | 0                | 0.365                      | 0.524                    | 0.210                    | 0.889                          | 0.575                               |

| SUM $\sum$ SAR1g Chain0 WLAN U-NII-3 + Chain1 WLAN U-NII-3/ Bluetooth |                  |                            |                          |                          |                                |                                     |
|---|------------------|----------------------------|--------------------------|--------------------------|--------------------------------|-------------------------------------|
| Position  | Distance<br>[mm] | Stand alone SAR(1g) [W/kg] |                          |                          | SUM SAR(1g)[W/kg]              |                                     |
|   |                  | Main Antenna<br>WLAN 5.8G  | Aux Antenna<br>WLAN 5.8G | Aux Antenna<br>Bluetooth | Main ant 5.8G+<br>Aux ant 5.8G | Main ant<br>WLAN 5.8+<br>Aux ant BT |
| Bottom  | 0                | 0.359                      | 0.408                    | 0.210                    | 0.767                          | 0.569                               |

## 11. EQUIPMENT LIST &amp; CALIBRATION STATUS

| Name of Equipment            | Manufacturer | Type/Model    | Serial Number   | Calibration Cycle(year) | Calibration Due |
|------------------------------|--------------|---------------|-----------------|-------------------------|-----------------|
| P C                          | HP           | Core(rm)3.16G | CZCO48171H      | N/A                     | N/A             |
| Signal Generator             | Agilent      | E8257C        | US37101915      | 1                       | 10/31/2017      |
| S-Parameter Network Analyzer | Agilent      | E5071B        | MY42301382      | 1                       | 02/27/2018      |
| Power meter                  | Anritsu      | ML2495A       | 1445010         | 1                       | 04/25/2018      |
| Power sensor                 | Anritsu      | MA2411B       | 1339220         | 1                       | 04/25/2018      |
| E-field PROBE                | SPEAG        | EX3DV4        | 3798            | 1                       | 07/25/2018      |
| DAE                          | SPEAG        | DEA4          | 1245            | 1                       | 07/19/2018      |
| Temperature meter            | TES          | TES 1360      | 050907372       | 1                       | 02/14/2018      |
| Electro Thermometer          | DTM          | DTM3000       | 3030            | 1                       | 01/03/2018      |
| DIPOLE 2450MHZ ANTENNA       | SPEAG        | D2450V2       | 817             | 2                       | 05/29/2018      |
| DIPOLE 5GHZ ANTENNA          | SPEAG        | D5GHzV2       | 1095            | 2                       | 05/22/2018      |
| DUMMY PROBE                  | SPEAG        | DP_2          | SPDP2001AA      | N/A                     | N/A             |
| SAM PHANTOM (ELI4 v4.0)      | SPEAG        | QDOVA001BB    | 1102            | N/A                     | N/A             |
| Twin SAM Phantom             | SPEAG        | QD000P40CD    | 1609            | N/A                     | N/A             |
| ROBOT                        | SPEAG        | TX60          | F10/5E6AA1/A101 | N/A                     | N/A             |
| ROBOT KRC                    | SPEAG        | CS8C          | F10/5E6AA1/C101 | N/A                     | N/A             |
| LIQUID CALIBRATION KIT       | ANTENNESSA   | 41/05 OCP9    | 00425167        | N/A                     | N/A             |

## 12. FACILITIES

All measurement facilities used to collect the measurement data are located at

No.10, Weiye Rd., Innovation Park, Eco & Tec. Development Part, Kunshan City, Jiangsu Province, China.

## 13. REFERENCES

- [1] Federal Communications Commission, \Report and order: Guidelines for evaluating the environmental effects of radiofrequency radiation", Tech. Rep. FCC 96-326, FCC, Washington, D.C. 20554, 1996.
- [2] David L. Means Kwok Chan, Robert F. Cleveland, \Evaluating compliance with FCC guidelines for human exposure to radiofrequency electromagnetic fields", Tech. Rep., Federal Communication Commision, O\_ce of Engineering & Technology, Washington, DC, 1997.
- [3] Thomas Schmid, Oliver Egger, and Niels Kuster, \Automated E\_eld scanning system for dosimetric assessments", IEEE Transactions on Microwave Theory and Techniques, vol. 44, pp. 105{113, Jan. 1996.
- [4] Niels Kuster, Ralph Kastle, and Thomas Schmid, \Dosimetric evaluation of mobile communications equipment with known precision", IEICE Transactions on Communications, vol. E80-B, no. 5, pp. 645{652, May 1997.
- [5] CENELEC, \Considerations for evaluating of human exposure to electromagnetic fields (EMFs) from mobile telecommunication equipment (MTE) in the frequency range 30MHz – 6GHz", Tech. Rep., CENELEC, European Committee for Electrotechnical Standardization, Brussels, 1997.
- [6] ANSI, ANSI/IEEE C95.1-1999: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz, The Institute of Electrical and Electronics Engineers, Inc., New York, NY 10017, 1992.
- [7] Katja Pokovic, Thomas Schmid, and Niels Kuster, \Robust setup for precise calibration of E\_eld probes in tissue simulating liquids at mobile communications frequencies", in ICECOM \_ 97, Dubrovnik, October 15{17, 1997, pp. 120{124.
- [8] Katja Pokovic, Thomas Schmid, and Niels Kuster, \E\_eld probe with improved isotropy in brain simulating liquids", in Proceedings of the ELMAR, Zadar, Croatia, 23{25 June, 1996, pp. 172{175.
- [9] Volker Hombach, Klaus Meier, Michael Burkhardt, Eberhard K. uhn, and Niels Kuster, \The dependence of EM energy absorption upon human head modeling at 900 MHz", IEEE Transactions onMicrowave Theory and Techniques, vol. 44, no. 10, pp. 1865{1873, Oct. 1996.
- [10] Klaus Meier, Ralf Kastle, Volker Hombach, Roger Tay, and Niels Kuster, \The dependence of EM energy absorption upon human head modeling at 1800 MHz", IEEE Transactions on Microwave Theory and Techniques, Oct. 1997, in press.
- [11] W. Gander, Computermathematik, Birkhaeuser, Basel, 1992.
- [12] W. H. Press, S. A. Teukolsky, W. T. Vetterling, and B. P. Flannery, Numerical Recepies in C, The Art of Scientific Computing, Second Edition, Cambridge University Press, 1992.. Dosimetric Evaluation of Sample device, month 1998 9
- [13] NIS81 NAMAS, \The treatment of uncertainty in EMC measurement", Tech. Rep., NAMAS Executive, National Physical Laboratory, Teddington, Middlesex, England, 1994.
- [14] Barry N. Taylor and Christ E. Kuyatt, \Guidelines for evaluating and expressing the uncertainty of NIST measurement results", Tech. Rep., National Institute of Standards and Technology, 1994. Dosimetric Evaluation of Sample device, month 1998 10

**APPENDIX A: DUT AND SAR SETUP PHOTO****APPENDIX B: PLOTS OF PERFORMANCE CHECK**

**The plots are showing as followings.**

Test Laboratory: Compliance Certification Services Inc.

Date: 9/15/2017

**System Performance Check - Body D2450**

**DUT: Dipole 2450 MHz D2450V2; Type: D2450V2; Serial: 817**

Communication System: UID 0, CW; Communication System Band: D2450 (2450.0 MHz); Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.943$  S/m;  $\epsilon_r = 51.697$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(7.32, 7.32, 7.32); Calibrated: 7/26/2017;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/20/2017
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:xxxx
- DASY52 52.8.8(1222);
- SEMCAD X Version 14.6.10 (7331)

**System Performance Check at Frequencies above 1 GHz/Pin=250 mW, dist=10mm (EX-Probe)/Area Scan (9x10x1):** Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 17.8 W/kg


**System Performance Check at Frequencies above 1 GHz/Pin=250 mW, dist=10mm (EX-Probe)/Zoom Scan (7x7x7) (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 101.3 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 29.3 W/kg

**SAR(1 g) = 12.7 W/kg; SAR(10 g) = 6.12 W/kg**

Maximum value of SAR (measured) = 19.5 W/kg



Test Laboratory: Compliance Certification Services Inc.

Date: 9/14/2017

**System Performance Check - Body D5200**

**DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN:1095**

Communication System: UID 0, CW; Communication System Band: D5GHz (5000.0 - 6000.0 MHz); Frequency: 5200 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 5200$  MHz;  $\sigma = 5.233$  S/m;  $\epsilon_r = 48.913$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(4.81, 4.81, 4.81); Calibrated: 7/26/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/20/2017
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:xxxx
- DASY52 52.8.8(1222);
- SEMCAD X Version 14.6.10 (7331)

**System Performance Check with D5GHzV2 Dipole (graded grid)/d=10mm, Pin=100mW, f=5200**

**MHz 2/Area Scan (10x10x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 17.9 W/kg


**System Performance Check with D5GHzV2 Dipole (graded grid)/d=10mm, Pin=100mW, f=5200**  
**MHz 2/Zoom Scan (4x4x1.4mm, graded), dist=1.4mm (7x7x6)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 64.62 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 34.8 W/kg

**SAR(1 g) = 7.38 W/kg; SAR(10 g) = 2.26 W/kg**

Maximum value of SAR (measured) = 17.7 W/kg



Test Laboratory: Compliance Certification Services Inc.

Date: 9/14/2017

**System Performance Check - Body D5300**

**DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN:1095**

Communication System: UID 0, CW; Communication System Band: D5GHz (5000.0 - 6000.0 MHz); Frequency: 5300 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 5300$  MHz;  $\sigma = 5.364$  S/m;  $\epsilon_r = 48.673$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(4.67, 4.67, 4.67); Calibrated: 7/26/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/20/2017
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:xxxx
- DASY52 52.8.8(1222);
- SEMCAD X Version 14.6.10 (7331)

**System Performance Check with D5GHzV2 Dipole (graded grid)/d=10mm, Pin=100mW, f=5300**

**MHz 2/Area Scan (10x10x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 19.1 W/kg


**System Performance Check with D5GHzV2 Dipole (graded grid)/d=10mm, Pin=100mW, f=5300**  
**MHz 2/Zoom Scan (4x4x1.4mm, graded), dist=1.4mm (7x7x6)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 63.97 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 37.1 W/kg

**SAR(1 g) = 7.63 W/kg; SAR(10 g) = 2.21 W/kg**

Maximum value of SAR (measured) = 18.1 W/kg



Test Laboratory: Compliance Certification Services Inc.

Date: 9/14/2017

**System Performance Check - Body D5500**

**DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN:1095**

Communication System: UID 0, CW; Communication System Band: D5GHz (5000.0 - 6000.0 MHz);

Frequency: 5500 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 5500$  MHz;  $\sigma = 5.632$  S/m;  $\epsilon_r = 48.202$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(4.26, 4.26, 4.26); Calibrated: 7/26/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/20/2017
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:xxxx
- DASY52 52.8.8(1222);
- SEMCAD X Version 14.6.10 (7331)

**System Performance Check with D5GHzV2 Dipole (graded grid)/d=10mm, Pin=100mW, f=5500**

**MHz 2 2/Area Scan (10x10x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 19.5 W/kg

**System Performance Check with D5GHzV2 Dipole (graded grid)/d=10mm, Pin=100mW, f=5500**

**MHz 2 2/Zoom Scan (4x4x1.4mm, graded), dist=1.4mm (8x8x7)/Cube 0:** Measurement grid:


dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 67.20 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 40.5 W/kg

**SAR(1 g) = 8.04 W/kg; SAR(10 g) = 2.34 W/kg**

Maximum value of SAR (measured) = 21.4 W/kg



Test Laboratory: Compliance Certification Services Inc.

Date: 9/14/2017

**System Performance Check - Body D5600**

**DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN:1095**

Communication System: UID 0, CW; Communication System Band: D5GHz (5000.0 - 6000.0 MHz); Frequency: 5600 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 5600$  MHz;  $\sigma = 5.773$  S/m;  $\epsilon_r = 47.973$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(4.18, 4.18, 4.18); Calibrated: 7/26/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/20/2017
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:xxxx
- DASY52 52.8.8(1222);
- SEMCAD X Version 14.6.10 (7331)

**System Performance Check with D5GHzV2 Dipole (graded grid)/d=10mm, Pin=100mW, f=5600**

**MHz 2/Area Scan (10x10x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 20.4 W/kg

**System Performance Check with D5GHzV2 Dipole (graded grid)/d=10mm, Pin=100mW, f=5600**


**MHz 2/Zoom Scan (4x4x1.4mm, graded), dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 65.54 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 42.6 W/kg

**SAR(1 g) = 8.15 W/kg; SAR(10 g) = 2.32 W/kg**

Maximum value of SAR (measured) = 22.4 W/kg



Test Laboratory: Compliance Certification Services Inc.

Date: 9/14/2017

**System Performance Check - Body D5800**

**DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN:1095**

Communication System: UID 0, CW; Communication System Band: D5GHz (5000.0 - 6000.0 MHz); Frequency: 5800 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 5800$  MHz;  $\sigma = 6.071$  S/m;  $\epsilon_r = 47.521$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(4.45, 4.45, 4.45); Calibrated: 7/26/2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/20/2017
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:xxxx
- DASY52 52.8.8(1222);
- SEMCAD X Version 14.6.10 (7331)

**System Performance Check with D5GHzV2 Dipole (graded grid)/d=10mm, Pin=100mW, f=5800**

**MHz 2/Area Scan (10x10x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 18.4 W/kg

**System Performance Check with D5GHzV2 Dipole (graded grid)/d=10mm, Pin=100mW, f=5800**


**MHz 2/Zoom Scan (4x4x1.4mm, graded), dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 62.98 V/m; Power Drift = 0.19 dB

Peak SAR (extrapolated) = 41.6 W/kg

**SAR(1 g) = 7.84 W/kg; SAR(10 g) = 2.30 W/kg**

Maximum value of SAR (measured) = 21.0 W/kg



**APPENDIX C: DASY CALIBRATION CERTIFICATE**

The DASY Calibration Certificates are showing in the file named Appendix C DASY Calibration Certificate.

**APPENDIX D: PLOTS OF SAR TEST RESULT**

The plots are showing in the file named Appendix D Plots of SAR Test Result

**END REPORT**