

# FCC SAR Test Report


Report No. : SA160330C14  
Applicant : Qualcomm Atheros, Inc.  
Address : 1700 Technology Dr San Jose, CA 95110  
Product : 802.11a/b/g/n/ac + BT 4.1 M.2 2230 Type Card  
FCC ID : PPD-QCNFA364AH  
Brand : Qualcomm Atheros  
Model No. : QCNFA364A  
Standards : FCC 47 CFR Part 2 (2.1093) / IEEE C95.1:1992 / IEEE Std 1528:2013  
KDB 865664 D01 v01r04 / KDB 865664 D02 v01r02  
KDB 248227 D01 v02r02 / KDB 447498 D01 v06  
KDB 616217 D04 v01r02  
Sample Received Date : Mar. 30, 2016  
Date of Testing : May 03, 2016 ~ Jun. 22, 2016

**CERTIFICATION:** The above equipment have been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch – Lin Kou Laboratories**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's SAR characteristics under the conditions specified in this report. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval, or endorsement by TAF or any government agencies.

Prepared By :

  
Vera Huang / Specialist

Approved By :

  
Eli Hsu / Supervisor

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

## Table of Contents

Release Control Record .....	3
1. Summary of Maximum SAR Value .....	4
2. Description of Equipment Under Test .....	5
3. SAR Measurement System .....	6
3.1 Definition of Specific Absorption Rate (SAR) .....	6
3.2 SPEAG DASY System .....	6
3.2.1 Robot.....	7
3.2.2 Probes.....	8
3.2.3 Data Acquisition Electronics (DAE) .....	8
3.2.4 Phantoms.....	9
3.2.5 Device Holder.....	10
3.2.6 System Validation Dipoles.....	10
3.2.7 Tissue Simulating Liquids.....	11
3.3 SAR System Verification .....	14
3.4 SAR Measurement Procedure .....	15
3.4.1 Area & Zoom Scan Procedure .....	15
3.4.2 Volume Scan Procedure.....	15
3.4.3 Power Drift Monitoring.....	16
3.4.4 Spatial Peak SAR Evaluation.....	16
3.4.5 SAR Averaged Methods.....	16
4. SAR Measurement Evaluation .....	17
4.1 EUT Configuration and Setting.....	17
4.2 EUT Testing Position .....	19
4.2.1 Simultaneous Transmission Possibilities.....	19
4.3 Tissue Verification .....	20
4.4 System Validation.....	20
4.5 System Verification .....	21
4.6 Maximum Output Power.....	22
4.6.1 Maximum Conducted Power .....	22
4.6.2 Measured Conducted Power Result.....	25
4.7 SAR Testing Results .....	26
4.7.1 SAR Test Reduction Considerations .....	26
4.7.2 SAR Results for Body Exposure Condition (Separation Distance is 0 cm Gap).....	27
4.7.3 SAR Measurement Variability.....	29
5. Calibration of Test Equipment.....	31
6. Measurement Uncertainty .....	32
7. Information on the Testing Laboratories.....	34

**Appendix A. SAR Plots of System Verification**
**Appendix B. SAR Plots of SAR Measurement**
**Appendix C. Calibration Certificate for Probe and Dipole**
**Appendix D. Photographs of EUT and Setup**

# Release Control Record

## 1. Summary of Maximum SAR Value

Equipment Class	Mode	EUT 1	EUT 2
		Highest Reported Body SAR <sub>1g</sub> (0 cm Gap) (W/kg)	Highest Reported Body SAR <sub>1g</sub> (0 cm Gap) (W/kg)
DTS	2.4G WLAN	1.00	1.10
NII	5.3G WLAN	1.14	1.15
	5.6G WLAN	1.16	1.16
	5.8G WLAN	1.08	0.96
DSS	Bluetooth	0.00	0.01
Highest Simultaneous Transmission SAR		Body (W/kg)	Body (W/kg)
DTS + DSS		1.00	1.11
NII + DSS		1.16	1.17

**Note:**

1. The SAR limit (**Head & Body: SAR<sub>1g</sub> 1.6 W/kg, Extremity: SAR<sub>10g</sub> 4.0 W/kg**) for general population / uncontrolled exposure is specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992.

## FCC SAR Test Report

### 2. Description of Equipment Under Test

EUT Type	802.11a/b/g/n/ac + BT 4.1 M.2 2230 Type Card
FCC ID	PPD-QCNFA364AH
Brand Name	Qualcomm Atheros
Model Name	QCNFA364A
EUT Configuration	EUT 1: EUT + Antenna 1 (ACON) EUT 2: EUT + Antenna 2 (TE)
Tx Frequency Bands (Unit: MHz)	WLAN : 2412 ~ 2462, 5180 ~ 5240, 5260 ~ 5320, 5500 ~ 5700, 5745 ~ 5825 Bluetooth : 2402 ~ 2480
Uplink Modulations	802.11b : DSSS 802.11a/g/n/ac : OFDM Bluetooth : GFSK, π/4-DQPSK, 8-DPSK
Maximum Tune-up Conducted Power (Unit: dBm)	Please refer to section 4.6.1 of this report.
Antenna Type	Refer to Note
EUT Stage	Production Unit

**Note:**

1. The EUT was installed in Portable Computer (Brand: Dell, Model: P56F).
2. The antenna information is listed as below.

Antenna Type	Manufacturer	Part Number	Antenna Gain (dBi)			
			2.4GHz	5.3 GHz	5.6 GHz	5.8 GHz
PIFA	ACON	WLAN Main Antenna: APL6Y-700002 WLAN Aux. Antenna: APL6Y-700002	Main: 1.01 Aux.: -0.07	Main: 2.77 Aux.: 0.97	Main: 1.65 Aux.: 1.72	Main: 1.65 Aux.: 1.72
PIFA	TE	WLAN Main Antenna: 1556723-1 WLAN Aux. Antenna: 1556723-1	Main: -2.24 Aux.: -1.97	Main: -0.33 Aux.: -2.98	Main: -3.26 Aux.: -2.22	Main: -2.40 Aux.: -2.22

3. The above EUT information is declared by manufacturer and for more detailed features description please refers to the manufacturer's specifications or User's Manual.

**List of Accessory:**

Battery 1	Brand Name	Dell
	Manufacturer	SIMPLO
	Model Name	1P6KD
	Power Rating	11.4Vdc, 84Wh
	Type	Li-ion
Battery 2	Brand Name	Dell
	Manufacturer	LG
	Model Name	62MJV
	Power Rating	11.4Vdc, 56Wh
	Type	Li-ion
Antenna 1	Brand Name	Dell
	Manufacturer	ACON
	Model Name	APL6Y-700002
Antenna 2	Brand Name	Dell
	Manufacturer	TE
	Model Name	1556723-1

### 3. SAR Measurement System

#### 3.1 Definition of Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density ( $\rho$ ). The equation description is as below:

$$SAR = \frac{d}{dt} \left( \frac{dW}{dm} \right) = \frac{d}{dt} \left( \frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)


SAR measurement can be related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where:  $\sigma$  is the conductivity of the tissue,  $\rho$  is the mass density of the tissue and  $E$  is the RMS electrical field strength.

#### 3.2 SPEAG DASY System

DASY system consists of high precision robot, probe alignment sensor, phantom, robot controller, controlled measurement server and near-field probe. The robot includes six axes that can move to the precision position of the DASY4/5 software defined. The DASY software can define the area that is detected by the probe. The robot is connected to controlled box. Controlled measurement server is connected to the controlled robot box. The DAE includes amplifier, signal multiplexing, AD converter, offset measurement and surface detection. It is connected to the Electro-optical coupler (ECO). The ECO performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC.


**Fig-3.1 SPEAG DASY52 System Setup**

### 3.2.1 Robot

The SPEAG DASY52 systems use the high precision robots from Stäubli SA (France). For the 6-axis controller system, the robot controller version (CS8c) from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- High precision (repeatability  $\pm 0.035$  mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)


**Fig-3.2 SPEAG DASY52 System**

## FCC SAR Test Report

### 3.2.2 Probes

The SAR measurement is conducted with the dosimetric probe. The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency.

<b>Model</b>	EX3DV4	
<b>Construction</b>	Symmetrical design with triangular core. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE).	
<b>Frequency</b>	10 MHz to 6 GHz Linearity: $\pm 0.2$ dB	
<b>Directivity</b>	$\pm 0.3$ dB in HSL (rotation around probe axis) $\pm 0.5$ dB in tissue material (rotation normal to probe axis)	
<b>Dynamic Range</b>	10 $\mu$ W/g to 100 mW/g Linearity: $\pm 0.2$ dB (noise: typically $< 1$ $\mu$ W/g)	
<b>Dimensions</b>	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

<b>Model</b>	ES3DV3	
<b>Construction</b>	Symmetrical design with triangular core. Interleaved sensors. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE).	
<b>Frequency</b>	10 MHz to 4 GHz Linearity: $\pm 0.2$ dB	
<b>Directivity</b>	$\pm 0.2$ dB in HSL (rotation around probe axis) $\pm 0.3$ dB in tissue material (rotation normal to probe axis)	
<b>Dynamic Range</b>	5 $\mu$ W/g to 100 mW/g Linearity: $\pm 0.2$ dB	
<b>Dimensions</b>	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 3.9 mm (Body: 12 mm) Distance from probe tip to dipole centers: 2.0 mm	

### 3.2.3 Data Acquisition Electronics (DAE)

<b>Model</b>	DAE3, DAE4	
<b>Construction</b>	Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY embedded system (fully remote controlled). Two step probe touch detector for mechanical surface detection and emergency robot stop.	
<b>Measurement Range</b>	-100 to +300 mV (16 bit resolution and two range settings: 4mV, 400mV)	
<b>Input Offset Voltage</b>	$< 5\mu$ V (with auto zero)	
<b>Input Bias Current</b>	$< 50$ fA	
<b>Dimensions</b>	60 x 60 x 68 mm	

## 3.2.4 Phantoms

<b>Model</b>	Twin SAM	
<b>Construction</b>	The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot.	
<b>Material</b>	Vinylester, glass fiber reinforced (VE-GF)	
<b>Shell Thickness</b>	$2 \pm 0.2$ mm ( $6 \pm 0.2$ mm at ear point)	
<b>Dimensions</b>	Length: 1000 mm Width: 500 mm Height: adjustable feet	
<b>Filling Volume</b>	approx. 25 liters	

<b>Model</b>	ELI	
<b>Construction</b>	Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles.	
<b>Material</b>	Vinylester, glass fiber reinforced (VE-GF)	
<b>Shell Thickness</b>	$2.0 \pm 0.2$ mm (bottom plate)	
<b>Dimensions</b>	Major axis: 600 mm Minor axis: 400 mm	
<b>Filling Volume</b>	approx. 30 liters	

## FCC SAR Test Report

### 3.2.5 Device Holder

<b>Model</b>	Mounting Device	
<b>Construction</b>	In combination with the Twin SAM Phantom or ELI4, the Mounting Device enables the rotation of the mounted transmitter device in spherical coordinates. Rotation point is the ear opening point. Transmitter devices can be easily and accurately positioned according to IEC, IEEE, FCC or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat).	
<b>Material</b>	POM	


<b>Model</b>	Laptop Extensions Kit	
<b>Construction</b>	Simple but effective and easy-to-use extension for Mounting Device that facilitates the testing of larger devices according to IEC 62209-2 (e.g., laptops, cameras, etc.). It is lightweight and fits easily on the upper part of the Mounting Device in place of the phone positioner.	
<b>Material</b>	POM, Acrylic glass, Foam	

### 3.2.6 System Validation Dipoles

<b>Model</b>	D-Serial	
<b>Construction</b>	Symmetrical dipole with 1/4 balun. Enables measurement of feed point impedance with NWA. Matched for use near flat phantoms filled with tissue simulating solutions.	
<b>Frequency</b>	750 MHz to 5800 MHz	
<b>Return Loss</b>	> 20 dB	
<b>Power Capability</b>	> 100 W (f < 1GHz), > 40 W (f > 1GHz)	

### 3.2.7 Tissue Simulating Liquids

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5% are listed in Table-3.1.



The dielectric properties of the head tissue simulating liquids are defined in IEEE 1528, and KDB 865664 D01 Appendix A. For the body tissue simulating liquids, the dielectric properties are defined in KDB 865664 D01 Appendix A. The dielectric properties of the tissue simulating liquids were verified prior to the SAR evaluation using a dielectric assessment kit and a network analyzer.

Table-3.1 Targets of Tissue Simulating Liquid

Frequency (MHz)	Target Permittivity	Range of ±5%	Target Conductivity	Range of ±5%
<b>For Head</b>				
750	41.9	39.8 ~ 44.0	0.89	0.85 ~ 0.93
835	41.5	39.4 ~ 43.6	0.90	0.86 ~ 0.95
900	41.5	39.4 ~ 43.6	0.97	0.92 ~ 1.02
1450	40.5	38.5 ~ 42.5	1.20	1.14 ~ 1.26
1640	40.3	38.3 ~ 42.3	1.29	1.23 ~ 1.35
1750	40.1	38.1 ~ 42.1	1.37	1.30 ~ 1.44
1800	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
1900	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
2000	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
2300	39.5	37.5 ~ 41.5	1.67	1.59 ~ 1.75
2450	39.2	37.2 ~ 41.2	1.80	1.71 ~ 1.89
2600	39.0	37.1 ~ 41.0	1.96	1.86 ~ 2.06
3500	37.9	36.0 ~ 39.8	2.91	2.76 ~ 3.06
5200	36.0	34.2 ~ 37.8	4.66	4.43 ~ 4.89
5300	35.9	34.1 ~ 37.7	4.76	4.52 ~ 5.00
5500	35.6	33.8 ~ 37.4	4.96	4.71 ~ 5.21
5600	35.5	33.7 ~ 37.3	5.07	4.82 ~ 5.32
5800	35.3	33.5 ~ 37.1	5.27	5.01 ~ 5.53
<b>For Body</b>				
750	55.5	52.7 ~ 58.3	0.96	0.91 ~ 1.01
835	55.2	52.4 ~ 58.0	0.97	0.92 ~ 1.02
900	55.0	52.3 ~ 57.8	1.05	1.00 ~ 1.10
1450	54.0	51.3 ~ 56.7	1.30	1.24 ~ 1.37
1640	53.8	51.1 ~ 56.5	1.40	1.33 ~ 1.47
1750	53.4	50.7 ~ 56.1	1.49	1.42 ~ 1.56
1800	53.3	50.6 ~ 56.0	1.52	1.44 ~ 1.60
1900	53.3	50.6 ~ 56.0	1.52	1.44 ~ 1.60
2000	53.3	50.6 ~ 56.0	1.52	1.44 ~ 1.60
2300	52.9	50.3 ~ 55.5	1.81	1.72 ~ 1.90
2450	52.7	50.1 ~ 55.3	1.95	1.85 ~ 2.05
2600	52.5	49.9 ~ 55.1	2.16	2.05 ~ 2.27
3500	51.3	48.7 ~ 53.9	3.31	3.14 ~ 3.48
5200	49.0	46.6 ~ 51.5	5.30	5.04 ~ 5.57
5300	48.9	46.5 ~ 51.3	5.42	5.15 ~ 5.69
5500	48.6	46.2 ~ 51.0	5.65	5.37 ~ 5.93
5600	48.5	46.1 ~ 50.9	5.77	5.48 ~ 6.06
5800	48.2	45.8 ~ 50.6	6.00	5.70 ~ 6.30

**FCC SAR Test Report**


The following table gives the recipes for tissue simulating liquids.

**Table-3.2 Recipes of Tissue Simulating Liquid**

Tissue Type	Bactericide	DGBE	HEC	NaCl	Sucrose	Triton X-100	Water	Diethylene Glycol Mono-hexylether
H750	0.2	-	0.2	1.5	56.0	-	42.1	-
H835	0.2	-	0.2	1.5	57.0	-	41.1	-
H900	0.2	-	0.2	1.4	58.0	-	40.2	-
H1450	-	43.3	-	0.6	-	-	56.1	-
H1640	-	45.8	-	0.5	-	-	53.7	-
H1750	-	47.0	-	0.4	-	-	52.6	-
H1800	-	44.5	-	0.3	-	-	55.2	-
H1900	-	44.5	-	0.2	-	-	55.3	-
H2000	-	44.5	-	0.1	-	-	55.4	-
H2300	-	44.9	-	0.1	-	-	55.0	-
H2450	-	45.0	-	0.1	-	-	54.9	-
H2600	-	45.1	-	0.1	-	-	54.8	-
H3500	-	8.0	-	0.2	-	20.0	71.8	-
H5G	-	-	-	-	-	17.2	65.5	17.3
B750	0.2	-	0.2	0.8	48.8	-	50.0	-
B835	0.2	-	0.2	0.9	48.5	-	50.2	-
B900	0.2	-	0.2	0.9	48.2	-	50.5	-
B1450	-	34.0	-	0.3	-	-	65.7	-
B1640	-	32.5	-	0.3	-	-	67.2	-
B1750	-	31.0	-	0.2	-	-	68.8	-
B1800	-	29.5	-	0.4	-	-	70.1	-
B1900	-	29.5	-	0.3	-	-	70.2	-
B2000	-	30.0	-	0.2	-	-	69.8	-
B2300	-	31.0	-	0.1	-	-	68.9	-
B2450	-	31.4	-	0.1	-	-	68.5	-
B2600	-	31.8	-	0.1	-	-	68.1	-
B3500	-	28.8	-	0.1	-	-	71.1	-
B5G	-	-	-	-	-	10.7	78.6	10.7

### 3.3 SAR System Verification

The system check verifies that the system operates within its specifications. It is performed daily or before every SAR measurement. The system check uses normal SAR measurements in the flat section of the phantom with a matched dipole at a specified distance. The system verification setup is shown as below.



The validation dipole is placed beneath the flat phantom with the specific spacer in place. The distance spacer is to touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The spectrum analyzer measures the forward power at the location of the system check dipole connector. The signal generator is adjusted for the desired forward power (250 mW is used for 700 MHz to 3 GHz, 100 mW is used for 3.5 GHz to 6 GHz) at the dipole connector and the power meter is read at that level. After connecting the cable to the dipole, the signal generator is readjusted for the same reading at power meter.

After system check testing, the SAR result will be normalized to 1W forward input power and compared with the reference SAR value derived from validation dipole certificate report. The deviation of system check should be within 10 %.

### 3.4 SAR Measurement Procedure

According to the SAR test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

The SAR measurement procedures for each of test conditions are as follows:

- (a) Make EUT to transmit maximum output power
- (b) Measure conducted output power through RF cable
- (c) Place the EUT in the specific position of phantom
- (d) Perform SAR testing steps on the DASY system
- (e) Record the SAR value

#### 3.4.1 Area & Zoom Scan Procedure

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. According to KDB 865664 D01, the resolution for Area and Zoom scan is specified in the table below.

Items	<= 2 GHz	2-3 GHz	3-4 GHz	4-5 GHz	5-6 GHz
Area Scan ( $\Delta x, \Delta y$ )	<= 15 mm	<= 12 mm	<= 12 mm	<= 10 mm	<= 10 mm
Zoom Scan ( $\Delta x, \Delta y$ )	<= 8 mm	<= 5 mm	<= 5 mm	<= 4 mm	<= 4 mm
Zoom Scan ( $\Delta z$ )	<= 5 mm	<= 5 mm	<= 4 mm	<= 3 mm	<= 2 mm
Zoom Scan Volume	>= 30 mm	>= 30 mm	>= 28 mm	>= 25 mm	>= 22 mm

**Note:**

When zoom scan is required and report SAR is  $\leq 1.4 \text{ W/kg}$ , the zoom scan resolution of  $\Delta x / \Delta y$  (2-3GHz:  $\leq 8 \text{ mm}$ , 3-4GHz:  $\leq 7 \text{ mm}$ , 4-6GHz:  $\leq 5 \text{ mm}$ ) may be applied.

#### 3.4.2 Volume Scan Procedure

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

### 3.4.3 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drift more than 5%, the SAR will be retested.

### 3.4.4 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

### 3.4.5 SAR Averaged Methods

In DASY, the interpolation and extrapolation are both based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5 mm.

## 4. SAR Measurement Evaluation

### 4.1 EUT Configuration and Setting

#### <Considerations Related to WLAN for Setup and Testing>

In general, various vendor specific external test software and chipset based internal test modes are typically used for SAR measurement. These chipset based test mode utilities are generally hardware and manufacturer dependent, and often include substantial flexibility to reconfigure or reprogram a device. A Wi-Fi device must be configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools for SAR measurement. The test frequencies established using test mode must correspond to the actual channel frequencies. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. In addition, a periodic transmission duty factor is required for current generation SAR systems to measure SAR correctly. The reported SAR must be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

According to KDB 248227 D01, this device has installed WLAN engineering testing software which can provide continuous transmitting RF signal. During WLAN SAR testing, this device was operated to transmit continuously at the maximum transmission duty with specified transmission mode, operating frequency, lowest data rate, and maximum output power.

#### Initial Test Configuration

An initial test configuration is determined for OFDM transmission modes in 2.4 GHz and 5 GHz bands according to the channel bandwidth, modulation and data rate combination(s) with the highest maximum output power specified for production units in each standalone and aggregated frequency band. When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel in the initial test configuration, for each frequency band.

#### Subsequent Test Configuration

SAR measurement requirements for the remaining 802.11 transmission mode configurations that have not been tested in the initial test configuration are determined separately for each standalone and aggregated frequency band, in each exposure condition, according to the maximum output power specified for production units. Additional power measurements may be required to determine if SAR measurements are required for subsequent highest output power channels in a subsequent test configuration. When the highest reported SAR for the initial test configuration according to the initial test position or fixed exposure position requirements, is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is  $\leq 1.2 \text{ W/kg}$ , SAR is not required for that subsequent test configuration.

### SAR Test Configuration and Channel Selection

When multiple channel bandwidth configurations in a frequency band have the same specified maximum output power, the initial test configuration is using largest channel bandwidth, lowest order modulation, lowest data rate, and lowest order 802.11 mode (i.e., 802.11a is chosen over 802.11n then 802.11ac or 802.11g is chosen over 802.11n). After an initial test configuration is determined, if multiple test channels have the same measured maximum output power, the channel chosen for SAR measurement is determined according to the following.

- 1) The channel closest to mid-band frequency is selected for SAR measurement.
- 2) For channels with equal separation from mid-band frequency; for example, high and low channels or two mid-band channels, the higher frequency (number) channel is selected for SAR measurement.

### Test Reduction for U-NII-1 (5.2 GHz) and U-NII-2A (5.3 GHz) Bands

For devices that operate in both U-NII bands using the same transmitter and antenna(s), SAR test reduction is determined according to the following.


- 1) When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is  $\leq 1.2 \text{ W/kg}$ , SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition).
- 2) When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is  $\leq 1.2 \text{ W/kg}$ , SAR is not required for the band with lower maximum output power in that test configuration.

### <Considerations Related to Bluetooth for Setup and Testing>

This device has installed Bluetooth engineering testing software which can provide continuous transmitting RF signal. During Bluetooth SAR testing, this device was operated to transmit continuously at the maximum transmission duty with specified transmission mode, operating frequency, lowest data rate, and maximum output power.

## 4.2 EUT Testing Position

For laptop PC, according to KDB 616217 D04, SAR evaluation is required for the bottom surface of the keyboard. This EUT was tested in the base of EUT directly against the flat phantom. The required minimum test separation distance for incorporating transmitters and antennas into laptop computer display is determined with the display screen opened at an angle of 90° to the keyboard compartment.



**Fig-4.1 Illustration for Laptop Setup**

### 4.2.1 Simultaneous Transmission Possibilities

The simultaneous transmission possibilities for this device are listed as below.

Simultaneous TX Combination	Capable Transmit Configurations	Body Exposure Condition
1	WLAN 2.4G( Data) + BT (Data)	Yes
2	WLAN 5G( Data) + BT (Data)	Yes

**Note :**

1. The 2.4G WLAN and 5G WLAN cannot transmit simultaneously.

#### 4.3 Tissue Verification

The measuring results for tissue simulating liquid are shown as below.

Test Date	Tissue Type	Frequency (MHz)	Liquid Temp. (°C)	Measured Conductivity ( $\sigma$ )	Measured Permittivity ( $\epsilon_r$ )	Target Conductivity ( $\sigma$ )	Target Permittivity ( $\epsilon_r$ )	Conductivity Deviation (%)	Permittivity Deviation (%)
May 03, 2016	Body	2450	23.6	2.017	51.297	1.95	52.7	3.44	-2.66
May 04, 2016	Body	2450	23.4	2.015	51.580	1.95	52.7	3.33	-2.13
May 18, 2016	Body	2450	23.5	1.966	52.164	1.95	52.7	0.82	-1.02
May 20, 2016	Body	2450	23.5	2.012	51.434	1.95	52.7	3.18	-2.40
Jun. 16, 2016	Body	2450	23.5	2.013	51.240	1.95	52.7	3.23	-2.77
May 04, 2016	Body	5300	23.2	5.561	48.020	5.42	48.9	2.60	-1.80
May 19, 2016	Body	5300	23.3	5.521	46.985	5.42	48.9	1.86	-3.92
Jun 22, 2016	Body	5300	23.3	5.430	47.965	5.42	48.9	0.18	-1.91
May 05, 2016	Body	5600	23.4	5.971	47.139	5.77	48.5	3.48	-2.81
May 19, 2016	Body	5600	23.3	5.928	46.687	5.77	48.5	2.74	-3.74
May 05, 2016	Body	5800	23.4	6.268	46.705	6.00	48.2	4.47	-3.10
May 19, 2016	Body	5800	23.3	6.240	46.245	6.00	48.4	4.00	-4.53
Jun 15, 2016	Body	5800	23.1	6.181	46.557	6.00	48.4	3.02	-3.81
Jun 22, 2016	Body	5800	23.6	6.073	47.228	6.00	48.4	1.22	-2.42

**Note:**

The dielectric properties of the tissue simulating liquid must be measured within 24 hours before the SAR testing and within  $\pm 5\%$  of the target values. Liquid temperature during the SAR testing must be within  $\pm 2$  °C.

#### 4.4 System Validation

The SAR measurement system was validated according to procedures in KDB 865664 D01. The validation status in tabulated summary is as below.

Test Date	Probe S/N	Calibration Point		Measured Conductivity ( $\sigma$ )	Measured Permittivity ( $\epsilon_r$ )	Validation for CW			Validation for Modulation		
						Sensitivity Range	Probe Linearity	Probe Isotropy	Modulation Type	Duty Factor	PAR
May 03, 2016	3650	Body	2450	2.017	51.297	Pass	Pass	Pass	OFDM	N/A	Pass
May 04, 2016	3650	Body	2450	2.015	51.580	Pass	Pass	Pass	OFDM	N/A	Pass
May 18, 2016	3864	Body	2450	1.966	52.164	Pass	Pass	Pass	OFDM	N/A	Pass
May 20, 2016	3864	Body	2450	2.012	51.434	Pass	Pass	Pass	OFDM	N/A	Pass
Jun. 16, 2016	3864	Body	2450	2.013	51.240	Pass	Pass	Pass	OFDM	N/A	Pass
May 04, 2016	3864	Body	5300	5.561	48.020	Pass	Pass	Pass	OFDM	N/A	Pass
May 19, 2016	3864	Body	5300	5.521	46.985	Pass	Pass	Pass	OFDM	N/A	Pass
Jun. 22, 2016	7350	Body	5300	5.430	47.965	Pass	Pass	Pass	OFDM	N/A	Pass
May 05, 2016	3650	Body	5600	5.971	47.139	Pass	Pass	Pass	OFDM	N/A	Pass
May 19, 2016	3864	Body	5600	5.928	46.687	Pass	Pass	Pass	OFDM	N/A	Pass
May 05, 2016	3650	Body	5800	6.268	46.705	Pass	Pass	Pass	OFDM	N/A	Pass
May 19, 2016	3864	Body	5800	6.240	46.245	Pass	Pass	Pass	OFDM	N/A	Pass
Jun. 15, 2016	3650	Body	5800	6.181	46.557	Pass	Pass	Pass	OFDM	N/A	Pass
Jun. 22, 2016	7350	Body	5800	6.073	47.228	Pass	Pass	Pass	OFDM	N/A	Pass

#### 4.5 System Verification

The measuring result for system verification is tabulated as below.

Test Date	Mode	Frequency (MHz)	1W Target SAR-1g (W/kg)	Measured SAR-1g (W/kg)	Normalized to 1W SAR-1g (W/kg)	Deviation (%)	Dipole S/N	Probe S/N	DAE S/N
May 03, 2016	Body	2450	51.10	12.40	49.60	-2.94	737	3650	1277
May 04, 2016	Body	2450	51.10	12.70	50.80	-0.59	737	3650	1277
May 18, 2016	Body	2450	51.10	11.80	47.20	-7.63	737	3864	579
May 20, 2016	Body	2450	51.10	12.40	49.60	-2.94	737	3864	579
Jun. 16, 2016	Body	2450	51.10	12.70	50.80	-0.59	737	3864	579
May 04, 2016	Body	5300	76.60	7.73	77.30	0.91	1019	3864	579
May 19, 2016	Body	5300	76.60	7.77	77.70	1.44	1019	3864	579
Jun. 22, 2016	Body	5300	76.60	7.64	76.40	-0.26	1019	7350	1305
May 05, 2016	Body	5600	79.80	8.05	80.50	0.88	1019	3650	1277
May 19, 2016	Body	5600	79.80	8.00	80.00	0.25	1019	3864	579
May 05, 2016	Body	5800	77.30	8.25	82.50	6.73	1019	3650	1277
May 19, 2016	Body	5800	77.30	7.92	79.20	2.46	1019	3864	579
Jun. 15, 2016	Body	5800	77.30	7.99	79.90	3.36	1019	3650	1277
Jun. 22, 2016	Body	5800	77.30	8.05	80.50	4.14	1019	7350	1305

**Note:**

Comparing to the reference SAR value provided by SPEAG, the validation data should be within its specification of 10 %. The result indicates the system check can meet the variation criterion and the plots can be referred to Appendix A of this report.

## 4.6 Maximum Output Power

### 4.6.1 Maximum Conducted Power

The maximum conducted average power (Unit: dBm) including tune-up tolerance is shown as below.

Mode	Ant.	802.11b	802.11g	802.11n HT20	802.11n HT40
2.4G WLAN	Ant-0	CH 1-10: 18.0 CH 11: 17.0	CH 1: 17.0 CH 2-10: 18.0 CH 11:16.0	CH 1: 17.0 CH 2-10: 17.5 CH 11:16.0	CH 3: 11.5 CH 4-8: 17.5 CH 9: 10.5
		CH 1-10: 18.0 CH 11: 17.0	CH 1: 17.0 CH 2-10: 18.0 CH 11:16.0	CH 1: 17.0 CH 2-10: 17.5 CH 11:16.0	CH 3: 11.5 CH 4-8: 17.5 CH 9: 10.5
		<b>Ant0</b> CH 1-10: 18.0 CH 11: 17.0	<b>Ant0</b> CH 1: 17.0 CH 2-10: 18.0 CH 11:16.0	<b>Ant0</b> CH 1: 17.0 CH 2-10: 17.5 CH 11:16.0	<b>Ant0</b> CH 3: 11.5 CH 4-8: 17.5 CH 9: 10.5
	2Tx Ant-0 + Ant-1	<b>Ant1</b> CH 1-10: 18.0 CH 11: 17.0	<b>Ant1</b> CH 1: 17.0 CH 2-10: 18.0 CH 11:16.0	<b>Ant1</b> CH 1: 17.0 CH 2-10: 17.5 CH 11:16.0	<b>Ant1</b> CH 3: 11.5 CH 4-8: 17.5 CH 9: 10.5
		<b>Ant0+1</b> CH 1-10: 21.0 CH 11: 20.0	<b>Ant0+1</b> CH 1: 20.0 CH 2-10: 21.0 CH 11:19.0	<b>Ant0+1</b> CH 1: 20.0 CH 2-10: 20.5 CH 11:19.0	<b>Ant0+1</b> CH 3: 14.5 CH 4-8: 20.5 CH 9: 13.5

BUREAU  
VERITAS

## FCC SAR Test Report

Mode	Ant.	802.11a	802.11n HT20	802.11n HT40	802.11ac VHT80
5.2G WLAN	Ant-0	15.0	15.0	15.0	14.0
	Ant-1	15.0	15.0	15.0	14.0
	Ant-0 + Ant-1	<b>Ant0</b> 15.0 <b>Ant1</b> 15.0 <b>Ant0+1</b> 18.0	<b>Ant0</b> 15.0 <b>Ant1</b> 15.0 <b>Ant0+1</b> 18.0	<b>Ant0</b> 15.0 <b>Ant1</b> 15.0 <b>Ant0+1</b> 18.0	<b>Ant0</b> 14.0 <b>Ant1</b> 14.0 <b>Ant0+1</b> 17.0
5.3G WLAN	Ant-0	17.0	17.0	CH 54: 17.0 CH 62: 16.5	14.0
	Ant-1	17.0	17.0	CH 54: 17.0 CH 62: 16.5	14.0
	Ant-0 + Ant-1	<b>Ant0</b> 17.0 <b>Ant1</b> 17.0 <b>Ant0+1</b> 20.0	<b>Ant0</b> 17.0 <b>Ant1</b> 17.0 <b>Ant0+1</b> 20.0	<b>Ant0</b> CH 54: 17.0 CH 62: 16.5 <b>Ant1</b> CH 54: 17.0 CH 62: 16.5 <b>Ant0+1</b> CH 54: 20.0 CH 62: 19.5	<b>Ant0</b> 14.0 <b>Ant1</b> 14.0 <b>Ant0+1</b> 17.0
5.6G WLAN	Ant-0	CH 100-136: 17.0 CH 140: 16.5 CH 144:17.0	CH 100-136: 17.0 CH 140: 16.0 CH 144:17.0	CH 102: 13.0 CH 110-142: 17.0	CH 106: 14.5 CH 122-138: 16.5
	Ant-1	CH 100-136: 17.0 CH 140: 16.5 CH 144:17.0	CH 100-136: 17.0 CH 140: 16.0 CH 144:17.0	CH 102: 13.0 CH 110-142: 17.0	CH 106: 14.5 CH 122-138: 16.5
	Ant-0 + Ant-1	<b>Ant0</b> CH 100-136: 17.0 CH 140: 16.5 CH 144:17.0 <b>Ant1</b> CH 100-136: 17.0 CH 140: 16.5 CH 144:17.0 <b>Ant0+1</b> CH 100-136: 20.0 CH 140: 19.5 CH 144:20.0	<b>Ant0</b> CH 100-136: 17.0 CH 140: 16.0 CH 144:17.0 <b>Ant1</b> CH 100-136: 17.0 CH 140: 16.0 CH 144:17.0 <b>Ant0+1</b> CH 100-136: 20.0 CH 140: 19.0 CH 144: 20.0	<b>Ant0</b> CH 102: 13.0 CH 110-142: 17.0 <b>Ant1</b> CH 102: 13.0 CH 110-142: 17.0 <b>Ant0+1</b> CH 102: 16.0 CH 110-142: 20.0	<b>Ant0</b> CH 106: 14.5 CH 122-138: 16.5 <b>Ant1</b> CH 106: 14.5 CH 122-138: 16.5 <b>Ant0+1</b> CH 106: 17.5 CH 122-138: 19.5



BUREAU  
VERITAS

## FCC SAR Test Report

Mode	Ant.	802.11a	802.11n HT20	802.11n HT40	802.11ac VHT80
5.8G WLAN	Ant-0	17.0	17.0	CH 151: 14.5 CH 159: 17.0	14.0
	Ant-1	17.0	17.0	CH 151: 14.5 CH 159: 17.0	14.0
	Ant-0 + Ant-1	<b>Ant0</b> 17.0 <b>Ant1</b> 17.0 <b>Ant0+1</b> 20.0	<b>Ant0</b> 17.0 <b>Ant1</b> 17.0 <b>Ant0+1</b> 20.0	<b>Ant0</b> CH 151: 14.5 CH 159: 17.0 <b>Ant1</b> CH 151: 14.5 CH 159: 17.0 <b>Ant0+1</b> CH 151: 17.5 CH 159: 20.0	<b>Ant0</b> 14.0 <b>Ant1</b> 14.0 <b>Ant0+1</b> 17.0

Mode	2.4G Bluetooth
Bluetooth DH	7.0

## FCC SAR Test Report

### 4.6.2 Measured Conducted Power Result

The measuring conducted average power (Unit: dBm) is shown as below.

#### <WLAN 2.4G>

Mode	802.11b		
Channel / Frequency (MHz)	1 (2412)	6 (2437)	11 (2462)
Average Power (Ant-0)	17.79	17.83	15.92
Average Power (Ant-1)	17.62	17.87	16.98
2Tx Average Power (Ant-0)	17.53	17.61	15.51
2Tx Average Power (Ant-1)	17.57	17.78	15.61
2Tx Average Power (Ant-0 + Ant-1)	20.56	20.71	18.57

#### <WLAN 5.3G>

Mode	802.11n (HT40)	
Channel / Frequency (MHz)	54 (5270)	62 (5310)
Average Power (Ant-0)	16.59	16.32
Average Power (Ant-1)	16.65	16.46
2Tx Average Power (Ant-0)	16.82	15.44
2Tx Average Power (Ant-1)	16.58	14.51
2Tx Average Power (Ant-0 + Ant-1)	19.71	18.01

#### <WLAN 5.6G>

Mode	802.11n (HT40)					
Channel / Frequency (MHz)	102 (5510)	110 (5550)	118 (5590)	126 (5630)	134 (5670)	142 (5710)
Average Power (Ant-0)	12.91	16.23	16.68	16.38	16.63	16.49
Average Power (Ant-1)	12.93	16.56	16.89	16.12	15.95	16.11
2Tx Average Power (Ant-0)	11.02	16.73	16.94	16.12	15.62	16.39
2Tx Average Power (Ant-1)	11.14	16.98	16.85	16.33	15.67	15.94
2Tx Average Power (Ant-0 + Ant-1)	14.09	19.87	19.91	19.24	18.66	19.18

#### <WLAN 5.8G>

Mode	802.11n (HT40)		
Channel / Frequency (MHz)	151 (5755)	159 (5795)	
Average Power (Ant-0)	14.45	16.79	
Average Power (Ant-1)	14.47	16.54	
2Tx Average Power (Ant-0)	13.82	16.65	
2Tx Average Power (Ant-1)	14.00	16.70	
2Tx Average Power (Ant-0 + Ant-1)	16.92	19.69	

#### <Bluetooth>

Mode	Bluetooth		
Channel / Frequency (MHz)	0 (2402)	39 (2441)	78 (2480)
Average Power	6.00	6.13	6.48

### **4.7 SAR Testing Results**

#### **4.7.1 SAR Test Reduction Considerations**

##### **<KDB 447498 D01, General RF Exposure Guidance>**

Testing of other required channels within the operating mode of a frequency band is not required when the reported SAR for the mid-band or highest output power channel is:

- (1)  $\leq 0.8 \text{ W/kg}$  or  $2.0 \text{ W/kg}$ , for 1-g or 10-g respectively, when the transmission band is  $\leq 100 \text{ MHz}$
- (2)  $\leq 0.6 \text{ W/kg}$  or  $1.5 \text{ W/kg}$ , for 1-g or 10-g respectively, when the transmission band is between  $100 \text{ MHz}$  and  $200 \text{ MHz}$
- (3)  $\leq 0.4 \text{ W/kg}$  or  $1.0 \text{ W/kg}$ , for 1-g or 10-g respectively, when the transmission band is  $\geq 200 \text{ MHz}$

##### **<KDB 248227 D01, SAR Guidance for Wi-Fi Transmitters>**

- (1) For handsets operating next to ear, hotspot mode or mini-tablet configurations, the initial test position procedures were applied. The test position with the highest extrapolated peak SAR will be used as the initial test position. When the reported SAR of initial test position is  $\leq 0.4 \text{ W/kg}$ , SAR testing for remaining test positions is not required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is  $\leq 0.8 \text{ W/kg}$  or all test positions are measured.
- (2) For WLAN 2.4 GHz, the highest measured maximum output power channel for DSSS was selected for SAR measurement. When the reported SAR is  $\leq 0.8 \text{ W/kg}$ , no further SAR testing is required. Otherwise, SAR is evaluated at the next highest measured output power channel. When any reported SAR is  $> 1.2 \text{ W/kg}$ , SAR is required for the third channel. For OFDM modes (802.11g/n), SAR is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and it is  $\leq 1.2 \text{ W/kg}$ .
- (3) For WLAN 5 GHz, the initial test configuration was selected according to the transmission mode with the highest maximum output power. When the reported SAR of initial test configuration is  $> 0.8 \text{ W/kg}$ , SAR is required for the subsequent highest measured output power channel until the reported SAR result is  $\leq 1.2 \text{ W/kg}$  or all required channels are measured. For other transmission modes, SAR is not required when the highest reported SAR for initial test configuration is adjusted by the ratio of subsequent test configuration to initial test configuration specified maximum output power and it is  $\leq 1.2 \text{ W/kg}$ .
- (4) For WLAN MIMO mode, the power-based standalone SAR test exclusion or the sum of SAR provision in KDB 447498 to determine simultaneous transmission SAR test exclusion should be applied. Otherwise, SAR for MIMO mode will be measured with all applicable antennas transmitting simultaneously at the specified maximum output power of MIMO operation.

## FCC SAR Test Report

### 4.7.2 SAR Results for Body Exposure Condition (Separation Distance is 0 cm Gap)

#### EUT 1:

Plot No.	Band	Mode	Test Position	Ch.	Tx Antenna	Battery	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)	
	2.4G WLAN	802.11b	Bottom Side	6	0	1	18.0	17.83	1.04	-0.1	0.465	0.48	
01	2.4G WLAN	802.11b	Bottom Side	6	1	1	18.0	17.87	1.03	0	0.967	1.00	
	2.4G WLAN	802.11b	Bottom Side	6	1	1	18.0	17.87	1.03	0	0.958	0.99	
	2.4G WLAN	802.11b	Bottom Side	1	1	1	18.0	17.62	1.09	0.06	0.890	0.97	
	2.4G WLAN	802.11b	Bottom Side	6	2TX	1	18.0	17.61	1.09	0	0.380	0.42	
	2.4G WLAN	802.11b	Bottom Side				18.0	17.78	1.05		0.627	0.66	
	2.4G WLAN	802.11b	Bottom Side	6	1	2	18.0	17.87	1.03	0	0.642	0.66	
	5.3G WLAN	802.11ac VHT40	Bottom Side	54	0	1	17.0	16.59	1.10	0	0.219	0.24	
02	5.3G WLAN	802.11ac VHT40	Bottom Side	54	1	1	17.0	16.65	1.08	0	1.05	1.14	
	5.3G WLAN	802.11ac VHT40	Bottom Side	54	1	1	17.0	16.65	1.08	0.01	0.99	1.07	
	5.3G WLAN	802.11ac VHT40	Bottom Side	62	1	1	16.5	16.46	1.01	0.05	0.92	0.93	
	5.3G WLAN	802.11ac VHT40	Bottom Side	54	2TX	0	1	17.0	16.58	1.10	0.01	0.982	1.08
	5.3G WLAN	802.11ac VHT40	Bottom Side	62	2TX	0	1	16.5	14.51	1.58	0	0.713	1.13
	5.3G WLAN	802.11ac VHT40	Bottom Side	54	1	2	17.0	16.65	1.08	0.01	0.673	0.73	
	5.6G WLAN	802.11ac VHT40	Bottom Side	118	0	1	17.0	16.68	1.08	0.06	0.573	0.62	
	5.6G WLAN	802.11ac VHT40	Bottom Side	118	1	1	17.0	16.89	1.03	0.01	1.08	1.11	
	5.6G WLAN	802.11ac VHT40	Bottom Side	110	1	1	17.0	16.56	1.11	0.05	1.03	1.14	
	5.6G WLAN	802.11ac VHT40	Bottom Side	118	2TX	0	17.0	16.94	1.01	0	0.57	0.58	
	5.6G WLAN	802.11ac VHT40	Bottom Side				17.0	16.85	1.04		1.02	1.06	
03	5.6G WLAN	802.11ac VHT40	Bottom Side	110	2TX	1	1	17.0	16.98	1.00	0.01	1.15	1.16
	5.6G WLAN	802.11ac VHT40	Bottom Side	110	2TX	1	1	17.0	16.98	1.00	0	1.08	1.08
	5.6G WLAN	802.11ac VHT40	Bottom Side	110	2TX	0	17.0	16.73	1.06	0	0.592	0.63	
	5.6G WLAN	802.11ac VHT40	Bottom Side				17.0	16.98	1.00		1.02	1.02	
	5.6G WLAN	802.11ac VHT40	Bottom Side	118	2TX	1	2	17.0	16.85	1.04	0	1.09	1.13
	5.8G WLAN	802.11ac VHT40	Bottom Side	159	0	1	17.0	16.79	1.05	0	0.685	0.72	
04	5.8G WLAN	802.11ac VHT40	Bottom Side	159	1	1	17.0	16.54	1.11	0	0.970	1.08	
	5.8G WLAN	802.11ac VHT40	Bottom Side	159	1	1	17.0	16.54	1.11	0.03	0.964	1.07	
	5.8G WLAN	802.11ac VHT40	Bottom Side	151	1	1	14.5	14.47	1.01	0.01	0.485	0.49	
	5.8G WLAN	802.11ac VHT40	Bottom Side	159	2TX	1	1	17.0	16.70	1.07	0	0.961	1.03
	5.8G WLAN	802.11ac VHT40	Bottom Side	151	2TX	1	1	14.5	14.00	1.12	-0.03	0.431	0.48
	5.8G WLAN	802.11ac VHT40	Bottom Side	159	1	2	17.0	16.54	1.11	0.01	0.740	0.82	
	5.8G WLAN	802.11ac VHT40	Bottom Side	151	1	2	14.5	14.47	1.01	-0.07	0.376	0.38	
	Bluetooth	DH1	Bottom Side	78	0	1	7.0	6.48	1.13	0	0.00396	0.00	
05	Bluetooth	DH1	Bottom Side	78	0	2	7.0	6.48	1.13	0	0.00407	0.00	

**FCC SAR Test Report**
**EUT 2:**

Plot No.	Band	Mode	Test Position	Ch.	Tx Antenna	Battery	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
06	2.4G WLAN	802.11b	Bottom Side	6	0	1	18.0	17.83	1.04	0.04	1.06	<b>1.10</b>
	2.4G WLAN	802.11b	Bottom Side	6	0	1	18.0	17.83	1.04	0	1.03	1.07
	2.4G WLAN	802.11b	Bottom Side	1	0	1	18.0	17.79	1.05	0.01	0.967	1.01
	2.4G WLAN	802.11b	Bottom Side	6	1	1	18.0	17.87	1.03	0	1.04	1.07
	2.4G WLAN	802.11b	Bottom Side	1	1	1	18.0	17.62	1.09	0	0.792	0.86
	2.4G WLAN	802.11b	Bottom Side	6	2TX	0	18.0	17.61	1.09	0	0.709	0.78
	2.4G WLAN	802.11b	Bottom Side			1						
	2.4G WLAN	802.11b	Bottom Side	6	0	2	18.0	17.83	1.04	0.01	0.503	0.52
07	5.3G WLAN	802.11ac VHT40	Bottom Side	54	0	1	17.0	16.59	1.10	0	1.05	<b>1.15</b>
	5.3G WLAN	802.11ac VHT40	Bottom Side	54	0	1	17.0	16.59	1.10	0.01	1.03	1.13
	5.3G WLAN	802.11ac VHT40	Bottom Side	62	0	1	16.5	16.32	1.04	0	0.920	0.96
	5.3G WLAN	802.11ac VHT40	Bottom Side	54	1	1	17.0	16.65	1.08	0.01	0.874	0.95
	5.3G WLAN	802.11ac VHT40	Bottom Side	62	1	1	16.5	16.46	1.01	0	0.638	0.64
	5.3G WLAN	802.11ac VHT40	Bottom Side	54	2TX	0	17.0	16.82	1.04	0	1.04	1.08
	5.3G WLAN	802.11ac VHT40	Bottom Side			1						
	5.3G WLAN	802.11ac VHT40	Bottom Side	62	2TX	0	16.5	15.44	1.28	0.15	0.837	1.07
	5.3G WLAN	802.11ac VHT40	Bottom Side	54	0	2	17.0	16.59	1.10	0	0.709	0.78
	5.6G WLAN	802.11ac VHT40	Bottom Side	118	0	1	17.0	16.68	1.08	-0.02	1.05	1.13
	5.6G WLAN	802.11ac VHT40	Bottom Side	118	0	1	17.0	16.68	1.08	0	1.01	1.09
	5.6G WLAN	802.11ac VHT40	Bottom Side	134	0	1	17.0	16.63	1.09	0	0.671	0.73
	5.6G WLAN	802.11ac VHT40	Bottom Side	118	1	1	17.0	16.89	1.03	0.05	0.917	0.94
	5.6G WLAN	802.11ac VHT40	Bottom Side	110	1	1	17.0	16.56	1.11	0	0.761	0.84
	5.6G WLAN	802.11ac VHT40	Bottom Side	118	2TX	1	17.0	16.85	1.04	0.01	0.902	0.93
08	5.6G WLAN	802.11ac VHT40	Bottom Side	110	2TX	0	17.0	16.73	1.06	0.01	1.09	<b>1.16</b>
	5.6G WLAN	802.11ac VHT40	Bottom Side			1						
	5.6G WLAN	802.11ac VHT40	Bottom Side	110	2TX	0	17.0	16.73	1.06	-0.03	1.03	1.1
	5.6G WLAN	802.11ac VHT40	Bottom Side			1						
	5.6G WLAN	802.11ac VHT40	Bottom Side	110	2TX	0	17.0	16.73	1.06	0.04	0.647	0.69
	5.6G WLAN	802.11ac VHT40	Bottom Side			1						
	5.8G WLAN	802.11ac VHT40	Bottom Side	159	0	1	17.0	16.79	1.05	0.01	0.683	0.72
09	5.8G WLAN	802.11ac VHT40	Bottom Side	159	1	1	17.0	16.54	1.11	0.03	0.862	<b>0.96</b>
	5.8G WLAN	802.11ac VHT40	Bottom Side	151	1	1	14.5	14.47	1.01	0.02	0.432	0.43
	5.8G WLAN	802.11ac VHT40	Bottom Side	159	2TX	0	17.0	16.65	1.08	-0.11	0.533	0.58
	5.8G WLAN	802.11ac VHT40	Bottom Side			1						
	5.8G WLAN	802.11ac VHT40	Bottom Side	159	2TX	0	17.0	16.70	1.07	-0.14	0.871	0.93
	5.8G WLAN	802.11ac VHT40	Bottom Side			1						
	5.8G WLAN	802.11ac VHT40	Bottom Side	151	2TX	0	14.5	16.65	1.08	0.03	0.528	0.57
	5.8G WLAN	802.11ac VHT40	Bottom Side			1						
	5.8G WLAN	802.11ac VHT40	Bottom Side	159	2TX	0	14.5	13.82	1.17	0	0.460	0.54
	5.8G WLAN	802.11ac VHT40	Bottom Side			1						
	5.8G WLAN	802.11ac VHT40	Bottom Side	159	1	2	17.0	16.54	1.11	0	0.840	0.93
	5.8G WLAN	802.11ac VHT40	Bottom Side	151	1	2	14.5	14.47	1.01	0.01	0.406	0.41
10	Bluetooth	DH1	Bottom Side	78	0	1	7.0	6.48	1.13	0	0.00541	<b>0.01</b>
	Bluetooth	DH1	Bottom Side	78	0	2	7.0	6.48	1.13	0	0.00512	0.01

#### 4.7.3 SAR Measurement Variability

According to KDB 865664 D01, SAR measurement variability was assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. Alternatively, if the highest measured SAR for both head and body tissue-equivalent media are  $\leq 1.45$  W/kg and the ratio of these highest SAR values, i.e., largest divided by smallest value, is  $\leq 1.10$ , the highest SAR configuration for either head or body tissue-equivalent medium may be used to perform the repeated measurement. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR repeated measurement procedure:

1. When the highest measured SAR is  $< 0.80$  W/kg, repeated measurement is not required.
2. When the highest measured SAR is  $\geq 0.80$  W/kg, repeat that measurement once.
3. If the ratio of largest to smallest SAR for the original and first repeated measurements is  $> 1.20$ , or when the original or repeated measurement is  $\geq 1.45$  W/kg, perform a second repeated measurement.
4. If the ratio of largest to smallest SAR for the original, first and second repeated measurements is  $> 1.20$ , and the original, first or second repeated measurement is  $\geq 1.5$  W/kg, perform a third repeated measurement.

#### EUT 1:

Band	Mode	Test Position	Ch.	Original Measured SAR-1g (W/kg)	1st Repeated SAR-1g (W/kg)	L/S Ratio	2nd Repeated SAR-1g (W/kg)	L/S Ratio	3rd Repeated SAR-1g (W/kg)	L/S Ratio
2.4G WLAN	802.11b	Bottom Side	6	0.967	0.958	1.01	N/A	N/A	N/A	N/A
5.3G WLAN	802.11ac VHT40	Bottom Side	54	1.05	0.99	1.06	N/A	N/A	N/A	N/A
5.6G WLAN	802.11ac VHT40	Bottom Side	110	1.15	1.08	1.06	N/A	N/A	N/A	N/A
5.8G WLAN	802.11ac VHT40	Bottom Side	159	0.97	0.964	1.01	N/A	N/A	N/A	N/A

#### EUT 2:

Band	Mode	Test Position	Ch.	Original Measured SAR-1g (W/kg)	1st Repeated SAR-1g (W/kg)	L/S Ratio	2nd Repeated SAR-1g (W/kg)	L/S Ratio	3rd Repeated SAR-1g (W/kg)	L/S Ratio
2.4G WLAN	802.11b	Bottom Side	6	1.06	1.03	1.03	N/A	N/A	N/A	N/A
5.3G WLAN	802.11ac VHT40	Bottom Side	54	1.05	1.03	1.02	N/A	N/A	N/A	N/A
5.6G WLAN	802.11ac VHT40	Bottom Side	110	1.09	1.03	1.06	N/A	N/A	N/A	N/A
5.8G WLAN	802.11ac VHT40	Bottom Side	159	0.871	0.863	1.01	N/A	N/A	N/A	N/A

**<SAR Summation Analysis>**

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. When the sum of  $SAR_{1g}$  of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit ( $SAR_{1g}$  1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of  $SAR_{1g}$  is greater than the SAR limit ( $SAR_{1g}$  1.6 W/kg), SAR test exclusion is determined by the SPLSR.

No.	EUT Config.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	SAR Summation	SPLSR Analysis
1	EUT 1	WLAN (DTS) + BT (DSS)	Body	Bottom Side	1.00	0.00	1.00	$\Sigma$ SAR < 1.6, Not required
2	EUT 1	WLAN (NII) + BT (DSS)	Body	Bottom Side	1.16	0.00	1.16	$\Sigma$ SAR < 1.6, Not required
3	EUT 2	WLAN (DTS) + BT (DSS)	Body	Bottom Side	1.10	0.01	1.11	$\Sigma$ SAR < 1.6, Not required
4	EUT 2	WLAN (NII) + BT (DSS)	Body	Bottom Side	1.16	0.01	1.17	$\Sigma$ SAR < 1.6, Not required

**Test Engineer :** Willy Chang, and Kevin Yao

## 5. Calibration of Test Equipment

Equipment	Manufacturer	Model	SN	Cal. Date	Cal. Interval
System Validation Dipole	SPEAG	D2450V2	737	Aug. 20, 2015	1 Year
System Validation Dipole	SPEAG	D5GHzV2	1019	Aug. 28, 2015	1 Year
Dosimetric E-Field Probe	SPEAG	EX3DV4	3650	Jul. 23, 2015	1 Year
Dosimetric E-Field Probe	SPEAG	EX3DV4	3864	Jul. 23, 2015	1 Year
Dosimetric E-Field Probe	SPEAG	EX3DV4	7350	Dec. 17, 2015	1 Year
Data Acquisition Electronics	SPEAG	DAE3	579	Aug. 24, 2015	1 Year
Data Acquisition Electronics	SPEAG	DAE4	1277	Jul. 22, 2015	1 Year
Data Acquisition Electronics	SPEAG	DAE4	1305	Dec. 11, 2015	1 Year
Spectrum Analyzer	R&S	FSL6	102006	Mar. 25, 2016	1 Year
MXG Analog Signal Generator	Agilent	N5181A	MY50143868	Jul. 06, 2015	1 Year
Power Meter	Anritsu	ML2495A	1218009	Jul. 06, 2015	1 Year
Power Sensor	Anritsu	MA2411B	1207252	Jul. 06, 2015	1 Year
Thermometer	YFE	YF-160A	130504579	Aug. 20, 2015	1 Year

## 6. Measurement Uncertainty

Source of Uncertainty	Tolerance (± %)	Probability Distribution	Divisor	Ci (1g)	Ci (10g)	Standard Uncertainty (± %, 1g)	Standard Uncertainty (± %, 10g)	Vi
<b>Measurement System</b>								
Probe Calibration	6.0	Normal	1	1	1	6.0	6.0	$\infty$
Axial Isotropy	4.7	Rectangular	$\sqrt{3}$	0.707	0.707	1.9	1.9	$\infty$
Hemispherical Isotropy	9.6	Rectangular	$\sqrt{3}$	0.707	0.707	3.9	3.9	$\infty$
Boundary Effect	1.0	Rectangular	$\sqrt{3}$	1	1	0.6	0.6	$\infty$
Linearity	4.7	Rectangular	$\sqrt{3}$	1	1	2.7	2.7	$\infty$
System Detection Limits	0.25	Rectangular	$\sqrt{3}$	1	1	0.14	0.14	$\infty$
Readout Electronics	0.3	Normal	1	1	1	0.3	0.3	$\infty$
Response Time	0.0	Rectangular	$\sqrt{3}$	1	1	0.0	0.0	$\infty$
Integration Time	1.7	Rectangular	$\sqrt{3}$	1	1	1.0	1.0	$\infty$
RF Ambient Conditions - Noise	3.0	Rectangular	$\sqrt{3}$	1	1	1.7	1.7	$\infty$
RF Ambient Conditions - Reflections	3.0	Rectangular	$\sqrt{3}$	1	1	1.7	1.7	$\infty$
Probe Positioner Mechanical Tolerance	0.4	Rectangular	$\sqrt{3}$	1	1	0.2	0.2	$\infty$
Probe Positioning with Respect to Phantom Shell	2.9	Rectangular	$\sqrt{3}$	1	1	1.7	1.7	$\infty$
Extrapolation, interpolation, and integration algorithms for max. SAR evaluation	2.0	Rectangular	$\sqrt{3}$	1	1	1.2	1.2	$\infty$
<b>Test Sample Related</b>								
Test Sample Positioning	1.5 / 0.7	Normal	1	1	1	1.5	0.7	32
Device Holder Uncertainty	4.2 / 1.8	Normal	1	1	1	4.2	1.8	32
Output Power Variation - SAR Drift Measurement	5.0	Rectangular	$\sqrt{3}$	1	1	2.9	2.9	$\infty$
<b>Phantom and Tissue Parameters</b>								
Phantom Uncertainty (Shape and Thickness Tolerances)	7.2	Rectangular	$\sqrt{3}$	1	1	4.2	4.2	$\infty$
Liquid Conductivity - Deviation from Target Values	5.0	Rectangular	$\sqrt{3}$	0.64	0.43	1.8	1.2	$\infty$
Liquid Conductivity - Measurement Uncertainty	1.0	Normal	1	0.64	0.43	0.6	0.4	25
Liquid Permittivity - Deviation from Target Values	5.0	Rectangular	$\sqrt{3}$	0.60	0.49	1.7	1.4	$\infty$
Liquid Permittivity - Measurement Uncertainty	0.5	Normal	1	0.60	0.49	0.3	0.2	25
<b>Combined Standard Uncertainty</b>							$\pm 11.2\%$	$\pm 10.4\%$
<b>Expanded Uncertainty (K=2)</b>							$\pm 22.4\%$	$\pm 20.8\%$

### Uncertainty budget for frequency range 300 MHz to 3 GHz

**FCC SAR Test Report**

Source of Uncertainty	Tolerance ( $\pm$ %)	Probability Distribution	Divisor	Ci (1g)	Ci (10g)	Standard Uncertainty ( $\pm$ %, 1g)	Standard Uncertainty ( $\pm$ %, 10g)	Vi
<b>Measurement System</b>								
Probe Calibration	6.55	Normal	1	1	1	6.55	6.55	$\infty$
Axial Isotropy	4.7	Rectangular	$\sqrt{3}$	0.707	0.707	1.9	1.9	$\infty$
Hemispherical Isotropy	9.6	Rectangular	$\sqrt{3}$	0.707	0.707	3.9	3.9	$\infty$
Boundary Effect	2.0	Rectangular	$\sqrt{3}$	1	1	1.2	1.2	$\infty$
Linearity	4.7	Rectangular	$\sqrt{3}$	1	1	2.7	2.7	$\infty$
System Detection Limits	0.25	Rectangular	$\sqrt{3}$	1	1	0.14	0.14	$\infty$
Readout Electronics	0.3	Normal	1	1	1	0.3	0.3	$\infty$
Response Time	0.0	Rectangular	$\sqrt{3}$	1	1	0.0	0.0	$\infty$
Integration Time	1.7	Rectangular	$\sqrt{3}$	1	1	1.0	1.0	$\infty$
RF Ambient Conditions - Noise	3.0	Rectangular	$\sqrt{3}$	1	1	1.7	1.7	$\infty$
RF Ambient Conditions - Reflections	3.0	Rectangular	$\sqrt{3}$	1	1	1.7	1.7	$\infty$
Probe Positioner Mechanical Tolerance	0.4	Rectangular	$\sqrt{3}$	1	1	0.2	0.2	$\infty$
Probe Positioning with Respect to Phantom Shell	6.7	Rectangular	$\sqrt{3}$	1	1	3.9	3.9	$\infty$
Extrapolation, interpolation, and integration algorithms for max. SAR evaluation	4.0	Rectangular	$\sqrt{3}$	1	1	2.3	2.3	$\infty$
<b>Test Sample Related</b>								
Test Sample Positioning	1.5 / 0.7	Normal	1	1	1	1.5	0.7	32
Device Holder Uncertainty	4.2 / 1.8	Normal	1	1	1	4.2	1.8	32
Output Power Variation - SAR Drift Measurement	5.0	Rectangular	$\sqrt{3}$	1	1	2.9	2.9	$\infty$
<b>Phantom and Tissue Parameters</b>								
Phantom Uncertainty (Shape and Thickness Tolerances)	7.6	Rectangular	$\sqrt{3}$	1	1	4.4	4.4	$\infty$
Liquid Conductivity - Deviation from Target Values	5.0	Rectangular	$\sqrt{3}$	0.64	0.43	1.8	1.2	$\infty$
Liquid Conductivity - Measurement Uncertainty	1.0	Normal	1	0.64	0.43	0.6	0.4	25
Liquid Permittivity - Deviation from Target Values	5.0	Rectangular	$\sqrt{3}$	0.60	0.49	1.7	1.4	$\infty$
Liquid Permittivity - Measurement Uncertainty	0.5	Normal	1	0.60	0.49	0.3	0.2	25
<b>Combined Standard Uncertainty</b>							$\pm 12.3\%$	$\pm 11.5\%$
<b>Expanded Uncertainty (K=2)</b>							$\pm 24.6\%$	$\pm 23.0\%$

**Uncertainty budget for frequency range 3 GHz to 6 GHz**

## 7. Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Taiwan HwaYa EMC/RF/Safety/Telecom Lab:**

Add: No. 19, Hwa Ya 2nd Rd, Wen Hwa Vil., Kwei Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-318-3232

Fax: 886-3-327-0892

**Taiwan LinKo EMC/RF Lab:**

Add: No. 47-2, 14th Ling, Chia Pau Vil., Linkou Dist., New Taipei City 244, Taiwan, R.O.C.

Tel: 886-2-2605-2180

Fax: 886-2-2605-1924

**Taiwan HsinChu EMC/RF Lab:**

Add: No. 81-1, Lu Liao Keng, 9<sup>th</sup> Ling, Wu Lung Vil., Chiung Lin Township, Hsinchu County 307, Taiwan, R.O.C.

Tel: 886-3-593-5343

Fax: 886-3-593-5342

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.adt.com.tw](http://www.adt.com.tw)

The road map of all our labs can be found in our web site also.

---END---



## Appendix A. SAR Plots of System Verification

The plots for system verification with largest deviation for each SAR system combination are shown as follows.

## System Check\_B2450\_160518

**DUT: Dipole 2450 MHz; Type: D2450V2; SN: 737**

Communication System: CW ; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: B19T27N3\_0518 Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.966$  S/m;  $\epsilon_r = 52.164$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 24.0 °C ; Liquid Temperature : 23.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3864; ConvF(7.3, 7.3, 7.3); Calibrated: 2015/07/23;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2015/08/24
- Phantom: ELI Phantom\_1039; Type: QDOVA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Pin=250mW/Area Scan (81x81x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 18.1 W/kg


**Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 97.45 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 24.2 W/kg

**SAR(1 g) = 11.8 W/kg; SAR(10 g) = 5.42 W/kg**

Maximum value of SAR (measured) = 18.1 W/kg



## System Check\_B5300\_160519

**DUT: Dipole 5 GHz; Type: D5GHzV2; SN: 1019**

Communication System: CW; Frequency: 5300 MHz; Duty Cycle: 1:1

Medium: B34T60N3\_0519 Medium parameters used:  $f = 5300$  MHz;  $\sigma = 5.521$  S/m;  $\epsilon_r = 46.985$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.8 °C ; Liquid Temperature : 23.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3864; ConvF(4.41, 4.41, 4.41); Calibrated: 2015/07/23;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2015/08/24
- Phantom: ELI Phantom\_1039; Type: QDOVA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Pin=100mW/Area Scan (91x91x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 18.3 W/kg


**Pin=100mW/Zoom Scan (7x7x12)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 58.00 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 30.8 W/kg

**SAR(1 g) = 7.77 W/kg; SAR(10 g) = 2.24 W/kg**

Maximum value of SAR (measured) = 19.3 W/kg



## System Check\_B5600\_160505

**DUT: Dipole 5 GHz; Type: D5GHzV2; SN: 1019**

Communication System: CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: B34T60N2\_0505 Medium parameters used:  $f = 5600$  MHz;  $\sigma = 5.971$  S/m;  $\epsilon_r = 47.139$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.7 °C ; Liquid Temperature : 23.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(4.05, 4.05, 4.05); Calibrated: 2015/07/23;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2015/07/22
- Phantom: ELI Phantom\_1204; Type: QDOVA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Pin=100mW/Area Scan (91x91x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 18.9 W/kg


**Pin=100mW/Zoom Scan (7x7x12)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 59.07 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 34.5 W/kg

**SAR(1 g) = 8.05 W/kg; SAR(10 g) = 2.28 W/kg**

Maximum value of SAR (measured) = 20.9 W/kg



## System Check\_B5800\_160505

**DUT: Dipole 5 GHz; Type: D5GHzV2; SN: 1019**

Communication System: CW; Frequency: 5800 MHz; Duty Cycle: 1:1

Medium: B34T60N2\_0505 Medium parameters used:  $f = 5800$  MHz;  $\sigma = 6.268$  S/m;  $\epsilon_r = 46.705$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.7 °C ; Liquid Temperature : 23.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(4.45, 4.45, 4.45); Calibrated: 2015/07/23;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2015/07/22
- Phantom: ELI Phantom\_1204; Type: QDOVA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Pin=100mW/Area Scan (91x91x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 16.4 W/kg


**Pin=100mW/Zoom Scan (7x7x12)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 57.89 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 36.2 W/kg

**SAR(1 g) = 8.25 W/kg; SAR(10 g) = 2.3 W/kg**

Maximum value of SAR (measured) = 18.0 W/kg





## Appendix B. SAR Plots of SAR Measurement

The SAR plots for highest measured SAR in each exposure configuration, wireless mode and frequency band combination, and measured SAR > 1.5 W/kg are shown as follows.

**P01 2.4GWLAN\_802.11b\_Bottom Side\_0cm\_Ch6\_Ant1****DUT: 150330C14**

Communication System: WLAN\_2.4G; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: B19T27N1\_0504 Medium parameters used:  $f = 2437$  MHz;  $\sigma = 2$  S/m;  $\epsilon_r = 51.617$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.8 °C ; Liquid Temperature : 23.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(7.03, 7.03, 7.03); Calibrated: 2015/07/23;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2015/07/22
- Phantom: ELI Phantom\_1204; Type: QDOVA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**- Area Scan (71x191x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 1.53 W/kg


**- Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 0 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 2.07 W/kg

**SAR(1 g) = 0.967 W/kg; SAR(10 g) = 0.466 W/kg**

Maximum value of SAR (measured) = 1.66 W/kg



**P02 5.3G WLAN\_802.11ac VHT40\_Bottom Side\_0cm\_Ch54\_Ant1****DUT: 150330C14**

Communication System: WLAN\_5G; Frequency: 5270 MHz; Duty Cycle: 1:1

Medium: B34T60N3\_0504 Medium parameters used:  $f = 5270$  MHz;  $\sigma = 5.535$  S/m;  $\epsilon_r = 48.122$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.5 °C ; Liquid Temperature : 23.2 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3864; ConvF(4.64, 4.64, 4.64); Calibrated: 2015/07/23;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2015/08/24
- Phantom: ELI Phantom\_1039; Type: QDOVA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**- Area Scan (101x241x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.37 W/kg


**- Zoom Scan (6x6x12)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=2mm

Reference Value = 0 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 4.22 W/kg

**SAR(1 g) = 1.05 W/kg; SAR(10 g) = 0.348 W/kg**

Maximum value of SAR (measured) = 2.34 W/kg



**P03 5.6GWLAN\_802.11ac VHT40\_Bottom Side\_0cm\_Ch110\_Ant0+1****DUT: 150330C14**

Communication System: WLAN\_5G; Frequency: 5550 MHz; Duty Cycle: 1:1

Medium: B34T60N3\_0519 Medium parameters used:  $f = 5550$  MHz;  $\sigma = 5.851$  S/m;  $\epsilon_r = 46.515$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.8 °C ; Liquid Temperature : 23.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3864; ConvF(3.93, 3.93, 3.93); Calibrated: 2015/07/23;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2015/08/24
- Phantom: ELI Phantom\_1039; Type: QDOVA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**- Area Scan (81x301x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 2.30 W/kg


**- Zoom Scan (6x6x12)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=2mm

Reference Value = 0 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 4.51 W/kg

**SAR(1 g) = 1.15 W/kg; SAR(10 g) = 0.408 W/kg**

Maximum value of SAR (measured) = 2.57 W/kg



**P04 5.8G WLAN\_802.11ac\_VHT40\_Bottom Side\_0cm\_Ch159\_Ant1****DUT: 150330C14**

Communication System: WLAN\_5G; Frequency: 5795 MHz; Duty Cycle: 1:1

Medium: B34T60N2\_0505 Medium parameters used:  $f = 5795$  MHz;  $\sigma = 6.257$  S/m;  $\epsilon_r = 46.695$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.7 °C ; Liquid Temperature : 23.4 °C

## DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(4.45, 4.45, 4.45); Calibrated: 2015/07/23;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2015/07/22
- Phantom: ELI Phantom\_1204; Type: QDOVA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**- Area Scan (81x221x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.31 W/kg


**- Zoom Scan (6x6x12)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=2mm

Reference Value = 0 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 3.99 W/kg

**SAR(1 g) = 0.970 W/kg; SAR(10 g) = 0.310 W/kg**

Maximum value of SAR (measured) = 2.25 W/kg



**P05 Bluetooth\_DH1\_Bottom Side\_0cm\_Ch78\_Ant0\_Battery2****DUT: 150330C14**

Communication System: BT; Frequency: 2480 MHz; Duty Cycle: 1:1.53

Medium: B19T27N3\_0520 Medium parameters used:  $f = 2480$  MHz;  $\sigma = 2.044$  S/m;  $\epsilon_r = 51.354$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.7 °C ; Liquid Temperature : 23.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3864; ConvF(7.3, 7.3, 7.3); Calibrated: 2015/07/23;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2015/08/24
- Phantom: ELI Phantom\_1039; Type: QDOVA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**- Area Scan (221x321x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.00799 W/kg

**- Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 0 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.0160 W/kg

**SAR(1 g) = 0.00407 W/kg; SAR(10 g) = 0.00112 W/kg**

Maximum value of SAR (measured) = 0.00878 W/kg



**P06 2.4G WLAN\_802.11b\_Bottom Side\_0cm\_Ch6\_Ant0****DUT: 150330C14**

Communication System: WLAN\_2.4G; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: B19T27N1\_0503 Medium parameters used:  $f = 2437$  MHz;  $\sigma = 2.003$  S/m;  $\epsilon_r = 51.331$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.9 °C ; Liquid Temperature : 23.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(7.03, 7.03, 7.03); Calibrated: 2015/07/23;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2015/07/22
- Phantom: ELI Phantom\_1204; Type: QDOVA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**- Area Scan (71x191x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 1.76 W/kg


**- Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 0.7860 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 2.23 W/kg

**SAR(1 g) = 1.06 W/kg; SAR(10 g) = 0.514 W/kg**

Maximum value of SAR (measured) = 1.81 W/kg



**P07 5.3G WLAN\_802.11ac VHT40\_Bottom Side\_0cm\_Ch54\_Ant0****DUT: 150330C14**

Communication System: WLAN\_5G; Frequency: 5270 MHz; Duty Cycle: 1:1

Medium: B34T60N3\_0504 Medium parameters used:  $f = 5270$  MHz;  $\sigma = 5.535$  S/m;  $\epsilon_r = 48.122$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.5 °C ; Liquid Temperature : 23.2 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3864; ConvF(4.64, 4.64, 4.64); Calibrated: 2015/07/23;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2015/08/24
- Phantom: ELI Phantom\_1039; Type: QDOVA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**- Area Scan (101x241x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.41 W/kg


**- Zoom Scan (6x6x12)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=2mm

Reference Value = 0 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 4.20 W/kg

**SAR(1 g) = 1.05 W/kg; SAR(10 g) = 0.357 W/kg**

Maximum value of SAR (measured) = 2.48 W/kg



**P08 5.6G WLAN\_802.11ac VHT40\_Bottom Side\_0cm\_Ch110\_Ant0+1****DUT: 150330C14**

Communication System: WLAN\_5G; Frequency: 5550 MHz; Duty Cycle: 1:1

Medium: B34T60N3\_0519 Medium parameters used:  $f = 5550$  MHz;  $\sigma = 5.851$  S/m;  $\epsilon_r = 46.515$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.8 °C ; Liquid Temperature : 23.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3864; ConvF(3.93, 3.93, 3.93); Calibrated: 2015/07/23;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2015/08/24
- Phantom: ELI Phantom\_1039; Type: QDOVA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**- Area Scan (101x221x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.65 W/kg

**- Zoom Scan (6x6x12)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=2mm

Reference Value = 0 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 4.50 W/kg

**SAR(1 g) = 1.09 W/kg; SAR(10 g) = 0.351 W/kg**

Maximum value of SAR (measured) = 2.62 W/kg


**- Zoom Scan (6x6x12)/Cube 1:** Measurement grid: dx=5mm, dy=5mm, dz=2mm

Reference Value = 0 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 3.97 W/kg

**SAR(1 g) = 0.956 W/kg; SAR(10 g) = 0.306 W/kg**

Maximum value of SAR (measured) = 2.14 W/kg



**P09 5.8G WLAN\_802.11ac\_VHT40\_Bottom Side\_0cm\_Ch159\_Ant1****DUT: 150330C14**

Communication System: WLAN\_5G; Frequency: 5795 MHz; Duty Cycle: 1:1

Medium: B34T60N2\_0505 Medium parameters used:  $f = 5795$  MHz;  $\sigma = 6.257$  S/m;  $\epsilon_r = 46.695$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.7 °C ; Liquid Temperature : 23.4 °C

## DASY5 Configuration:

- Probe: EX3DV4 - SN3650; ConvF(4.45, 4.45, 4.45); Calibrated: 2015/07/23;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1277; Calibrated: 2015/07/22
- Phantom: ELI Phantom\_1204; Type: QDOVA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**- Area Scan (81x221x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.964 W/kg


**- Zoom Scan (6x6x12)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=2mm

Reference Value = 0.7420 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 3.97 W/kg

**SAR(1 g) = 0.862 W/kg; SAR(10 g) = 0.274 W/kg**

Maximum value of SAR (measured) = 2.17 W/kg



**P10 Bluetooth\_DH1\_Bottom Side\_0cm\_Ch78\_Ant0****DUT: 150330C14**

Communication System: BT; Frequency: 2480 MHz; Duty Cycle: 1:1.53

Medium: B19T27N3\_0520 Medium parameters used:  $f = 2480$  MHz;  $\sigma = 2.044$  S/m;  $\epsilon_r = 51.354$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.7 °C ; Liquid Temperature : 23.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3864; ConvF(7.3, 7.3, 7.3); Calibrated: 2015/07/23;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2015/08/24
- Phantom: ELI Phantom\_1039; Type: QDOVA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**- Area Scan (71x151x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.00908 W/kg

**- Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 0 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.0200 W/kg

**SAR(1 g) = 0.00541 W/kg; SAR(10 g) = 0.00184 W/kg**

Maximum value of SAR (measured) = 0.0104 W/kg

