

FCC Part 15C Compliance Test Report

Test Report no.:	FCC15CWLAN_RM-714_14.docx	Date of Report:	19-Dec-2011
Number of pages:	32	Customer's Contact person:	Bruno Ramelli
Testing laboratory:	TCC Nokia Tampere Laboratory P.O. Box 68 Sinitaival 5 FIN-33720 TAMPERE, FINLAND Tel. +358 (0) 7180 46800 Fax. +358 (0) 7180 46880	Customer:	Nokia Corporation Lise Meitner Strasse 10 89081 ULM GERMANY Tel. +49 731 1754 0 Fax. +49 731 1754 6800
FCC listing no.:	94436		
IC recognition no.:	661AK-1		
Tested devices/ accessories:	Phone RM-714 / Battery BL-4U / AC charger AC-16 / Data cable CA-190CD / Headset WH-102		
FCC ID:	PPIRM-714	IC:	661U-RM714
Supplement reports:	-		
Testing has been carried out in accordance with:	CFR 47, FCC rules Part 15 Subpart C, ANSI C63.4 (2003), Public Notice DA 00-705, DTS procedures KDB 558074, IC standards, RSS-210 (Issue 8, December 2010). Deviations, modifications or clarifications (if any) to above mentioned documents are written in each section under "Test method and limit".		
Documentation:	The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 15 years at TCC Nokia.		
Test Results:	The EUT complies with the requirements in respect of all parameters subject to the test. The test results relate only to devices specified in this document		
Date and signature for the contents:			

Hannu Söderholm, Senior Engineer, EMC

1. Summary for FCC Part 15C Compliance Test Report

Date of receipt	05-Dec-2011
Testing completed	19-Dec-2011
The customer's contact person	Bruno Ramelli
Test Plan referred to	T:\Projects\RM-714\TestPlan\RS_testplan_RM-714.xls
Notes	-
Document name	T:\Projects\RM-714\EMC\FCC15CWLAN_RM-714_14.docx

1.1. EUT and Accessory Information

The EUT is a 9-band mobile phone:

GSM850/900/1800/1900/GPRS/EGPRS

WCDMA I/II(1900)/IV(1700)/V(850)/VIII/HSDPA/HSUPA

WLAN/Bluetooth

The EUT is tested with maximum rated TX power, modulated with pseudo random bit sequence (PRBS9).

Product	Type	SN	HW	MV	SW	DUT
Phone	RM-714	004402136826652	0420		Vp hwi11w47	42725
Battery	BL-4U	4620408224i20179507;0670560				42731
AC charger	AC-16	409049111158XX00006;0675491	0.3	-	-	42542
Data cable	CA-190CD	-	-	-	-	42720
Headset	WH-102	06943230363MA614499				42734

1.2. Summary of Test Results

WLAN:

Section in CFR 47	Section in RSS-GEN or RSS-210	Name of the test	Result
15.247(b)(1)	A8(0.4(4))	Conducted peak output power	PASSED
15.247(d)	A8(0.5)	Band edge compliance of RF emissions	NP
15.247(d)	A8(0.5)	Spurious RF conducted emissions	PASSED
15.247(d), 15.209	A8(0.5)	Spurious radiated emissions	NP
15.207	7.2.2	AC powerline conducted emissions	NP
15.247(a)(2)	A8(0.1(1))	6dB(bandwidth)	PASSED
15.247(e)	A8(0.1(2))	Power spectral density	PASSED

PASSED
FAILED
NP

The EUT complies with the essential requirements in the standard.
The EUT does not comply with the essential requirements in the standard.
The test was not performed by the TCC Nokia Laboratory.


CONTENTS

1. Summary for FCC Part 15C Compliance Test Report.....	2
1.1. EUT and Accessory Information	2
1.2. Summary of Test Results	2
2. Conducted peak output power (15.247(b)(1), RSS-210 A8.4 (4))	4
2.1. Test Setup	4
2.2. Test method and limit.....	4
2.3. WLAN Test results	5
3. Spurious RF conducted emissions (FCC §15.247(d), RSS-210 A8.5)	11
3.1. Test Setup	11
3.2. Test method and limit.....	11
3.3. WLAN Test results	12
4. 6 dB bandwidth (FCC §15.247(a)(2), RSS-210 A8.2 (1))	18
4.1. Test Setup	18
4.2. Test method and limit.....	18
4.3. WLAN Test results	19
5. Power spectral density (FCC §15.247(e), RSS-210 A8.2 (2))	25
5.1. Test Setup	25
5.2. Test method and limit.....	25
5.3. WLAN Test results	26
6. Test Equipment.....	31
6.1. Conducted measurements	31
6.2. Radiated measurements	31

2. Conducted peak output power (15.247(b)(1), RSS-210 A8.4 (4))

EUT with DUT number	RM-714, DUT 42725
Accessories with DUT numbers	BL-4U, DUT 42731 ; AC-16, DUT 42542 ; CA-190CD, DUT 42720 ; WH-102, DUT 42734
Operation Voltage [V] / [Hz]	Nominal
Results	PASSED
Remarks	USB charger was used
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	21.5 / 60 / 98.8
Date of measurements	19-Dec-2011
Measured by	Timo Raiskio

2.1. Test Setup



2.2. Test method and limit

The measurement is made according to DTS procedures KDB 558074 and IC standard RSS-210.

Limits for conducted peak output power measurements


Frequency range [MHz]	Limit [W]	Limit [dBm]
2400 – 2483.5	≤ 1	≤ 30

2.3. WLAN Test results


2.3.1 DSSS mode, QPSK modulation, 11 Mbps data rate

Channel / f _c [MHz]	P [dBm]	P [mW]	Result
1 / 2412	22.85	192.752	PASSED
7 / 2442	22.97	198.153	PASSED
11 / 2462	23.2	208.93	PASSED


Channel 1 / 2412 MHz



Channel 7 / 2442 MHz




Channel 11 / 2462 MHz




2.3.2 OFDM mode, BPSK modulation, 6 Mbps data rate

Channel / f _c [MHz]	P [dBm]	P [mW]	Result
1 / 2412	21.78	150.661	PASSED
7 / 2442	21.83	152.405	PASSED
11 / 2462	22.1	162.181	PASSED


Channel 1 / 2412 MHz



Channel 7 / 2442 MHz




Channel 11 / 2462 MHz




2.3.3 802.11n mode, HT20 modulation, MCS0 Mbps data rate

Channel / f _c [MHz]	P [dBm]	P [mW]	Result
1 / 2412	20.17	103.992	PASSED
7 / 2442	20.39	109.396	PASSED
11 / 2462	20.64	115.878	PASSED


Channel 1 / 2412 MHz



Channel 7 / 2442 MHz




Channel 11 / 2462 MHz



3. Spurious RF conducted emissions (FCC §15.247(d), RSS-210 A8.5)

EUT with DUT number	RM-714, DUT 42725
Accessories with DUT numbers	BL-4U, DUT 42731 ; AC-16, DUT 42542 ; CA-190CD, DUT 42720 ; WH-102, DUT 42734
Operation Voltage [V] / [Hz]	Nominal
Results	PASSED
Remarks	USB charger was used
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	21.5 / 60 / 98.8
Date of measurements	19-Dec-2011
Measured by	Timo Raiskio

3.1. Test Setup



3.2. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210.


Limits for spurious RF conducted emissions measurements

Frequency range [MHz]	Limit [dBc]
1 – 25000	<= -20

3.3. WLAN Test results

3.3.1 DSSS mode, QPSK modulation, 11 Mbps data rate


Channel 1 / 2412 MHz



Peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	P [dBc]	Result
4844	-43.91	PASSED
7257	-43.12	PASSED


Channel 7 / 2442 MHz



Peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	P [dBc]	Result
4836.4	-42.84	PASSED
7326.6	-42.67	PASSED

Channel 11 / 2462 MHz




Peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	P [dBc]	Result
4878.4	-44.13	PASSED
7383.6	-42.8	PASSED

3.3.2 OFDM mode, BPSK modulation, 6 Mbps data rate


Channel 1 / 2412 MHz



Peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	P [dBc]	Result
4810.4	-40.52	PASSED
7200	-39.96	PASSED


Channel 7 / 2442 MHz



Peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	P [dBc]	Result
4922.4	-39.77	PASSED
7348.8	-39.68	PASSED

Channel 11 / 2462 MHz




Peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	P [dBc]	Result
4918.8	-40.72	PASSED
7393.2	-39.84	PASSED

3.3.3 802.11n mode, HT20 modulation, MCS0 Mbps data rate


Channel 1 / 2412 MHz



Peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	P [dBc]	Result
4852.4	-39.52	PASSED
7257	-38.47	PASSED


Channel 7 / 2442 MHz



Peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	P [dBc]	Result
4886.8	-38.49	PASSED
7372.2	-38.12	PASSED

Channel 11 / 2462 MHz




Peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	P [dBc]	Result
4958.8	-38.48	PASSED
7342.2	-38.63	PASSED

4. 6 dB bandwidth (FCC §15.247(a)(2), RSS-210 A8.2 (1))

EUT with DUT number	RM-714, DUT 42725
Accessories with DUT numbers	BL-4U, DUT 42731 ; AC-16, DUT 42542 ; CA-190CD, DUT 42720 ; WH-102, DUT 42734
Operation Voltage [V] / [Hz]	Nominal
Results	PASSED
Remarks	USB charger was used
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	21.5 / 60 / 98.8
Date of measurements	19-Dec-2011
Measured by	Timo Raiskio

4.1. Test Setup



4.2. Test method and limit

The measurement is made according to DTS procedures KDB 558074 and IC standard RSS-210.

Limits for 6 dB bandwidth measurements


Limit [kHz]
>= 500

4.3. WLAN Test results


4.3.1 DSSS mode, QPSK modulation, 11 Mbps data rate

Channel / f_c [MHz]	6 dB bandwidth [kHz]	Result
1 / 2412	8012.8	PASSED
7 / 2442	7852.6	PASSED
11 / 2462	7772.4	PASSED


Channel 1 / 2412 MHz



Channel 7 / 2442 MHz




Channel 11 / 2462 MHz




4.3.2 OFDM mode, BPSK modulation, 6 Mbps data rate

Channel / f_c [MHz]	6 dB bandwidth [kHz]	Result
1 / 2412	16025.6	PASSED
7 / 2442	15544.9	PASSED
11 / 2462	16025.6	PASSED


Channel 1 / 2412 MHz



Channel 7 / 2442 MHz




Channel 11 / 2462 MHz




4.3.3 802.11n mode, HT20 modulation, MCS0 Mbps data rate

Channel / f _c [MHz]	6 dB bandwidth [kHz]	Result
1 / 2412	16826.9	PASSED
7 / 2442	16105.8	PASSED
11 / 2462	16746.8	PASSED


Channel 1 / 2412 MHz



Channel 7 / 2442 MHz




Channel 11 / 2462 MHz



5. Power spectral density (FCC §15.247(e), RSS-210 A8.2 (2))

EUT with DUT number	RM-714, DUT 42725
Accessories with DUT numbers	BL-4U, DUT 42731 ; AC-16, DUT 42542 ; CA-190CD, DUT 42720 ; WH-102, DUT 42734
Operation Voltage [V] / [Hz]	Nominal
Results	PASSED
Remarks	USB charger was used
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	21.5 / 60 / 98.8
Date of measurements	19-Dec-2011
Measured by	Timo Raiskio

5.1. Test Setup



5.2. Test method and limit

The measurement is made according to DTS procedures KDB 558074 and IC standard RSS-210.

Limits for power spectral density measurements


Limit [dBm] @ 3 kHz
<= 8

5.3. WLAN Test results


5.3.1 DSSS mode, QPSK modulation, 11 Mbps data rate

Channel / f_c [MHz]	P [dBm]	Result
1 / 2412	-6.21	PASSED
7 / 2442	-5.88	PASSED
11 / 2462	-5.39	PASSED


Channel 1 / 2412 MHz



Channel 7 / 2442 MHz




Channel 11 / 2462 MHz




5.3.2 OFDM mode, BPSK modulation, 6 Mbps data rate

Channel / f_c [MHz]	P [dBm]	Result
1 / 2412	-8.19	PASSED
7 / 2442	-7.82	PASSED
11 / 2462	-7.9	PASSED


Channel 1 / 2412 MHz



Channel 7 / 2442 MHz




Channel 11 / 2462 MHz




5.3.3 802.11n mode, HT20 modulation, MCS0 Mbps data rate

Channel / f_c [MHz]	P [dBm]	Result
1 / 2412	-8.83	PASSED
7 / 2442	-8.92	PASSED
11 / 2462	-8.48	PASSED


Channel 1 / 2412 MHz



Channel 7 / 2442 MHz



Channel 11 / 2462 MHz



6. Test Equipment

6.1. Conducted measurements

Eq. No	Equipment	Type	Manufacturer	Used in
TM38112	Power supply	6632A	Agilent	22/24/27, 15C
TM38631	Signal Generator	83640L	Agilent	22/24/27, 15C, 15B
OM06312	Signal Generator	E4422B	Agilent	22/24
TM37678	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
TM37773	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
TM30600	Impulse limiter	ESH3-Z2	R&S	15C, 15B
TM26490	LISN 50 µH	ESH3-Z5	R&S	15C, 15B
TM26491	LISN 50 µH	ESH3-Z5	R&S	15C, 15B
TM37610	Spectrum Analyzer	FSU26	R&S	22/24/27, 15C
TM22806	Battery	BAT 20/E	Fiskars	15C, 15B
TM22805	UPS	PS 20/1.2	Fiskars	15C, 15B
-	Temperature and humidity logger	175-H2	Testo	15C, 15B
-	Temperature and humidity logger	175-H2	Testo	22/24/27, 15C
-	Air pressure and temperature logger	635-2	Testo	22/24/27, 15C, 15B
-	Air pressure sensor	0638-1835	Testo	22/24/27, 15C, 15B
-	Temperature test chamber	VT 4002	Vötsch	22/24
2058	Receiver	ESPC	R&S	15C, 15B
2001	Bluetooth tester	CBT	R&S	22/24/27, 15C, 15B
2002	Communication Tester	CMU200	R&S	22/24/27
2009	LISN 50 µH	ENV216	R&S	15C, 15B
2010	LISN 50 µH	ENV216	R&S	15C, 15B
2012	Power splitter	11667B	Agilent	22/24/27, 15C
2013	Attenuator	8493C	Agilent	22/24/27, 15C
2014	Attenuator	8493C	Agilent	22/24/27, 15C
2019	Power splitter	ZN2PD-9G-S+	Mini-Circuits	15E
2020	Power splitter	ZN2PD-9G-S+	Mini-Circuits	15E

6.2. Radiated measurements

Eq. No	Equipment	Type	Manufacturer	Used in
TM38114	Power supply	6632A	Agilent	22/24/27, 15C, 15B
TM38631	Signal Generator	83640L	Agilent	22/24/27, 15C, 15B
TM38323	Preamplifier	PA-02 18-26 GHz	EMC Automation	22/24/27, 15C, 15B
-	Antenna	BBHA 9120 D	Schwarzbeck	22/24/27, 15C
TM26497	Antenna	3115	Emco	22/24/27, 15C, 15B
TM37678	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
TM37773	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
TM38845	Receiver	ESIB 26	R&S	22/24/27, 15C, 15B
-	Antenna	HL562	R&S	22/24/27, 15C, 15B
-	Turntable	2188	EMCO	22/24/27, 15C, 15B
-	Turntable controller	2090	EMCO	22/24/27, 15C, 15B
-	RF system panel	TS-RSP	R&S	22/24/27, 15C, 15B
-	RF system panel	TS-RSP	R&S	22/24/27, 15C, 15B
-	Mini mast	2075-2	ETS Lindgren	22/24/27, 15C, 15B

Eq. No	Equipment	Type	Manufacturer	Used in
TM38843	Mini mast	2075	Emco	22/24/27, 15C, 15B
TM38842	Antenna mast controller	2090	Emco	22/24/27, 15C, 15B
TM30643	LISN 50 μ H	LISN-5-20-2	FCC	22/24/27, 15C, 15B
TM30644	LISN 50 μ H	LISN-5-20-2	FCC	22/24/27, 15C, 15B
-	Temperature and humidity logger	175-H2	Testo	22/24/27, 15C, 15B
-	Air pressure and temperature logger	635-2	Testo	22/24/27, 15C, 15B
-	Air pressure sensor	0638-1835	Testo	22/24/27, 15C, 15B
TM39180	Laser distance meter	Disto Pro	Leica	22/24/27, 15C, 15B
TM37523	Preamplifier	AMF-4D-10M-3G-25-20P	Miteq	22/24/27, 15C, 15B
TM37498	Preamplifier	AMF-5D-020180-26-10P	Miteq	22/24/27, 15C, 15B
TM30599	Semi anechoic chambre	UNKNOWN	TDK	22/24/27, 15C, 15B
TM22638	Power supply	OL63743-901	-	22/24/27, 15C, 15B
TM38066	High pass filter	4HC3000/18000-3-KK	Trilithic	22/24/27, 15C, 15B
-	High pass filter	WHKX 1.6/15G-12SS	Wainwright	22/24/27, 15C, 15B
TM37545	Tunable notch filter	800.0/960.0-0.2/40-8SSK	Wainwright	22
TM26512	Tunable notch filter	WRC1850/1910-0.2/40-10SSK	Wainwright	24
-	Band reject filter	WRCG1877/1883-1870/1890-40/6EE	Wainwright	24
-	Band reject filter	WRCG1729.4/1735.4-1722.4/1742.4-40/6SS	Wainwright	27
-	Band reject filter	WRCG832/838-825/848-40/5SS	Wainwright	22
TM23892	Controller	G-1000SDX	Yaesu	22/24/27
2001	Bluetooth tester	CBT	R&S	22/24/27, 15C, 15B
6023	Antenna	VUBA 9117	Schwarzbeck	22/24/27, 15C