



Radio Frequency Exposure

Applicant : LITE-ON TECHNOLOGY CORP.

Address : 22F., No. 392, Ruiguang Rd., Neihu Dist.,
Taipei City 114753, Taiwan (R.O.C.)

Equipment : Solid State Digital Sign Computer

Model No. : MD455, MD455-WW


Trade Name : BrightSign

FCC ID : PPQ-MD455

I HEREBY CERTIFY THAT :

The sample was received on Jun. 24, 2025 and the testing was completed on Jul. 18, 2025 at Cerpass Technology Corp. The test result refers exclusively to the test presented test model / sample. Without written approval of Cerpass Technology Corp., the test report shall not be reproduced except in full.

Approved by:



Mark Liao / Supervisor

Laboratory Accreditation:

Cerpass Technology Corporation Test Laboratory





CONTENTS

1.	Summary of Test Procedure and Test Results	4
1.1.	Applicable Standards	4
2.	Test Configuration of Equipment under Test	5
2.1.	Feature of Equipment under Test	5
2.2.	General Information of Test	6
2.3.	Measurement Uncertainty	6
3.	Test Equipment and Ancillaries Used for Tests	7
4.	Radio Frequency Exposure	8
4.1.	Applicable Standards	8
4.2.	EUT Specification	9
4.3.	Test Result	9



History of this test report



1. Summary of Test Procedure and Test Results

1.1. Applicable Standards

FCC Rules and Regulations Part 2.1091

FCC Rule	Description of Test	Result
2.1091	Radio Frequency Exposure	PASS

*The lab has reduced the uncertainty risk factor from test equipment, environment and staff technicians which according to the standard on contract. Therefore, the test result will only be determined by standard requirement, measurement uncertainty evaluation is not considered.

*The differences is list below:

1. Model No.: MD455, MD455-WW is MD435, MD435-WW (FCC ID: PPQ-MD435)
add LCD Board.
2. Add Audio cable, HDMI cable, RJ45 cable and Conn adaptor.

Refer to original report for other test categories.

Test report number: 24090226-TRFCC04.



2. Test Configuration of Equipment under Test

2.1. Feature of Equipment under Test

Operation Frequency Range	802.11b/g/n: 2400-2483.5MHz 802.11a/n/ac: 5150-5250MHz, 5250-5350MHz, 5470-5725MHz, 5725-5850MHz
Center Frequency Range	802.11b/g/n: 2412MHz-2462MHz 802.11a/n/ac: 5180-5240MHz, 5260-5320MHz, 5500-5720MHz, 5745-5825MHz
Modulation Type	2.4GHz: 802.11b: CCK, DQPSK, DBPSK 802.11g/n: BPSK, QPSK, 16QAM, 64QAM 5GHz: 802.11n/a: BPSK, QPSK, 16QAM, 64QAM 802.11ac: BPSK, QPSK, 16QAM, 64QAM, 256QAM
Modulation Technology	DSSS, OFDM
Data Rate	2.4GHz: 802.11b: 1, 2, 5.5, 11Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54Mbps 802.11n: MCS0 – MCS7, HT20/40 5GHz: 802.11a: 6, 9, 12, 18, 24, 36, 48, 54Mbps 802.11n: MCS0 – MCS7, HT20/40 802.11ac: MCS0 – MCS9, VHT20/40/80
Antenna Type	Dipole Antenna
Antenna Gain	2400-2500MHz: 1.95dBi 5180-5240MHz: 2.37dBi 5260-5320MHz: 2.49dBi 5500-5700MHz: 3.64dBi 5745-5825MHz: 3.34dBi
Adapter	RISUNIC \ R0182-1201500US APD \ WB-18U12R
Firmware No.	5.10.198+bs9.0.166.1
Audio Cable	MDLINK \ 11200008
HDMI Cable	MDLINK \ 11500004
RJ45 Cable	MDLINK \ 10600049
Conn Adaptor	MDLINK \ 11200009

Note:

1. EUT support TPC Function.
2. EUT support DFS Client Mode, without radar detection.
3. For more details, please refer to the User's manual of the EUT.

Difference description:

1. All the Model No. are marketing purpose.
2. The Test Model No.: MD455.



2.2. General Information of Test

Organization	Cerpass Technology Corp.			
☒ Test Site	Cerpass Technology Corporation Test Laboratory Address: No.10, Ln. 2, Lianfu St., Luzhu Dist., Taoyuan City 33848, Taiwan (R.O.C.) Tel: +886-3-3226-888 Fax: +886-3-3226-881			
	FCC	TW1439, TW1079		
	IC	4934E-1, 4934E-2		
	Conducted: from 150kHz to 30 MHz Radiation: from 9kHz to 40,000MHz			
Test Distance	The test distance of radiated emission from antenna to EUT is 3 M.			

For 24090226

For 2.4GHz

Test Item	Test Site	Test period	Environmental Conditions	Tested By
RF Conducted	RFCON01-NK	2024/09/25	25.9°C / 41%	Leon Huang
RF Conducted	RFCON01-NK	2024/09/26	26.3°C / 42%	Leon Huang
RF Conducted	RFCON01-NK	2024/10/10	24.8°C / 47%	Leon Huang

For 5GHz

Test Item	Test Site	Test period	Environmental Conditions	Tested By
RF Conducted	RFCON01-NK	2024/09/24	25.5°C / 44%	Leon Huang

2.3. Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Item	Uncertainty
AC Power Line Conduction(150K~30MHz)	±3.2dB
Radiated Spurious Emission(9KHz~30MHz)	±3.5dB
Radiated Spurious Emission(30MHz~1GHz)	±5.1dB
Radiated Spurious Emission(1GHz~40GHz)	±5.2dB
Conducted Spurious Emission	±2.1dB
6dB Bandwidth	±5.4%
20dB Bandwidth	±4.4%
Occupied Bandwidth	±4.5%
Peak Output Power(Conducted Power Meter)	±1.1dB
Dwell Time / Deactivation Time	±7.6%
Power Spectral Density	±2.0dB
Duty Cycle	±3.5%



3. Test Equipment and Ancillaries Used for Tests

For 24090226

For 2.4GHz

Test Item	RF Conducted				
Test Site	RFC01-NK				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
CAX Signal Analyzer	KEYSIGHT	N9000B	MY57100339	2023/11/06	2024/11/05
Power Meter	Anritsu	ML2495A	1224005	2024/02/17	2025/02/16
Power Sensor	Anritsu	MA2411B	1207295	2024/02/17	2025/02/16
Attenuator	KEYSIGHT	8491B	MY39250703	2024/02/20	2025/02/19

For 5GHz

Test Item	RF Conducted				
Test Site	RFC01-NK				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
Spectrum Analyzer	R&S	FSP 40	100047	2024/03/01	2025/02/28
Attenuator	KEYSIGHT	8491B	MY39250703	2024/02/20	2025/02/19
Cable-0.5m (30M-40G)	HUBER SUHNER	SUCOFLEX 102	28420/2	2023/10/12	2024/10/11
Power Meter	Anritsu	ML2495A	1224005	2024/02/17	2025/02/16
Power Sensor	Anritsu	MA2411B	1207295	2024/02/17	2025/02/16
Switch Box	Theda	1-4	TW5451159	NA	NA



4. Radio Frequency Exposure

4.1. Applicable Standards

<input type="checkbox"/>	§ 1.1307(b)(3)(i)(A)	The available maximum time-averaged power is no more than 1 mW, regardless of separation distance.									
<input type="checkbox"/>	§ 1.1307(b)(3)(i)(c)	ERP is below a threshold calculated based on the distance , R between the person and the antenna / radiating structure, where $R > \lambda / 2\pi$.									
TABLE B.1—THRESHOLDS FOR SINGLE RF SOURCES SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION											
RF Source Frequency		Minimum Distance		Threshold ERP							
f_L MHz	f_H MHz	$\lambda_L / 2\pi$	$\lambda_H / 2\pi$	W							
0.3	—	1.34	159 m	—	35.6 m	1,920 R^2					
1.34	—	30	35.6 m	—	1.6 m	3,450 R^2/f^2					
30	—	300	1.6 m	—	159 mm	3.83 R^2					
300	—	1,500	159 mm	—	31.8 mm	0.0128 R^2/f					
1,500	—	100,000	31.8 mm	—	0.5 mm	19.2 R^2					
Subscripts L and H are low and high; λ is wavelength. From § 1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns.											
<input checked="" type="checkbox"/>	§ 1.1307(b)(3)(i)(B).	Device operates between 300 MHz and 6 GHz and the maximum time-averaged power or effective radiated power (ERP), whichever is greater, $\leq P_{th}$									
P_{th} (mW) = $\begin{cases} ERP_{20\text{ cm}}(d/20\text{ cm})^x & d \leq 20\text{ cm} \\ ERP_{20\text{ cm}} & 20\text{ cm} < d \leq 40\text{ cm} \end{cases}$											
Where											
$x = -\log_{10} \left(\frac{60}{ERP_{20\text{ cm}} \sqrt{f}} \right)$ and f is in GHz;											
and											
$ERP_{20\text{ cm}}$ (mW) = $\begin{cases} 2040f & 0.3\text{ GHz} \leq f < 1.5\text{ GHz} \\ 3060 & 1.5\text{ GHz} \leq f \leq 6\text{ GHz} \end{cases}$											
d = the separation distance (cm);											



4.2. EUT Specification

Frequency band (Operating)	<input checked="" type="checkbox"/> WLAN: 2412MHz ~ 2462MHz <input checked="" type="checkbox"/> WLAN: 5150MHz ~ 5250MHz <input checked="" type="checkbox"/> WLAN: 5250MHz ~ 5350MHz <input checked="" type="checkbox"/> WLAN: 5470MHz ~ 5725MHz <input checked="" type="checkbox"/> WLAN: 5725MHz ~ 5850MHz <input type="checkbox"/> SRD: 2402MHz ~ 2480MHz <input type="checkbox"/> BLE: 2402MHz ~ 2480MHz
Device category	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation)
Antenna diversity	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <ul style="list-style-type: none"> <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
Evaluation applied	<input type="checkbox"/> Blanket 1 mW Blanket Exemption <input checked="" type="checkbox"/> MPE-based Exemption <input type="checkbox"/> SAR-based Exemption
Remark:	
The maximum conducted output power is <u>17.66dBm (58.345mW)</u> at <u>2412MHz</u> (with <u>1.95dBi antenna gain</u> .)	

4.3. Test Result

For 24090226

2.4GHz						
Channel Frequency (MHz)	Max. Conducted output power(dBm)	Max. Tune up power (dBm)	Antenna Gain (dBi)	Max.Tune up e.r.p. Power (dBm)	Max.Tune up e.r.p. Power (mW)	Limit (mW)
2412-2462	17.66	18.16	1.95	17.96	62.52	3060

5GHz						
Channel Frequency (MHz)	Max. Conducted output power(dBm)	Max. Tune up power (dBm)	Antenna Gain (dBi)	Max.Tune up e.r.p. Power (dBm)	Max.Tune up e.r.p. Power (mW)	Limit (mW)
5180-5240	15.46	15.96	2.37	16.18	41.50	3060
5260-5320	15.63	16.13	2.49	16.47	44.36	3060
5500-5720	15.14	15.64	3.64	17.13	51.64	3060
5745-5825	14.26	14.76	3.34	15.95	39.36	3060

No non-compliance noted.

Distance: 20cm.

-----THE END OF REPORT-----