

RF Test Report

Applicant : Lite-On Technology Corp.
Product Type : BLE Bluetooth Module
Trade Name : LITE-ON
Model Number : WB101N
Test Specification : FCC 47 CFR PART 15 SUBPART C
ANSI C63.10:2013
Receive Date : Oct. 03, 2019
Test Period : Oct. 14 ~ Oct. 21, 2019
Issue Date : Oct. 23, 2019

Issue by

A Test Lab Techno Corp.
No. 140-1, Changan Street, Bade District,
Taoyuan City 33465, Taiwan (R.O.C.)
Tel : +886-3-2710188 / Fax : +886-3-2710190



Taiwan Accreditation Eoundation accreditation number: 1330

Test Firm MRA designation number: TW0010

Note:

1. The test results are valid only for samples provided by customers and under the test conditions described in this report.
2. This report shall not be reproduced except in full, without the written approval of A Test Lab Technology Corporation.
3. The relevant information is provided by customers in this test report. According to the correctness, appropriateness or completeness of the information provided by the customer, if there is any doubt or error in the information which affects the validity of the test results, the laboratory does not take the responsibility.



Revision History

Rev.	Issue Date	Revisions	Revised By
00	Oct. 23, 2019	Initial Issue	Tobey Cheng

Verification of Compliance

Issued Date: Oct. 23, 2019

Applicant : Lite-On Technology Corp.
Product Type : BLE Bluetooth Module
Trade Name : LITE-ON
Model Number : WB101N
FCC ID : PPQ-WB101N
EUT Rated Voltage : DC 1.8 V ~ 3.6 V (3.3 V typical)
Test Voltage : 120 Vac / 60 Hz, DC 5 V
Applicable Standard : FCC 47 CFR PART 15 SUBPART C
ANSI C63.10:2013
Test Result : Complied

Performing Lab. : A Test Lab Techno Corp.
No. 140-1, Changan Street, Bade District,
Taoyuan City 33465, Taiwan (R.O.C.)
Tel : +886-3-2710188 / Fax : +886-3-2710190
Taiwan Accreditation Foundation accreditation number: 1330
<http://www.atl-lab.com.tw/e-index.htm>



A Test Lab Techno Corp. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by A Test Lab Techno Corp. based on interpretations and/or observations of test results. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Approved By

: Fly Lu

(Manager)

(Fly Lu)

TABLE OF CONTENTS

1	General Information	5
1.1.	Summary of Test Result.....	5
1.2.	Measurement Uncertainty.....	6
2	EUT Description	7
3	Test Methodology	8
3.1.	Mode of Operation.....	8
3.2.	EUT Test Step	8
3.3.	Configuration of Test System Details	9
3.4.	Test Instruments	10
3.5.	Test Site Environment.....	11
4	Measurement Procedure	12
4.1.	AC Power Line Conducted Emission Measurement.....	12
4.2.	Radiated Emission Measurement	14
4.3.	Maximum Conducted Output Power Measurement.....	18
4.4.	6 dB RF Bandwidth Measurement	19
4.5.	Maximum Power Density Measurement	20
4.6.	Out of Band Conducted Emissions Measurement.....	21
4.7.	Antenna Measurement	21
5	Test Results.....	22
	Annex A. Conducted Emission	22
	Annex B. Conducted Test Results	24
	Annex C. Radiated Emission Measurement	31



1 General Information

1.1. Summary of Test Result

Standard	Item	Result	Remark
15.207	AC Power Conducted Emission	PASS	-----
15.247(d)	Transmitter Radiated Emissions	PASS	-----
15.247(b)(3)	Max. Output Power	PASS	-----
15.247(a)(2)	6 dB RF Bandwidth	PASS	-----
15.247(e)	Maximum Power Spectral Density	PASS	-----
15.247(d)	Out of Band Conducted Spurious Emission	PASS	-----
15.203	Antenna Requirement	PASS	-----

Standard	Description
CFR47, Part 15, Subpart C	Intentional Radiators
ANSI C63. 10: 2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
KDB 558074 D01 15.247 Meas Guidance v05r02	GUIDANCE FOR COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEM, FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM, AND HYBRID SYSTEM DEVICES OPERATING UNDER SECTION 15.247 OF THE FCC RULES

Decision Rule

- ☒ Uncertainty is not included.
- ☐ Uncertainty is included.

1.2. Measurement Uncertainty

Test Item	Frequency Range	Uncertainty (dB)
Conducted Emission	150 kHz ~ 30 MHz	2.8
Radiated Emission	9 kHz ~ 30 MHz	1.7
	30 MHz ~ 1000 MHz	5.7
	1000 MHz ~ 18000 MHz	5.6
	18000 MHz ~ 26500 MHz	4.9
	26500 MHz ~ 40000 MHz	4.8
Conducted Output Power	+0.27 dB / -0.28 dB	
RF Bandwidth	4.96 %	
Power Spectral Density	+0.71 dB / -0.77 dB	

2 EUT Description

Applicant	Lite-On Technology Corp. Bldg. C, 90, Chien 1 Road, Chung Ho, New Taipei City 23585, Taiwan, R.O.C.	
Manufacturer	LITE-ON TECHNOLOGY (Changzhou) CO., LTD A9 Building, No. 88 Yanghu Road, Wujin Hi-Tech Industrial Development Zone, Changzhou City, Jiangsu Province 213100 China	
Product Type	BLE Bluetooth Module	
Trade Name	LITE-ON	
Model No.	WB101N	
FCC ID	PPQ-WB101N	
Class II Permissive Change	Add Bluetooth 2LE function by software.	
Frequency Range	2402 ~ 2480 MHz	
Modulation Type	GFSK	
Operate Temp. Range	-40 ~ +85 °C	
Antenna information	Type	Max. Gain (dBi)
	Printed Antenna	3.0
RF Output Power	2LE, GFSK: 0.00202 W	

3 Test Methodology

3.1. Mode of Operation

Decision of Test ATL has verified the construction and function in typical operation. All the test modes were carried out with the EUT in normal operation, which was shown in this test report and defined as:

Test Mode
Mode 1: Transmit mode
Mode 2: 2LE, GFSK Continuous TX Mode

Software used to control the EUT for staying in continuous transmitting mode was programmed.

After verification, all tests were carried out with the worst case test modes.

By preliminary testing and verifying three axis (X, Y and Z) position of EUT transmitted status, it was found that "X axis" position was the worst, then the final test was executed the worst condition and test data were recorded in this report.

Note: The EUT was programmed to be in continuously transmitting mode and the transmit duty cycle is not less than 98 %.


3.2. EUT Test Step

1	Setup the EUT shown on "Configuration of Test System Details".
2	Turn on the power of all equipment.
3	Turn on TX function.
4	EUT run test program.


Measurement Software			
No.	Description	Software	Version
1	Conducted Emission	EZ EMC	1.1.4.3
2	Radiated Emission	EZ EMC	1.1.4.4

3.3. Configuration of Test System Details

Conducted Emission



Radiated Emissions



Devices Description					
	Product	Manufacturer	Model Number	Serial Number	Power Cord
(1)	Notebook	HP	PROBOOK 4421s	CNF1182X1G	---
(2)	AC Adapter	HP	Series PPP012H-S	---	Non-Shielded, 1.7 m
(3)	USB Cable	CHINGLUNG	E238846	AWM 2725	---



3.4. Test Instruments

For Conducted Emission

Test Period: Oct. 21, 2019

Testing Engineer: Louis Shen

Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Cal. Period
Test Receiver	R&S	ESCI	100367	05/23/2019	1 year
LISN	R&S	ENV216	101040	04/03/2019	1 year
LISN	R&S	ENV216	101041	03/28/2019	1 year
RF Cable	Woken	00100D1380194M	TE-02-03	05/23/2019	1 year

For Radiated Emissions

Test Period: Oct. 14 ~ Oct. 21, 2019

Testing Engineer: Ricky Liu

Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Cal. Period
Spectrum Analyzer (10 Hz~44 GHz)	Keysight	N9010A	MY52221312	01/14/2019	1 year
Pre Amplifier (1~26.5 GHz)	Agilent	8449B	3008A02456	03/20/2019	1 year
Pre Amplifier (100 kHz~1.3 GHz)	Agilent	8447D	2944A11119	01/14/2019	1 year
Broadband Antenna	Schwarzbeck	VULB9168	0841	11/19/2018	1 year
Broadband Antenna	Schwarzbeck	VULB9168	416	10/19/2018	1 year
Horn Antenna (1~18 GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA9120D	9120D-550	08/22/2019	1 year
Horn Antenna (18~40 GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA9170	9170-320	08/14/2019	1 year
Loop Antenna	COM-POWER CORPORATION	AL-130	121014	03/29/2019	1 year
RF Cable	EMCI	EMC104-N-N-6000	TE01-1	02/20/2019	1 year
Microwave Cable	EMCI	EMC104-SM -SM-13000	170814	10/30/2018	1 year
Microwave Cable	EMCI	EMC102-KM -KM-14000	151001	02/20/2019	1 year

For Conducted

Test Period: Oct. 21, 2019

Testing Engineer: Negi Chiu

Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Cal. Period
Spectrum Analyzer	Agilent	E4408B	MY45107753	08/13/2019	1 year
Power Sensor	Anritsu	MA2411B	1126022	09/02/2019	1 year
Power Meter	Anritsu	ML2495A	1135009	09/02/2019	1 year

Note: N.C.R. = No Calibration Request.



3.5. Test Site Environment

Items	Required (IEC 60068-1)	Actual
Temperature (°C)	15-35	23-26
Humidity (%RH)	25-75	55-60
Barometric pressure (mbar)	860-1060	990


4 Measurement Procedure

4.1. AC Power Line Conducted Emission Measurement

■ Limit

Frequency (MHz)	Quasi-peak	Average
0.15 - 0.5	66 to 56	56 to 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

■ Test Setup



■ Test Procedure

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a $50\ \Omega // 50\ \mu\text{H}$ coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a $50\ \Omega // 50\ \mu\text{H}$ coupling impedance with 50 ohm termination.

Tabletop device shall be placed on a non-conducting platform, of nominal size 1 m by 1.5 m, raised 80 cm above the reference ground plane. The wall of screened room shall be located 40 cm to the rear of the EUT. Other surfaces of tabletop or floor standing EUT shall be at least 80 cm from any other ground conducting surface including one or more LISNs. For floor-standing device shall be placed under the EUT with a 12 mm insulating material.

Conducted emissions were investigated over the frequency range from 0.15 MHz to 30 MHz using a resolution bandwidth of 9 kHz. The equipment under test (EUT) shall be meet the limits in section 4.1, as applicable, including the average limit and the quasi-peak limit when using respectively, an average detector and quasi-peak detector measured in accordance with the methods described of related standard. When all of peak value were complied with quasi-peak and average limit from 150 kHz to 30 MHz then quasi-peak and average measurement was unnecessary.

The AMN shall be placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for AMNs mounted on top of the ground reference plane. This distance is between the closest points of the AMN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8 m from the AMN. If the mains power cable is longer than 1 m then the cable shall be folded back and forth at the centre of the lead to form a bundle no longer than 0.4 m. All of interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 cm to 40 cm long. All of EUT and AE shall be separate place more than 0.1 m. All 50 Ω ports of the LISN shall be resistively terminated into 50 Ω loads when not connected to the measuring instrument.

If the reading of the measuring receiver shows fluctuations close to the limit, the reading shall be observed for at least 15 s at each measurement frequency; the higher reading shall be recorded with the exception of any brief isolated high reading which shall be ignored.

4.2. Radiated Emission Measurement

■ Limit


According to §15.209(a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$ at meter)	Measurement Distance (meters)
0.009 – 0.490	$2400 / F$ (kHz)	300
0.490 – 1.705	$24000 / F$ (kHz)	30
1.705 – 30.0	30	30
30 - 88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3


** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

■ Setup


9 kHz ~ 30 MHz



Below 1 GHz



Above 1 GHz



■ Test Procedure

Final radiation measurements were made on a three-meter, Semi Anechoic Chamber. The EUT system was placed on a nonconductive turntable which is 0.8 or 1.5 meters height, top surface 1.0 x 1.5 meter. The spectrum was examined from 250 MHz to 2.5 GHz in order to cover the whole spectrum below 10th harmonic which could generate from the EUT. During the test, EUT was set to transmit continuously & Measurements spectrum range from 9 kHz to 26.5 GHz is investigated.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, and then the video bandwidth is set to 3 MHz for peak measurements and 10 Hz for average measurements when Duty cycle >0.98 / $1/T$ for average measurements when Duty cycle <0.98 . A nonconductive material surrounded the EUT to supporting the EUT for standing on three orthogonal planes. At each condition, the EUT was rotated 360 degrees, and the antenna was raised and lowered from one to four meters to find the maximum emission levels. Measurements were taken using both horizontal and vertical antenna polarization.

SCHWARZBECK MESS-ELEKTRONIK Biconilog Antenna at 3 Meter and the SCHWARZBECK Double Ridged Guide Antenna was used in frequencies 1 –26.5 GHz at a distance of 3 meter. The antenna at an angle toward the source of the emission. All test results were extrapolated to equivalent signal at 3 meters utilizing an inverse linear distance extrapolation Factor (20 dB/decade).

For testing above 1 GHz, the emission level of the EUT in peak mode was 20 dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

Appropriate preamplifiers were used for improving sensitivity and precautions were taken to avoid overloading or desensitizing the spectrum analyzer. No post – detector video filters were used in the test.

The spectrum analyzer's 6 dB bandwidth was set to 1 MHz, and the analyzer was operated in the peak detection mode, for frequencies both below and up 1 GHz. The average levels were obtained by subtracting the duty cycle correction factor from the peak readings.

The following procedures were used to convert the emission levels measured in decibels referenced to 1 microvolt (dBuV) into field intensity in micro volts pre meter (uV/m).

The actual field intensity in decibels referenced to 1 microvolt in to field intensity in micro volts per meter (dBuV/m).

The actual field intensity in referenced to 1 microvolt per meter (dBuV/m) is determined by algebraically adding the measured reading in dBuV, the antenna factor (dB), and cable loss (dB) and Subtracting the gain of preamplifier (dB) is auto calculate in spectrum analyzer.

$$(1) \text{ Amplitude (dBuV/m) = FI (dBuV) + AF (dBuV) + CL (dBuV) - Gain (dB)}$$

FI= Reading of the field intensity.

AF= Antenna factor.

CL= Cable loss.

P.S Amplitude is auto calculate in spectrum analyzer.

$$(2) \text{ Actual Amplitude (dBuV/m) = Amplitude (dBuV) - Dis(dB)}$$

The FCC specified emission limits were calculated according the EUT operating frequency and by following linear interpolation equations:

(a) For fundamental frequency : Transmitter Output < +30 dBm

(b) For spurious frequency : Spurious emission limits = fundamental emission limit /10


Data of measurement within this frequency range without mark in the table above means the reading of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.

4.3. Maximum Conducted Output Power Measurement

■ Limit

For systems using digital modulation in the 2400-2483.5 MHz, the limit for peak output power is 30 dBm.

■ Test Setup



■ Test Procedure

The testing follows the Measurement Procedure of ANSI C63.10:2013 section 11.9.2.3.2 Method AVGPM.

The tests below are run with the EUT's transmitter set at high power in TX mode. The EUT is needed to force selection of output power level and channel number. While testing, EUT was set to transmit continuously. Remove the Subjective device's antenna and connect the RF output port to power sensor..


4.4. 6 dB RF Bandwidth Measurement

■ Limit

6 dB RF Bandwidth: Systems using digital modulation techniques may operate in the 2400–2483.5 MHz bands. The minimum 6 dB band-width shall be at least 500 kHz.

99 % Occupied Bandwidth: N/A

■ Test Setup



■ Test Procedure

The EUT tested to DTS test procedure of ANSI C63.10:2013 section 11.8.2 option2 for compliance to FCC 47CFR 15.247 requirements.

6 dB RF Bandwidth: The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RBW was set to 100 kHz. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A peak output reading was taken, a DISPLAY line was drawn 6 dB lower than peak level. The 6 dB bandwidth was determined from where the channel output spectrum intersected the display line.


The test was performed at 3 channels (Channel low, middle, high)

4.5. Maximum Power Density Measurement

■ Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

■ Test Setup



■ Test Procedure

The EUT tested to DTS test procedure of ANSI C63.10:2013 section 11.10.2 Method PKPSD.


1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

4.6. Out of Band Conducted Emissions Measurement

■ Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

■ Test Setup



■ Test Procedure

In any 100 kHz bandwidth outside the EUT pass band, the RF power produced by the modulation products of the spreading sequence, the information sequence, and the carrier frequency shall be at least 20 dB below that of the maximum in-band 100 kHz emission, antenna output of the EUT was coupled directly to spectrum analyzer; if an external attenuator and/or cable was used, these losses are compensated for with the analyzer OFFSET function.

All other types of emissions from the EUT shall meet the general limits for radiated frequencies outside the pass band. The test was performed at 3 channels.

4.7. Antenna Measurement

■ Limit

For intentional device, according to 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And According to 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


■ Antenna Connector Construction

See section 2 – antenna information.

5 Test Results

Annex A. Conducted Emission

Standard:	FCC Part 15.247	Line:	L1
Test Mode:	Mode 1	Power:	AC 120 V/60 Hz
		Temp.(°C)/Hum.(%RH):	26(°C)/60 %RH
Description:			




No.	Frequency (MHz)	QP reading (dBuV)	AVG reading (dBuV)	Correction factor (dB)	QP result (dBuV)	AVG result (dBuV)	QP limit (dBuV)	AVG limit (dBuV)	QP margin (dB)	AVG margin (dB)	Remark
1	0.1620	33.24	23.10	9.65	42.89	32.75	65.36	55.36	-22.47	-22.61	Pass
2	0.1740	30.32	20.52	9.65	39.97	30.17	64.77	54.77	-24.80	-24.60	Pass
3	0.1980	27.22	18.46	9.64	36.86	28.10	63.69	53.69	-26.83	-25.59	Pass
4	0.4980	31.06	26.15	9.66	40.72	35.81	56.03	46.03	-15.31	-10.22	Pass
5	0.6340	27.32	21.05	9.66	36.98	30.71	56.00	46.00	-19.02	-15.29	Pass
6	2.4460	30.20	25.67	9.73	39.93	35.40	56.00	46.00	-16.07	-10.60	Pass

Note: 1. Result (dBuV) = Correction factor (dB) + Reading(dBuV).

Example: 42.89 = 9.65 + 33.24

2. Correction factor (dB) = Cable loss (dB) + L.I.S.N. factor (dB).

Standard:	FCC Part 15.247	Line:	N
Test Mode:	Mode 1	Power:	AC 120 V/60 Hz
		Temp.(°C)/Hum.(%RH):	26(°C)/60 %RH
Description:			



No.	Frequency (MHz)	QP reading (dBuV)	AVG reading (dBuV)	Correction factor (dB)	QP result (dBuV)	AVG result (dBuV)	QP limit (dBuV)	AVG limit (dBuV)	QP margin (dB)	AVG margin (dB)	Remark
1	0.1740	29.81	16.02	9.68	39.49	25.70	64.77	54.77	-25.28	-29.07	Pass
2	0.1900	28.36	16.60	9.67	38.03	26.27	64.04	54.04	-26.01	-27.77	Pass
3	0.2100	27.06	17.98	9.67	36.73	27.65	63.21	53.21	-26.48	-25.56	Pass
4	0.5180	26.61	21.70	9.69	36.30	31.39	56.00	46.00	-19.70	-14.61	Pass
5	0.6300	28.37	20.04	9.69	38.06	29.73	56.00	46.00	-17.94	-16.27	Pass
6	2.8060	28.36	24.43	9.77	38.13	34.20	56.00	46.00	-17.87	-11.80	Pass

Note: 1. Result (dBuV) = Correction factor (dB) + Reading(dBuV).

Example: 39.49 = 9.68 + 29.81

2. Correction factor (dB) = Cable loss (dB) + L.I.S.N. factor (dB).

Annex B. Conducted Test Results

Maximum Conducted Output Power Measurement

Test Mode	Mode 2				
Frequency (MHz)	Average Power		Peak Power		Limit (dBm)
	(dBm)	(W)	(dBm)	(W)	
2402	2.80	0.00191	3.06	0.00202	≤ 30
2440	2.47	0.00177	2.71	0.00187	≤ 30
2480	2.20	0.00166	2.50	0.00178	≤ 30

Note: The relevant measured result has the offset with cable loss already.

6 dB RF Bandwidth Measurement

Test Mode	Mode 2	
Frequency (MHz)	Measurement Results (kHz)	Limit (kHz)
2402	863.903	≥ 500
2440	884.549	≥ 500
2480	889.400	≥ 500



■ Test Graphs

Mode 2	
2402 MHz	Agilent R T Ch Freq 2.402 GHz Trig Free Occupied Bandwidth Averages: 10 Ref 15 dBm Atten 25 dB Peak Log 10 dB/ Offst 1 dB Center 2.402 GHz Res BW 100 kHz VBW 300 kHz Sweep 5 ms (401 pts) Span 3 MHz Occupied Bandwidth 1.7942 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB Transmit Freq Error 38.011 kHz x dB Bandwidth 863.903 kHz Freq/Channel Center Freq 2.4020000 GHz Start Freq 2.40050000 GHz Stop Freq 2.40350000 GHz CF Step 300.000000 kHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off
2440 MHz	Agilent R T Ch Freq 2.44 GHz Trig Free Occupied Bandwidth Averages: 10 Ref 15 dBm Atten 25 dB Peak Log 10 dB/ Offst 1 dB Center 2.44 GHz Res BW 100 kHz VBW 300 kHz Sweep 5 ms (401 pts) Span 3 MHz Occupied Bandwidth 1.8758 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB Transmit Freq Error 31.280 kHz x dB Bandwidth 884.549 kHz Freq/Channel Center Freq 2.44000000 GHz Start Freq 2.43850000 GHz Stop Freq 2.44150000 GHz CF Step 300.000000 kHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off
2480 MHz	Agilent R T Ch Freq 2.48 GHz Trig Free Occupied Bandwidth Averages: 10 Ref 15 dBm Atten 25 dB Peak Log 10 dB/ Offst 1 dB Center 2.48 GHz Res BW 100 kHz VBW 300 kHz Sweep 5 ms (401 pts) Span 3 MHz Occupied Bandwidth 1.9071 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB Transmit Freq Error 39.707 kHz x dB Bandwidth 889.400 kHz Freq/Channel Center Freq 2.48000000 GHz Start Freq 2.47850000 GHz Stop Freq 2.48150000 GHz CF Step 300.000000 kHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off C:\B88.GIF file saved






Maximum Power Density Measurement

Test Mode	Mode 2	
Frequency (MHz)	Measurement Results (dBm/ 3kHz)	Limit (dBm)
2402	-9.703	≤ 8
2440	-9.826	≤ 8
2480	-9.603	≤ 8



■ Test Graphs




Mode 2	
2402 MHz	Agilent Ref 15 dBm Peak Log 10 dB/ Offst 1 dB Atten 25 dB Mkr1 2.40211625 GHz -9.703 dBm M1 S2 S3 FC AA  Center 2.402 GHz *Res BW 3 kHz Span 1.5 MHz *VBW 10 kHz Sweep 171.5 ms (401 pts) Freq/Channel Center Freq 2.40200000 GHz Start Freq 2.40125000 GHz Stop Freq 2.40275000 GHz CF Step 150.000000 kHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off
2440 MHz	Agilent Ref 15 dBm Peak Log 10 dB/ Offst 1 dB Atten 25 dB Mkr1 2.44014250 GHz -9.826 dBm M1 S2 S3 FC AA  Center 2.44 GHz *Res BW 3 kHz Span 1.5 MHz *VBW 10 kHz Sweep 171.5 ms (401 pts) Freq/Channel Center Freq 2.44000000 GHz Start Freq 2.43925000 GHz Stop Freq 2.44075000 GHz CF Step 150.000000 kHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off
2480 MHz	Agilent Ref 15 dBm Peak Log 10 dB/ Offst 1 dB Atten 25 dB Mkr1 2.48001500 GHz -9.603 dBm M1 S2 S3 FC AA  Center 2.48 GHz *Res BW 3 kHz Span 1.5 MHz *VBW 10 kHz Sweep 171.5 ms (401 pts) Freq/Channel Center Freq 2.48000000 GHz Start Freq 2.47925000 GHz Stop Freq 2.48075000 GHz CF Step 150.000000 kHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off



Out of Band Conducted Emissions Measurement

■ Test Graphs

Reference level



Mode 2	
2402 MHz	
2440 MHz	
2480 MHz	



Out of Band Conducted Emissions

Mode 2	
2402 MHz	Agilent R T Ref 15 dBm Atten 25 dB Mkr1 2.40 GHz 2.966 dBm Peak Log 10 dB/ Offst 1 dB DI -17.2 dBm Start 30 MHz Stop 26.5 GHz Res BW 100 kHz VBW 300 kHz Sweep 2.742 s (401 pts) Marker 1 Trace (1) Type Freq X Axis 2.40 GHz Amplitude 2.966 dBm Freq/Channel Center Freq 13.2650000 GHz Start Freq 30.0000000 MHz Stop Freq 26.5000000 GHz CF Step 2.64700000 GHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off
2440 MHz	Agilent R T Ref 15 dBm Atten 25 dB Mkr1 2.44 GHz 2.578 dBm Peak Log 10 dB/ Offst 1 dB DI -17.5 dBm Start 30 MHz Stop 26.5 GHz Res BW 100 kHz VBW 300 kHz Sweep 2.742 s (401 pts) Marker 1 Trace (1) Type Freq X Axis 2.44 GHz Amplitude 2.578 dBm Freq/Channel Center Freq 13.2650000 GHz Start Freq 30.0000000 MHz Stop Freq 26.5000000 GHz CF Step 2.64700000 GHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off
2480 MHz	Agilent R T Ref 15 dBm Atten 25 dB Mkr1 2.48 GHz 1.651 dBm Peak Log 10 dB/ Offst 1 dB DI -17.7 dBm Start 30 MHz Stop 26.5 GHz Res BW 100 kHz VBW 300 kHz Sweep 2.742 s (401 pts) Marker 1 Trace (1) Type Freq X Axis 2.48 GHz Amplitude 1.651 dBm Freq/Channel Center Freq 13.2650000 GHz Start Freq 30.0000000 MHz Stop Freq 26.5000000 GHz CF Step 2.64700000 GHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off

Conducted Band Edge

Mode 2	
2402 MHz	
2480 MHz	

Annex C. Radiated Emission Measurement

Harmonic

Below 1 GHz

Standard:		FCC Part 15.247		Test Distance:		3 m	
Test Mode:		Mode 2		Power:		DC 5 V	
				Temp.(°C)/Hum.(%RH):		26(°C)/60 %RH	
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
239.5200	51.37	-6.44	44.93	46.00	-1.07	QP	H
263.7700	50.47	-5.62	44.85	46.00	-1.15	QP	H
359.8000	43.53	-2.89	40.64	46.00	-5.36	QP	H
408.3000	37.95	-2.22	35.73	46.00	-10.27	QP	H
495.6000	36.95	-0.58	36.37	46.00	-9.63	QP	H
698.3300	29.24	3.44	32.68	46.00	-13.32	QP	H
107.6000	46.79	-10.24	36.55	43.50	-6.95	QP	V
144.4600	43.41	-6.36	37.05	43.50	-6.45	QP	V
239.5200	41.76	-6.44	35.32	46.00	-10.68	QP	V
335.5500	37.77	-3.34	34.43	46.00	-11.57	QP	V
480.0800	35.61	-0.74	34.87	46.00	-11.13	QP	V
672.1400	30.20	3.05	33.25	46.00	-12.75	QP	V


Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading (dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3.When the peak results are less than average limit, so not need to evaluate the average.

Above 1 GHz

Standard:	FCC Part 15.247	Test Distance:	3 m
Test item:	Harmonic	Power:	DC 5 V
Frequency:	2402 MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60 %RH
Mode:	Mode 2		
Ant.Polar.:	Horizontal		



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4804.000	40.73	4.28	45.01	74.00	-28.99	peak
2	7206.000	34.54	10.19	44.73	74.00	-29.27	peak


Note: 1. Result (dBuV/m) = Correct Factor (dB/m) + Reading (dBuV).

Example: $45.01 = 4.28 + 40.73$

2. Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3 m
Test item:	Harmonic	Power:	DC 5 V
Frequency:	2402 MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60 %RH
Mode:	Mode 2		
Ant.Polar.:	Vertical		



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4804.000	44.71	4.28	48.99	74.00	-25.01	peak
2	7206.000	34.23	10.19	44.42	74.00	-29.58	peak


Note: 1. Result (dBuV/m) = Correct Factor (dB/m) + Reading (dBuV).

Example: $48.99 = 4.28 + 44.71$

2. Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3 m
Test item:	Harmonic	Power:	DC 5 V
Frequency:	2440 MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60 %RH
Mode:	Mode 2		
Ant.Polar.:	Horizontal		



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4880.000	42.99	4.44	47.43	74.00	-26.57	peak
2	7320.000	44.91	10.41	55.32	74.00	-18.68	peak
3	7320.000	23.07	10.41	33.48	54.00	-20.52	AVG


Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.



Standard:	FCC Part 15.247	Test Distance:	3 m
Test item:	Harmonic	Power:	DC 5 V
Frequency:	2440 MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60 %RH
Mode:	Mode 2		
Ant.Polar.:	Vertical		



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4880.000	46.76	4.44	51.20	74.00	-22.80	peak
2	7320.000	43.55	10.41	53.96	74.00	-20.04	peak
3	7320.000	21.12	10.41	31.53	54.00	-22.47	AVG


Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.



Standard:	FCC Part 15.247	Test Distance:	3 m
Test item:	Harmonic	Power:	DC 5 V
Frequency:	2480 MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60 %RH
Mode:	Mode 2		
Ant.Polar.:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4960.000	39.04	4.60	43.64	74.00	-30.36	peak
2	7440.000	40.98	10.65	51.63	74.00	-22.37	peak

Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3 m
Test item:	Harmonic	Power:	DC 5 V
Frequency:	2480 MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60 %RH
Mode:	Mode 2		
Ant.Polar.:	Vertical		



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4960.000	41.03	4.60	45.63	74.00	-28.37	peak
2	7440.000	40.63	10.65	51.28	74.00	-22.72	peak


Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Band Edge

Standard:	FCC Part 15.247	Test Distance:	3 m
Test item:	Band edge	Power:	DC 5 V
Frequency:	2402 MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60 %RH
Mode:	Mode 2		
Ant.Polar.:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2319.680	58.80	-3.08	55.72	74.00	-18.28	peak
2	2319.680	55.13	-3.08	52.05	54.00	-1.95	AVG
3	2337.830	61.19	-2.99	58.20	74.00	-15.80	peak
4	2337.830	55.88	-2.99	52.89	54.00	-1.11	AVG
5	2390.000	48.13	-2.75	45.38	74.00	-28.62	peak
6	2401.740	104.45	-2.70	101.75	--	--	peak

Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3 m
Test item:	Band edge	Power:	DC 5 V
Frequency:	2402 MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60 %RH
Mode:	Mode 2		
Ant.Polar.:	Vertical		



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2337.720	53.55	-2.99	50.56	74.00	-23.44	peak
2	2390.000	45.58	-2.75	42.83	74.00	-31.17	peak
3	2402.400	97.03	-2.70	94.33	--	--	peak


Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.



Standard:	FCC Part 15.247	Test Distance:	3 m
Test item:	Band edge	Power:	DC 5 V
Frequency:	2480 MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60 %RH
Mode:	Mode 2		
Ant.Polar.:	Horizontal		





Standard:	FCC Part 15.247	Test Distance:	3 m
Test item:	Band edge	Power:	DC 5 V
Frequency:	2480 MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60 %RH
Mode:	Mode 2		
Ant.Polar.:	Horizontal		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2480.400	101.53	-2.35	99.18	--	--	peak
2	2483.500	57.76	-2.34	55.42	74.00	-18.58	peak
3	2483.500	45.09	-2.34	42.75	54.00	-11.25	AVG
4	2483.780	62.02	-2.34	59.68	74.00	-14.32	peak
5	2483.780	43.92	-2.34	41.58	54.00	-12.42	AVG
6	2484.040	61.50	-2.33	59.17	74.00	-14.83	peak
7	2484.040	42.89	-2.33	40.56	54.00	-13.44	AVG
8	2484.320	61.58	-2.33	59.25	74.00	-14.75	peak
9	2484.320	42.31	-2.33	39.98	54.00	-14.02	AVG
10	2484.600	61.45	-2.33	59.12	74.00	-14.88	peak
11	2484.600	42.25	-2.33	39.92	54.00	-14.08	AVG
12	2484.980	59.77	-2.33	57.44	74.00	-16.56	peak
13	2484.980	41.84	-2.33	39.51	54.00	-14.49	AVG
14	2485.220	60.69	-2.33	58.36	74.00	-15.64	peak
15	2485.220	41.41	-2.33	39.08	54.00	-14.92	AVG
16	2485.560	59.30	-2.33	56.97	74.00	-17.03	peak
17	2485.560	41.05	-2.33	38.72	54.00	-15.28	AVG


Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.



Standard:	FCC Part 15.247	Test Distance:	3 m
Test item:	Band edge	Power:	DC 5 V
Frequency:	2480 MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60 %RH
Mode:	Mode 2		
Ant.Polar.:	Vertical		





Standard:	FCC Part 15.247	Test Distance:	3 m
Test item:	Band edge	Power:	DC 5 V
Frequency:	2480 MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60 %RH
Mode:	Mode 2		
Ant.Polar.:	Vertical		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2480.380	99.71	-2.35	97.36	--	--	peak
2	2483.500	56.44	-2.34	54.10	74.00	-19.90	peak
3	2483.500	43.21	-2.34	40.87	54.00	-13.13	AVG
4	2483.880	61.42	-2.33	59.09	74.00	-14.91	peak
5	2483.880	41.66	-2.33	39.33	54.00	-14.67	AVG
6	2484.060	60.44	-2.33	58.11	74.00	-15.89	peak
7	2484.060	41.61	-2.33	39.28	54.00	-14.72	AVG
8	2484.520	59.38	-2.33	57.05	74.00	-16.95	peak
9	2484.520	40.80	-2.33	38.47	54.00	-15.53	AVG
10	2485.240	58.47	-2.33	56.14	74.00	-17.86	peak
11	2485.240	40.21	-2.33	37.88	54.00	-16.12	AVG
12	2486.780	54.82	-2.32	52.50	74.00	-21.50	peak
13	2486.780	38.56	-2.32	36.24	54.00	-17.76	AVG

Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

--- END---