



# FCC RF Test Report

**APPLICANT** : LITE-ON Technology Corp.  
**EQUIPMENT** : 802.11 a/b/g/n/ac 2T2R+BT V4.2LE combo module  
**BRAND NAME** : LITE-ON  
**MODEL NAME** : WCBN3510A  
**FCC ID** : PPQ-WCBN3510A  
**STANDARD** : FCC Part 15 Subpart E §15.407  
**CLASSIFICATION** : (NII) Unlicensed National Information Infrastructure

The product was installed into Lenovo Smart Display (Brand Name: Lenovo, Model Name: Lenovo SD-8501F) during test.

The product was received on Feb. 08, 2018 and testing was completed on Apr. 26, 2018. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

Approved by: James Huang / Manager



**Sporton International (Kunshan) Inc.**

**No.3-2 Ping-Xiang Rd, Kunshan Development Zone Kunshan City Jiangsu Province 215335  
China**



## TABLE OF CONTENTS

|                                                      |                                                          |           |
|------------------------------------------------------|----------------------------------------------------------|-----------|
| <b>1</b>                                             | <b>GENERAL DESCRIPTION .....</b>                         | <b>5</b>  |
| 1.1                                                  | Applicant .....                                          | 5         |
| 1.2                                                  | Manufacturer .....                                       | 5         |
| 1.3                                                  | Product Feature of Equipment Under Test .....            | 5         |
| 1.4                                                  | Product Specification of Equipment Under Test .....      | 6         |
| 1.5                                                  | Modification of EUT .....                                | 6         |
| 1.6                                                  | Component List .....                                     | 6         |
| 1.7                                                  | Testing Location .....                                   | 7         |
| 1.8                                                  | Applicable Standards .....                               | 7         |
| <b>2</b>                                             | <b>TEST CONFIGURATION OF EQUIPMENT UNDER TEST .....</b>  | <b>8</b>  |
| 2.1                                                  | Carrier Frequency and Channel .....                      | 8         |
| 2.2                                                  | Test Mode .....                                          | 9         |
| 2.3                                                  | Connection Diagram of Test System .....                  | 10        |
| 2.4                                                  | Support Unit used in test configuration and system ..... | 10        |
| 2.5                                                  | EUT Operation Test Setup .....                           | 10        |
| <b>3</b>                                             | <b>TEST RESULT .....</b>                                 | <b>11</b> |
| 3.1                                                  | Maximum Conducted Output Power Measurement .....         | 11        |
| 3.2                                                  | Unwanted Emissions Measurement .....                     | 12        |
| 3.3                                                  | AC Conducted Emission Measurement .....                  | 17        |
| 3.4                                                  | Automatically Discontinue Transmission .....             | 19        |
| 3.5                                                  | Antenna Requirements .....                               | 20        |
| <b>4</b>                                             | <b>LIST OF MEASURING EQUIPMENT .....</b>                 | <b>21</b> |
| <b>5</b>                                             | <b>UNCERTAINTY OF EVALUATION .....</b>                   | <b>22</b> |
| <b>APPENDIX A. CONDUCTED TEST RESULTS</b>            |                                                          |           |
| <b>APPENDIX B. AC CONDUCTED EMISSION TEST RESULT</b> |                                                          |           |
| <b>APPENDIX C. RADIATED SPURIOUS EMISSION</b>        |                                                          |           |
| <b>APPENDIX D. DUTY CYCLE PLOTS</b>                  |                                                          |           |
| <b>APPENDIX E. SETUP PHOTOGRAPHS</b>                 |                                                          |           |



## REVISION HISTORY

| REPORT NO. | VERSION | DESCRIPTION             | ISSUED DATE   |
|------------|---------|-------------------------|---------------|
| FR880813E  | Rev. 01 | Initial issue of report | Apr. 28, 2018 |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |

## SUMMARY OF TEST RESULT

| Report Section                                                                                   | FCC Rule           | Description                            | Limit                       | Result | Remark                                    |
|--------------------------------------------------------------------------------------------------|--------------------|----------------------------------------|-----------------------------|--------|-------------------------------------------|
| -                                                                                                | 15.403(i)          | 6dB, 26dB and 99% Occupied Bandwidth   | > 500kHz                    | Pass   | 1                                         |
| 3.1                                                                                              | 15.407(a)          | Maximum Conducted Output Power         | ≤ 30 dBm                    | Pass   | -                                         |
| -                                                                                                | 15.407(a)          | Power Spectral Density                 | ≤ 30 dBm/500kHz             | Pass   | 1                                         |
| 3.2                                                                                              | 15.407(b)          | Unwanted Emissions                     | 15.407(b)(4)(i) & 15.209(a) | Pass   | Under limit<br>3.29 dB at<br>11650.00 MHz |
| 3.3                                                                                              | 15.207             | AC Conducted Emission                  | 15.207(a)                   | Pass   | Under limit<br>18.18 dB at<br>0.479 MHz   |
| 3.4                                                                                              | 15.407(c)          | Automatically Discontinue Transmission | Discontinue Transmission    | Pass   | -                                         |
| 3.5                                                                                              | 15.203 & 15.407(a) | Antenna Requirement                    | N/A                         | Pass   | -                                         |
| <b>Remark:</b><br>1. All conducted test items were leveraged from module RF report "FR7N1336AN". |                    |                                        |                             |        |                                           |

# 1 General Description

## 1.1 Applicant

LITE-ON Technology Corp.

Bldg. C, 90, Chien 1 Road, Chung Ho, New Taipei City 23585, Taiwan, R.O.C

## 1.2 Manufacturer

LITE-ON TECHNOLOGY (Changzhou) CO., LTD

A9 Building, No.88 Yanghu Road, Wujin Hi-Tech Industrial Development Zone, Changzhou City, Jiangsu Province 213100 China

## 1.3 Product Feature of Equipment Under Test

| Product Feature & Specification |                                                                                                                                                                                         |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Equipment                       | 802.11 a/b/g/n/ac 2T2R+BT V4.2LE combo module                                                                                                                                           |
| Brand Name                      | LITE-ON                                                                                                                                                                                 |
| Model Name                      | WCBN3510A                                                                                                                                                                               |
| FCC ID                          | PPQ-WCBN3510A                                                                                                                                                                           |
| EUT supports Radios application | WLAN 2.4GHz 802.11b/g/n HT20/HT40<br>WLAN 2.4GHz 802.11ac VHT20/VHT40<br>WLAN 5GHz 802.11a/n HT20/HT40<br>WLAN 5GHz 802.11ac VHT20/VHT40/VHT80<br>Bluetooth v2.1+EDR, Bluetooth v4.2 LE |
| EUT Stage                       | Identical Prototype                                                                                                                                                                     |

| Host Feature & Specification |                                                                                                                                                           |
|------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Equipment                    | Lenovo Smart Display                                                                                                                                      |
| Brand Name                   | Lenovo                                                                                                                                                    |
| Model Name                   | Lenovo SD-8501F                                                                                                                                           |
| Applicant                    | <b>Lenovo (Shanghai) Electronics Technology Co., Ltd.</b><br>NO.68 BUILDING, 199 FENJU RD, China (Shanghai) Pilot Free Trade Zone, Shanghai, 200131 China |
| Manufacturer                 | <b>Lenovo PC HK Limited</b><br>23/F, Lincoln House, Taikoo Place, 979 King's Road, Quarry Bay Hong Kong                                                   |

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

## 1.4 Product Specification of Equipment Under Test

| Standards-related Product Specification |                                                                                                                                                                                                                                                                                                              |               |               |
|-----------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|---------------|
| <b>Tx/Rx Channel Frequency Range</b>    | 5745 MHz ~ 5825 MHz                                                                                                                                                                                                                                                                                          |               |               |
| <b>Maximum Output Power</b>             | <b>MIMO &lt;Ant. 1 + 2&gt;</b><br><b>&lt;5745 MHz ~ 5825 MHz&gt;</b><br>802.11a : 24.70 dBm / 0.2951 W<br>802.11n HT20 : 24.60 dBm / 0.2884 W<br>802.11n HT40 : 24.06 dBm / 0.2547 W<br>802.11ac VHT20: 24.64 dBm / 0.2911 W<br>802.11ac VHT40: 24.08 dBm / 0.2559 W<br>802.11ac VHT80: 21.81 dBm / 0.1517 W |               |               |
| <b>Type of Modulation</b>               | 802.11a/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)<br>802.11ac : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)                                                                                                                                                                                                     |               |               |
| <b>Antenna Type / Gain</b>              | <Ant. 1> : PIFA Antenna with gain 3.81 dBi<br><Ant. 2> : PIFA Antenna with gain 4.13 dBi                                                                                                                                                                                                                     |               |               |
| <b>Antenna Function Description</b>     |                                                                                                                                                                                                                                                                                                              | <b>Ant. 1</b> | <b>Ant. 2</b> |
|                                         | 802.11 a/n/ac SISO                                                                                                                                                                                                                                                                                           | V             | V             |
|                                         | 802.11 a/n/ac MIMO                                                                                                                                                                                                                                                                                           | V             | V             |

**Note:**

- For 802.11n HT20 / ac VHT20 and 802.11n HT40 / ac VHT40 mode, the whole testing has assessed only 802.11ac VHT20/ VHT40 by referring to their maximum conducted power.
- For 802.11n/ac SISO & MIMO mode, the whole testing has assessed only MIMO mode by referring to their higher conducted power.

## 1.5 Component List

| Object      | Specifications                                | Supplier |
|-------------|-----------------------------------------------|----------|
| CPU         | APQ-8053-A-792NSP-MT-01-1-AA                  | Qualcomm |
| Memory      | EMMC04G-M627X02U ( 4G+32G )                   | Kingston |
| PANEL       | P080DDD-AB4 W134.2*H202.05*3.5MM 800*RGB*1280 | longhai  |
| Camera      | CBFH53520004950LH 2592*1994 megapixel         | chicony  |
| loudspeaker | 1.75" 6Ω 10W fullrange driver                 | sanfu    |
| PCB         | L102*W91*T0.8MM 94V0                          | tripod   |
| Module      | WCBN3510A QCA9379-3 WIFI and Bluetooth combo  | Liteon   |

## 1.6 Modification of EUT

No modifications are made to the EUT during all test items.



## 1.7 Testing Location

Sporton International (Kunshan) Inc. is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600155-0) and the FCC designation No. is CN5013.

|                           |                                                                                                                                               |           |         |                                       |
|---------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|-----------|---------|---------------------------------------|
| <b>Test Site</b>          | Sporton International (Kunshan) Inc.                                                                                                          |           |         |                                       |
| <b>Test Site Location</b> | No.3-2 Ping-Xiang Rd, Kunshan Development Zone Kunshan City Jiangsu Province 215335 China<br>TEL : +86-512-57900158<br>FAX : +86-512-57900958 |           |         |                                       |
| <b>Test Site No.</b>      | <b>Sporton Site No.</b>                                                                                                                       |           |         | <b>FCC Test Firm Registration No.</b> |
|                           | TH01-KS                                                                                                                                       | 03CH03-KS | CO01-KS | 630927                                |

**Note:** The test site complies with ANSI C63.4 2014 requirement.

## 1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart E
- FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ANSI C63.10-2013

### Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

## 2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst (Y plane) cases were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

### 2.1 Carrier Frequency and Channel

| Frequency Band                       | Channel          | Freq.<br>(MHz) | Channel | Freq.<br>(MHz) |
|--------------------------------------|------------------|----------------|---------|----------------|
| 5725-5850 MHz<br>Band 4<br>(U-NII-3) | 149              | 5745           | 157     | 5785           |
|                                      | 151*             | 5755           | 159*    | 5795           |
|                                      | 153              | 5765           | 161     | 5805           |
|                                      | 155 <sup>#</sup> | 5775           | 165     | 5825           |

**Note:**

1. The above Frequency and Channel in "\*" were 802.11n HT40 and 802.11ac VHT40.
2. The above Frequency and Channel in "<sup>#</sup>" were 802.11ac VHT80.

## 2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.


### MIMO Mode

| Modulation     | Data Rate |
|----------------|-----------|
| 802.11a        | 6 Mbps    |
| 802.11ac VHT20 | MCS0      |
| 802.11ac VHT40 | MCS0      |
| 802.11ac VHT80 | MCS0      |

| Test Cases                                                                                                                                                                          |                                                                                                                   |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------|
| <b>AC Conducted Emission</b>                                                                                                                                                        | Mode 1 : <b>Bluetooth Idle + WLAN Link(5G) + Adapter 1</b><br>Mode 2 : Bluetooth Idle + WLAN Link(5G) + Adapter 2 |
| <b>Remark:</b><br>1. The worst case of conducted emission is mode 1; only the test data of it was reported.<br>2. For Radiated Test Cases, The tests were performed with Adapter 1. |                                                                                                                   |

| Ch. # |        | Band IV : 5725-5850 MHz |                |                |                |
|-------|--------|-------------------------|----------------|----------------|----------------|
|       |        | 802.11a                 | 802.11ac VHT20 | 802.11ac VHT40 | 802.11ac VHT80 |
| L     | Low    | 149                     | 149            | 151            | -              |
| M     | Middle | 157                     | 157            | -              | 155            |
| H     | High   | 165                     | 165            | 159            | -              |

## 2.3 Connection Diagram of Test System



## 2.4 Support Unit used in test configuration and system

| Item | Equipment          | Trade Name | Model Name | FCC ID         | Data Cable | Power Cord                                                |
|------|--------------------|------------|------------|----------------|------------|-----------------------------------------------------------|
| 1.   | WLAN AP            | LINKSYS    | WRT600N    | Q87-WRT600NV11 | N/A        | shielded cable DC O/P 1.8m , Unshielded AC I/P 1.8m       |
| 2.   | Bluetooth Earphone | Lenovo     | LBH308     | N/A            | N/A        | N/A                                                       |
| 3.   | SD Card            | Kingston   | SDC4/4GB   | N/A            | N/A        | N/A                                                       |
| 4.   | Notebook           | Lenovo     | G480       | PRC4           | N/A        | shielded cable DC O/P 1.8m , Unshielded AC I/P cable 1.8m |

## 2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

### 3 Test Result

#### 3.1 Maximum Conducted Output Power Measurement

##### 3.1.1 Limit of Maximum Conducted Output Power

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

##### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


##### 3.1.3 Test Procedures

The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM (Measurement using an RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
3. Measure the average power of the transmitter, and the average power is corrected with duty factor,  $10 \log(1/x)$ , where  $x$  is the duty cycle.

##### 3.1.4 Test Setup



##### 3.1.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.

## 3.2 Unwanted Emissions Measurement

This section is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement.

### 3.2.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5.725-5.85 GHz band:

15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

- (2) Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as below table,

| Frequency<br>(MHz) | Field Strength<br>(microvolts/meter) | Measurement Distance<br>(meters) |
|--------------------|--------------------------------------|----------------------------------|
| 0.009 – 0.490      | 2400/F(kHz)                          | 300                              |
| 0.490 – 1.705      | 24000/F(kHz)                         | 30                               |
| 1.705 – 30.0       | 30                                   | 30                               |
| 30 – 88            | 100                                  | 3                                |
| 88 – 216           | 150                                  | 3                                |
| 216 - 960          | 200                                  | 3                                |
| Above 960          | 500                                  | 3                                |



| EIRP (dBm) | Field Strength at 3m (dBμV/m) |
|------------|-------------------------------|
| - 27       | 68.3                          |

**Note:** The following formula is used to convert the EIRP to field strength.

$$\text{EIRP} = E_{\text{Meas}} + 20\log(d_{\text{Meas}}) - 104.7$$

where

EIRP is the equivalent isotropically radiated power, in dBm

$E_{\text{Meas}}$  is the field strength of the emission at the measurement distance, in dBμV/m

$d_{\text{Meas}}$  is the measurement distance, in m

### 3.2.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

### 3.2.3 Test Procedures


1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.  
Section G) Unwanted emissions measurement.
  - (1) Procedure for Unwanted Emissions Measurements Below 1000MHz
    - RBW = 120 kHz
    - VBW = 300 kHz
    - Detector = Peak
    - Trace mode = max hold
  - (2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz
    - RBW = 1 MHz
    - VBW  $\geq$  3 MHz
    - Detector = Peak
    - Sweep time = auto
    - Trace mode = max hold
  - (3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz
    - RBW = 1 MHz
    - VBW = 10 Hz, when duty cycle is no less than 98 percent.
    - VBW  $\geq$  1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

### 3.2.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



**For radiated emissions above 1GHz**



### 3.2.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

### 3.2.6 Test Result of Radiated Band Edges

Please refer to Appendix C.

### 3.2.7 Duty Cycle

Please refer to Appendix D.

### 3.2.8 Test Result of Unwanted Radiated Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C.

### 3.2.9 Test Result of Radiated Spurious Emission (Simultaneous TX )

Please refer to test report (FR820813D)

### 3.3 AC Conducted Emission Measurement

#### 3.3.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

| Frequency of emission (MHz) | Conducted limit (dBμV) |           |
|-----------------------------|------------------------|-----------|
|                             | Quasi-peak             | Average   |
| 0.15-0.5                    | 66 to 56*              | 56 to 46* |
| 0.5-5                       | 56                     | 46        |
| 5-30                        | 60                     | 50        |

\*Decreases with the logarithm of the frequency.


#### 3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.3.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

### 3.3.4 Test Setup



### 3.3.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



## **3.4 Automatically Discontinue Transmission**

### **3.4.1 Limit of Automatically Discontinue Transmission**

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

### **3.4.2 Measuring Instruments**

The measuring equipment is listed in the section 4 of this test report.

### **3.4.3 Test Result of Automatically Discontinue Transmission**

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.

### 3.5 Antenna Requirements

#### 3.5.1 Standard Applicable

If transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### 3.5.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

#### 3.5.3 Antenna Gain

<CDD Modes >

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

For CDD transmissions, directional gain is calculated as

Directional gain = G<sub>ANT</sub> + Array Gain, where Array Gain is as follows.

For power spectral density (PSD) measurements on all devices,

Array Gain = 10 log(NANT/NSS=1) dB.

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for NANT ≤ 4.

Directional gain may be calculated by using the formulas applicable to equal gain antennas with G<sub>ANT</sub> set equal to the gain of the antenna having the highest gain;

The EUT supports CDD mode.

For power, the directional gain G<sub>ANT</sub> is set equal to the antenna having the highest gain, i.e., F)2)f)i).

For PSD, the directional gain calculation is following F)2)f)ii) of KDB 662911 D01 v02r01.

The power and PSD limit should be modified if the directional gain of EUT is over 6 dBi,

The directional gain "DG" is calculated as following table.

| <CDD Modes> |                 |                 |                             |                           |                                     |                                   |
|-------------|-----------------|-----------------|-----------------------------|---------------------------|-------------------------------------|-----------------------------------|
|             |                 |                 | DG<br>for<br>Power<br>(dBi) | DG<br>for<br>PSD<br>(dBi) | Power<br>Limit<br>Reduction<br>(dB) | PSD<br>Limit<br>Reduction<br>(dB) |
|             | Ant. 1<br>(dBi) | Ant. 2<br>(dBi) |                             |                           |                                     |                                   |
| Band IV     | 3.81            | 4.13            | 4.13                        | 6.98                      | 0.00                                | 0.98                              |

*Power Limit Reduction = DG(Power) – 6dBi, ( min = 0 )*

*PSD Limit Reduction = DG(PSD) – 6dBi, ( min = 0 )*



## 4 List of Measuring Equipment

| Instrument                           | Manufacturer | Model No.               | Serial No.  | Characteristics         | Calibration Date | Test Date     | Due Date      | Remark                |
|--------------------------------------|--------------|-------------------------|-------------|-------------------------|------------------|---------------|---------------|-----------------------|
| Pulse Power Sensor                   | Anritsu      | MA2411B                 | 0917070     | 300MHz~40GHz            | Jan. 18, 2018    | Apr. 16, 2018 | Jan. 17, 2019 | Conducted (TH01-KS)   |
| Power Meter                          | Anritsu      | ML2495A                 | 1005002     | 50MHz Bandwidth         | Jan. 18, 2018    | Apr. 16, 2018 | Jan. 17, 2019 | Conducted (TH01-KS)   |
| Spectrum Analyzer                    | R&S          | FSV40                   | 101040      | 10Hz~40GHz              | Aug. 08, 2017    | Apr. 16, 2018 | Aug. 07, 2018 | Conducted (TH01-KS)   |
| EMI Receiver                         | R&S          | ESCI7                   | 100768      | 9kHz~7GHz;              | Apr. 20, 2017    | Mar. 29, 2018 | Apr. 19, 2018 | Conduction (CO01-KS)  |
| AC LISN                              | MessTec      | AN3016                  | 060103      | 9kHz~30MHz              | Oct. 13, 2017    | Mar. 29, 2018 | Oct. 12, 2018 | Conduction (CO01-KS)  |
| AC LISN<br>(for auxiliary equipment) | MessTec      | AN3016                  | 060105      | 9kHz~30MHz              | Oct. 13, 2017    | Mar. 29, 2018 | Oct. 12, 2018 | Conduction (CO01-KS)  |
| AC Power Source                      | Chroma       | 61602                   | ABP00000811 | AC 0V~300V, 45Hz~1000Hz | Oct. 12, 2017    | Mar. 29, 2018 | Oct. 11, 2018 | Conduction (CO01-KS)  |
| EMI Test Receiver                    | Keysight     | N9038A                  | MY56400004  | 3Hz~8.5GHz; Max 30dBm   | Oct. 19, 2017    | Apr. 26, 2018 | Oct. 18, 2018 | Radiation (03CH03-KS) |
| EXA Spectrum Analyzer                | Keysight     | N9010A                  | MY55150244  | 10Hz~44GHz              | Apr. 17, 2018    | Apr. 26, 2018 | Apr. 16, 2019 | Radiation (03CH03-KS) |
| Loop Antenna                         | R&S          | HFH2-Z2                 | 100321      | 9kHz~30MHz              | Oct. 22, 2017    | Apr. 26, 2018 | Oct. 21, 2018 | Radiation (03CH03-KS) |
| Bilog Antenna                        | TeseQ        | CBL6112D                | 47610       | 30MHz~1GHz              | Sep. 12, 2017    | Apr. 26, 2018 | Sep. 11, 2018 | Radiation (03CH03-KS) |
| Double Ridge Horn Antenna            | ETS-Lindgren | 3117                    | 75959       | 1GHz~18GHz              | Jan. 21, 2018    | Apr. 26, 2018 | Jan. 20, 2019 | Radiation (03CH03-KS) |
| SHF-EHF Horn                         | Schwarzbeck  | BBHA 9170               | BBHA170249  | 15GHz~40GHz             | Feb. 07, 2018    | Apr. 26, 2018 | Feb. 06, 2019 | Radiation (03CH03-KS) |
| Amplifier                            | com-power    | PA-103A                 | 161069      | 1MHz ~1000MHz / 32 dB   | Apr 17, 2018     | Apr. 26, 2018 | Apr 16, 2019  | Radiation (03CH03-KS) |
| Amplifier                            | MITEQ        | TTA1840-35-HG           | 1887435     | 18~40GHz                | Oct. 12, 2017    | Apr. 26, 2018 | Oct. 11, 2018 | Radiation (03CH03-KS) |
| high gain Amplifier                  | MITEQ        | AMF-7D-0010 1800-30-10P | 2025788     | 1Ghz-18Ghz              | Apr. 17, 2018    | Apr. 26, 2018 | Apr. 16, 2019 | Radiation (03CH03-KS) |
| Amplifier                            | Agilent      | 8449B                   | 3008A02370  | 1GHz~26.5GHz            | Oct. 12, 2017    | Apr. 26, 2018 | Oct. 11, 2018 | Radiation (03CH03-KS) |
| AC Power Source                      | Chroma       | 61601                   | F104090004  | N/A                     | NCR              | Apr. 26, 2018 | NCR           | Radiation (03CH03-KS) |
| Turn Table                           | ChamPro      | EM 1000-T               | 060762-T    | 0~360 degree            | NCR              | Apr. 26, 2018 | NCR           | Radiation (03CH03-KS) |
| Antenna Mast                         | ChamPro      | EM 1000-A               | 060762-A    | 1 m~4 m                 | NCR              | Apr. 26, 2018 | NCR           | Radiation (03CH03-KS) |

NCR: No Calibration Required

## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

|                                                                          |        |
|--------------------------------------------------------------------------|--------|
| Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_c(y)$ ) | 2.3 dB |
|--------------------------------------------------------------------------|--------|

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

|                                                                          |       |
|--------------------------------------------------------------------------|-------|
| Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_c(y)$ ) | 4.5dB |
|--------------------------------------------------------------------------|-------|

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

|                                                                          |       |
|--------------------------------------------------------------------------|-------|
| Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_c(y)$ ) | 4.1dB |
|--------------------------------------------------------------------------|-------|

### Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

|                                                                          |       |
|--------------------------------------------------------------------------|-------|
| Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_c(y)$ ) | 5.0dB |
|--------------------------------------------------------------------------|-------|

**Appendix A. Test Result of Conducted Test Items**


|                |            |                    |       |    |
|----------------|------------|--------------------|-------|----|
| Test Engineer: | Silent Hai | Temperature:       | 21~25 | °C |
| Test Date:     | 2018/4/16  | Relative Humidity: | 51~55 | %  |


**TEST RESULTS DATA**  
**Average Power Table**

| Band IV |           |     |     |             |                  |       |                               |       |       |                                 |       |          |       |  |           |
|---------|-----------|-----|-----|-------------|------------------|-------|-------------------------------|-------|-------|---------------------------------|-------|----------|-------|--|-----------|
| Mod.    | Data Rate | NTX | CH. | Freq. (MHz) | Duty Factor (dB) |       | Average Conducted Power (dBm) |       |       | FCC Conducted Power Limit (dBm) |       | DG (dBi) |       |  | Pass/Fail |
|         |           |     |     |             | Ant 1            | Ant 2 | Ant 1                         | Ant 2 | SUM   | Ant 1                           | Ant 2 | Ant 1    | Ant 2 |  |           |
| 11a     | 6Mbps     | 2   | 149 | 5745        | 0.20             | 0.26  | 21.21                         | 20.84 | 24.04 | 30.00                           |       | 4.13     |       |  | Pass      |
| 11a     | 6Mbps     | 2   | 157 | 5785        | 0.20             | 0.26  | 21.59                         | 21.13 | 24.38 | 30.00                           |       | 4.13     |       |  | Pass      |
| 11a     | 6Mbps     | 2   | 165 | 5825        | 0.20             | 0.26  | 21.99                         | 21.35 | 24.70 | 30.00                           |       | 4.13     |       |  | Pass      |
| HT20    | MCS0      | 2   | 149 | 5745        | 0.25             | 0.25  | 20.97                         | 20.61 | 23.80 | 30.00                           |       | 4.13     |       |  | Pass      |
| HT20    | MCS0      | 2   | 157 | 5785        | 0.25             | 0.25  | 21.41                         | 20.97 | 24.21 | 30.00                           |       | 4.13     |       |  | Pass      |
| HT20    | MCS0      | 2   | 165 | 5825        | 0.25             | 0.25  | 21.93                         | 21.21 | 24.60 | 30.00                           |       | 4.13     |       |  | Pass      |
| HT40    | MCS0      | 2   | 151 | 5755        | 0.49             | 0.43  | 20.94                         | 20.74 | 23.86 | 30.00                           |       | 4.13     |       |  | Pass      |
| HT40    | MCS0      | 2   | 159 | 5795        | 0.49             | 0.43  | 21.40                         | 20.66 | 24.06 | 30.00                           |       | 4.13     |       |  | Pass      |
| VHT20   | MCS0      | 2   | 149 | 5745        | 0.47             | 0.47  | 21.02                         | 20.61 | 23.83 | 30.00                           |       | 4.13     |       |  | Pass      |
| VHT20   | MCS0      | 2   | 157 | 5785        | 0.47             | 0.47  | 21.42                         | 21.09 | 24.27 | 30.00                           |       | 4.13     |       |  | Pass      |
| VHT20   | MCS0      | 2   | 165 | 5825        | 0.47             | 0.47  | 21.92                         | 21.30 | 24.64 | 30.00                           |       | 4.13     |       |  | Pass      |
| VHT40   | MCS0      | 2   | 151 | 5755        | 0.76             | 0.82  | 20.88                         | 20.83 | 23.87 | 30.00                           |       | 4.13     |       |  | Pass      |
| VHT40   | MCS0      | 2   | 159 | 5795        | 0.76             | 0.82  | 21.37                         | 20.74 | 24.08 | 30.00                           |       | 4.13     |       |  | Pass      |
| VHT80   | MCS0      | 2   | 155 | 5775        | 1.52             | 1.48  | 18.99                         | 18.61 | 21.81 | 30.00                           |       | 4.13     |       |  | Pass      |



## Appendix B. AC Conducted Emission Test Results







## Appendix C. Radiated Spurious Emission

### Band 4 - 5725~5850MHz

#### WIFI 802.11a (Band Edge @ 3m)

| WIFI Ant.                    | Note | Frequency | Level      | Over Limit | Limit Line | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Ant Pos | Table Pos | Peak Avg. | Pol.    |
|------------------------------|------|-----------|------------|------------|------------|------------|----------------|------------|---------------|---------|-----------|-----------|---------|
| 1+2                          |      | ( MHz )   | ( dBμV/m ) | ( dB )     | ( dBμV/m ) | ( dBμV )   | ( dB/m )       | ( dB )     | ( dB )        | ( cm )  | ( deg )   | ( P/A )   | ( H/V ) |
| 802.11a<br>CH 149<br>5745MHz |      | 5646.8    | 54.11      | -14.19     | 68.3       | 43.72      | 35             | 8.56       | 33.17         | 147     | 32        | P         | H       |
|                              |      | 5696.4    | 70.59      | -32.06     | 102.65     | 60.24      | 34.95          | 8.57       | 33.17         | 147     | 32        | P         | H       |
|                              |      | 5716.4    | 83.43      | -26.46     | 109.89     | 73.08      | 34.94          | 8.58       | 33.17         | 147     | 32        | P         | H       |
|                              |      | 5724.8    | 91.4       | -30.44     | 121.84     | 81.07      | 34.92          | 8.58       | 33.17         | 147     | 32        | P         | H       |
|                              |      | 5740      | 118.51     | -          | -          | 108.18     | 34.91          | 8.59       | 33.17         | 147     | 32        | P         | H       |
|                              |      | 5740      | 111.13     | -          | -          | 100.8      | 34.91          | 8.59       | 33.17         | 147     | 32        | A         | H       |
|                              |      | 5636.4    | 52.87      | -15.43     | 68.3       | 42.48      | 35             | 8.56       | 33.17         | 111     | 348       | P         | V       |
|                              |      | 5696      | 65.42      | -36.93     | 102.35     | 55.07      | 34.95          | 8.57       | 33.17         | 111     | 348       | P         | V       |
|                              |      | 5720      | 78.19      | -32.71     | 110.9      | 67.86      | 34.92          | 8.58       | 33.17         | 111     | 348       | P         | V       |
|                              |      | 5724.8    | 86.92      | -34.92     | 121.84     | 76.59      | 34.92          | 8.58       | 33.17         | 111     | 348       | P         | V       |
|                              |      | 5748      | 117.63     | -          | -          | 107.3      | 34.91          | 8.59       | 33.17         | 111     | 348       | P         | V       |
|                              |      | 5748      | 109.7      | -          | -          | 99.37      | 34.91          | 8.59       | 33.17         | 111     | 348       | A         | V       |



| WIFI<br>Ant.<br>1+2          | Note | Frequency<br>( MHz ) | Level<br>( dBμV/m ) | Over<br>Limit<br>( dB ) | Limit<br>Line<br>( dBμV/m ) | Read<br>Level<br>( dBμV ) | Antenna<br>Factor<br>( dB/m ) | Cable<br>Loss<br>( dB ) | Preamp<br>Factor<br>( dB ) | Ant<br>Pos<br>( cm ) | Table<br>Pos<br>( deg ) | Peak<br>Avg.<br>( P/A ) | Pol.<br>( H/V ) |
|------------------------------|------|----------------------|---------------------|-------------------------|-----------------------------|---------------------------|-------------------------------|-------------------------|----------------------------|----------------------|-------------------------|-------------------------|-----------------|
| 802.11a<br>CH 157<br>5785MHz |      | 5618.4               | 52.47               | -15.83                  | 68.3                        | 42.08                     | 35.01                         | 8.56                    | 33.18                      | 100                  | 27                      | P                       | H               |
|                              |      | 5689.6               | 53.76               | -43.87                  | 97.63                       | 43.41                     | 34.95                         | 8.57                    | 33.17                      | 100                  | 27                      | P                       | H               |
|                              |      | 5719.6               | 58.01               | -52.78                  | 110.79                      | 47.68                     | 34.92                         | 8.58                    | 33.17                      | 100                  | 27                      | P                       | H               |
|                              |      | 5724.4               | 60.77               | -60.16                  | 120.93                      | 50.44                     | 34.92                         | 8.58                    | 33.17                      | 100                  | 27                      | P                       | H               |
|                              |      | 5852.8               | 53.07               | -62.85                  | 115.92                      | 42.81                     | 34.82                         | 8.61                    | 33.17                      | 100                  | 27                      | P                       | H               |
|                              |      | 5857.2               | 52.66               | -57.62                  | 110.28                      | 42.41                     | 34.8                          | 8.62                    | 33.17                      | 100                  | 27                      | P                       | H               |
|                              |      | 5882.4               | 52.48               | -47.32                  | 99.8                        | 42.24                     | 34.8                          | 8.62                    | 33.18                      | 100                  | 27                      | P                       | H               |
|                              |      | 5955.6               | 51.93               | -16.37                  | 68.3                        | 41.69                     | 34.81                         | 8.65                    | 33.22                      | 100                  | 27                      | P                       | H               |
|                              |      | 5786                 | 117.71              | -                       | -                           | 107.42                    | 34.86                         | 8.6                     | 33.17                      | 100                  | 27                      | P                       | H               |
|                              |      | 5786                 | 109.94              | -                       | -                           | 99.65                     | 34.86                         | 8.6                     | 33.17                      | 100                  | 27                      | A                       | H               |
|                              |      | 5634.4               | 51.76               | -16.54                  | 68.3                        | 41.37                     | 35                            | 8.56                    | 33.17                      | 100                  | 329                     | P                       | V               |
|                              |      | 5693.2               | 53.65               | -46.64                  | 100.29                      | 43.3                      | 34.95                         | 8.57                    | 33.17                      | 100                  | 329                     | P                       | V               |
|                              |      | 5718.8               | 56.72               | -53.84                  | 110.56                      | 46.39                     | 34.92                         | 8.58                    | 33.17                      | 100                  | 329                     | P                       | V               |
|                              |      | 5722                 | 61.3                | -54.16                  | 115.46                      | 50.97                     | 34.92                         | 8.58                    | 33.17                      | 100                  | 329                     | P                       | V               |
|                              |      | 5850.8               | 53.35               | -67.13                  | 120.48                      | 43.09                     | 34.82                         | 8.61                    | 33.17                      | 100                  | 329                     | P                       | V               |
|                              |      | 5858                 | 52.33               | -57.73                  | 110.06                      | 42.08                     | 34.8                          | 8.62                    | 33.17                      | 100                  | 329                     | P                       | V               |
|                              |      | 5906.4               | 52.83               | -29.2                   | 82.03                       | 42.58                     | 34.81                         | 8.63                    | 33.19                      | 100                  | 329                     | P                       | V               |
|                              |      | 5936.4               | 52.6                | -15.7                   | 68.3                        | 42.35                     | 34.81                         | 8.64                    | 33.2                       | 100                  | 329                     | P                       | V               |
|                              |      | 5782                 | 116                 | -                       | -                           | 105.69                    | 34.88                         | 8.6                     | 33.17                      | 100                  | 329                     | P                       | V               |
|                              |      | 5782                 | 107.9               | -                       | -                           | 97.59                     | 34.88                         | 8.6                     | 33.17                      | 100                  | 329                     | A                       | V               |



| WIFI<br>Ant.<br>1+2          | Note                                                                                        | Frequency<br>( MHz ) | Level<br>( dBμV/m ) | Over<br>Limit<br>( dB ) | Limit<br>Line<br>( dBμV/m ) | Read<br>Level<br>( dBμV ) | Antenna<br>Factor<br>( dB/m ) | Cable<br>Loss<br>( dB ) | Preamp<br>Factor<br>( dB ) | Ant<br>Pos<br>( cm ) | Table<br>Pos<br>( deg ) | Peak<br>Avg.<br>( P/A ) | Pol.<br>( H/V ) |
|------------------------------|---------------------------------------------------------------------------------------------|----------------------|---------------------|-------------------------|-----------------------------|---------------------------|-------------------------------|-------------------------|----------------------------|----------------------|-------------------------|-------------------------|-----------------|
| 802.11a<br>CH 165<br>5825MHz |                                                                                             | 5850                 | 79.47               | -42.83                  | 122.3                       | 69.21                     | 34.82                         | 8.61                    | 33.17                      | 100                  | 35                      | P                       | H               |
|                              |                                                                                             | 5856.4               | 75.25               | -35.26                  | 110.51                      | 65                        | 34.8                          | 8.62                    | 33.17                      | 100                  | 35                      | P                       | H               |
|                              |                                                                                             | 5876.8               | 62.17               | -41.79                  | 103.96                      | 51.93                     | 34.8                          | 8.62                    | 33.18                      | 100                  | 35                      | P                       | H               |
|                              |                                                                                             | 5927.2               | 53.55               | -14.75                  | 68.3                        | 43.3                      | 34.81                         | 8.64                    | 33.2                       | 100                  | 35                      | P                       | H               |
|                              |                                                                                             | 5826                 | 118.78              | -                       | -                           | 108.51                    | 34.83                         | 8.61                    | 33.17                      | 100                  | 35                      | P                       | H               |
|                              |                                                                                             | 5826                 | 110.02              | -                       | -                           | 99.75                     | 34.83                         | 8.61                    | 33.17                      | 100                  | 35                      | A                       | H               |
|                              |                                                                                             | 5850                 | 77.1                | -45.2                   | 122.3                       | 66.84                     | 34.82                         | 8.61                    | 33.17                      | 103                  | 348                     | P                       | V               |
|                              |                                                                                             | 5856                 | 74.21               | -36.41                  | 110.62                      | 63.96                     | 34.8                          | 8.62                    | 33.17                      | 103                  | 348                     | P                       | V               |
|                              |                                                                                             | 5876.4               | 63.19               | -41.07                  | 104.26                      | 52.95                     | 34.8                          | 8.62                    | 33.18                      | 103                  | 348                     | P                       | V               |
|                              |                                                                                             | 5934.4               | 53.59               | -14.71                  | 68.3                        | 43.34                     | 34.81                         | 8.64                    | 33.2                       | 103                  | 348                     | P                       | V               |
|                              |                                                                                             | 5826                 | 117.24              | -                       | -                           | 106.97                    | 34.83                         | 8.61                    | 33.17                      | 103                  | 348                     | P                       | V               |
|                              |                                                                                             | 5826                 | 109.26              | -                       | -                           | 98.99                     | 34.83                         | 8.61                    | 33.17                      | 103                  | 348                     | A                       | V               |
| Remark                       | 1. No other spurious found.<br>2. All results are PASS against Peak and Average limit line. |                      |                     |                         |                             |                           |                               |                         |                            |                      |                         |                         |                 |



## Band 4 5725~5850MHz

## WIFI 802.11a (Harmonic @ 3m)

| WIFI<br>Ant.<br>1+2          | Note                                                                                        | Frequency<br>( MHz ) | Level<br>( dBμV/m ) | Over<br>Limit<br>( dB ) | Limit<br>Line<br>( dBμV/m ) | Read<br>Level<br>( dBμV ) | Antenna<br>Factor<br>( dB/m ) | Cable<br>Loss<br>( dB ) | Preamp<br>Factor<br>( dB ) | Ant<br>Pos<br>( cm ) | Table<br>Pos<br>( deg ) | Peak<br>Avg.<br>( P/A ) | Pol.<br>( H/V ) |
|------------------------------|---------------------------------------------------------------------------------------------|----------------------|---------------------|-------------------------|-----------------------------|---------------------------|-------------------------------|-------------------------|----------------------------|----------------------|-------------------------|-------------------------|-----------------|
| 802.11a<br>CH 149<br>5745MHz |                                                                                             | 11490                | 51.08               | -22.92                  | 74                          | 51.72                     | 39.29                         | 12.91                   | 52.84                      | 100                  | 360                     | P                       | H               |
|                              |                                                                                             | 11490                | 47.57               | -6.43                   | 54                          | 48.21                     | 39.29                         | 12.91                   | 52.84                      | 100                  | 360                     | A                       | H               |
|                              |                                                                                             | 11490                | 53.39               | -20.61                  | 74                          | 54.03                     | 39.29                         | 12.91                   | 52.84                      | 100                  | 360                     | P                       | V               |
|                              |                                                                                             | 11490                | 46.57               | -7.43                   | 54                          | 47.21                     | 39.29                         | 12.91                   | 52.84                      | 100                  | 360                     | A                       | V               |
| 802.11a<br>CH 157<br>5785MHz |                                                                                             | 11570                | 53.96               | -20.04                  | 74                          | 54.77                     | 39.37                         | 12.84                   | 53.02                      | 100                  | 360                     | P                       | H               |
|                              | !                                                                                           | 11570                | 48.14               | -5.86                   | 54                          | 48.95                     | 39.37                         | 12.84                   | 53.02                      | 100                  | 360                     | A                       | H               |
|                              |                                                                                             | 11570                | 53.55               | -20.45                  | 74                          | 54.36                     | 39.37                         | 12.84                   | 53.02                      | 100                  | 360                     | P                       | V               |
|                              | !                                                                                           | 11570                | 48.4                | -5.6                    | 54                          | 49.21                     | 39.37                         | 12.84                   | 53.02                      | 100                  | 360                     | A                       | V               |
| 802.11a<br>CH 165<br>5825MHz |                                                                                             | 11650                | 57.13               | -16.87                  | 74                          | 58.07                     | 39.44                         | 12.78                   | 53.16                      | 100                  | 360                     | P                       | H               |
|                              | !                                                                                           | 11650                | 49.63               | -4.37                   | 54                          | 50.57                     | 39.44                         | 12.78                   | 53.16                      | 100                  | 360                     | A                       | H               |
|                              |                                                                                             | 11655                | 56.64               | -17.36                  | 74                          | 57.61                     | 39.46                         | 12.77                   | 53.2                       | 100                  | 360                     | P                       | V               |
|                              | !                                                                                           | 11655                | 49.41               | -4.59                   | 54                          | 50.38                     | 39.46                         | 12.77                   | 53.2                       | 100                  | 354                     | A                       | V               |
| Remark                       | 1. No other spurious found.<br>2. All results are PASS against Peak and Average limit line. |                      |                     |                         |                             |                           |                               |                         |                            |                      |                         |                         |                 |



**Band 4 5725~5850MHz**  
**WIFI 802.11ac VHT20 (Band Edge @ 3m)**

| WIFI<br>Ant.<br>1+2                    | Note | Frequency<br>( MHz ) | Level<br>( dBμV/m ) | Over<br>Limit<br>( dB ) | Limit<br>Line<br>( dBμV/m ) | Read<br>Level<br>( dBμV ) | Antenna<br>Factor<br>( dB/m ) | Cable<br>Loss<br>( dB ) | Preamp<br>Factor<br>( dB ) | Ant<br>Pos<br>( cm ) | Table<br>Pos<br>( deg ) | Peak<br>Avg.<br>( P/A ) | Pol.<br>( H/V ) |
|----------------------------------------|------|----------------------|---------------------|-------------------------|-----------------------------|---------------------------|-------------------------------|-------------------------|----------------------------|----------------------|-------------------------|-------------------------|-----------------|
| 802.11ac<br>VHT20<br>CH 149<br>5745MHz |      | 5648.8               | 54.57               | -13.73                  | 68.3                        | 44.18                     | 35                            | 8.56                    | 33.17                      | 179                  | 30                      | P                       | H               |
|                                        |      | 5700                 | 69.6                | -35.7                   | 105.3                       | 59.25                     | 34.95                         | 8.57                    | 33.17                      | 179                  | 30                      | P                       | H               |
|                                        |      | 5720                 | 82.94               | -27.96                  | 110.9                       | 72.61                     | 34.92                         | 8.58                    | 33.17                      | 179                  | 30                      | P                       | H               |
|                                        |      | 5724.8               | 89.26               | -32.58                  | 121.84                      | 78.93                     | 34.92                         | 8.58                    | 33.17                      | 179                  | 30                      | P                       | H               |
|                                        |      | 5740                 | 118.99              | -                       | -                           | 108.66                    | 34.91                         | 8.59                    | 33.17                      | 179                  | 30                      | P                       | H               |
|                                        |      | 5740                 | 109.07              | -                       | -                           | 98.74                     | 34.91                         | 8.59                    | 33.17                      | 179                  | 30                      | A                       | H               |
|                                        |      | 5650                 | 54.74               | -13.56                  | 68.3                        | 44.36                     | 34.98                         | 8.57                    | 33.17                      | 112                  | 350                     | P                       | V               |
|                                        |      | 5700                 | 68.47               | -36.83                  | 105.3                       | 58.12                     | 34.95                         | 8.57                    | 33.17                      | 112                  | 350                     | P                       | V               |
|                                        |      | 5719.2               | 79.76               | -30.92                  | 110.68                      | 69.43                     | 34.92                         | 8.58                    | 33.17                      | 112                  | 350                     | P                       | V               |
|                                        |      | 5721.6               | 87.25               | -27.3                   | 114.55                      | 76.92                     | 34.92                         | 8.58                    | 33.17                      | 112                  | 350                     | P                       | V               |
|                                        |      | 5748                 | 116.02              | -                       | -                           | 105.69                    | 34.91                         | 8.59                    | 33.17                      | 112                  | 350                     | P                       | V               |
|                                        |      | 5748                 | 108.13              | -                       | -                           | 97.8                      | 34.91                         | 8.59                    | 33.17                      | 112                  | 350                     | A                       | V               |



| WIFI<br>Ant.<br>1+2                    | Note | Frequency<br>( MHz ) | Level<br>( dBμV/m ) | Over<br>Limit<br>( dB ) | Limit<br>Line<br>( dBμV/m ) | Read<br>Level<br>( dBμV ) | Antenna<br>Factor<br>( dB/m ) | Cable<br>Loss<br>( dB ) | Preamp<br>Factor<br>( dB ) | Ant<br>Pos<br>( cm ) | Table<br>Pos<br>( deg ) | Peak<br>Avg.<br>( P/A ) | Pol.<br>( H/V ) |
|----------------------------------------|------|----------------------|---------------------|-------------------------|-----------------------------|---------------------------|-------------------------------|-------------------------|----------------------------|----------------------|-------------------------|-------------------------|-----------------|
| 802.11ac<br>VHT20<br>CH 157<br>5785MHz |      | 5616.4               | 52.53               | -15.77                  | 68.3                        | 42.14                     | 35.01                         | 8.56                    | 33.18                      | 101                  | 32                      | P                       | H               |
|                                        |      | 5692.8               | 55.43               | -44.56                  | 99.99                       | 45.08                     | 34.95                         | 8.57                    | 33.17                      | 101                  | 32                      | P                       | H               |
|                                        |      | 5719.6               | 57.26               | -53.53                  | 110.79                      | 46.93                     | 34.92                         | 8.58                    | 33.17                      | 101                  | 32                      | P                       | H               |
|                                        |      | 5723.2               | 60.84               | -57.36                  | 118.2                       | 50.51                     | 34.92                         | 8.58                    | 33.17                      | 101                  | 32                      | P                       | H               |
|                                        |      | 5850.4               | 53.51               | -67.88                  | 121.39                      | 43.25                     | 34.82                         | 8.61                    | 33.17                      | 101                  | 32                      | P                       | H               |
|                                        |      | 5868                 | 52.37               | -54.89                  | 107.26                      | 42.12                     | 34.8                          | 8.62                    | 33.17                      | 101                  | 32                      | P                       | H               |
|                                        |      | 5888.4               | 53.07               | -42.28                  | 95.35                       | 42.82                     | 34.8                          | 8.63                    | 33.18                      | 101                  | 32                      | P                       | H               |
|                                        |      | 5930.4               | 51.43               | -16.87                  | 68.3                        | 41.18                     | 34.81                         | 8.64                    | 33.2                       | 101                  | 32                      | P                       | H               |
|                                        |      | 5786                 | 116.54              | -                       | -                           | 106.25                    | 34.86                         | 8.6                     | 33.17                      | 101                  | 32                      | P                       | H               |
|                                        |      | 5786                 | 108.32              | -                       | -                           | 98.03                     | 34.86                         | 8.6                     | 33.17                      | 101                  | 32                      | A                       | H               |
|                                        |      | 5628                 | 53.05               | -15.25                  | 68.3                        | 42.66                     | 35.01                         | 8.56                    | 33.18                      | 100                  | 352                     | P                       | V               |
|                                        |      | 5691.6               | 53.96               | -45.15                  | 99.11                       | 43.61                     | 34.95                         | 8.57                    | 33.17                      | 100                  | 352                     | P                       | V               |
|                                        |      | 5719.2               | 55.89               | -54.79                  | 110.68                      | 45.56                     | 34.92                         | 8.58                    | 33.17                      | 100                  | 352                     | P                       | V               |
|                                        |      | 5724                 | 58.09               | -61.93                  | 120.02                      | 47.76                     | 34.92                         | 8.58                    | 33.17                      | 100                  | 352                     | P                       | V               |
|                                        |      | 5850.8               | 54.96               | -65.52                  | 120.48                      | 44.7                      | 34.82                         | 8.61                    | 33.17                      | 100                  | 352                     | P                       | V               |
|                                        |      | 5856.4               | 52.33               | -58.18                  | 110.51                      | 42.08                     | 34.8                          | 8.62                    | 33.17                      | 100                  | 352                     | P                       | V               |
|                                        |      | 5915.6               | 52.93               | -22.3                   | 75.23                       | 42.68                     | 34.81                         | 8.63                    | 33.19                      | 100                  | 352                     | P                       | V               |
|                                        |      | 5980.8               | 51.89               | -16.41                  | 68.3                        | 41.66                     | 34.81                         | 8.65                    | 33.23                      | 100                  | 352                     | P                       | V               |
|                                        |      | 5786                 | 115.78              | -                       | -                           | 105.49                    | 34.86                         | 8.6                     | 33.17                      | 100                  | 352                     | P                       | V               |
|                                        |      | 5786                 | 107.29              | -                       | -                           | 97                        | 34.86                         | 8.6                     | 33.17                      | 100                  | 352                     | A                       | V               |



| WIFI<br>Ant.<br>1+2                    | Note | Frequency<br>( MHz )                                                                        | Level<br>( dBμV/m ) | Over<br>Limit<br>( dB ) | Limit<br>Line<br>( dBμV/m ) | Read<br>Level<br>( dBμV ) | Antenna<br>Factor<br>( dB/m ) | Cable<br>Loss<br>( dB ) | Preamp<br>Factor<br>( dB ) | Ant<br>Pos<br>( cm ) | Table<br>Pos<br>( deg ) | Peak<br>Avg.<br>( P/A ) | Pol.<br>( H/V ) |
|----------------------------------------|------|---------------------------------------------------------------------------------------------|---------------------|-------------------------|-----------------------------|---------------------------|-------------------------------|-------------------------|----------------------------|----------------------|-------------------------|-------------------------|-----------------|
| 802.11ac<br>VHT20<br>CH 165<br>5825MHz |      | 5850                                                                                        | 78.46               | -43.84                  | 122.3                       | 68.2                      | 34.82                         | 8.61                    | 33.17                      | 117                  | 5                       | P                       | H               |
|                                        |      | 5858                                                                                        | 72.08               | -37.98                  | 110.06                      | 61.83                     | 34.8                          | 8.62                    | 33.17                      | 117                  | 5                       | P                       | H               |
|                                        |      | 5877.6                                                                                      | 59.64               | -43.73                  | 103.37                      | 49.4                      | 34.8                          | 8.62                    | 33.18                      | 117                  | 5                       | P                       | H               |
|                                        |      | 5977.2                                                                                      | 53.03               | -15.27                  | 68.3                        | 42.8                      | 34.81                         | 8.65                    | 33.23                      | 117                  | 5                       | P                       | H               |
|                                        |      | 5824                                                                                        | 115.97              | -                       | -                           | 105.7                     | 34.83                         | 8.61                    | 33.17                      | 117                  | 5                       | P                       | H               |
|                                        |      | 5824                                                                                        | 107.29              | -                       | -                           | 97.02                     | 34.83                         | 8.61                    | 33.17                      | 117                  | 5                       | A                       | H               |
|                                        |      | 5850.8                                                                                      | 79.32               | -41.16                  | 120.48                      | 69.06                     | 34.82                         | 8.61                    | 33.17                      | 100                  | 349                     | P                       | V               |
|                                        |      | 5855.6                                                                                      | 76.09               | -34.64                  | 110.73                      | 65.84                     | 34.8                          | 8.62                    | 33.17                      | 100                  | 349                     | P                       | V               |
|                                        |      | 5877.2                                                                                      | 59.91               | -43.76                  | 103.67                      | 49.67                     | 34.8                          | 8.62                    | 33.18                      | 100                  | 349                     | P                       | V               |
|                                        |      | 5990                                                                                        | 52.47               | -15.83                  | 68.3                        | 42.22                     | 34.82                         | 8.66                    | 33.23                      | 100                  | 349                     | P                       | V               |
|                                        |      | 5824                                                                                        | 114.65              | -                       | -                           | 104.38                    | 34.83                         | 8.61                    | 33.17                      | 100                  | 349                     | P                       | V               |
|                                        |      | 5824                                                                                        | 106.4               | -                       | -                           | 96.13                     | 34.83                         | 8.61                    | 33.17                      | 100                  | 349                     | A                       | V               |
| Remark                                 |      | 1. No other spurious found.<br>2. All results are PASS against Peak and Average limit line. |                     |                         |                             |                           |                               |                         |                            |                      |                         |                         |                 |



## Band 4 5725~5850MHz

## WIFI 802.11ac VHT20 (Harmonic @ 3m)

| WIFI<br>Ant.<br>1+2 | Note                                                                                        | Frequency<br>( MHz ) | Level<br>( dBμV/m ) | Over<br>Limit<br>( dB ) | Limit<br>Line<br>( dBμV/m ) | Read<br>Level<br>( dBμV ) | Antenna<br>Factor<br>( dB/m ) | Cable<br>Loss<br>( dB ) | Preamp<br>Factor<br>( dB ) | Ant<br>Pos<br>( cm ) | Table<br>Pos<br>( deg ) | Peak<br>Avg.<br>( P/A ) | Pol.<br>( H/V ) |
|---------------------|---------------------------------------------------------------------------------------------|----------------------|---------------------|-------------------------|-----------------------------|---------------------------|-------------------------------|-------------------------|----------------------------|----------------------|-------------------------|-------------------------|-----------------|
| 802.11ac            |                                                                                             | 11490                | 51.49               | -22.51                  | 74                          | 52.13                     | 39.29                         | 12.91                   | 52.84                      | 100                  | 360                     | P                       | H               |
| VHT20               |                                                                                             | 11490                | 47.57               | -6.43                   | 54                          | 48.21                     | 39.29                         | 12.91                   | 52.84                      | 100                  | 360                     | A                       | H               |
| CH 149              |                                                                                             | 11490                | 52.82               | -21.18                  | 74                          | 53.46                     | 39.29                         | 12.91                   | 52.84                      | 100                  | 360                     | P                       | V               |
| 5745MHz             |                                                                                             | 11490                | 46.5                | -7.5                    | 54                          | 47.14                     | 39.29                         | 12.91                   | 52.84                      | 100                  | 360                     | A                       | V               |
| 802.11ac            |                                                                                             | 11570                | 55.55               | -18.45                  | 74                          | 56.36                     | 39.37                         | 12.84                   | 53.02                      | 100                  | 214                     | P                       | H               |
| VHT20               | !                                                                                           | 11570                | 48.43               | -5.57                   | 54                          | 49.24                     | 39.37                         | 12.84                   | 53.02                      | 100                  | 214                     | A                       | H               |
| CH 157              |                                                                                             | 11570                | 55.93               | -18.07                  | 74                          | 56.74                     | 39.37                         | 12.84                   | 53.02                      | 100                  | 360                     | P                       | V               |
| 5785MHz             | !                                                                                           | 11570                | 48.95               | -5.05                   | 54                          | 49.76                     | 39.37                         | 12.84                   | 53.02                      | 100                  | 360                     | A                       | V               |
| 802.11ac            |                                                                                             | 11650                | 55.7                | -18.3                   | 74                          | 56.64                     | 39.44                         | 12.78                   | 53.16                      | 100                  | 360                     | P                       | H               |
| VHT20               | !                                                                                           | 11650                | 48.85               | -5.15                   | 54                          | 49.79                     | 39.44                         | 12.78                   | 53.16                      | 100                  | 360                     | A                       | H               |
| CH 165              |                                                                                             | 11650                | 54.99               | -19.01                  | 74                          | 55.93                     | 39.44                         | 12.78                   | 53.16                      | 100                  | 346                     | P                       | V               |
| 5825MHz             | !                                                                                           | 11650                | 50.71               | -3.29                   | 54                          | 51.65                     | 39.44                         | 12.78                   | 53.16                      | 100                  | 346                     | A                       | V               |
| Remark              | 1. No other spurious found.<br>2. All results are PASS against Peak and Average limit line. |                      |                     |                         |                             |                           |                               |                         |                            |                      |                         |                         |                 |



**Band 4 5725~5850MHz**  
**WIFI 802.11ac VHT40 (Band Edge @ 3m)**

| WIFI<br>Ant.<br>1+2                              | Note | Frequency<br>( MHz ) | Level<br>( dBμV/m ) | Over<br>Limit<br>( dB ) | Limit<br>Line<br>( dBμV/m ) | Read<br>Level<br>( dBμV ) | Antenna<br>Factor<br>( dB/m ) | Cable<br>Loss<br>( dB ) | Preamp<br>Factor<br>( dB ) | Ant<br>Pos<br>( cm ) | Table<br>Pos<br>( deg ) | Peak<br>Avg.<br>( P/A ) | Pol.<br>( H/V ) |
|--------------------------------------------------|------|----------------------|---------------------|-------------------------|-----------------------------|---------------------------|-------------------------------|-------------------------|----------------------------|----------------------|-------------------------|-------------------------|-----------------|
| <b>802.11ac<br/>VHT40<br/>CH 151<br/>5755MHz</b> |      | 5650                 | 61.55               | -6.75                   | 68.3                        | 51.17                     | 34.98                         | 8.57                    | 33.17                      | 100                  | 35                      | P                       | H               |
|                                                  |      | 5699.2               | 72.15               | -32.56                  | 104.71                      | 61.8                      | 34.95                         | 8.57                    | 33.17                      | 100                  | 35                      | P                       | H               |
|                                                  |      | 5720                 | 87.23               | -23.67                  | 110.9                       | 76.9                      | 34.92                         | 8.58                    | 33.17                      | 100                  | 35                      | P                       | H               |
|                                                  |      | 5722.4               | 91.06               | -25.31                  | 116.37                      | 80.73                     | 34.92                         | 8.58                    | 33.17                      | 100                  | 35                      | P                       | H               |
|                                                  |      | 5854.8               | 64.55               | -46.81                  | 111.36                      | 54.3                      | 34.8                          | 8.62                    | 33.17                      | 100                  | 35                      | P                       | H               |
|                                                  |      | 5868.8               | 56.9                | -50.13                  | 107.03                      | 46.65                     | 34.8                          | 8.62                    | 33.17                      | 100                  | 35                      | P                       | H               |
|                                                  |      | 5886.8               | 62.48               | -34.06                  | 96.54                       | 52.24                     | 34.8                          | 8.62                    | 33.18                      | 100                  | 35                      | P                       | H               |
|                                                  |      | 5945.2               | 60.27               | -8.03                   | 68.3                        | 50.03                     | 34.81                         | 8.64                    | 33.21                      | 100                  | 35                      | P                       | H               |
|                                                  |      | 5752                 | 113.84              | -                       | -                           | 103.53                    | 34.89                         | 8.59                    | 33.17                      | 100                  | 35                      | P                       | H               |
|                                                  |      | 5752                 | 105.36              | -                       | -                           | 95.05                     | 34.89                         | 8.59                    | 33.17                      | 100                  | 35                      | A                       | H               |
|                                                  | !    | 5649.6               | 62.34               | -5.96                   | 68.3                        | 51.96                     | 34.98                         | 8.57                    | 33.17                      | 114                  | 335                     | P                       | V               |
|                                                  |      | 5680.4               | 69.85               | -20.98                  | 90.83                       | 59.48                     | 34.97                         | 8.57                    | 33.17                      | 114                  | 335                     | P                       | V               |
|                                                  |      | 5718.8               | 84.79               | -25.77                  | 110.56                      | 74.46                     | 34.92                         | 8.58                    | 33.17                      | 114                  | 335                     | P                       | V               |
|                                                  |      | 5723.2               | 88.72               | -29.48                  | 118.2                       | 78.39                     | 34.92                         | 8.58                    | 33.17                      | 114                  | 335                     | P                       | V               |
|                                                  |      | 5852                 | 52.84               | -64.9                   | 117.74                      | 42.58                     | 34.82                         | 8.61                    | 33.17                      | 114                  | 335                     | P                       | V               |
|                                                  |      | 5856.4               | 61.96               | -48.55                  | 110.51                      | 51.71                     | 34.8                          | 8.62                    | 33.17                      | 114                  | 335                     | P                       | V               |
|                                                  |      | 5890.4               | 58.74               | -35.13                  | 93.87                       | 48.49                     | 34.8                          | 8.63                    | 33.18                      | 114                  | 335                     | P                       | V               |
|                                                  |      | 5948.8               | 55.72               | -12.58                  | 68.3                        | 45.48                     | 34.81                         | 8.64                    | 33.21                      | 114                  | 335                     | P                       | V               |
|                                                  |      | 5748                 | 111.67              | -                       | -                           | 101.34                    | 34.91                         | 8.59                    | 33.17                      | 114                  | 335                     | P                       | V               |
|                                                  |      | 5748                 | 103.58              | -                       | -                           | 93.25                     | 34.91                         | 8.59                    | 33.17                      | 114                  | 335                     | A                       | V               |



| WIFI<br>Ant.<br>1+2                    | Note                                                                                        | Frequency<br>( MHz ) | Level<br>( dBμV/m ) | Over<br>Limit<br>( dB ) | Limit<br>Line<br>( dBμV/m ) | Read<br>Level<br>( dBμV ) | Antenna<br>Factor<br>( dB/m ) | Cable<br>Loss<br>( dB ) | Preamp<br>Factor<br>( dB ) | Ant<br>Pos<br>( cm ) | Table<br>Pos<br>( deg ) | Peak<br>Avg.<br>( P/A ) | Pol.<br>( H/V ) |
|----------------------------------------|---------------------------------------------------------------------------------------------|----------------------|---------------------|-------------------------|-----------------------------|---------------------------|-------------------------------|-------------------------|----------------------------|----------------------|-------------------------|-------------------------|-----------------|
| 802.11ac<br>VHT40<br>CH 159<br>5795MHz | !                                                                                           | 5646.4               | 64.27               | -4.03                   | 68.3                        | 53.88                     | 35                            | 8.56                    | 33.17                      | 104                  | 33                      | P                       | H               |
|                                        |                                                                                             | 5655.2               | 63.87               | -8.29                   | 72.16                       | 53.49                     | 34.98                         | 8.57                    | 33.17                      | 104                  | 33                      | P                       | H               |
|                                        |                                                                                             | 5718.4               | 66.32               | -44.13                  | 110.45                      | 55.99                     | 34.92                         | 8.58                    | 33.17                      | 104                  | 33                      | P                       | H               |
|                                        |                                                                                             | 5721.6               | 68.05               | -46.5                   | 114.55                      | 57.72                     | 34.92                         | 8.58                    | 33.17                      | 104                  | 33                      | P                       | H               |
|                                        |                                                                                             | 5851.2               | 68.51               | -51.05                  | 119.56                      | 58.25                     | 34.82                         | 8.61                    | 33.17                      | 104                  | 33                      | P                       | H               |
|                                        |                                                                                             | 5859.2               | 68.08               | -41.64                  | 109.72                      | 57.83                     | 34.8                          | 8.62                    | 33.17                      | 104                  | 33                      | P                       | H               |
|                                        |                                                                                             | 5897.2               | 60.8                | -28.03                  | 88.83                       | 50.55                     | 34.8                          | 8.63                    | 33.18                      | 104                  | 33                      | P                       | H               |
|                                        |                                                                                             | 5935.6               | 60.41               | -7.89                   | 68.3                        | 50.16                     | 34.81                         | 8.64                    | 33.2                       | 104                  | 33                      | P                       | H               |
|                                        |                                                                                             | 5792                 | 113.58              | -                       | -                           | 103.29                    | 34.86                         | 8.6                     | 33.17                      | 104                  | 33                      | P                       | H               |
|                                        |                                                                                             | 5792                 | 104.92              | -                       | -                           | 94.63                     | 34.86                         | 8.6                     | 33.17                      | 104                  | 33                      | A                       | H               |
|                                        |                                                                                             | 5624                 | 57.56               | -10.74                  | 68.3                        | 47.17                     | 35.01                         | 8.56                    | 33.18                      | 100                  | 349                     | P                       | V               |
|                                        |                                                                                             | 5692                 | 64.52               | -34.88                  | 99.4                        | 54.17                     | 34.95                         | 8.57                    | 33.17                      | 100                  | 349                     | P                       | V               |
|                                        |                                                                                             | 5720                 | 66.08               | -44.82                  | 110.9                       | 55.75                     | 34.92                         | 8.58                    | 33.17                      | 100                  | 349                     | P                       | V               |
|                                        |                                                                                             | 5723.2               | 69.32               | -48.88                  | 118.2                       | 58.99                     | 34.92                         | 8.58                    | 33.17                      | 100                  | 349                     | P                       | V               |
|                                        |                                                                                             | 5851.6               | 65.97               | -52.68                  | 118.65                      | 55.71                     | 34.82                         | 8.61                    | 33.17                      | 100                  | 349                     | P                       | V               |
|                                        |                                                                                             | 5856.4               | 66.64               | -43.87                  | 110.51                      | 56.39                     | 34.8                          | 8.62                    | 33.17                      | 100                  | 349                     | P                       | V               |
|                                        |                                                                                             | 5878.8               | 60.16               | -42.32                  | 102.48                      | 49.92                     | 34.8                          | 8.62                    | 33.18                      | 100                  | 349                     | P                       | V               |
|                                        |                                                                                             | 5994                 | 58.58               | -9.72                   | 68.3                        | 48.33                     | 34.82                         | 8.66                    | 33.23                      | 100                  | 349                     | P                       | V               |
|                                        |                                                                                             | 5800                 | 112.19              | -                       | -                           | 101.9                     | 34.86                         | 8.6                     | 33.17                      | 100                  | 349                     | P                       | V               |
|                                        |                                                                                             | 5800                 | 103.21              | -                       | -                           | 92.92                     | 34.86                         | 8.6                     | 33.17                      | 100                  | 349                     | A                       | V               |
| Remark                                 | 1. No other spurious found.<br>2. All results are PASS against Peak and Average limit line. |                      |                     |                         |                             |                           |                               |                         |                            |                      |                         |                         |                 |



## Band 4 5725~5850MHz

## WIFI 802.11ac VHT40 (Harmonic @ 3m)

| WIFI<br>Ant.<br>1+2 | Note                                                                                        | Frequency<br>( MHz ) | Level<br>( dBμV/m ) | Over<br>Limit<br>( dB ) | Limit<br>Line<br>( dBμV/m ) | Read<br>Level<br>( dBμV ) | Antenna<br>Factor<br>( dB/m ) | Cable<br>Loss<br>( dB ) | Preamp<br>Factor<br>( dB ) | Ant<br>Pos<br>( cm ) | Table<br>Pos<br>( deg ) | Peak<br>Avg.<br>(P/A) | Pol.<br>(H/V) |
|---------------------|---------------------------------------------------------------------------------------------|----------------------|---------------------|-------------------------|-----------------------------|---------------------------|-------------------------------|-------------------------|----------------------------|----------------------|-------------------------|-----------------------|---------------|
| 802.11ac<br>VHT40   |                                                                                             | 11510                | 49.13               | -24.87                  | 74                          | 49.81                     | 39.3                          | 12.9                    | 52.88                      | 100                  | 360                     | P                     | H             |
| CH 151<br>5755MHz   |                                                                                             | 11510                | 48.19               | -25.81                  | 74                          | 48.87                     | 39.3                          | 12.9                    | 52.88                      | 100                  | 360                     | P                     | V             |
| 802.11ac<br>VHT40   |                                                                                             | 11590                | 50.29               | -23.71                  | 74                          | 51.13                     | 39.39                         | 12.82                   | 53.05                      | 100                  | 360                     | P                     | H             |
| CH 159<br>5795MHz   |                                                                                             | 11590                | 49.77               | -24.23                  | 74                          | 50.61                     | 39.39                         | 12.82                   | 53.05                      | 100                  | 360                     | P                     | V             |
| Remark              | 1. No other spurious found.<br>2. All results are PASS against Peak and Average limit line. |                      |                     |                         |                             |                           |                               |                         |                            |                      |                         |                       |               |



**Band 4 5725~5850MHz**  
**WIFI 802.11ac VHT80 (Band Edge @ 3m)**

| WIFI<br>Ant.<br>1+2                    | Note                                                                                        | Frequency<br>( MHz ) | Level<br>( dBμV/m ) | Over<br>Limit<br>( dB ) | Limit<br>Line<br>( dBμV/m ) | Read<br>Level<br>( dBμV ) | Antenna<br>Factor<br>( dB/m ) | Cable<br>Loss<br>( dB ) | Preamp<br>Factor<br>( dB ) | Ant<br>Pos<br>( cm ) | Table<br>Pos<br>( deg ) | Peak<br>Avg.<br>( P/A ) | Pol.<br>( H/V ) |
|----------------------------------------|---------------------------------------------------------------------------------------------|----------------------|---------------------|-------------------------|-----------------------------|---------------------------|-------------------------------|-------------------------|----------------------------|----------------------|-------------------------|-------------------------|-----------------|
| 802.11ac<br>VHT80<br>CH 155<br>5775MHz | !                                                                                           | 5647.6               | 64.89               | -3.41                   | 68.3                        | 54.5                      | 35                            | 8.56                    | 33.17                      | 179                  | 39                      | P                       | H               |
|                                        |                                                                                             | 5700                 | 75.42               | -29.88                  | 105.3                       | 65.07                     | 34.95                         | 8.57                    | 33.17                      | 179                  | 39                      | P                       | H               |
|                                        |                                                                                             | 5720                 | 81.65               | -29.25                  | 110.9                       | 71.32                     | 34.92                         | 8.58                    | 33.17                      | 179                  | 39                      | P                       | H               |
|                                        |                                                                                             | 5723.2               | 82.88               | -35.32                  | 118.2                       | 72.55                     | 34.92                         | 8.58                    | 33.17                      | 179                  | 39                      | P                       | H               |
|                                        |                                                                                             | 5850                 | 71.35               | -50.95                  | 122.3                       | 61.09                     | 34.82                         | 8.61                    | 33.17                      | 179                  | 39                      | P                       | H               |
|                                        |                                                                                             | 5855.2               | 67.34               | -43.5                   | 110.84                      | 57.09                     | 34.8                          | 8.62                    | 33.17                      | 179                  | 39                      | P                       | H               |
|                                        |                                                                                             | 5880                 | 61.82               | -39.77                  | 101.59                      | 51.58                     | 34.8                          | 8.62                    | 33.18                      | 179                  | 39                      | P                       | H               |
|                                        |                                                                                             | 5932                 | 54.05               | -14.25                  | 68.3                        | 43.8                      | 34.81                         | 8.64                    | 33.2                       | 179                  | 39                      | P                       | H               |
|                                        |                                                                                             | 5772                 | 112.21              | -                       | -                           | 101.9                     | 34.88                         | 8.6                     | 33.17                      | 179                  | 39                      | P                       | H               |
|                                        |                                                                                             | 5772                 | 103.14              | -                       | -                           | 92.83                     | 34.88                         | 8.6                     | 33.17                      | 179                  | 39                      | A                       | H               |
|                                        |                                                                                             | 5645.2               | 58.64               | -9.66                   | 68.3                        | 48.25                     | 35                            | 8.56                    | 33.17                      | 107                  | 351                     | P                       | V               |
|                                        |                                                                                             | 5691.2               | 71.48               | -27.33                  | 98.81                       | 61.13                     | 34.95                         | 8.57                    | 33.17                      | 107                  | 351                     | P                       | V               |
|                                        |                                                                                             | 5719.2               | 80.98               | -29.7                   | 110.68                      | 70.65                     | 34.92                         | 8.58                    | 33.17                      | 107                  | 351                     | P                       | V               |
|                                        |                                                                                             | 5724.4               | 81.27               | -39.66                  | 120.93                      | 70.94                     | 34.92                         | 8.58                    | 33.17                      | 107                  | 351                     | P                       | V               |
|                                        |                                                                                             | 5850                 | 68.59               | -53.71                  | 122.3                       | 58.33                     | 34.82                         | 8.61                    | 33.17                      | 107                  | 351                     | P                       | V               |
|                                        |                                                                                             | 5856                 | 66.81               | -43.81                  | 110.62                      | 56.56                     | 34.8                          | 8.62                    | 33.17                      | 107                  | 351                     | P                       | V               |
|                                        |                                                                                             | 5875.2               | 61.09               | -44.06                  | 105.15                      | 50.85                     | 34.8                          | 8.62                    | 33.18                      | 107                  | 351                     | P                       | V               |
|                                        |                                                                                             | 5925.2               | 53.41               | -14.89                  | 68.3                        | 43.16                     | 34.81                         | 8.64                    | 33.2                       | 107                  | 351                     | P                       | V               |
|                                        |                                                                                             | 5770                 | 109.12              | -                       | -                           | 98.81                     | 34.88                         | 8.6                     | 33.17                      | 107                  | 351                     | P                       | V               |
|                                        |                                                                                             | 5770                 | 101.12              | -                       | -                           | 90.81                     | 34.88                         | 8.6                     | 33.17                      | 107                  | 351                     | A                       | V               |
| Remark                                 | 1. No other spurious found.<br>2. All results are PASS against Peak and Average limit line. |                      |                     |                         |                             |                           |                               |                         |                            |                      |                         |                         |                 |


**Band 4 5725~5850MHz**
**WIFI 802.11ac VHT80 (Harmonic @ 3m)**

| WIFI<br>Ant.<br>1+2 | Note                                                                                        | Frequency<br>( MHz ) | Level<br>( dBμV/m ) | Over<br>Limit<br>( dB ) | Limit<br>Line<br>( dBμV/m ) | Read<br>Level<br>( dBμV ) | Antenna<br>Factor<br>( dB/m ) | Cable<br>Loss<br>( dB ) | Preamp<br>Factor<br>( dB ) | Ant<br>Pos<br>( cm ) | Table<br>Pos<br>( deg ) | Peak<br>Avg.<br>( P/A ) | Pol.<br>( H/V ) |
|---------------------|---------------------------------------------------------------------------------------------|----------------------|---------------------|-------------------------|-----------------------------|---------------------------|-------------------------------|-------------------------|----------------------------|----------------------|-------------------------|-------------------------|-----------------|
| 802.11ac<br>VHT80   |                                                                                             | 11550                | 48.01               | -25.99                  | 74                          | 48.79                     | 39.35                         | 12.85                   | 52.98                      | 100                  | 360                     | P                       | H               |
| CH 155<br>5775MHz   |                                                                                             | 11550                | 47.72               | -26.28                  | 74                          | 48.5                      | 39.35                         | 12.85                   | 52.98                      | 100                  | 360                     | P                       | V               |
| <b>Remark</b>       | 1. No other spurious found.<br>2. All results are PASS against Peak and Average limit line. |                      |                     |                         |                             |                           |                               |                         |                            |                      |                         |                         |                 |



## Emission below 1GHz

## WIFI 802.11ac VHT20 (LF @ 3m)

| WIFI                    | Note                                        | Frequency | Level      | Over   | Limit      | Read     | Antenna  | Cable  | Preamp | Ant    | Table   | Peak    | Pol.    |
|-------------------------|---------------------------------------------|-----------|------------|--------|------------|----------|----------|--------|--------|--------|---------|---------|---------|
| Ant.                    |                                             |           |            | Limit  | Line       | Level    | Factor   | Loss   | Factor | Pos    | Pos     | Avg.    |         |
| 1+2                     |                                             | ( MHz )   | ( dBμV/m ) | ( dB ) | ( dBμV/m ) | ( dBμV ) | ( dB/m ) | ( dB ) | ( dB ) | ( cm ) | ( deg ) | ( P/A ) | ( H/V ) |
| 802.11ac<br>VHT80<br>LF |                                             | 31.94     | 23.41      | -16.59 | 40         | 29.77    | 24.1     | 0.6    | 31.06  | -      | -       | P       | H       |
|                         |                                             | 96.93     | 27.3       | -16.2  | 43.5       | 41.35    | 15.64    | 1.07   | 30.76  | 100    | 216     | P       | H       |
|                         |                                             | 138.64    | 16.28      | -27.22 | 43.5       | 28.39    | 17.48    | 1.26   | 30.85  | -      | -       | P       | H       |
|                         |                                             | 151.25    | 18.72      | -24.78 | 43.5       | 31.48    | 16.81    | 1.33   | 30.9   | -      | -       | P       | H       |
|                         |                                             | 185.2     | 16.7       | -26.8  | 43.5       | 31.27    | 15       | 1.47   | 31.04  | -      | -       | P       | H       |
|                         |                                             | 374.35    | 26.13      | -19.87 | 46         | 34.53    | 20.99    | 2.11   | 31.5   | -      | -       | P       | H       |
|                         |                                             | 37.76     | 33.52      | -6.48  | 40         | 43.17    | 20.8     | 0.67   | 31.12  | 100    | 54      | P       | V       |
|                         |                                             | 54.25     | 28.67      | -11.33 | 40         | 46.19    | 13.18    | 0.8    | 31.5   | -      | -       | P       | V       |
|                         |                                             | 92.08     | 32.52      | -10.98 | 43.5       | 47.11    | 15.04    | 1.05   | 30.68  | -      | -       | P       | V       |
|                         |                                             | 156.1     | 25.37      | -18.13 | 43.5       | 38.4     | 16.53    | 1.36   | 30.92  | -      | -       | P       | V       |
|                         |                                             | 191.02    | 24.24      | -19.26 | 43.5       | 38.81    | 15       | 1.49   | 31.06  | -      | -       | P       | V       |
|                         |                                             | 391.81    | 27.53      | -18.47 | 46         | 35.46    | 21.41    | 2.16   | 31.5   | -      | -       | P       | V       |
| Remark                  | 1. No other spurious found.                 |           |            |        |            |          |          |        |        |        |         |         |         |
|                         | 2. All results are PASS against limit line. |           |            |        |            |          |          |        |        |        |         |         |         |

**Note symbol**

|     |                                                                                                                                                          |
|-----|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| *   | <b>Fundamental Frequency</b> which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency. |
| !   | Test result is <b>not under limit 6dB</b> .                                                                                                              |
| P/A | <b>P</b> eak or <b>A</b> verage                                                                                                                          |
| H/V | <b>H</b> orizontal or <b>V</b> ertical                                                                                                                   |



A calculation example for radiated spurious emission is shown as below:

| WIFI    | Note | Frequency | Level      | Over   | Limit      | Read     | Antenna  | Cable  | Preamp | Ant    | Table   | Peak    | Pol.    |
|---------|------|-----------|------------|--------|------------|----------|----------|--------|--------|--------|---------|---------|---------|
| Ant.    |      |           |            | Limit  | Line       | Level    | Factor   | Loss   | Factor | Pos    | Pos     | Avg.    |         |
| 1+2     |      | ( MHz )   | ( dBμV/m ) | ( dB ) | ( dBμV/m ) | ( dBμV ) | ( dB/m ) | ( dB ) | ( dB ) | ( cm ) | ( deg ) | ( P/A ) | ( H/V ) |
| 802.11b |      | 2390      | 55.45      | -18.55 | 74         | 54.51    | 32.22    | 4.58   | 35.86  | 103    | 308     | P       | H       |
| CH 01   |      |           |            |        |            |          |          |        |        |        |         |         |         |
| 2412MHz |      | 2390      | 43.54      | -10.46 | 54         | 42.6     | 32.22    | 4.58   | 35.86  | 103    | 308     | A       | H       |

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

**For Peak Limit @ 2390MHz:**

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

**For Average Limit @ 2390MHz:**

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)


= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.

## Appendix D. Duty Cycle Plots


| Antenna | Band           | Duty Cycle(%) | T(ms) | 1/T(kHz) | VBW Setting |
|---------|----------------|---------------|-------|----------|-------------|
| 1+2     | 802.11a        | 94.10         | 2.058 | 0.486    | 1kHz        |
| 1+2     | 802.11ac VHT20 | 89.66         | 0.993 | 1.007    | 3kHz        |
| 1+2     | 802.11ac VHT40 | 83.98         | 0.501 | 1.994    | 3kHz        |
| 1+2     | 802.11ac VHT80 | 71.20         | 0.258 | 3.876    | 10kHz       |

802.11a Ant. 1+2






## 802.11ac VHT20 Ant. 1+2



## 802.11ac VHT40 Ant. 1+2





802.11ac VHT80 Ant. 1+2

