

CHARGING STATION

Model: EX-1193-M

In/Out: 208-240VAC, 1Ø, 50/60Hz, Max.80A

Type: Type 3R Enclosure

Temp: -35°C~50°C, 50°C~55°C de-rating Max.60A

Date:

SN:

FOR USE WITH ELECTRIC VEHICLES.

VENTILATION NOT REQUIRED.

FOR INDOOR OR OUTDOOR USE.

MADE IN TAIWAN.

CAN ICES-3(B) / NMB-3(B)



This device contains
FCC ID: xxxxxxxx
FCC ID: xxxxxxxxxxxxxx



Contains FCC ID: PPQ202008EG91NAXD

Contains FCC ID: PPQLILYWI3I

Contains FCC ID: PPQRYORR2L

Contains IC: 4491A-021EG91NAXD

Contains IC: 4491A-LILYWI3I

Contains IC: 4491A-RYORR2L

CHARGING STATION

Model: EX-1193-M-48

In/Out: 208-240VAC, 1Ø, 50/60Hz, Max.48A

Type: Type 3R Enclosure

Temp: -35°C~55°C

Date:

SN:

FOR USE WITH ELECTRIC VEHICLES.

VENTILATION NOT REQUIRED.

FOR INDOOR OR OUTDOOR USE.

MADE IN TAIWAN.

CAN ICES-3(B) / NMB-3(B)



This device contains
FCC ID: xxxxxxxx
FCC ID: xxxxxxxxxxxxxx



Contains FCC ID: PPQ202008EG91NAXD

Contains FCC ID: PPQLILYWI3I

Contains FCC ID: PPQRYORR2L

Contains IC: 4491A-021EG91NAXD

Contains IC: 4491A-LILYWI3I

Contains IC: 4491A-RYORR2L