

BANDAI (SHENZHEN) CO., LTD.

TEST REPORT

SCOPE OF WORK

FCC TESTING—SWALLOWUNI

REPORT NUMBER

SZHH01752302-001

ISSUE DATE

JAN 9, 2023

[REVISED DATE]

[-----]

PAGES

60

DOCUMENT CONTROL NUMBER

FCC ID 247_b

© 2017 INTERTEK



BANDAI (SHENZHEN) CO., LTD.

Application For Certification

FCC ID: PQ3SWALLOWUNI

Tamagotchi Uni-43350
43351,43352,43353,43354,43355,43356,43357,43358,43359

Model: SWALLOWUNI**2.4GHz Wi-Fi Transceiver**

Report No.: SZHH01752302-001

We hereby certify that the sample of the above item is considered to comply with the requirements of FCC Part 15, Subpart C for Intentional Radiator, mention 47 CFR [10-1-21]

Prepared and Checked by:**Approved by:**

Sign on file

Terry Tang
Assistant Supervisor

Ryan Chen
Project Engineer
Date: Jan 9, 2023

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Intertek Testing Service Shenzhen Ltd. Longhua Branch101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community GuanHu Subdistrict, LongHua District, Shenzhen, People's Republic of China
Tel: (86 755) 8601 6288 Fax: (86 755) 8601 6751

MEASUREMENT/TECHNICAL REPORT**Tamagotchi Uni-43350****Model: SWALLOWUNI****FCC ID: PQ3SWALLOWUNI**

This report concerns (check one) Original Grant Class II Change

Equipment Type: DTS - Part 15 Digital Transmission Systems (Wi-Fi transmitter portion)

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? Yes No

If yes, defer until : _____
date

Company Name agrees to notify the Commission by: _____
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Transition Rules Request per 15.37? Yes No

If no, assumed Part 15, Subpart C for intentional radiator - the new 47 CFR [10-01-21] Edition] provision.

Report prepared by:

Terry Tang
Intertek Testing Services Shenzhen Ltd. Longhua Branch
101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing
Community GuanHu Subdistrict, LongHua District, Shenzhen,
People's Republic of China
Tel / Fax: 86-755-8601 6288/86-755-8601 6751

Table of Contents

1.0	Summary of Test results	4
2.0	<u>General Description</u>	5
2.1	Product Description	5
2.2	Related Submittal(s) Grants	5
2.3	Test Methodology	5
2.4	Test Facility	5
3.0	System Test Configuration	6
3.1	Justification	6
3.2	EUT Exercising Software	6
3.3	Special Accessories	7
3.4	Measurement Uncertainty	7
3.5	Equipment Modification	7
3.6	Support Equipment List and Description	7
4.0	<u>Measurement Results</u>	8
4.1	Maximum Conducted Output Power at Antenna Terminals	8
4.2	Minimum 6 dB RF Bandwidth	9
4.3	Maximum Power Density Reading	16
4.4	Out of Band Conducted Emissions	23
4.5	Out of Band Radiated Emissions	42
4.6	Transmitter Radiated Emissions in Restricted Bands	43
4.7	Field Strength Calculation	44
4.8	Radiated Spurious Emission	45
4.9	Radiated Emissions from Digital Section of Transceiver	57
4.10	Transmitter Duty Cycle Calculation and Measurements	58
5.0	<u>Equipment Photographs</u>	59
6.0	<u>Product Labelling</u>	59
7.0	<u>Technical Specifications</u>	59
8.0	<u>Instruction Manual</u>	59
9.0	<u>Confidentiality Request</u>	59
10.0	<u>Discussion of Pulse Desensitization</u>	59
11.0	<u>Test Equipment List</u>	60

TEST REPORT

Intertek Report No.: SZHH01752302-001

1.0 Summary of Test Results

Applicant: BANDAI (SHENZHEN) CO., LTD.

Applicant Address: 13/F., Dingfeng Building, No.1036, Baoan Nan Rd, Luohu District, Shenzhen China

Manufacturer: BANDAI (SHENZHEN) CO., LTD.

Manufacturer Address: 13/F., Dingfeng Building, No.1036, Baoan Nan Rd, Luohu District, Shenzhen China

Model: SWALLOWUNI

FCC ID: PQ3SWALLOWUNI

TEST ITEM	REFERENCE	RESULTS
Max. Output power	15.247(b)(3)	Pass
6 dB Bandwidth	15.247(a)(2)	Pass
Max. Power Density	15.247(e)	Pass
Out of Band Antenna Conducted Emission	15.247(d)	Pass
Radiated Emission in Restricted Bands	15.247(d)	Pass
Antenna Requirement	15.203	Pass (See Notes)

Notes: The EUT uses an Integral Antenna which in accordance to Section 15.203 is considered sufficient to comply with the provisions of this section.

2.0 General Description

2.1 Product Description

The Equipment Under Test (EUT) is a Tamagotchi Uni-43350 with Wi-Fi function operating at 2412-2462MHz for 802.11b/g/n-HT20, 11 channels with 5MHz channel spacing. The EUT is powered by DC 3.7V rechargeable battery. Once use the USB cable charging to the EUT, the wireless function will be closed. For more detailed features description, please refer to the user's manual.

Type of Modulation: CCK, BPSK, QPSK, 16QAM, 64QAM.

Antenna Type: Integral Antenna

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

2.2 Related Submittal(s) Grants

This is an application for certification of:

DTS- Part 15 Digital Transmission Systems (2.4GHz Wi-Fi transmitter portion).

Remaining portions are subject to the following procedures:

1. Receiver portion of WiFi: exempt from technical requirement of this Part.
2. Other Digital Function: Subject to FCC Part 15B SDOC.

2.3 Test Methodology

Radiated emission measurements was performed according to the procedures in ANSI C63.10: 2013 and KDB 558074 D01 v05r02. Radiated emission measurement was performed in semi-anechoic chamber. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application. All other measurements were made in accordance with the procedures in part 2 of CFR 47.

2.4 Test Facility

The Semi-anechoic chamber used to collect the radiated data is **Intertek Testing Services Shenzhen Ltd. Longhua Branch** and located at 101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community GuanHu Subdistrict, LongHua District, Shenzhen, People's Republic of China. This test facility and site measurement data have been fully placed on file with the FCC (Registration Number: CN1188).

3.0 System Test Configuration

3.1 Justification

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, all cables were manipulated to produce worst case emissions. The EUT was powered by DC 3.7V rechargeable battery during the test. Only the worst case mode is shown in the report.

The EUT has 802.11b/g/n-HT20 mode and one WIFI antenna is used, and all data rate were tested and only the worst case data is shown in the report.

For maximizing emissions, the EUT was rotated through 360°, the EUT was placed on the styrene turntable with 0.8m up to 1GHz and 1.5 m above 1GHz. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance.

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000 MHz. The resolution is 1 MHz or greater for frequencies above 1000 MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

The unit was operated standalone and placed at the center of table.

Radiated emission measurement were performed the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

3.2 EUT Exercising Software

The EUT exercise program (provided by client) used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use. The worst case configuration is used in all specified testing.

Test software: EspRFTestTool_v2.8

The parameters of test software setting:

During the test, Channel and power controlling software provided by the applicant was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the application and is going to be fixed on the firmware of the end product.

TEST REPORT

Intertek Report No.: SZHH01752302-001

3.3 Special Accessories

N/A.

3.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

Uncertainty and Compliance - Unless the standard specifically states that measured values are to be extended by the measurement uncertainty in determining compliance, all compliance determinations are based on the actual measured value.

3.5 Equipment Modification

Any modifications installed previous to testing by BANDAI (SHENZHEN) CO., LTD. will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd. Longhua Branch.

3.6 Support Equipment List and Description

This product was tested in the following configuration:

Refer List:

Description	Manufacturer	Model No.
iPod (Provided by Intertek)	Apple	A1421

TEST REPORT

Intertek Report No.: SZHH01752302-001

Applicant: BANDAI (SHENZHEN) CO., LTD.

Date of Test: Jan 4, 2023

Model: SWALLOWUNI

4.0 Measurement Results**4.1 Maximum Conducted Output Power at Antenna Terminals, FCC Rules 15.247(b)(3):**

The antenna power of the EUT was connected to the input of a broadband peak RF power meter. The power meter have a video bandwidth that is greater than DTS bandwidth and utilize a fast-responding diode detector. Power was read directly at the EUT antenna terminals with cable loss added.

For antennas with gains of 6 dBi or less, maximum allowed Transmitter output is 1 watt (+30 dBm).

IEEE 802.11b (Antenna Gain = 3.37dBi) (CCK, 1Mbps)		
Frequency (MHz)	Output in dBm (Peak Reading)	Output in mWatt
Low Channel: 2412	14.2	26.3
Middle Channel: 2437	14.1	25.7
High Channel: 2462	13.8	24.0

IEEE 802.11g (Antenna Gain = 3.37dBi) (16QAM, 6Mbps)		
Frequency (MHz)	Output in dBm (Peak Reading)	Output in mWatt
Low Channel: 2412	20.3	107.2
Middle Channel: 2437	20.2	104.7
High Channel: 2462	19.6	91.2

IEEE 802.11n-HT20 (Antenna Gain = 3.37dBi) (64QAM, 6Mbps)		
Frequency (MHz)	Output in dBm (Peak Reading)	Output in mWatt
Low Channel: 2412	19.6	91.2
Middle Channel: 2437	19.2	83.2
High Channel: 2462	19.1	81.3

Cable loss: 0.5 dB External Attenuation: 0 dB

Cable loss, external attenuation has been included in OFFSET function

EUT max. output level = 20.3dBm

EUT max. E.I.R.P = 20.3dBm + 3.37dBi = 23.7dBm

TEST REPORT

Intertek Report No.: SZHH01752302-001

Applicant: BANDAI (SHENZHEN) CO., LTD.

Date of Test: Jan 4, 2023

Model: SWALLOWUNI

4.2 Minimum 6 dB RF Bandwidth, FCC Rule 15.247(a) (2):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RES BW was set to 100 KHz according to FCC KDB 558074 D01 v05r02. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A PEAK output reading was taken, a DISPLAY line was drawn 6 dB lower than PEAK level. The 6dB bandwidth was determined from where the channel output spectrum intersected the display line.

Limit: The 6 dB Bandwidth is at least 500 kHz.

IEEE 802.11b (CCK, 1Mbps)	
Frequency (MHz)	6 dB Bandwidth (MHz)
2412	9.120
2437	9.300
2462	8.190

IEEE 802.11g(16QAM, 6Mbps)	
Frequency (MHz)	6 dB Bandwidth (MHz)
2412	16.620
2437	16.410
2462	16.410



IEEE 802.11n-HT20 (64QAM, 6Mbps)	
Frequency (MHz)	6 dB Bandwidth (MHz)
2412	17.670
2437	17.640
2462	17.670

The test plots are attached as below.

TEST REPORT


802.11b

Intertek Report No.: SZHH01752302-001



TEST REPORT



Intertek Report No.: SZHH01752302-001



TEST REPORT


802.11g

Intertek Report No.: SZHH01752302-001



TEST REPORT



Intertek Report No.: SZHH01752302-001



TEST REPORT


Intertek Report No.: SZHH01752302-001

802.11n-HT20



TEST REPORT

Intertek Report No.: SZHH01752302-001



TEST REPORT

Intertek Report No.: SZHH01752302-001

Applicant: BANDAI (SHENZHEN) CO., LTD.

Date of Test: Jan 4, 2023

Model: SWALLOWUNI

4.3 Maximum Power Density Reading, FCC Rule 15.247(e):

The Measurement Procedure PKPSD was set according to the FCC KDB 558074 D01 v05r02.

Antenna output of the EUT was coupled directly to spectrum analyzer; if an external attenuator and/or cable was used, these losses are compensated for with the analyzer OFFSET function.

Limit: The Power Density does not exceed 8dBm/3 kHz.

IEEE 802.11b (CCK, 1Mbps)	
Frequency (MHz)	Power Density with RBW 3KHz
2412	-9.98
2437	-10.00
2462	-11.04

IEEE 802.11g (16QAM, 6Mbps)	
Frequency (MHz)	Power Density with RBW 3KHz
2412	-14.6
2437	-14.88
2462	-15.28



IEEE 802.11n-HT20 (64QAM, 6Mbps)	
Frequency (MHz)	Power Density with RBW 3KHz
2412	-14.71
2437	-15.11
2462	-15.42

The test plots are attached as below.

TEST REPORT


802.11b

Intertek Report No.: SZHH01752302-001



TEST REPORT



Intertek Report No.: SZHH01752302-001



TEST REPORT


802.11g

Intertek Report No.: SZHH01752302-001



TEST REPORT



Intertek Report No.: SZHH01752302-001



TEST REPORT


Intertek Report No.: SZHH01752302-001

802.11n-HT20



TEST REPORT

Intertek Report No.: SZHH01752302-001



TEST REPORT

Intertek Report No.: SZHH01752302-001

Applicant: BANDAI (SHENZHEN) CO., LTD.

Date of Test: Jan 4, 2023

Model: SWALLOWUNI

4.4 Out of Band Conducted Emissions, FCC Rule 15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. The Measurement Procedure was set according to the FCC KDB 558074 D01 v05r02.

All other types of emissions from the EUT shall meet the general limits for radiated frequencies outside the passband.

Refer to the attached test plots for out of band conducted emissions data with rate of 1Mbps for 802.11b and 6Mbps for 802.11g/n-HT20.

The test plots showed all spurious emission up to the tenth harmonic were measured and they were found to be at least 20 dB below the highest level of the desired power in the passband.



The test plots are attached as below.

TEST REPORT

Intertek Report No.: SZHH01752302-001



802.11b

Channel 01 (2412MHz) Reference Level: 2.75dBm



TEST REPORT

Intertek Report No.: SZHH01752302-001



TEST REPORT


Intertek Report No.: SZHH01752302-001

Channel 06 (2437MHz) Reference Level: 2.16dBm



TEST REPORT



Intertek Report No.: SZHH01752302-001



TEST REPORT


Intertek Report No.: SZHH01752302-001

Channel 11 (2462MHz) Reference Level: 2.73dBm



TEST REPORT

Intertek Report No.: SZHH01752302-001




TEST REPORT

Intertek Report No.: SZHH01752302-001


802.11g

Channel 01 (2412MHz) Reference Level: -0.75dBm



TEST REPORT



Intertek Report No.: SZHH01752302-001



TEST REPORT


Intertek Report No.: SZHH01752302-001

Channel 06 (2437MHz) Reference Level: -1.11Bm



TEST REPORT



Intertek Report No.: SZHH01752302-001



TEST REPORT



Intertek Report No.: SZHH01752302-001

Channel 11 (2462MHz) Reference Level: -3.82dBm



TEST REPORT

Intertek Report No.: SZHH01752302-001





TEST REPORT

Intertek Report No.: SZHH01752302-001



802.11n-HT20

Channel 01 (2412MHz) Reference Level: -4.71dBm



TEST REPORT

Intertek Report No.: SZHH01752302-001





Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1	1		2.41692 GHz	-1.73 dBm		
M2	1		2.4 GHz	-35.91 dBm		
M3	1		2.39 GHz	-52.59 dBm		
M4	1		2.399855 GHz	-36.52 dBm		

TEST REPORT


Intertek Report No.: SZHH01752302-001

Channel 06 (2437MHz) Reference Level: -2.38dBm



TEST REPORT


Intertek Report No.: SZHH01752302-001



TEST REPORT



Intertek Report No.: SZHH01752302-001

Channel 11 (2462MHz) Reference Level: -2.85dBm



TEST REPORT

Intertek Report No.: SZHH01752302-001



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1	1		2.45568 GHz	-2.30 dBm		
M2	1		2.4835 GHz	-50.29 dBm		
M3	1		2.5 GHz	-55.38 dBm		
M4	1		2.483841 GHz	-48.94 dBm		

TEST REPORT

Intertek Report No.: SZHH01752302-001

Applicant: BANDAI (SHENZHEN) CO., LTD.

Date of Test: Jan 4, 2023

Model: SWALLOWUNI

4.5 Out of Band Radiated Emissions (for emissions in 4.4 above that are less than 20dB below carrier), FCC Rule 15.247(d):

For out of band emissions that are close to or that exceed the 20dB attenuation requirement described in the specification, radiated measurements were performed at a 3m separation distance to determine whether these emissions complied with the general radiated emission requirement.

- Not required, since all emissions are more than 20dB below fundamental
 See attached data sheet

TEST REPORT

Intertek Report No.: SZHH01752302-001

Applicant: BANDAI (SHENZHEN) CO., LTD.

Date of Test: Jan 4, 2023

Model: SWALLOWUNI

4.6 Transmitter Radiated Emissions in Restricted Bands, FCC Rule 15.35(b) (c):

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included. All measurements were performed with peak detection unless otherwise specified.

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance.

TEST REPORT

Intertek Report No.: SZHH01752302-001

Applicant: BANDAI (SHENZHEN) CO., LTD.

Date of Test: Jan 4, 2023

Model: SWALLOWUNI

4.7 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD$$

Where

FS = Field Strength in $\text{dB}\mu\text{V}/\text{m}$ RA = Receiver Amplitude (including preamplifier) in $\text{dB}\mu\text{V}$

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB

AG = Amplifier Gain in dB

PD = Pulse Desensitization in dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD$$

Example

Assume a receiver reading of 62.0 $\text{dB}\mu\text{V}$ is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB. The net field strength for comparison to the appropriate emission limit is 42 $\text{dB}\mu\text{V}/\text{m}$. This value in $\text{dB}\mu\text{V}/\text{m}$ was converted to its corresponding level in $\mu\text{V}/\text{m}$.

RA = 62.0 $\text{dB}\mu\text{V}$

AF = 7.4 dB/m

CF = 1.6 dB

AG = 29.0 dB

PD = 0 dB

$$FS = 62 + 7.4 + 1.6 - 29 + 0 = 42 \text{ dB}\mu\text{V}/\text{m}$$

Level in mV/m = Common Antilogarithm $[(42 \text{ dB}\mu\text{V}/\text{m})/20] = 125.9 \mu\text{V}/\text{m}$

TEST REPORT

Intertek Report No.: SZHH01752302-001

Applicant: BANDAI (SHENZHEN) CO., LTD.

Date of Test: Jan 4, 2023

Model: SWALLOWUNI

4.8 Radiated Spurious Emission

Worst Case Radiated Spurious Emission (802.11b-Channel 01)
at
4924.000MHz

Judgement: Passed by 5.3dB margin.

For the electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

TEST REPORT

Intertek Report No.: SZHH01752302-001


Applicant: BANDAI (SHENZHEN) CO., LTD.

Date of Test: Jan 4, 2023

Model: SWALLOWUNI

Worst Case Operating Mode: WIFI Link

ANT Polarity: Horizontal



Frequency (MHz)	QuasiPeak (dB μ V/m)	Meas. Time (ms)	Bandwidth (kHz)	Polarization	Corr. (dB)	Margin - QPK (dB)	Limit - QPK (dB μ V/m)
299.417500	36.8	1000.0	120.000	H	16.3	9.2	46.0
373.280000	37.8	1000.0	120.000	H	18.4	8.2	46.0
453.405000	33.3	1000.0	120.000	H	20.7	12.7	46.0

Remark:

1. Corr. (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB)
2. QuasiPeak (dB μ V/m) = Corr. (dB/m) + Read Level (dB μ V)
3. Margin (dB) = Limit Line(dB μ V/m) – Level (dB μ V/m)

TEST REPORT

Intertek Report No.: SZHH01752302-001


Applicant: BANDAI (SHENZHEN) CO., LTD.

Date of Test: Jan 4, 2023

Model: SWALLOWUNI

Worst Case Operating Mode: WIFI Link

ANT Polarity: Vertical



Frequency (MHz)	QuasiPeak (dBuV/m)	Meas. Time (ms)	Bandwidth (kHz)	Polarization	Corr. (dB)	Margin - QPK (dB)	Limit - QPK (dBuV/m)
299.417500	28.7	1000.0	120.000	V	16.3	17.3	46.0
307.662500	30.7	1000.0	120.000	V	16.6	15.3	46.0
426.560000	28.7	1000.0	120.000	V	20.1	17.3	46.0

Remark:

1. Corr. (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB)
2. QuasiPeak (dB μ V/m) = Corr. (dB/m) + Read Level (dB μ V)
3. Margin (dB) = Limit Line(dB μ V/m) – Level (dB μ V/m)

TEST REPORT

Intertek Report No.: SZHH01752302-001

Applicant: BANDAI (SHENZHEN) CO., LTD.

Date of Test: Jan 4, 2023

Model: SWALLOWUNI

Operating Mode: Transmitting (802.11b-Channel 01)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
Horizontal	*4824.000	53.9	36.1	34.2	52.0	74.0	-22.0
Horizontal	*2376.125	53.7	34.7	33.1	52.1	74.0	-21.9

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
Horizontal	*4824.000	44.5	36.1	34.2	42.6	54.0	-11.4
Horizontal	*2376.125	46.8	34.7	33.1	45.2	54.0	-8.8

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz/VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TEST REPORT

Intertek Report No.: SZHH01752302-001

Applicant: BANDAI (SHENZHEN) CO., LTD.

Date of Test: Jan 4, 2023

Model: SWALLOWUNI

Operating Mode: Transmitting (802.11b-Channel 06)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
Horizontal	*4874.000	53.6	36.1	34.6	52.1	74.0	-21.9
Horizontal	*7311.000	49.5	35.6	37.1	51.0	74.0	-23.0

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
Horizontal	*4874.000	43.9	36.1	34.6	42.4	54.0	-11.6
Horizontal	*7311.000	38.6	35.6	37.1	40.1	54.0	-13.9

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TEST REPORT

Intertek Report No.: SZHH01752302-001

Applicant: BANDAI (SHENZHEN) CO., LTD.

Date of Test: Jan 4, 2023

Model: SWALLOWUNI

Operating Mode: Transmitting (802.11b-Channel 11)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
Horizontal	*4924.000	59.3	36.1	34.6	57.8	74.0	-16.2
Horizontal	*2483.575	53.4	35.6	37.2	55.0	74.0	-19.0

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
Horizontal	*4924.000	50.2	36.1	34.6	48.7	54.0	-5.3
Horizontal	*2483.575	43.2	35.6	37.2	44.8	54.0	-9.2

- NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TEST REPORT

Intertek Report No.: SZHH01752302-001

Applicant: BANDAI (SHENZHEN) CO., LTD.

Date of Test: Jan 4, 2023

Model: SWALLOWUNI

Operating Mode: Transmitting (802.11g-Channel 01)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
Horizontal	*4824.000	51.9	36.1	34.2	50.0	74.0	-24.0
Horizontal	*2322.200	55.1	34.7	33.1	53.5	74.0	-20.5

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
Horizontal	*4824.000	40.7	36.1	34.2	38.8	54.0	-15.2
Horizontal	*2322.200	45.1	34.7	33.1	43.5	54.0	-10.5

- NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz/VBW=10Hz for average value.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TEST REPORT

Intertek Report No.: SZHH01752302-001

Applicant: BANDAI (SHENZHEN) CO., LTD.

Date of Test: Jan 4, 2023

Model: SWALLOWUNI

Operating Mode: Transmitting (802.11g-Channel 06)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
Horizontal	*4874.000	52.0	36.1	34.6	50.5	74.0	-23.5
Horizontal	*7311.000	50.3	35.6	37.1	51.8	74.0	-22.2

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
Horizontal	*4874.000	40.4	36.1	34.6	38.9	54.0	-15.1
Horizontal	*7311.000	43.6	35.6	37.1	45.1	54.0	-8.9

- NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TEST REPORT

Intertek Report No.: SZHH01752302-001

Applicant: BANDAI (SHENZHEN) CO., LTD.

Date of Test: Jan 4, 2023

Model: SWALLOWUNI

Operating Mode: Transmitting (802.11g-Channel 11)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
Horizontal	*4924.000	50.4	36.1	34.6	48.9	74.0	-25.1
Horizontal	*2489.520	51.6	35.6	37.2	53.2	74.0	-20.8

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
Horizontal	*4924.000	40.6	36.1	34.6	39.1	54.0	-14.9
Horizontal	*2489.520	42.9	35.6	37.2	44.5	54.0	-9.5

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TEST REPORT

Intertek Report No.: SZHH01752302-001

Applicant: BANDAI (SHENZHEN) CO., LTD.

Date of Test: Jan 4, 2023

Model: SWALLOWUNI

Operating Mode: Transmitting (802.11n-HT20-Channel 01)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
Horizontal	*4824.000	46.1	36.1	34.2	44.2	74.0	-29.8
Horizontal	*2335.100	52.8	34.7	33.1	51.2	74.0	-22.8

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
Horizontal	*4824.000	40.2	36.1	34.2	38.3	54.0	-15.7
Horizontal	*2335.100	41.2	34.7	33.1	39.6	54.0	-14.4

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz/VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TEST REPORT

Intertek Report No.: SZHH01752302-001

Applicant: BANDAI (SHENZHEN) CO., LTD.

Date of Test: Jan 4, 2023

Model: SWALLOWUNI

Operating Mode: Transmitting (802.11n-HT20-Channel 06)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
Horizontal	*4874.000	48.1	36.1	34.6	46.6	74.0	-27.4
Horizontal	*7311.000	48.9	35.6	37.1	50.4	74.0	-23.6

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
Horizontal	*4874.000	39.1	36.1	34.6	37.6	54.0	-16.4
Horizontal	*7311.000	41.0	35.6	37.1	42.5	54.0	-11.5

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TEST REPORT

Intertek Report No.: SZHH01752302-001

Applicant: BANDAI (SHENZHEN) CO., LTD.

Date of Test: Jan 4, 2023

Model: SWALLOWUNI

Operating Mode: Transmitting (802.11n-HT20-Channel 11)

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
Horizontal	*4924.000	46.7	36.1	34.6	45.2	74.0	-28.8
Horizontal	*2487.120	51.0	35.6	37.2	52.6	74.0	-21.4

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
Horizontal	*4924.000	39.9	36.1	34.6	38.4	54.0	-15.6
Horizontal	*2487.120	39.9	35.6	37.2	41.5	54.0	-12.5

- NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.



Total Quality. Assured.

TEST REPORT

Intertek Report No.: SZHH01752302-001

Applicant: BANDAI (SHENZHEN) CO., LTD.

Date of Test: Jan 4, 2023

Model: SWALLOWUNI

4.9 Radiated Emissions from Digital Section of Transceiver, FCC Ref: 15.109

- [] Not required - No digital part
- [] Test results are attached
- [x] Included in the separated report.

TEST REPORT

Intertek Report No.: SZHH01752302-001

Applicant: BANDAI (SHENZHEN) CO., LTD.

Date of Test: Jan 4, 2023

Model: SWALLOWUNI

4.10 Transmitter Duty Cycle Calculation and Measurements, FCC Rule 15.35(b), (c)

The EUT antenna output port was connected to the input of the spectrum analyzer. The analyzer center frequency was set to EUT RF channel carrier. The SWEP function on the analyzer was set to ZERO SPAN. The Transmitter ON time was determined from the resultant time-amplitude display:

	See attached spectrum analyzer chart (s) for Transmitter timing
	See Transmitter timing diagram provided by manufacturer
x	Not applicable, duty cycle was not used.

5.0 Equipment Photographs

For electronic filing, the photographs are saved with filename: external photos.pdf & internal photos.pdf.

6.0 Product Labeling

For electronic filing, the FCC ID label artwork and location is saved with filename: label.pdf.

7.0 Technical Specifications

For electronic filing, the block diagram and circuit diagram are saved with filename: block.pdf and circuit.pdf respectively.

8.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

9.0 Confidentiality Request

For electronic filing, the confidentiality request of the tested EUT is saved with filename: request.pdf.

10.0 Discussion of Pulse Desensitization

The determination of pulse desensitivity was made in accordance with Hewlett Packard Application Note 150-2, *Spectrum Analysis ... Pulsed RF*.

Pulse desensitivity is not applicable for this device since the transmitter transmits the RF signal continuously.

TEST REPORT

Intertek Report No.: SZHH01752302-001

11.0 Test Equipment List

Equipment No.	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
SZ182-02	RF Power Meter	Anritsu	ML2496A	1302005	16-May-2022	16-May-2023
SZ182-02-01	Power Sensor	Anritsu	MA2411B	1207429	16-May-2022	16-May-2023
SZ061-12	BiConiLog Antenna	ETS	3142E	00166158	4-Aug-2021	4-Aug-2024
SZ185-02	EMI Receiver	R&S	ESCI	100692	8-Jul-2022	8-Jul-2023
SZ061-08	Horn Antenna	ETS	3115	00092346	5-Sep-2021	5-Sep-2024
SZ061-06	Active Loop Antenna	Electro-Metrics	EM-6876	217	18-May-2021	18-May-2023
SZ056-03	Spectrum Analyzer	R&S	FSP 30	101148	16-May-2022	16-May-2023
SZ056-06	Spectrum Analyzer	R&S	FSV40	101101	19-Dec-2022	19-Dec-2023
SZ181-04	Preamplifier	Agilent	8449B	3008A0247 4	16-May-2022	16-May-2023
SZ188-01	Anechoic Chamber	ETS	RFD-F/A-100	4102	12-Dec-2021	12-Dec-2024
SZ062-02	RF Cable	RADIALL	RG 213U	--	1-Nov -2022	1-May-2023
SZ062-05	RF Cable	RADIALL	0.04-26.5GHz	--	1-Nov -2022	1-May-2023
SZ062-12	RF Cable	RADIALL	0.04-26.5GHz	--	1-Nov -2022	1-May-2023
SZ067-04	Notch Filter	Micro-Tronics	BRM5070 2-02	--	17-May-2022	17-May-2023

***** End of Report *****