

FCC PART 15.247


TEST REPORT

For

HONG KONG IPRO TECHNOLOGY CO.,LIMITED

FLAT/RM A3, 9/F SILVERCORP INT TOWER 707-713 NATHAN RD MONGKOK, HONGKONG

FCC ID: PQ4IPROACROA58

Report Type: Original Report	Product Type: Smart Mobile Phone
Test Engineer:	Lion Xiao 
Report Number:	RDG150505007-00B
Report Date:	2015-05-14
Reviewed By:	Sula Huang  RF Leader
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan). This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EQUIPMENT MODIFICATIONS	6
EUT EXERCISE SOFTWARE	7
SUPPORT EQUIPMENT LIST AND DETAILS	7
EXTERNAL CABLE.....	7
BLOCK DIAGRAM OF TEST SETUP	8
SUMMARY OF TEST RESULTS	9
FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE	10
APPLICABLE STANDARD	10
FCC §15.203 - ANTENNA REQUIREMENT.....	11
APPLICABLE STANDARD	11
ANTENNA CONNECTOR CONSTRUCTION	11
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	12
APPLICABLE STANDARD	12
MEASUREMENT UNCERTAINTY	12
EUT SETUP	12
EMI TEST RECEIVER SETUP.....	13
TEST PROCEDURE	13
CORRECTED AMPLITUDE & MARGIN CALCULATION	13
TEST EQUIPMENT LIST AND DETAILS.....	14
TEST RESULTS SUMMARY	14
TEST DATA	14
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	19
APPLICABLE STANDARD	19
MEASUREMENT UNCERTAINTY	19
EUT SETUP	19
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	20
TEST PROCEDURE	20
CORRECTED AMPLITUDE & MARGIN CALCULATION	21
TEST EQUIPMENT LIST AND DETAILS.....	21
TEST RESULTS SUMMARY	21
TEST DATA	21
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....	35
APPLICABLE STANDARD	35
TEST PROCEDURE	35
TEST EQUIPMENT LIST AND DETAILS.....	35
TEST DATA	35
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....	44

APPLICABLE STANDARD	44
TEST PROCEDURE	44
TEST EQUIPMENT LIST AND DETAILS.....	44
TEST DATA	44
FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	46
APPLICABLE STANDARD	46
TEST PROCEDURE	46
TEST EQUIPMENT LIST AND DETAILS.....	46
TEST DATA	46
FCC §15.247(e) - POWER SPECTRAL DENSITY	52
APPLICABLE STANDARD	52
TEST PROCEDURE	52
TEST EQUIPMENT LIST AND DETAILS.....	52
TEST DATA	52

FINAL

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *HONG KONG IPRO TECHNOLOGY CO., LIMITED*'s product, model number: *ACRO A58* (FCC ID: *PQ4IPROACROA58*) (the "EUT") in this report was a *Smart Mobile Phone*, which was measured approximately: 143.5 mm (L) x 69.7 mm (W) x 5.85 mm (H), rated input voltage: DC3.8V rechargeable Li-ion battery or DC5.0V charging from adapter.

Adapter information: IPRO

Model: NTR-A58

Input: AC100-240V, 50/60Hz 150mA

Output: DC5.0V, 1000 mA

All measurement and test data in this report was gathered from production sample serial number: IPROACROA58000001 (Assigned by BACL, Dongguan). The EUT was received on 2015-05-06.

Objective

This report is prepared on behalf of *HONG KONG IPRO TECHNOLOGY CO., LIMITED* in accordance with Part 2, Subpart J, Part 15, Subparts A, B and C of the Federal Communications Commission's rules

The tests were performed in order to determine the compliance of the EUT with FCC Part 15-Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15B JBP submissions with FCC ID: PQ4IPROACROA58.

FCC Part 15C DSS submissions with FCC ID: PQ4IPROACROA58.

FCC Part 22H, 24E PCE submissions with FCC ID: PQ4IPROACROA58.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 06, 2015. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in testing mode, which was provided by manufacturer.
For 2.4GHz band, 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For 802.11b, 802.11g, and 802.11n ht20 modes were tested with Channel 1, 6 and 11.
For 802.11n ht40 mode were tested with Channel 3, 6 and 9.

For Bluetooth LE mode, 40 channels are provided for testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	...	...
...	...	...	...
...	...	...	...
..	...	38	2478
19	2440	39	2480

EUT was tested with channel 0, 19 and 39.

The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all data rates bandwidths, and modulations.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

Test Mode	Test Software Version	Engineering Mode		
802.11b	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	1Mbps	1Mbps	1Mbps
	Power Level Setting	9	9	9
802.11g	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	6Mbps	6Mbps	6Mbps
	Power Level Setting	19	9	9
802.11n ht20	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	MCS0	MCS0	MCS0
	Power Level Setting	9	9	9
802.11n ht40	Test Frequency	2422MHz	2437MHz	2452MHz
	Data Rate	MCS0	MCS0	MCS0
	Power Level Setting	9	9	9
BLE	Test Frequency	2402MHz	2440 MHz	2480MHz
	BLE	N/A	N/A	N/A


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
/	/	/	/

External Cable

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
USB Cable	Yes	No	1.2	USB Port of Laptop	EUT
Earphone Cable	No	No	1.2	Audio Port of EUT	Earphone

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i) & §1.1310 & §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.247(d)	Spurious Emissions at Antenna Port	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum conducted output power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE**Applicable Standard**

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v05r02:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Measurement Result

The maximum average target output power = 9.5 dBm (8.91mW) at 2462 MHz
 $[(\text{max. power of channel, mW})/(\text{min. test separation distance, mm})][\sqrt{f(\text{GHz})}]$
 $= 8.91/5 \cdot (\sqrt{2.462}) = 2.80 < 3.0$

So the stand-alone SAR evaluation is not necessary.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Antenna Connector Construction

The EUT has one integral antenna arrangement, which was permanently attached and the antenna gain is 1.5 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cispr} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cispr} of Table 1, then:


- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cispr})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cispr})$, exceeds the disturbance limit.

Based on CISPR 16-4-2-2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Dongguan) is 3.46 dB (150 kHz to 30 MHz).

Table 1 – Values of U_{cispr}

Measurement	U_{cispr}
Conducted disturbance at mains port using AMN (150 kHz to 30 MHz)	3.4 dB

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2009 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

V_C (cord. Reading): corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN

C_f : Correction Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCS 30	830245/006	2014-10-20	2015-10-20
R&S	L.I.S.N	ESH2-Z5	892107/021	2014-06-09	2015-06-09
R&S	Two-line V-network	ENV 216	3560.6550.12	2014-12-11	2015-12-11
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, with the worst margin reading of:

5.7 dB at 1.310256 MHz in the **Neutral** conducted mode for BLE.


Test Data**Environmental Conditions**

Temperature:	26.6 °C
Relative Humidity:	50 %
ATM Pressure:	100.6 kPa

The testing was performed by Lion Xiao on 2015-05-12.


Test Mode: Transmitting (Wi-Fi)

AC120 V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.432855	37.9	9.000	L1	10.2	19.3	57.2	Compliance
0.732382	35.8	9.000	L1	10.4	20.2	56.0	Compliance
0.872708	35.1	9.000	L1	10.4	20.9	56.0	Compliance
1.126176	31.1	9.000	L1	10.4	24.9	56.0	Compliance
1.239175	35.0	9.000	L1	10.4	21.0	56.0	Compliance
1.259081	37.6	9.000	L1	10.4	18.4	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.429420	27.4	9.000	L1	10.2	19.9	47.3	Compliance
0.432855	27.9	9.000	L1	10.2	19.3	47.2	Compliance
0.732382	27.7	9.000	L1	10.4	18.3	46.0	Compliance
0.780588	28.3	9.000	L1	10.4	17.7	46.0	Compliance
1.573796	27.5	9.000	L1	10.4	18.5	46.0	Compliance
15.616430	26.6	9.000	L1	10.6	23.4	50.0	Compliance


AC120 V, 60 Hz, Neutral:

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.495646	40.4	9.000	N	10.1	15.6	56.1	Compliance
0.634524	39.3	9.000	N	10.3	16.7	56.0	Compliance
0.805868	41.1	9.000	N	10.4	14.9	56.0	Compliance
1.239175	45.0	9.000	N	10.4	11.0	56.0	Compliance
1.310256	45.4	9.000	N	10.4	10.6	56.0	Compliance
1.430284	41.9	9.000	N	10.4	14.1	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.805868	34.7	9.000	N	10.4	11.3	46.0	Compliance
1.239175	38.2	9.000	N	10.4	7.8	46.0	Compliance
1.310256	39.4	9.000	N	10.4	6.6	46.0	Compliance
1.407671	35.8	9.000	N	10.4	10.2	46.0	Compliance
1.430284	35.3	9.000	N	10.4	10.7	46.0	Compliance
1.548915	33.4	9.000	N	10.4	12.6	46.0	Compliance


Test Mode: Transmitting (BLE)

AC120 V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.732382	36.5	9.000	L1	10.4	19.5	56.0	Compliance
0.825364	35.3	9.000	L1	10.4	20.7	56.0	Compliance
0.999305	32.7	9.000	L1	10.4	23.3	56.0	Compliance
1.082190	31.9	9.000	L1	10.4	24.1	56.0	Compliance
1.190776	32.3	9.000	L1	10.4	23.7	56.0	Compliance
1.289541	34.2	9.000	L1	10.4	21.8	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.429420	29.0	9.000	L1	10.2	18.2	47.3	Compliance
0.432855	27.3	9.000	L1	10.2	19.9	47.2	Compliance
0.732382	28.8	9.000	L1	10.4	17.2	46.0	Compliance
0.900972	29.0	9.000	L1	10.4	17.0	46.0	Compliance
1.548915	25.8	9.000	L1	10.4	20.2	46.0	Compliance
2.641698	23.0	9.000	L1	10.5	23.0	46.0	Compliance

AC120 V, 60 Hz, Neutral:

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.720803	39.7	9.000	N	10.4	16.3	56.0	Compliance
0.852094	40.9	9.000	N	10.4	15.1	56.0	Compliance
1.239175	45.0	9.000	N	10.4	11.0	56.0	Compliance
1.289541	44.3	9.000	N	10.4	11.7	56.0	Compliance
1.677385	37.5	9.000	N	10.4	18.5	56.0	Compliance
1.831043	35.5	9.000	N	10.4	20.5	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.852094	35.6	9.000	N	10.4	10.4	46.0	Compliance
1.190776	35.5	9.000	N	10.4	10.5	46.0	Compliance
1.239175	38.9	9.000	N	10.4	7.1	46.0	Compliance
1.259081	37.3	9.000	N	10.4	8.7	46.0	Compliance
1.289541	37.8	9.000	N	10.4	8.2	46.0	Compliance
1.310256	40.3	9.000	N	10.4	5.7	46.0	Compliance

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard

FCC §15.247 (d); §15.209; §15.205;

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cisp} of Table 2, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cisp} of Table 2, then:

- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit.

Based on CISPR 16-4-2-2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Dongguan) is:

30M~200MHz: 5.0 dB

200M~1GHz: 6.2 dB

1G~6GHz: 4.45 dB


6G~18GHz: 5.23 dB


Table 2 – Values of U_{cisp}

Measurement	U_{cisp}
Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB

EUT Setup

Below 1GHz:



Above 1GHz:

The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC 15.209, and FCC 15.247 limits. The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	Ave.

Test Procedure

During the radiated emission test, the adapter was connected to the first AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Loss} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2014-05-09	2015-05-09
	EMI Test Receiver	ESCI	100224	2015-05-09	2016-05-09
Sunol Sciences	Antenna	JB3	A060611-3	2014-07-28	2017-07-27
HP	Amplifier	8447E	2434A02181	2014-09-01	2015-09-01
R&S	Spectrum Analyzer	FSEM	DE31388	2014-05-09	2015-05-09
	Spectrum Analyzer	FSEM	DE31388	2015-05-09	2016-05-09
ETS LINDGREN	Horn Antenna	3115	000 527 35	2012-09-06	2015-09-06
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	2015-02-19	2016-02-19
R&S	Spectrum Analyzer	FSP 38	100478	2014-05-09	2015-05-09
	Spectrum Analyzer	FSP 38	100478	2015-05-09	2016-05-09
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2014-06-16	2017-06-15
Quinstar	Amplifier	QLW- 18405536-JO	15964001001	2014-09-06	2015-09-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Section 15.205, 15.209 and 15.247, with the worst margin reading of:

6.33dB at 344.23 MHz in the Horizontal polarization for 802.11g Mode

Test Data

Environmental Conditions

Temperature:	25.6~25.8 °C
Relative Humidity:	51~53 %
ATM Pressure:	100~100.2 kPa

The testing was performed by Lion Xiao on 2015-05-08 & 2015-05-11.

Test Mode: Transmitting

802.11b Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2412 MHz									
2412	57.23	PK	H	25.67	3.68	0.00	86.58	N/A	N/A
2412	52.62	AV	H	25.67	3.68	0.00	81.97	N/A	N/A
2412	55.83	PK	V	25.67	3.68	0.00	85.18	N/A	N/A
2412	51.89	AV	V	25.67	3.68	0.00	81.24	N/A	N/A
2390	26.38	PK	H	25.61	3.63	0.00	55.62	74.00	18.38
2390	14.03	AV	H	25.61	3.63	0.00	43.27	54.00	10.73
4824	34.23	PK	H	30.64	5.03	27.41	42.49	74.00	31.51
4824	21.25	AV	H	30.64	5.03	27.41	29.51	54.00	24.49
7236	32.17	PK	H	34.17	6.65	25.90	47.09	74.00	26.91
7236	19.36	AV	H	34.17	6.65	25.90	34.28	54.00	19.72
9648	30.48	PK	H	36.06	8.55	27.46	47.63	74.00	26.37
9648	17.69	AV	H	36.06	8.55	27.46	34.84	54.00	19.16
3131	35.29	PK	H	27.62	6.93	27.43	42.41	74.00	31.59
3131	22.18	AV	H	27.62	6.93	27.43	29.30	54.00	24.70
344.3	43.2	QP	H	14.95	2.22	21.63	38.74	46.00	7.26
Middle Channel: 2437 MHz									
2437	58.11	PK	H	25.74	3.75	0.00	87.60	N/A	N/A
2437	53.47	AV	H	25.74	3.75	0.00	82.96	N/A	N/A
2437	56.56	PK	V	25.74	3.75	0.00	86.05	N/A	N/A
2437	52.62	AV	V	25.74	3.75	0.00	82.11	N/A	N/A
4874	34.49	PK	H	30.77	5.14	27.42	42.98	74.00	31.02
4874	21.34	AV	H	30.77	5.14	27.42	29.83	54.00	24.17
7311	32.21	PK	H	34.35	6.74	25.88	47.42	74.00	26.58
7311	19.44	AV	H	34.35	6.74	25.88	34.65	54.00	19.35
9748	30.58	PK	H	36.30	8.61	27.24	48.25	74.00	25.75
9748	17.74	AV	H	36.30	8.61	27.24	35.41	54.00	18.59
3131	35.42	PK	H	27.62	6.93	27.43	42.54	74.00	31.46
3131	22.37	AV	H	27.62	6.93	27.43	29.49	54.00	24.51
3190	33.14	PK	H	27.81	6.26	27.38	39.83	74.00	34.17
3190	20.26	AV	H	27.81	6.26	27.38	26.95	54.00	27.05
344.3	43.3	QP	H	14.95	2.22	21.63	38.84	46.00	7.16
High Channel: 2462 MHz									
2462	59.08	PK	H	25.80	3.75	0.00	88.63	N/A	N/A
2462	54.3	AV	H	25.80	3.75	0.00	83.85	N/A	N/A
2462	57.5	PK	V	25.80	3.75	0.00	87.05	N/A	N/A
2462	52.59	AV	V	25.80	3.75	0.00	82.14	N/A	N/A
2483.5	26.34	PK	H	25.86	3.67	0.00	55.87	74.00	18.13
2483.5	14.03	AV	H	25.86	3.67	0.00	43.56	54.00	10.44
4924	34.61	PK	H	30.90	5.34	27.43	43.42	74.00	30.58
4924	21.52	AV	H	30.90	5.34	27.43	30.33	54.00	23.67
7386	32.23	PK	H	34.53	6.83	25.86	47.73	74.00	26.27
7386	19.52	AV	H	34.53	6.83	25.86	35.02	54.00	18.98
9848	30.61	PK	H	36.54	8.66	26.94	48.87	74.00	25.13
9848	17.78	AV	H	36.54	8.66	26.94	36.04	54.00	17.96
3131	35.43	PK	H	27.62	6.93	27.43	42.55	74.00	31.45
3131	22.42	AV	H	27.62	6.93	27.43	29.54	54.00	24.46
344.3	43	QP	H	14.95	2.22	21.63	38.54	46.00	7.46

802.11g Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
	Reading (dBµV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2412 MHz									
2412	61.58	PK	H	25.67	3.68	0.00	90.93	N/A	N/A
2412	50.94	AV	H	25.67	3.68	0.00	80.29	N/A	N/A
2412	58.34	PK	V	25.67	3.68	0.00	87.69	N/A	N/A
2412	47.13	AV	V	25.67	3.68	0.00	76.48	N/A	N/A
2390	26.18	PK	H	25.61	3.63	0.00	55.42	74.00	18.58
2390	13.68	AV	H	25.61	3.63	0.00	42.92	54.00	11.08
4824	34.36	PK	H	30.64	5.03	27.41	42.62	74.00	31.38
4824	21.48	AV	H	30.64	5.03	27.41	29.74	54.00	24.26
7236	32.4	PK	H	34.17	6.65	25.90	47.32	74.00	26.68
7236	19.63	AV	H	34.17	6.65	25.90	34.55	54.00	19.45
9648	30.73	PK	H	36.06	8.55	27.46	47.88	74.00	26.12
9648	17.91	AV	H	36.06	8.55	27.46	35.06	54.00	18.94
2950	35.32	PK	H	27.07	6.61	27.54	41.46	74.00	32.54
2950	22.33	AV	H	27.07	6.61	27.54	28.47	54.00	25.53
344.23	42.9	QP	H	14.95	2.22	21.63	38.44	46.00	7.56
Middle Channel: 2437 MHz									
2437	62.15	PK	H	25.74	3.75	0.00	91.64	N/A	N/A
2437	51.52	AV	H	25.74	3.75	0.00	81.01	N/A	N/A
2437	58.72	PK	V	25.74	3.75	0.00	88.21	N/A	N/A
2437	47.65	AV	V	25.74	3.75	0.00	77.14	N/A	N/A
4874	34.57	PK	H	30.77	5.14	27.42	43.06	74.00	30.94
4874	21.55	AV	H	30.77	5.14	27.42	30.04	54.00	23.96
7311	32.37	PK	H	34.35	6.74	25.88	47.58	74.00	26.42
7311	19.65	AV	H	34.35	6.74	25.88	34.86	54.00	19.14
9748	30.85	PK	H	36.30	8.61	27.24	48.52	74.00	25.48
9748	17.96	AV	H	36.30	8.61	27.24	35.63	54.00	18.37
2950	35.47	PK	H	27.07	6.61	27.54	41.61	74.00	32.39
2950	22.65	AV	H	27.07	6.61	27.54	28.79	54.00	25.21
3610	33.29	PK	H	29.04	4.61	27.28	39.66	74.00	34.34
3610	20.47	AV	H	29.04	4.61	27.28	26.84	54.00	27.16
344.23	44.13	QP	H	14.95	2.22	21.63	39.67	46.00	6.33
High Channel: 2462 MHz									
2462	62.67	PK	H	25.80	3.75	0.00	92.22	N/A	N/A
2462	51.94	AV	H	25.80	3.75	0.00	81.49	N/A	N/A
2462	59.07	PK	V	25.80	3.75	0.00	88.62	N/A	N/A
2462	47.99	AV	V	25.80	3.75	0.00	77.54	N/A	N/A
2483.5	28.37	PK	H	25.86	3.67	0.00	57.90	74.00	16.10
2483.5	14.84	AV	H	25.86	3.67	0.00	44.37	54.00	9.63
4924	34.88	PK	H	30.90	5.34	27.43	43.69	74.00	30.31
4924	21.62	AV	H	30.90	5.34	27.43	30.43	54.00	23.57
7386	32.48	PK	H	34.53	6.83	25.86	47.98	74.00	26.02
7386	19.71	AV	H	34.53	6.83	25.86	35.21	54.00	18.79
9848	30.79	PK	H	36.54	8.66	26.94	49.05	74.00	24.95
9848	17.97	AV	H	36.54	8.66	26.94	36.23	54.00	17.77
2950	35.72	PK	H	27.07	6.61	27.54	41.86	74.00	32.14
2950	22.67	AV	H	27.07	6.61	27.54	28.81	54.00	25.19
344.23	42.9	QP	H	14.95	2.22	21.63	38.44	46.00	7.56

802.11 n ht20 Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2412 MHz									
2412	60.89	PK	H	25.67	3.68	0.00	90.24	N/A	N/A
2412	50.56	AV	H	25.67	3.68	0.00	79.91	N/A	N/A
2412	57.36	PK	V	25.67	3.68	0.00	86.71	N/A	N/A
2412	46.24	AV	V	25.67	3.68	0.00	75.59	N/A	N/A
2390	26.37	PK	H	25.61	3.63	0.00	55.61	74.00	18.39
2390	14.02	AV	H	25.61	3.63	0.00	43.26	54.00	10.74
4824	34.14	PK	H	30.64	5.03	27.41	42.40	74.00	31.60
4824	21.11	AV	H	30.64	5.03	27.41	29.37	54.00	24.63
7236	32.15	PK	H	34.17	6.65	25.90	47.07	74.00	26.93
7236	19.38	AV	H	34.17	6.65	25.90	34.30	54.00	19.70
9648	30.51	PK	H	36.06	8.55	27.46	47.66	74.00	26.34
9648	17.59	AV	H	36.06	8.55	27.46	34.74	54.00	19.26
2950	35.07	PK	H	27.07	6.61	27.54	41.21	74.00	32.79
2950	21.84	AV	H	27.07	6.61	27.54	27.98	54.00	26.02
344.2	43.6	QP	H	14.95	2.22	21.63	39.14	46.00	6.86
Middle Channel: 2437 MHz									
2437	61.37	PK	H	25.74	3.75	0.00	90.86	N/A	N/A
2437	51	AV	H	25.74	3.75	0.00	80.49	N/A	N/A
2437	57.9	PK	V	25.74	3.75	0.00	87.39	N/A	N/A
2437	46.68	AV	V	25.74	3.75	0.00	76.17	N/A	N/A
4874	34.17	PK	H	30.77	5.14	27.42	42.66	74.00	31.34
4874	21.22	AV	H	30.77	5.14	27.42	29.71	54.00	24.29
7311	32.02	PK	H	34.35	6.74	25.88	47.23	74.00	26.77
7311	19.34	AV	H	34.35	6.74	25.88	34.55	54.00	19.45
9748	30.55	PK	H	36.30	8.61	27.24	48.22	74.00	25.78
9748	17.61	AV	H	36.30	8.61	27.24	35.28	54.00	18.72
2950	35.14	PK	H	27.07	6.61	27.54	41.28	74.00	32.72
2950	22.36	AV	H	27.07	6.61	27.54	28.50	54.00	25.50
3610	32.91	PK	H	29.04	4.61	27.28	39.28	74.00	34.72
3610	20.04	AV	H	29.04	4.61	27.28	26.41	54.00	27.59
344.2	42.7	QP	H	14.95	2.22	21.63	38.24	46.00	7.76
High Channel: 2462 MHz									
2462	61.7	PK	H	25.80	3.75	0.00	91.25	N/A	N/A
2462	51.38	AV	H	25.80	3.75	0.00	80.93	N/A	N/A
2462	58.31	PK	V	25.80	3.75	0.00	87.86	N/A	N/A
2462	47.01	AV	V	25.80	3.75	0.00	76.56	N/A	N/A
2483.5	34.23	PK	H	25.86	3.67	0.00	63.76	74.00	10.24
2483.5	15.16	AV	H	25.86	3.67	0.00	44.69	54.00	9.31
4924	34.57	PK	H	30.90	5.34	27.43	43.38	74.00	30.62
4924	21.3	AV	H	30.90	5.34	27.43	30.11	54.00	23.89
7386	32.04	PK	H	34.53	6.83	25.86	47.54	74.00	26.46
7386	19.43	AV	H	34.53	6.83	25.86	34.93	54.00	19.07
9848	30.49	PK	H	36.54	8.66	26.94	48.75	74.00	25.25
9848	17.62	AV	H	36.54	8.66	26.94	35.88	54.00	18.12
2950	35.5	PK	H	27.07	6.61	27.54	41.64	74.00	32.36
2950	22.37	AV	H	27.07	6.61	27.54	28.51	54.00	25.49
344.2	43	QP	H	14.95	2.22	21.63	38.54	46.00	7.46

802.11 n ht40 Mode


Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2422 MHz									
2422	59.34	PK	H	25.70	3.71	0.00	88.75	N/A	N/A
2422	48.23	AV	H	25.70	3.71	0.00	77.64	N/A	N/A
2422	56.17	PK	V	25.70	3.71	0.00	85.58	N/A	N/A
2422	45.29	AV	V	25.70	3.71	0.00	74.70	N/A	N/A
2390	26.14	PK	H	25.61	3.63	0.00	55.38	74.00	18.62
2390	14.37	AV	H	25.61	3.63	0.00	43.61	54.00	10.39
4844	33.75	PK	H	30.69	4.99	27.42	42.01	74.00	31.99
4844	20.76	AV	H	30.69	4.99	27.42	40.20	54.00	13.80
7266	31.94	PK	H	34.24	6.68	25.89	34.14	74.00	39.86
7266	19.11	AV	H	34.24	6.68	25.89	34.14	54.00	19.86
9688	30.06	PK	H	36.15	8.58	27.37	47.42	74.00	26.58
9688	17.35	AV	H	36.15	8.58	27.37	34.71	54.00	19.29
2950	34.83	PK	H	27.07	6.61	27.54	40.97	74.00	33.03
2950	21.49	AV	H	27.07	6.61	27.54	27.63	54.00	26.37
344.28	42.4	QP	H	14.95	2.22	21.63	37.94	46.00	8.06
Middle Channel: 2437 MHz									
2437	59.67	PK	H	25.74	3.75	0.00	89.16	N/A	N/A
2437	48.68	AV	H	25.74	3.75	0.00	78.17	N/A	N/A
2437	56.72	PK	V	25.74	3.75	0.00	86.21	N/A	N/A
2437	45.84	AV	V	25.74	3.75	0.00	75.33	N/A	N/A
4874	33.87	PK	H	30.77	5.14	27.42	42.36	74.00	31.64
4874	20.86	AV	H	30.77	5.14	27.42	29.35	54.00	24.65
7311	31.61	PK	H	34.35	6.74	25.88	46.82	74.00	27.18
7311	18.85	AV	H	34.35	6.74	25.88	34.06	54.00	19.94
9748	30.31	PK	H	36.30	8.61	27.24	47.98	74.00	26.02
9748	17.2	AV	H	36.30	8.61	27.24	34.87	54.00	19.13
2950	34.82	PK	H	27.07	6.61	27.54	40.96	74.00	33.04
2950	22.1	AV	H	27.07	6.61	27.54	28.24	54.00	25.76
3610	32.67	PK	H	29.04	4.61	27.28	39.04	74.00	34.96
3610	19.62	AV	H	29.04	4.61	27.28	25.99	54.00	28.01
344.28	42.2	QP	H	14.95	2.22	21.63	37.74	46.00	8.26
High Channel: 2452 MHz									
2452	60.19	PK	H	25.78	3.78	0.00	89.75	N/A	N/A
2452	48.99	AV	H	25.78	3.78	0.00	78.55	N/A	N/A
2452	57.25	PK	V	25.78	3.78	0.00	86.81	N/A	N/A
2452	46.18	AV	V	25.78	3.78	0.00	75.74	N/A	N/A
2483.5	26.31	PK	H	25.86	3.67	0.00	55.84	74.00	18.16
2483.5	14.28	AV	H	25.86	3.67	0.00	43.81	54.00	10.19
4904	34.36	PK	H	30.85	5.31	27.43	43.09	74.00	30.91
4904	20.99	AV	H	30.85	5.31	27.43	29.72	54.00	24.28
7356	31.64	PK	H	34.45	6.79	25.87	47.01	74.00	26.99
7356	19.01	AV	H	34.45	6.79	25.87	34.38	54.00	19.62
9808	30.14	PK	H	36.44	8.64	27.09	48.13	74.00	25.87
9808	17.13	AV	H	36.44	8.64	27.09	35.12	54.00	18.88
2950	35.22	PK	H	27.07	6.61	27.54	41.36	74.00	32.64
2950	22.16	AV	H	27.07	6.61	27.54	28.30	54.00	25.70
344.28	42.6	QP	H	14.95	2.22	21.63	38.14	46.00	7.86

BLE Mode


Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2402 MHz									
2402	54.6	PK	H	25.65	3.66	0.00	83.91	N/A	N/A
2402	47.31	AV	H	25.65	3.66	0.00	76.62	N/A	N/A
2402	53.24	PK	V	25.65	3.66	0.00	82.55	N/A	N/A
2402	46.31	AV	V	25.65	3.66	0.00	75.62	N/A	N/A
2390	26.35	PK	H	25.61	3.63	0.00	55.59	74.00	18.41
2390	14.12	AV	H	25.61	3.63	0.00	43.36	54.00	10.64
4804	32.96	PK	H	30.59	5.06	27.41	41.20	74.00	32.80
4804	21.04	AV	H	30.59	5.06	27.41	29.28	54.00	24.72
7206	32.9	PK	H	34.09	6.61	25.91	47.69	74.00	26.31
7206	18.51	AV	H	34.09	6.61	25.91	33.30	54.00	20.70
9608	29.92	PK	H	35.96	8.53	27.55	46.86	74.00	27.14
9608	16.63	AV	H	35.96	8.53	27.55	33.57	54.00	20.43
3075	33.64	PK	H	27.44	6.74	27.47	40.35	74.00	33.65
3075	20.66	AV	H	27.44	6.74	27.47	27.37	54.00	26.63
344.24	43.2	QP	H	14.95	2.22	21.63	38.74	46.00	7.26
Middle Channel: 2440 MHz									
2440	55.18	PK	H	25.74	3.76	0.00	84.68	N/A	N/A
2440	47.9	AV	H	25.74	3.76	0.00	77.40	N/A	N/A
2440	53.85	PK	V	25.74	3.76	0.00	83.35	N/A	N/A
2440	46.77	AV	V	25.74	3.76	0.00	76.27	N/A	N/A
4880	33.27	PK	H	30.79	5.18	27.42	41.82	74.00	32.18
4880	21.24	AV	H	30.79	5.18	27.42	29.79	54.00	24.21
7320	33.02	PK	H	34.37	6.75	25.88	48.26	74.00	25.74
7320	18.77	AV	H	34.37	6.75	25.88	34.01	54.00	19.99
9760	30.08	PK	H	36.32	8.62	27.21	47.81	74.00	26.19
9760	16.9	AV	H	36.32	8.62	27.21	34.63	54.00	19.37
3671	33.88	PK	H	29.18	4.58	27.31	40.33	74.00	33.67
3671	20.91	AV	H	29.18	4.58	27.31	27.36	54.00	26.64
1644	34.41	PK	H	23.89	2.87	27.75	33.42	74.00	40.58
1644	21.21	AV	H	23.89	2.87	27.75	20.22	54.00	33.78
344.24	43.5	QP	H	14.95	2.22	21.63	39.04	46.00	6.96
High Channel: 2480 MHz									
2480	55.68	PK	H	25.85	3.68	0.00	85.21	N/A	N/A
2480	48.36	AV	H	25.85	3.68	0.00	77.89	N/A	N/A
2480	54.36	PK	V	25.85	3.68	0.00	83.89	N/A	N/A
2480	47.32	AV	V	25.85	3.68	0.00	76.85	N/A	N/A
2483.5	25.6	PK	H	25.86	3.67	0.00	55.13	74.00	18.87
2483.5	13.87	AV	H	25.86	3.67	0.00	43.40	54.00	10.60
4960	33.38	PK	H	31.00	5.34	27.43	42.29	74.00	31.71
4960	21.37	AV	H	31.00	5.34	27.43	30.28	54.00	23.72
7440	33.06	PK	H	34.66	6.89	25.97	48.64	74.00	25.36
7440	18.97	AV	H	34.66	6.89	25.97	34.55	54.00	19.45
9920	30.28	PK	H	36.71	8.71	26.66	49.04	74.00	24.96
9920	17.18	AV	H	36.71	8.71	26.66	35.94	54.00	18.06
4365	34.15	PK	H	29.83	5.00	26.92	42.06	74.00	31.94
4365	21.14	AV	H	29.83	5.00	26.92	29.05	54.00	24.95
344.24	43.3	QP	H	14.95	2.22	21.63	38.84	46.00	7.16

Conducted Spurious Emissions at Antenna Port


802.11b Low Channel




802.11b Middle Channel




802.11b High Channel




802.11g Low Channel



802.11g Middle Channel




802.11g High Channel




802.11n ht20 Low Channel

Fundamental




802.11n ht20 Middle Channel

Fundamental




802.11n ht20 High Channel

Fundamental




802.11n ht40 Low Channel


Fundamental




802.11n ht40 Middle Channel




802.11n ht40 High Channel




BLE Low Channel



BLE Middle Channel



BLE High Channel



FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH

Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

According to KDB 558074 D01 DTS Meas Guidance v03r02 clause8.1 Option 1:

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW) $\geq 3 \times \text{RBW}$.
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2014-05-09	2015-05-09
	Spectrum Analyzer	FSEM	DE31388	2015-05-09	2016-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	25.3~25.8 °C
Relative Humidity:	51~53 %
ATM Pressure:	100~100.8 kPa


The testing was performed by Lion Xiao from 2015-05-08 to 2015-05-12.

Test Mode: Transmitting


Test Result: Compliant. Please refer to the following table and plots.

Test mode	Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)
802.11b	Low	2412	10.02	≥ 0.5
	Middle	2437	10.10	≥ 0.5
	High	2462	10.02	≥ 0.5
802.11g	Low	2412	16.59	≥ 0.5
	Middle	2437	16.59	≥ 0.5
	High	2462	16.59	≥ 0.5
802.11n20	Low	2412	17.88	≥ 0.5
	Middle	2437	17.88	≥ 0.5
	High	2462	17.88	≥ 0.5
802.11n40	Low	2422	36.71	≥ 0.5
	Middle	2437	36.71	≥ 0.5
	High	2452	36.71	≥ 0.5
BLE	Low	2402	0.754	≥ 0.5
	Middle	2440	0.741	≥ 0.5
	High	2480	0.745	≥ 0.5


802.11b Low Channel





802.11b Middle Channel




802.11b High Channel




802.11g Low Channel**802.11g Middle Channel**


802.11g High Channel




802.11n ht20 Low Channel




802.11n ht20 Middle Channel




802.11n ht20 High Channel




802.11n ht40 Low Channel




802.11n ht40 Middle Channel




802.11n ht40 High Channel




BLE Low Channel



BLE Middle Channel



BLE High Channel



FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

According to KDB 558074 D01 DTS Meas Guidance v03r02

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
3. Add a correction factor to the display.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	Wideband Power Sensor	N1921A	MY54210016	2014-11-03	2015-11-03
Agilent	Wideband Power Sensor	N1921A	MY54170013	2014-11-03	2015-11-03
Agilent	P-Series Power Meter	N1912A	MY5000448	2014-11-03	2015-11-03

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	25.3 °C
Relative Humidity:	52 %
ATM Pressure:	100.6 kPa

The testing was performed by Lion Xiao on 2015-05-12.

Test Mode: Transmitting (Wi-Fi)

Test Result: Compliant. Please refer to the following table.

Test mode	Channel	Frequency	Max Peak Conducted Output Power	Limit	Result
		(MHz)	(dBm)	(dBm)	
802.11b	Low	2412	10.23	30	PASS
	Middle	2437	10.40	30	PASS
	High	2462	10.28	30	PASS
802.11g	Low	2412	15.13	30	PASS
	Middle	2437	15.13	30	PASS
	High	2462	15.13	30	PASS
802.11n20	Low	2412	15.27	30	PASS
	Middle	2437	15.10	30	PASS
	High	2462	15.44	30	PASS
802.11n40	Low	2422	14.56	30	PASS
	Middle	2437	14.82	30	PASS
	High	2452	14.70	30	PASS

Test mode	Channel	Frequency	Max Conducted Average Output Power	Limit	Result
		(MHz)	(dBm)	(dBm)	
802.11b	Low	2412	9.22	30	PASS
	Middle	2437	9.35	30	PASS
	High	2462	9.27	30	PASS
802.11g	Low	2412	9.11	30	PASS
	Middle	2437	8.95	30	PASS
	High	2462	9.01	30	PASS
802.11n20	Low	2412	8.91	30	PASS
	Middle	2437	8.74	30	PASS
	High	2462	9.05	30	PASS
802.11n40	Low	2422	7.39	30	PASS
	Middle	2437	7.68	30	PASS
	High	2452	7.55	30	PASS

Test Mode: Transmitting (BLE)

Test mode	Channel	Frequency	Max Peak Conducted Output Power	Limit	Result
		(MHz)	(dBm)	(dBm)	
BLE	Low	2402	-4.19	30	PASS
	Middle	2440	-3.75	30	PASS
	High	2480	-3.13	30	PASS

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2014-05-09	2015-05-09
	Spectrum Analyzer	FSEM	DE31388	2015-05-09	2016-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions


Temperature:	25.6~25.8°C
Relative Humidity:	51~53 %
ATM Pressure:	100~100.2 kPa

* The testing was performed by Lion Xiao from 2015-05-08 to 2015-05-15.


Test mode: Transmitting



Test Result: Compliant. Please refer to following plots.

802.11b: Band Edge, Left Side



802.11b: Band Edge, Right Side



802.11g: Band Edge, Left Side**802.11g: Band Edge, Right Side**


Marker 3 [T1]

Date: 08.MAY 2015 14:33:48


Marker 3 [T1]



Date: 08.MAY 2015 14:42:15

802.11n ht40 Band Edge, Left Side



802.11n ht40 Band Edge, Right Side



BLE Band Edge , Left Side**BLE Band Edge, Right Side**

FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

According to KDB 558074 D01 DTS Meas Guidance v03r02 clause10.2:

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set the VBW $\geq 3 \times \text{RBW}$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.
- If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2014-05-09	2015-05-09
	Spectrum Analyzer	FSEM	DE31388	2015-05-09	2016-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	25.3 °C
Relative Humidity:	56 %
ATM Pressure:	100.4kPa


* The testing was performed by Lion Xiao on 2015-05-08 & 2015-05-11.

Test Mode: Transmitting


Test Result: Compliant. Please refer to the following table and plots

Test mode	Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
802.11b	Low	2412	-22.31	≤ 8
	Middle	2437	-22.25	≤ 8
	High	2462	-23.09	≤ 8
802.11g	Low	2412	-21.34	≤ 8
	Middle	2437	-21.74	≤ 8
	High	2462	-21.78	≤ 8
802.11n20	Low	2412	-21.08	≤ 8
	Middle	2437	-20.69	≤ 8
	High	2462	-21.03	≤ 8
802.11n40	Low	2422	-23.05	≤ 8
	Middle	2437	-23.14	≤ 8
	High	2452	-22.82	≤ 8
BLE	Low	2402	-17.75	≤ 8
	Middle	2440	-17.37	≤ 8
	High	2480	-17.17	≤ 8


Power Spectral Density, 802.11b Low Channel




Power Spectral Density, 802.11b Middle Channel




Power Spectral Density, 802.11b High Channel




Power Spectral Density, 802.11g Low Channel




Power Spectral Density, 802.11g Middle Channel




Power Spectral Density, 802.11g High Channel




Power Spectral Density, 802.11n ht20 Low Channel




Power Spectral Density, 802.11n ht20 Middle Channel




Power Spectral Density, 802.11n ht20 High Channel





Power Spectral Density, 802.11n ht40 Low Channel




Power Spectral Density, 802.11n ht40 Middle Channel




Power Spectral Density, 802.11n ht40 High Channel**Power Spectral Density, BLE Low Channel**

Power Spectral Density, BLE Middle Channel



Power Spectral Density, BLE High Channel



*****END OF REPORT*****